
HIGH-PERFORMANCE BLOWER · SINGLE STAGE

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.

Vacuum or pressure · Continuous duty




145 m³/h	7.0 psi	−5.2 psi	1.75–2.55 kW	68 dB(A)	26–29 kg
85 CFM	0.48 bar	−0.36 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz


CONFIGURATION	USE	MOTOR	AMBIENT / INLET
Single stage	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C

PERFORMANCE CURVES

FLOW VS PRESSURE



POWER VS PRESSURE



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.


MODELS · 60 Hz


TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0120-1MT151-6	1.75	220-275 Δ / 380-480 Y	Δ 7.6 / Y 4.4	145 m³/h 85 CFM	−4.9 psi −0.34 bar	4.6 psi 0.32 bar	68	26
STRP0120-1MT221-6	2.55	220-275 Δ / 380-480 Y	Δ 11.2 / Y 6.5	145 m³/h 85 CFM	−5.2 psi −0.36 bar	7.0 psi 0.48 bar	68	29


50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.

DIMENSIONS

All dimensions in mm







Type	A	B	B1	C	D	E	F	G	H	J	K	M	N	O	P
STRP0120-1MT151-6	368	395	39	114	328	363	361	185	205	128	152	265	68	148	G1 ¼"
STRP0120-1MT221-6	368	395	39	114	328	363	361	185	205	128	152	265	68	148	G1 ¼"

Type	Q	R	S1	S2	S3	T	T1	U	V	V1	W	X	YxZ
STRP0120-1MT151-6	64	14	4	140	31	137	138	M6 X 17	–	M16 X 1.5	32	192	M8 X 15
STRP0120-1MT221-6	64	14	4	140	31	137	138	M6 X 17	–	M16 X 1.5	32	192	M8 X 15

Let's size your blower.
Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com