HIGH-PERFORMANCE BLOWER · 3 STAGES IN SERIES

High-performance regenerative blower.

Higher pressure and vacuum in a compact package. Oil-free, direct-driven by a 50/60 Hz motor.



Vacuum or pressure · Continuous duty


147 m³/h	14.9 psi	−9.3 psi	4.6–6.3 kW	73 dB(A)	62–68 kg
87 CFM	1.03 bar	−0.64 bar			
MAX. FLOW	MAX. PRESSURE	MAX. VACUUM	MOTOR POWER	NOISE	WEIGHT

Values at 60 Hz


CONFIGURATION	USE	MOTOR	AMBIENT / INLET
3 stages, series	Vacuum pump or compressor	50/60 Hz, class F, IP55	−25 to 40 °C

PERFORMANCE CURVES

FLOW VS PRESSURE



POWER VS PRESSURE



Curves are based on air at 15 °C, measured at the inlet port, 1013 mbar atmospheric pressure, tolerance ± 10 %. Pressure axes in mbar: 100 mbar = 1.45 psi = 0.1 bar. For other gases or conditions, please get in touch with us.


MODELS · 60 Hz

TYPE	KW	VOLTAGE (V)	CURRENT (A)	FLOW	MAX. VACUUM	MAX. PRESSURE	DB(A)	KG
STRP0120-3ST401-7	4.6	380-480 Δ / 660-720 Y	Δ 9.5 / Y 4.5	147 m³/h 87 CFM	−9.3 psi −0.64 bar	10.6 psi 0.73 bar	73	62
STRP0120-3ST551-7	6.3	380-480 Δ / 660-720 Y	Δ 13.3 / Y 7.7	147 m³/h 87 CFM	−9.3 psi −0.64 bar	14.9 psi 1.03 bar	73	68

50 Hz data and other voltages on request. Relief valves are available to limit the differential pressure. Noise measured to EN ISO 3744 at 1 m with hoses connected.

DIMENSIONS

All dimensions in mm



Type	A	B	B′	C2	D	E	F	G	H	H1	J	K	M	N	O	P
STRP0120-3ST401-7	387	402	432	57	328	363	682	252	206	344	148	152	532	333	149	G1 ¼″
STRP0120-3ST551-7	442	402	432	63	371	406	717	274	236	389	148	152	539	336	172	G1 ¼″

Type	Q	ØR	S1	S2	T	U	V	W1	W2
STRP0120-3ST401-7	64	14	5	143	137	M6 × 17	M32 × 1.5	42	120
STRP0120-3ST551-7	64	14	5	146	153	M6 × 17	M32 × 1.5	42	120

Let's size your blower.
Send us your pressure, flow and gas type.

EMAIL abruens@id-industries.com
PHONE +1 438-880-4655
WEB id-industries.com