

In-House Development Reference Architecture 1.0

VP	DIRECTOR	DIRECTOR	DIRECTOR	MGR	MGR

DEALER / SUPPLIER

User Device (PC, Tablet, Phone)
BROWSER
INTERNET EXPLORER 8 & 9 (HTML4 & 5, CSS 2 & 3 & JAVASCRIPT)
FIREFOX 4, CHROME, SAFARI (HTML5, CSS 3 & JAVASCRIPT)

EXTERNAL SYSTEMS
LOGISTICS
DEALERS
SUPPLIERS
PARTS

SECURITY (TBC)

SECURITY PLATFORM

Edge Firewall

Reverse Proxy

TME DMZ Firewall

AGCO User Desktop

BROWSER
INTERNET EXPLORER 8 & 9 (HTML4 & 5, CSS 2 & 3 & JAVASCRIPT)

OPERATING SYSTEM
WINDOWS 7

Server

WEB TIER
APACHE
CLIENT SIDE PRESENTATION
JAVASCRIPT JAVASCRIPT FRAMEWORKS (JQUERY, BACKBONE) HTML 4/5 + CSS 2/3

APPLICATION SERVER
JETTY
SERVICE TIER
LOG4J Spring POJO Based Services CXF
HTTP CLIENT Spring Security Service CAMEL
JMS CLIENT
DATA TIER
JPA JDBC DRIVER

Operating System
LINUX

Virtualisation Platform
VMWARE ESX

MIDDLEWARE SERVER

EXTERNAL
HTTP Endpoint
JMS Endpoint

CXF
CAMEL
ACTIVE MQ
JETTY (optional)

INTERNAL
HTTP Endpoint
JMS Endpoint

HTTP Clients

JMS Clients

RDBMS Servers

Enterprise RDBMS
MSSQL
DATA
APP DATABASE(S)

Operating System
WINDOWS SERVER

Virtualisation Platform
VMWARE ESX

LOAD BALANCER

HTTP (JSON Payload)

JDBC

DOCUMENT LOCATOR

PROJECT DOCS	TBC
DIAGRAMS	TBC

ENVIRONMENT CONFIGURATION

DEV UAT 1 PROD 1
 DEV UAT 2 PROD 2

UAT and PROD Load Balanced if applicable
UAT & PROD must be same size, spec and configuration
MAX Downtime = 4 Hours unless project has further requiremnt

LEGEND

JDBC TRAFFIC
JMS TRAFFIC
HTTP TRAFFIC
REST WIS TRAFFIC

APPLICATION CODE
STANDARD
ACCEPTABLE COUNTERMEASURE
RETIRING STANDARD
INFORMATIONAL ITEM
GAP – STANDARD REQUIRED