

Describing lengths of walks in directed graphs

Anthony Widjaja Lin

Oxford University Department of Computer Science

Introduction

Intro.

CM thm.
Outline
Notations
Little lemma
Comp. complex.
Example
Application
Notes
Thanks

Problem: Given a (directed) graph $G = (V, E)$ and two nodes $s, t \in V$, describe the set $L(G, s, t)$ of lengths of walks from s to t in a “nice” way.

- ✓ Self-loops are allowed in our graphs.
- ✓ “Nice” means can be easily manipulated algorithmically
 - ✗ So, infinite sums are less “nice”
- ✓ “Nice” means easy to understand.

Introduction

Intro.

CM thm.
Outline
Notations
Little lemma
Comp. complex.
Example
Application
Notes
Thanks

Problem: Given a (directed) graph $G = (V, E)$ and two nodes $s, t \in V$, describe the set $L(G, s, t)$ of lengths of walks from s to t in a “nice” way.

- ✓ Describe $L(G, s, t)$ as a union of a small number of **arithmetic progressions (AP)** with small offsets and periods.
 - ✗ AP is any set $a + b\mathbb{N} := \{a + bk : k \in \mathbb{N}\}$, for some offset $a \in \mathbb{N}$ and period $b \in \mathbb{N}$.
- ✓ The result has interesting applications in computer science. (trust me)

Chrobak-Martinez Theorem

Intro.

CM thm.

Outline

Notations

Little lemma

Comp. complex.

Example

Application

Notes

Thanks

Theorem (Chrobak-Martinez): Given a graph $G = (V, E)$ with nodes $s, t \in V$, the set $\bar{L}(G, s, t)$ can be described as a union of $O(|V|^2)$ many arithmetic progressions with offsets at most $O(|V|^2)$ and periods at most $O(|V|)$. Moreover, this union can be computed in polynomial time.

- ✓ Describable as a union of exponentially many APs is well-known in automata theory (using “determinization”: compute large “equivalent” lasso-shaped graph).
- ✓ CM Theorem gives exponentially better upper bounds.
- ✓ Matching (asymptotic) lower bounds are known.

Chrobak-Martinez Theorem

Intro.

CM thm.

Outline

Notations

Little lemma

Comp. complex.

Example

Application

Notes

Thanks

Theorem (Chrobak-Martinez): Given a graph $G = (V, E)$ with nodes $s, t \in V$, the set $\bar{L}(G, s, t)$ can be described as a union of $O(|V|^2)$ many arithmetic progressions with offsets at most $O(|V|^2)$ and periods at most $O(|V|)$. Moreover, this union can be computed in polynomial time.

- ✓ A subtle bug in the original proof was recently found and fixed.
- ✓ This talk describes a corrected proof. (A restriction of the proof of a more general case in my LICS'10 paper)

Outline of proof

- Intro.
- CM thm.
- Outline**
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

- ✓ Little lemma from number theory about solutions of Diophantine equations.
- ✓ Graph analysis to derive **existence** of APs descriptions.
- ✓ Further analysis to derive **polynomial-time algorithms**.

A few words on notations and terminologies

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

- ✓ Given two sets $S_1, S_2 \subseteq \mathbb{N}$, define standard arithmetic operations on such sets, e.g.,:

$$\times S_1 + S_2 := \{s_1 + s_2 : s_1, s_2 \in \mathbb{N}\}.$$

$$\times S_1 \cdot S_2 := \{s_1 \cdot s_2 : s_1, s_2 \in \mathbb{N}\}.$$

- ✓ If S_1 is a singleton $\{s_1\}$, write $s_1 + S_2$ (resp. $s_1 \cdot S_2$) for $\{s_1\} + S_2$ (resp. $\{s_1\} \cdot S_2$).
- ✓ This notation is consistent with earlier definition of an arithmetic progression $a + b\mathbb{N}$.
- ✓ A closed walk in G is **short** if it is of length $\leq |V|$.

A little lemma from number theory

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma**
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Lemma (Erdos-Graham): For all $v_1, \dots, v_m \in \mathbb{N}$, each set

$$v_1\mathbb{N} + \dots + v_m\mathbb{N}$$

with $n := \max(v_1, \dots, v_m)$ equals $S \cup a + b\mathbb{N}$, where

- ✓ each $c \in S$ is $\leq n^2$,
- ✓ a is the least integer bigger than n^2 that is a multiple of $b := \gcd(v_1, \dots, v_m)$

If $\gcd(v_1, \dots, v_m) = 1$, then eventually all numbers are in $v_1\mathbb{N} + \dots + v_m\mathbb{N}$.

A little lemma from number theory

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma**
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Lemma (Erdos-Graham): For all $v_1, \dots, v_m \in \mathbb{N}$, each set

$$v_1\mathbb{N} + \dots + v_m\mathbb{N}$$

with $n := \max(v_1, \dots, v_m)$ equals $S \cup a + b\mathbb{N}$, where

- ✓ each $c \in S$ is $\leq n^2$,
- ✓ a is the least integer bigger than n^2 that is a multiple of $b := \gcd(v_1, \dots, v_m)$

Can be computed in polynomial time (numbers given in unary).

A little lemma: example

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Suppose that McDonalds sells their Chicken McNuggets in 3s and in 7s. What is the largest number of Chicken McNuggets that **cannot** be purchased?



A little lemma: example

Intro.
CM thm.
Outline
Notations
Little lemma
Comp. complex.
Example
Application
Notes
Thanks

$3\mathbb{N} + 7\mathbb{N}$ equals

$$0 + 3\mathbb{N} \cup 7 + 3\mathbb{N} \cup 14 + 3\mathbb{N}$$

How so?

A little lemma: example

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

$3\mathbb{N} + 7\mathbb{N}$ equals


$$0 + 3\mathbb{N} \cup 7 + 3\mathbb{N} \cup 14 + 3\mathbb{N}$$

How so?

Therefore, $3\mathbb{N} + 7\mathbb{N} = \{0, 3, 6, 7, 9, 10\} \cup 12 + 1\mathbb{N}$. So, the answer is smallest 2 (mod 3) representative less than 14, which is 11.

Describing $L(G, s, t)$ as a union of APs

Take a walk π and all short closed walks C_1, \dots, C_m visiting π .



The walk type T_π of π is the linear set $|\pi| + \sum_{i=1}^m |C_i|\mathbb{N}$.

Removing redundant terms, T_π has “small” size

Describing $L(G, s, t)$ as a union of APs

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma**
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Lemma: $L(G, s, t) = \bigcup_{\pi} T_{\pi}$, where π ranges over walks from s to t of length at most $(|V| - 1)^2$.

Applying Erdos-Graham on each T_{π} , we get 1 part of CM:

Corollary: $L(G, s, t)$ coincides with the union $I \cup K$ s.t.

- ✓ I contains no numbers exceeding $|V|^2 + (|V| - 1)^2$,
- ✓ K is a union of arithmetic progressions of the form $a + b\mathbb{N}$ with $|V|^2 + (|V| - 1)^2 < a \leq |V|^2 + (|V| - 1)^2 + |V|$ and $0 < b \leq |V|$.

Describing $L(G, s, t)$ as a union of APs

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

To prove this characterization lemma, we need the following simple fact.

Fact: Given a walk π in G from p to q , there exists a (simple) path π' from p to q and finitely many cycles C_1, \dots, C_h (possibly with duplicates) such that

$$|\pi| = |\pi'| + \sum_{i=1}^h |C_i|$$

Note: the proof is similar to the existence of simple paths between two connected vertices.

Describing $L(G, s, t)$ as a union of APs

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma**
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Let us prove $L(G, s, t) \subseteq \bigcup_{\pi} T_{\pi}$.

Take $a \in L(G, s, t)$ and a witnessing walk π from s to t .

Describing $L(G, s, t)$ as a union of APs

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Let us prove $L(G, s, t) \subseteq \bigcup_{\pi} T_{\pi}$.

Take $a \in L(G, s, t)$ and a witnessing walk π from s to t .

Q: Why not just use Fact obtaining the **simple path** $\pi' +$ cycles, and show that $a \in T_{\pi'}$?

Describing $L(G, s, t)$ as a union of APs

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Let us prove $L(G, s, t) \subseteq \bigcup_{\pi} T_{\pi}$.

Take $a \in L(G, s, t)$ and a witnessing walk π from s to t .

Q: Why not just use Fact obtaining the **simple path** $\pi' +$ cycles, and show that $a \in T_{\pi'}$?

A: **Cannot**

Describing $L(G, s, t)$ as a union of APs


Intro.
CM thm.
Outline
Notations
Little lemma
Comp. complex.
Example
Application
Notes
Thanks

Let us prove $L(G, s, t) \subseteq \bigcup_{\pi} T_{\pi}$.

Take $a \in L(G, s, t)$ and a witnessing walk π from s to t .

Q: Why not just use Fact obtaining the **simple path** π' + cycles, and show that $a \in T_{\pi'}$?

A: **Cannot**



Describing $L(G, s, t)$ as a union of APs

Intro.
CM thm.
Outline
Notations
Little lemma
Comp. complex.
Example
Application
Notes
Thanks


Let us prove $L(G, s, t) \subseteq \bigcup_{\pi} T_{\pi}$.

Take $a \in L(G, s, t)$ and a witnessing walk π from s to t .

Q: Why not just use Fact obtaining the **simple path** π' + cycles, and show that $a \in T_{\pi'}$?

A: **Cannot**

Soln: For each node p in π , pick the **last** position in π at which p is visited + apply Fact on each segment.



The resulting walk is of length at most $(|V| - 1)^2$.

Describing $L(G, s, t)$ as a union of APs

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma**
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Conversely, that $L(G, s, t) \supseteq \bigcup_{\pi} T_{\pi}$ is obvious from definition of T_{π} .

Any $a \in T_{\pi}$ describes the length of a walk from s to t in G .

Computational complexity

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

Summary so far:

Corollary: $L(G, s, t)$ coincides with the union $I \cup K$ s.t.

- ✓ I contains no numbers exceeding $|V|^2 + (|V| - 1)^2$,
- ✓ K is a union of APs of the form $a + b\mathbb{N}$ with $|V|^2 + (|V| - 1)^2 < b \leq |V|^2 + (|V| - 1)^2 + |V|$ and $0 < b \leq |V|$.

A naive implementation of the previous construction takes exponential time.

Can do better using dynamic programming!

Computational complexity

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

- ✓ Characteristic Matrices $\mathbb{M} = \{M_i\}_{i=0}^{n-1}$ of **existence** of walks of length $i = 1, \dots, n - 1$ can be computed in cubic time. (by matrix multiplication)
- ✓ So, for each state q , the set Γ_q of **lengths** of closed walks meeting with q up to length n can be read off directly from \mathbb{M} . (diagonal entries)
- ✓ For each $v \in V$, let $T_{i,v} := \bigcup_{\pi} T_{\pi}$, where π ranges over walks in G of length i from s to v .
- ✓ So, $L(G, s, t) = \bigcup_{i=0}^{(|V|-1)^2} T_{i,t}$.

Computational complexity

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

We can compute each $\{T_{i,v}\}_{v \in V}$ recursively on i using:

Lemma: $T_{0,s} = \{0\}$ and $T_{0,v} = \emptyset$ for $v \in V \setminus \{s\}$.

Whenever $i > 0$ and $v \in V$, we have:

$$T_{i,v} = \bigcup_{u \in V} \left(T_{i-1,u} + \sum_{(u,v) \in E, k \in \Gamma_v} (1 + k\mathbb{N}) \right).$$

Each application of this lemma is to be combined with Erdos-Graham (and remove redundant linear sets) to keep the size of $T_{i,v}$ small.

This takes polynomial time.

Algorithm in action on a wee example

See the white/black board.

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example**
- Application
- Notes
- Thanks

An application

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application**
- Notes
- Thanks

Let IP_k be the set of integer programs with variables x_1, \dots, x_k, y . For every fixed k , checking whether $P \in \text{IP}_k$ has an integer solution is solvable in polynomial time (Lenstra 81).

Problem: Given $P \in \text{IP}_k$, a graph $G = (V, E)$, and nodes $s, t \in V$, decide the existence of a walk from s to t in G of length k such that P is solvable with $y := k$.

This problem is solvable in polynomial time by first computing a union of m APs for $L(G, s, t)$, and solve m integer programs in IP_{k+1} (each obtained by “appending” each AP to P).

Other computer science applications

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application**
- Notes
- Thanks

- ✓ Polynomial-time algorithms for checking walks with more complex constraints (motivation from databases)
- ✓ An optimal complexity for model checking EF logic over one-counter machines. (infinite-state model checking)

Bibliographic notes

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks

- ✓ The problem we considered is an instance of a more general problem in automata theory.
- ✓ An **automaton** is an edge-labeled graph $G = (V, \{E_a\}_{a \in \Sigma})$, where $\Sigma := \{a_1, \dots, a_k\}$ is a finite set (called alphabet).
- ✓ Given $s, t \in V$, let $L(G, s, t)$ denote the set of tuples (m_1, \dots, m_k) such that there is a path from s to t in which each $a_i \in \Sigma$ occurs precisely m_i times.
- ✓ Can we describe $L(G, s, t)$ in a “nice” way?

Bibliographic notes

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes**
- Thanks

- ✓ Can we describe $L(G, s, t)$ in a “nice” way? **Yes**
- ✓ Use generalizations of union of arithmetic progressions (called semilinear sets)
- ✓ Chrobak-Martinez Theorem is replaced by Caratheodory Theorem from convex geometry.
- ✓ Use bounds on solutions of integer programs (Papadimitriou’83).
- ✓ Lots of applications in computer science and operation research.
- ✓ See my LICS’10 paper for this.

Thank you

Thank you in every language.

- Intro.
- CM thm.
- Outline
- Notations
- Little lemma
- Comp. complex.
- Example
- Application
- Notes
- Thanks