

Table of Contents

| | |
|---------------------|----|
| Layer | 1 |
| Basics | 1 |
| Geoprocessing | 9 |
| Graticule | 42 |

Layer

Basics

Open

Open a Layer.

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-----------|--------------------|-----------|-------------------|---------------------|
| workspace | The Workspace name | true | | |
| layer | The Layer name | true | | |
| name | The name | false | | |

```
geo-shell> workspace open --name naturalearth --params src/test/resources/naturalearth.gpkg  
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> workspace close --name naturalearth  
Workspace naturalearth closed!
```

Close

Close a Layer.

```
geo-shell> layer close --name countries
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------|----------------|-----------|-------------------|---------------------|
| name | The Layer name | true | | |

```
geo-shell> workspace open --name naturalearth --params src/test/resources/naturalearth.gpkg  
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer close --name countries  
Layer countries closed!
```

```
geo-shell> workspace close --name naturalearth  
Workspace naturalearth closed!
```

List

List open Layers.

```
geo-shell> layer list
```



No parameters

```
geo-shell> workspace open --name naturalearth --params src/test/resources/naturalearth.gpkg  
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean  
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer open --workspace naturalearth --layer states --name states  
Opened Workspace naturalearth Layer states as states
```

```
geo-shell> layer list  
countries = GeoPackage  
ocean = GeoPackage  
states = GeoPackage
```

```
geo-shell> workspace close --name naturalearth  
Workspace naturalearth closed!
```

Schema

Inspect a Layer's Schema.

```
geo-shell> layer schema --name countries
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------|----------------|-----------|-------------------|---------------------|
| name | The Layer name | true | | |

```
geo-shell> workspace open --name naturalearth --params src/test/resources/naturalearth.gpkg  
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer schema --name countries  
Name Type
```

```
-----  
the_geom MultiPolygon  
ScaleRank Integer  
FeatureCla String
```

SOVEREIGNT String
SOVISO String
SOV_A3 String
LEVEL Double
TYPE String
NAME String
SORTNAME String
ADM0_A3 String
NAME_SM String
NAME_LNG String
TERR_ String
PARENTHETI String
NAME_ALT String
LOCAL_LNG String
LOCAL_SM String
FORMER String
ABBREV_ String
MAP_COLOR Double
PEOPLE Double
GDP_USDM Double
FIPS_10 String
ISO_A2 String
ISO_A3 String
ISO_N3 Double
ITU String
IOC String
FIFA String
DS String
WMO String
GAUL Double
MARC String
STANAG1059 String
GW_ID Double
DIAL Double
INTERNET_ String
COG String
ACTUAL String
CAPAY String
CRPAY String
ANI String
LIBENR String
ANCNOM String
PAYS_R_GIO String
COMMENT String

geo-shell> **workspace close** --name naturalearth
Workspace naturalearth closed!

Count

Count the Feature in a Layer.

```
geo-shell> layer count --name countries
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------|----------------|-----------|-------------------|---------------------|
| name | The Layer name | true | | |

```
geo-shell> workspace open --name naturalearth --params src/test/resources/naturalearth.gpkg  
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer count --name countries  
177
```

```
geo-shell> workspace close --name naturalearth  
Workspace naturalearth closed!
```

Projection

Get the Projection of a Layer.

```
geo-shell> layer projection --name countries
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------|----------------|-----------|-------------------|---------------------|
| name | The Layer name | true | | |

```
geo-shell> workspace open --name naturalearth --params src/test/resources/naturalearth.gpkg  
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer projection --name countries  
EPSG:4326
```

```
geo-shell> workspace close --name naturalearth  
Workspace naturalearth closed!
```

Features

Display the Features of a Layer.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------|-------------|-----------|-------------------|---------------------|
| | | | | |

| | | | | |
|--------|-------------------------------|-------|--|----|
| name | The Layer name | true | | |
| filter | The CQL Filter | false | | |
| sort | A Sort parameter (fld dir) | false | | |
| start | The start index | false | | -1 |
| max | The maximum number of records | false | | -1 |
| field | A subfield to include | false | | |

Get Style

Get the Layer's style.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-------|----------------|-----------|-------------------|---------------------|
| name | The Layer name | true | | |
| style | The SLD File | false | | |

Set Style

Set a Layer's style

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-------|---------------------|-----------|-------------------|---------------------|
| name | The Layer name | true | | |
| style | The SLD or CSS File | true | | |

Copy

Copy one Layer to another Workspace.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| filter | The CQL Filter | false | | |
| sort | A Sort parameter (fld dir) | false | | |
| start | The start index | false | | -1 |

| | | | | |
|-------|-------------------------------|-------|--|----|
| max | The maximum number of records | false | | -1 |
| field | A subfield to include | false | | |

Add

Add a new Feature to a Layer.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|--------|---|-----------|-------------------|---------------------|
| name | The Layer name | true | | |
| values | The pipe delimited list of values (field=value) | true | | |

Remove

Remove a Layer from a Workspace.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-----------|--------------------|-----------|-------------------|---------------------|
| workspace | The Workspace name | true | | |
| layer | The Layer name | true | | |

Create

Create a new Layer.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-----------|---|-----------|-------------------|---------------------|
| workspace | The Workspace name | true | | |
| name | The new Layer name | true | | |
| fields | The pipe delimited list of fields (name=type) | true | | |

Delete

Delete features from the Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------|-------------|-----------|-------------------|---------------------|
|------|-------------|-----------|-------------------|---------------------|

| | | | | |
|--------|----------------|------|--|--|
| name | The Layer name | true | | |
| filter | The CQL Filter | true | | |

Update

Calculate the update between a Layer with another Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| other-name | The other Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

Update Field

Delete features from the Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|--------|--------------------------------------|-----------|-------------------|---------------------|
| name | The Layer name | true | | |
| field | The field name | true | | |
| value | The value | true | | |
| filter | The CQL Filter | false | INCLUDE | INCLUDE |
| script | Whether the value is a script or not | false | false | false |

Add Fields

Add Fields to the input Layer and save the result to the output Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|-----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| fields | The Fields (name=type proj) | true | | |

Add Area Field

Add area Field to the input Layer and save the result to the output Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| area-fieldname | The area field name | true | area | area |

Add ID Field

Add area ID to the input Layer and save the result to the output Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| id-fieldname | The id field name | true | id | id |
| start-value | The value to start at | true | 1 | 1 |

Add XY Fields

Add x and y coordinate Fields to the input Layer and save the result to the output Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| x-fieldname | The x field name | true | x | x |
| y-fieldname | The y field name | true | y | y |

Validity

Check for invalid geometries in the Layer.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|--------|---|-----------|-------------------|---------------------|
| name | The Layer name | true | | |
| fields | A comma delimited list of Fields to include | false | | |

Geoprocessing

Clip

Clip the input Layer by the other Layer to produce the output Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| clip-name | The clip Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

Convex Hull

Calculate the convexhull of the input Layer and save it to the output Layer.

```
geo-shell> layer convexhull --input-name countries --output-workspace layers --output-name convexhull
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| geometry-field | The geometry field name | false | the_geom | the_geom |

```
geo-shell> workspace open --name layers --params memory  
Workspace layers opened!
```

geo-shell> **workspace open** --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!

geo-shell> **layer open** --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries

geo-shell> **layer style set** --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries

geo-shell> **layer open** --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean

geo-shell> **layer style set** --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

geo-shell> **layer convexhull** --input-name countries --output-workspace layers --output-name convexhull
Done!

geo-shell> **style vector default** --layer convexhull --color #1E90FF --opacity 0.25 --file examples/convexhull.sld
Default Vector Style for convexhull written to /home/travis/build/jericks/geo-shell/examples/convexhull.sld!

geo-shell> **layer style set** --name convexhull --style examples/convexhull.sld
Style /home/travis/build/jericks/geo-shell/examples/convexhull.sld set on convexhull

geo-shell> **map open** --name map
Map map opened!

geo-shell> **map add layer** --name map --layer ocean
Added ocean layer to map map

geo-shell> **map add layer** --name map --layer countries
Added countries layer to map map

geo-shell> **map add layer** --name map --layer convexhull
Added convexhull layer to map map

geo-shell> **map draw** --name map --file examples/layer_convexhull.png
Done drawing /home/travis/build/jericks/geo-shell/examples/layer_convexhull.png!

geo-shell> **map close** --name map
Map map closed!



Convex Hulls

Calculate the convexhull of each Feature in the input Layer and save them to the output Layer.

```
geo-shell> layer convexhulls --input-name countries --output-workspace layers --output-name convexhulls
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer style set --name ocean --style examples/ocean.sld
```

Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

```
geo-shell> layer convexhulls --input-name countries --output-workspace layers --output-name convexhulls
```

Done!

```
geo-shell> style vector default --layer convexhulls --color #1E90FF --opacity 0.25 --file examples/convexhulls.sld
```

Default Vector Style for convexhulls written to /home/travis/build/jericks/geo-shell/examples/convexhulls.sld!

```
geo-shell> layer style set --name convexhulls --style examples/convexhulls.sld
```

Style /home/travis/build/jericks/geo-shell/examples/convexhulls.sld set on convexhulls

```
geo-shell> map open --name map
```

Map map opened!

```
geo-shell> map add layer --name map --layer ocean
```

Added ocean layer to map map

```
geo-shell> map add layer --name map --layer countries
```

Added countries layer to map map

```
geo-shell> map add layer --name map --layer convexhulls
```


Added convexhulls layer to map map

```
geo-shell> map draw --name map --file examples/layer_convexhulls.png
```

Done drawing /home/travis/build/jericks/geo-shell/examples/layer_convexhulls.png!

```
geo-shell> map close --name map
```

Map map closed!



Coordinates

Extract the coordinates each Feature in the input Layer and save them to the output Layer.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

Delaunay

Calculate a delaunay diagram of the input Layer and save it to the output Layer.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| geometry-field | The geometry field name | false | the_geom | the_geom |

Densify

Densify the features of the input Layer and save them to the output Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| distance | The distance tolerance | true | | |

Dissolve

Dissolve the Features of a Layer by a Field.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|---------------------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| field | The field to use to dissolve features | true | | |
| idField | The name of the id field | false | id | id |
| countField | The name of the count field | false | count | count |

Erase

Erase one Layer from another Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| other-name | The other Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

Grid Row / Column

Create a grid Layer with rows and columns

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|-------------------------------------|-----------|-------------------|---------------------|
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| rows | The number of rows | true | | |
| columns | The number of columns | true | | |
| geometry | The constraining geometry | true | | |
| type | The geometry type (point or polygon | false | polygon | polygon |
| projection | The projection | false | EPSG:4326 | EPSG:4326 |
| geometry-field | The geometry field name | false | the_geom | the_geom |

Grid Width / Height

Create a grid Layer with cell width and height

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|-------------------------------------|-----------|-------------------|---------------------|
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| cell-width | The width of each cell | true | | |
| cell-height | The height of each cell | true | | |
| geometry | The constraining geometry | true | | |
| type | The geometry type (point or polygon | false | polygon | polygon |
| projection | The projection | false | EPSG:4326 | EPSG:4326 |
| geometry-field | The geometry field name | false | the_geom | the_geom |

Identity

Calculate the intersection between a Layer with another Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|--------------------|---|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| other-name | The other Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| postfix-all | Whether to postfix all field names when combining schemas | false | false | false |
| include-duplicates | Whether to include duplicate field names | false | true | true |

Intersection

Calculate the intersection between a Layer with another Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|--------------------|---|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| other-name | The other Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| postfix-all | Whether to postfix all field names when combining schemas | false | false | false |
| include-duplicates | Whether to include duplicate field names | false | true | true |

Minimum Circle

Calculate the minimum bounding circle of the input Layer and save it to the output Layer.

```
geo-shell> layer mincircle --input-name countries --output-workspace layers --output-name mincircle
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| geometry-field | The geometry field name | false | the_geom | the_geom |

```
geo-shell> workspace open --name layers --params memory  
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg  
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld  
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean  
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer style set --name ocean --style examples/ocean.sld  
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean
```

```
geo-shell> layer mincircle --input-name countries --output-workspace layers --output-name mincircle  
Done!
```

```
geo-shell> style vector default --layer mincircle --color #1E90FF --opacity 0.25 --file examples/mincircle.sld  
Default Vector Style for mincircle written to /home/travis/build/jericks/geo-shell/examples/mincircle.sld!
```

```
geo-shell> layer style set --name mincircle --style examples/mincircle.sld  
Style /home/travis/build/jericks/geo-shell/examples/mincircle.sld set on mincircle
```

```
geo-shell> map open --name map  
Map map opened!
```

```
geo-shell> map add layer --name map --layer ocean  
Added ocean layer to map map
```

```
geo-shell> map add layer --name map --layer countries
```

Added countries layer to map map

```
geo-shell> map add layer --name map --layer mincircle
```

Added mincircle layer to map map

```
geo-shell> map draw --name map --file examples/layer_mincircle.png
```

Done drawing /home/travis/build/jericks/geo-shell/examples/layer_mincircle.png!

```
geo-shell> map close --name map
```

Map map closed!



Minimum Circles

Calculate the minimum bounding circle of each Feature in the input Layer and save them to the output Layer.

```
geo-shell> layer mincircles --input-name countries --output-workspace layers --output-name mincircles
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

```
geo-shell> workspace open --name layers --params memory
```

Workspace layers opened!

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!

geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries

geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries

geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean

geo-shell> layer style set --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

geo-shell> layer mincircles --input-name countries --output-workspace layers --output-name mincircles
Done!

geo-shell> style vector default --layer mincircles --color #1E90FF --opacity 0.25 --file examples/mincircles.sld
Default Vector Style for mincircles written to /home/travis/build/jericks/geo-shell/examples/mincircles.sld!

geo-shell> layer style set --name mincircles --style examples/mincircles.sld
Style /home/travis/build/jericks/geo-shell/examples/mincircles.sld set on mincircles

geo-shell> map open --name map
Map map opened!


geo-shell> map add layer --name map --layer ocean
Added ocean layer to map map

geo-shell> map add layer --name map --layer countries
Added countries layer to map map

geo-shell> map add layer --name map --layer mincircles
Added mincircles layer to map map

geo-shell> map draw --name map --file examples/layer_mincircles.png
Done drawing /home/travis/build/jericks/geo-shell/examples/layer_mincircles.png!

geo-shell> map close --name map
Map map closed!
```



Minimum Rectangle

Calculate the minimum rectangle of the input Layer and save it to the output Layer.

```
geo-shell> layer minrect --input-name countries --output-workspace layers --output-name minrect
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| geometry-field | The geometry field name | false | the_geom | the_geom |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

geo-shell> **layer open** --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean

geo-shell> **layer style set** --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

geo-shell> **layer minrect** --input-name countries --output-workspace layers --output-name minrect
Done!

geo-shell> **style vector default** --layer minrect --color #1E90FF --opacity 0.25 --file
examples/minrect.sld
Default Vector Style for minrect written to /home/travis/build/jericks/geo-shell/examples/minrect.sld!

geo-shell> **layer style set** --name minrect --style examples/minrect.sld
Style /home/travis/build/jericks/geo-shell/examples/minrect.sld set on minrect

geo-shell> **map open** --name map
Map map opened!

geo-shell> **map add layer** --name map --layer ocean
Added ocean layer to map map

geo-shell> **map add layer** --name map --layer countries
Added countries layer to map map

geo-shell> **map add layer** --name map --layer minrect
Added minrect layer to map map

geo-shell> **map draw** --name map --file examples/layer_minrect.png
Done drawing /home/travis/build/jericks/geo-shell/examples/layer_minrect.png!

geo-shell> **map close** --name map
Map map closed!



Minimum Rectangles

Calculate the minimum rectangle of each Feature in the input Layer and save them to the output Layer.

```
geo-shell> layer minrects --input-name countries --output-workspace layers --output-name minrects
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
```

Opened Workspace naturalearth Layer ocean as ocean

```
geo-shell> layer style set --name ocean --style examples/ocean.sld
```

Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

```
geo-shell> layer minrects --input-name countries --output-workspace layers --output-name minrects
```

Done!

```
geo-shell> style vector default --layer minrects --color #1E90FF --opacity 0.25 --file examples/minrects.sld
```

Default Vector Style for minrects written to /home/travis/build/jericks/geo-shell/examples/minrects.sld!

```
geo-shell> layer style set --name minrects --style examples/minrects.sld
```

Style /home/travis/build/jericks/geo-shell/examples/minrects.sld set on minrects

```
geo-shell> map open --name map
```

Map map opened!

```
geo-shell> map add layer --name map --layer ocean
```

Added ocean layer to map map

```
geo-shell> map add layer --name map --layer countries
```

Added countries layer to map map

```
geo-shell> map add layer --name map --layer minrects
```


Added minrects layer to map map

```
geo-shell> map draw --name map --file examples/layer_minrects.png
```

Done drawing /home/travis/build/jericks/geo-shell/examples/layer_minrects.png!

```
geo-shell> map close --name map
```

Map map closed!



Octangle Envelope

Calculate the octagonal envelope of the input Layer and save it to the output Layer.

```
geo-shell> layer octagonalenvelope --input-name countries --output-workspace layers --output
-name octagonalenvelope
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| geometry-field | The geometry field name | false | the_geom | the_geom |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

geo-shell> **layer open** --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean

geo-shell> **layer style set** --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

geo-shell> **layer octagonalenvelope** --input-name countries --output-workspace layers --output
-name octagonalenvelope
Done!

geo-shell> **style vector default** --layer octagonalenvelope --color #1E90FF --opacity 0.25 --file
examples/octagonalenvelope.sld
Default Vector Style for octagonalenvelope written to /home/travis/build/jericks/geo-
shell/examples/octagonalenvelope.sld!

geo-shell> **layer style set** --name octagonalenvelope --style examples/octagonalenvelope.sld
Style /home/travis/build/jericks/geo-shell/examples/octagonalenvelope.sld set on octagonalenvelope

geo-shell> **map open** --name map
Map map opened!

geo-shell> **map add layer** --name map --layer ocean
Added ocean layer to map map

geo-shell> **map add layer** --name map --layer countries
Added countries layer to map map

geo-shell> **map add layer** --name map --layer octagonalenvelope
Added octagonalenvelope layer to map map

geo-shell> **map draw** --name map --file examples/layer_octagonalenvelope.png
Done drawing /home/travis/build/jericks/geo-shell/examples/layer_octagonalenvelope.png!

geo-shell> **map close** --name map
Map map closed!



Octangle Envelopes

Calculate the octagonal envelope of each Feature in the input Layer and save them to the output Layer.

```
geo-shell> layer octagonalenvelopes --input-name countries --output-workspace layers --output
-name octagonalenvelopes
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
```

Opened Workspace naturalearth Layer ocean as ocean

```
geo-shell> layer style set --name ocean --style examples/ocean.sld
```

Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

```
geo-shell> layer octagonalenvelopes --input-name countries --output-workspace layers --output  
-name octagonalenvelopes
```

Done!

```
geo-shell> style vector default --layer octagonalenvelopes --color #1E90FF --opacity 0.25 --file  
examples/octagonalenvelopes.sld
```

Default Vector Style for octagonalenvelopes written to /home/travis/build/jericks/geo-shell/examples/octagonalenvelopes.sld!

```
geo-shell> layer style set --name octagonalenvelopes --style examples/octagonalenvelopes.sld
```

Style /home/travis/build/jericks/geo-shell/examples/octagonalenvelopes.sld set on octagonalenvelopes

```
geo-shell> map open --name map
```

Map map opened!

```
geo-shell> map add layer --name map --layer ocean
```

Added ocean layer to map map

```
geo-shell> map add layer --name map --layer countries
```

Added countries layer to map map

```
geo-shell> map add layer --name map --layer octagonalenvelopes
```


Added octagonalenvelopes layer to map map

```
geo-shell> map draw --name map --file examples/layer_octagonalenvelopes.png
```

Done drawing /home/travis/build/jericks/geo-shell/examples/layer_octagonalenvelopes.png!

```
geo-shell> map close --name map
```

Map map closed!



Points Along Lines

Create points along lines

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|-----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| distance | The distance between points | true | | |

Simplify

Simplify the features of the input Layer and save them to the output Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

| | | | | |
|-----------|---|-------|----|----|
| algorithm | The simplify algorithm (DouglasPeucker - dp or TopologyPreserving - tp) | false | tp | tp |
| distance | The distance tolerance | true | | |

Symmetric Difference

Calculate the symmetric difference between a Layer and another Layer.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|--------------------|---|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| other-name | The other Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| postfix-all | Whether to postfix all field names when combining schemas | false | false | false |
| include-duplicates | Whether to include duplicate field names | false | true | true |

Transform

Transform the features of the input Layer and save them to the output Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|--|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| transforms | The pipe delimited list of transforms (field=expression or function) | true | | |

Union

Union a Layer with another Layer

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|--------------------|---|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| other-name | The other Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| postfix-all | Whether to postfix all field names when combining schemas | false | false | false |
| include-duplicates | Whether to include duplicate field names | false | true | true |

Voronoi

Calculate a voronoi diagram of the input Layer and save it to the output Layer.

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| geometry-field | The geometry field name | false | the_geom | the_geom |

Random Points

Create a Layer with a number of randomly located points

```
geo-shell> layer random --output-workspace layers --output-name points --geometry -180,-90,180,90 --number 100 --projection EPSG:4326
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| output-workspace | The output Layer Workspace | true | | |

| | | | | |
|-----------------------|--|-------|----------|----------|
| output-name | The output Layer name | true | | |
| number | The number of points | true | | |
| geometry | The geometry or bounds in which to create the points | true | | |
| projection | The projection | true | | |
| id-field | The id field name | false | id | id |
| geometry-field | The geometry field name | false | the_geom | the_geom |
| grid | Whether to create points in a grid | false | false | false |
| constrained-to-circle | Whether points should be constrained to a circle | false | false | false |
| gutter-fraction | The size of gutter between cells | false | 0 | 0 |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> layer random --output-workspace layers --output-name points --geometry -180,-90,180,90
--number 100 --projection EPSG:4326
Done!
```

```
geo-shell> style vector default --layer points --color #1E90FF --file examples/points.sld
Default Vector Style for points written to /home/travis/build/jericks/geo-shell/examples/points.sld!
```

```
geo-shell> layer style set --name points --style examples/points.sld
Style /home/travis/build/jericks/geo-shell/examples/points.sld set on points
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer style set --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean
```



```
geo-shell> map open --name randomMap
```

Map randomMap opened!

```
geo-shell> map add layer --name randomMap --layer ocean
```

Added ocean layer to map randomMap

```
geo-shell> map add layer --name randomMap --layer countries
```

Added countries layer to map randomMap

```
geo-shell> map add layer --name randomMap --layer points
```


Added points layer to map randomMap

```
geo-shell> map draw --name randomMap --file examples/random_points.png
```

Done drawing /home/travis/build/jericks/geo-shell/examples/random_points.png!

```
geo-shell> map close --name randomMap
```

Map randomMap closed!



Buffer

Buffer the input Layer to the output Layer.

```
geo-shell> layer buffer --input-name points --output-workspace layers --output-name buffers  
--distance 10
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------|----------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |

| | | | | |
|------------------|----------------------------|------|--|--|
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| distance | The buffer distance | true | | |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> layer random --output-workspace layers --output-name points --geometry -180,-90,180,90
--number 100 --projection EPSG:4326
Done!
```

```
geo-shell> layer buffer --input-name points --output-workspace layers --output-name buffers
--distance 10
Done!
```

```
geo-shell> style vector default --layer points --color #1E90FF --file examples/points.sld
Default Vector Style for points written to /home/travis/build/jericks/geo-shell/examples/points.sld!
```

```
geo-shell> style vector default --layer buffers --color #1E90FF --opacity 0.25 --file
examples/buffers.sld
Default Vector Style for buffers written to /home/travis/build/jericks/geo-shell/examples/buffers.sld!
```

```
geo-shell> layer style set --name points --style examples/points.sld
Style /home/travis/build/jericks/geo-shell/examples/points.sld set on points
```

```
geo-shell> layer style set --name buffers --style examples/buffers.sld
Style /home/travis/build/jericks/geo-shell/examples/buffers.sld set on buffers
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer style set --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean
```

```
geo-shell> map open --name map
Map map opened!
```

```
geo-shell> map add layer --name map --layer ocean
```

Added ocean layer to map map

```
geo-shell> map add layer --name map --layer countries
```

Added countries layer to map map

```
geo-shell> map add layer --name map --layer buffers
```

Added buffers layer to map map

```
geo-shell> map add layer --name map --layer points
```


Added points layer to map map

```
geo-shell> map draw --name map --file examples/layer_buffer.png
```

Done drawing /home/travis/build/jericks/geo-shell/examples/layer_buffer.png!

```
geo-shell> map close --name map
```

Map map closed!



Centroid

Calculate the centroids of the input Layer to the output Layer.

```
geo-shell> layer centroid --input-name countries --output-name centroids --output-workspace layers
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |

| | | | | |
|-------------|-----------------------|------|--|--|
| output-name | The output Layer name | true | | |
|-------------|-----------------------|------|--|--|

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer centroid --input-name countries --output-name centroids --output-workspace
layers
Done!
```

```
geo-shell> style vector default --layer centroids --color #1E90FF --file examples/centroids.sld
Default Vector Style for centroids written to /home/travis/build/jericks/geo-shell/examples/centroids.sld!
```

```
geo-shell> layer style set --name centroids --style examples/centroids.sld
Style /home/travis/build/jericks/geo-shell/examples/centroids.sld set on centroids
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer style set --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean
```

```
geo-shell> map open --name map
Map map opened!
```

```
geo-shell> map add layer --name map --layer ocean
Added ocean layer to map map
```

```
geo-shell> map add layer --name map --layer countries
Added countries layer to map map
```

```
geo-shell> map add layer --name map --layer centroids
Added centroids layer to map map
```

```
geo-shell> map draw --name map --file examples/layer_centroid.png
Done drawing /home/travis/build/jericks/geo-shell/examples/layer_centroid.png!
```

```
geo-shell> map close --name map
Map map closed!
```



Interior Point

Calculate the interior points of the input Layer to the output Layer.

```
geo-shell> layer interiorpoint --input-name countries --output-name interiorpoints --output
-workspace layers
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer interiorpoint --input-name countries --output-name interiorpoints --output
-workspace layers
```

Done!

```
geo-shell> style vector default --layer interiorpoints --color #1E90FF --file
examples/interiorpoints.sld
```

Default Vector Style for interiorpoints written to /home/travis/build/jericks/geo-shell/examples/interiorpoints.sld!

```
geo-shell> layer style set --name interiorpoints --style examples/interiorpoints.sld
Style /home/travis/build/jericks/geo-shell/examples/interiorpoints.sld set on interiorpoints
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer style set --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean
```

```
geo-shell> map open --name map
Map map opened!
```

```
geo-shell> map add layer --name map --layer ocean
Added ocean layer to map map
```

```
geo-shell> map add layer --name map --layer countries
Added countries layer to map map
```

```
geo-shell> map add layer --name map --layer interiorpoints
Added interiorpoints layer to map map
```

```
geo-shell> map draw --name map --file examples/layer_interiorpoint.png
Done drawing /home/travis/build/jericks/geo-shell/examples/layer_interiorpoint.png!
```

```
geo-shell> map close --name map
Map map closed!
```



Extent

Calculate the extent of the input Layer and save it to the output Layer.

```
geo-shell> layer extent --input-name states --output-workspace layers --output-name usa
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |
| geometry-field | The geometry field name | false | the_geom | the_geom |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer style set --name states --style examples/states.sld
Unable to find Layer states
```

```
geo-shell> layer open --workspace naturalearth --layer states --name states
Opened Workspace naturalearth Layer states as states
```

geo-shell> **layer extent** --input-name states --output-workspace layers --output-name usa
Done!

geo-shell> **style vector default** --layer usa --color #1E90FF --opacity 0.25 --file examples/extent.sld
Default Vector Style for usa written to /home/travis/build/jericks/geo-shell/examples/extent.sld!

geo-shell> **layer style set** --name usa --style examples/extent.sld
Style /home/travis/build/jericks/geo-shell/examples/extent.sld set on usa

geo-shell> **layer open** --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries

geo-shell> **layer style set** --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries

geo-shell> **layer open** --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean

geo-shell> **layer style set** --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

geo-shell> **map open** --name map
Map map opened!

geo-shell> **map add layer** --name map --layer ocean
Added ocean layer to map map

geo-shell> **map add layer** --name map --layer countries
Added countries layer to map map

geo-shell> **map add layer** --name map --layer states
Added states layer to map map

geo-shell> **map add layer** --name map --layer usa
Added usa layer to map map

geo-shell> **map draw** --name map --file examples/layer_extent.png
Done drawing /home/travis/build/jericks/geo-shell/examples/layer_extent.png!

geo-shell> **map close** --name map
Map map closed!



Extents

Calculate the extents of each Feature in the input Layer and save them to the output Layer.

```
geo-shell> layer extents --input-name states --output-workspace layers --output-name state_extents
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|------------------|----------------------------|-----------|-------------------|---------------------|
| input-name | The Layer name | true | | |
| output-workspace | The output Layer Workspace | true | | |
| output-name | The output Layer name | true | | |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
Workspace naturalearth opened!
```

```
geo-shell> layer style set --name states --style examples/states.sld
Unable to find Layer states
```

```
geo-shell> layer open --workspace naturalearth --layer states --name states
Opened Workspace naturalearth Layer states as states
```

```
geo-shell> layer extents --input-name states --output-workspace layers --output-name state_extents
Done!
```

```
geo-shell> style vector default --layer state_extents --color #1E90FF --opacity 0.25 --file
examples/extent.sld
Default Vector Style for state_extents written to /home/travis/build/jericks/geo-
shell/examples/extent.sld!

geo-shell> layer style set --name state_extents --style examples/extent.sld
Style /home/travis/build/jericks/geo-shell/examples/extent.sld set on state_extents

geo-shell> layer open --workspace naturalearth --layer countries --name countries
Opened Workspace naturalearth Layer countries as countries

geo-shell> layer style set --name countries --style examples/countries.sld
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries

geo-shell> layer open --workspace naturalearth --layer ocean --name ocean
Opened Workspace naturalearth Layer ocean as ocean

geo-shell> layer style set --name ocean --style examples/ocean.sld
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

geo-shell> map open --name map
Map map opened!

geo-shell> map add layer --name map --layer ocean
Added ocean layer to map map


geo-shell> map add layer --name map --layer countries
Added countries layer to map map

geo-shell> map add layer --name map --layer states
Added states layer to map map

geo-shell> map add layer --name map --layer state_extents
Added state_extents layer to map map

geo-shell> map draw --name map --file examples/layer_extents.png
Done drawing /home/travis/build/jericks/geo-shell/examples/layer_extents.png!

geo-shell> map close --name map
Map map closed!
```



Graticule

Square

Create a square graticule.

```
geo-shell> layer graticule square --workspace layers --name squares --bounds -180,-90,180,90
--length 20
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-----------|--------------------|-----------|-------------------|---------------------|
| workspace | The Workspace name | true | | |
| name | The new Layer name | true | | |
| bounds | The bounds | true | | |
| length | The length | true | | |
| spacing | The spacing | false | -1 | -1 |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> layer graticule square --workspace layers --name squares --bounds -180,-90,180,90
--length 20
Created Square Graticule Layer squares!
```

```
geo-shell> style vector default --layer squares --color #1E90FF --opacity 0.30 --file
```

examples/squares.sld

Default Vector Style for squares written to /home/travis/build/jericks/geo-shell/examples/squares.sld!

geo-shell> **layer style set** --name squares --style examples/squares.sld

Style /home/travis/build/jericks/geo-shell/examples/squares.sld set on squares

geo-shell> **workspace open** --name naturalearth --params examples/naturalearth.gpkg

Workspace naturalearth opened!

geo-shell> **layer open** --workspace naturalearth --layer countries --name countries

Opened Workspace naturalearth Layer countries as countries

geo-shell> **layer style set** --name countries --style examples/countries.sld

Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries

geo-shell> **layer open** --workspace naturalearth --layer ocean --name ocean

Opened Workspace naturalearth Layer ocean as ocean

geo-shell> **layer style set** --name ocean --style examples/ocean.sld

Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

geo-shell> **map open** --name graticule

Map graticule opened!

geo-shell> **map add layer** --name graticule --layer ocean

Added ocean layer to map graticule

geo-shell> **map add layer** --name graticule --layer countries

Added countries layer to map graticule

geo-shell> **map add layer** --name graticule --layer squares

Added squares layer to map graticule

geo-shell> **map draw** --name graticule --file examples/square_graticules.png

Done drawing /home/travis/build/jericks/geo-shell/examples/square_graticules.png!

geo-shell> **map close** --name graticule

Map graticule closed!



Rectangle

Create a rectangle graticule.

```
geo-shell> layer graticule rectangle --workspace layers --name rectangles --bounds -180,-90,180,90
--width 20 --height 10
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-----------|--------------------|-----------|-------------------|---------------------|
| workspace | The Workspace name | true | | |
| name | The new Layer name | true | | |
| bounds | The bounds | true | | |
| width | The width | true | | |
| height | The height | true | | |
| spacing | The spacing | false | -1 | -1 |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> layer graticule rectangle --workspace layers --name rectangles --bounds -180,-90,180,90
--width 20 --height 10
Created Rectangle Graticule Layer rectangles!
```

```
geo-shell> style vector default --layer rectangles --color #1E90FF --opacity 0.30 --file
examples/rectangles.sld
```

Default Vector Style for rectangles written to /home/travis/build/jericks/geo-shell/examples/rectangles.sld!

```
geo-shell> layer style set --name rectangles --style examples/rectangles.sld  
Style /home/travis/build/jericks/geo-shell/examples/rectangles.sld set on rectangles
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg  
Workspace naturalearth opened!
```

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld  
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean  
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer style set --name ocean --style examples/ocean.sld  
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean
```

```
geo-shell> map open --name graticule  
Map graticule opened!
```


```
geo-shell> map add layer --name graticule --layer ocean  
Added ocean layer to map graticule
```

```
geo-shell> map add layer --name graticule --layer countries  
Added countries layer to map graticule
```

```
geo-shell> map add layer --name graticule --layer rectangles  
Added rectangles layer to map graticule
```

```
geo-shell> map draw --name graticule --file examples/rectangle_graticules.png  
Done drawing /home/travis/build/jericks/geo-shell/examples/rectangle_graticules.png!
```

```
geo-shell> map close --name graticule  
Map graticule closed!
```



Oval

Create a oval graticule.

```
geo-shell> layer graticule oval --workspace layers --name ovals --bounds -180,-90,180,90 --size 20
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-----------|--------------------|-----------|-------------------|---------------------|
| workspace | The Workspace name | true | | |
| name | The new Layer name | true | | |
| bounds | The bounds | true | | |
| size | The size | true | | |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> layer graticule oval --workspace layers --name ovals --bounds -180,-90,180,90 --size 20
Created Oval Graticule Layer ovals!
```

```
geo-shell> style vector default --layer ovals --color #1E90FF --opacity 0.30 --file examples/ovals.sld
Default Vector Style for ovals written to /home/travis/build/jericks/geo-shell/examples/ovals.sld!
```

```
geo-shell> layer style set --name ovals --style examples/ovals.sld
Style /home/travis/build/jericks/geo-shell/examples/ovals.sld set on ovals
```

```
geo-shell> workspace open --name naturalearth --params examples/naturalearth.gpkg
```

Workspace naturalearth opened!

```
geo-shell> layer open --workspace naturalearth --layer countries --name countries  
Opened Workspace naturalearth Layer countries as countries
```

```
geo-shell> layer style set --name countries --style examples/countries.sld  
Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries
```

```
geo-shell> layer open --workspace naturalearth --layer ocean --name ocean  
Opened Workspace naturalearth Layer ocean as ocean
```

```
geo-shell> layer style set --name ocean --style examples/ocean.sld  
Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean
```

```
geo-shell> map open --name graticule  
Map graticule opened!
```


```
geo-shell> map add layer --name graticule --layer ocean  
Added ocean layer to map graticule
```

```
geo-shell> map add layer --name graticule --layer countries  
Added countries layer to map graticule
```

```
geo-shell> map add layer --name graticule --layer ovals  
Added ovals layer to map graticule
```

```
geo-shell> map draw --name graticule --file examples/oval_graticules.png  
Done drawing /home/travis/build/jericks/geo-shell/examples/oval_graticules.png!
```

```
geo-shell> map close --name graticule  
Map graticule closed!
```

Hexagon

Create a hexagon graticule.

```
geo-shell> layer graticule hexagon --workspace layers --name hexagons --bounds -180,-90,180,90
--length 10
```

| Name | Description | Mandatory | Specified Default | Unspecified Default |
|-------------|----------------------------------|-----------|-------------------|---------------------|
| workspace | The Workspace name | true | | |
| name | The new Layer name | true | | |
| bounds | The bounds | true | | |
| length | The length | true | | |
| spacing | The spacing | false | 5 | 5 |
| orientation | The orientation (flat or angled) | false | flat | flat |

```
geo-shell> workspace open --name layers --params memory
Workspace layers opened!
```

```
geo-shell> layer graticule hexagon --workspace layers --name hexagons --bounds -180,-90,180,90
--length 10
Created Hexagon Graticule Layer hexagons!
```

```
geo-shell> style vector default --layer hexagons --color #1E90FF --opacity 0.30 --file
```

examples/hexagons.sld

Default Vector Style for hexagons written to /home/travis/build/jericks/geo-shell/examples/hexagons.sld!

geo-shell> **layer style set** --name hexagons --style examples/hexagons.sld

Style /home/travis/build/jericks/geo-shell/examples/hexagons.sld set on hexagons

geo-shell> **workspace open** --name naturalearth --params examples/naturalearth.gpkg

Workspace naturalearth opened!

geo-shell> **layer open** --workspace naturalearth --layer countries --name countries

Opened Workspace naturalearth Layer countries as countries

geo-shell> **layer style set** --name countries --style examples/countries.sld

Style /home/travis/build/jericks/geo-shell/examples/countries.sld set on countries

geo-shell> **layer open** --workspace naturalearth --layer ocean --name ocean

Opened Workspace naturalearth Layer ocean as ocean

geo-shell> **layer style set** --name ocean --style examples/ocean.sld

Style /home/travis/build/jericks/geo-shell/examples/ocean.sld set on ocean

geo-shell> **map open** --name graticule

Map graticule opened!

geo-shell> **map add layer** --name graticule --layer ocean

Added ocean layer to map graticule

geo-shell> **map add layer** --name graticule --layer countries

Added countries layer to map graticule

geo-shell> **map add layer** --name graticule --layer hexagons

Added hexagons layer to map graticule

geo-shell> **map draw** --name graticule --file examples/hexagon_graticules.png

Done drawing /home/travis/build/jericks/geo-shell/examples/hexagon_graticules.png!

geo-shell> **map close** --name graticule

Map graticule closed!

