

30
double-sided
adhesive tape

60
wire black (-)
AWG28 UL1571

50
wire red (+)
AWG28 UL1571

40
adhesive tape kapton

20
PCM

10
LP571225

40
adhesive tape
kapton (2x)

5.7
 $+0.3$
 -0.3

LiPo Battery 3.7V
LP571225 200mAh

26
 $+1.0$
 -1.0

10
 $+3.0$
 -3.0

12
 $+0.5$
 -0.5

Circuit Diagram

LP571225

PCM

Specification

Lithium Polymer Battery Pack LP571225 200mAh 3.7V with Protection Circuit Module (PCM)
This data sheet describes the requirements and properties of lithium polymer rechargeable battery pack manufactured by LiPol Battery Co., Ltd - China

Mechanical Characteristics

Cell	▶ LP571225
PCM	▶ Yes
NTC	▶ No
Configuration	▶ 1S1P
Weight	▶ appr. 4g

Electrical Specification

Rated Capacity	▶ 200mAh min, 210mAh typ.
Nominal Voltage	▶ 3.7V
Wat-Hour Rating	▶ 0.74Wh
Max. Operating Voltage Range	▶ 2.75V to 4.20V
Max. Charge Voltage	▶ 4.2V ± 50 mV
Max. Charge Current	▶ 100mA
Standard Charge Current	▶ 40mA
Max. Discharge Current	▶ 200mA
Standard Discharge Current	▶ 100mA
Discharge Cut Off	▶ 2.75V
Internal Impedance	▶ <200 m Ω
Expected Cycle Life	▶ 500 cycles $\geq 80\%$
@ (0.5C/0.5C) @ 23 $\pm 5^{\circ}$ C	

Cell Protection

Overcharge Detection	▶ 4.275 ± 50 mV (0.7 to 1.3sec. delay, release 4.275V ± 50 mV)
Overdischarge Detection	▶ 2.75V ± 50 mV (14 to 26msec. delay, resume 2.50V ± 50 mV)
Overcurrent Detection	▶ 2A to 2.5A (8 to 16msec. delay)

Ambient Conditions

Charge Temp. Range	▶ 0 to +45 $^{\circ}$ C
Discharge Temp. Range	▶ -20 to +60 $^{\circ}$ C
Storage Temp. Range	▶ 1 year at -20 to +30 $^{\circ}$ C $>70\%$
	▶ 3 months at -20 to +45 $^{\circ}$ C $>70\%$
	▶ 1 month at -20 to +60 $^{\circ}$ C $>70\%$
Humidity	▶ 65 $\pm 20\%$ RH

Environmental and Safety

Please follow LiPol Handling and Safety Precautions for Lithium Polymer Battery.
This battery meets the requirements of Battery Directives, and the battery parts are IEC 62133 & RoHS-Compliant. For more safety precautions and performance standards, please go to www.lipolbattery.com/support.html

Mae in mm All dimensions in mm	Freimatoleranzen Generaltolerances	Date Erst. / Orig	Name Xie Qingfang	LiPol Battery	
Als Betriebsgeheimnis anvertraut, alle Rechte vorbehalten	up to 6 over 6 up to 30 over 30 up to 100 over 100	Gepr./Check	Guo Daxia		
Proprietary data, company confidential, all rights reserved.	$\cdot 0.1$ $\cdot 0.2$ $\cdot 0.3$ $\cdot 0.5$	Benennung/ Designation	LP571225	Zchnng. / Dwg. Nr. 1 FD_4739_10	Index
		Origin:		support@lipolbattery.com	www.LiPolBattery.com