
shm analysis

Analysis of substitution type and frequency

Load preprocessed data

```
library(dplyr)
library(ggplot2)
library(data.table)
library(scales)
select = dplyr::select
summarise = dplyr::summarise
load("shm_rep2.rda")
df = data.table(shm) %>%
    mutate(region = as.character(region)) %>%
    filter(type == "RNA") %>%
    mutate(region = factor(region, c("FR1","CDR1","FR2","CDR2","FR3","CDR3","FR4"))) %>%
    mutate(mutation.type = ifelse(as.character(from.aa) == as.character(to.aa), "S", "R")) %>%
    group_by(proj, type, sample, replica) %>%
    mutate(weight2 = 1/n())
Check if we observe well-documented increase in replacement:synonimic hypermutation ratio in CDR regions:
p5=ggplot(df %>% mutate(weight2 = weight2/sum(weight2))) +
    geom_histogram(binwidth = 1, aes(x=pos.aa, weight=weight2, fill=region)) +
    \#geom\_density(adjust=2, aes(x=pos.aa, weight=weight, fill=region), position = "stack", color = NA) + (adjust=2, aes(x=pos.aa, weight=weight, fill=region), position = "stack", color = NA) + (adjust=2, aes(x=pos.aa, weight=weight, fill=region), position = "stack", color = NA) + (adjust=2, aes(x=pos.aa, weight=weight, fill=region), position = "stack", color = NA) + (adjust=2, aes(x=pos.aa, weight=weight, fill=region), position = "stack", color = NA) + (adjust=2, aes(x=pos.aa, weight=weight, fill=region), position = "stack", color = NA) + (adjust=2, aes(x=pos.aa, weight=weight, fill=region), position = "stack", color = NA) + (adjust=2, aes(x=pos.aa, weight=weight, fill=region), position = "stack", color = NA) + (aes(x=pos.aa, weight=weight, fill=region), position = (aes(x=pos.aa, weight=weight), fill=region), position = (aes(x=pos.aa, weight=weight), fill=region), fill=region), fill=region), fill=region = (aes(x=pos.aa, weight=weight), fill=region), fill=region), fill=region = (aes(x=pos.aa, weight=weight), fill=region), fill=region = (aes(x=pos.aa, weight=weight), fill=region), fill=region = (aes(x=pos.aa, weight=weight), fill=region), fill=region), fill=region = (aes(x=pos.aa, weight=weight), fill=region), fill=region), fill=region = (aes(x=pos.aa, weight=weight), fill=region = (aes(x=pos.aa, weight=weight), fill=region = (aes(x=pos.aa, weight=weight=weight), fill=region = (aes(x=pos.aa, weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=weight=wei
    geom density(binwidth = 1, aes(x=pos.aa, weight=weight2, linetype = mutation.type)) +
    scale_y_continuous("Hypermutation density", expand = c(0,0)) +
    scale x continuous ("Position in IG, AA", expand = c(0,0)) +
    scale_linetype("SHM type") +
    scale_fill_brewer("Region", palette = "Paired") +
    theme_bw() +
    theme(panel.grid.major = element_blank(), panel.grid.minor = element_blank(),
                 legend.position = c(0.75, 0.81),
                 legend.direction = "horizontal")
## Warning: Ignoring unknown aesthetics: weight
## Warning: Ignoring unknown parameters: binwidth
р5
## Warning in density.default(x, weights = w, bw = bw, adjust = adjust, kernel
## = kernel, : sum(weights) != 1 -- will not get true density
## Warning in density.default(x, weights = w, bw = bw, adjust = adjust, kernel
## = kernel, : sum(weights) != 1 -- will not get true density
```



Relative hypermutation burden by region for old and young

```
df <- df %>%
  filter(from.aa != "" | to.aa != "" | is.na(pos.nt))
df.shm.share = df %>%
  group_by(proj, sample, region) %>%
  summarise(count = n()) %>%
  group_by(sample) %>%
 mutate(share = count/sum(count))
df.shm.1 = df \%>\%
  group_by(proj, sample, region, clone) %>%
  summarise(shms = n())
ggplot(df.shm.1, aes(x = shms, group = proj, color = proj)) +
  stat_ecdf() +
  scale_y_continuous("") +
  xlab("") +
  scale_fill_brewer("Age", palette = "Set1") +
  facet_wrap(~region, scales = "free", ncol=4) +
  theme_bw() +
  theme(panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(),
        legend.position = c(0.90, 0.25),
        strip.background = element_blank())
```

```
FR1
                                 CDR1
                                                         FR2
                                                                               CDR2
1.00
                       1.00
                                              1.00
                                                                     1.00 -
0.75
                       0.75
                                              0.75
                                                                     0.75
0.50
                                              0.50
                       0.50
                                                                     0.50
0.25
                       0.25
                                              0.25
                                                                     0.25
                                              0.00
                                                                     0.00
0.00
                       0.00
                 15
                                       12
                                                             10
            10
                                                                                    10
           FR3
                                 CDR3
                                                         FR4
1.00
                       1.00
                                              1.00
0.75
                       0.75
                                              0.75
                                                                             proj
                                                                                - old
0.50
                       0.50
                                              0.50
                                                                                 young
0.25
                       0.25
                                              0.25
                       0.00
0.00
                                              0.00
                                                    2.5 5.0 7.5 10.0
        10
             20
                 30
                             2.5 5.0 7.5 10.012.5
dt.p = data.table()
for (r in unique(df.shm.share$region)) {
  tt = t.test(share~proj, df.shm.share %>% filter(region == r))
  p = tt$p.value
  dt.p = rbind(dt.p,
                data.table(region = r, p.adj = p))
}
dt.p$p.adj = p.adjust(dt.p$p.adj, method="BH")
print(dt.p)
      region
                    p.adj
         FR1 0.005831331
## 1:
## 2:
        CDR1 0.323091924
## 3:
         FR2 0.005831331
## 4:
        CDR2 0.989881416
## 5:
         FR3 0.365904903
## 6:
        CDR3 0.463264841
         FR4 0.989881416
ggplot(df.shm.share, aes(x = proj, group = proj, y = share, fill = proj)) +
  geom_boxplot(width = 0.5) +
  scale y continuous("Share of SHMs", label = percent) +
  xlab("") +
  scale_fill_brewer("Age", palette = "Set1") +
  facet_wrap(~region, scales = "free", ncol=4) +
  theme_bw() +
  theme(panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(),
        legend.position = c(0.90, 0.25),
```

```
axis.text.x = element_blank(), axis.ticks.x = element_blank(),
         strip.background = element_blank())
                FR1
                                       CDR1
                                                                FR2
                                                                                       CDR2
                                                   13.0%
     15%
                                                                           16.0%
                           13.5%
                                                   12.5%
     14%
                                                                           15.5%
                                                   12.0%
                           13.0%
                                                                           15.0%
                                                   11.5%
     13%
                           12.5%
                                                                           14.5%
Share of SHMs
                                                   11.0%
     12%
                FR3
                                       CDR3
                                                                FR4
   35.5%
                            7.5%
                                                    5.0%
                                                                                     Age
   35.0%
                            7.0%
                                                                                        old
                                                                                        young
                                                    4.5%
                            6.5%
   34.5%
                            6.0%
                                                     4.0%
    34.0%
dt.p = data.table()
for (r in unique(df.shm.share$region)) {
  tt = t.test(share~proj, df.shm.share %>% filter(region == r))
  p = tt$p.value
  dt.p = rbind(dt.p,
                data.table(region = r, p.adj = p))
}
dt.p$p.adj = p.adjust(dt.p$p.adj, method="BH")
print(dt.p)
##
      region
                     p.adj
## 1:
         FR1 0.005831331
        CDR1 0.323091924
## 2:
## 3:
          FR2 0.005831331
        CDR2 0.989881416
## 4:
## 5:
         FR3 0.365904903
         CDR3 0.463264841
## 6:
## 7:
          FR4 0.989881416
Replacement to silent ratio
df.shm.rs = df %>%
  group_by(proj, sample, region, mutation.type) %>%
  summarise(count = n()) %>%
  group_by(proj, sample, region) %>%
  summarise(rs = sum(c(0,count[which(mutation.type == "R")])) / sum(c(0,count[which(mutation.type == "S")])) / sum(c(0,count[which(mutation.type == "S")]))
```

```
ggplot(df.shm.rs, aes(x = proj, group = proj, y = rs, fill = proj)) +
  geom_boxplot(width = 0.5) +
  scale_y_continuous("R:S ratio") +
  xlab("") +
  scale_fill_brewer("Age", palette = "Set1") +
  facet_wrap(~region, scales = "free", ncol=4) +
  theme_bw() +
  theme(panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(),
        legend.position = c(0.90, 0.25),
        axis.text.x = element_blank(), axis.ticks.x = element_blank(),
        strip.background = element_blank())
               FR1
                                     CDR1
                                                             FR2
                                                                                   CDR2
                                                 0.40 -
    0.5
                          0.150 -
                                                 0.35
                                                                        0.13
    0.4
                          0.125 -
                                                 0.30
    0.3
                                                                        0.11
                          0.100 -
                                                 0.25
    0.2
                                                                        0.09
                          0.075 -
                                                 0.20
    0.1
R:S ratio
               FR3
                                     CDR3
                                                             FR4
                           0.20 -
                                                 0.25
                                                                                 Age
   0.15
                           0.15 -
                                                                                     old
                                                 0.20
                                                 0.15
   0.10
                           0.10
                                                 0.10
                           0.05
dt.p = data.table()
for (r in unique(df.shm.rs$region)) {
 tt = t.test(rs~proj, df.shm.rs %>% filter(region == r))
 p = tt$p.value
 dt.p = rbind(dt.p,
               data.table(region = r, p=p,p.adj = p))
dt.p$p.adj = p.adjust(dt.p$p.adj, method="BH")
print(dt.p)
##
      region
                                  p.adj
## 1:
         FR1 0.0009172687 0.006420881
```

2:

3:

4:

CDR1 0.0182061406 0.042556498

FR2 0.0182384989 0.042556498

CDR2 0.6200315297 0.723370118

```
## 5:
        FR3 0.2332620000 0.408208500
## 6:
        CDR3 0.4460072914 0.624410208
## 7:
        FR4 0.9310035113 0.931003511
Overall statistics
df.shm.share.s = df %>%
  group_by(proj, sample, stat="# SHMs") %>%
  summarise(value = n())
df.shm.rs.s = df \%>\%
  group_by(proj, sample, mutation.type) %>%
  summarise(count = n()) %>%
  group_by(proj, sample, stat="R:S ratio") %>%
  summarise(value = sum(c(0,count[which(mutation.type == "R")])) / sum(c(0,count[which(mutation.type ==
tmp = rbind(df.shm.share.s,
             df.shm.rs.s)
p6=ggplot(tmp,
       aes(x = proj, y = value, fill = proj))+
geom_boxplot(width = 0.5) +
  scale_y_continuous("") +
  xlab("") +
```

scale_fill_brewer("Age", palette = "Set1") +


strip.background = element_blank())

axis.text.x = element_blank(), axis.ticks.x = element_blank(),

facet_wrap(~stat, scales = "free") +

theme bw() +

p6



R:S ratio across different substitution patterns at nucleotide level


```
df.sign.rs = df.sign %>%
    group_by(mutation.signature, mutation.type) %>%
    summarise(count = n()) %>%
    dcast(mutation.signature ~ mutation.type, value.var = "count") %>%
    mutate(rs = R/S)

p7=ggplot(df.sign.rs, aes(x = mutation.signature, y = rs, fill = mutation.signature)) +
    geom_bar(stat="identity", color="black") +
    geom_hline(yintercept = 1, linetype="dashed") +
    scale_fill_brewer("Signature", palette = "Paired") +
```

```
scale_y_continuous("R:S ratio", breaks=0:8) +
  xlab("") +
  theme_bw() +
  theme(panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(),
        axis.text.x = element_blank(), axis.ticks.x = element_blank())
р7
                                                                                  Signature
                                                                                      A>C
                                                                                      A>G
                                                                                      A>T
                                                                                      C>A
                                                                                      C>G
R:S ratio
                                                                                      C>T
                                                                                      G>A
                                                                                      G>C
                                                                                      G>T
                                                                                      T>A
```

Share of different substitution patterns compared between young and old. Age-related difference observed for certain substitution patterns aross hypermutations.


T>C T>G



```
a = aov(freq ~ proj * mutation.signature, df.sign.s)
summary(a)
```

```
##
                          Df Sum Sq Mean Sq F value
                                                        Pr(>F)
                           1 0.00000 0.000000
                                                 0.00 1.000000
## proj
## mutation.signature
                          11 0.21447 0.019497 681.23 < 2e-16 ***
## proj:mutation.signature 11 0.00113 0.000102
                                                 3.58 0.000301 ***
## Residuals
                          96 0.00275 0.000029
## Signif. codes: 0 '***' 0.001 '**' 0.05 '.' 0.1 ' ' 1
dt.p = data.table()
for (ms in unique(df.sign.s$mutation.signature)) {
tt = t.test(freq ~ proj, df.sign.s %>% filter(mutation.signature == ms))
```

```
p = tt$p.value
  dt.p = rbind(dt.p,
               data.table(mutation.signature = ms, p=p))
}
dt.p$p.adj = p.adjust(dt.p$p, method = "BH")
print(dt.p %>% arrange(p.adj))
##
      mutation.signature
                                          p.adj
## 1
                     G>A 0.001634609 0.01961531
## 2
                     C>G 0.008651607 0.05190964
## 3
                     T>C 0.143563917 0.45932501
                     T>G 0.153108337 0.45932501
## 4
## 5
                     C>A 0.357554836 0.61295115
## 6
                     C>T 0.352831310 0.61295115
## 7
                     G>T 0.279190083 0.61295115
## 8
                     T>A 0.439025235 0.65853785
## 9
                     A>C 0.870625042 0.87062504
## 10
                     A>G 0.701246870 0.87062504
                     A>T 0.863525705 0.87062504
## 11
                     G>C 0.780921733 0.87062504
## 12
aa.classes = data.table(aa = strsplit("I,V,L,F,C,M,A,W,G,T,S,Y,P,H,N,D,Q,E,K,R", ",")[[1]],
                         hydrop = c(rep("hydrophobic", 8), rep("neutral", 6),
                                    rep("hydrophilic", 6)))
df.aachange = df %>%
  merge(aa.classes %>% mutate(from.aa = aa, from.value = hydrop) %>% select(from.aa, from.value)) %>%
  merge(aa.classes %>% mutate(to.aa = aa, to.value = hydrop) %>% select(to.aa, to.value))
hydrop_toint = function(x) {
  ifelse(x == "hydrophobic", 1, ifelse(x == "neutral", 0, -1))
dt.aachange.s = df.aachange %>%
  group_by(sample, proj, from.value, to.value) %>%
  summarise(count = n()) %>%
  group_by(sample, proj) %>%
  mutate(freq = count / sum(count),
         hydrop.change = hydrop_toint(to.value) - hydrop_toint(from.value)) %>%
  group_by(hydrop.change) %>%
  mutate(freq2 = freq / length(unique(paste(from.value, to.value))))
p9=ggplot(dt.aachange.s, aes(x=hydrop.change, group=paste(hydrop.change, proj), fill = proj, y= freq2))
  geom_boxplot() +
  scale_fill_brewer("Age", palette = "Set1") +
  ylab("Share of hypermutations") +
  xlab("Hydropathy change (hydrophobic>hydrophilic) .. (hydrophilic>hydrophobic)") +
  theme bw() +
  theme(aspect=1,
        legend.position = c(0.85, 0.85),
        panel.grid.major = element_blank(),
        panel.grid.minor = element_blank())
p9
```



Hydropathy change (hydrophobic>hydrophilic) .. (hydrophilic>hydrophobic)

```
dt.p = data.table()
for (hc in unique(dt.aachange.s$hydrop.change)) {
  tt = t.test(freq ~ proj, dt.aachange.s %>% filter(hydrop.change == hc))
  p = tt$p.value
  dt.p = rbind(dt.p,
               data.table(hydrop.change = hc, p=p))
}
dt.p$p.adj = p.adjust(dt.p$p, method = "BH")
print(dt.p %>% arrange(p.adj))
     hydrop.change
## 1
                 2 0.005610143 0.02805071
## 2
                 1 0.269552193 0.67388048
## 3
                 0 0.880382343 0.89206698
## 4
                -2 0.892066979 0.89206698
                -1 0.851821299 0.89206698
ggsave("figures/p5.pdf", p5, width = 10, height = 5)
## Warning in density.default(x, weights = w, bw = bw, adjust = adjust, kernel
## = kernel, : sum(weights) != 1 -- will not get true density
## Warning in density.default(x, weights = w, bw = bw, adjust = adjust, kernel
## = kernel, : sum(weights) != 1 -- will not get true density
```

```
ggsave("figures/p6.pdf", p6, width = 5, height = 5)
ggsave("figures/p7.pdf", p7, width = 5, height = 5)
ggsave("figures/p8.pdf", p8, width = 8, height = 5)
ggsave("figures/p9.pdf", p9, width = 7, height = 5)
```