Standard Code Library

antileaf

Last Compiled: 14:55 Aug 05, 2024

目录

1 数学 1
1.1 多项式 1
1.1.1 FFT 1
1.1.2 NTT 1
1.1.3 任意模数卷积（MTT） 1
1.1.4 多项式操作 2
1.1.5 多点求值应用：$O(\sqrt{n}\log^2 n)$ 快速求阶乘 4
1.1.6 多项式快速插值 4
1.1.7 Bostan-Mori（求多项式分式第 n 项） 5
1.1.8 快速线性递推 $O(k\log k\log n)$ 5
1.1.9 多项式复合逆 6
1.1.10 多项式复合 8
1.1.11 分治 FFT 9
1.1.12 半在线卷积 9
1.1.13 生成函数计数原理 9
1.1.14 常用生成函数变换 10
1.2 插值 10
1.2.1 牛顿插值 10
1.2.2 拉格朗日（Lagrange）插值 10
1.3 FWT 快速沃尔什变换 10
1.3.1 三行 FWT 10
1.4 线性代数 10
1.4.1 矩阵乘法 11
1.4.2 高斯消元 11
1.4.3 行列式取模 11
1.4.4 线性基（消成对角） 11
1.4.5 线性代数知识 11
1.4.6 矩阵树定理，BEST 定理 11
1.5 $O(k^2\log n)$ 齐次线性递推 12
1.6 Berlekamp-Massey 最小递推式 12
1.6.1 优化矩阵快速幂DP 12
1.6.2 求矩阵最小多项式 13
1.6.3 求稀疏矩阵的行列式 13
1.6.4 求稀疏矩阵的秩 13
1.6.5 解稀疏方程组 13
1.7 线性规划 13
1.7.1 单纯形 Simplex 13
1.7.2 线性规划对偶原理 14
1.8 博弈论 14
1.8.1 SG 定理 14
1.8.2 纳什均衡 14
1.8.3 经典博弈 14
1.8.4 例题 15
1.9 自适应 Simpson 积分 15
1.10 常见数列 15
1.10.1 斐波那契数 Fibonacci 卢卡斯数 15
1.10.2 伯努利数 Bernoulli 自然数幂次和 15
1.10.3 分拆数 16
1.10.4 斯特林数 Stiring 16
1.10.5 贝尔数 Bell 17
1.10.6 欧拉数 Eulerian 17
1.10.7 卡特兰数 施罗德数 默慈金数 17
1.11 常用公式及结论 17
1.11.1 方差 17
1.11.2 min-max 反演 17
1.11.3 单位根反演（展开整除条件 $[k|n]$） 18
1.11.4 康托展开（排列的排名） 18
1.11.5 常系数齐次线性递推求通项 18

2 数论 19
2.1 $O(n)$ 预处理逆元 19
2.2 线性筛 19
2.3 杜教筛 19
2.4 Powerful Number 筛 19
2.5 洲阁筛 20
2.6 min25 筛 21
2.7 Miller-Rabin 22
2.8 Pollard's Rho 23
2.9 快速阶乘算法 23
2.10 扩展欧几里德 exgcd 23
2.10.1 求通解的方法 23
2.10.2 类欧几里德算法（直线下整点个数） 23
2.11 中国剩余定理 24
2.11.1 ex-CRT 24
2.12 二次剩余 24
2.13 原根 阶 24
2.14 常用数论公式 25
2.14.1 狄利克雷（Dirichlet）卷积 25
2.14.2 莫比乌斯反演 25
2.14.3 降幂公式 25
2.14.4 其他常用公式 25

3 图论 26
3.1 最小生成树 26
3.1.1 Boruvka 算法 26
3.1.2 动态最小生成树 26
3.1.3 最小树形图 27
3.1.4 斯坦纳树 Steiner Tree 27
3.1.5 最小直径生成树 28
3.2 最短路 29
3.2.1 Dijkstra 29
3.2.2 Johnson 算法（负权图多源最短路） 29
3.2.3 k 短路 29
3.3 Tarjan 算法 30
3.3.1 强连通分量 30
3.3.2 割点 点双 30
3.3.3 桥 边双 31
3.4 欧拉回路 31
3.5 仙人掌 31
3.5.1 仙人掌 DP 31
3.6 二分图 32
3.6.1 匈牙利 Hungary 32
3.6.2 Hopcroft-Karp 二分图匹配 32
3.6.3 KM 二分图最大权匹配 33
3.6.4 二分图原理 34
3.7 一般图匹配 34
3.7.1 高斯消元 34
3.7.2 带花树 35
3.7.3 带权带花树 36
3.8 支配树 38
3.9 2-SAT 39
3.10 最大流 39
3.10.1 Dinic 39
3.10.2 ISAP 39
3.10.3 最高标号预流推进 HLPP 40
3.11 费用流 41
3.11.1 SPFA 费用流 41
3.11.2 Dijkstra 费用流 42
3.11.3 预流推进费用流（可处理负环） 42
3.12 网络流原理 44
3.12.1 最大流 44
3.12.2 最小割 44
3.12.3 上下界网络流 44
3.12.4 常见建图方法 45
3.12.5 例题 45
3.13 Prufer 序列 45
3.14 弦图相关 46
3.15 其他 46

3.15.1 Stoer-Wagner 全局最小割 46

4 数据结构 48
4.1 线段树 48
4.1.1 非递归线段树 48
4.1.2 线段树维护矩形并 48
4.1.3 历史和 49
4.2 陈丹琦分治 50
4.2.1 动态图连通性（分治并查集） 50
4.2.2 动态最小生成树 51
4.2.3 四维偏序 51
4.3 整体二分 51
4.4 平衡树 52
4.4.1 Treap 52
4.4.2 无旋 Treap / 可持久化 Treap 53
4.4.3 Splay 53
4.5 树链剖分 54
4.5.1 动态树形 DP（最大权独立集） 54
4.6 树分治 56
4.6.1 动态树分治 56
4.6.2 紫荆花之恋 57
4.7 LCT 动态树 59
4.7.1 不换根（弹飞绵羊） 59
4.7.2 换根/维护生成树 60
4.7.3 维护子树信息 61
4.7.4 模板题：动态QTREE4 62
4.8 K-D 树 65
4.8.1 动态 K-D 树（定期重构） 65
4.9 LCA 最近公共祖先 66
4.9.1 Tarjan LCA $O(n+m)$ 66
4.10 虚树 66
4.11 长链剖分 67
4.11.1 梯子剖分 68
4.12 堆 68
4.12.1 左偏树 68
4.12.2 二叉堆 68
4.13 莫队 69
4.13.1 莫队二次离线 69
4.13.2 带修莫队在线化 $O(n^{\frac{5}{3}})$ 70
4.13.3 莫队二次离线在线化 $O((n+m)\sqrt{n})$ 70
4.13.4 例题 71
4.14 常见根号思路 71

5 字符串 73
5.1 KMP 73
5.1.1 ex-KMP 73
5.2 AC 自动机 73
5.3 后缀数组 SA 73
5.3.1 倍增 73
5.3.2 SA-IS 74
5.3.3 SAMSA 75
5.4 后缀平衡树 75
5.5 后缀自动机 SAM 75
5.5.1 广义后缀自动机 76
5.5.2 区间本质不同子串计数 76
5.6 回文树 PAM 79
5.6.1 广义回文树 79
5.7 Manacher 马拉车 81
5.8 字符串原理 81

6 动态规划 82
6.1 决策单调性 $O(n\log n)$ 82
6.2 例题 82
6.2.1 103388A Assigning Prizes 容斥 82

7 计算几何 84
7.1 Delaunay 三角剖分 84
7.2 最近点对 86

8 杂项 87
8.1 $O(1)$ 快速乘 87
8.2 Kahan 求和算法（减少浮点数累加的误差） 87
8.3 Python Decimal 87
8.4 $O(n^2)$ 高精度 87
8.5 笛卡尔树 90
8.6 GarsiaWachs 算法（$O(n\log n)$ 合并石子） 90
8.7 常用 NTT 素数及原根 90
8.8 xorshift 90
8.9 枚举子集 90
8.10 STL 91
8.10.1 vector 91
8.10.2 list 91
8.10.3 unordered_set/map 91
8.10.4 自定义 Hash 91
8.11 Public Based DataStructure (PB_DS) 91
8.11.1 哈希表 91
8.11.2 堆 91
8.11.3 平衡树 91
8.12 rope 92
8.13 其他 C++ 相关 92
8.13.1 cmath 92
8.13.2 algorithm 92
8.13.3 std::tuple 92
8.13.4 complex 92
8.14 一些游戏 92
8.14.1 德州扑克 92
8.14.2 炉石传说 95
8.15 OEIS 95
8.15.1 计数相关 95
8.15.2 线性递推数列 96
8.15.3 数论相关 96
8.15.4 其他 96
8.16 编译选项 96

9 附录 96
9.1 VScode 相关 96
9.1.1 插件 96
9.1.2 设置选项 96
9.1.3 快捷键 96
9.2 骂人的艺术—梁实秋 97
9.3 Cheat Sheet 97

1 数学

1.1 多项式

1.1.1 FFT

```cpp
using cp = complex<double>;
const double PI = acos(-1.0);

vector<cp> omega[25];

void fft_init(int n) {
    for (int k = 2, d = 0; k <= n; k *= 2, d++) {
        omega[d].resize(k + 1);
        for (int i = 0; i <= k; i++)
            omega[d][i] = polar(1.0, 2 * PI * i / k);
    }
}

void fft(cp* a, int n, int t) {
    for (int i = 1, j = 0; i < n - 1; i++) {
        int k = n;
        do
            j ^= (k >>= 1);
        while (j < k);

        if (i < j)
            swap(a[i], a[j]);
    }

    for (int k = 1, d = 0; k < n; k *= 2, d++)
        for (int i = 0; i < n; i += k * 2)
            for (int j = 0; j < k; j++) {
                cp w = omega[d][t > 0 ? j : k * 2 - j];
                cp u = a[i + j], v = w * a[i + j + k];
                a[i + j] = u + v;
                a[i + j + k] = u - v;
            }

    if (t < 0)
        for (int i = 0; i < n; i++)
            a[i] /= n;
}
```

1.1.2 NTT

```cpp
using ll = long long;
using ull = unsigned long long;

int inv[MAXN]; // 逆元，如果需要积分就顺便预处理出来
poly omega[25]; // 单位根

// n 是 DFT 的最大长度
// 例如如果最多有两个长为 k 的多项式相乘，或者求逆的长度为 k，那么 n 需要 >= 2k

void ntt_init(int n) {
    for (int k = 2, d = 0; k <= n; k *= 2, d++) {
        omega[d].resize(k + 1);

        int wn = qpow(3, (p - 1) / k), tmp = 1;
        for (int i = 0; i <= k; i++) {
            omega[d][i] = tmp;
            tmp = (ll)tmp * wn % p;
        }
    }

    inv[1] = 1;
    for (int i = 2; i < n; i++)
        inv[i] = (ll)(p - p / i) * inv[p % i] % p;
}

// 传入的必须是 [0, p) 范围内，不能有负的，不然会溢出
// 不能保证就把 d == 16 改成 d % 8 == 0 之类
void ntt(int *c, int n, int t) {
    static ull a[MAXN];
    for (int i = 0; i < n; i++) a[i] = c[i];

    for (int i = 1, j = 0; i < n - 1; i++) {
        int k = n;
        do
            j ^= (k >>= 1);
        while (j < k);

        if (i < j)
            swap(a[i], a[j]);
    }

    for (int k = 1, d = 0; k < n; k *= 2, d++) {
        if (d == 16)
            for (int i = 0; i < n; i++)
                a[i] %= p;

        for (int i = 0; i < n; i += k * 2)
            for (int j = 0; j < k; j++) {
                int w = omega[d][t > 0 ? j : k * 2 - j];
                ull u = a[i + j], v = w * a[i + j + k] % p;
                a[i + j] = u + v;
                a[i + j + k] = u - v + p;
            }
    }

    if (t > 0) {
        for (int i = 0; i < n; i++)
            c[i] = a[i] % p;
    }
    else {
        int inv = qpow(n, p - 2);
        for (int i = 0; i < n; i++)
            c[i] = a[i] * inv % p;
    }
}
```

1.1.3 任意模数卷积（MTT）

三模数 NTT 和直接拆系数 FFT 都太慢了，不要用。
MTT 的原理就是拆系数 FFT，只不过优化了做变换的次数。
考虑要对 $A(x), B(x)$ 两个多项式做 DFT，可以构造两个复多项式

$$P(x) = A(x) + iB(x) \quad Q(x) = A(x) - iB(x)$$

只需要 DFT 一个，另一个 DFT 实际上就是前者反转再取共轭，再利用

$$A(x) = \frac{P(x) + Q(x)}{2} \quad B(x) = \frac{P(x) - Q(x)}{2i}$$

即可还原出 $A(x), B(x)$。
IDFT 的道理更简单，如果要对 $A(x)$ 和 $B(x)$ 做 IDFT，只需要对 $A(x) + iB(x)$ 做 IDFT 即可，因为 IDFT 的结果必定为实数，所以结果的实部和虚部就分别是 $A(x)$ 和 $B(x)$。
实际上任何同时对两个实序列进行 DFT，或者同时对结果为实序列的 DFT 进行逆变换时都可以按照上面的方法优化，可以减少一半的 DFT 次数。

```cpp
void dft(cp* a, cp* b, int n) {
    static cp c[MAXN];
    for (int i = 0; i < n; i++)
        c[i] = cp(a[i].real(), b[i].real());
```

```cpp

    fft(c, n, 1);
    for (int i = 0; i < n; i++) {
        int j = (n - i) & (n - 1);
        a[i] = (c[i] + conj(c[j])) * 0.5;
        b[i] = (c[i] - conj(c[j])) * -0.5i;
    }
}

void idft(cp* a, cp* b, int n) {
    static cp c[MAXN];
    for (int i = 0; i < n; i++)
        c[i] = a[i] + 1i * b[i];

    fft(c, n, -1);
    for (int i = 0; i < n; i++) {
        a[i] = c[i].real();
        b[i] = c[i].imag();
    }
}

vector<int> multiply(const vector<int>& u, const vector<int>& v, int mod) {
    static cp a[2][MAXN], b[2][MAXN], c[3][MAXN];

    int base = ceil(sqrt(mod));
    int n = (int)u.size(), m = (int)v.size();

    int fft_n = 1;
    while (fft_n < n + m - 1)
        fft_n *= 2;

    for (int i = 0; i < 2; i++) {
        fill(a[i], a[i] + fft_n, 0);
        fill(b[i], b[i] + fft_n, 0);
    }
    for (int i = 0; i < 3; i++)
        fill(c[i], c[i] + fft_n, 0);

    for (int i = 0; i < n; i++) {
        a[0][i] = (u[i] % mod) % base;
        a[1][i] = (u[i] % mod) / base;
    }

    for (int i = 0; i < m; i++) {
        b[0][i] = (v[i] % mod) % base;
        b[1][i] = (v[i] % mod) / base;
    }

    dft(a[0], a[1], fft_n);
    dft(b[0], b[1], fft_n);

    for (int i = 0; i < fft_n; i++) {
        c[0][i] = a[0][i] * b[0][i];
        c[1][i] = a[0][i] * b[1][i] + a[1][i] * b[0][i];
        c[2][i] = a[1][i] * b[1][i];
    }

    fft(c[1], fft_n, -1);
    idft(c[0], c[2], fft_n);

    int base2 = base * base % mod;
    vector<int> ans(n + m - 1);

    for (int i = 0; i < n + m - 1; i++)
        ans[i] = ((ll)(c[0][i].real() + 0.5) +
            (ll)(c[1][i].real() + 0.5) % mod * base +
            (ll)(c[2][i].real() + 0.5) % mod * base2) % mod;

    return ans;
}
```

1.1.4 多项式操作

```cpp
int get_ntt_n(int n) { // not inclusive
    int ntt_n = 1;
    while (ntt_n < n)
        ntt_n *= 2;
    return ntt_n;
}

using poly = vector<int>;

// u, v 长度要相同，返回长度是两倍
poly poly_calc(const poly& u, const poly& v, function<int(int, int)> op) {
    static int a[MAXN], b[MAXN], c[MAXN];

    int n = (int)u.size();

    memcpy(a, u.data(), sizeof(int) * n);
    fill(a + n, a + n * 2, 0);
    memcpy(b, v.data(), sizeof(int) * n);
    fill(b + n, b + n * 2, 0);

    ntt(a, n * 2, 1);
    ntt(b, n * 2, 1);

    for (int i = 0; i < n * 2; i++)
        c[i] = op(a[i], b[i]);

    ntt(c, n * 2, -1);

    return poly(c, c + n * 2);
}

// 乘法，返回长度是两倍
poly poly_mul(const poly& u, const poly& v) {
    return poly_calc(u, v, [](int a, int b) { return (ll)a * b % p; });
}

// 求逆，返回长度不变
poly poly_inv(const poly& a) {
    poly c{qpow(a[0], p - 2)}; // 常数项一般都是 1

    for (int k = 2; k <= (int)a.size(); k *= 2) {
        c.resize(k);

        poly b(a.begin(), a.begin() + k);
        c = poly_calc(b, c, [](int bi, int ci) {
            return ((2 - (ll)bi * ci) % p + p) * ci % p;
        });
        memset(c.data() + k, 0, sizeof(int) * k);
    }

    c.resize(a.size());
    return c;
}

// 开根，返回长度不变
poly poly_sqrt(const poly& a) {
    poly c{1}; // 常数项不是 1 的话要写二次剩余

    for (int k = 2; k <= (int)a.size(); k *= 2) {
        c.resize(k);

        poly b(a.begin(), a.begin() + k);
        b = poly_mul(b, poly_inv(c));

```

```cpp
        for (int i = 0; i < k; i++)
            c[i] = (ll)(c[i] + b[i]) * inv_2 % p; // inv_2 是 2 的逆元
    }

    c.resize(a.size());
    return c;
}

// 求导
poly poly_derivative(const poly& a) {
    poly c(a.size());
    for (int i = 1; i < (int)a.size(); i++)
        c[i - 1] = (ll)a[i] * i % p;
    return c;
}

// 不定积分，最好预处理逆元
poly poly_integrate(const poly& a) {
    poly c(a.size());
    for (int i = 1; i < (int)a.size(); i++)
        c[i] = (ll)a[i - 1] * inv[i] % p;
    return c;
}

// ln，常数项不能为 0，返回长度不变
poly poly_ln(const poly& a) {
    poly c = poly_mul(poly_derivative(a), poly_inv(a));
    c.resize(a.size());
    return poly_integrate(c);
}

// exp，常数项必须是 0，返回长度不变
// 常数很大并且总代码很长，一般可以改用分治 FFT
// 依据：设 $G(x) = \exp F(x)$，则 $g_i = \frac{1}{i}\sum_{k=1}^{i-1} g_{i-k}\, k\, f_k$
poly poly_exp(const poly& a) {
    poly c{1};

    for (int k = 2; k <= (int)a.size(); k *= 2) {
        c.resize(k);

        poly b = poly_ln(c);
        for (int i = 0; i < k; i++) {
            b[i] = a[i] - b[i];
            if (b[i] < 0)
                b[i] += p;
        }
        (++b[0]) %= p;

        c = poly_mul(b, c);
        memset(c.data() + k, 0, sizeof(int) * k);
    }

    c.resize(a.size());
    return c;
}

// k 次幂，返回长度不变
// 注意常数项必须是 0，一次项必须是 1，否则需要在调用前处理一下
poly poly_pow(const poly& a, int k) {
    poly c = poly_ln(a);
    for (int i = 0; i < (int)c.size(); i++)
        c[i] = (ll)c[i] * k % p;
    return poly_exp(c);
}

// 自动判断长度的乘法
poly poly_auto_mul(poly a, poly b) {
    int res_len = (int)a.size() + (int)b.size() - 1;
    int ntt_n = get_ntt_n(res_len);

    a.resize(ntt_n);
    b.resize(ntt_n);

    ntt(a.data(), ntt_n, 1);
    ntt(b.data(), ntt_n, 1);

    for (int i = 0; i < ntt_n; i++)
        a[i] = (ll)a[i] * b[i] % p;

    ntt(a.data(), ntt_n, -1);
    a.resize(res_len);
    return a;
}

// 多项式除法，a 和 b 长度可以任意
// 商的长度是 n - m + 1，余数的长度是 m - 1
poly poly_div(const poly& a, const poly& b) {
    int n = (int)a.size(), m = (int)b.size();
    if (n < m)
        return {};

    int ntt_n = get_ntt_n(n - m + 1);

    poly f(ntt_n), g(ntt_n);
    for (int i = 0; i < n - m + 1; i++)
        f[i] = a[n - i - 1];
    for (int i = 0; i < m && i < n - m + 1; i++)
        g[i] = b[m - i - 1];

    poly g_inv = poly_inv(g);
    fill(g_inv.begin() + n - m + 1, g_inv.end(), 0);
    poly c = poly_mul(f, g_inv);
    c.resize(n - m + 1);
    reverse(c.begin(), c.end());
    return c;
}

// 多项式取模，a 和 b 长度可以任意，返回 (余数，商)
pair<poly, poly> poly_mod(const poly& a, const poly& b) {
    int n = (int)a.size(), m = (int)b.size();
    if (n < m)
        return {a, {}};

    poly d = poly_div(a, b);
    poly c = poly_auto_mul(b, d);

    poly r(m - 1);
    for (int i = 0; i < m - 1; i++)
        r[i] = (a[i] - c[i] + p) % p;
    return {r, d};
}

// 多项式多点求值，f 是多项式，x 是询问
struct poly_eval {
    poly f;
    vector<int> x;
    vector<poly> gs;
    vector<int> ans;

    poly_eval(const poly& f, const vector<int>& x) : f(f), x(x) {}

    void pretreat(int l, int r, int o) {
        poly& g = gs[o];

        if (l == r) {
            g = poly{p - x[l], 1};
            return;
        }

        int mid = (l + r) / 2;
```

```cpp
        pretreat(l, mid, o * 2);
        pretreat(mid + 1, r, o * 2 + 1);

        if (o > 1)
            g = poly_auto_mul(gs[o * 2], gs[o * 2 + 1]);
    }

    void solve(int l, int r, int o, const poly& f) {
        if (l == r) {
            ans[l] = f[0];
            return;
        }

        int mid = (l + r) / 2;
        solve(l, mid, o * 2, poly_mod(f, gs[o * 2]).first);
        solve(mid + 1, r, o * 2 + 1, poly_mod(f, gs[o * 2 + 1]).first);
    }

    vector<int> operator() () {
        int n = (int)f.size(), m = (int)x.size();
        if (m <= n)
            x.resize(m = n + 1);
        else if (n < m - 1)
            f.resize(n = m - 1);

        int bit_ceil = get_ntt_n(m);
        ntt_init(bit_ceil * 2); // 注意这里初始化了

        gs.resize(2 * bit_ceil + 1);
        pretreat(0, m - 1, 1);

        ans.resize(m);
        solve(0, m - 1, 1, f);
        return ans;
    }
};
```

1.1.5 多点求值应用：$O(\sqrt{n}\log^2 n)$ 快速求阶乘

问题 求 $n!\pmod p$，$n<p$，p 是 NTT 模数。
考虑令 $m=\lfloor\sqrt{n}\rfloor$，那么我们可以写出连续 m 个数相乘的多项式：

$$f(x)=\prod_{i=1}^{m}(x+i)$$

那么显然就有

$$n!=\left(\prod_{k=0}^{m-1}f(km)\right)\prod_{i=m^2+1}^{n}i$$

$f(x)$ 的系数可以用倍增求（或者懒一点直接分治 FFT），然后 $f(km)$ 可以用多点求值求出，所以总复杂度就是 $O(\sqrt{n}\log^2 n)$。
当然如果 p 不变并且多次询问的话，我们只需要取一个 m，也就是预处理 $O(\sqrt{p}\log^2 p)$，询问 $O(\sqrt{p})$。

1.1.6 多项式快速插值

问题 给出 n 个 x_i 与 y_i，求一个 $(n-1)$ 次多项式 $F(x)$，满足 $F(x_i)=y_i$。
考虑拉格朗日插值：

$$F(x)=\sum_{i=1}^{n}\frac{\prod_{i\neq j}(x-x_j)}{\prod_{i\neq j}(x_i-x_j)}y_i$$

第一步要先对每个 i 求出

$$\prod_{i\neq j}(x_i-x_j)$$

设

$$M(x)=\prod_{i=1}^{n}(x-x_i)$$

那么想要的是

$$\frac{M(x)}{x-x_i}$$

取 $x=x_i$ 时，上下都为 0，使用洛必达法则，则原式化为 $M'(x)$。
使用分治算出 $M(x)$，然后使用多点求值即可算出每个

$$\prod_{i\neq j}(x_i-x_j)=M'(x_i)$$

记

$$v_i=\frac{y_i}{\prod_{i\neq j}(x_i-x_j)}$$

那么第二步要求出

$$\sum_{i=1}^{n}v_i\prod_{i\neq j}(x-x_j)$$

使用分治，设

$$L(x)=\prod_{i=1}^{\lfloor n/2\rfloor}(x-x_i),\ R(x)=\prod_{i=\lfloor n/2\rfloor+1}^{n}(x-x_i)$$

则原式化为

$$\left(\sum_{i=1}^{\lfloor n/2\rfloor}v_i\prod_{i\neq j,\,j\le\lfloor n/2\rfloor}(x-x_j)\right)R(x)+$$
$$\left(\sum_{i=\lfloor n/2\rfloor+1}^{n}v_i\prod_{i\neq j,\,j>\lfloor n/2\rfloor}(x-x_j)\right)L(x)$$

递归计算，复杂度 $O(n\log^2 n)$。
注意由于整体和局部的 $M(x)$ 都要用到，要预处理一下。

```cpp
int qx[maxn], qy[maxn];
int th[25][maxn * 2], ansf[maxn]; // th存的是各阶段的M(x)

void pretreat2(int l, int r, int k) { // 预处理
    static int A[maxn], B[maxn];
    int *h = th[k] + l * 2;

    if (l == r) {
        h[0] = p - qx[l];
        h[1] = 1;
        return;
    }

    int mid = (l + r) / 2;

    pretreat2(l, mid, k + 1);
    pretreat2(mid + 1, r, k + 1);

    int N = 1;
    while (N <= r - l + 1)
        N *= 2;

    int *hl = th[k + 1] + l * 2, *hr = th[k + 1] + (mid + 1) * 2;

```

```cpp
    memset(A, 0, sizeof(int) * N);
    memset(B, 0, sizeof(int) * N);

    memcpy(A, hl, sizeof(int) * (mid - l + 2));
    memcpy(B, hr, sizeof(int) * (r - mid + 1));

    NTT(A, N, 1);
    NTT(B, N, 1);

    for (int i = 0; i < N; i++)
        A[i] = (long long)A[i] * B[i] % p;

    NTT(A, N, -1);

    for (int i = 0; i <= r - l + 1; i++)
        h[i] = A[i];
}

void solve2(int l, int r, int k) { // 分治
    static int A[maxn], B[maxn], t[maxn];

    if (l == r)
        return;

    int mid = (l + r) / 2;

    solve2(l, mid, k + 1);
    solve2(mid + 1, r, k + 1);

    int *hl = th[k + 1] + l * 2, *hr = th[k + 1] + (mid + 1) * 2;

    int N = 1;

    while (N < r - l + 1)
        N *= 2;

    memset(A, 0, sizeof(int) * N);
    memset(B, 0, sizeof(int) * N);

    memcpy(A, ansf + l, sizeof(int) * (mid - l + 1));
    memcpy(B, hr, sizeof(int) * (r - mid + 1));

    NTT(A, N, 1);
    NTT(B, N, 1);

    for (int i = 0; i < N; i++)
        t[i] = (long long)A[i] * B[i] % p;

    memset(A, 0, sizeof(int) * N);
    memset(B, 0, sizeof(int) * N);

    memcpy(A, ansf + mid + 1, sizeof(int) * (r - mid));
    memcpy(B, hl, sizeof(int) * (mid - l + 2));

    NTT(A, N, 1);
    NTT(B, N, 1);

    for (int i = 0; i < N; i++)
        t[i] = (t[i] + (long long)A[i] * B[i]) % p;

    NTT(t, N, -1);

    memcpy(ansf + l, t, sizeof(int) * (r - l + 1));
}

// 主过程
// 如果x, y传nullptr表示询问已经存在了qx, qy里
void interpolation(int *x, int *y, int n, int *f = nullptr) {
    static int d[maxn];

    if (x)
        memcpy(qx, x, sizeof(int) * n);
    if (y)
        memcpy(qy, y, sizeof(int) * n);

    pretreat2(0, n - 1, 0);

    get_derivative(th[0], d, n + 1);

    multipoint_eval(d, qx, nullptr, n, n);

    for (int i = 0; i < n; i++)
        ansf[i] = (long long)qy[i] * qpow(ans[i], p - 2) % p;

    solve2(0, n - 1, 0);

    if (f)
        memcpy(f, ansf, sizeof(int) * n);
}
```

1.1.7 Bostan-Mori

问题 已知两个 n 次多项式 $f(x)$ 与 $g(x)$，求 $\frac{f(x)}{g(x)}$ 的第 k 项系数。

做法 上下同乘 $g(-x)$，则底下的 $g(x)g(-x)$ 只有偶数项，所以上面的奇/偶数项乘完之后奇偶性是不变的。然后就可以直接按照 n 的奇偶性分情况只取出奇数项或者偶数项，这样就在 n 不变的情况下把 k 折半了，一直做到 $k=0$ 然后输出常数项即可。

$$[x^k]\frac{f(x)}{g(x)} = [x^k]\frac{f(x)g(-x)}{g(x)g(-x)} = [x^k]\frac{F(x^2)+xG(x^2)}{H(x^2)}$$
$$= \begin{cases} [x^{\lfloor k/2 \rfloor}]\dfrac{F(x)}{H(x)} & (k \text{ is even}) \\ [x^{\lfloor k/2 \rfloor}]\dfrac{G(x)}{H(x)} & (k \text{ is odd}) \end{cases}$$

复杂度 $O(n \log n \log k)$。

```cpp
int bostan_mori(int k, poly a, poly b) {
    int n = (int)a.size();

    while (k) {
        poly c = b;
        for (int i = 1; i < n; i += 2)
            c[i] = (p - c[i]) % p;

        a = poly_mul(a, c);
        b = poly_mul(b, c);

        for (int i = 0; i < n; i++) {
            a[i] = a[i * 2 + k % 2];
            b[i] = b[i * 2];
        }

        a.resize(n);
        b.resize(n);
        k /= 2;
    }

    return (ll)a[0] * qpow(b[0], p - 2) % p;
}
```

1.1.8 快速线性递推 $O(k \log k \log n)$

多项式除法 需要的代码参见 1.1.4.多项式操作 (第 2 页)。

```cpp
poly poly_power_mod(ll k, const poly& m) { // x^k mod m
    poly ans{1}, a{0, 1};

```

```
    while (k) {
        if (k & 1)
            ans = poly_mod(poly_auto_mul(ans, a), m).first;
        a = poly_mod(poly_auto_mul(a, a), m).first;
        k /= 2;
    }

    return ans;
}

// a_n = ∑_{i=1}^m c_i a_{n-i}   (c_0 = 0)
struct linear_recurrence {
    poly f; // f是预处理结果

    linear_recurrence(const poly& c, ll n) {
        assert(c[0] == 0); // c[0] 是没有用的
        int m = (int)c.size() - 1;

        int ntt_n = 1;
        while (ntt_n < m * 2)
            ntt_n *= 2;
        ntt_init(ntt_n); // 图省事就直接 ntt_init(1 << 18)

        poly t(m + 1);
        t[m] = 1;

        for (int i = 0; i < m; i++)
            t[i] = (p - c[m - i]) % p;
        f = poly_power_mod(n, t);
    }

    int operator()(const vector<int>& a) { // 0~m-1项初始值
        assert(a.size() == f.size()); int ans = 0;
        for (int i = 0; i < (int)a.size(); i++)
            ans = (ans + (ll)f[i] * a[i]) % p;
        return ans;
    }
};
```

Bostan-Mori 具体参见 1.1.7.Bostan-Mori (第 5 页)。

这个做法只需要抄多项式乘法，并且常数更小。

```
// a_n = ∑_{i=1}^m f_i a_{n-i}   (f_0 = 0)
// f.size() = a.size() + 1
int linear_recurrance(int n, poly f, poly a) {
    int m = (int)a.size();

    int ntt_n = 1;
    while (ntt_n <= m)
        ntt_n *= 2;

    ntt_init(ntt_n * 2);

    f.resize(ntt_n);
    a.resize(ntt_n);

    for (int i = 1; i <= m; i++)
        f[i] = (p - f[i]) % p;
    f[0] = 1;

    a = poly_mul(a, f);
    a.resize(ntt_n);
    fill(a.data() + m, a.data() + ntt_n, 0);

    return bostan_mori(n, a, f);
}
```

1.1.9 多项式复合逆

拉格朗日反演 如果 $f(x)$ 与 $g(x)$ 互为复合逆，则有

$$[x^n]\,f(x) = \frac{1}{n}\,[x^{n-1}]\left(\frac{x}{g(x)}\right)^n$$

$$[x^n]\,h(f(x)) = \frac{1}{n}\,[x^{n-1}]\,h'(x)\left(\frac{x}{g(x)}\right)^n$$

这样可以得到复合逆的一项。如果需要 $0\ldots n$ 项的所有系数，就麻烦一些。

推导过程省略，直接上结论：

$$\begin{aligned} f(x) \equiv & x\left(\sum_{k=1}^{n} x^{n-k}\frac{n}{k}\,[x^n]\,g^k(x)\right)^{-1/n} \pmod{x^{n+1}} \\ \equiv & \frac{x}{g_1}\left(\sum_{k=1}^{n}\frac{n}{k}\left(\frac{x}{g_1}\right)^{n-k}[z^n]\left(\frac{g(z)}{g_1}\right)^k\right)^{-1/n} \end{aligned}$$

g_1 是 $g(x)$ 的一次项。把它提出来是为了把要开根的式子常数项化成 1，避免考虑 $n \bmod \varphi(p)$ 的逆元。

现在唯一的难点就在于求 $[x^n]\left(\frac{g(x)}{g_1}\right)^k$。

考虑更一般的问题，即 **对所有** $k \in [1, n]$，**如何分别求出** $[x^n]A^k(x)$。引入另一个自变量 y，代表 $A(x)$ 的次数这一维，得到一个二元生成函数：

$$\sum_i x^i \sum_j y^j [x^i] A^j(x) = \sum_j y^j A^j(x) = \frac{1}{1 - yA(x)}$$

x^n 项的系数即为所求。

针对这个子问题，再考虑更一般的问题，即求 $[x^n]\frac{P(x,y)}{Q(x,y)}$。

按照 Bostan-Mori (1.1.7, 第 5 页) 一样的思路，上下同乘 $Q(-x,y)$，又会发现分母 $Q(x,y)Q(-x,y)$ 里 x 只有偶数项，只取出奇数项或者偶数项就可以把 n 折半，然后递归下去即可。边界是 $\frac{P(0,y)}{Q(0,y)}$。

在这里初始时 x 最高项是 n 次，而 y 只有一次。每步 x 的最大次数都会减半，而 y 的最大次数会翻倍，所以总的项数一直是 $O(n)$ 的。总的复杂度是 $O(n\log^2 n)$。

这里有一个优化：做完 k 次迭代之后 y 的最高次数是 2^k，也就是说有 2^k+1 项，在做卷积的时候就会白白多做一倍的长度。实际上可以注意到，$P(x,0)$ 和 $Q(x,0)$ 的 y^0 项只能是 0 或者 1，不会包含 x。所以可以把它提出来，这样 y 这一维的长度就刚好是 2^k 了。

$Q(x,0)$ 因为每次都保留偶数项，所以常数项一直都是 1。$P(x,0)$ 初始常数项也是 1，但在保留一次奇数项之后就一直是 0 了。

设 $P(x,0)$ 的常数项是 k，按照 $(Py+k)(Qy+1) = (PQy+P+kQ)y+k$ 计算即可。

解决上面的所有子问题之后别忘了还要有一个多项式开 n 次根，总代码量还是很大的。

```
// 对二元多项式做 DFT
void dft_2d(vector<poly>& a, int ntt_n, int ntt_m) {
    int n = (int)a.size();

    a.resize(ntt_n);
    for (int i = 0; i < ntt_n; i++) {
        a[i].resize(ntt_m);

        if (i < n)
            ntt(a[i].data(), ntt_m, 1);
    }

    for (int j = 0; j < ntt_m; j++) {
        poly t(ntt_n);

        for (int i = 0; i < n; i++)
            t[i] = a[i][j];

        ntt(t.data(), ntt_n, 1);
```

```cpp

        for (int i = 0; i < ntt_n; i++)
            a[i][j] = t[i];
    }
}

// 对二元多项式做 DFT，只保留前 n 行中 filter = true 的行
void idft_2d(vector<poly>& a, int n, function<bool(int)> filter) {
    int ntt_n = (int)a.size(), m = (int)a[0].size();

    for (int j = 0; j < m; j++) {
        poly t(ntt_n);
        for (int i = 0; i < ntt_n; i++)
            t[i] = a[i][j];

        ntt(t.data(), ntt_n, -1);

        for (int i = 0; i < n; i++)
            a[i][j] = t[i];
    }

    a.resize(n);
    for (int i = 0; i < n; i++)
        if (filter(i))
            ntt(a[i].data(), m, -1);
}

// 对所有 k ∈ [1, n]，求 [x^n] f^k(x)
// 注意这里 n 是最高次数，即 f 的长度为 n+1
poly bostan_mori(const poly& f) {
    int n = (int)f.size() - 1;
    vector<poly> a(n + 1), b(n + 1);

    for (int i = 0; i <= n; i++) {
        a[i] = {0};
        b[i] = {(p - f[i]) % p};
    }

    bool a00 = true;
    int m = 1;
    while (n) {
        vector<poly> ac(a), bc(b);
        for (int i = 0; i <= n; i++)
            for (int j = 0; j < m; j++) {
                if (a00) {
                    int d = i % 2 ? p - b[i][j] : b[i][j];
                    (a[i][j] += d) %= p;
                }

                if (i % 2 == 0)
                    b[i][j] = b[i][j] * 2 % p;
                else
                    b[i][j] = 0;
            }

        int ntt_n = get_ntt_n(n * 2 + 1);

        dft_2d(ac, ntt_n, m * 2);
        dft_2d(bc, ntt_n, m * 2);

        for (int i = 0; i < ntt_n; i++)
            for (int j = 0; j < m * 2; j++) // Q(-x, y) 的 DFT 直接从 Q(x, y) 的 DFT 转化过来就行了
                ac[i][j] = (ll)ac[i][j] * bc[(i + ntt_n / 2) & (ntt_n - 1)][j] % p;

        for (int i = 0; i < ntt_n / 2; i++) // 因为 Q(x, y) Q(-x, y) 只有 x^2k 项，所以只需做一半
            for (int j = 0; j < m * 2; j++) // DFT 的后一半一定和前一半一样
                bc[i][j] = (ll)bc[i][j] * bc[i + ntt_n / 2][j] % p;

        bc.resize(ntt_n / 2);

        idft_2d(ac, n + 1, [n](int i) { return i % 2 == n % 2; });
        idft_2d(bc, n / 2 + 1, [](int i) { return true; });

        for (int i = 0; i <= n; i++)
            if (i % 2 == n % 2) {
                a[i].resize(m * 2);

                for (int j = 1; j < m * 2; j++)
                    (a[i][j] += ac[i][j - 1]) %= p;

                a[i / 2].swap(a[i]);
            }

        for (int i = 0; i <= n / 2; i++) {
            b[i].swap(b[i * 2]);
            b[i].resize(m * 2);

            for (int j = 1; j < m * 2; j++)
                (b[i][j] += bc[i][j - 1]) %= p;
        }

        a00 &= !(n % 2);
        n /= 2;
        m *= 2;

        a.resize(n + 1);
        b.resize(n + 1);
    }

    for (int i = (int)f.size() - 1; i; i--) {
        a[0][i] = a[0][i - 1];
        b[0][i] = b[0][i - 1];
    }
    a[0][0] = b[0][0] = 1;

    poly res = poly_mul(a[0], poly_inv(b[0])); // 因为 m 每次都翻倍，所以此时 FFT 的长度一定就是 m
    res.resize(f.size());
    return res;
}

// 返回长度和 g 相同
// 因为做 DFT 的时候没有二维转一维，所以还是只需要初始化 get_ntt_n(n + 1) * 2 就行了
poly poly_composite_inversion(const poly& g) {
    assert(!g[0] && g[1]);

    int n = (int)g.size() - 1;

    int g1_inv = qpow(g[1], p - 2);
    poly t(n + 1);
    for (int i = 1; i <= n; i++)
        t[i] = (ll)g[i] * g1_inv % p;

    poly res = bostan_mori(t);

    for (int i = 0, pw = 1; i < n; i++) {
        t[i] = (ll)n * inv[n - i] % p * res[n - i] % p * pw % p;
        pw = (ll)pw * g1_inv % p;
    }

    int ntt_n = 1;
```

```
    while (ntt_n <= n)
        ntt_n *= 2;
    t.resize(ntt_n);

    t = poly_pow(t, p - inv[n]);

    poly f(n + 1);
    for (int i = 1; i <= n; i++)
        f[i] = (ll)t[i - 1] * g1_inv % p;
    return f;
}
```

1.1.10 多项式复合

问题 给出两个最高次数均为 x^n 的多项式 $F(x)$ 和 $G(x)$，求 $F(G(x))$ 的 $0\dots n$ 项系数。

首先要注意形式幂级数的复合只有在 $G(x)$ 没有常数项时才是良定义的，不然 $F(G(0))$ 不一定收敛。不过如果只是多项式复合就无所谓了。

做法 设 $H(x)=F(G(x))$，也就是

$$H(x)=\sum_{i=0}^{n} f_i G(x)^i$$

点积是不好做的，不过可以把 $F(x)$ 的系数反过来变成卷积。设 $r_i=f_{n-i}$，那么

$$\begin{aligned}H(x)&\equiv\sum_{i=0}^{n} r_{n-i}G(x)^i\\&\equiv\sum_{i=0}^{n} r_{n-i}\left[y^i\right]\frac{1}{1-yG(x)}\\&\equiv\left[y^n\right]\frac{R(y)}{1-yG(x)}\pmod{x^{n+1}}\end{aligned}$$

发现这个形式和多项式复合逆的子问题很像，不过这里要求的是 y^n 项的系数。仍然按照 Bostan-Mori 算法的思路，上下同乘 $Q(-x,y)$：

$$\begin{aligned}\left[y^n\right]\frac{R(y)}{Q(x,y)}&\equiv\left[y^n\right]\frac{R(y)}{Q(x,y)Q(-x,y)}Q(-x,y)\\&\equiv\left[y^n\right]\frac{R(y)}{V(x^2,y)}Q(-x,y)\pmod{x^{n+1}}\end{aligned}$$

那么 $\frac{R(y)}{V(x^2,y)}\pmod{x^{n+1}}$ 就变成了一个 x 的最高次数减半的子问题，这时后面的 $\pmod{x^{n+1}}$ 就用得上了。因为乘了一次所以 y 的最高次数会翻倍，一直递归到底才会达到 y^n。注意递归的时候 $R(y)$ 是完全不变的，因此为了保证复杂度需要先递归地做下去，返回的时候再乘 $Q(-x,y)$。边界是 $\frac{R(y)}{Q(x,y)}\equiv R(y)Q(0,y)^{-1}\pmod{x^1}$。

返回的时候 x 的最高次数要翻一倍，不需要处理，最多把超过当前层 n 的部分截掉就行了。而因为我们最终只需要 y^n 项，假设当前 $Q(-x,y)$ 的 y 次数是 2^k，那么当前层返回的结果的 y^i 项最多会影响到最终的第 $i+1+2+4+\cdots+2^{k-1}=i+2^k-1$ 项，因此每层只需要返回最高的 2^k 项。每层的总项数都是 $O(n)$ 的，总复杂度是 $O(n\log^2 n)$。

类似多项式复合逆，这里也有一个优化：在递归的时候 y 的最高次数是 2^k，项数就是 2^k+1，做卷积的时候会多做一倍。但可以注意到 $Q(x,y)$ 的 y_0 项始终是 1，所以可以把它提出来，这样项数就刚好是 2^k 了，每步按照 $(Ay+1)(By+1)=(ABy+A+B)y+1$ 计算即可。

这样优化的话，返回时会变成取一个 2^{k+1} 项多项式与一个 2^k 项多项式的乘积的较高 2^k 项。实际上按照循环卷积的原理，直接做长为 2^{k+1} 的 FFT 就行了，这时较高的 2^k 项在循环卷积下是不受影响的。另外因为返回时还涉及到 $\frac{R(y)}{V(x^2,y)}$ 的 FFT，因为 FFT 本质就是单位根处的点值，所以可以发现 x 这一维的 DFT 实际上就是 $\frac{R(y)}{V(x,y)}$ 的 DFT 再重复一次。这样返回时可以少做一半 FFT，减少一些常数。

代码里的 dft_2d 和 idft_2d 和多项式复合逆里的是一样的，去抄一下就行了。

```
// b.size() = n + 1
vector<poly> bostan_mori_comp(int n, const poly& a, vector<poly> b) {
    if (!n) { // a 的长度一定是最初的 n + 1
        int n0 = (int)a.size(), m = (int)b[0].size();

        b[0].insert(b[0].begin(), 1);
        b[0].resize(get_ntt_n(n0));
        poly b_inv = poly_inv(b[0]);
        b_inv.resize(a.size());

        poly t = poly_auto_mul(a, b_inv);
        poly res(m);
        for (int i = 0; i < n0; i++)
            res[i + m - n0] = t[i];

        return {res};
    }

    int ntt_n = get_ntt_n(n * 2 + 1);
    int m = (int)b[0].size();

    vector<poly> q = b;
    dft_2d(b, ntt_n, m * 2);

    vector<poly> c(ntt_n);
    for (int i = 0; i < ntt_n; i++) // Q(-x, y) 的 DFT 直接从 Q(x, y) 的 DFT 转化过来就行了
        c[i] = b[(i + ntt_n / 2) & (ntt_n - 1)];

    b.resize(ntt_n / 2);

    for (int i = 0; i < ntt_n / 2; i++)
        for (int j = 0; j < m * 2; j++)
            b[i][j] = (ll)b[i][j] * c[i][j] % p;

    idft_2d(b, n / 2 + 1, [] (int i) { return true; });

    for (int i = 0; i <= n / 2; i++) {
        for (int j = m * 2 - 1; j; j--)
            b[i][j] = b[i][j - 1];
        b[i][0] = 0;

        for (int j = 0; j < m; j++)
            b[i][j] = (b[i][j] + q[i * 2][j] * 2 % p) % p;
    }

    b.resize(n / 2 + 1);

    vector<poly> res = bostan_mori_comp(n / 2, a, move(b));

    vector<poly> t = res;
    dft_2d(t, ntt_n / 2, m * 2);

    for (int i = 0; i < ntt_n; i++) // 因为 V(x^2, y) 只有 x^2k 项，所以只需做一半
        for (int j = 0; j < m * 2; j++) // DFT 的后一半一定和前一半一样
            c[i][j] = (ll)t[i & (ntt_n / 2 - 1)][j] * c[i][j] % p;

    idft_2d(c, n + 1, [](int i) { return true; });

    t = vector<poly>(n + 1);
    for (int i = 0; i <= n; i++) {
        t[i].resize(m);

        for (int j = 0; j < m; j++)
```

```
            t[i][j] = c[i][j + m - 1];

        if (i % 2 == 0)
            for (int j = 0; j < m; j++)
                (t[i][j] += res[i / 2][j + m]) %= p;
    }

    return t;
}

// 求 F(G(x)), 长度要相同
poly poly_composition(const poly& f, const poly& g) {
    int n = (int)f.size() - 1;

    poly a(n + 1);
    for (int i = 0; i <= n; i++)
        a[i] = f[n - i];

    vector<poly> b(n + 1);
    for (int i = 0; i <= n; i++)
        b[i] = {(p - g[i]) % p};

    vector<poly> t = bostan_mori_comp(n, a, b);

    poly res(n + 1);
    for (int i = 0; i <= n; i++)
        res[i] = t[i][0];
    return res;
}
```

1.1.11 分治 FFT

```
void solve(int l,int r) {
    if (l == r)
        return;

    int mid = (l + r) / 2;

    solve(l, mid);

    int N = 1;
    while (N <= r - l + 1)
        N *= 2;

    for (int i = l; i <= mid; i++)
        B[i - l] = (long long)A[i] * fac_inv[i] % p;
    fill(B + mid - l + 1, B + N, 0);
    for (int i = 0; i < N; i++)
        C[i] = fac_inv[i];

    NTT(B, N, 1);
    NTT(C, N, 1);

    for (int i = 0; i < N; i++)
        B[i] = (long long)B[i] * C[i] % p;

    NTT(B, N, -1);

    for (int i = mid + 1; i <= r; i++)
        A[i] = (A[i] + B[i - l] * 2 % p * (long long)fac[i] % p) % p;

    solve(mid + 1, r);
}
```

1.1.12 半在线卷积

```
void solve(int l, int r) {
    if (r <= m)
        return;

    if (r - l == 1) {
        if (l == m)
            f[l] = a[m];
        else
            f[l] = (long long)f[l] * inv[l - m] % p;

        for (int i = l, t = (long long)l * f[l] % p; i <= n; i += l)
            g[i] = (g[i] + t) % p;

        return;
    }

    int mid = (l + r) / 2;

    solve(l, mid);

    if (l == 0) {
        for (int i = 1; i < mid; i++) {
            A[i] = f[i];
            B[i] = (c[i] + g[i]) % p;
        }
        NTT(A, r, 1);
        NTT(B, r, 1);
        for (int i = 0; i < r; i++)
            A[i] = (long long)A[i] * B[i] % p;
        NTT(A, r, -1);

        for (int i = mid; i < r; i++)
            f[i] = (f[i] + A[i]) % p;
    }
    else {
        for (int i = 0; i < r - l; i++)
            A[i] = f[i];
        for (int i = l; i < mid; i++)
            B[i - l] = (c[i] + g[i]) % p;
        NTT(A, r - l, 1);
        NTT(B, r - l, 1);
        for (int i = 0; i < r - l; i++)
            A[i] = (long long)A[i] * B[i] %p;
        NTT(A, r - l, -1);

        for (int i = mid; i < r; i++)
            f[i] = (f[i] + A[i - l]) % p;

        memset(A, 0, sizeof(int) * (r - l));
        memset(B, 0, sizeof(int) * (r - l));

        for (int i = l; i < mid; i++)
            A[i - l] = f[i];
        for (int i = 0; i < r - l; i++)
            B[i] = (c[i] + g[i]) % p;
        NTT(A, r - l, 1);
        NTT(B, r - l, 1);
        for (int i = 0; i < r - l; i++)
            A[i] = (long long)A[i] * B[i] % p;
        NTT(A, r - l, -1);

        for (int i = mid; i < r; i++)
            f[i] = (f[i] + A[i - l]) % p;
    }

    memset(A, 0, sizeof(int) * (r - l));
    memset(B, 0, sizeof(int) * (r - l));

    solve(mid, r);
}
```

1.1.13 生成函数计数原理

（待补充）

1.1.14 常用生成函数变换

$$\frac{x}{(1-x)^2}=\sum_{i\geq 0} ix^i$$

$$\frac{1}{(1-x)^k}=\sum_{i\geq 0}\binom{i+k-1}{i}x^i=\sum_{i\geq 0}\binom{i+k-1}{k-1}x^i,\ k>0$$

$$\begin{aligned}\sum_{i=0}^{\infty} i^n x^i &= \sum_{k=0}^{n}\left\{{n \atop k}\right\}k!\frac{x^k}{(1-x)^{k+1}}=\sum_{k=0}^{n}\left\{{n \atop k}\right\}k!\frac{x^k(1-x)^{n-k}}{(1-x)^{n+1}}\\ &= \frac{1}{(1-x)^{n+1}}\sum_{i=0}^{n}\frac{x^i}{(n-i)!}\sum_{k=0}^{i}\left\{{n \atop k}\right\}k!(n-k)!\frac{(-1)^{i-k}}{(i-k)!}\end{aligned}$$

(用上面的方法可以把分子化成一个 n 次以内的多项式，并且可以用一次卷积求出来。)
如果把 i^n 换成任意的一个 n 次多项式，那么我们可以求出它的下降幂表示形式（或者说是牛顿插值）的系数 r_i，发现用 r_k 替换掉上面的 $\left\{{n \atop k}\right\}k!$ 之后其余过程完全相同。

1.2 插值

1.2.1 牛顿插值

牛顿插值的原理是 **二项式反演**。
二项式反演

$$f(n)=\sum_{k=0}^{n}\binom{n}{k}g(k)\iff g(n)=\sum_{k=0}^{n}(-1)^{n-k}\binom{n}{k}f(k)$$

可以用 e^x 和 e^{-x} 的麦克劳林展开式证明。
套用二项式反演的结论即可得到牛顿插值：

$$f(n)=\sum_{i=0}^{k}\binom{n}{i}r_i,\ \text{where } r_i=\sum_{j=0}^{i}(-1)^{i-j}\binom{i}{j}f(j)$$

其中 k 表示 $f(n)$ 的最高次项系数。
实现时右边的式子等价于 k 次差分：

```
for (int i = 0; i <= k; i++)
    r[i] = f(i);
for (int j = 0; j < k; j++)
    for (int i = k; i > j; i--)
        r[i] -= r[i - 1];
```

注意到预处理 r_i 的式子满足卷积形式，必要时可以用 FFT 优化至 $O(k\log k)$。

1.2.2 Lagrange 插值

$$f(x)=\sum_i f(x_i)\prod_{j\neq i}\frac{x-x_j}{x_i-x_j}$$

快速插值参见 1.1.6.多项式快速插值（第 4 页）。

1.3 FWT

```
// 注意 FWT 常数比较小，这点与 FFT/NTT 不同
// 以下代码均以模质数情况为例，其中 n 为变换长度，t 表示正/逆变换

// 按位或版本
void FWT_or(int *A, int n, int t) {
    for (int k = 2; k <= n; k *= 2)
        for (int i = 0; i < n; i += k)
            for (int j = 0; j < k / 2; j++) {
                if (t > 0)
                    A[i + j + k / 2] = (A[i + j + k / 2] + A[i + j]) % p;
                else
                    A[i + j + k / 2] = (A[i + j + k / 2] - A[i + j] + p) % p;
            }
}

// 按位与版本
void FWT_and(int *A, int n, int t) {
    for (int k = 2; k <= n; k *= 2)
        for (int i = 0; i < n; i += k)
            for (int j = 0; j < k / 2; j++) {
                if (t > 0)
                    A[i + j] = (A[i + j] + A[i + j + k / 2]) % p;
                else
                    A[i + j] = (A[i + j] - A[i + j + k / 2] + p) % p;
            }
}

// 按位异或版本
void FWT_xor(int *A, int n, int t) {
    for (int k = 2; k <= n; k *= 2)
        for (int i = 0; i < n; i += k)
            for (int j = 0; j < k / 2; j++) {
                int a = A[i + j], b = A[i + j + k / 2];
                A[i + j] = (a + b) % p;
                A[i + j + k / 2] = (a - b + p) % p;
            }

    if (t < 0) {
        int inv = qpow(n % p, p - 2); // n 的逆元，在不取模时需要用每层除以 2 代替
        for (int i = 0; i < n; i++)
            A[i] = A[i] * inv % p;
    }
}
```

1.3.1 三行 FWT

```
void fwt_or(int *a, int n, int tp) {
    for (int j = 0; (1 << j) < n; j++)
        for (int i = 0; i < n; i++)
            if (i >> j & 1) {
                if (tp > 0)
                    a[i] += a[i ^ (1 << j)];
                else
                    a[i] -= a[i ^ (1 << j)];
            }
}

// and自然就是or反过来
void fwt_and(int *a, int n, int tp) {
    for (int j = 0; (1 << j) < n; j++)
        for (int i = 0; i < n; i++)
            if (!(i >> j & 1)) {
                if (tp > 0)
                    a[i] += a[i | (1 << j)];
                else
                    a[i] -= a[i | (1 << j)];
            }
}

// xor同理
```

1.4 线性代数

稀疏矩阵操作参见 1.6.Berlekamp-Massey 最小递推式（第 12 页）。

1.4.1 矩阵乘法

```
for (int i = 1; i <= n; i++)
    for (int k = 1; k <= n; k++)
        for (int j = 1; j <= n; j++)
            a[i][j] += b[i][k] * c[k][j];
// 通过改善内存访问连续性，显著提升速度
```

1.4.2 高斯消元

高斯-约当消元法 Gauss-Jordan 每次选取当前行绝对值最大的数作为代表元，在做浮点数消元时可以很好地保证精度。

```
void Gauss_Jordan(int A[][maxn], int n) {
    for (int i = 1; i <= n; i++) {
        int ii = i;
        for (int j = i + 1; j <= n; j++)
            if (fabs(A[j][i]) > fabs(A[ii][i]))
                ii = j;

        if (ii != i) // 这里没有判是否无解，如果有可能无解的话要判一下
            for (int j = i; j <= n + 1; j++)
                swap(A[i][j], A[ii][j]);

        for (int j = 1; j <= n; j++)
            if (j != i) // 消成对角
                for (int k = n + 1; k >= i; k--)
                    A[j][k] -= A[j][i] / A[i][i] * A[i][k];
    }
}
```

解线性方程组 在矩阵的右边加上一列表示系数即可，如果消成上三角的话最后要倒序回代。

求逆矩阵 维护一个矩阵 B，初始设为 n 阶单位矩阵。在消元的同时对 B 进行一样的操作，那么把 A 消成单位矩阵时 B 就是逆矩阵。

行列式 消成对角之后把代表元乘起来。如果是任意模数，要注意消元时每交换一次行列要取反一次。

1.4.3 行列式取模

```
int p;

int Gauss(int A[maxn][maxn], int n) {
    int det = 1;

    for (int i = 1; i <= n; i++) {
        for (int j = i + 1; j <= n; j++)
            while (A[j][i]) {
                int t = (p - A[i][i] / A[j][i]) % p;
                for (int k = i; k <= n; k++)
                    A[i][k] = (A[i][k] + (long long)A[j][k] * t) % p;

                swap(A[i], A[j]);
                det = (p - det) % p; // 交换一次之后行列式取负
            }

            if (!A[i][i])
                return 0;

            det = (long long)det * A[i][i] % p;
    }

    return det;
}
```

1.4.4 线性基（消成对角）

```
void add(unsigned long long x) {
    for (int i = 63; i >= 0; i--)
        if (x >> i & 1) {
            if (b[i])
                x ^= b[i];
            else {
                b[i] = x;

                for (int j = i - 1; j >= 0; j--)
                    if (b[j] && (b[i] >> j & 1))
                        b[i] ^= b[j];

                for (int j = i + 1; j < 64; j++)
                    if (b[j] >> i & 1)
                        b[j] ^= b[i];

                break;
            }
        }
}
```

1.4.5 线性代数知识

行列式

$$\det A = \sum_{\sigma} \operatorname{sgn}(\sigma) \prod_i a_{i,\sigma_i}$$

逆矩阵

$$B = A^{-1} \iff AB = 1$$

代数余子式

$$C_{i,j} = (-1)^{i+j} M_{i,j} = (-1)^{i+j} \left|A^{i,j}\right|$$

也就是 A 去掉一行一列之后的行列式。

伴随矩阵

$$A^* = C^T$$

即代数余子式矩阵的转置。
同时我们有

$$A^* = |A| A^{-1}$$

特征多项式

$$P_A(x) = \det(Ix - A)$$

特征根：特征多项式的所有 n 个根（可能有重根）。

1.4.6 矩阵树定理，BEST 定理

无向图 设图 G 的基尔霍夫矩阵 $L(G)$ 等于度数矩阵减去邻接矩阵，则 G 的生成树个数等于 $L(G)$ 的任意一个代数余子式的值。

有向图 类似地定义 $L_{in}(G)$ 等于 **入度** 矩阵减去邻接矩阵（i 指向 j 有边，则 $A_{i,j} = 1$），$L_{out}(G)$ 等于 **出度** 矩阵减去邻接矩阵。
则以 i 为根的内向树个数即为 L_{out} 的第 i 个主子式（关于第 i 行第 i 列的余子式），外向树个数即为 L_{in} 的第 i 个主子式。
（可以看出，只有无向图才满足 $L(G)$ 的所有代数余子式都相等。）

BEST定理（有向图欧拉回路计数） 如果 G 是有向欧拉图，则 G 的欧拉回路的个数等于以一个任意点为根的内/外向树个数乘以 $\prod_v (\deg(v) - 1)!$。
（在欧拉图里，无论以哪个结点为根，也无论内向树还是外向树，生成树数量都是一样的。）
另外无向图欧拉回路计数是挑战 NPC。

1.5 $O(k^2 \log n)$ 齐次线性递推

first 里面是第 1 到 k 项，trans 从低到高分别是 a_{n-1} 到 a_{n-k} 的系数。

```
struct LinearRecurrence {
    vector<int> first, trans;
    vector<vector<int> > bin;

    vector<int> multi(const vector<int> &a, const vector<int> &b) {
        int n = (int)a.size() - 1;

        vector<int> c(n * 2 + 1);

        for (int i = 0; i <= n; i++)
            for (int j = 0; j <= n; j++)
                c[i + j] = (c[i + j] + (long long)a[i] * b[j]) % p;

        for (int i = n * 2; i > n; i--) {
            for (int j = 0; j < n; j++)
                c[i - 1 - j] = (c[i - 1 - j] + (long long)c[i] * trans[j]) % p;

            c[i] = 0;
        }

        c.resize(n + 1);
        return c;
    }

    LinearRecurrence(vector<int> &first, vector<int> &trans) : first(first), trans(trans) {
        int n = (int)first.size();

        vector<int> a(n + 1);
        a[1] = 1;
        bin.push_back(a);

        for (int i = 1; i < 64; i++)
            bin.push_back(multi(bin[i - 1], bin[i - 1]));
    }

    int calc(long long k) {
        int n = (int)first.size();

        vector<int> a(n + 1);
        a[0] = 1;

        for (int i = 0; i < 64; i++)
            if (k >> i & 1)
                a = multi(a, bin[i]);

        int ans = 0;
        for (int i = 0; i < n; i++)
            ans = (ans + (long long)a[i + 1] * first[i]) % p;

        return ans;
    }
};
```

1.6 Berlekamp-Massey 最小递推式

如果要求出一个次数为 k 的递推式，则输入的数列需要至少有 $2k$ 项。
返回的内容满足 $\sum_{j=0}^{m-1} a_{i-j}c_j = 0$，并且 $c_0 = 1$。称为最小递推式。
如果不加最后的处理的话，代码返回的结果会变成 $a_i = \sum_{j=0}^{m-1} c_{j-1}a_{i-j}$，有时候这样会方便接着跑递推，需要的话就删掉最后的处理。
(实际上 Berlekamp-Massey 是对每个前缀都求出了递推式，不过一般用不到。)

```
vector<int> berlekamp_massey(const vector<int> &a) {
    vector<int> v, last; // v is the answer, 0-based
    int k = -1, delta = 0;

    for (int i = 0; i < (int)a.size(); i++) {

        int tmp = 0;
        for (int j = 0; j < (int)v.size(); j++)
            tmp = (tmp + (long long)a[i - j - 1] * v[j]) % p;

        if (a[i] == tmp)
            continue;

        if (k < 0) {
            k = i;
            delta = (a[i] - tmp + p) % p;
            v = vector<int>(i + 1);

            continue;
        }

        vector<int> u = v;
        int val = (long long)(a[i] - tmp + p) * qpow(delta, p - 2) % p;

        if (v.size() < last.size() + i - k)
            v.resize(last.size() + i - k);

        (v[i - k - 1] += val) %= p;

        for (int j = 0; j < (int)last.size(); j++) {
            v[i - k + j] = (v[i - k + j] - (long long)val * last[j]) % p;
            if (v[i - k + j] < 0)
                v[i - k + j] += p;
        }

        if ((int)u.size() - i < (int)last.size() - k) {
            last = u;
            k = i;
            delta = a[i] - tmp;
            if (delta < 0)
                delta += p;
        }
    }

    for (auto &x : v) // 一般是需要最小递推式的，所以处理一下
        x = (p - x) % p;
    v.insert(v.begin(), 1);

    return v; // $\forall i, \sum_{j=0}^{m} a_{i-j}v_j = 0$
}
```

如果要求向量序列的递推式，就乘一个随机行向量 $\boldsymbol{v}^T$（或者说是把每位乘一个随机权值）变成求数列递推式即可。
如果是矩阵序列的话就随机一个行向量 $\boldsymbol{u}^T$ 和列向量 $\boldsymbol{v}$，然后把矩阵变成 $\boldsymbol{u}^T A\boldsymbol{v}$ 的数列就行了。

1.6.1 优化矩阵快速幂DP

如果 $\boldsymbol{f_i}$ 是一个向量，并且转移是一个矩阵，那显然 $\{\boldsymbol{f_i}\}$ 是一个线性递推序列。
假设 $\boldsymbol{f_i}$ 有 n 维，先暴力求出 $\boldsymbol{f}_{0\ldots 2n-1}$，然后跑 Berlekamp-Massey，最后调用 1.1.8.快速线性递推 $O(k \log k \log n)$（第 5 页）即可。(快

速齐次线性递推的结果是一个序列，某个给定初值的结果就是点乘，所以只需要跑一次。)
如果要求 $\boldsymbol{f_m}$，并且矩阵有 k 个非零项的话，复杂度就是 $O(nk + n\log m\log n)$。(因为暴力求前 $2n-1$ 个 $\boldsymbol{f}_i$ 需要 $O(nk)$ 时间。)

1.6.2 求矩阵最小多项式

矩阵 A 的最小多项式是次数最小的并且 $f(A)=0$ 的多项式 f。
实际上最小多项式就是 $\{A^i\}$ 的最小递推式，所以直接调用 Berlekamp-Massey 就好了。显然它的次数不超过 n。
瓶颈在于求出 A^i，实际上我们只要处理 $A^i\boldsymbol{v}$ 就行了，每次对向量做递推。
设 A 有 k 个非零项，则复杂度为 $O(kn+n^2)$。

1.6.3 求稀疏矩阵的行列式

如果能求出特征多项式，则常数项乘上 $(-1)^n$ 就是行列式，但是最小多项式不一定就是特征多项式。
把 A 乘上一个随机对角阵 B（就是每行分别乘一个随机数），则 AB 的最小多项式有很大概率就是特征多项式，最后再除掉 $\det B$ 就行了。
设 A 有 k 个非零项，则复杂度为 $O(kn+n^2)$。

1.6.4 求稀疏矩阵的秩

设 A 是一个 $n\times m$ 的矩阵，首先随机一个 $n\times n$ 的对角阵 P 和一个 $m\times m$ 的对角阵 Q，然后计算 $QAPA^TQ$ 的最小多项式即可。
实际上不用计算这个矩阵，因为求最小多项式时要用它乘一个向量，我们依次把这几个矩阵乘到向量里就行了。答案就是最小多项式除掉所有 x 因子后剩下的次数。
设 A 有 k 个非零项，复杂度为 $O(kn+n^2)$。

1.6.5 解稀疏方程组

问题 $A\boldsymbol{x}=b$，其中 A 是一个 $n\times n$ 的 **满秩**稀疏矩阵，$\boldsymbol{b}$ 和 $\boldsymbol{x}$ 是 n 维 **列**向量，$A,\boldsymbol{b}$ 已知，需要解出 $\boldsymbol{x}$。
做法 显然 $\boldsymbol{x}=A^{-1}\boldsymbol{b}$。如果我们能求出 $\{A^i\boldsymbol{b}\}$ $(i\ge 0)$ 的最小递推式 $\{r_{0\ldots m-1}\}$ $(m\le n)$，那么就有结论

$$\boldsymbol{x}=A^{-1}\boldsymbol{b}=-\frac{1}{r_{m-1}}\sum_{i=0}^{m-2}r_{m-2-i}A^i\boldsymbol{b}$$

因为 A 是稀疏矩阵，直接按定义递推出 $\boldsymbol{b}\ldots A^{2n-1}\boldsymbol{b}$ 即可。设 A 中有 k 个非零项，则复杂度为 $O(kn+n^2)$。

```cpp
vector<int> solve_sparse_equations(const vector<tuple<int, int, int> > &A, const vector<int> &b) {
    int n = (int)b.size(); // 0-based

    vector<vector<int> > f({b});

    for (int i = 1; i < 2 * n; i++) {
        vector<int> v(n);
        auto &u = f.back();

        for (auto [x, y, z] : A) // [x, y, value]
            v[x] = (v[x] + (long long)u[y] * z) % p;

        f.push_back(v);
    }

    vector<int> w(n);
    mt19937 gen;
    for (auto &x : w)
        x = uniform_int_distribution<int>(1, p - 1)(gen);

    vector<int> a(2 * n);
    for (int i = 0; i < 2 * n; i++)
        for (int j = 0; j < n; j++)
            a[i] = (a[i] + (long long)f[i][j] * w[j]) % p;

    auto c = berlekamp_massey(a);
    int m = (int)c.size();

    vector<int> ans(n);

    for (int i = 0; i < m - 1; i++)
        for (int j = 0; j < n; j++)
            ans[j] = (ans[j] + (long long)c[m - 2 - i] * f[i][j]) % p;

    int inv = qpow(p - c[m - 1], p - 2);

    for (int i = 0; i < n; i++)
        ans[i] = (long long)ans[i] * inv % p;

    return ans;
}
```

1.7 线性规划

1.7.1 单纯形

```cpp
const double eps = 1e-10;

double A[maxn][maxn], x[maxn];
int n, m, t, id[maxn * 2];

// 方便起见，这里附上主函数
int main() {
    scanf("%d%d%d", &n, &m, &t);

    for (int i = 1; i <= n; i++) {
        scanf("%lf", &A[0][i]);
        id[i] = i;
    }

    for (int i = 1; i <= m; i++) {
        for (int j = 1; j <= n; j++)
            scanf("%lf", &A[i][j]);

        scanf("%lf", &A[i][0]);
    }

    if (!initalize())
        printf("Infeasible"); // 无解
    else if (!simplex())
        printf("Unbounded"); // 最优解无限大

    else {
        printf("%.15lf\n", -A[0][0]);
        if (t) {
            for (int i = 1; i <= m; i++)
                x[id[i + n]] = A[i][0];
            for (int i = 1; i <= n; i++)
                printf("%.15lf ",x[i]);
        }
    }
    return 0;
}

//初始化
//对于初始解可行的问题，可以把初始化省略掉
bool initalize() {
    while (true) {
        double t = 0.0;
        int l = 0, e = 0;
```

```
        for (int i = 1; i <= m; i++)
            if (A[i][0] + eps < t) {
                t = A[i][0];
                l = i;
            }

        if (!l)
            return true;

        for (int i = 1; i <= n; i++)
            if (A[l][i] < -eps && (!e || id[i] < id[e]))
                e = i;

        if (!e)
            return false;

        pivot(l, e);
    }
}

//求解
bool simplex() {
    while (true) {
        int l = 0, e = 0;
        for (int i = 1; i <= n; i++)
            if (A[0][i] > eps && (!e || id[i] < id[e]))
                e = i;

        if (!e)
            return true;

        double t = 1e50;
        for (int i = 1; i <= m; i++)
            if (A[i][e] > eps && A[i][0] / A[i][e] < t) {
                l = i;
                t = A[i][0]/A[i][e];
            }

        if (!l)
            return false;

        pivot(l, e);
    }
}

//转轴操作，本质是在凸包上沿着一条棱移动
void pivot(int l, int e) {
    swap(id[e], id[n + l]);
    double t = A[l][e];
    A[l][e] = 1.0;

    for (int i = 0; i <= n; i++)
        A[l][i] /= t;

    for (int i = 0; i <= m; i++)
        if (i != l) {
            t = A[i][e];
            A[i][e] = 0.0;
            for (int j = 0; j <= n; j++)
                A[i][j] -= t * A[l][j];
        }
}
```

1.7.2 线性规划对偶原理

给定一个原始线性规划:

$$\begin{aligned} \text{Minimize} \quad & \sum_{j=1}^{n} c_j x_j \\ \text{Subject to} \quad & \sum_{j=1}^{n} a_{ij} x_j \geq b_i, \\ & x_j \geq 0 \end{aligned}$$

定义它的对偶线性规划为:

$$\begin{aligned} \text{Maximize} \quad & \sum_{i=1}^{m} b_i y_i \\ \text{Subject to} \quad & \sum_{i=1}^{m} a_{ij} y_i \leq c_j, \\ & y_i \geq 0 \end{aligned}$$

用矩阵可以更形象地表示为:

$$\begin{aligned} \text{Minimize} \quad & c^T \boldsymbol{x} \\ \text{Subject to} \quad & A\boldsymbol{x} \geq \boldsymbol{b}, \\ & \boldsymbol{x} \geq 0 \end{aligned} \iff \begin{aligned} \text{Maximize} \quad & \boldsymbol{b}^T \boldsymbol{y} \\ \text{Subject to} \quad & A^T \boldsymbol{y} \leq \boldsymbol{c}, \\ & \boldsymbol{y} \geq 0 \end{aligned}$$

1.8 博弈论

1.8.1 SG 定理

对于一个 **平等** 游戏，可以为每个状态定义一个 SG 函数。
一个状态的 SG 函数等于所有它能一步到达的状态的 SG 函数的 mex，也就是最小的没有出现过的自然数。
那么所有先手必败态的 SG 函数为 0，先手必胜态的SG函数非 0。
如果有一个游戏，它由若干个独立的子游戏组成，且每次行动时 **只能选一个** 子游戏进行操作，则这个游戏的 SG 函数就是所有子游戏的SG函数的异或和。比如最经典的 Nim 游戏，每次只能选一堆取若干个石子。
同时操作多个子游戏的结论参见 1.8.3.经典博弈（第 14 页）。

1.8.2 纳什均衡

纯策略 混合策略 纯策略是指一定会选择某个选项，混合策略是指对每个选项都有一个概率分布 p_i，以相应的概率选择这个选项。
考虑这样的游戏：有几个人（当然可以是两个）各自独立地做决定，然后同时公布每个人的决定，而每个人的收益和所有人的选择有关。
那么纳什均衡就是每个人都决定一个混合策略，使得在其他人都是纯策略的情况下，这个人最坏情况下（也就是说其他人的纯策略最针对他的时候）的收益是最大的。也就是说，收益函数对这个人的混合策略求一个偏导，结果是 0（因为是极大值）。
纳什均衡点可能存在多个，不过在一个双人 **零和** 游戏中，纳什均衡点一定唯一存在。

1.8.3 经典博弈

1. **阶梯博弈**
台阶的每层都有一些石子，每次可以选一层（但不能是第 0 层），把任意个石子移到低一层。
结论 奇数层的石子数量进行异或和即可。
实际上只要路径长度唯一就可以，比如在树上博弈，然后石子向根节点方向移动，那么就是奇数深度的石子数量进行异或和。

2. **可以同时操作多个子游戏**
如果某个游戏由若干个独立的子游戏组成，并且每次可以 **任意选几个**（当然至少一个）子游戏进行操作，那么结论是：所有子游戏都必败时先手才会必败，否则先手必胜。

3. **每次最多操作 k 个子游戏 (Nim-K)**
如果每次最多操作 k 个子游戏，结论是：把所有子游戏的 SG 函数写成二进制表示，如果每一位上的 1 个数都是 $(k+1)$ 的倍数，则先手必败，否则先手必胜。

（实际上前一条可以看做 $k=\infty$ 的情况，也就是所有 SG 值都是 0 时才会先手必败。）
如果要求整个游戏的 SG 函数，就按照上面的方法每个二进制位相加后 $\mathrm{mod}(k+1)$，视为 $(k+1)$ 进制数求值即可。（**未验证**）

4. **反 Nim 游戏（Anti-Nim）**
和 Nim 游戏差不多，唯一的不同是取走最后一个石子的输。
分两种情况：

- 所有堆石子个数都是 1：有偶数堆时先手必胜，否则先手必败。
- 存在某个堆石子数多于 1：异或和不为 0 则先手必胜，否则先手必败。

当然石子个数实际上就是 SG 函数，所以判别条件全都改成 SG 函数也是一样的。（**未验证**）

5. **威佐夫博弈**
有两堆石子，每次要么从一堆中取任意个，要么从两堆中都取走相同数量。也等价于两个人移动一个只能向左上方走的皇后，不能动的输。
结论 设两堆石子分别有 a 个和 b 个，且 $a<b$，则先手必败当且仅当 $a=\left\lfloor (b-a)\frac{1+\sqrt{5}}{2}\right\rfloor$。

6. **删子树博弈**
有一棵有根树，两个人轮流操作，每次可以选一个点（除了根节点）然后把它的子树都删掉，不能操作的输。
结论
$$SG(u)=\mathrm{XOR}_{v\in son_u}\left(SG(v)+1\right)$$

7. **无向图游戏**
在一个无向图上的某个点上摆一个棋子，两个人轮流把棋子移动到相邻的点，并且每个点只能走一次，不能操作的输。
结论 如果某个点一定在最大匹配中，则先手必胜，否则先手必败。

1.8.4 例题

1. **黑白棋游戏**
一些棋子排成一列，棋子两面分别是黑色和白色。两个人轮流行动，每次可以选择一个白色朝上的棋子，把它和它左边的所有棋子都翻转，不能行动的输。
结论 只需要看最左边的棋子即可，因为每次操作最左边的棋子都一定会被翻转。
二维情况同理，如果每次是把左上角的棋子全部翻转，那么就只需要看左上角的那个棋子。

1.9 自适应 Simpson 积分

Copy-and-pasted from the template of *Nemesis*.

```cpp
// Adaptive Simpson's method : double simpson::solve (double (*f) (double), double l, double r, double eps) : integrates f over (l, r) with error eps.

double area (double (*f) (double), double l, double r) {
    double m = l + (r - l) / 2;
    return (f(l) + 4 * f(m) + f(r)) * (r - l) / 6;
}

double solve (double (*f) (double), double l, double r, double eps, double a) {
    double m = l + (r - l) / 2;
    double left = area(f, l, m), right = area(f, m, r);
    if (fabs(left + right - a) <= 15 * eps)
        return left + right + (left + right - a) / 15.0;
    return solve(f, l, m, eps / 2, left) + solve(f, m, r, eps / 2, right);
}

double solve (double (*f) (double), double l, double r, double eps) {
    return solve(f, l, r, eps, area (f, l, r));
}
```

1.10 常见数列

查表参见 8.15.OEIS（第 95 页）。

1.10.1 斐波那契数 Fibonacci 卢卡斯数

斐波那契数 $F_0=0,\ F_1=1,\ F_n=F_{n-1}+F_{n-2}$
$0,\ 1,\ 1,\ 2,\ 3,\ 5,\ 8,\ 13,\ 21,\ 34,\ 55,\ 89,\ \ldots$
卢卡斯数 $L_0=2,\ L_1=1$
$2,\ 1,\ 3,\ 4,\ 7,\ 11,\ 18,\ 29,\ 47,\ 76,\ 123,\ 199,\ \ldots$
通项公式 $\phi=\frac{1+\sqrt{5}}{2},\ \hat{\phi}=\frac{1-\sqrt{5}}{2}$
$F_n=\frac{\phi^n-\hat{\phi}^n}{\sqrt{5}},\ L_n=\phi^n+\hat{\phi}^n$
实际上有
$$\frac{L_n+F_n\sqrt{5}}{2}=\left(\frac{1+\sqrt{5}}{2}\right)^n$$
所以求通项的话写一个类然后快速幂就可以同时得到两者。
快速倍增法 $F_{2k}=F_k\left(2F_{k+1}-F_k\right),\ F_{2k+1}=F_{k+1}^2+F_k^2$

```cpp
pair<int, int> fib(int n) { // 返回F(n) 和F(n + 1)
    if (n == 0)
        return {0, 1};
    auto p = fib(n >> 1);
    int c = p.first * (2 * p.second - p.first);
    int d = p.first * p.first + p.second * p.second;
    if (n & 1)
        return {d, c + d};
    else
        return {c, d};
}
```

1.10.2 伯努利数

指数生成函数 $B(x)=\sum_{i\geq 0}\frac{B_i x^i}{i!}=\frac{x}{e^x-1}$

$$B_n=[n=0]-\sum_{i=0}^{n-1}\binom{n}{i}\frac{B_i}{n-k+1}$$

$$\sum_{i=0}^{n}\binom{n+1}{i}B_i=0$$

$$S_n(m)=\sum_{i=0}^{m-1}i^n=\sum_{i=0}^{n}\binom{n}{i}B_{n-i}\frac{m^{i+1}}{i+1}$$

$$B_0=1,\ B_1=-\frac{1}{2},\ B_4=-\frac{1}{30},\ B_6=\frac{1}{42},\ B_8=-\frac{1}{30},\ \ldots$$

（除了 $B_1=-\frac{1}{2}$ 以外，伯努利数的奇数项都是 0。）
自然数幂次和关于次数的 EGF：

$$\begin{aligned}F(x)&=\sum_{k=0}^{\infty}\frac{\sum_{i=0}^{n}i^k}{k!}x^k\\&=\sum_{i=0}^{n}e^{ix}\\&=\frac{e^{(n+1)x-1}}{e^x-1}\end{aligned}$$

1.10.3 分拆数

```
int b = sqrt(n);
ans[0] = tmp[0] = 1;

for (int i = 1; i <= b; ++i) {
    for (int rep = 0; rep < 2; ++rep)
        for (int j = i; j <= n - i * i; ++j)
            add(tmp[j], tmp[j - i]);

    for (int j = i * i; j <= n; ++j)
        add(ans[j], tmp[j - i * i]);
}

// -----

long long a[100010];
long long p[50005]; // 欧拉五边形数定理

int main() {
    p[0] = 1;
    p[1] = 1;
    p[2] = 2;
    int i;
    for (i = 1; i < 50005; i++) { // 递推式系数1,2,5,7,12,15,22,26 ... i*(3*i-1)/2,i*(3*i+1)/2
        a[2 * i] = i * (i * 3 - 1) / 2; // 五边形数为1,5,12,22 ... i*(3*i-1)/2
        a[2 * i + 1] = i * (i * 3 + 1) / 2;
    }
    for (i = 3; i < 50005; i++) { // p[n]=p[n-1]+p[n-2]-p[n-5]-p[n-7]+p[12]+p[15]- ... +p[n-i*[3i-1]/2]+p[n-i*[3i+1]/2]
        p[i] = 0;
        int j;
        for (j = 2; a[j] <= i; j++) { //有可能为负数，式中加1000007
            if (j & 2)
                p[i] = (p[i] + p[i - a[j]] + 1000007) % 1000007;
            else
                p[i] = (p[i] - p[i - a[j]] + 1000007) % 1000007;
        }
    }
    int n;
    while (~scanf("%d", &n))
        printf("%lld\n", p[n]);
}
```

1.10.4 斯特林数

1. **第一类斯特林数**

$\left[{n \atop k}\right]$ 表示 n 个元素划分成 k 个 **轮换** 的方案数。

递推式 $\left[{n \atop k}\right] = \left[{n-1 \atop k-1}\right] + (n-1)\left[{n-1 \atop k}\right]$

求同一行 分治 FFT $O(n\log^2 n)$，或者倍增 $O(n\log n)$（每次都是 $f(x) = g(x)g(x+d)$ 的形式）。

$$\sum_{k=0}^{n}\left[{n \atop k}\right]x^k = \prod_{i=0}^{n-1}(x+i)$$

求同一列 用一个轮换的 EGF 做 k 次幂。

$$\sum_{n=0}^{\infty}\left[{n \atop k}\right]\frac{x^n}{n!} = \frac{(\ln(1-x))^k}{k!} = \frac{x^k}{k!}\left(\frac{\ln(1-x)}{x}\right)^k$$

2. **第二类斯特林数**

$\left\{{n \atop k}\right\}$ 表示 n 个元素划分成 k 个子集的方案数。

递推式 $\left\{{n \atop k}\right\} = \left\{{n-1 \atop k-1}\right\} + k\left\{{n-1 \atop k}\right\}$

求某一项 容斥，狗都会做。

$$\left\{{n \atop k}\right\} = \frac{1}{k!}\sum_{i=0}^{k}(-1)^i\binom{k}{i}(k-i)^n = \sum_{i=0}^{k}\frac{(-1)^i}{i!}\frac{(k-i)^n}{(k-i)!}$$

求同一行 FFT，狗都会做。

求同一列 EGF：

$$\sum_{n=0}^{\infty}\left\{{n \atop k}\right\}\frac{x^n}{n!} = \frac{(e^x-1)^k}{k!} = \frac{x^k}{k!}\left(\frac{e^x-1}{x}\right)^k$$

OGF：

$$\sum_{n=0}^{\infty}\left\{{n \atop k}\right\}x^n = x^k\left(\prod_{i=1}^{k}(1-ix)\right)^{-1}$$

3. **斯特林反演**

$$f(n) = \sum_{k=0}^{n}\left\{{n \atop k}\right\}g(k) \iff g(n) = \sum_{k=0}^{n}(-1)^{n-k}\left[{n \atop k}\right]f(k)$$

4. **幂的转换**

上升幂与普通幂的转换

$$x^{\overline{n}} = \sum_k\left[{n \atop k}\right]x^k$$

$$x^n = \sum_k\left\{{n \atop k}\right\}(-1)^{n-k}x^{\overline{k}}$$

下降幂与普通幂的转换

$$x^n = \sum_k\left\{{n \atop k}\right\}x^{\underline{k}} = \sum_k\binom{x}{k}\left\{{n \atop k}\right\}k!$$

$$x^{\underline{n}} = \sum_k\left[{n \atop k}\right](-1)^{n-k}x^k$$

另外，多项式的 **点值** 表示的每项除以阶乘，卷上 e^{-x} 再乘上阶乘之后是 **牛顿插值** 表示，或者不乘阶乘就是 **下降幂** 系数表示。反过来的转换当然卷上 e^x 就行了。原理是每次差分等价于乘以 $(1-x)$，展开之后用一次卷积取代多次差分。（参见 1.2.1.牛顿插值（第 10 页）。）

5. **斯特林多项式（斯特林数关于斜线的性质）**

定义

$$\sigma_n(x) = \frac{\left[{x \atop n}\right]}{x(x-1)\dots(x-n)}$$

$\sigma_n(x)$ 的最高次数是 x^{n-1}。（所以作为唯一的特例，$\sigma_0(x) = \frac{1}{x}$ 不是多项式。）

斯特林多项式实际上非常神奇，它与两类斯特林数都有关系：

$$\left[{n \atop n-k}\right] = n^{\underline{k+1}}\sigma_k(n)$$

$$\left\{{n \atop n-k}\right\} = (-1)^{k+1}n^{\underline{k+1}}\sigma_k(-(n-k))$$

不过它并不好求。可以 $O(k^2)$ 直接计算前几个点值然后插值，或者如果要推式子的话，可以用后面提到的二阶欧拉数（1.10.6.欧拉数 Eulerian（第 17 页））。

1.10.5 贝尔数

$$B_0 = 1,\ B_1 = 1,\ B_2 = 2,\ B_3 = 5,$$
$$B_4 = 15,\ B_5 = 52,\ B_6 = 203, \ldots$$

$$B_n = \sum_{k=0}^{n} \left\{ {n \atop k} \right\}$$

递推式

$$B_{n+1} = \sum_{k=0}^{n} \binom{n}{k} B_k$$

指数生成函数 $B(x) = e^{e^x - 1}$

Touchard 同余 如果 p 是素数，那么：

$$B_{n+p^m} \equiv (mB_n + B_{n+1}) \pmod p$$

1.10.6 欧拉数

1. **欧拉数**

$\left\langle {n \atop k} \right\rangle$ 表示 n 个数的排列，有 k 个上升的方案数。

$$\left\langle {n \atop k} \right\rangle = (n-k)\left\langle {n-1 \atop k-1} \right\rangle + (k+1)\left\langle {n-1 \atop k} \right\rangle$$

$$\left\langle {n \atop k} \right\rangle = \sum_{i=0}^{k+1} (-1)^i \binom{n+1}{i} (k+1-i)^n$$

$$\sum_{k=0}^{n-1} \left\langle {n \atop k} \right\rangle = n!$$

$$x^n = \sum_{k=0}^{n-1} \left\langle {n \atop k} \right\rangle \binom{x+k}{n}$$

$$k! \left\{ {n \atop k} \right\} = \sum_{i=0}^{n-1} \left\langle {n \atop i} \right\rangle \binom{i}{n-k}$$

2. **二阶欧拉数**

$\left\langle\!\left\langle {n \atop k} \right\rangle\!\right\rangle$ 表示每个数都出现 **两次** 的多重排列，并且每个数两次出现之间的数都比它要大。在此前提下有 k 个上升的方案数。

$$\left\langle\!\left\langle {n \atop k} \right\rangle\!\right\rangle = (2n-k-1)\left\langle\!\left\langle {n-1 \atop k-1} \right\rangle\!\right\rangle + (k+1)\left\langle\!\left\langle {n-1 \atop k} \right\rangle\!\right\rangle$$

$$\sum_{k=0}^{n-1} \left\langle\!\left\langle {n \atop k} \right\rangle\!\right\rangle = (2n-1)!! = \frac{(2n)^{\underline{n}}}{2^n}$$

3. **二阶欧拉数与斯特林数的关系**

$$\left\{ {x \atop x-n} \right\} = \sum_{k=0}^{n-1} \left\langle\!\left\langle {n \atop k} \right\rangle\!\right\rangle \binom{x+n-k-1}{2n}$$

$$\left[{x \atop x-n} \right] = \sum_{k=0}^{n-1} \left\langle\!\left\langle {n \atop k} \right\rangle\!\right\rangle \binom{x+k}{2n}$$

1.10.7 卡特兰数 施罗德数 默慈金数

1. **卡特兰数**

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n-1}$$

- n 个元素按顺序入栈，出栈序列方案数
- n 对括号的合法括号序列数
- $n+1$ 个叶子的满二叉树个数

递推式

$$C_n = \sum_{i=0}^{n-1} C_i C_{n-i-1} = C_{n-1}\frac{4n-2}{n+1}$$

普通生成函数 $C(x) = \frac{1-\sqrt{1-4x}}{2x}$

扩展 如果有 n 个（和 m 个），方案数为 $\binom{n+m}{n} - \binom{n+m}{m-1}$。

2. **施罗德数**

$$S_n = S_{n-1} + \sum_{i=0}^{n-1} S_i S_{n-i-1}$$

$$(n+1)s_n = (6n-3)s_{n-1} - (n-2)s_{n-2}$$

其中 S_n 是（大）施罗德数，s_n 是小施罗德数（也叫超级卡特兰数）。除了 $S_0 = s_0 = 1$ 以外，都有 $S_i = 2s_i$。
施罗德数的组合意义：

- 从 $(0,0)$ 走到 (n,n)，每次可以走右、上或者右上一步，并且不能超过 $y = x$ 这条线的方案数
- 可以有空位，并且括号对数和空位置数加起来等于 n 的合法括号序列数
- 凸 n 边形的 **任意** 剖分方案数

（有些人会把大（而不是小）施罗德数叫做超级卡特兰数。）

3. **默慈金数**

$$M_{n+1} = M_n + \sum_{i=0}^{n-1} M_i M_{n-1-i} = \frac{(2n+3)M_n + 3nM_{n-1}}{n+3}$$

$$M_n = \sum_{i=0}^{\frac{n}{2}} \binom{n}{2i} C_i$$

- 从 $(0,0)$ 走到 $(n,0)$，每次可以走右上、右下或者正右方一步，且不能走到 $y < 0$ 的位置的方案数
- 可以有空位，长为 n 的合法括号序列数
- 在圆上的 n 个 **不同的** 点之间画任意条不相交（**包括端点**）的弦的方案数

扩展 默慈金数画的弦不可以共享端点。如果可以共享端点的话是 A054726，参见 8.15.OEIS（第 95 页）。

1.11 常用公式及结论

1.11.1 方差

m 个数的方差：

$$s^2 = \frac{\sum_{i=1}^{m} x_i^2}{m} - \overline{x}^2$$

随机变量的方差：$D^2(x) = E(x^2) - E^2(x)$

1.11.2 min-max 反演

$$\max(S) = \sum_{T \subset S} (-1)^{|T|+1} \min(T)$$
$$\min(S) = \sum_{T \subset S} (-1)^{|T|+1} \max(T)$$

推广 求第 k 大：

$$k\text{-}\max(S) = \sum_{T \subset S} (-1)^{|T|-k} \binom{|T|-1}{k-1} \min(T)$$

显然只有大小至少为 k 的子集会被枚举到。

1.11.3 单位根反演（展开整除条件 $[k|n]$）

$$[k|n] = \frac{1}{k}\sum_{i=0}^{k-1}\omega_k^{in}$$

$$\sum_{i\geq 0}[x^{ik}]f(x) = \frac{1}{k}\sum_{j=0}^{k-1}f(\omega_k^j)$$

如果要求 $k \equiv r \bmod n$，就等价于 $[k|(n-r)]$，类似地推导一下即可。

1.11.4 康托展开

求排列的排名 先对每个数都求出它后面有几个数比它小（可以用树状数组），记为 c_i，则排列的排名就是

$$\sum_{i=1}^{n} c_i(n-i)!$$

已知排名构造排列 从前到后先分别求出 c_i，有了 c_i 之后再用一个平衡树（需要维护排名）倒序处理即可。

1.11.5 常系数齐次线性递推求通项

- **定理3.1:** 设数列$\{u_n : n \geq 0\}$ 满足r 阶齐次线性常系数递推关系$u_n = \sum_{j=1}^{r} c_j u_{n-j}$ $(n \geq r)$. 则

  $(i).$ $$U(x) = \sum_{n\geq 0} u_n x^n = \frac{h(x)}{1-\sum_{j=1}^{r} c_j x^j}, \quad deg(h(x)) < r.$$

  (ii). 若特征多项式

  $$c(x) = x^r - \sum_{j=1}^{r} c_j x^{r-j} = (x-\alpha_1)^{e_1}\cdots(x-\alpha_s)^{e_s},$$

  其中$\alpha_1, \cdots, \alpha_s$ 互异，$e_1 + \cdots + e_s = r$ 则u_n 有表达式

  $$u_n = p_1(n)\alpha_1^n + \cdots + p_s(n)\alpha_s^n, \quad deg(p_i) < e_i, i = 1, \cdots, s.$$

  多项式$p_1, \cdots, p_s$ 的共$e_1 + \cdots + e_s = r$ 个系数可由初始值$u_0, \cdots, u_{r-1}$ 唯一确定。

2 数论

2.1 $O(n)$ 预处理逆元

$$i^{-1} = -\frac{p}{i}(p \bmod i)^{-1},\ p \in \mathbb{P}$$

```
inv[1] = 1; // 如果 p 是素数，那 p % i 必不可能是 0
for (int i = 2; i <= n; i++)
    inv[i] = (long long)(p - (p / i)) * inv[p % i] % p;
```

2.2 线性筛

适用于任何 $f(p^k)$ 便于计算的 **积性** 函数。
代码里的例子是求约数之和 $\sigma_1(n)$，mod 10^9+7。

```
constexpr int p = 1000000007;

int prime[MAXN / 10], sigma_one[MAXN], f[MAXN], g[MAXN];
// f: 除掉最小质因子后剩下的部分
// g: 最小质因子的幂次，在 f(p^k) 比较复杂时很有用，但 f(p^k) 可以递推时就可以省略了
// 这里没有记录最小质因子，但根据线性筛的性质，每个合数只会被它最小的质因子筛掉
bool notp[MAXN]; // 顾名思义

void get_table(int n) {
    sigma_one[1] = 1; // 积性函数必有f(1) = 1
    for (int i = 2; i <= n; i++) {
        if (!notp[i]) { // 质数情况
            prime[++prime[0]] = i;
            sigma_one[i] = i + 1;
            f[i] = g[i] = 1;
        }

        for (int j = 1; j <= prime[0] && i * prime[j] <= n; j++) {
            notp[i * prime[j]] = true;

            if (i % prime[j]) { // 加入一个新的质因子，这种情况很简单
                sigma_one[i * prime[j]] = (long long)sigma_one[i] * (prime[j] + 1) % p;
                f[i * prime[j]] = i;
                g[i * prime[j]] = 1;
            }
            else { // 再加入一次最小质因子，需要再进行分类讨论
                f[i * prime[j]] = f[i];
                g[i * prime[j]] = g[i] + 1;
                // 对于 f(p^k) 可以直接递推的函数，这里的判断可以改成
                // i / prime[j] % prime[j] != 0, 这样可以省下 f[] 的空间，
                // 但常数很可能会稍大一些

                if (f[i] == 1) // 质数的幂次，这里 σ1 可以递推
                    sigma_one[i * prime[j]] = (sigma_one[i] + i * prime[j]) % p;
                    // 对于更一般的情况，可以借助 g[] 计算 f(p^k)
                else sigma_one[i * prime[j]] = // 否则直接利用积性，两半乘起来
                    (long long)sigma_one[i * prime[j] / f[i]] * sigma_one[f[i]] % p;
                break;
            }
        }
    }
}
```

2.3 杜教筛

$$S_\varphi(n) = \frac{n(n+1)}{2} - \sum_{d=2}^{n} S_\varphi\left(\left\lfloor \frac{n}{d} \right\rfloor\right)$$

$$S_\mu(n) = 1 - \sum_{d=2}^{n} S_\mu\left(\left\lfloor \frac{n}{d} \right\rfloor\right)$$

```
// 用于求可以用狄利克雷卷积构造出好求和的东西的函数的前缀和（有点绕）
// 有些题只要求n <= 10 ^ 9, 这时就没必要开long long了，但记得乘法时强转

//常量/全局变量/数组定义
const int maxn = 5000005, table_size = 5000000, p = 1000000007, inv_2 = (p + 1) / 2;
bool notp[maxn];
int prime[maxn / 20], phi[maxn], tbl[100005];
// tbl用来顶替哈希表，其实开到n ^ {1 / 3} 就够了，不过保险起见开成\sqrt n比较好
long long N;

// 主函数前面加上这么一句
memset(tbl, -1, sizeof(tbl));

// 线性筛预处理部分略去

// 杜教筛主过程 总计O(n ^ {2 / 3})
// 递归调用自身
// 递推式还需具体情况具体分析，这里以求欧拉函数前缀和(mod 10 ^ 9 + 7) 为例
int S(long long n) {
    if (n <= table_size)
        return phi[n];
    else if (~tbl[N / n])
        return tbl[N / n];
    // 原理：n除以所有可能的数的结果一定互不相同

    int ans = 0;
    for (long long i = 2, last; i <= n; i = last + 1) {
        last = n / (n / i);
        ans = (ans + (last - i + 1) % p * S(n / i)) % p; // 如果n是int范围的话记得强转
    }

    ans = (n % p * ((n + 1) % p) % p * inv_2 - ans + p) % p; // 同上
    return tbl[N / n] = ans;
}
```

2.4 Powerful Number 筛

注意 Powerful Number 筛只能求一些 **特殊** 的 **积性函数** 的前缀和。本质上就是构造一个方便求前缀和的函数，然后做类似杜教筛的操作。
定义 Powerful Number 表示每个质因子幂次都大于 1 的数，显然最多有 $\sqrt{n}$ 个。
设我们要求和的函数是 $f(n)$，构造一个 方便求前缀和的 **积性** 函数 $g(n)$ 使得 $g(p) = f(p)$。
那么就存在一个积性函数 $h = f * g^{-1}$，也就是 $f = g * h$。可以证明 $h(p) = 0$，所以只有 Powerful Number 的 h 值不为 0。

$$_f(i) = \sum_{d=1}^{n} h(d) S_g\left(\left\lfloor \frac{n}{d} \right\rfloor\right)$$

只需要枚举每个 Powerful Number 作为 d，然后用杜教筛计算 g 的前缀和即可。
求 $h(d)$ 时要先预处理 $h(p^k)$，显然有

$$h\left(p^k\right)=f\left(p^k\right)-\sum_{i=1}^{k} g\left(p^i\right) h\left(p^{k-i}\right)$$

处理完之后 DFS 就行了。(显然只需要筛 $\sqrt{n}$ 以内的质数。)
复杂度取决于杜教筛的复杂度，特殊题目构造的好也可以做到 $O(\sqrt{n})$。
例题:

- $f\left(p^k\right)=p^k\left(p^k-1\right)$: $g(n)=\mathrm{id}(n)\varphi(n)$。
- $f\left(p^k\right)=p \operatorname{xor} k$: n 为偶数时 $g(n)=3\varphi(n)$，否则 $g(n)=\varphi(n)$。

2.5 洲阁筛

(比较难写，不建议用。最好用后面的 min25 筛。)
计算 **积性函数** $f(n)$ 的前 n 项之和时，我们可以把所有项按照是否有 $>\sqrt{n}$ 的质因子分两类讨论，最后将两部分的贡献加起来即可。

1. **有 $>\sqrt{n}$ 的质因子**
显然 $>\sqrt{n}$ 的质因子幂次最多为 1，所以这一部分的贡献就是

$$\sum_{i=1}^{\sqrt{n}} f(i) \sum_{d=\sqrt{n}+1}^{\left\lfloor \frac{n}{i} \right\rfloor}[d \in \mathbb{P}] f(d)$$

我们可以 DP 后面的和式。由于 $f(p)$ 是一个关于 p 的低次多项式，我们可以对每个次数分别 DP：设 $g_{i,j}$ 表示 $[1,j]$ 中和前 i 个质数都互质的数的 k 次方之和。设 $\sqrt{n}$ 以内的质数总共有 m 个，显然贡献就转换成了

$$\sum_{i=1}^{\sqrt{n}} i^k g_{m,\left\lfloor \frac{n}{i} \right\rfloor}$$

边界显然就是自然数幂次和，转移是

$$g_{i,j}=g_{i-1,j}-p_i^k g_{i-1,\left\lfloor \frac{j}{p_i} \right\rfloor}$$

也就是减掉和第 i 个质数不互质的贡献。
在滚动数组的基础上再优化一下：首先如果 $j<p_i$ 那肯定就只有 1 一个数；另外，如果 $p_i \le j<p_i^2$，显然就有 $g_{i,j}=g_{i-1,j}-p_i^k$。所以对每个 j 记下最大的 i 使得 $p_i^2 \le j$，那么比这个还大的情况就不需要递推了，用到的时候再加上一个前缀和即可。

2. **所有质因子都 $\le \sqrt{n}$**
类似的道理，我们继续 DP：$h_{i,j}$ 表示只含有第 i 到 m ($m=\pi(\sqrt{n})$) 个质数作为质因子的所有数的 $f(i)$ 之和。(这里不需要对每个次幂单独 DP 了，另外倒着 DP 是为了方便卡上限。)
边界显然是 $h_{m+1,j}=1$，转移是

$$h_{i,j}=h_{i+1,j}+\sum_c f(p_i^c) h_{i+1,\left\lfloor \frac{j}{p_i^c} \right\rfloor}$$

跟上面一样的道理优化，分成三段: $j<p_i$ 时 $h_{i,j}=1$；$j<p_i^2$ 时 $h_{i,j}=h_{i+1,j}+f(p_i)$ (同样用前缀和解决)；再小的部分就老实递推。

预处理 $\sqrt{n}$ 以内的部分之后跑两次DP，最后把两部分的贡献加起来就行了。两部分的复杂度都是 $\Theta\left(\frac{n^{\frac{3}{4}}}{\log n}\right)$。
以下代码以洛谷 P5325 ($f(p^k)=p^k(p^k-1)$) 为例。

```cpp
constexpr int MAXN = 200005, p = 1000000007;

long long N, divs[MAXN]; // 询问的 n 和存储所有整除结果的表
int sqrtn;

inline int getid(long long x) {
    if (x <= sqrtn)
        return x;

    return divs[0] - N / x + 1;
}

bool notp[MAXN];
int prime[MAXN], prime_cnt, rem[MAXN]; // 线性筛用数组

int f[MAXN], pr[MAXN], g[2][MAXN], dp[MAXN];
int l[MAXN], r[MAXN];

// 线性筛省略

inline int get_sum(long long n, int k) {
    n %= p;

    if (k == 1)
        return n * (n + 1) % p * ((p + 1) / 2) % p;

    else
        return n * (n + 1) % p * (2 * n + 1) % p * ((p + 1) / 6) % p;
}

void get_dp(long long n, int k, int *dp) {
    for (int j = 1; j <= divs[0]; j++)
        dp[j] = get_sum(divs[j], k);

    for (int i = 1; i <= prime_cnt; i++) {
        long long lb = (long long)prime[i] * prime[i];
        int pw = (k == 1 ? prime[i] : (int)(lb % p));

        pr[i] = (pr[i - 1] + pw) % p;

        for (int j = divs[0]; j && divs[j] >= lb; j--) {
            int t = getid(divs[j] / prime[i]);

            int tmp = dp[t];
            if (l[t] < i)
                tmp = (tmp - pr[min(i - 1, r[t])] + pr[l[t]]) % p;

            dp[j] = (dp[j] - (long long)pw * tmp) % p;
            if (dp[j] < 0)
                dp[j] += p;
        }
    }

    for (int j = 1; j <= divs[0]; j++) {
        dp[j] = (dp[j] - pr[r[j]] + pr[l[j]]) % p;

        dp[j] = (dp[j] + p - 1) % p; // 因为DP数组是有1的，但后面计算不应该有1
    }
}

int calc1(long long n) {
    get_dp(n, 1, g[0]);
    get_dp(n, 2, g[1]);

    int ans = 0;

    for (int i = 1; i <= sqrtn; i++)
        ans = (ans + (long long)f[i] * (g[1][getid(N / i)] - g[0][getid(N / i)])) % p;

    if (ans < 0)
        ans += p;
```

```cpp

    return ans;
}

int calc2(long long n) {
    for (int j = 1; j <= divs[0]; j++)
        dp[j] = 1;

    for (int i = 1; i <= prime_cnt; i++)
        pr[i] = (pr[i - 1] + f[prime[i]]) % p;

    for (int i = prime_cnt; i; i--) {
        long long lb = (long long)prime[i] * prime[i];

        for (int j = divs[0]; j && divs[j] >= lb; j--)
            for (long long pc = prime[i]; pc <= divs[j]; pc *= prime[i]) {
                int t = getid(divs[j] / pc);

                int tmp = dp[t];
                if (r[t] > i)
                    tmp = (tmp + pr[r[t]] - pr[max(i, l[t])]) % p;

                dp[j] = (dp[j] + pc % p * ((pc - 1) % p) % p * tmp) % p;
            }
    }

    return (long long)(dp[divs[0]] + pr[r[divs[0]]] - pr[l[divs[0]]] + p) % p;
}

int main() {
    // ios::sync_with_stdio(false);

    cin >> N;

    sqrtn = (int)sqrt(N);

    get_table(sqrtn);

    for (int i = 1; i <= sqrtn; i++)
        divs[++divs[0]] = i;

    for (int i = 1; i <= sqrtn; i++)
        divs[++divs[0]] = N / i;

    sort(divs + 1, divs + divs[0] + 1);

    divs[0] = unique(divs + 1, divs + divs[0] + 1) - divs - 1;

    int li = 0, ri = 0;
    for (int j = 1; j <= divs[0]; j++) {
        while (ri < prime_cnt && prime[ri + 1] <= divs[j])
            ri++;

        while (li <= prime_cnt && (long long)prime[li] * prime[li] <= divs[j])
            li++;

        l[j] = li - 1;
        r[j] = ri;
    }

    cout << (calc1(N) + calc2(N)) % p << endl;

    return 0;
}
```

2.6 min25 筛

问题仍然是计算 **积性函数** $f(n)$ 的前 n 项和。
设 $\sqrt{n}$ 以内的质数为 $p_1 \dots p_{\pi(\sqrt{n})}$，记

$$g(n) = \sum_{i=1}^{n} [i \in \mathbb{P}]\, f(i)$$

也就是只考虑质数项的和。
为了方便求出 g，构造一个多项式函数 $F(x) = \sum a_i x^i$，满足 $F(p) = f(p)$，这样每个次数就可以分开算贡献。（$f(p^c)$ 的形式是无所谓的，只需要能直接求就行。）
再令

$$h_k(i,n) = \sum_{x=2}^{n} [x \in \mathbb{P} \text{ 或 } x \text{ 与前 } i \text{ 个质数互质}]\, x^k$$

显然 $g(n) = \sum_k a_k h_k\left(\pi\left(\sqrt{n}\right), n\right)$，递推求出所有 h_k 即可得到 g。
考虑 h 的转移，当 $p_i > \sqrt{n}$ 时显然有 $h_k(i,n) = h_k(i-1,n)$，否则有

$$h_k(i,n) = h_k(i-1,n) - p_i^k h_k\left(i-1, \left\lfloor \frac{n}{p_i} \right\rfloor\right) + p_i^k \sum_{j=1}^{i-1} p_j^k$$

边界为 $h_k(0,n) = \sum_{i=2}^{n} i^k$。
求出 g 之后，为了得到所有 $f(i)$ 之和还需要一次递推。设

$$S(i,n) = \sum_{k=2}^{n} [k \text{ 与前 } (i-1) \text{ 个质数互质}]\, f(k)$$

则

$$\begin{aligned} S(i,n) =& g(n) - \sum_{k=1}^{i-1} f(p_k) \\ &+ \sum_{k=i}^{p_k \le \sqrt{n}} \sum_{c=1}^{p_k^{c+1} \le n} \left(S\left(k+1, \left\lfloor \frac{n}{p_k^c} \right\rfloor\right) f\left(p_k^c\right) + f\left(p_k^{c+1}\right) \right) \end{aligned}$$

这里直接递归即可，注意边界应设为 $p_i > n$ 或 $n < 1$ 时 $S(i,n) = 0$。最后的答案即为 $\text{ans} = S(1,n) + f(1)$。
也可以从大到小枚举 i 递推，考虑到只有 $p_i \le \sqrt{n}$ 时才有递推，可以后缀和优化。不优化的复杂度是 $O(n^{1-\epsilon})$，优化之后是 $O\left(\frac{n^{\frac{3}{4}}}{\log n}\right)$，不过一般是不优化更快。

```cpp
constexpr int MAXN = 200005, p = (int)1e9 + 7;

bool notp[MAXN];
int prime[MAXN / 5], prime_cnt;

// 线性筛省略

long long divs[MAXN]; // n 的所有整除结果
int sqrtn;

void get_divs(long long n) {
    for (int i = 1; i <= sqrtn; i++)
        divs[++divs[0]] = i;

    for (int i = sqrtn; i; i--)
        divs[++divs[0]] = n / i;

    assert(is_sorted(divs + 1, divs + divs[0] + 1));
    divs[0] = unique(divs + 1, divs + divs[0] + 1) - divs - 1;
```

```cpp
}

int getid(long long x) { // divs[divs[0]] 就是 n
    return x <= sqrtn ? x : (divs[0] - divs[divs[0]] / x + 1);
}

int f(long long n) {
    n %= p;
    return n * (n - 1) % p;
}

int g[MAXN];
int dp[MAXN], prime_sum[MAXN];

void get_dp(function<int(long long)> pw, function<int(long long)> sum) {
    memset(dp, 0, sizeof(dp));
    memset(prime_sum, 0, sizeof(prime_sum));

    for (int i = 1; i <= prime_cnt; i++)
        prime_sum[i] = (prime_sum[i - 1] + pw(prime[i])) % p;

    for (int i = 1; i <= divs[0]; i++)
        dp[i] = (sum(divs[i]) + p - 1) % p;

    for (int i = 1; i <= prime_cnt; i++) {
        int pi = prime[i];

        for (int j = divs[0]; (long long)pi * pi <= divs[j]; j--) {
            int k = getid(divs[j] / pi);

            dp[j] = (dp[j] + (long long)pw(pi) * (prime_sum[i - 1] - dp[k])) % p;
            if (dp[j] < 0)
                dp[j] += p;
        }
    }
}

void calc(long long n) {
    get_divs(n);

    get_dp([] (long long x) {
        x %= p;
        return x * x % p;
    }, [] (long long n) {
        n %= p;
        return n * (n + 1) % p * (2 * n + 1) % p * ((p + 1) / 6) % p;
    }); // x ^ 2

    for (int i = 1; i <= divs[0]; i++)
        g[i] = dp[i];

    get_dp([] (long long x) {
        return x % p;
    }, [] (long long n) {
        n %= p;
        return n * (n + 1) / 2 % p;
    }); // x

    for (int i = 1; i <= divs[0]; i++)
        g[i] = (g[i] - dp[i] + p) % p;

    memset(prime_sum, 0, sizeof(prime_sum));
    for (int i = 1; i <= prime_cnt; i++)
        prime_sum[i] = (prime_sum[i - 1] + f(prime[i])) % p;
}

int S(int i, long long n) {
    if (prime[i] > n || n < 1)
        return 0;

    int sq = sqrt(n + 0.5);
    int tmp = (g[getid(n)] - prime_sum[i - 1] + p) % p;

    for (int k = i; k <= prime_cnt && prime[k] <= sq; k++) {
        int pk = prime[k];
        long long pw = pk;

        for (int c = 1; pw * pk <= n; c++, pw *= pk)
            tmp = (tmp + (long long)S(k + 1, n / pw) * f(pw) + f(pw * pk)) % p;
    }

    return tmp;
}

int main() {

    long long n;
    cin >> n;

    sqrtn = 1; // sqrtn 是全局的
    while ((long long)(sqrtn + 1) * (sqrtn + 1) <= n)
        sqrtn++;

    get_table(sqrtn);

    calc(n);

    int ans = (S(1, n) + 1) % p;

    cout << ans << endl;

    return 0;
}
```

2.7 Miller-Rabin

```cpp
// 复杂度可以认为是常数

// 用一个数检测
// 需要调用long long快速幂和O(1) 快速乘
bool check(long long n, long long b) { // b: base
    long long a = n - 1;
    int k = 0;

    while (a % 2 == 0) {
        a /= 2;
        k++;
    }

    long long t = qpow(b, a, n); // 这里的快速幂函数需要写O(1) 快速乘
    if (t == 1 || t == n - 1)
        return true;

    while (k--) {
        t = mul(t, t, n); // mul是O(1) 快速乘函数
        if(t == n - 1)
            return true;
    }

    return false;
}
```

```cpp
// 封装好的函数体
// 需要调用check
bool Miller_Rabin(long long n) {
    if (n == 1)
        return false;
    if (n == 2)
        return true;
    if (n % 2 == 0)
        return false;

    // int范围内只需要检查 {2, 7, 61}
    // long long范围内只需要检查 {2, 325, 9375, 28178, 450775, 9780504, 1795265022}

    for (int i : {2, 325, 9375, 28178, 450775, 9780504, 1795265022}) {
        if (i >= n)
            break;
        if (!check(n, i))
            return false;
    }

    return true;
}
```

2.8 Pollard's Rho

```cpp
// 注意，虽然Pollard's Rho的理论复杂度是O(n ^ {1 / 4})的，
// 但实际跑起来比较慢，一般用于做long long范围内的质因数分解


// 封装好的函数体
// 需要调用solve
void factorize(long long n, vector<long long> &v) { // v用于存分解出来的质因子，重复的会放多个
    for (int i : {2, 3, 5, 7, 11, 13, 17, 19})
        while (n % i == 0) {
            v.push_back(i);
            n /= i;
        }

    solve(n, v);
    sort(v.begin(), v.end()); // 从小到大排序后返回
}

// 递归过程
// 需要调用Pollard's Rho主过程，同时递归调用自身
void solve(long long n, vector<long long> &v) {
    if (n == 1)
        return;

    long long p;
    do
        p = Pollards_Rho(n);
    while (!p); // p是任意一个非平凡因子

    if (p == n) {
        v.push_back(p); // 说明n本身就是质数
        return;
    }

    solve(p, v); // 递归分解两半
    solve(n / p, v);
}

// Pollard's Rho主过程
// 需要使用Miller-Rabin作为子算法
// 同时需要调用O(1) 快速乘和gcd函数
long long Pollards_Rho(long long n) {
    // assert(n > 1);

    if (Miller_Rabin(n))
        return n;

    long long c = rand() % (n - 2) + 1, i = 1, k = 2, x = rand() % (n - 3) + 2, u = 2; // 注意这里rand函数需要重定义一下
    while (true) {
        i++;
        x = (mul(x, x, n) + c) % n; // mul是O(1) 快速乘函数

        long long g = gcd((u - x + n) % n, n);
        if (g > 1 && g < n)
            return g;

        if (u == x)
            return 0; // 失败，需要重新调用

        if (i == k) {
            u = x;
            k *= 2;
        }
    }
}
```

2.9 快速阶乘算法

参见 1.1.5.多点求值应用：$O(\sqrt{n}\log^2 n)$ 快速求阶乘（第 4 页）。

2.10 扩展欧几里德 exgcd

```cpp
void exgcd(LL a, LL b, LL &c, LL &x, LL &y) {
    if (b == 0) {
        c = a;
        x = 1;
        y = 0;
        return;
    }

    exgcd(b, a % b, c, x, y);

    LL tmp = x;
    x = y;
    y = tmp - (a / b) * y;
}
```

2.10.1 求通解的方法

假设我们已经找到了一组解 (p_0, q_0) 满足 $ap_0 + bq_0 = \gcd(a, b)$，那么其他的解都满足

$$p = p_0 + \frac{b}{\gcd(p, q)} \times t \qquad q = q_0 - \frac{a}{\gcd(p, q)} \times t$$

其中 t 为任意整数。

2.10.2 类欧几里德算法

问题 $a, b \geq 0, m > 0$，计算 $\sum_{i=0}^{n-1} \left\lfloor \frac{a+bi}{m} \right\rfloor$。

```cpp
int solve(int n, int a, int b, int m) {
    if (!b)
        return n * (a / m);
    if (a >= m)
        return n * (a / m) + solve(n, a % m, b, m);
    if (b >= m)
        return (n - 1) * n / 2 * (b / m) + solve(n, a, b % m, m);
```

```
    return solve((a + b * n) / m, (a + b * n) % m, m, b);
}
```

2.11 中国剩余定理

$$x \equiv a_i \pmod{m_i}$$

$$M = \prod_i m_i,\ M_i = \frac{M}{m_i}$$

$$M_i' \equiv M_i^{-1} \pmod{m_i}$$

$$x \equiv \sum_i a_i M_i M_i' \pmod{M}$$

2.11.1 ex-CRT

设两个方程分别是 $x \equiv a_1 \pmod{m_1}$ 和 $x \equiv a_2 \pmod{m_2}$。
将它们转化为不定方程 $x = m_1 p + a_1 = m_2 q + a_2$，其中 p, q 是整数，则有 $m_1 p - m_2 q = a_2 - a_1$。
当 $a_2 - a_1$ 不能被 $\gcd(m_1, m_2)$ 整除时无解，否则可以通过扩展欧几里德解出来一组可行解 (p, q)。
则原来的两方程组成的模方程组的解为 $x \equiv b \pmod{M}$，其中 $b = m_1 p + a_1$，$M = \operatorname{lcm}(m_1, m_2)$。

2.12 二次剩余

```
int p, w;

struct pi {
    int a, b; // a + b * sqrt(w)

    pi(int a = 0, int b = 0) : a(a), b(b) {}

    friend pi operator * (const pi &u, const pi &v) {
        return pi(((long long)u.a * v.a + (long long)u.b * v.b % p * w) % p,
            ((long long)u.a * v.b + (long long)u.b * v.a) % p);
    }
};

pi qpow(pi a, int b) {
    pi ans(1, 0);

    while (b) {
        if (b & 1)
            ans = ans * a;

        b >>= 1;
        a = a * a;
    }

    return ans;
}

int qpow(int a, int b) {
    int ans = 1;

    while (b) {
        if (b & 1)
            ans = (long long)ans * a % p;

        b >>= 1;
        a = (long long)a * a % p;
    }

    return ans;
}

int my_legendre(int a) { // std有同名函数，最好换个名字，不然传了两个数都查不出来
    return qpow(a, (p - 1) / 2);
}

int quadratic_residual(int b, int mod) {
    p = mod;

    if (p == 2)
        return 1;

    if (my_legendre(b) == p - 1)
        return -1; // 无解

    int a;
    do {
        a = rand() % p;
        w = ((long long)a * a - b) % p;
        if (w < 0)
            w += p;
    } while (my_legendre(w) != p - 1);

    return qpow(pi(a, 1), (p + 1) / 2).a;
}
```

2.13 原根 阶

阶 最小的整数 k 使得 $a^k \equiv 1 \pmod{m}$，记为 $\delta_m(a)$。
显然 a 在阶以下次数的幂是两两不同的。
一个性质：如果 a, b 均与 m 互质，则

$$\delta_m(ab) = \delta_m(a)\delta_m(b) \iff \gcd\left(\delta_m(a), \delta_p(b)\right) = 1$$

另外，如果 a 与 m 互质，则有 $\delta_p(a^k) = \dfrac{\delta_p(a)}{\gcd\left(\delta_p(a), k\right)}$。（也就是长为 $\delta_m(a)$ 的环上一次跳 k 步的周期。）
原根 所有阶等于 $\varphi(m)$ 的数。
只有形如 $2, 4, p^k, 2p^k$（p 是奇素数）的数才有原根。并且如果 m 有原根，那么原根的个数一定是 $\varphi\left(\varphi(m)\right)$ 个。
暴力找原根代码：

```
def split(n): # 分解质因数
    i = 2
    a = []
    while i * i <= n:
        if n % i == 0:
            a.append(i)

            while n % i == 0:
                n /= i

        i += 1

    if n > 1:
        a.append(n)

    return a

def getg(p): # 找原根
    def judge(g):
        for i in d:
            if pow(g, (p - 1) / i, p) == 1:
                return False
        return True

    d = split(p - 1)
```

```
    g = 2

    while not judge(g):
        g += 1

    return g

print(getg(int(input())))
```

2.14 常用数论公式

2.14.1 Dirichlet 卷积

$$(f*g)(n)=\sum_{d|n}f(d)g\left(\frac{n}{d}\right)$$

$$\mu*I=e$$

其中 e 为单位元，满足 $e(n)=[n=1]$。

$$\varphi*I=id$$

$$\mu*id=\varphi$$

$$\sigma_0=I*I,\ \sigma_1=id*I,\ \sigma_k=id^{k-1}*I$$

2.14.2 莫比乌斯反演

$$f(n)=\sum_{d|n}g(d)\quad\Longleftrightarrow\quad g(n)=\sum_{d|n}\mu\left(\frac{n}{d}\right)f(d)$$

$$f(d)=\sum_{d|k}g(k)\quad\Longleftrightarrow\quad g(d)=\sum_{d|k}\mu\left(\frac{k}{d}\right)f(k)$$

$$\sum_{i=1}^{n}\sum_{j=1}^{m}[(i,j)=d]=\sum_{d|k}\mu\left(\frac{k}{d}\right)\left\lfloor\frac{n}{k}\right\rfloor\left\lfloor\frac{m}{k}\right\rfloor$$

2.14.3 降幂公式

$$a^k\equiv a^{k \bmod \varphi(p)+\varphi(p)}\pmod p,\ k\geq\varphi(p)$$

和费马小定理的区别在于不需要 a 与 p 互质，但要注意 $k<\varphi(p)$ 时不成立。

2.14.4 其他常用公式

$$\sum_{i=1}^{n}[(i,n)=1]\,i=n\frac{\varphi(n)+e(n)}{2}$$

$$\sum_{i=1}^{n}\sum_{j=1}^{i}[(i,j)=d]=S_\varphi\left(\left\lfloor\frac{n}{d}\right\rfloor\right)$$

$$\sum_{i=1}^{n}f(i)\sum_{j=1}^{\lfloor\frac{n}{i}\rfloor}g(j)=\sum_{i=1}^{n}g(i)\sum_{j=1}^{\lfloor\frac{n}{i}\rfloor}f(j)$$

3 图论

3.1 最小生成树

3.1.1 Boruvka 算法

思想：每次选择连接每个连通块的最小边，把连通块缩起来。
每次连通块个数至少减半，所以迭代 $O(\log n)$ 次即可得到最小生成树。
一种比较简单的实现方法：每次迭代遍历所有边，用并查集维护连通性和每个连通块的最小边权。
应用：最小异或生成树

3.1.2 动态最小生成树

对时间分治，在每层分治时找出一定在/不在 MST 上的边，只带着不确定边继续递归。
过程中的两种重要操作如下：

- Reduction：待修改边标为 $+\infty$，跑 MST 后把非树边删掉，减少无用边
- Contraction：待修改边标为 $-\infty$，跑 MST 后把待修改边之外的所有树边缩点，缩掉必须边

每轮分治需要 Reduction-Contraction，借此减少不确定边，从而保证复杂度。
复杂度证明：假设当前区间有 k 条待修改边，n 和 m 表示点数和边数，那么最坏情况下 R-C 的效果为 $(n,m) \to (n, n+k-1) \to (k+1, 2k)$。

```cpp
struct Edge { int u, v, w; } edges[MAXN];

int vis[MAXN], stamp = 0; // 因为不好清空，用时间戳标记

struct Modify { int i, new_w; } op[MAXN]; // 方便起见，只有修改边权一种操作

int ufs[MAXN], ufs_size[MAXN]; // 因为要撤销，不方便存 rank，所以用 size

void ufs_init(int n) {
    for (int i = 1; i <= n; i++) {
        ufs[i] = i;
        ufs_size[i] = 1;
    }
}

int findufs(int x) { while (ufs[x] != x) x = ufs[x]; return x; }

void undo(const vector<int>& stk) {
    for (int i = (int)stk.size() - 1; ~i; i--) {
        int x = stk[i]; ufs_size[ufs[x]] -= ufs_size[x];
        ufs[x] = x; } }

bool link(int u, int v, vector<int>& stk) {
    int x = findufs(u), y = findufs(v);

    if (x != y) {
        if (ufs_size[x] > ufs_size[y])
            swap(x, y);

        ufs[x] = y;
        ufs_size[y] += ufs_size[x];
        stk.push_back(x);
        return true;
    }
    return false;
}

// Returns { unused, used }. e should be already sorted.
pair<vector<int>, vector<int>> kruskal(const vector<int>& e, const vector<int>& must) {
    vector<int> stk, used[2];

    for (int i : must)
        link(edges[i].u, edges[i].v, stk);

    for (int i : e)
        used[link(edges[i].u, edges[i].v, stk)].push_back(i);

    undo(stk);

    return {used[0], used[1]};
}

ll ans[MAXN];

void solve(int l, int r, vector<int> e, ll sum) {
    if (l == r) {
        edges[op[l].i].w = op[l].new_w;

        sort(e.begin(), e.end(), [] (int i, int j) { return edges[i].w < edges[j].w; });
        for (int i : kruskal(e, {}).second)
            sum += edges[i].w;

        // Did not check if the graph is connected.
        ans[l] = sum;

        return;
    }

    sort(e.begin(), e.end(), [] (int i, int j) { return edges[i].w < edges[j].w; });

    stamp++;
    vector<int> mod;
    for (int t = l; t <= r; t++)
        if (vis[op[t].i] < stamp) {
            vis[op[t].i] = stamp;
            mod.push_back(op[t].i);
        }

    vector<int> notmod;
    for (int i : e)
        if (vis[i] < stamp)
            notmod.push_back(i);

    // Reduction, unused edges are dismissed.
    notmod = get<1>(kruskal(notmod, {}));

    // Contraction, used edges are sure to be in MST.
    auto [notsure, must] = kruskal(notmod, mod);

    vector<int> stk;
    for (int i : must) {
        assert(link(edges[i].u, edges[i].v, stk));
        sum += edges[i].w;
    }

    for (int i : mod)
        notsure.push_back(i);

    int mid = (l + r) / 2;
    solve(l, mid, notsure, sum);
    solve(mid + 1, r, notsure, sum);

    undo(stk);
}
```

```
int main() { ufs_init(n); }
```

3.1.3 最小树形图

对每个点找出最小的入边，如果是一个 DAG 那么就已经结束了。
否则把环都缩起来，每个点的边权减去环上的边权之后再跑一遍，直到没有环为止。
可以用可并堆优化到 $O(m\log n)$，需要写一个带懒标记的左偏树。

$O(nm)$ 版本

```
constexpr int maxn = 105, maxe = 10005, inf = 0x3f3f3f3f;

struct edge {
    int u, v, w;
} e[maxe];

int mn[maxn], pr[maxn], ufs[maxn], vis[maxn];
bool alive[maxn];

int edmonds(int n, int m, int rt) {
    for (int i = 1; i <= n; i++)
        alive[i] = true;

    int ans = 0;

    while (true) {
        memset(mn, 63, sizeof(int) * (n + 1));
        memset(pr, 0, sizeof(int) * (n + 1));
        memset(ufs, 0, sizeof(int) * (n + 1));
        memset(vis, 0, sizeof(int) * (n + 1));

        mn[rt] = 0;

        for (int i = 1; i <= m; i++)
            if (e[i].u != e[i].v && e[i].w < mn[e[i].v]) {
                mn[e[i].v] = e[i].w;
                pr[e[i].v] = e[i].u;
            }

        for (int i = 1; i <= n; i++)
            if (alive[i]) {
                if (mn[i] >= inf)
                    return -1; // 不存在最小树形图

                ans += mn[i];
            }

        bool flag = false;

        for (int i = 1; i <= n; i++) {
            if (!alive[i])
                continue;

            int x = i;
            while (x && !vis[x]) {
                vis[x] = i;
                x = pr[x];
            }

            if (x && vis[x] == i) {
                flag = true;
                for (int u = x; !ufs[u]; u = pr[u])
                    ufs[u] = x;
            }
        }

        for (int i = 1; i <= m; i++) {
            e[i].w -= mn[e[i].v];

            if (ufs[e[i].u])
                e[i].u = ufs[e[i].u];
            if (ufs[e[i].v])
                e[i].v = ufs[e[i].v];
        }

        if (!flag)
            return ans;

        for (int i = 1; i <= n; i++)
            if (ufs[i] && i != ufs[i])
                alive[i] = false;
    }
}
```

$O(m\log n)$ 版本

(堆优化版本可以参考 *fstqwq* 的模板，在最后没有目录的部分。)

3.1.4 斯坦纳树

问题 一张图上有 k 个关键点，求让关键点两两连通的最小生成树。

做法 状压 DP，$f_{i,S}$ 表示以 i 号点为树根，i 与 S 中的所有点连通的最小边权和。
转移有两种：

1. 枚举子集：
$$f_{i,S} = \min_{T\subset S}\{f_{i,T} + f_{i,S\setminus T}\}$$
2. 新加一条边：
$$f_{i,S} = \min_{(i,j)\in E}\{f_{j,S} + w_{i,j}\}$$

第一种直接枚举子集 DP 就行了，第二种可以用 SPFA 或者 Dijkstra 松弛（显然负边一开始全选就行了，所以只需要处理非负边）。
复杂度 $O(n3^k + 2^k\mathrm{SSSP}(n,m)))$，其中 $\mathrm{SSSP}(n,m)$ 可以是 nm (SPFA) 或者 n^2+m 或者 $m\log n$（后两种都是 Dijkstra）。

```
constexpr int maxn = 105, inf = 0x3f3f3f3f;

int dp[maxn][(1 << 10) + 1];
int g[maxn][maxn], a[15];
bool inq[maxn];

int main() {

    int n, m, k;
    scanf("%d%d%d", &n, &m, &k);

    memset(g, 63, sizeof(g));

    while (m--) {
        int u, v, c;
        scanf("%d%d%d", &u, &v, &c);

        g[u][v] = g[v][u] = min(g[u][v], c); // 不要忘了是双向边
    }

    memset(dp, 63, sizeof(dp));

    for (int i = 0; i < k; i++) {
        scanf("%d", &a[i]);

        dp[a[i]][1 << i] = 0;
    }

    for (int s = 1; s < (1 << k); s++) {
        for (int i = 1; i <= n; i++)
            for (int t = (s - 1) & s; t; (--t) &= s)
                dp[i][s] = min(dp[i][s], dp[i][t] + dp[i][s ^ t]);
```

```cpp

        // SPFA
        queue<int> q;
        for (int i = 1; i <= n; i++)
            if (dp[i][s] < inf) {
                q.push(i);
                inq[i] = true;
            }

        while (!q.empty()) {
            int i = q.front();
            q.pop();
            inq[i] = false; // 最终结束时inq一定全0，所以不用清空

            for (int j = 1; j <= n; j++)
                if (dp[i][s] + g[i][j] < dp[j][s]) {
                    dp[j][s] = dp[i][s] + g[i][j];
                    if (!inq[j]) {
                        q.push(j);
                        inq[j] = true;
                    }
                }
        }
    }

    int ans = inf;
    for (int i = 1; i <= n; i++)
        ans = min(ans, dp[i][(1 << k) - 1]);

    printf("%d\n", ans);

    return 0;
}
```

3.1.5 最小直径生成树

首先找到图的绝对中心（可能在点上，也可能在某条边上），然后以绝对中心为起点建最短路树就是最小直径生成树。

```cpp
#include <bits/stdc++.h>

using namespace std;

constexpr int maxn = 505;
constexpr long long inf = 0x3f3f3f3f3f3f3f3fll;

int g[maxn][maxn], id[maxn][maxn], pr[maxn]; // g是邻接矩阵
long long f[maxn][maxn], d[maxn];
bool vis[maxn];

vector<pair<int, int>> minimum_diameter_spanning_tree(int n) { // 1-based
    for (int i = 1; i <= n; i++)
        for (int j = 1; j <= n; j++)
            g[i][j] *= 2; // 输入的边权都要乘2

    memset(f, 63, sizeof(f));

    for (int i = 1; i <= n; i++)
        f[i][i] = 0;

    for (int i = 1; i <= n; i++)
        for (int j = 1; j <= n; j++)
            if (g[i][j])
                f[i][j] = g[i][j];

    for (int k = 1; k <= n; k++)
        for (int i = 1; i <= n; i++)
            for (int j = 1; j <= n; j++)
                f[i][j] = min(f[i][j], f[i][k] + f[k][j]);

    for (int i = 1; i <= n; i++) {
        for (int j = 1; j <= n; j++)
            id[i][j] = j; // 距离i第j近的点

        sort(id[i] + 1, id[i] + n + 1, [&i] (int x, int y) {
            return f[i][x] < f[i][y];
        });
    }

    int o = 0;
    long long ansv = inf; // vertex

    for (int i = 1; i <= n; i++)
        if (f[i][id[i][n]] * 2 < ansv) {
            ansv = f[i][id[i][n]] * 2;
            o = i;
        }

    int u = 0, v = 0;
    long long disu = -inf, disv = -inf, anse = inf;

    for (int x = 1; x <= n; x++)
        for (int y = 1; y <= n; y++)
            if (g[x][y]) { // 如果g[x][y] = 0说明没有边
                int w = g[x][y];

                for (int i = n - 1, j = n; i; i--)
                    if (f[y][id[x][i]] > f[y][id[x][j]]) {
                        long long tmp = f[x][id[x][i]] + f[y][id[x][j]] + w;
                        if (tmp < anse) {
                            anse = tmp;
                            u = x;
                            v = y;

                            disu = tmp / 2 - f[x][id[x][i]];
                            disv = w - disu;
                        }
                        j = i;
                    }
            }

    printf("%lld\n", min(ansv, anse) / 2); // 直径

    memset(d, 63, sizeof(d));

    if (ansv <= anse)
        d[o] = 0;
    else {
        d[u] = disu;
        d[v] = disv;
    }

    for (int k = 1; k <= n; k++) { // Dijkstra
        int x = 0;
        for (int i = 1; i <= n; i++)
            if (!vis[i] && d[i] < d[x])
                x = i;

        vis[x] = true;
        for (int y = 1; y <= n; y++)
            if (g[x][y] && !vis[y]) {
                if (d[y] > d[x] + g[x][y]) {
                    d[y] = d[x] + g[x][y];
                    pr[y] = x;
                }
```

```cpp
            else if (d[y] == d[x] + g[x][y] && d[pr[y]] < d[x])
                pr[y] = x;
        }
    }

    vector<pair<int, int>> vec;
    for (int i = 1; i <= n; i++)
        if (pr[i])
            vec.emplace_back(i, pr[i]);

    if (ansv > anse)
        vec.emplace_back(u, v);

    return vec;
}

int main() {

    int n, m;
    scanf("%d%d", &n, &m);

    while (m--) {
        int x, y, z;
        scanf("%d%d%d", &x, &y, &z);

        g[x][y] = g[y][x] = z; // 无向图
    }

    auto vec = minimum_diameter_spanning_tree(n);
    for (auto [x, y] : vec)
        printf("%d %d\n", x, y);

    return 0;
}
```

3.2 最短路

3.2.1 Dijkstra

参见 3.2.3.k 短路（第 29 页），注意那边是求到 t 的最短路。

3.2.2 Johnson 算法

首先前提是图没有负环。
先任选一个起点 s，跑一遍 SPFA，计算每个点的势 $h_u = d_{s,u}$，然后将每条边 $u \to v$ 的权值 w 修改为 $w + h[u] - h[v]$ 即可，由最短路的性质显然修改后边权非负。
然后对每个起点跑 Dijkstra，再修正距离 $d_{u,v} = d'_{u,v} - h_u + h_v$ 即可。复杂度 $O(nm \log n)$，在稀疏图上是要优于 Floyd 的。

3.2.3 k 短路

```cpp
// 注意这是个多项式算法，在k比较大时很有优势，但k比较小时最好还是用A*
// DAG和有环的情况都可以，有重边或自环也无所谓，但不能有零环
// 以下代码以Dijkstra + 可持久化左偏树为例

constexpr int maxn = 1005, maxe = 10005, maxm = maxe * 30; //点数，边数，左偏树结点数

// 结构体定义
struct A { // 用来求最短路
    int x, d;

    A(int x, int d) : x(x), d(d) {}

    bool operator < (const A &a) const {
        return d > a.d;
    }
};

struct node { // 左偏树结点
    int w, i, d; // i: 最后一条边的编号 d: 左偏树附加信息
    node *lc, *rc;

    node() {}

    node(int w, int i) : w(w), i(i), d(0) {}

    void refresh(){
        d = rc -> d + 1;
    }
} null[maxm], *ptr = null, *root[maxn];

struct B { // 维护答案用
    int x, w; // x是结点编号，w表示之前已经产生的权值
    node *rt; // 这个答案对应的堆顶，注意可能不等于任何一个结点的堆

    B(int x, node *rt, int w) : x(x), w(w), rt(rt) {}

    bool operator < (const B &a) const {
        return w + rt -> w > a.w + a.rt -> w;
    }
};

// 全局变量和数组定义
vector<int> G[maxn], W[maxn], id[maxn]; // 最开始要存反向图，然后把G清空作为儿子列表
bool vis[maxn], used[maxe]; // used表示边是否在最短路树上
int u[maxe], v[maxe], w[maxe]; // 存下每条边，注意是有向边
int d[maxn], p[maxn]; // p表示最短路树上每个点的父边
int n, m, k, s, t; // s, t分别表示起点和终点


// 以下是主函数中较关键的部分
for (int i = 0 ; i <= n; i++)
    root[i] = null; // 一定要加上!!!

// (读入& 建反向图)

Dijkstra();

// (清空G, W, id)

for (int i = 1; i <= n; i++)
    if (p[i]) {
        used[p[i]] = true; // 在最短路树上
        G[v[p[i]]].push_back(i);
    }

for (int i = 1; i <= m; i++) {
    w[i] -= d[u[i]] - d[v[i]]; // 现在的w[i] 表示这条边能使路径长度增加多少
    if (!used[i])
        root[u[i]] = merge(root[u[i]], newnode(w[i], i));
}

dfs(t);

priority_queue<B> heap;
heap.push(B(s, root[s], 0)); // 初始状态是找贡献最小的边加进去

printf("%d\n",d[s]); // 第1短路需要特判
while (--k) { // 其余k - 1短路径用二叉堆维护
    if (heap.empty())
```

```
        printf("-1\n");
    else {
        int x = heap.top().x, w = heap.top().w;
        node *rt = heap.top().rt;
        heap.pop();

        printf("%d\n", d[s] + w + rt -> w);

        if (rt -> lc != null || rt -> rc != null)
            heap.push(B(x, merge(rt -> lc, rt -> rc), w)); // pop掉当前边，换成另一条贡献大一点的边
        if (root[v[rt -> i]] != null)
            heap.push(B(v[rt -> i], root[v[rt -> i]], w + rt -> w)); // 保留当前边，往后面再接上另一条边
    }
}
// 主函数到此结束


// Dijkstra预处理最短路 O(m\log n)
void Dijkstra() {
    memset(d, 63, sizeof(d));
    d[t] = 0;
    priority_queue<A> heap;
    heap.push(A(t, 0));

    while (!heap.empty()) {
        int x = heap.top().x;
        heap.pop();

        if(vis[x])
            continue;

        vis[x] = true;
        for (int i = 0; i < (int)G[x].size(); i++)
            if (!vis[G[x][i]] && d[G[x][i]] > d[x] + W[x][i]) {
                d[G[x][i]] = d[x] + W[x][i];
                p[G[x][i]] = id[x][i];

                heap.push(A(G[x][i], d[G[x][i]]));
            }
    }
}

// dfs求出每个点的堆 总计O(m\log n)
// 需要调用merge，同时递归调用自身
void dfs(int x) {
    root[x] = merge(root[x], root[v[p[x]]]);

    for (int i = 0; i < (int)G[x].size(); i++)
        dfs(G[x][i]);
}

// 包装过的new node() O(1)
node *newnode(int w, int i) {
    *++ptr = node(w, i);
    ptr -> lc = ptr -> rc = null;
    return ptr;
}

// 带可持久化的左偏树合并 总计O(\log n)
// 递归调用自身
node *merge(node *x, node *y) {
    if (x == null)
        return y;
    if (y == null)
        return x;

    if (x -> w > y -> w)
        swap(x, y);

    node *z = newnode(x -> w, x -> i);
    z -> lc = x -> lc;
    z -> rc = merge(x -> rc, y);

    if (z -> lc -> d < z -> rc -> d)
        swap(z -> lc, z -> rc);
    z -> refresh();

    return z;
}
```

3.3 Tarjan 算法

3.3.1 强连通分量

```
int dfn[maxn], low[maxn], tim = 0;
vector<int> G[maxn], scc[maxn];
int sccid[maxn], scc_cnt = 0, stk[maxn];
bool instk[maxn];

void dfs(int x) {
    dfn[x] = low[x] = ++tim;

    stk[++stk[0]] = x;
    instk[x] = true;

    for (int y : G[x]) {
        if (!dfn[y]) {
            dfs(y);
            low[x] = min(low[x], low[y]);
        }
        else if (instk[y])
            low[x] = min(low[x], dfn[y]);
    }

    if (dfn[x] == low[x]) {
        scc_cnt++;

        int u;
        do {
            u = stk[stk[0]--];
            instk[u] = false;
            sccid[u] = scc_cnt;
            scc[scc_cnt].push_back(u);
        } while (u != x);
    }
}

void tarjan(int n) {
    for (int i = 1; i <= n; i++)
        if (!dfn[i])
            dfs(i);
}
```

3.3.2 割点 点双

```
vector<int> G[maxn], bcc[maxn];
int dfn[maxn], low[maxn], tim = 0, bccid[maxn], bcc_cnt = 0;
bool iscut[maxn];

pair<int, int> stk[maxn];
int stk_cnt = 0;

void dfs(int x, int pr) {
    int child = 0;
    dfn[x] = low[x] = ++tim;

```

```
    for (int y : G[x]) {
        if (!dfn[y]) {
            stk[++stk_cnt] = make_pair(x, y);
            child++;
            dfs(y, x);
            low[x] = min(low[x], low[y]);

            if (low[y] >= dfn[x]) {
                iscut[x] = true;
                bcc_cnt++;

                while (true) {
                    auto pi = stk[stk_cnt--];

                    if (bccid[pi.first] != bcc_cnt) {
                        bcc[bcc_cnt].push_back(pi.first);
                        bccid[pi.first] = bcc_cnt;
                    }
                    if (bccid[pi.second] != bcc_cnt) {
                        bcc[bcc_cnt].push_back(pi.second);
                        bccid[pi.second] = bcc_cnt;
                    }

                    if (pi.first == x && pi.second == y)
                        break;
                }
            }
        }
        else if (dfn[y] < dfn[x] && y != pr) {
            stk[++stk_cnt] = make_pair(x, y);
            low[x] = min(low[x], dfn[y]);
        }
    }

    if (!pr && child == 1)
        iscut[x] = false;
}

void Tarjan(int n) {
    for (int i = 1; i <= n; i++)
        if (!dfn[i])
            dfs(i, 0);
}
```

3.3.3 桥 边双

```
int u[maxe], v[maxe];
vector<int> G[maxn]; // 存的是边的编号

int stk[maxn], top, dfn[maxn], low[maxn], tim, bcc_cnt;
vector<int> bcc[maxn];

bool isbridge[maxe];

void dfs(int x, int pr) { // 这里pr是入边的编号
    dfn[x] = low[x] = ++tim;
    stk[++top] = x;

    for (int i : G[x]) {
        int y = (u[i] == x ? v[i] : u[i]);

        if (!dfn[y]) {
            dfs(y, i);
            low[x] = min(low[x], low[y]);

            if (low[y] > dfn[x])
                bridge[i] = true;
        }
        else if (i != pr)
            low[x] = min(low[x], dfn[y]);
    }

    if (dfn[x] == low[x]) {
        bcc_cnt++;
        int y;
        do {
            y = stk[top--];
            bcc[bcc_cnt].push_back(y);
        } while (y != x);
    }
}
```

3.4 欧拉回路

C[x] 是记录每条边对应的编号的。
另外为了保证复杂度需要加当前弧优化。

```
vector<int> G[maxn], C[maxn], v[maxn]; // C是边的编号
int cur[maxn];
bool vis[maxn * 2];

vector<pair<int, int> > vec;

int d[maxn];

void dfs(int x) {
    bool bad = false;

    while (!bad) {
        bad = true;

        for (int &i = cur[x]; i < (int)G[x].size(); i++)
            if (!vis[C[x][i]]) {
                vis[C[x][i]] = true;
                vec.emplace_back(x, i);
                x = G[x][i];
                bad = false;

                break;
            }
    }
}
```

3.5 仙人掌

一般来说仙人掌问题都可以通过圆方树转成有两种点的树上问题来做。

3.5.1 仙人掌 DP

```
struct edge {
    int to, w, prev;
} e[maxn * 2];

vector<pair<int, int> > v[maxn];
vector<long long> d[maxn];
stack<int> stk;

int p[maxn];
bool vis[maxn], vise[maxn * 2];
int last[maxn], cnte;

long long f[maxn], g[maxn], sum[maxn];
int n, m, cnt;

void addedge(int x, int y, int w) {
    v[x].push_back(make_pair(y, w));
}

```

```cpp
void dfs(int x) {

    vis[x] = true;

    for (int i = last[x]; ~i; i = e[i].prev) {
        if (vise[i ^ 1])
            continue;

        int y = e[i].to, w = e[i].w;

        vise[i] = true;

        if (!vis[y]) {
            stk.push(i);
            p[y] = x;
            dfs(y);

            if (!stk.empty() && stk.top() == i) {
                stk.pop();
                addedge(x, y, w);
            }
        }

        else {
            cnt++;

            long long tmp = w;
            while (!stk.empty()) {
                int i = stk.top();
                stk.pop();

                int yy = e[i].to, ww = e[i].w;

                addedge(cnt, yy, 0);

                d[cnt].push_back(tmp);

                tmp += ww;

                if (e[i ^ 1].to == y)
                    break;
            }

            addedge(y, cnt, 0);

            sum[cnt] = tmp;
        }
    }
}

void dp(int x) {

    for (auto o : v[x]) {
        int y = o.first, w = o.second;
        dp(y);
    }

    if (x <= n) {
        for (auto o : v[x]) {
            int y = o.first, w = o.second;

            f[x] += 2 * w + f[y];
        }

        g[x] = f[x];

        for (auto o : v[x]) {
            int y = o.first, w = o.second;

            g[x] = min(g[x], f[x] - f[y] - 2 * w + g[y] + w);
        }
    }
    else {
        f[x] = sum[x];
        for (auto o : v[x]) {
            int y = o.first;

            f[x] += f[y];
        }

        g[x] = f[x];

        for (int i = 0; i < (int)v[x].size(); i++) {
            int y = v[x][i].first;

            g[x] = min(g[x], f[x] - f[y] + g[y] + min(d[x][i], sum[x] - d[x][i]));
        }
    }
}
```

3.6 二分图

3.6.1 匈牙利

```cpp
vector<int> G[maxn];

int girl[maxn], boy[maxn]; // 男孩在左边，女孩在右边
bool vis[maxn];

bool dfs(int x) {
    for (int y : G[x])
        if (!vis[y]) {
            vis[y] = true;

            if (!boy[y] || dfs(boy[y])) {
                girl[x] = y;
                boy[y] = x;

                return true;
            }
        }

    return false;
}

int hungary() {
    int ans = 0;

    for (int i = 1; i <= n; i++)
        if (!girl[i]) {
            memset(vis, 0, sizeof(vis));
            ans += dfs(i);
        }

    return ans;
}
```

3.6.2 Hopcroft-Karp

其实长得和 Dinic 差不太多，或者说像匈牙利和 Dinic 的缝合怪.

```cpp
vector<int> G[maxn];

int girl[maxn], boy[maxn]; // girl: 左边匹配右边  boy: 右边匹配左边

bool vis[maxn]; // 右半的点是否已被访问
int dx[maxn], dy[maxn];
int q[maxn];

bool bfs(int n) {
```

```cpp
    memset(dx, -1, sizeof(int) * (n + 1));
    memset(dy, -1, sizeof(int) * (n + 1));

    int head = 0, tail = 0;
    for (int i = 1; i <= n; i++)
        if (!girl[i]) {
            q[tail++] = i;
            dx[i] = 0;
        }

    bool flag = false;

    while (head != tail) {
        int x = q[head++];

        for (auto y : G[x])
            if (dy[y] == -1) {
                dy[y] = dx[x] + 1;

                if (boy[y]) {
                    if (dx[boy[y]] == -1) {
                        dx[boy[y]] = dy[y] + 1;
                        q[tail++] = boy[y];
                    }
                }
                else
                    flag = true;
            }
    }

    return flag;
}

bool dfs(int x) {
    for (int y : G[x])
        if (!vis[y] && dy[y] == dx[x] + 1) {
            vis[y] = true;

            if (boy[y] && !dfs(boy[y]))
                continue;

            girl[x] = y;
            boy[y] = x;
            return true;
        }

    return false;
}

int hopcroft_karp(int n) {
    int ans = 0;

    for (int x = 1; x <= n; x++) // 先贪心求出一组初始匹配，当然不写贪心也行
        for (int y : G[x])
            if (!boy[y]) {
                girl[x] = y;
                boy[y] = x;
                ans++;
                break;
            }

    while (bfs(n)) {
        memset(vis, 0, sizeof(bool) * (n + 1));

        for (int x = 1; x <= n; x++)
            if (!girl[x])
                ans += dfs(x);
    }

    return ans;
}
```

3.6.3 KM

```cpp
const long long INF = 0x3f3f3f3f3f3f3f3f;

long long w[maxn][maxn], lx[maxn], ly[maxn], slack[maxn];
// 边权 顶标 slack
// 如果要求最大权完美匹配就把不存在的边设为-INF，否则所有边对0取max

bool visx[maxn], visy[maxn];

int boy[maxn], girl[maxn], p[maxn], q[maxn], head, tail; // p : pre

int n, m, N, e;

// 增广
bool check(int y) {
    visy[y] = true;

    if (boy[y]) {
        visx[boy[y]] = true;
        q[tail++] = boy[y];
        return false;
    }

    while (y) {
        boy[y] = p[y];
        swap(y, girl[p[y]]);
    }

    return true;
}

// bfs每个点
void bfs(int x) {
    memset(q, 0, sizeof(q));
    head = tail = 0;

    q[tail++] = x;
    visx[x] = true;

    while (true) {
        while (head != tail) {
            int x = q[head++];

            for (int y = 1; y <= N; y++)
                if (!visy[y]) {
                    long long d = lx[x] + ly[y] - w[x] + [y];

                    if (d < slack[y]) {
                        p[y] = x;
                        slack[y] = d;

                        if (!slack[y] && check(y))
                            return;
                    }
                }
        }

        long long d = INF;
        for (int i = 1; i <= N; i++)
            if (!visy[i])
                d = min(d, slack[i]);

        for (int i = 1; i <= N; i++) {
            if (visx[i])
                lx[i] -= d;
```

```cpp
            if (visy[i])
                ly[i] += d;
            else
                slack[i] -= d;
        }

        for (int i = 1; i <= N; i++)
            if (!visy[i] && !slack[i] && check(i))
                return;
    }
}

// 主过程
long long KM() {
    for (int i = 1; i <= N; i++) {
        // lx[i] = 0;
        ly[i] = -INF;
        // boy[i] = girl[i] = -1;

        for (int j = 1; j <= N; j++)
            ly[i] = max(ly[i], w[j][i]);
    }

    for (int i = 1; i <= N; i++) {
        memset(slack, 0x3f, sizeof(slack));
        memset(visx, 0, sizeof(visx));
        memset(visy, 0, sizeof(visy));
        bfs(i);
    }

    long long ans = 0;
    for (int i = 1; i <= N; i++)
        ans += w[i][girl[i]];
    return ans;
}

// 为了方便贴上主函数
int main() {

    scanf("%d%d%d", &n, &m, &e);
    N = max(n, m);

    while (e--) {
        int x, y, c;
        scanf("%d%d%d", &x, &y, &c);
        w[x][y] = max(c, 0);
    }

    printf("%lld\n", KM());

    for (int i = 1; i <= n; i++) {
        if (i > 1)
            printf(" ");
        printf("%d", w[i][girl[i]] > 0 ? girl[i] : 0);
    }
    printf("\n");

    return 0;
}
```

3.6.4 二分图原理

- **最大匹配的可行边与必须边、关键点**

以下的“残量网络”指网络流图的残量网络。

可行边 一条边的两个端点在残量网络中处于同一个 SCC，不论是正向边还是反向边。

必须边 一条属于当前最大匹配的边，且残量网络中两个端点不在同一个 SCC 中。

关键点/必须点 这里不考虑网络流图而只考虑原始的图，将匹配边改成从右到左之后从左边的每个未匹配点进行 floodfill，左边没有被标记的点即为关键点。右边同理。

- **独立集**

二分图独立集可以看成最小割问题，割掉最少的点使得 S 和 T 不连通，则剩下的点自然都在独立集中。
所以独立集输出方案就是求出不在最小割中的点，独立集的必须点/可行点就是最小割的不可行点/非必须点。
割点等价于割掉它与源点或汇点相连的边，可以通过设置中间的边权为无穷以保证不能割掉中间的边，然后按照上面的方法判断即可。(由于一个点最多流出一个流量，所以中间的边权其实是可以任取的。)

- **二分图最大权匹配**

二分图最大权匹配的对偶问题是 **最小顶标和** 问题，即：为图中的每个顶点赋予一个非负顶标，使得对于任意一条边，两端点的顶标和都要不小于边权，最小化顶标之和。
KM 算法的原理实际上就是求最小顶标和。

3.7 一般图匹配

3.7.1 高斯消元

设图 G 的 Tutte 矩阵是 $\tilde{A}$，首先是最基础的引理：

- G 的最大匹配大小是 $\frac{1}{2}\mathrm{rank}\tilde{A}$；
- $\left(\tilde{A}^{-1}\right)_{i,j} \neq 0 \iff G - \{v_i, v_j\}$ 有完美匹配。
  (考虑到逆矩阵与伴随矩阵的关系，这是显然的。)

构造最大匹配的方法见板子。对于更一般的问题，可以借助构造方法转化为完美匹配问题。
设最大匹配的大小为 k，新建 $n-2k$ 个辅助点，让它们和其他所有点连边，那么如果一个点匹配了一个辅助点，就说明它在原图的匹配中不匹配任何点。

可行边 对原图中的任意一条边 (u, v)，如果删掉 u, v 后新图仍然有完美匹配（即 $\tilde{A}^{-1}_{u,v} \neq 0$），则它是一条可行边。

必须边 待补充。

必须点 可以删掉这个点和一个辅助点，然后判断剩下的图是否还有完美匹配，如果有则说明它不是必须的，否则是必须的。只需要用到逆矩阵即可。

可行点 显然对于任意一个点，只要它不是孤立点，就是可行点。

```cpp
// 这个算法基于Tutte定理和高斯消元，思维难度相对小一些，也更方便进行可行边的判定
// 注意这个算法复杂度是满的，并且常数有点大，而带花树通常是跑不满的
// 以及，根据Tutte定理，如果求最大匹配的大小的话直接输出Tutte矩阵的秩/2即可
// 需要输出方案时才需要再写后面那些乱七八糟的东西


// 复杂度和常数所限，1s之内500已经是这个算法的极限了
const int maxn = 505, p = 1000000007; // p可以是任意10^9以内的质数

// 全局数组和变量定义
int A[maxn][maxn], B[maxn][maxn], t[maxn][maxn], id[maxn], a[maxn];
bool row[maxn] = {false}, col[maxn] = {false};
int n, m, girl[maxn]; // girl是匹配点，用来输出方案

// 为了方便使用，贴上主函数
// 需要调用高斯消元和eliminate
int main() {
    srand(19260817);

    scanf("%d%d", &n, &m); // 点数和边数
    while (m--) {
        int x, y;
        scanf("%d%d", &x, &y);
```

```
        A[x][y] = rand() % p;
        A[y][x] = -A[x][y]; // Tutte矩阵是反对称矩阵
    }

    for (int i = 1; i <= n; i++)
        id[i] = i; // 输出方案用的，因为高斯消元的时候会交换列
    memcpy(t, A, sizeof(t));
    Gauss(A, NULL, n);

    m = n;
    n = 0; // 这里变量复用纯属个人习惯

    for (int i = 1; i <= m; i++)
        if (A[id[i]][id[i]])
            a[++n] = i; // 找出一个极大满秩子矩阵

    for (int i = 1;i <= n; i++)
        for (int j = 1; j <= n; j++)
            A[i][j] = t[a[i]][a[j]];

    Gauss(A, B, n);

    for (int i = 1; i <= n; i++)
        if (!girl[a[i]])
            for (int j = i + 1; j <= n; j++)
                if (!girl[a[j]] && t[a[i]][a[j]] && B[j][i]) {
                    // 注意上面那句if的写法，现在t是邻接矩阵的备份，
                    // 逆矩阵j行i列不为0当且仅当这条边可行
                    girl[a[i]] = a[j];
                    girl[a[j]] = a[i];

                    eliminate(i, j);
                    eliminate(j, i);
                    break;
                }

    printf("%d\n", n / 2);
    for (int i = 1; i <= m; i++)
        printf("%d ", girl[i]);

    return 0;
}

// 高斯消元 O(n^3)
// 在传入B时表示计算逆矩阵，传入NULL则只需计算矩阵的秩
void Gauss(int A[][maxn], int B[][maxn], int n) {
    if(B) {
        memset(B, 0, sizeof(t));
        for (int i = 1; i <= n; i++)
            B[i][i] = 1;
    }

    for (int i = 1; i <= n; i++) {
        if (!A[i][i]) {
            for (int j = i + 1; j <= n; j++)
                if (A[j][i]) {
                    swap(id[i], id[j]);
                    for (int k = i; k <= n; k++)
                        swap(A[i][k], A[j][k]);

                    if (B)
                        for (int k = 1; k <= n; k++)
                            swap(B[i][k], B[j][k]);
                    break;
                }

            if (!A[i][i])
                continue;
        }

        int inv = qpow(A[i][i], p - 2);

        for (int j = 1; j <= n; j++)
            if (i != j && A[j][i]) {
                int t = (long long)A[j][i] * inv % p;

                for (int k = i; k <= n; k++)
                    if (A[i][k])
                        A[j][k] = (A[j][k] - (long long)t * A[i][k]) % p;

                if (B)
                    for (int k = 1; k <= n; k++)
                        if (B[i][k])
                            B[j][k] = (B[j][k] - (long long)t * B[i][k])%p;
            }
    }

    if (B)
        for (int i = 1; i <= n; i++) {
            int inv = qpow(A[i][i], p - 2);

            for (int j = 1; j <= n; j++)
                if (B[i][j])
                    B[i][j] = (long long)B[i][j] * inv % p;
        }
}

// 消去一行一列 O(n^2)
void eliminate(int r, int c) {
    row[r] = col[c] = true; // 已经被消掉

    int inv = qpow(B[r][c], p - 2);

    for (int i = 1; i <= n; i++)
        if (!row[i] && B[i][c]) {
            int t = (long long)B[i][c] * inv % p;

            for (int j = 1; j <= n; j++)
                if (!col[j] && B[r][j])
                    B[i][j] = (B[i][j] - (long long)t * B[r][j]) % p;
        }
}
```

3.7.2 带花树

```
// 带花树通常比高斯消元快很多，但在只需要求最大匹配大小的时候并没有高斯消元好写
// 当然输出方案要方便很多

// 全局数组与变量定义
vector<int> G[maxn];
int girl[maxn], f[maxn], t[maxn], p[maxn], vis[maxn], tim, q[maxn], head, tail;
int n, m;


// 封装好的主过程 O(nm)
int blossom() {
    int ans = 0;

    for (int i = 1; i <= n; i++)
        if (!girl[i])
            ans += bfs(i);

    return ans;
```

```cpp
}


// bfs找增广路 O(m)
bool bfs(int s) {
    memset(t, 0, sizeof(t));
    memset(p, 0, sizeof(p));

    for (int i = 1; i <= n; i++)
        f[i] = i; // 并查集

    head = tail = 0;
    q[tail++] = s;
    t[s] = 1;

    while (head != tail) {
        int x = q[head++];
        for (int y : G[x]) {
            if (findroot(y) == findroot(x) || t[y] == 2)
                continue;

            if (!t[y]) {
                t[y] = 2;
                p[y] = x;

                if (!girl[y]) {
                    for (int u = y, t; u; u = t) {
                        t = girl[p[u]];
                        girl[p[u]] = u;
                        girl[u] = p[u];
                    }
                    return true;
                }

                t[girl[y]] = 1;
                q[tail++] = girl[y];
            }
            else if (t[y] == 1) {
                int z = LCA(x, y);

                shrink(x, y, z);
                shrink(y, x, z);
            }
        }
    }

    return false;
}

//缩奇环 O(n)
void shrink(int x, int y, int z) {
    while (findroot(x) != z) {
        p[x] = y;
        y = girl[x];

        if (t[y] == 2) {
            t[y] = 1;
            q[tail++] = y;
        }

        if (findroot(x) == x)
            f[x] = z;
        if (findroot(y) == y)
            f[y] = z;

        x = p[y];
    }
}

//暴力找LCA O(n)
int LCA(int x, int y) {
    tim++;
    while (true) {
        if (x) {
            x = findroot(x);

            if (vis[x] == tim)
                return x;
            else {
                vis[x] = tim;
                x = p[girl[x]];
            }
        }
        swap(x, y);
    }
}

//并查集的查找 O(1)
int findroot(int x) {
    return x == f[x] ? x : (f[x] = findroot(f[x]));
}
```

3.7.3 带权带花树

Copy-and-pasted from the template of *Imperisible Night*.
(有一说一这玩意实在太难写了，抄之前建议先想想算法是不是假的或者有 SB 做法。)

```cpp
//maximum weight blossom,  change g[u][v].w to INF - g[u][v].w when minimum weight blossom is needed
//type of ans is long long
//replace all int to long long if weight of edge is long long

struct WeightGraph {
    static const int INF = INT_MAX;
    static const int MAXN = 400;
    struct edge{
        int u, v, w;
        edge() {}
        edge(int u, int v, int w): u(u), v(v), w(w) {}
    };
    int n, n_x;
    edge g[MAXN * 2 + 1][MAXN * 2 + 1];
    int lab[MAXN * 2 + 1];
    int match[MAXN * 2 + 1], slack[MAXN * 2 + 1], st[MAXN * 2 + 1], pa[MAXN * 2 + 1];
    int flower_from[MAXN * 2 + 1][MAXN+1], S[MAXN * 2 + 1], vis[MAXN * 2 + 1];
    vector<int> flower[MAXN * 2 + 1];
    queue<int> q;
    inline int e_delta(const edge &e){ // does not work inside blossoms
        return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2;
    }
    inline void update_slack(int u, int x){
        if(!slack[x] || e_delta(g[u][x]) < e_delta(g[slack[x]][x]))
            slack[x] = u;
    }
    inline void set_slack(int x){
        slack[x] = 0;
        for(int u = 1;u <= n; ++u)
            if(g[u][x].w > 0 && st[u] != x && S[st[u]] == 0)
                update_slack(u, x);
    }
    void q_push(int x){
        if(x <= n)q.push(x);
        else for(size_t i = 0;i < flower[x].size(); i++)
            q_push(flower[x][i]);
    }
```

```
    inline void set_st(int x, int b){
        st[x]=b;
        if(x > n) for(size_t i = 0;i < flower[x].size(); ++i)
                    set_st(flower[x][i], b);
    }
    inline int get_pr(int b, int xr){
        int pr = find(flower[b].begin(), flower[b].end(), xr) - flower[b].begin();
        if(pr % 2 == 1){
            reverse(flower[b].begin() + 1, flower[b].end());
            return (int)flower[b].size() - pr;
        } else return pr;
    }
    inline void set_match(int u, int v){
        match[u]=g[u][v].v;
        if(u > n){
            edge e=g[u][v];
            int xr = flower_from[u][e.u], pr=get_pr(u, xr);
            for(int i = 0;i < pr; ++i)
                set_match(flower[u][i], flower[u][i ^ 1]);
            set_match(xr, v);
            rotate(flower[u].begin(), flower[u].begin()+pr, flower[u].end());
        }
    }
    inline void augment(int u, int v){
        for(; ; ){
            int xnv=st[match[u]];
            set_match(u, v);
            if(!xnv)return;
            set_match(xnv, st[pa[xnv]]);
            u=st[pa[xnv]], v=xnv;
        }
    }
    inline int get_lca(int u, int v){
        static int t=0;
        for(++t; u || v; swap(u, v)){
            if(u == 0)continue;
            if(vis[u] == t)return u;
            vis[u] = t;
            u = st[match[u]];
            if(u) u = st[pa[u]];
        }
        return 0;
    }
    inline void add_blossom(int u, int lca, int v){
        int b = n + 1;
        while(b <= n_x && st[b]) ++b;
        if(b > n_x) ++n_x;
        lab[b] = 0, S[b] = 0;
        match[b] = match[lca];
        flower[b].clear();
        flower[b].push_back(lca);
        for(int x = u, y; x != lca; x = st[pa[y]]) {
            flower[b].push_back(x),
            flower[b].push_back(y = st[match[x]]),
            q_push(y);
        }
        reverse(flower[b].begin() + 1, flower[b].end());
        for(int x = v, y; x != lca; x = st[pa[y]]) {
            flower[b].push_back(x),
            flower[b].push_back(y = st[match[x]]),
            q_push(y);
        }
        set_st(b, b);
        for(int x = 1; x <= n_x; ++x) g[b][x].w = g[x][b].w = 0;
        for(int x = 1; x <= n; ++x) flower_from[b][x] = 0;
        for(size_t i = 0 ; i < flower[b].size(); ++i){
            int xs = flower[b][i];
            for(int x = 1; x <= n_x; ++x)
                if(g[b][x].w == 0 || e_delta(g[xs][x]) < e_delta(g[b][x]))
                    g[b][x] = g[xs][x], g[x][b] = g[x][xs];
            for(int x = 1;x <= n; ++x)
                if(flower_from[xs][x]) flower_from[b][x] = xs;
        }
        set_slack(b);
    }
    inline void expand_blossom(int b){ // S[b]  ==  1
        for(size_t i = 0; i < flower[b].size(); ++i)
            set_st(flower[b][i], flower[b][i]);
        int xr = flower_from[b][g[b][pa[b]].u], pr = get_pr(b, xr);
        for(int i = 0; i < pr; i += 2){
            int xs = flower[b][i], xns = flower[b][i + 1];
            pa[xs] = g[xns][xs].u;
            S[xs] = 1, S[xns] = 0;
            slack[xs] = 0, set_slack(xns);
            q_push(xns);
        }
        S[xr] = 1, pa[xr] = pa[b];
        for(size_t i = pr + 1;i < flower[b].size(); ++i){
            int xs = flower[b][i];
            S[xs] = -1, set_slack(xs);
        }
        st[b] = 0;
    }
    inline bool on_found_edge(const edge &e){
        int u = st[e.u], v = st[e.v];
        if(S[v] == -1){
            pa[v] = e.u, S[v] = 1;
            int nu = st[match[v]];
            slack[v] = slack[nu] = 0;
            S[nu] = 0, q_push(nu);
        }else if(S[v] == 0){
            int lca = get_lca(u, v);
            if(!lca) return augment(u, v), augment(v, u), true;
            else add_blossom(u, lca, v);
        }
        return false;
    }
    inline bool matching(){
        memset(S + 1, -1, sizeof(int) * n_x);
        memset(slack + 1, 0, sizeof(int) * n_x);
        q = queue<int>();
        for(int x = 1;x <= n_x; ++x)
            if(st[x] == x && !match[x]) pa[x]=0, S[x]=0, q_push(x);
        if(q.empty())return false;
        for(;;){
            while(q.size()){
                int u = q.front();q.pop();
                if(S[st[u]] == 1)continue;
                for(int v = 1;v <= n; ++v)
                    if(g[u][v].w > 0 && st[u] != st[v]) {
                        if(e_delta(g[u][v]) == 0){
                            if(on_found_edge(g[u][v]))return true;
                        }else update_slack(u, st[v]);
                    }
            }
```

```
            int d = INF;
            for(int b = n + 1; b <= n_x;++b)
                if(st[b] == b && S[b] == 1)d = min(d, lab[b]/2);
            for(int x = 1; x <= n_x; ++x)
                if(st[x] == x && slack[x]){
                    if(S[x] == -1)d = min(d, e_delta(g[slack[x]][x]));
                    else if(S[x] == 0)d = min(d, e_delta(g[slack[x]][x])/2);
                }
            for(int u = 1; u <= n; ++u){
                if(S[st[u]] == 0){
                    if(lab[u] <= d)return 0;
                    lab[u] -= d;
                }else if(S[st[u]] == 1)lab[u] += d;
            }
            for(int b = n+1; b <= n_x; ++b)
                if(st[b] == b){
                    if(S[st[b]] == 0) lab[b] += d * 2;
                    else if(S[st[b]] == 1) lab[b] -= d * 2;
                }
            q=queue<int>();
            for(int x = 1; x <= n_x; ++x)
                if(st[x] == x && slack[x] && st[slack[x]] != x && e_delta(g[slack[x]][x]) == 0)
                    if(on_found_edge(g[slack[x]][x]))return true;
            for(int b = n + 1; b <= n_x; ++b)
                if(st[b] == b && S[b] == 1 && lab[b] == 0)expand_blossom(b);
        }
        return false;
    }
    inline pair<long long, int> solve(){
        memset(match + 1, 0, sizeof(int) * n);
        n_x = n;
        int n_matches = 0;
        long long tot_weight = 0;
        for(int u = 0; u <= n; ++u) st[u] = u, flower[u].clear();
        int w_max = 0;
        for(int u = 1; u <= n; ++u)
            for(int v = 1; v <= n; ++v){
                flower_from[u][v] = (u == v ? u : 0);
                w_max = max(w_max, g[u][v].w);
            }
        for(int u = 1; u <= n; ++u) lab[u] = w_max;
        while(matching()) ++n_matches;
        for(int u = 1; u <= n; ++u)
            if(match[u] && match[u] < u)
                tot_weight += g[u][match[u]].w;
        return make_pair(tot_weight, n_matches);
    }
    inline void init(){
        for(int u = 1; u <= n; ++u)
            for(int v = 1; v <= n; ++v)
                g[u][v]=edge(u, v, 0);
    }
};
```

3.8 支配树

记得建反图!

```
vector<int> G[maxn], R[maxn], son[maxn]; // R是反图, son存的是sdom树上的儿子

int ufs[maxn];

int idom[maxn], sdom[maxn], anc[maxn]; // anc: sdom的dfn最小的祖先

int p[maxn], dfn[maxn], id[maxn], tim;

int findufs(int x) {
    if (ufs[x] == x)
        return x;

    int t = ufs[x];
    ufs[x] = findufs(ufs[x]);

    if (dfn[sdom[anc[x]]] > dfn[sdom[anc[t]]])
        anc[x] = anc[t];

    return ufs[x];
}

void dfs(int x) {
    dfn[x] = ++tim;
    id[tim] = x;
    sdom[x] = x;

    for (int y : G[x])
        if (!dfn[y]) {
            p[y] = x;
            dfs(y);
        }
}

void get_dominator(int n) {
    for (int i = 1; i <= n; i++)
        ufs[i] = anc[i] = i;

    dfs(1);

    for (int i = n; i > 1; i--) {
        int x = id[i];

        for (int y : R[x])
            if (dfn[y]) {
                findufs(y);
                if (dfn[sdom[x]] > dfn[sdom[anc[y]]])
                    sdom[x] = sdom[anc[y]];
            }

        son[sdom[x]].push_back(x);
        ufs[x] = p[x];

        for (int u : son[p[x]]) {
            findufs(u);
            idom[u] = (sdom[u] == sdom[anc[u]] ? p[x] : anc[u]);
        }

        son[p[x]].clear();
    }

    for (int i = 2; i <= n; i++) {
        int x = id[i];

        if (idom[x] != sdom[x])
            idom[x] = idom[idom[x]];

        son[idom[x]].push_back(x);
    }
}
```

3.9 2-SAT

如果限制满足对称性（每个命题的逆否命题对应的边也存在），那么可以使用 Tarjan 算法求 SCC 搞定。
具体来说，如果某个变量的两个点在同一 SCC 中则显然无解，否则按拓扑序倒序尝试选择每个SCC即可。
由于 Tarjan 算法的特性，找到 SCC 的顺序就是拓扑序 **倒序**，所以判断完是否有解之后，每个变量只需要取 SCC 编号 **较小** 的那个即可。

```
if (!ok)
    printf("IMPOSSIBLE\n");
else {
    printf("POSSIBLE\n");

    for (int i = 1; i <= n; i++)
        printf("%d%c", sccid[i * 2 - 1] > sccid[i * 2],
          ↪ i < n ? ' ' : '\n');
}
```

如果要字典序最小就用 DFS，注意可以压位优化。另外这份代码是 0-base 的。

```
bool vis[maxn];
int stk[maxn], top;

// 主函数
for (int i = 0; i < n; i += 2)
    if (!vis[i] && !vis[i ^ 1]) {
            top = 0;
            if (!dfs(i)) {
                while (top)
                    vis[stk[top--]] = false;

                if (!dfs(i + 1)) {
                    bad = true;
                    break;
                }
            }
        }
// 最后stk中的所有元素就是选中的值

// dfs
bool dfs(int x) {
    if (vis[x ^ 1])
        return false;

    if (vis[x])
        return true;

    vis[x] = true;
    stk[++top] = x;

    for (int i = 0; i < (int)G[x].size(); i++)
        if (!dfs(G[x][i]))
            return false;

    return true;
}
```

3.10 最大流

3.10.1 Dinic

```
// 注意Dinic适用于二分图或分层图，对于一般稀疏图ISAP更优，
  ↪ 稠密图则HLPP更优

struct edge {
    int to, cap, prev;
} e[maxe * 2];

int last[maxn], len, d[maxn], cur[maxn], q[maxn];

// main函数里要初始化
memset(last, -1, sizeof(last));

void AddEdge(int x, int y, int z) {
    e[len].to = y;
    e[len].cap = z;
    e[len].prev = last[x];
    last[x] = len++;
}

void addedge(int x, int y, int z) {
    AddEdge(x, y, z);
    AddEdge(y, x, 0);
}

void bfs() {
    int head = 0, tail = 0;
    memset(d, -1, sizeof(int) * (t + 5));
    q[tail++] = s;
    d[s] = 0;

    while (head != tail) {
        int x = q[head++];
        for (int i = last[x]; ~i; i = e[i].prev)
            if (e[i].cap > 0 && d[e[i].to] == -1) {
                d[e[i].to] = d[x] + 1;
                q[tail++] = e[i].to;
            }
    }
}

int dfs(int x, int a) {
    if (x == t || !a)
        return a;

    int flow = 0, f;
    for (int &i = cur[x]; ~i; i = e[i].prev)
        if (e[i].cap > 0 && d[e[i].to] == d[x] + 1 &&
          ↪ (f = dfs(e[i].to, min(e[i].cap,a)))) {

            e[i].cap -= f;
            e[i^1].cap += f;
            flow += f;
            a -= f;

            if (!a)
                break;
        }

    return flow;
}

int Dinic() {
    int flow = 0;
    while (bfs(), ~d[t]) {
        memcpy(cur, last, sizeof(int) * (t + 5));
        flow += dfs(s, inf);
    }
    return flow;
}
```

3.10.2 ISAP

可能有毒，慎用。

```
// 注意ISAP适用于一般稀疏图，对于二分图或分层图情
  ↪ 况Dinic比较优，稠密图则HLPP更优

// 边的定义
// 这里没有记录起点和反向边，因为反向边即为正向边xor 1，
  ↪ 起点即为反向边的终点
```

```cpp
struct edge {
    int to, cap, prev;
} e[maxe * 2];

// 全局变量和数组定义
int last[maxn], cnte = 0, d[maxn], p[maxn], c[maxn], cur[maxn], q[maxn];
int n, m, s, t; // s, t一定要开成全局变量

void AddEdge(int x, int y, int z) {
    e[cnte].to = y;
    e[cnte].cap = z;
    e[cnte].prev = last[x];
    last[x] = cnte++;
}

void addedge(int x, int y, int z) {
    AddEdge(x, y, z);
    AddEdge(y, x, 0);
}

// 预处理到t的距离标号
// 在测试数据组数较少时可以省略，把所有距离标号初始化为0
void bfs() {
    memset(d, -1, sizeof(d));

    int head = 0, tail = 0;
    d[t] = 0;
    q[tail++] = t;

    while (head != tail) {
        int x = q[head++];
        c[d[x]]++;

        for (int i = last[x]; ~i; i = e[i].prev)
            if (e[i ^ 1].cap && d[e[i].to] == -1) {
                d[e[i].to] = d[x] + 1;
                q[tail++] = e[i].to;
            }
    }
}

// augment函数 O(n) 沿增广路增广一次，返回增广的流量
int augment() {
    int a = (~0u) >> 1; // INT_MAX

    for (int x = t; x != s; x = e[p[x] ^ 1].to)
        a = min(a, e[p[x]].cap);

    for (int x = t; x != s; x = e[p[x] ^ 1].to) {
        e[p[x]].cap -= a;
        e[p[x] ^ 1].cap += a;
    }

    return a;
}

// 主过程 O(n^2 m)，返回最大流的流量
// 注意这里的n是编号最大值，在这个值不为n的时候一定要开个变量记录下来并修改代码
int ISAP() {
    bfs();

    memcpy(cur, last, sizeof(cur));

    int x = s, flow = 0;

    while (d[s] < n) {
        if (x == t) { // 如果走到了t就增广一次，并返回s重新找增广路
            flow += augment();
            x = s;
        }

        bool ok = false;
        for (int &i = cur[x]; ~i; i = e[i].prev)
            if (e[i].cap && d[x] == d[e[i].to] + 1) {
                p[e[i].to] = i;
                x = e[i].to;

                ok = true;
                break;
            }

        if (!ok) { // 修改距离标号
            int tmp = n - 1;
            for (int i = last[x]; ~i; i = e[i].prev)
                if (e[i].cap)
                    tmp = min(tmp, d[e[i].to] + 1);

            if (!--c[d[x]])
                break; // gap优化，一定要加上

            c[d[x] = tmp]++;
            cur[x] = last[x];

            if(x != s)
                x = e[p[x] ^ 1].to;
        }
    }
    return flow;
}

// 重要! main函数最前面一定要加上如下初始化
memset(last, -1, sizeof(last));
```

3.10.3 HLPP

```cpp
constexpr int maxn = 1205, maxe = 120005;

struct edge {
    int to, cap, prev;
} e[maxe * 2];

int n, m, s, t;
int last[maxn], cnte;
int h[maxn], gap[maxn * 2];
long long ex[maxn]; // 多余流量
bool inq[maxn];

struct cmp {
    bool operator() (int x, int y) const {
        return h[x] < h[y];
    }
};

priority_queue<int, vector<int>, cmp> heap;

void adde(int x, int y, int z) {
    e[cnte].to = y;
    e[cnte].cap = z;
    e[cnte].prev = last[x];
    last[x] = cnte++;
}

void addedge(int x, int y, int z) {
    adde(x, y, z);
    adde(y, x, 0);
}

bool bfs() {
    static int q[maxn];

```

```
    fill(h, h + n + 1, 2 * n); // 如果没有全局的n, 记得改这里
    int head = 0, tail = 0;
    q[tail++] = t;
    h[t] = 0;

    while (head < tail) {
        int x = q[head++];
        for (int i = last[x]; ~i; i = e[i].prev)
            if (e[i ^ 1].cap && h[e[i].to] > h[x] + 1) {
                h[e[i].to] = h[x] + 1;
                q[tail++] = e[i].to;
            }
    }

    return h[s] < 2 * n;
}

void push(int x) {
    for (int i = last[x]; ~i; i = e[i].prev)
        if (e[i].cap && h[x] == h[e[i].to] + 1) {
            int d = min(ex[x], (long long)e[i].cap);

            e[i].cap -= d;
            e[i ^ 1].cap += d;
            ex[x] -= d;
            ex[e[i].to] += d;

            if (e[i].to != s && e[i].to != t && !inq[e[i].to]) {
                heap.push(e[i].to);
                inq[e[i].to] = true;
            }

            if (!ex[x])
                break;
        }
}

void relabel(int x) {
    h[x] = 2 * n;

    for (int i = last[x]; ~i; i = e[i].prev)
        if (e[i].cap)
            h[x] = min(h[x], h[e[i].to] + 1);
}

long long hlpp() {
    if (!bfs())
        return 0;

    // memset(gap, 0, sizeof(int) * 2 * n);
    h[s] = n;

    for (int i = 1; i <= n; i++)
        gap[h[i]]++;

    for (int i = last[s]; ~i; i = e[i].prev)
        if (e[i].cap) {
            int d = e[i].cap;

            e[i].cap -= d;
            e[i ^ 1].cap += d;
            ex[s] -= d;
            ex[e[i].to] += d;

            if (e[i].to != s && e[i].to != t && !inq[e[i].to]) {
                heap.push(e[i].to);
                inq[e[i].to] = true;
            }
        }

    while (!heap.empty()) {
        int x = heap.top();
        heap.pop();
        inq[x] = false;

        push(x);
        if (ex[x]) {
            if (!--gap[h[x]]) { // gap
                for (int i = 1; i <= n; i++)
                    if (i != s && i != t && h[i] > h[x])
                        h[i] = n + 1;
            }

            relabel(x);
            ++gap[h[x]];
            heap.push(x);
            inq[x] = true;
        }
    }

    return ex[t];
}

//记得初始化
memset(last, -1, sizeof(last));
```

3.11 费用流

3.11.1 SPFA 费用流

```
constexpr int maxn = 20005, maxm = 200005;

struct edge {
    int to, prev, cap, w;
} e[maxm * 2];

int last[maxn], cnte, d[maxn], p[maxn]; // 记得把last初始化成-1, 不然会死循环
bool inq[maxn];

void spfa(int s) {

    memset(d, -63, sizeof(d));
    memset(p, -1, sizeof(p));

    queue<int> q;

    q.push(s);
    d[s] = 0;

    while (!q.empty()) {
        int x = q.front();
        q.pop();
        inq[x] = false;

        for (int i = last[x]; ~i; i = e[i].prev)
            if (e[i].cap) {
                int y = e[i].to;

                if (d[x] + e[i].w > d[y]) {
                    p[y] = i;
                    d[y] = d[x] + e[i].w;
                    if (!inq[y]) {
                        q.push(y);
                        inq[y] = true;
                    }
                }
            }
```

```
    }
}

int mcmf(int s, int t) {
    int ans = 0;

    while (spfa(s), d[t] > 0) {
        int flow = 0x3f3f3f3f;
        for (int x = t; x != s; x = e[p[x] ^ 1].to)
            flow = min(flow, e[p[x]].cap);

        ans += flow * d[t];

        for (int x = t; x != s; x = e[p[x] ^ 1].to) {
            e[p[x]].cap -= flow;
            e[p[x] ^ 1].cap += flow;
        }
    }

    return ans;
}

void add(int x, int y, int c, int w) {
    e[cnte].to = y;
    e[cnte].cap = c;
    e[cnte].w = w;

    e[cnte].prev = last[x];
    last[x] = cnte++;
}

void addedge(int x, int y, int c, int w) {
    add(x, y, c, w);
    add(y, x, 0, -w);
}
```

3.11.2 Dijkstra 费用流

也叫原始-对偶费用流。
原理和求多源最短路的 Johnson 算法是一样的，都是给每个点维护一个势 h_u，使得对任何有向边 $u \to v$ 都满足 $w + h_u - h_v \geq 0$。
如果有负费用则从 s 开始跑一遍 SPFA 初始化，否则可以直接初始化 $h_u = 0$。
每次增广时得到的路径长度就是 $d_{s,t} + h_t$，增广之后让所有 $h_u = h'_u + d'_{s,u}$，直到 $d_{s,t} = +\infty$（最小费用最大流）或 $d_{s,t} \geq 0$（最小费用流）为止。
注意最大费用流要转成取负之后的最小费用流，因为 Dijkstra 求的是最短路。

```
struct edge {
    int to, cap, prev, w;
} e[maxe * 2];

int last[maxn], cnte;

long long d[maxn], h[maxn];
int p[maxn];

bool vis[maxn];
int s, t;

void Adde(int x, int y, int z, int w) {
    e[cnte].to = y;
    e[cnte].cap = z;
    e[cnte].w = w;
    e[cnte].prev = last[x];
    last[x] = cnte++;
}

void addedge(int x, int y, int z, int w) {
    Adde(x, y, z, w);
    Adde(y, x, 0, -w);
}

void dijkstra() {
    memset(d, 63, sizeof(d));
    memset(vis, 0, sizeof(vis));

    priority_queue<pair<long long, int> > heap;

    d[s] = 0;
    heap.push(make_pair(0ll, s));

    while (!heap.empty()) {
        int x = heap.top().second;
        heap.pop();

        if (vis[x])
            continue;

        vis[x] = true;
        for (int i = last[x]; ~i; i = e[i].prev)
            if (e[i].cap > 0 && d[e[i].to] > d[x] + e[i].w + h[x] - h[e[i].to]) {
                d[e[i].to] = d[x] + e[i].w + h[x] - h[e[i].to];
                p[e[i].to] = i;
                heap.push(make_pair(-d[e[i].to], e[i].to));
            }
    }
}

pair<long long, long long> mcmf() {
    /*
    spfa();
    for (int i = 1; i <= t; i++)
        h[i] = d[i];
    // 如果初始有负权就像这样跑一遍SPFA预处理
    */

    long long flow = 0, cost = 0;

    while (dijkstra(), d[t] < 0x3f3f3f3f) {
        for (int i = 1; i <= t; i++)
            h[i] += d[i];

        int a = 0x3f3f3f3f;

        for (int x = t; x != s; x = e[p[x] ^ 1].to)
            a = min(a, e[p[x]].cap);

        flow += a;
        cost += (long long)a * h[t];

        for (int x = t; x != s; x = e[p[x] ^ 1].to) {
            e[p[x]].cap -= a;
            e[p[x] ^ 1].cap += a;
        }

    }

    return make_pair(flow, cost);
}

// 记得初始化
memset(last, -1, sizeof(last));
```

3.11.3 预流推进费用流（可处理负环）

搬来的，不是很懂什么原理，待研究。复杂度 $O(nm \log C)$。

```cpp
// Push-Relabel implementation of the cost-scaling algorithm
// Runs in O( <max_flow> * log(V * max_edge_cost)) = O(V^3 * log(V * C))
// Really fast in practice, 3e4 edges are fine.
// Operates on integers, costs are multiplied by N!!

#include <bits/stdc++.h>
using namespace std;

// source: unknown
template<typename flow_t = int, typename cost_t = int>
struct mcSFlow {
    struct Edge {
        cost_t c;
        flow_t f;
        int to, rev;
        Edge(int _to, cost_t _c, flow_t _f, int _rev): c(_c), f(_f), to(_to), rev(_rev) {}
    };

    static constexpr cost_t INFCOST = numeric_limits<cost_t>::max() / 2;

    cost_t eps;
    int N, S, T;
    vector<vector<Edge>> G;
    vector<unsigned int> isq, cur;
    vector<flow_t> ex;
    vector<cost_t> h;

    mcSFlow(int _N, int _S, int _T): eps(0), N(_N), S(_S), T(_T), G(_N) {}

    void add_edge(int a, int b, flow_t cap, cost_t cost) {
        assert(cap >= 0);
        assert(a >= 0 && a < N && b >= 0 && b < N);

        if (a == b) {
            assert(cost >= 0);
            return;
        }

        cost *= N;
        eps = max(eps, abs(cost));
        G[a].emplace_back(b, cost, cap, G[b].size());
        G[b].emplace_back(a, -cost, 0, G[a].size() - 1);
    }

    void add_flow(Edge &e, flow_t f) {
        Edge &back = G[e.to][e.rev];

        if (!ex[e.to] && f)
            hs[h[e.to]].push_back(e.to);

        e.f -= f;
        ex[e.to] += f;
        back.f += f;
        ex[back.to] -= f;
    }

    vector<vector<int>> hs;
    vector<int> co;

    flow_t max_flow() {
        ex.assign(N, 0);
        h.assign(N, 0);
        hs.resize(2 * N);
        co.assign(2 * N, 0);
        cur.assign(N, 0);
        h[S] = N;
        ex[T] = 1;
        co[0] = N - 1;

        for (auto &e : G[S])
            add_flow(e, e.f);

        if (hs[0].size())
            for (int hi = 0; hi >= 0;) {
                int u = hs[hi].back();
                hs[hi].pop_back();

                while (ex[u] > 0) { // discharge u
                    if (cur[u] == G[u].size()) {
                        h[u] = 1e9;

                        for (unsigned int i = 0; i < G[u].size(); ++i) {
                            auto &e = G[u][i];

                            if (e.f && h[u] > h[e.to] + 1) {
                                h[u] = h[e.to] + 1, cur[u] = i;
                            }
                        }

                        if (++co[h[u]], !--co[hi] && hi < N)
                            for (int i = 0; i < N; ++i)
                                if (hi < h[i] && h[i] < N) {
                                    --co[h[i]];
                                    h[i] = N + 1;
                                }

                        hi = h[u];
                    }
                    else if (G[u][cur[u]].f && h[u] == h[G[u][cur[u]].to] + 1)
                        add_flow(G[u][cur[u]], min(ex[u], G[u][cur[u]].f));
                    else
                        ++cur[u];
                }

                while (hi >= 0 && hs[hi].empty())
                    --hi;
            }

        return -ex[S];
    }

    void push(Edge &e, flow_t amt) {
        if (e.f < amt)
            amt = e.f;

        e.f -= amt;
        ex[e.to] += amt;
        G[e.to][e.rev].f += amt;
        ex[G[e.to][e.rev].to] -= amt;
    }

    void relabel(int vertex) {
        cost_t newHeight = -INFCOST;

        for (unsigned int i = 0; i < G[vertex].size(); ++i) {
            Edge const &e = G[vertex][i];

```

```
            if (e.f && newHeight < h[e.to] - e.c) {
                newHeight = h[e.to] - e.c;
                cur[vertex] = i;
            }
        }

        h[vertex] = newHeight - eps;
    }

    static constexpr int scale = 2;

    pair<flow_t, cost_t> minCostMaxFlow() {
        cost_t retCost = 0;

        for (int i = 0; i < N; ++i)
            for (Edge &e : G[i])
                retCost += e.c * (e.f);

        //find max-flow
        flow_t retFlow = max_flow();
        h.assign(N, 0);
        ex.assign(N, 0);
        isq.assign(N, 0);
        cur.assign(N, 0);
        queue<int> q;

        for (; eps; eps >>= scale) {
            //refine
            fill(cur.begin(), cur.end(), 0);

            for (int i = 0; i < N; ++i)
                for (auto &e : G[i])
                    if (h[i] + e.c - h[e.to] < 0 &&
                      ↪ e.f)
                        push(e, e.f);

            for (int i = 0; i < N; ++i) {
                if (ex[i] > 0) {
                    q.push(i);
                    isq[i] = 1;
                }
            }

            // make flow feasible
            while (!q.empty()) {
                int u = q.front();
                q.pop();
                isq[u] = 0;

                while (ex[u] > 0) {
                    if (cur[u] == G[u].size())
                        relabel(u);

                    for (unsigned int &i = cur[u],
                      ↪ max_i = G[u].size(); i < max_i;
                      ↪ ++i) {
                        Edge &e = G[u][i];

                        if (h[u] + e.c - h[e.to] < 0) {
                            push(e, ex[u]);

                            if (ex[e.to] > 0 &&
                              ↪ isq[e.to] == 0) {
                                q.push(e.to);
                                isq[e.to] = 1;
                            }

                            if (ex[u] == 0)
                                break;
                        }
                    }
                }
            }

            if (eps > 1 && eps >> scale == 0)
                eps = 1 << scale;
        }

        for (int i = 0; i < N; ++i)
            for (Edge &e : G[i])
                retCost -= e.c * (e.f);

        return make_pair(retFlow, retCost / 2 / N);
    }

    flow_t getFlow(Edge const &e) {
        return G[e.to][e.rev].f;
    }
};

int main() {

    int n, m;
    scanf("%d%d", &n, &m);

    mcSFlow<long long, long long> mcmf(n, 0, n - 1);

    while (m--) {
        int x, y, z, w;
        scanf("%d%d%d%d", &x, &y, &z, &w);

        mcmf.add_edge(x - 1, y - 1, z, w);
    }

    auto [flow, cost] = mcmf.minCostMaxFlow();

    printf("%lld %lld\n", flow, cost);

    return 0;
}
```

3.12 网络流原理

3.12.1 最大流

- **判断一条边是否必定满流**

在残量网络中跑一遍 Tarjan，如果某条满流边的两端处于同一 SCC 中，则说明它不一定满流。(因为可以找出包含反向边的环，增广之后就不满流了。)

3.12.2 最小割

首先牢记最小割的定义：选权值和尽量小的一些边，使得删除这些边之后 S 无法到达 T。

最小割输出一种方案 在残量网络上从 S 开始 floodfill，源点可达的记为 S 集，不可达的记为 T 集。如果一条边的起点在 S 集而终点在 T 集，就将其加入最小割中。

最小割的可行边与必须边

- 可行边：满流，且残量网络上不存在 u 到 v 的路径，也就是 u 和 v 不在同一 SCC 中。(实际上也就是最大流必定满流的边。)
- 必须边：满流，且残量网络上 S 可达 u，v 可达 T。

字典序最小的最小割 直接按字典序从小到大的顺序依次判断每条边能否在最小割中即可。
如果一条边是可行边，我们就需要把它删掉，同时进行退流，$u \to s$ 和 $t \to v$ 都退掉等同于这条边容量的流量。
退流用 Dinic 实现即可。

3.12.3 上下界网络流

无源汇上下界可行流 新建源汇 S', T'，然后如图转化每一条边。

在新图跑一遍最大流之后检查一遍辅助边，如果有辅助边没满流则无解，否则把每条边的流量加上 b 就是一组可行方案。

有源汇上下界最大流 如果不需要判断是否有解的话，可以直接按照和上面一样的方法转化。因为附加边实际上算了两次流量，所以最终答案应该减掉所有下界之和。
(另外这里如果要压缩附加边的话，不能像无源汇的情况一样对每个点只开一个变量统计溢出的流量。正确的做法是进出流量各统计一下，每个点连两条附加边。)
如果需要判有解的话会出一点问题。这时候就需要转化成无源汇的情况，验证有解之后撤掉 T 到 S 的那条附加边，再从 S 到 T 跑一遍最大流。

```
int ex[maxn], id[maxn];

int main() {

    memset(last, -1, sizeof(last));

    int n, m, src, sink;
    scanf("%d%d%d%d", &n, &m, &src, &sink);
    s = n + 1;
    t = n + 2;

    while (m--) {
        int x, y, b, c;
        scanf("%d%d%d%d", &x, &y, &b, &c);

        addedge(x, y, c - b);

        ex[y] += b;
        ex[x] -= b;
    }

    for (int i = 1; i <= n; i++) {
        id[i] = cnte;

        if (ex[i] >= 0)
            addedge(s, i, ex[i]);
        else
            addedge(i, t, -ex[i]);
    }

    addedge(sink, src, (~0u) >> 1);

    Dinic();

    if (any_of(id + 1, id + n + 1, [] (int i) {return
      ↪ (bool)e[i].cap;}))
        printf("please go home to sleep\n");
    else {
        int flow = e[cnte - 1].cap;
        e[cnte - 1].cap = e[cnte - 2].cap = 0;
        s = src;
        t = sink;

        printf("%d\n", flow + Dinic());
    }

    return 0;
}
```

有源汇上下界最小流 按照上面的方法转换后先跑一遍最大流，然后撤掉超级源汇和附加边，反过来跑一次最大流退流，最大流减去退掉的流量就是最小流。

3.12.4 常见建图方法

- **最大流/费用流**

流量不是很多的时候可以理解成很多条路径，并且每条边可以经过的次数有限。

- **最小割**

常用的模型是 **最大权闭合子图**。当然它并不是万能的，因为限制条件可以带权值。

1. 如果某些点全部在 S 集或者 T 集，则获得一个正的收益
   把这个条件建成一个点，向要求的点连 $+\infty$ 边，然后 s 向它连 $+\infty$ 边。(如果是 T 集就都反过来)
   那么如果它在 S 集，就一定满足它要求的点都在 S 集，反之如果是 T 集亦然。
2. 如果两个点不在同一集合中，则需要付出代价
   建双向边，那显然如果它们不在同一集合中就需要割掉中间的边，付出对应的代价。
3. 二分图，如果相邻的两个点在同一集合则需要付出代价
   染色后给一半的点反转源汇，就转换成上面的问题了。

3.12.5 例题

- 费用流

1. 序列上选总和尽量大的数，但连续 k 个数中最多选 p 个
   费用流建图，先建一条 $n+1$ 个点的无限容量的链表示不选，然后每个 i 向 $(i+k)$ 连边费用是第 i 个位置的权值。答案是流量为 p 的最大费用流，因为条件等价于选 p 次并且每次选的所有数间隔都至少是 k。
2. 除此之外还要求连续 k 个数中最少选 q 个
   任选一个位置把图前后切开，会发现通过截面的流量总和恰为 p。注意到如果走了最开始的链就代表不选，因此要限制至少有 q 的流量不走链，那么只需要把链的容量改成 $p-q$ 就行了。

3.13 Prufer 序列

对一棵有 $n \geq 2$ 个结点的树，它的 Prufer 编码是一个长为 $n-2$，且每个数都在 $[1, n]$ 内的序列。
构造方法：每次选取编号最小的叶子结点，记录它的父亲，然后把它删掉，直到只剩两个点为止。(并且最后剩的两个点一定有一个是 n 号点。)
相应的，由 Prufer 编码重构树的方法：按顺序读入序列，每次选取编号最小的且度数为 1 的结点，把这个点和序列当前点连上，然后两个点剩余度数同时 -1。

性质

- 每个至少 2 个结点的树都唯一对应一个 Prufer 编码。(当然也就可以做无根树哈希。)
- 每个点在 Prufer 序列中出现的次数恰好是度数 -1。所以如果给定某些点的度数然后求方案数，就可以用简单的组合数解决。

最后，构造和重构直接写都是 $O(n \log n)$ 的，想优化成线性需要一些技巧。
线性求 Prufer 序列代码：

```
// 0-based
vector<vector<int>> adj;
vector<int> parent;

void dfs(int v) {
    for (int u : adj[v]) {
        if (u != parent[v]) parent[u] = v, dfs(u);
    }
}

vector<int> pruefer_code() { // pruefer是德语
    int n = adj.size();
    parent.resize(n), parent[n - 1] = -1;
    dfs(n - 1);
```

```cpp

    int ptr = -1;
    vector<int> degree(n);
    for (int i = 0; i < n; i++) {
        degree[i] = adj[i].size();
        if (degree[i] == 1 && ptr == -1) ptr = i;
    }

    vector<int> code(n - 2);
    int leaf = ptr;
    for (int i = 0; i < n - 2; i++) {
        int next = parent[leaf];
        code[i] = next;
        if (--degree[next] == 1 && next < ptr)
            leaf = next;
        else {
            ptr++;
            while (degree[ptr] != 1)
              ptr++;
            leaf = ptr;
       }
    }
    return code;
}
```

线性重构树代码：

```cpp
// 0-based
vector<pair<int, int>> pruefer_decode(vector<int> const &code) {
    int n = code.size() + 2;
    vector<int> degree(n, 1);
    for (int i : code) degree[i]++;

    int ptr = 0;
    while (degree[ptr] != 1) ptr++;
    int leaf = ptr;

    vector<pair<int, int>> edges;
    for (int v : code) {
        edges.emplace_back(leaf, v);
        if (--degree[v] == 1 && v < ptr)
            leaf = v;
        else {
            ptr++;
            while (degree[ptr] != 1)
                ptr++;
            leaf = ptr;
        }
    }
    edges.emplace_back(leaf, n - 1);
    return edges;
}
```

3.14 弦图相关

Copy-and-pasted from the template of *NEW CODE!!*.

1. 团数 $\leq$ 色数，弦图团数 = 色数；
2. 设 $next(v)$ 表示 $N(v)$ 中最前的点，令 $w*$ 表示所有满足 $A \in B$ 的 w 中最后的一个点，判断 $v \cup N(v)$ 是否为极大团，只需判断是否存在一个 w，满足 $Next(w) = v$ 且 $|N(v)| + 1 \leq |N(w)|$ 即可。
3. 最小染色：完美消除序列 **从后往前** 依次给每个点染色，给每个点染上可以染的最小的颜色。
4. 最大独立集：完美消除序列 **从前往后** 能选就选。
5. 弦图最大独立集数 = 最小团覆盖数。
6. 最小团覆盖：设最大独立集为 $\{p_1, p_2, \ldots, p_t\}$，则 $\{p_1 \cup N(p_1), \ldots, p_t \cup N(p_t)\}$ 为最小团覆盖。

3.15 其他

3.15.1 Stoer-Wagner

```cpp
const int N = 601;
int fa[N], siz[N], edge[N][N];

int find(int x) {
    return fa[x] == x ? x : fa[x] = find(fa[x]);
}

int dist[N], vis[N], bin[N];
int n, m;

int contract(int& s, int& t) { // Find s,t
    memset(dist, 0, sizeof(dist));
    memset(vis, false, sizeof(vis));

    int i, j, k, mincut, maxc;

    for (i = 1; i <= n; i++) {
        k = -1;
        maxc = -1;

        for (j = 1; j <= n; j++)
            if (!bin[j] && !vis[j] && dist[j] > maxc) {
                k = j;
                maxc = dist[j];
            }

        if (k == -1)
            return mincut;

        s = t;
        t = k;
        mincut = maxc;
        vis[k] = true;

        for (j = 1; j <= n; j++)
            if (!bin[j] && !vis[j]) dist[j] += edge[k][j];
    }

    return mincut;
}

const int inf = 0x3f3f3f3f;

int Stoer_Wagner() {
    int mincut, i, j, s, t, ans;
    for (mincut = inf, i = 1; i < n; i++) {
        ans = contract(s, t);
        bin[t] = true;

        if (mincut > ans)
            mincut = ans;
        if (mincut == 0)
            return 0;

        for (j = 1; j <= n; j++)
            if (!bin[j])
                edge[s][j] = (edge[j][s] += edge[j][t]);
    }

    return mincut;
}

int main() {
    cin >> n >> m;

```

```
    if (m < n - 1) {
        cout << 0;
        return 0;
    }

    for (int i = 1; i <= n; ++i)
        fa[i] = i, siz[i] = 1;

    for (int i = 1, u, v, w; i <= m; ++i) {
        cin >> u >> v >> w;

        int fu = find(u), fv = find(v);
        if (fu != fv) {
            if (siz[fu] > siz[fv]) swap(fu, fv);
            fa[fu] = fv, siz[fv] += siz[fu];
        }

        edge[u][v] += w, edge[v][u] += w;
    }

    int fr = find(1);

    if (siz[fr] != n) {
        cout << 0;
        return 0;
    }

    cout << Stoer_Wagner();

    return 0;
}
```

4 数据结构

4.1 线段树

4.1.1 非递归线段树

~~让 fstqwq 手撕~~ 我队友呢?

- 如果 $M = 2^k$，则只能维护 $[1, M-2]$ 范围
- 找叶子：i 对应的叶子就是 $i + M$
- 单点修改：找到叶子然后向上跳
- 区间查询：左右区间各扩展一位，转换成开区间查询

```
int query(int l, int r) {
    l += M - 1;
    r += M + 1;

    int ans = 0;
    while (l ^ r != 1) {
        ans += sum[l ^ 1] + sum[r ^ 1];

        l >>= 1;
        r >>= 1;
    }

    return ans;
}
```

区间修改要标记永久化，并且求区间和和求最值的代码不太一样。

区间加，区间求和

```
void update(int l, int r, int d) {
    int len = 1, cntl = 0, cntr = 0; // cntl, cntr是左右两边分别实际修改的区间长度
    for (l += n - 1, r += n + 1; l ^ r ^ 1; l >>= 1, r >>= 1, len <<= 1) {
        tree[l] += cntl * d, tree[r] += cntr * d;
        if (~l & 1) tree[l ^ 1] += d * len, mark[l ^ 1] += d, cntl += len;
        if (r & 1) tree[r ^ 1] += d * len, mark[r ^ 1] += d, cntr += len;
    }

    for (; l; l >>= 1, r >>= 1)
        tree[l] += cntl * d, tree[r] += cntr * d;
}

int query(int l, int r) {
    int ans = 0, len = 1, cntl = 0, cntr = 0;
    for (l += n - 1, r += n + 1; l ^ r ^ 1; l >>= 1, r >>= 1, len <<= 1) {
        ans += cntl * mark[l] + cntr * mark[r];
        if (~l & 1) ans += tree[l ^ 1], cntl += len;
        if (r & 1) ans += tree[r ^ 1], cntr += len;
    }

    for (; l; l >>= 1, r >>= 1)
        ans += cntl * mark[l] + cntr * mark[r];

    return ans;
}
```

区间加，区间求最大值

```
void update(int l, int r, int d) {
    for (l += N - 1, r += N + 1; l ^ r ^ 1; l >>= 1, r >>= 1) {
        if (l < N) {
            tree[l] = max(tree[l << 1], tree[l << 1 | 1]) + mark[l];
            tree[r] = max(tree[r << 1], tree[r << 1 | 1]) + mark[r];
        }

        if (~l & 1) {
            tree[l ^ 1] += d;
            mark[l ^ 1] += d;
        }
        if (r & 1) {
            tree[r ^ 1] += d;
            mark[r ^ 1] += d;
        }
    }

    for (; l; l >>= 1, r >>= 1)
        if (l < N) tree[l] = max(tree[l << 1], tree[l << 1 | 1]) + mark[l],
            tree[r] = max(tree[r << 1], tree[r << 1 | 1]) + mark[r];
}

int query(int l, int r) {
    int maxl = -INF, maxr = -INF;

    for (l += N - 1, r += N + 1; l ^ r ^ 1; l >>= 1, r >>= 1) {
        maxl += mark[l];
        maxr += mark[r];

        if (~l & 1)
            maxl = max(maxl, tree[l ^ 1]);
        if (r & 1)
            maxr = max(maxr, tree[r ^ 1]);
    }

    while (l) {
        maxl += mark[l];
        maxr += mark[r];

        l >>= 1;
        r >>= 1;
    }

    return max(maxl, maxr);
}
```

4.1.2 线段树维护矩形并

为线段树的每个结点维护 cover_i 表示这个区间被完全覆盖的次数。更新时分情况讨论，如果当前区间已被完全覆盖则长度就是区间长度，否则长度是左右儿子相加。

```
constexpr int maxn = 100005, maxm = maxn * 70;

int lc[maxm], rc[maxm], cover[maxm], sum[maxm], root, seg_cnt;
int s, t, d;

void refresh(int l, int r, int o) {
    if (cover[o])
        sum[o] = r - l + 1;
    else
        sum[o] = sum[lc[o]] + sum[rc[o]];
}

void modify(int l, int r, int &o) {
    if (!o)
        o = ++seg_cnt;

    if (s <= l && t >= r) {
        cover[o] += d;
        refresh(l, r, o);

        return;
```

```
    }

    int mid = (l + r) / 2;

    if (s <= mid)
        modify(l, mid, lc[o]);
    if (t > mid)
        modify(mid + 1, r, rc[o]);

    refresh(l, r, o);
}

struct modi {
    int x, l, r, d;

    bool operator < (const modi &o) {
        return x < o.x;
    }
} a[maxn * 2];

int main() {

    int n;
    scanf("%d", &n);

    for (int i = 1; i <= n; i++) {
        int lx, ly, rx, ry;
        scanf("%d%d%d%d", &lx, &ly, &rx, &ry);

        a[i * 2 - 1] = {lx, ly + 1, ry, 1};
        a[i * 2] = {rx, ly + 1, ry, -1};
    }

    sort(a + 1, a + n * 2 + 1);

    int last = -1;
    long long ans = 0;

    for (int i = 1; i <= n * 2; i++) {
        if (last != -1)
            ans += (long long)(a[i].x - last) * sum[1];
        last = a[i].x;

        s = a[i].l;
        t = a[i].r;
        d = a[i].d;

        modify(1, 1e9, root);
    }

    printf("%lld\n", ans);

    return 0;
}
```

4.1.3 历史和

EC-Final2020 G，原题是询问某个区间有多少子区间，满足子区间中数的种类数为奇数。
离线之后转化成枚举右端点并用线段树维护左端点，然后就是一个支持区间反转（0/1 互换）和询问历史和的线段树。
“既然标记会复合，就说明在两个标记中间没有经过任何 pushup 操作
也就是说一个这两个标记对应着相同的 0 的数量以及相同的 1 的数量
那么标记对于答案的影响只能是 a * 0 + b * 1
我们维护 a，b 即可”

```
#include <bits/stdc++.h>

using namespace std;

constexpr int maxn = (1 << 20) + 5;

int cnt[maxn][2], mul[maxn][2];
bool rev[maxn];
long long sum[maxn];

int now;

void build(int l, int r, int o) {
    cnt[o][0] = r - l + 1;

    if (l == r)
        return;

    int mid = (l + r) / 2;

    build(l, mid, o * 2);
    build(mid + 1, r, o * 2 + 1);
}

void apply(int o, bool flip, long long w0, long long
  ↪ w1) {
    sum[o] += w0 * cnt[o][0] + w1 * cnt[o][1];

    if (flip)
        swap(cnt[o][0], cnt[o][1]);

    if (rev[o])
        swap(w0, w1);

    mul[o][0] += w0;
    mul[o][1] += w1;
    rev[o] ^= flip;
}

void pushdown(int o) {
    if (!mul[o][0] && !mul[o][1] && !rev[o])
        return;

    apply(o * 2, rev[o], mul[o][0], mul[o][1]);
    apply(o * 2 + 1, rev[o], mul[o][0], mul[o][1]);

    mul[o][0] = mul[o][1] = 0;
    rev[o] = false;
}

void update(int o) {
    cnt[o][0] = cnt[o * 2][0] + cnt[o * 2 + 1][0];
    cnt[o][1] = cnt[o * 2][1] + cnt[o * 2 + 1][1];

    sum[o] = sum[o * 2] + sum[o * 2 + 1];
}

int s, t;

void modify(int l, int r, int o) {
    if (s <= l && t >= r) {
        apply(o, true, 0, 0);
        return;
    }

    int mid = (l + r) / 2;
    pushdown(o);

    if (s <= mid)
        modify(l, mid, o * 2);
    if (t > mid)
        modify(mid + 1, r, o * 2 + 1);

    update(o);
}
```

```

long long query(int l, int r, int o) {
    if (s <= l && t >= r)
        return sum[o];

    int mid = (l + r) / 2;
    pushdown(o);

    long long ans = 0;
    if (s <= mid)
        ans += query(l, mid, o * 2);
    if (t > mid)
        ans += query(mid + 1, r, o * 2 + 1);

    return ans;
}

vector<pair<int, int> > vec[maxn]; // pos, id

long long ans[maxn];
int a[maxn], last[maxn];

int main() {

    int n;
    scanf("%d", &n);

    build(1, n, 1);

    for (int i = 1; i <= n; i++)
        scanf("%d", &a[i]);

    int m;
    scanf("%d", &m);

    for (int i = 1; i <= m; i++) {
        int l, r;
        scanf("%d%d", &l, &r);

        vec[r].emplace_back(l, i);
    }

    for (int i = 1; i <= n; i++) {
        s = last[a[i]] + 1;
        t = now = i;

        modify(1, n, 1);
        apply(1, false, 0, 1);

        for (auto [l, k] : vec[i]) {
            s = l;
            ans[k] = query(1, n, 1);
        }

        last[a[i]] = i;
    }

    for (int i = 1; i <= m; i++)
        printf("%lld\n", ans[i]);

    return 0;
}
```

4.2 陈丹琦分治

4.2.1 动态图连通性

```
vector<pair<int, int> > seg[(1 << 22) + 5];

int s, t;
pair<int, int> d;

void add(int l, int r, int o) {
    if (s > t)
        return;

    if (s <= l && t >= r) {
        seg[o].push_back(d);
        return;
    }

    int mid = (l + r) / 2;

    if (s <= mid)
        add(l, mid, o * 2);
    if (t > mid)
        add(mid + 1, r, o * 2 + 1);
}

int ufs[maxn], sz[maxn], stk[maxn], top;

int findufs(int x) {
    while (ufs[x] != x)
        x = ufs[x];

    return ufs[x];
}

void link(int x, int y) {
    x = findufs(x);
    y = findufs(y);

    if (x == y)
        return;

    if (sz[x] < sz[y])
        swap(x, y);

    ufs[y] = x;
    sz[x] += sz[y];
    stk[++top] = y;
}

int ans[maxm];

void solve(int l, int r, int o) {
    int tmp = top;

    for (auto pi : seg[o])
        link(pi.first, pi.second);

    if (l == r)
        ans[l] = top;
    else {
        int mid = (l + r) / 2;

        solve(l, mid, o * 2);
        solve(mid + 1, r, o * 2 + 1);
    }

    for (int i = top; i > tmp; i--) {
        int x = stk[i];

        sz[ufs[x]] -= sz[x];
        ufs[x] = x;
    }

    top = tmp;
}

map<pair<int, int>, int> mp;
```

4.2.2 动态最小生成树

参见 3.1.2.动态最小生成树（第 26 页）。

4.2.3 四维偏序

```
// 四维偏序

void CDQ1(int l, int r) {
    if (l >= r)
        return;

    int mid = (l + r) / 2;

    CDQ1(l, mid);
    CDQ1(mid + 1, r);

    int i = l, j = mid + 1, k = l;

    while (i <= mid && j <= r) {
        if (a[i].x < a[j].x) {
            a[i].ins = true;
            b[k++] = a[i++];
        }
        else {
            a[j].ins = false;
            b[k++] = a[j++];
        }
    }

    while (i <= mid) {
        a[i].ins = true;
        b[k++] = a[i++];
    }

    while (j <= r) {
        a[j].ins = false;
        b[k++] = a[j++];
    }

    copy(b + l, b + r + 1, a + l); // 后面的分治会破坏排序，所以要复制一份

    CDQ2(l, r);
}

void CDQ2(int l, int r) {
    if (l >= r)
        return;

    int mid = (l + r) / 2;

    CDQ2(l, mid);
    CDQ2(mid + 1, r);

    int i = l, j = mid + 1, k = l;

    while (i <= mid && j <= r) {
        if (b[i].y < b[j].y) {
            if (b[i].ins)
                add(b[i].z, 1); // 树状数组

            t[k++] = b[i++];
        }
        else{
            if (!b[j].ins)
                ans += query(b[j].z - 1);

            t[k++] = b[j++];
        }
    }

    while (i <= mid) {
        if (b[i].ins)
            add(b[i].z, 1);

        t[k++] = b[i++];
    }

    while (j <= r) {
        if (!b[j].ins)
            ans += query(b[j].z - 1);

        t[k++] = b[j++];
    }

    for (i = l; i <= mid; i++)
        if (b[i].ins)
            add(b[i].z, -1);

    copy(t + l, t + r + 1, b + l);
}
```

4.3 整体二分

修改和询问都要划分，备份一下，递归之前 copy 回去。
如果是满足可减性的问题（例如查询区间 k 小数），可以直接在划分的时候把询问的 k 修改一下。否则需要维护一个全局的数据结构，一般来说可以先递归右边再递归左边，具体维护方法视情况而定。
以下代码以 ZJOI K 大数查询为例（区间都添加一个数，询问区间 k 大数）。

```
int op[maxn], ql[maxn], qr[maxn]; // 1: modify  2: query
long long qk[maxn]; // 修改和询问可以一起存

int ans[maxn];

void solve(int l, int r, vector<int> v) { // 如果想卡常可以用数组，然后只需要传一个数组的l, r; 递归的时候类似归并反过来，开两个辅助数组，处理完再复制回去即可
    if (v.empty())
        return;

    if (l == r) {
        for (int i : v)
            if (op[i] == 2)
                ans[i] = l;

        return;
    }

    int mid = (l + r) / 2;

    vector<int> vl, vr;

    for (int i : v) {
        if (op[i] == 1) {
            if (qk[i] <= mid)
                vl.push_back(i);
            else {
                update(ql[i], qr[i], 1); // update是区间加
                vr.push_back(i);
            }
        }
        else {
            long long tmp = query(ql[i], qr[i]);

            if (qk[i] <= tmp) // 因为是k大数查询
                vr.push_back(i);
            else {
                qk[i] -= tmp;
```

```
                vl.push_back(i);
            }
        }
    }

    for (int i : vr)
        if (op[i] == 1)
            update(ql[i], qr[i], -1);

    v.clear();

    solve(l, mid, vl);
    solve(mid + 1, r, vr);
}

int main() {
    int n, m;
    scanf("%d%d", &n, &m);

    M = 1;
    while (M < n + 2)
        M *= 2;

    for (int i = 1; i <= m; i++)
        scanf("%d%d%d%lld", &op[i], &ql[i], &qr[i], &qk[i]);

    vector<int> v;
    for (int i = 1; i <= m; i++)
        v.push_back(i);

    solve(1, 1e9, v);

    for (int i = 1; i <= m; i++)
        if (op[i] == 2)
            printf("%d\n", ans[i]);

    return 0;
}
```

4.4 平衡树

pb_ds 平衡树参见 8.11.Public Based DataStructure (PB_DS)（第 91 页）。

4.4.1 Treap

```
// 注意：相同键值可以共存

struct node { // 结点类定义
    int key, size, p; // 分别为键值，子树大小，优先度
    node *ch[2]; // 0表示左儿子，1表示右儿子

    node(int key = 0) : key(key), size(1), p(rand()) {}

    void refresh() {
        size = ch[0] -> size + ch[1] -> size + 1;
    } // 更新子树大小（和附加信息，如果有的话）
} null[maxn], *root = null, *ptr = null; // 数组名叫做null是为了方便开哨兵节点
// 如果需要删除而空间不能直接开下所有结点，则需要再写一个垃圾回收
// 注意：数组里的元素一定不能delete，否则会导致RE

// 重要！在主函数最开始一定要加上以下预处理：
null -> ch[0] = null -> ch[1] = null;
null -> size = 0;

// 伪构造函数 O(1)
// 为了方便，在结点类外面再定义一个伪构造函数
node *newnode(int x) { // 键值为x
    *++ptr = node(x);
    ptr -> ch[0] = ptr -> ch[1] = null;
    return ptr;
}

// 插入键值 期望O(\log n)
// 需要调用旋转
void insert(int x, node *&rt) { // rt为当前结点，建议调用时传入root，下同
    if (rt == null) {
        rt = newnode(x);
        return;
    }

    int d = x > rt -> key;
    insert(x, rt -> ch[d]);
    rt -> refresh();

    if (rt -> ch[d] -> p < rt -> p)
        rot(rt, d ^ 1);
}

// 删除一个键值 期望O(\log n)
// 要求键值必须存在至少一个，否则会导致RE
// 需要调用旋转
void erase(int x, node *&rt) {
    if (x == rt -> key) {
        if (rt -> ch[0] != null && rt -> ch[1] != null) {
            int d = rt -> ch[0] -> p < rt -> ch[1] -> p;
            rot(rt, d);
            erase(x, rt -> ch[d]);
        }
        else
            rt = rt -> ch[rt -> ch[0] == null];
    }
    else
        erase(x, rt -> ch[x > rt -> key]);

    if (rt != null)
        rt -> refresh();
}

// 求元素的排名（严格小于键值的个数 + 1）期望O(\log n)
// 非递归
int rank(int x, node *rt) {
    int ans = 1, d;
    while (rt != null) {
        if ((d = x > rt -> key))
            ans += rt -> ch[0] -> size + 1;

        rt = rt -> ch[d];
    }

    return ans;
}

// 返回排名第k(从1开始) 的键值对应的指针 期望O(\log n)
// 非递归
node *kth(int x, node *rt) {
    int d;
    while (rt != null) {
        if (x == rt -> ch[0] -> size + 1)
            return rt;

        if ((d = x > rt -> ch[0] -> size))
            x -= rt -> ch[0] -> size + 1;

        rt = rt -> ch[d];
    }

```

```
    return rt;
}

// 返回前驱（最大的比给定键值小的键值）对应的指针 期望O(\log n)
// 非递归
node *pred(int x, node *rt) {
    node *y = null;
    int d;

    while (rt != null) {
        if ((d = x > rt -> key))
            y = rt;

        rt = rt -> ch[d];
    }

    return y;
}

// 返回后继（最小的比给定键值大的键值）对应的指针 期望O(\log n)
// 非递归
node *succ(int x, node *rt) {
    node *y = null;
    int d;

    while (rt != null) {
        if ((d = x < rt -> key))
            y = rt;

        rt = rt -> ch[d ^ 1];
    }

    return y;
}

// 旋转（Treap版本）O(1)
// 平衡树基础操作
// 要求对应儿子必须存在，否则会导致后续各种莫名其妙的问题
void rot(node *&x, int d) { // x为被转下去的结点，会被修改以维护树结构
    node *y = x -> ch[d ^ 1];

    x -> ch[d ^ 1] = y -> ch[d];
    y -> ch[d] = x;

    x -> refresh();
    (x = y) -> refresh();
}
```

4.4.2 无旋 Treap

```
struct node {
    int val, size;
    node *ch[2];

    node(int val) : val(val), size(1) {}

    inline void update() {
        size = ch[0] -> size + ch[1] -> size;
    }


} null[maxn];

node *copied(node *x) { // 如果不用可持久化的话，直接用就行了
    return new node(*x);
}

node *merge(node *x, node *y) {
    if (x == null)
        return y;
    if (y == null)
        return x;

    node *z;
    if (rand() % (x -> size + y -> size) < x -> size) {
        z = copied(x);
        z -> ch[1] = merge(x -> ch[1], y);
    }
    else {
        z = copied(y);
        z -> ch[0] = merge(x, y -> ch[0]);
    }

    z -> update(); // 因为每次只有一边会递归到儿子，所以z 不可能取到 null
    return z;
}

pair<node*, node*> split(node *x, int k) { // 左边大小为k
    if (x == null)
        return make_pair(null, null);

    pair<node*, node*> pi(null, null);

    if (k <= x -> ch[0] -> size) {
        pi = split(x -> ch[0], k);

        node *z = copied(x);
        z -> ch[0] = pi.second;
        z -> update();
        pi.second = z;
    }
    else {
        pi = split(x -> ch[1], k - x -> ch[0] -> size - 1);

        node *y = copied(x);
        y -> ch[1] = pi.first;
        y -> update();
        pi.first = y;
    }

    return pi;
}

// 记得初始化null
int main() {
    for (int i = 0; i <= n; i++)
        null[i].ch[0] = null[i].ch[1] = null;
    null -> size = 0;

    // do something

    return 0;
}
```

4.4.3 Splay

如果插入的话可以直接找到底然后 splay 一下，也可以直接 splay 前驱后继。

```
#define dir(x) ((x) == (x) -> p -> ch[1])

struct node {
    int size;
    bool rev;
    node *ch[2],*p;

```

```
    node() : size(1), rev(false) {}

    void pushdown() {
        if(!rev)
            return;

        ch[0] -> rev ^= true;
        ch[1] -> rev ^= true;
        swap(ch[0], ch[1]);

        rev=false;
    }

    void refresh() {
        size = ch[0] -> size + ch[1] -> size + 1;
    }
} null[maxn], *root = null;

void rot(node *x, int d) {
    node *y = x -> ch[d ^ 1];

    if ((x -> ch[d ^ 1] = y -> ch[d]) != null)
        y -> ch[d] -> p = x;
    ((y -> p = x -> p) != null ? x -> p -> ch[dir(x)] : root) = y;
    (y -> ch[d] = x) -> p = y;

    x -> refresh();
    y -> refresh();
}

void splay(node *x, node *t) {
    while (x -> p != t) {
        if (x -> p -> p == t) {
            rot(x -> p, dir(x) ^ 1);
            break;
        }

        if (dir(x) == dir(x -> p))
            rot(x -> p -> p, dir(x -> p) ^ 1);
        else
            rot(x -> p, dir(x) ^ 1);
        rot(x -> p, dir(x) ^ 1);
    }
}

node *kth(int k, node *o) {
    int d;
    k++; // 因为最左边有一个哨兵

    while (o != null) {
        o -> pushdown();

        if (k == o -> ch[0] -> size + 1)
            return o;

        if ((d = k > o -> ch[0] -> size))
            k -= o -> ch[0] -> size + 1;
        o = o -> ch[d];
    }

    return null;
}

void reverse(int l, int r) {
    splay(kth(l - 1));
    splay(kth(r + 1), root);

    root -> ch[1] -> ch[0] -> rev ^= true;
}

int n, m;

int main() {
    null -> size = 0;
    null -> ch[0] = null -> ch[1] = null -> p = null;

    scanf("%d%d", &n, &m);
    root = null + n + 1;
    root -> ch[0] = root -> ch[1] = root -> p = null;

    for (int i = 1; i <= n; i++) {
        null[i].ch[1] = null[i].p = null;
        null[i].ch[0] = root;
        root -> p = null + i;
        (root = null + i) -> refresh();
    }

    null[n + 2].ch[1] = null[n + 2].p = null;
    null[n + 2].ch[0] = root; // 这里直接建成一条链的，如果想减少常数也可以递归建一个平衡的树
    root -> p = null + n + 2; // 总之记得建两个哨兵，这样splay起来不需要特判
    (root = null + n + 2) -> refresh();

    // Do something

    return 0;
}
```

4.5 树链剖分

4.5.1 动态树形 DP

代码是维护最大权独立集。

```
#include <bits/stdc++.h>

using namespace std;

constexpr int maxn = 100005, maxm = 262155, inf = 0x3f3f3f3f;

struct binary_heap {
    priority_queue<int> q, t;

    binary_heap() {}

    void push(int x) {
        q.push(x);
    }

    void erase(int x) {
        t.push(x);
    }

    int top() {
        while (!t.empty() && q.top() == t.top()) {
            q.pop();
            t.pop();
        }

        return q.top();
    }
} heap;

int pool[maxm][2][2], (*pt)[2][2] = pool;

void merge(int a[2][2], int b[2][2]) {
    static int c[2][2];
    memset(c, 0, sizeof(c));

    for (int i = 0; i < 2; i++)
        for (int j = 0; j < 2; j++)
```

```
            for (int k = 0; k < 2; k++)
                if (!(j && k))
                    for (int t = 0; t < 2; t++)
                        c[i][t] = max(c[i][t], a[i][j] + b[k][t]);

    memcpy(a, c, sizeof(c));
}

vector<pair<int, int> > tw;

struct seg_tree {
    int (*tr)[2][2], n;

    int s, d[2];

    seg_tree() {}

    void update(int o) {
        memcpy(tr[o], tr[o * 2], sizeof(int) * 4);
        merge(tr[o], tr[o * 2 + 1]);
    }

    void build(int l, int r, int o) {
        if (l == r) {
            tr[o][0][0] = tw[l - 1].first;
            tr[o][0][1] = tr[o][1][0] = -inf;
            tr[o][1][1] = tw[l - 1].second;

            return;
        }

        int mid = (l + r) / 2;

        build(l, mid, o * 2);
        build(mid + 1, r, o * 2 + 1);

        update(o);
    }

    void modify(int l, int r, int o) {
        if (l == r) {
            tr[o][0][0] = d[0];
            tr[o][0][1] = tr[o][1][0] = -inf;
            tr[o][1][1] = d[1];

            return;
        }

        int mid = (l + r) / 2;

        if (s <= mid)
            modify(l, mid, o * 2);
        else
            modify(mid + 1, r, o * 2 + 1);

        update(o);
    }

    int getval() {
        int ans = 0;
        for (int i = 0; i < 2; i++)
            for (int j = 0; j < 2; j++)
                ans = max(ans, tr[1][i][j]);

        return ans;
    }

    pair<int, int> getpair() {
        int ans[2] = {0};
        for (int i = 0; i < 2; i++)
            for (int j = 0; j < 2; j++)
                ans[i] = max(ans[i], tr[1][i][j]);

        return make_pair(ans[0], ans[1]);
    }

    void build(int len) {
        n = len;
        int N = 1;
        while (N < n * 2)
            N *= 2;

        tr = pt;
        pt += N;

        build(1, n, 1);
    }

    void modify(int x, int dat[2]) {
        s = x;
        for (int i = 0; i < 2; i++)
            d[i] = dat[i];
        modify(1, n, 1);
    }
} seg[maxn];

vector<int> G[maxn];

int p[maxn], d[maxn], sz[maxn], son[maxn], top[maxn];
int dp[maxn][2], dptr[maxn][2], w[maxn];

void dfs1(int x) {
    d[x] = d[p[x]] + 1;
    sz[x] = 1;

    for (int y : G[x])
        if (y != p[x]) {
            p[y] = x;
            dfs1(y);

            if (sz[y] > sz[son[x]])
                son[x] = y;

            sz[x] += sz[y];
        }
}

void dfs2(int x) {
    if (x == son[p[x]])
        top[x] = top[p[x]];
    else
        top[x] = x;

    for (int y : G[x])
        if (y != p[x])
            dfs2(y);

    dp[x][1] = w[x];
    for (int y : G[x])
        if (y != p[x] && y != son[x]) {
            dp[x][1] += dptr[y][0];
            dp[x][0] += max(dptr[y][0], dptr[y][1]);
        }

    if (top[x] == x) {
        tw.clear();

        for (int u = x; u; u = son[u])
            tw.push_back(make_pair(dp[u][0], dp[u][1]));

        seg[x].build((int)tw.size());

```

```
        tie(dptr[x][0], dptr[x][1]) = seg[x].getpair();

        heap.push(seg[x].getval());
    }
}

void modify(int x, int dat) {
    dp[x][1] -= w[x];
    dp[x][1] += (w[x] = dat);

    while (x) {
        if (p[top[x]]) {
            dp[p[top[x]]][0] -= max(dptr[top[x]][0], dptr[top[x]][1]);
            dp[p[top[x]]][1] -= dptr[top[x]][0];
        }

        heap.erase(seg[top[x]].getval());
        seg[top[x]].modify(d[x] - d[top[x]] + 1, dp[x]);
        heap.push(seg[top[x]].getval());

        tie(dptr[top[x]][0], dptr[top[x]][1]) = seg[top[x]].getpair();

        if (p[top[x]]) {
            dp[p[top[x]]][0] += max(dptr[top[x]][0], dptr[top[x]][1]);
            dp[p[top[x]]][1] += dptr[top[x]][0];
        }

        x = p[top[x]];
    }
}

int main() {

    int n, m;
    scanf("%d%d", &n, &m);

    for (int i = 1; i <= n; i++)
        scanf("%d", &w[i]);

    for (int i = 1; i < n; i++) {
        int x, y;
        scanf("%d%d", &x, &y);

        G[x].push_back(y);
        G[y].push_back(x);
    }

    dfs1(1);
    dfs2(1);

    while (m--) {
        int x, dat;
        scanf("%d%d", &x, &dat);

        modify(x, dat);

        printf("%d\n", heap.top());
    }

    return 0;
}
```

4.6 树分治

4.6.1 动态树分治

```
// 为了减小常数，这里采用bfs写法，实测预处理比dfs快将近一半
// 以下以维护一个点到每个黑点的距离之和为例

// 全局数组定义
vector<int> G[maxn], W[maxn];
int size[maxn], son[maxn], q[maxn];
int p[maxn], depth[maxn], id[maxn][20], d[maxn][20]; // id是对应层所在子树的根
int a[maxn], ca[maxn], b[maxn][20], cb[maxn][20]; // 维护距离和用的
bool vis[maxn], col[maxn];

// 建树 总计O(n\log n)
// 需要调用找重心和预处理距离，同时递归调用自身
void build(int x, int k, int s, int pr) { // 结点，深度，连通块大小，点分树上的父亲
    x = getcenter(x, s);
    vis[x] = true;
    depth[x] = k;
    p[x] = pr;

    for (int i = 0; i < (int)G[x].size(); i++)
        if (!vis[G[x][i]]) {
            d[G[x][i]][k] = W[x][i];
            p[G[x][i]] = x;

            getdis(G[x][i], k, G[x][i]); // bfs每个子树，预处理距离
        }

    for (int i = 0; i < (int)G[x].size(); i++)
        if (!vis[G[x][i]])
            build(G[x][i], k + 1, size[G[x][i]], x); // 递归建树
}

// 找重心 O(n)
int getcenter(int x, int s) {
    int head = 0, tail = 0;
    q[tail++] = x;

    while (head != tail) {
        x = q[head++];
        size[x] = 1; // 这里不需要清空，因为以后要用的话一定会重新赋值
        son[x] = 0;

        for (int i = 0; i < (int)G[x].size(); i++)
            if (!vis[G[x][i]] && G[x][i] != p[x]) {
                p[G[x][i]] = x;
                q[tail++] = G[x][i];
            }
    }

    for (int i = tail - 1; i; i--) {
        x = q[i];
        size[p[x]] += size[x];

        if (size[x] > size[son[p[x]]])
            son[p[x]] = x;
    }

    x = q[0];
    while (son[x] && size[son[x]] * 2 >= s)
        x = son[x];

    return x;
}
```

```cpp

// 预处理距离 O(n)
// 方便起见，这里直接用了笨一点的方法，O(n\log n) 全存下来
void getdis(int x, int k, int rt) {
    int head = 0, tail = 0;
    q[tail++] = x;

    while (head != tail) {
        x = q[head++];
        size[x] = 1;
        id[x][k] = rt;

        for (int i = 0; i < (int)G[x].size(); i++)
            if (!vis[G[x][i]] && G[x][i] != p[x]) {
                p[G[x][i]] = x;
                d[G[x][i]][k] = d[x][k] + W[x][i];

                q[tail++] = G[x][i];
            }
    }

    for (int i = tail - 1; i; i--)
        size[p[q[i]]] += size[q[i]]; // 后面递归建树要用到子问题大小
}

// 修改 O(\log n)
void modify(int x) {
    if (col[x])
        ca[x]--;
    else
        ca[x]++; // 记得先特判自己作为重心的那层

    for (int u = p[x], k = depth[x] - 1; u; u = p[u], k--) {
        if (col[x]) {
            a[u] -= d[x][k];
            ca[u]--;

            b[id[x][k]][k] -= d[x][k];
            cb[id[x][k]][k]--;
        }
        else {
            a[u] += d[x][k];
            ca[u]++;

            b[id[x][k]][k] += d[x][k];
            cb[id[x][k]][k]++;
        }
    }

    col[x] ^= true;
}

// 询问 O(\log n)
int query(int x) {
    int ans = a[x]; // 特判自己是重心的那层

    for (int u = p[x], k = depth[x] - 1; u; u = p[u], k--)
        ans += a[u] - b[id[x][k]][k] + d[x][k] * (ca[u] - cb[id[x][k]][k]);

    return ans;
}
```

4.6.2 紫荆花之恋

这个是 BFS 版本，跑得比 DFS 要快不少。(虽然主要复杂度并不在重构上。)

```cpp
#include <bits/stdc++.h>

using namespace std;

constexpr int maxn = 100005, maxk = 49;
constexpr double alpha = .75;

mt19937 rnd(23333333);

struct node {
    int key, size, p;
    node *ch[2];

    node() {}

    node(int key) : key(key), size(1), p(rnd()) {}

    inline void update() {
        size = ch[0] -> size + ch[1] -> size + 1;
    }
} null[maxn * maxk], *pt = null;

vector<node*> pool;

node *newnode(int val) {
    node *x;

    if (!pool.empty()) {
        x = pool.back();
        pool.pop_back();
    }
    else
        x = ++pt;

    *x = node(val);
    x -> ch[0] = x -> ch[1] = null;

    return x;
}

void rot(node *&x, int d) {
    node *y = x -> ch[d ^ 1];
    x -> ch[d ^ 1] = y -> ch[d];
    y -> ch[d] = x;

    x -> update();
    (x = y) -> update();
}

void insert(node *&o, int x) {
    if (o == null) {
        o = newnode(x);
        return;
    }

    int d = (x > o -> key);

    insert(o -> ch[d], x);
    o -> update();

    if (o -> ch[d] -> p < o -> p)
        rot(o, d ^ 1);
}

int get_order(node *o, int x) {
    int ans = 0;

    while (o != null) {
        int d = (x > o -> key);

        if (d)
```

```
            ans += o -> ch[0] -> size + 1;

        o = o -> ch[d];
    }

    return ans;
}

void destroy(node *x) {
    if (x == null)
        return;

    pool.push_back(x);
    destroy(x -> ch[0]);
    destroy(x -> ch[1]);
}

struct my_tree { // 封装了一下，如果不卡内存直接换成PBDS就好了
    node *rt;

    my_tree() : rt(null) {}

    void clear() {
        ::destroy(rt);
        rt = null;
    }

    void insert(int x) {
        ::insert(rt, x);
    }

    int order_of_key(int x) { // less than x
        return ::get_order(rt, x);
    }
} tr[maxn], tre[maxn][maxk];

vector<pair<int, int> > G[maxn];

int p[maxn], depth[maxn], d[maxn][maxk], rid[maxn][maxk];
int sz[maxn], siz[maxn][maxk], q[maxn];
bool vis[maxn];

int w[maxn];

void destroy(int o) {
    int head = 0, tail = 0;
    q[tail++] = o;
    vis[o] = false;

    while (head != tail) {
        int x = q[head++];
        tr[x].clear();

        for (int i = depth[o]; i <= depth[x]; i++) {
            tre[x][i].clear();
            d[x][i] = rid[x][i] = siz[x][i] = 0;
        }

        for (auto pi : G[x]) {
            int y = pi.first;

            if (vis[y] && depth[y] >= depth[o]) {
                vis[y] = false;
                q[tail++] = y;
            }
        }
    }
}

int getcenter(int o, int s) {
    int head = 0, tail = 0;
    q[tail++] = o;

    while (head != tail) {
        int x = q[head++];
        sz[x] = 1;

        for (auto pi : G[x]) {
            int y = pi.first;

            if (!vis[y] && y != p[x]) {
                p[y] = x;
                q[tail++] = y;
            }
        }
    }

    for (int i = s - 1; i; i--)
        sz[p[q[i]]] += sz[q[i]];

    int x = o;
    while (true) {
        bool ok = false;

        for (auto pi : G[x]) {
            int y = pi.first;
            if (!vis[y] && y != p[x] && sz[y] * 2 > s) {
                x = y;
                ok = true;
                break;
            }
        }

        if (!ok)
            break;
    }

    return x;
}

void getdis(int st, int o, int k) {
    int head = 0, tail = 0;
    q[tail++] = st;

    while (head != tail) {
        int x = q[head++];
        sz[x] = 1;
        rid[x][k] = st;

        tr[o].insert(d[x][k] - w[x]);
        tre[st][k].insert(d[x][k] - w[x]);

        for (auto pi : G[x]) {
            int y = pi.first, val = pi.second;

            if (!vis[y] && y != p[x]) {
                p[y] = x;
                d[y][k] = d[x][k] + val;
                q[tail++] = y;
            }
        }
    }

    for (int i = tail - 1; i; i--)
        sz[p[q[i]]] += sz[q[i]];

    siz[st][k] = sz[st];
}

void rebuild(int x, int s, int pr) {
    x = getcenter(x, s);
```

```
    vis[x] = true;
    p[x] = pr;
    depth[x] = depth[pr] + 1;
    sz[x] = s;

    tr[x].insert(-w[x]);

    for (auto pi : G[x]) {
        int y = pi.first, val = pi.second;

        if (!vis[y]) {
            p[y] = x;
            d[y][depth[x]] = val;
            getdis(y, x, depth[x]);
        }
    }

    for (auto pi : G[x]) {
        int y = pi.first;

        if (!vis[y])
            rebuild(y, sz[y], x);
    }
}

long long add_node(int x, int nw) { // nw是边权
    depth[x] = depth[p[x]] + 1;
    sz[x] = 1;
    vis[x] = true;

    tr[x].insert(-w[x]);

    long long tmp = 0;
    int goat = 0; // 替罪羊

    for (int u = p[x], k = depth[x] - 1; u; u = p[u], k--) {
        d[x][k] = d[p[x]][k] + nw;
        rid[x][k] = (rid[p[x]][k] ? rid[p[x]][k] : x);

        tmp += tr[u].order_of_key(w[x] - d[x][k] + 1);
        tmp -= tre[rid[x][k]][k].order_of_key(w[x] - d[x][k] + 1);

        tr[u].insert(d[x][k] - w[x]);
        tre[rid[x][k]][k].insert(d[x][k] - w[x]);

        sz[u]++;
        siz[rid[x][k]][k]++;

        if (siz[rid[x][k]][k] > sz[u] * alpha + 5)
            goat = u;
    }

    if (goat) {
        destroy(goat);
        rebuild(goat, sz[goat], p[goat]);
    }

    return tmp;
}

int main() {

    null -> ch[0] = null -> ch[1] = null;
    null -> size = 0;

    int n;
    scanf("%*d%d", &n);

    scanf("%*d%*d%d", &w[1]);
    vis[1] = true;
    sz[1] = 1;
    tr[1].insert(-w[1]);

    printf("0\n");

    long long ans = 0;

    for (int i = 2; i <= n; i++) {
        int nw;
        scanf("%d%d%d", &p[i], &nw, &w[i]);

        p[i] ^= (ans % 1000000000);

        G[i].push_back(make_pair(p[i], nw));
        G[p[i]].push_back(make_pair(i, nw));

        ans += add_node(i, nw);

        printf("%lld\n", ans);
    }

    return 0;
}
```

4.7 LCT

4.7.1 不换根

```
#define isroot(x) ((x) != (x) -> p -> ch[0] && (x) != (x) -> p -> ch[1]) // 判断是不是Splay的根
#define dir(x) ((x) == (x) -> p -> ch[1]) // 判断它是它父亲的左 / 右儿子

struct node { // 结点类定义
    int size; // Splay的子树大小
    node *ch[2], *p;

    node() : size(1) {}
    void refresh() {
        size = ch[0] -> size + ch[1] -> size + 1;
    } // 附加信息维护
} null[maxn];

// 在主函数开头加上这句初始化
null -> size = 0;

// 初始化结点
void initalize(node *x) {
    x -> ch[0] = x -> ch[1] = x -> p = null;
}

// Access 均摊O(\log n)
// LCT核心操作，把结点到根的路径打通，顺便把与重儿子的连边变成轻边
// 需要调用splay
node *access(node *x) {
    node *y = null;

    while (x != null) {
        splay(x);

        x -> ch[1] = y;
        (y = x) -> refresh();

        x = x -> p;
    }

    return y;
}

// Link 均摊O(\log n)
```

```cpp
// 把x的父亲设为y
// 要求x必须为所在树的根节点，否则会导致后续各种莫名其妙的问题
// 需要调用splay
void link(node *x, node *y) {
    splay(x);
    x -> p = y;
}

// Cut 均摊O(\log n)
// 把x与其父亲的连边断掉
// x可以是所在树的根节点，这时此操作没有任何实质效果
// 需要调用access和splay
void cut(node *x) {
    access(x);
    splay(x);

    x -> ch[0] -> p = null;
    x -> ch[0] = null;

    x -> refresh();
}

// Splay 均摊O(\log n)
// 需要调用旋转
void splay(node *x) {
    while (!isroot(x)) {
        if (isroot(x -> p)) {
            rot(x -> p, dir(x) ^ 1);
            break;
        }

        if (dir(x) == dir(x -> p))
            rot(x -> p -> p, dir(x -> p) ^ 1);
        else
            rot(x -> p, dir(x) ^ 1);
        rot(x -> p, dir(x) ^ 1);
    }
}

// 旋转 (LCT版本) O(1)
// 平衡树基本操作
// 要求对应儿子必须存在，否则会导致后续各种莫名其妙的问题
void rot(node *x, int d) {
    node *y = x -> ch[d ^ 1];

    y -> p = x -> p;
    if (!isroot(x))
        x -> p -> ch[dir(x)] = y;

    if ((x -> ch[d ^ 1] = y -> ch[d]) != null)
        y -> ch[d] -> p = x;
    (y -> ch[d] = x) -> p = y;

    x -> refresh();
    y -> refresh();
}
```

4.7.2 换根/维护生成树

```cpp
#define isroot(x) ((x) -> p == null || ((x) -> p -> ch[0] != (x) && (x) -> p -> ch[1] != (x)))
#define dir(x) ((x) == (x) -> p -> ch[1])

using namespace std;

const int maxn = 200005;

struct node{
    int key, mx, pos;
    bool rev;
    node *ch[2], *p;

    node(int key = 0): key(key), mx(key), pos(-1), rev(false) {}

    void pushdown() {
        if (!rev)
            return;

        ch[0] -> rev ^= true;
        ch[1] -> rev ^= true;
        swap(ch[0], ch[1]);

        if (pos != -1)
            pos ^= 1;

        rev = false;
    }

    void refresh() {
        mx = key;
        pos = -1;
        if (ch[0] -> mx > mx) {
            mx = ch[0] -> mx;
            pos = 0;
        }
        if (ch[1] -> mx > mx) {
            mx = ch[1] -> mx;
            pos = 1;
        }
    }
} null[maxn * 2];

void init(node *x, int k) {
    x -> ch[0] = x -> ch[1] = x -> p = null;
    x -> key = x -> mx = k;
}

void rot(node *x, int d) {
    node *y = x -> ch[d ^ 1];
    if ((x -> ch[d ^ 1] = y -> ch[d]) != null)
        y -> ch[d] -> p = x;

    y -> p = x -> p;
    if (!isroot(x))
        x -> p -> ch[dir(x)] = y;

    (y -> ch[d] = x) -> p = y;

    x -> refresh();
    y -> refresh();
}

void splay(node *x) {
    x -> pushdown();

    while (!isroot(x)) {
        if (!isroot(x -> p))
            x -> p -> p -> pushdown();
        x -> p -> pushdown();
        x -> pushdown();

        if (isroot(x -> p)) {
            rot(x -> p, dir(x) ^ 1);
            break;
        }

        if (dir(x) == dir(x -> p))
            rot(x -> p -> p, dir(x -> p) ^ 1);
        else
            rot(x -> p, dir(x) ^ 1);

```

```cpp
        rot(x -> p, dir(x) ^ 1);
    }
}

node *access(node *x) {
    node *y = null;

    while (x != null) {
        splay(x);

        x -> ch[1] = y;
        (y = x) -> refresh();

        x = x -> p;
    }

    return y;
}

void makeroot(node *x) {
    access(x);
    splay(x);
    x -> rev ^= true;
}

void link(node *x, node *y) {
    makeroot(x);
    x -> p = y;
}

void cut(node *x, node *y) {
    makeroot(x);
    access(y);
    splay(y);

    y -> ch[0] -> p = null;
    y -> ch[0] = null;
    y -> refresh();
}

node *getroot(node *x) {
    x = access(x);
    while (x -> pushdown(), x -> ch[0] != null)
        x = x -> ch[0];
    splay(x);
    return x;
}

node *getmax(node *x, node *y) {
    makeroot(x);
    x = access(y);

    while (x -> pushdown(), x -> pos != -1)
        x = x -> ch[x -> pos];
    splay(x);

    return x;
}

// 以下为主函数示例
for (int i = 1; i <= m; i++) {
    init(null + n + i, w[i]);
    if (getroot(null + u[i]) != getroot(null + v[i])) {
        ans[q + 1] -= k;
        ans[q + 1] += w[i];

        link(null + u[i], null + n + i);
        link(null + v[i], null + n + i);
        vis[i] = true;
    }
    else {
        int ii = getmax(null + u[i], null + v[i]) - null - n;
        if (w[i] >= w[ii])
            continue;

        cut(null + u[ii], null + n + ii);
        cut(null + v[ii], null + n + ii);

        link(null + u[i], null + n + i);
        link(null + v[i], null + n + i);

        ans[q + 1] -= w[ii];
        ans[q + 1] += w[i];
    }
}
```

4.7.3 维护子树信息

```cpp
// 这个东西虽然只需要抄板子但还是极其难写，常数极其巨大，没必要的时候就不要用
// 如果维护子树最小值就需要套一个可删除的堆来维护，复杂度会变成O(n\log^2 n)
// 注意由于这道题与边权有关，需要边权拆点变点权

// 宏定义
#define isroot(x) ((x) -> p == null || ((x) != (x) -> p -> ch[0] && (x) != (x) -> p -> ch[1]))
#define dir(x) ((x) == (x) -> p -> ch[1])

// 节点类定义
struct node { // 以维护子树中黑点到根距离和为例
    int w, chain_cnt, tree_cnt;
    long long sum, suml, sumr, tree_sum; // 由于换根需要子树反转，需要维护两个方向的信息
    bool rev, col;
    node *ch[2], *p;

    node() : w(0), chain_cnt(0), tree_cnt(0),sum(0),suml(0), sumr(0),
        tree_sum(0), rev(false), col(false) {}

    inline void pushdown() {
        if(!rev)
            return;

        ch[0]->rev ^= true;
        ch[1]->rev ^= true;
        swap(ch[0], ch[1]);
        swap(suml, sumr);

        rev = false;
    }

    inline void refresh() { // 如果不想这样特判就pushdown一下
        // pushdown();

        sum = ch[0] -> sum + ch[1] -> sum + w;
        suml = (ch[0] -> rev ? ch[0] -> sumr : ch[0] -> suml) + (ch[1] -> rev ? ch[1] -> sumr : ch[1] -> suml) + (tree_cnt + ch[1] -> chain_cnt) * (ch[0] -> sum + w) + tree_sum;
        sumr = (ch[0] -> rev ? ch[0] -> suml : ch[0] -> sumr) + (ch[1] -> rev ? ch[1] -> suml : ch[1] -> sumr) + (tree_cnt + ch[0] -> chain_cnt) * (ch[1] -> sum + w) + tree_sum;
        chain_cnt = ch[0] -> chain_cnt + ch[1] -> chain_cnt + tree_cnt;
    }
} null[maxn * 2]; // 如果没有边权变点权就不用乘2了

```

```cpp
// 封装构造函数
node *newnode(int w) {
    node *x = nodes.front(); // 因为有删边加边，可以用一个队列维护可用结点
    nodes.pop();
    initalize(x);
    x -> w = w;
    x -> refresh();
    return x;
}

// 封装初始化函数
// 记得在进行操作之前对所有结点调用一遍
inline void initalize(node *x) {
    *x = node();
    x -> ch[0] = x -> ch[1] = x -> p = null;
}

// 注意一下在Access的同时更新子树信息的方法
node *access(node *x) {
    node *y = null;

    while (x != null) {
        splay(x);

        x -> tree_cnt += x -> ch[1] -> chain_cnt - y -> chain_cnt;
        x -> tree_sum += (x -> ch[1] -> rev ? x -> ch[1] -> sumr : x -> ch[1] -> suml) - y -> suml;
        x -> ch[1] = y;

        (y = x) -> refresh();
        x = x -> p;
    }

    return y;
}

// 找到一个点所在连通块的根
// 对比原版没有变化
node *getroot(node *x) {
    x = access(x);

    while (x -> pushdown(), x -> ch[0] != null)
        x = x -> ch[0];
    splay(x);

    return x;
}

// 换根，同样没有变化
void makeroot(node *x) {
    access(x);
    splay(x);
    x -> rev ^= true;
    x -> pushdown();
}

// 连接两个点
// !!! 注意这里必须把两者都变成根，因为只能修改根结点
void link(node *x, node *y) {
    makeroot(x);
    makeroot(y);

    x -> p = y;
    y -> tree_cnt += x -> chain_cnt;
    y -> tree_sum += x -> suml;
    y -> refresh();
}

// 删除一条边
// 对比原版没有变化
void cut(node *x, node *y) {
    makeroot(x);
    access(y);
    splay(y);

    y -> ch[0] -> p = null;
    y -> ch[0] = null;
    y -> refresh();
}

// 修改/询问一个点，这里以询问为例
// 如果是修改就在换根之后搞一些操作
long long query(node *x) {
    makeroot(x);
    return x -> suml;
}

// Splay函数
// 对比原版没有变化
void splay(node *x) {
    x -> pushdown();

    while (!isroot(x)) {
        if (!isroot(x -> p))
            x -> p -> p -> pushdown();
        x -> p -> pushdown();
        x -> pushdown();

        if (isroot(x -> p)) {
            rot(x -> p, dir(x) ^ 1);
            break;
        }

        if (dir(x) == dir(x -> p))
            rot(x -> p -> p, dir(x -> p) ^ 1);
        else
            rot(x -> p, dir(x) ^ 1);

        rot(x -> p, dir(x) ^ 1);
    }
}

// 旋转函数
// 对比原版没有变化
void rot(node *x, int d) {
    node *y = x -> ch[d ^ 1];

    if ((x -> ch[d^1] = y -> ch[d]) != null)
        y -> ch[d] -> p = x;

    y -> p = x -> p;
    if (!isroot(x))
        x -> p -> ch[dir(x)] = y;

    (y -> ch[d] = x) -> p = y;

    x -> refresh();
    y -> refresh();
}
```

4.7.4 模板题：动态 QTREE4（询问树上相距最远点）

```cpp
#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/priority_queue.hpp>

#define isroot(x) ((x) -> p == null || ((x) != (x) -> p -> ch[0] && (x) != (x) -> p -> ch[1]))
#define dir(x) ((x) == (x) -> p -> ch[1])
```

```cpp

using namespace std;
using namespace __gnu_pbds;

constexpr int maxn = 100005;
constexpr long long INF = 1000000000000000000ll;

struct binary_heap {
    __gnu_pbds::priority_queue<long long, less<long long>, binary_heap_tag> q1, q2;
    binary_heap() {}

    void push(long long x) {
        if (x > (-INF) >> 2)
            q1.push(x);
    }

    void erase(long long x) {
        if (x > (-INF) >> 2)
            q2.push(x);
    }

    long long top() {
        if (empty())
            return -INF;

        while (!q2.empty() && q1.top() == q2.top()) {
            q1.pop();
            q2.pop();
        }

        return q1.top();
    }

    long long top2() {
        if (size() < 2)
            return -INF;

        long long a = top();
        erase(a);
        long long b = top();
        push(a);
        return a + b;
    }

    int size() {
        return q1.size() - q2.size();
    }

    bool empty() {
        return q1.size() == q2.size();
    }
} heap; // 全局堆维护每条链的最大子段和

struct node {
    long long sum, maxsum, prefix, suffix;
    int key;
    binary_heap heap; // 每个点的堆存的是它的子树中到它的最远距离，如果它是黑点的话还会包括自己
    node *ch[2], *p;
    bool rev;
    node(int k = 0): sum(k), maxsum(-INF), prefix(-INF),
        suffix(-INF), key(k), rev(false) {}
    inline void pushdown() {
        if (!rev)
            return;

        ch[0] -> rev ^= true;
        ch[1] -> rev ^= true;
        swap(ch[0], ch[1]);
        swap(prefix, suffix);
        rev = false;
    }
    inline void refresh() {
        pushdown();
        ch[0] -> pushdown();
        ch[1] -> pushdown();
        sum = ch[0] -> sum + ch[1] -> sum + key;
        prefix = max(ch[0] -> prefix,
                     ch[0] -> sum + key + ch[1] -> prefix);
        suffix = max(ch[1] -> suffix,
                     ch[1] -> sum + key + ch[0] -> suffix);
        maxsum = max(max(ch[0] -> maxsum, ch[1] -> maxsum),
                     ch[0] -> suffix + key + ch[1] -> prefix);

        if (!heap.empty()) {
            prefix = max(prefix,
                         ch[0] -> sum + key + heap.top());
            suffix = max(suffix,
                         ch[1] -> sum + key + heap.top());
            maxsum = max(maxsum, max(ch[0] -> suffix,
                                     ch[1] -> prefix) + key + heap.top());

            if (heap.size() > 1) {
                maxsum = max(maxsum, heap.top2() + key);
            }
        }
    }
} null[maxn << 1], *ptr = null;

void addedge(int, int, int);
void deledge(int, int);
void modify(int, int, int);
void modify_color(int);
node *newnode(int);
node *access(node *);
void makeroot(node *);
void link(node *, node *);
void cut(node *, node *);
void splay(node *);
void rot(node *, int);

queue<node *> freenodes;
tree<pair<int, int>, node *> mp;

bool col[maxn] = {false};
char c;
int n, m, k, x, y, z;

int main() {
    null -> ch[0] = null -> ch[1] = null -> p = null;
    scanf("%d%d%d", &n, &m, &k);

    for (int i = 1; i <= n; i++)
        newnode(0);

    heap.push(0);

    while (k--) {
        scanf("%d", &x);

        col[x] = true;
        null[x].heap.push(0);
    }
```

```

    for (int i = 1; i < n; i++) {
        scanf("%d%d%d", &x, &y, &z);

        if (x > y)
            swap(x, y);
        addedge(x, y, z);
    }

    while (m--) {
        scanf(" %c%d", &c, &x);

        if (c == 'A') {
            scanf("%d", &y);

            if (x > y)
                swap(x, y);
            deledge(x, y);
        }
        else if (c == 'B') {
            scanf("%d%d", &y, &z);

            if (x > y)
                swap(x, y);
            addedge(x, y, z);
        }
        else if (c == 'C') {
            scanf("%d%d", &y, &z);

            if (x > y)
                swap(x, y);
            modify(x, y, z);
        }
        else
            modify_color(x);

        printf("%lld\n", (heap.top() > 0 ? heap.top() : -1));
    }

    return 0;
}

void addedge(int x, int y, int z) {
    node *tmp;
    if (freenodes.empty())
        tmp = newnode(z);
    else {
        tmp = freenodes.front();
        freenodes.pop();
        *tmp = node(z);
    }

    tmp -> ch[0] = tmp -> ch[1] = tmp -> p = null;

    heap.push(tmp -> maxsum);
    link(tmp, null + x);
    link(tmp, null + y);
    mp[make_pair(x, y)] = tmp;
}

void deledge(int x, int y) {
    node *tmp = mp[make_pair(x, y)];

    cut(tmp, null + x);
    cut(tmp, null + y);

    freenodes.push(tmp);
    heap.erase(tmp -> maxsum);
    mp.erase(make_pair(x, y));
}

void modify(int x, int y, int z) {
    node *tmp = mp[make_pair(x, y)];
    makeroot(tmp);
    tmp -> pushdown();

    heap.erase(tmp -> maxsum);
    tmp -> key = z;
    tmp -> refresh();
    heap.push(tmp -> maxsum);
}

void modify_color(int x) {
    makeroot(null + x);
    col[x] ^= true;

    if (col[x])
        null[x].heap.push(0);
    else
        null[x].heap.erase(0);

    heap.erase(null[x].maxsum);
    null[x].refresh();
    heap.push(null[x].maxsum);
}

node *newnode(int k) {
    *(++ptr) = node(k);
    ptr -> ch[0] = ptr -> ch[1] = ptr -> p = null;
    return ptr;
}

node *access(node *x) {
    splay(x);
    heap.erase(x -> maxsum);
    x -> refresh();

    if (x -> ch[1] != null) {
        x -> ch[1] -> pushdown();
        x -> heap.push(x -> ch[1] -> prefix);
        x -> refresh();
        heap.push(x -> ch[1] -> maxsum);
    }

    x -> ch[1] = null;
    x -> refresh();
    node *y = x;
    x = x -> p;

    while (x != null) {
        splay(x);
        heap.erase(x -> maxsum);

        if (x -> ch[1] != null) {
            x -> ch[1] -> pushdown();
            x -> heap.push(x -> ch[1] -> prefix);
            heap.push(x -> ch[1] -> maxsum);
        }

        x -> heap.erase(y -> prefix);
        x -> ch[1] = y;
        (y = x) -> refresh();
        x = x -> p;
    }

    heap.push(y -> maxsum);
    return y;
}

void makeroot(node *x) {
    access(x);
    splay(x);
    x -> rev ^= true;
```

```
}

void link(node *x, node *y) { // 新添一条虚边，维护y对应的堆
    makeroot(x);
    makeroot(y);

    x -> pushdown();
    x -> p = y;
    heap.erase(y -> maxsum);
    y -> heap.push(x -> prefix);
    y -> refresh();
    heap.push(y -> maxsum);
}

void cut(node *x, node *y) { // 断开一条实边，一条链变成两条链，需要维护全局堆
    makeroot(x);
    access(y);
    splay(y);

    heap.erase(y -> maxsum);
    heap.push(y -> ch[0] -> maxsum);
    y -> ch[0] -> p = null;
    y -> ch[0] = null;
    y -> refresh();
    heap.push(y -> maxsum);
}

void splay(node *x) {
    x -> pushdown();

    while (!isroot(x)) {
        if (!isroot(x -> p))
            x -> p -> p -> pushdown();

        x -> p -> pushdown();
        x -> pushdown();

        if (isroot(x -> p)) {
            rot(x -> p, dir(x) ^ 1);
            break;
        }

        if (dir(x) == dir(x -> p))
            rot(x -> p -> p, dir(x -> p) ^ 1);
        else
            rot(x -> p, dir(x) ^ 1);

        rot(x -> p, dir(x) ^ 1);
    }
}

void rot(node *x, int d) {
    node *y = x -> ch[d ^ 1];

    if ((x -> ch[d ^ 1] = y -> ch[d]) != null)
        y -> ch[d] -> p = x;

    y -> p = x -> p;

    if (!isroot(x))
        x -> p -> ch[dir(x)] = y;

    (y -> ch[d] = x) -> p = y;

    x -> refresh();
    y -> refresh();
}
```

4.8 K-D 树

4.8.1 动态 K-D 树（定期重构）

```
int l[2], r[2], x[B + 10][2], w[B + 10];
int n, op, ans = 0, cnt = 0, tmp = 0;
int d;

struct node {
    int x[2], l[2], r[2], w, sum;
    node *ch[2];

    bool operator < (const node &a) const {
        return x[d] < a.x[d];
    }

    void refresh() {
        sum = ch[0] -> sum + ch[1] -> sum + w;
        l[0] = min(x[0], min(ch[0] -> l[0], ch[1] -> l[0]));
        l[1] = min(x[1], min(ch[0] -> l[1], ch[1] -> l[1]));
        r[0] = max(x[0], max(ch[0] -> r[0], ch[1] -> r[0]));
        r[1] = max(x[1], max(ch[0] -> r[1], ch[1] -> r[1]));
    }
} null[maxn], *root = null;

void build(int l, int r, int k, node *&rt) {
    if (l > r) {
        rt = null;
        return;
    }

    int mid = (l + r) / 2;

    d = k;
    nth_element(null + l, null + mid, null + r + 1);

    rt = null + mid;
    build(l, mid - 1, k ^ 1, rt -> ch[0]);
    build(mid + 1, r, k ^ 1, rt -> ch[1]);

    rt -> refresh();
}

void query(node *rt) {
    if (l[0] <= rt -> l[0] && l[1] <= rt -> l[1] && rt -> r[0] <= r[0] && rt -> r[1] <= r[1]) {
        ans += rt -> sum;
        return;
    }
    else if (l[0] > rt -> r[0] || l[1] > rt -> r[1] || r[0] < rt -> l[0] || r[1] < rt -> l[1])
        return;

    if (l[0] <= rt -> x[0] && l[1] <= rt -> x[1] && rt -> x[0] <= r[0] && rt -> x[1] <= r[1])
        ans += rt -> w;

    query(rt -> ch[0]);
    query(rt -> ch[1]);
}

int main() {

    null -> l[0] = null -> l[1] = 10000000;
    null -> r[0] = null -> r[1] = -10000000;
    null -> sum = 0;
    null -> ch[0] = null -> ch[1] = null;
    scanf("%*d");

```

```
    while (scanf("%d", &op) == 1 && op != 3) {
        if (op == 1) {
            tmp++;
            scanf("%d%d%d", &x[tmp][0], &x[tmp][1], &w[tmp]);
            x[tmp][0] ^= ans;
            x[tmp][1] ^= ans;
            w[tmp] ^= ans;

            if (tmp == B) {
                for (int i = 1; i <= tmp; i++) {
                    null[cnt + i].x[0] = x[i][0];
                    null[cnt + i].x[1] = x[i][1];
                    null[cnt + i].w = w[i];
                }

                build(1, cnt += tmp, 0, root);
                tmp = 0;
            }
        }
        else {
            scanf("%d%d%d%d", &l[0], &l[1], &r[0], &r[1]);
            l[0] ^= ans;
            l[1] ^= ans;
            r[0] ^= ans;
            r[1] ^= ans;
            ans = 0;

            for (int i = 1; i <= tmp; i++)
                if (l[0] <= x[i][0] && l[1] <= x[i][1] && x[i][0] <= r[0] && x[i][1] <= r[1])
                    ans += w[i];

            query(root);
            printf("%d\n", ans);
        }
    }

    return 0;
}
```

4.9 LCA

4.9.1 Tarjan LCA $O(n+m)$

```
vector<pair<int, int> > q[maxn];
int lca[maxn];

void dfs(int x) {
    dfn[x] = ++tim; // 其实求LCA是用不到DFS序的，但是一般其他步骤要用
    ufs[x] = x;

    for (auto pi : q[x]) {
        int y = pi.first, i = pi.second;
        if (dfn[y])
            lca[i] = findufs(y);
    }

    for (int y : G[x])
        if (y != p[x]) {
            p[y] = x;
            dfs(y);
        }

    ufs[x] = p[x];
}
```

4.10 虚树

```
struct Tree {
    vector<int> G[maxn], W[maxn];
    int p[maxn], d[maxn], size[maxn], mn[maxn], mx[maxn];
    bool col[maxn];
    long long ans_sum;
    int ans_min, ans_max;

    void add(int x, int y, int z) {
        G[x].push_back(y);
        W[x].push_back(z);
    }

    void dfs(int x) {
        size[x] = col[x];
        mx[x] = (col[x] ? d[x] : -inf);
        mn[x] = (col[x] ? d[x] : inf);

        for (int i = 0; i < (int)G[x].size(); i++) {
            d[G[x][i]] = d[x] + W[x][i];
            dfs(G[x][i]);
            ans_sum += (long long)size[x] * size[G[x][i]] * d[x];
            ans_max = max(ans_max, mx[x] + mx[G[x][i]] - (d[x] << 1));
            ans_min = min(ans_min, mn[x] + mn[G[x][i]] - (d[x] << 1));
            size[x] += size[G[x][i]];
            mx[x] = max(mx[x], mx[G[x][i]]);
            mn[x] = min(mn[x], mn[G[x][i]]);
        }
    }

    void clear(int x) {
        G[x].clear();
        W[x].clear();
        col[x] = false;
    }

    void solve(int rt) {
        ans_sum = 0;
        ans_max = -inf;
        ans_min = inf;
        dfs(rt);
        ans_sum <<= 1;
    }
} virtree;

void dfs(int);
int LCA(int, int);

vector<int> G[maxn];
int f[maxn][20], d[maxn], dfn[maxn], tim = 0;

bool cmp(int x, int y) {
    return dfn[x] < dfn[y];
}

int n, m, lgn = 0, a[maxn], s[maxn], v[maxn];

int main() {
    scanf("%d", &n);

    for (int i = 1, x, y; i < n; i++) {
        scanf("%d%d", &x, &y);
        G[x].push_back(y);
        G[y].push_back(x);
    }

    G[n + 1].push_back(1);
```

```
    dfs(n + 1);

    for (int i = 1; i <= n + 1; i++)
        G[i].clear();

    lgn--;

    for (int j = 1; j <= lgn; j++)
        for (int i = 1; i <= n; i++)
            f[i][j] = f[f[i][j - 1]][j - 1];

    scanf("%d", &m);

    while (m--) {
        int k;
        scanf("%d", &k);

        for (int i = 1; i <= k; i++)
            scanf("%d", &a[i]);

        sort(a + 1, a + k + 1, cmp);
        int top = 0, cnt = 0;
        s[++top] = v[++cnt] = n + 1;
        long long ans = 0;

        for (int i = 1; i <= k; i++) {
            virtree.col[a[i]] = true;
            ans += d[a[i]] - 1;
            int u = LCA(a[i], s[top]);

            if (s[top] != u) {
                while (top > 1 && d[s[top - 1]] >= d[u]) {
                    virtree.add(s[top - 1], s[top], d[s[top]] - d[s[top - 1]]);
                    top--;
                }

                if (s[top] != u) {
                    virtree.add(u, s[top], d[s[top]] - d[u]);
                    s[top] = v[++cnt] = u;
                }
            }

            s[++top] = a[i];
        }

        for (int i = top - 1; i; i--)
            virtree.add(s[i], s[i + 1], d[s[i + 1]] - d[s[i]]);

        virtree.solve(n + 1);
        ans *= k - 1;
        printf("%lld %d %d\n", ans - virtree.ans_sum, virtree.ans_min, virtree.ans_max);

        for (int i = 1; i <= k; i++)
            virtree.clear(a[i]);
        for (int i = 1; i <= cnt; i++)
            virtree.clear(v[i]);

    }

    return 0;
}

void dfs(int x) {
    dfn[x] = ++tim;
    d[x] = d[f[x][0]] + 1;

    while ((1 << lgn) < d[x])
        lgn++;

    for (int i = 0; i < (int)G[x].size(); i++)
        if (G[x][i] != f[x][0]) {
            f[G[x][i]][0] = x;
            dfs(G[x][i]);
        }
}

int LCA(int x, int y) {
    if (d[x] != d[y]) {
        if (d[x] < d[y])
            swap(x, y);

        for (int i = lgn; i >= 0; i--)
            if (((d[x] - d[y]) >> i) & 1)
                x = f[x][i];
    }

    if (x == y)
        return x;

    for (int i = lgn; i >= 0; i--)
        if (f[x][i] != f[y][i]) {
            x = f[x][i];
            y = f[y][i];
        }

    return f[x][0];
}
```

4.11 长链剖分

```
// 顾名思义，长链剖分是取最深的儿子作为重儿子

// O(n) 维护以深度为下标的子树信息
vector<int> G[maxn], v[maxn];
int n, p[maxn], h[maxn], son[maxn], ans[maxn];

// 原题题意：求每个点的子树中与它距离是几的点最多，相同的取最大深度
// 由于vector只能在后面加入元素，为了写代码方便，这里反过来存
// 或者开一个结构体维护倒过来的vector
void dfs(int x) {
    h[x] = 1;

    for (int y : G[x])
        if (y != p[x]){
            p[y] = x;
            dfs(y);

            if (h[y] > h[son[x]])
                son[x] = y;
        }

    if (!son[x]) {
        v[x].push_back(1);
        ans[x] = 0;
        return;
    }

    h[x] = h[son[x]] + 1;
    swap(v[x],v[son[x]]);

    if (v[x][ans[son[x]]] == 1)
        ans[x] = h[x] - 1;
    else
        ans[x] = ans[son[x]];

    v[x].push_back(1);
```

```

    int mx = v[x][ans[x]];
    for (int y : G[x])
        if (y != p[x] && y != son[x]) {
            for (int j = 1; j <= h[y]; j++) {
                v[x][h[x] - j - 1] += v[y][h[y] - j];

                int t = v[x][h[x] - j - 1];
                if (t > mx || (t == mx && h[x] - j - 1 > ans[x])) {
                    mx = t;
                    ans[x] = h[x] - j - 1;
                }
            }

            v[y].clear();
        }
}
```

4.11.1 梯子剖分

```
// 在线求一个点的第k祖先 O(n\log n)-O(1)
// 理论基础：任意一个点x的k级祖先y所在长链长度一定>=k

// 全局数组定义
vector<int> G[maxn], v[maxn];
int d[maxn], mxd[maxn], son[maxn], top[maxn], len[maxn];
int f[19][maxn], log_tbl[maxn];

// 在主函数中两遍dfs之后加上如下预处理
log_tbl[0] = -1;
for (int i = 1; i <= n; i++)
    log_tbl[i] = log_tbl[i / 2] + 1;
for (int j = 1; (1 << j) < n; j++)
    for (int i = 1; i <= n; i++)
        f[j][i] = f[j - 1][f[j - 1][i]];

// 第一遍dfs，用于计算深度和找出重儿子
void dfs1(int x) {
    mxd[x] = d[x];

    for (int y : G[x])
        if (y != f[0][x]){
            f[0][y] = x;
            d[y] = d[x] + 1;

            dfs1(y);

            mxd[x] = max(mxd[x], mxd[y]);
            if (mxd[y] > mxd[son[x]])
                son[x] = y;
        }
}

// 第二遍dfs，用于进行剖分和预处理梯子剖分（每条链向上延伸一倍）数组
void dfs2(int x) {
    top[x] = (x == son[f[0][x]] ? top[f[0][x]] : x);

    for (int y : G[x])
        if (y != f[0][x])
            dfs2(y);

    if (top[x] == x) {
        int u = x;
        while (top[son[u]] == x)
            u = son[u];

        len[x] = d[u] - d[x];
        for (int i = 0; i < len[x]; i++, u = f[0][u])
            v[x].push_back(u);

        u = x;
        for (int i = 0; i < len[x] && u; i++, u = f[0][u])
            v[x].push_back(u);
    }
}

// 在线询问x的k级祖先 O(1)
// 不存在时返回0
int query(int x, int k) {
    if (!k)
        return x;
    if (k > d[x])
        return 0;

    x = f[log_tbl[k]][x];
    k ^= 1 << log_tbl[k];
    return v[top[x]][d[top[x]] + len[top[x]] - d[x] + k];
}
```

4.12 堆

4.12.1 左偏树

参见 3.2.3.k 短路（第 29 页）。

4.12.2 二叉堆

```
struct my_binary_heap {
    static constexpr int maxn = 100005;

    int a[maxn], size;

    my_binary_heap() : size(0) {}

    void push(int val) {
        a[++size] = val;

        for (int x = size; x > 1; x /= 2) {
            if (a[x] < a[x / 2])
                swap(a[x], a[x / 2]);
            else
                break;
        }
    }

    int &top() {
        return a[1];
    }

    int pop() {
        int res = a[1];
        a[1] = a[size--];

        for (int x = 1, son; ; x = son) {
            if (x * 2 == size)
                son = x * 2;
            else if (x * 2 > size)
                break;
            else if (a[x * 2] < a[x * 2 + 1])
                son = x * 2;
            else
                son = x * 2 + 1;

            if (a[son] < a[x])
                swap(a[x], a[son]);
            else
                break;
```

```
        }

        return res;
    }
};
```

4.13 莫队

注意如果 n 和 q 不平衡，块大小应该设为 $\frac{n}{\sqrt{q}}$。
另外，如果裸的莫队要卡常，可以按块编号奇偶性分别对右端点正序或者倒序排序，期望可以减少一半的移动次数。

4.13.1 莫队二次离线

适用范围：询问的是点对相关（或者其它可以枚举每个点和区间算贡献）的信息，并且可以离线；更新时可以使用一些牺牲修改复杂度来改善询问复杂度的数据结构（如单点修改询问区间和）。
先按照普通的莫队将区间排序。考虑区间移动的情况，以 (l, r) 向右移动右端点到 (l, t) 为例。
对于每个 $i \in (r, t]$ 来说，它都要对区间 $[l, i)$ 算贡献。可以拆成 $[1, i)$ 和 $[1, l)$ 两部分，那么前一部分因为都是 i 和 $[1, i)$ 做贡献的形式，可以直接预处理。
考虑后一部分，i 和 $(1, l]$ 做贡献。因为莫队的性质，我们可以保证这样的询问次数不超过 $O((n+m)\sqrt{n})$，因此我们可以对每个 l 记录下来哪些 i 要和它询问。并且每次移动时询问的 i 都是连续的，所以对每个 l 开一个 `vector` 记录下对应的区间和编号就行了。
剩余的三种情况（右端点左移或者移动左端点）都是类似的，具体可以看代码。
例题：Yuno loves sqrt technology II（询问区间逆序对数）

```
#include <bits/stdc++.h>

using namespace std;

constexpr int maxn = 100005, B = 314;

struct Q {
    int l, r, d, id;

    Q() = default;

    Q(int l, int r, int d, int id) : l(l), r(r), d(d), id(id) {}

    friend bool operator < (const Q &a, const Q &b) {
        if (a.d != b.d)
            return a.d < b.d;

        return a.r < b.r;
    }
} q[maxn]; // 结构体可以复用，d既可以作为左端点块编号，也可以作为二次离线处理的倍数

int global_n, bid[maxn], L[maxn], R[maxn], cntb;

int sa[maxn], sb[maxn];

void addp(int x) { // sqrt(n) 修改 O(1) 查询
    for (int k = bid[x]; k <= cntb; k++)
        sb[k]++;

    for (int i = x; i <= R[bid[x]]; i++)
        sa[i]++;
}

int queryp(int x) {
    if (!x)
        return 0;

    return sa[x] + sb[bid[x] - 1];
}

void adds(int x) {
    for (int k = 1; k <= bid[x]; k++)
        sb[k]++;

    for (int i = L[bid[x]]; i <= x; i++)
        sa[i]++;
}

int querys(int x) {
    if (x > global_n)
        return 0; // 为了防止越界就判一下
    return sa[x] + sb[bid[x] + 1];
}

vector<Q> vp[maxn], vs[maxn]; // prefix, suffix

long long fp[maxn], fs[maxn]; // prefix, suffix

int a[maxn], b[maxn];

long long ta[maxn], ans[maxn];

int main() {

    int n, m;
    scanf("%d%d", &n, &m);

    global_n = n;

    for (int i = 1; i <= n; i++)
        scanf("%d", &a[i]);

    memcpy(b, a, sizeof(int) * (n + 1));
    sort(b + 1, b + n + 1);

    for (int i = 1; i <= n; i++)
        a[i] = lower_bound(b + 1, b + n + 1, a[i]) - b;

    for (int i = 1; i <= n; i++) {
        bid[i] = (i - 1) / B + 1;

        if (!L[bid[i]])
            L[bid[i]] = i;

        R[bid[i]] = i;
        cntb = bid[i];
    }

    for (int i = 1; i <= m; i++) {
        scanf("%d%d", &q[i].l, &q[i].r);

        q[i].d = bid[q[i].l];
        q[i].id = i;
    }

    sort(q + 1, q + m + 1);

    int l = 2, r = 1; // l, r是上一个询问的端点

    for (int i = 1; i <= m; i++) {
        int s = q[i].l, t = q[i].r; // s, t是当前要调整到的端点

        if (s < l)
            vs[r + 1].push_back(Q(s, l - 1, 1, i));
        else if (s > l)
            vs[r + 1].push_back(Q(l, s - 1, -1, i));

        l = s;
```

```
        if (t > r)
            vp[l - 1].push_back(Q(r + 1, t, 1, i));
        else if (t < r)
            vp[l - 1].push_back(Q(t + 1, r, -1, i));

        r = t;
    }

    for (int i = 1; i <= n; i++) { // 第一遍正着处理，解决关于前缀的询问
        fp[i] = fp[i - 1] + querys(a[i] + 1);

        adds(a[i]);

        for (auto q : vp[i]) {
            long long tmp = 0;
            for (int k = q.l; k <= q.r; k++)
                tmp += querys(a[k] + 1);

            ta[q.id] -= q.d * tmp;
        }
    }

    memset(sa, 0, sizeof(sa));
    memset(sb, 0, sizeof(sb));

    for (int i = n; i; i--) { // 第二遍倒着处理，解决关于后缀的询问
        fs[i] = fs[i + 1] + queryp(a[i] - 1);

        addp(a[i]);

        for (auto q : vs[i]) {
            long long tmp = 0;
            for (int k = q.l; k <= q.r; k++)
                tmp += queryp(a[k] - 1);

            ta[q.id] -= q.d * tmp;
        }
    }

    l = 2;
    r = 1;

    for (int i = 1; i <= m; i++) { // 求出fs和fp之后再加上这部分的贡献
        int s = q[i].l, t = q[i].r;

        ta[i] += fs[s] - fs[l];
        ta[i] += fp[t] - fp[r];

        l = s;
        r = t;

        ta[i] += ta[i - 1]; // 因为算出来的是相邻两个询问之间的贡献，所以要前缀和
        ans[q[i].id] = ta[i];
    }

    for (int i = 1; i <= m; i++)
        printf("%lld\n", ans[i]);

    return 0;
}
```

4.13.2 带修莫队在线化 $O(n^{\frac{5}{3}})$

最简单的带修莫队：块大小设成 $n^{\frac{2}{3}}$，排序时第一关键字是左端点块编号，第二关键字是右端点块编号，第三关键字是时间。（记得把时间压缩成只有修改的时间。）

现在要求在线的同时支持修改，仍然以 $B = n^{\frac{2}{3}}$ 分一块，预处理出两块之间的贡献，那么预处理复杂度就是 $O(n^{\frac{5}{3}})$。

修改时最简单的方法是直接把 $n^{\frac{2}{3}}$ 个区间全更新一遍。嫌慢的话可以给每个区间打一个懒标记，询问的时候如果解了再更新区间的信息。注意如果附加信息是可减的（比如每个数的出现次数），那么就只需要存 $O(n^{\frac{1}{3}})$ 个。

总复杂度仍然是 $O(n^{\frac{5}{3}})$，如果打懒标记的话是跑不太满的。如果附加信息可减，则空间复杂度是 $O(n^{\frac{4}{3}})$，否则和时间复杂度同阶。

4.13.3 莫队二次离线在线化 $O((n+m)\sqrt{n})$

和之前的道理是一样的，i 和 $[1, i)$ 的贡献这部分仍然可以预处理掉，而前后缀对区间的贡献那部分只保存块端点处的信息。

按照莫队二次离线的转移方法操作之后，发现只剩两边散块的贡献没有解决。这时可以具体问题具体解决，例如求逆序对的话直接预处理出排序后的数组，询问的时候归并即可。

时空复杂度均为 $O(n\sqrt{n})$。

以下代码以强制在线求区间逆序对为例。（洛谷上被卡常了，正常情况下极限数据应该在 1.5s 内。）

```
constexpr int maxn = 100005, B = 315, maxb = maxn / B + 5;

int n, bid[maxn], L[maxb], R[maxb], cntb;

struct DS { // O(sqrt(n)) 修改  O(1) 查询
    int total;
    int sa[maxn], sb[maxb];

    void init(const DS &o) {
        total = o.total;
        memcpy(sa, o.sa, sizeof(int) * (n + 1));
        memcpy(sb, o.sb, sizeof(int) * (cntb + 1));
    }

    void add(int x) {
        total++;
        for (int k = 1; k <= bid[x]; k++)
            sb[k]++;
        for (int i = L[bid[x]]; i <= x; i++)
            sa[i]++;
    }

    int querys(int x) {
        if (x > n)
            return 0;

        return sb[bid[x] + 1] + sa[x];
    }

    int queryp(int x) {
        return total - querys(x + 1);
    }
} pr[maxb];

int c[maxn]; // 树状数组

void addc(int x, int d) {
    while (x) {
        c[x] += d;
        x -= x & -x;
    }
}

int queryc(int x) {
    int ans = 0;
    while (x <= n) {
        ans += c[x];
        x += x & -x;
    }
```

```cpp
    return ans;
}

long long fp[maxn], fs[maxn];

int rnk[maxn], val[maxn][B + 5];

long long dat[maxb][maxb];

int a[maxn];

int main() {

    int m;
    cin >> n >> m;

    for (int i = 1; i <= n; i++) {
        cin >> a[i];

        bid[i] = (i - 1) / B + 1;
        if (!L[bid[i]])
            L[bid[i]] = i;
        R[bid[i]] = i;
        cntb = bid[i];

        rnk[i] = i;
    }

    for (int k = 1; k <= cntb; k++)
        sort(rnk + L[k], rnk + R[k] + 1, [](int x, int y) {return a[x] < a[y];}); // 每个块排序

    for (int i = n; i; i--)
        for (int j = 2; i + j - 1 <= R[bid[i]]; j++) {
            val[i][j] = val[i + 1][j - 1] + val[i][j - 1] - val[i + 1][j - 2];
            if (a[i] > a[i + j - 1])
                val[i][j]++; // 块内用二维前缀和预处理
        }

    for (int k = 1; k <= cntb; k++) {
        for (int i = L[k]; i <= R[k]; i++) {
            dat[k][k] += queryc(a[i] + 1); // 单块内的逆序对直接用树状数组预处理
            addc(a[i], 1);
        }

        for (int i = L[k]; i <= R[k]; i++)
            addc(a[i], -1);
    }

    for (int i = 1; i <= n; i++) {
        if (i > 1 && i == L[bid[i]])
            pr[bid[i]].init(pr[bid[i] - 1]);

        fp[i] = fp[i - 1] + pr[bid[i]].querys(a[i] + 1);

        pr[bid[i]].add(a[i]);
    }

    for (int i = n; i; i--) {
        fs[i] = fs[i + 1] + (n - i - queryc(a[i] + 1));
        addc(a[i], 1);
    }

    for (int s = 1; s <= cntb; s++)
        for (int t = s + 1; t <= cntb; t++) {
            dat[s][t] = dat[s][t - 1] + dat[t][t];

            for (int i = L[t]; i <= R[t]; i++) // 块间的逆序对用刚才处理的分块求出
                dat[s][t] += pr[t - 1].querys(a[i] + 1) - pr[s - 1].querys(a[i] + 1);
        }

    long long ans = 0;

    while (m--) {
        long long s, t;
        cin >> s >> t;

        int l = s ^ ans, r = t ^ ans;

        if (bid[l] == bid[r])
            ans = val[l][r - l + 1];
        else {
            ans = dat[bid[l] + 1][bid[r] - 1];

            ans += fp[r] - fp[L[bid[r]] - 1];
            for (int i = L[bid[r]]; i <= r; i++)
                ans -= pr[bid[l]].querys(a[i] + 1);

            ans += fs[l] - fs[R[bid[l]] + 1];
            for (int i = l; i <= R[bid[l]]; i++)
                ans -= (a[i] - 1) - pr[bid[r] - 1].queryp(a[i] - 1);

            int i = L[bid[l]], j = L[bid[r]], w = 0; // 手写归并

            while (true) {
                while (i <= R[bid[l]] && rnk[i] < l)
                    i++;
                while (j <= R[bid[r]] && rnk[j] > r)
                    j++;

                if (i > R[bid[l]] && j > R[bid[r]])
                    break;

                int x = (i <= R[bid[l]] ? a[rnk[i]] : (int)1e9), y = (j <= R[bid[r]] ? a[rnk[j]] : (int)1e9);

                if (x < y) {
                    ans += w;
                    i++;
                }
                else {
                    j++;
                    w++;
                }
            }
        }

        cout << ans << '\n';
    }

    return 0;
}
```

4.13.4 例题

子区间最小值之和

(HNOI2016 序列)

待完成。

4.14 常见根号思路

1. **通用**

- 出现次数大于 $\sqrt{n}$ 的数不会超过 $\sqrt{n}$ 个

- 对于带修改问题，如果不方便分治或者二进制分组，可以考虑对操作分块（定期重建），每次查询时暴力最后的 $\sqrt{n}$ 个修改并更正答案
- **根号分治**：如果分治时每个子问题需要 $O(N)$（N 是全局问题的大小的时间），而规模较小的子问题可以 $O(n^2)$ 解决，则可以使用根号分治
  - 规模大于 $\sqrt{n}$ 的子问题用 $O(N)$ 的方法解决，规模小于 $\sqrt{n}$ 的子问题用 $O(n^2)$ 暴力
  - 规模大于 $\sqrt{n}$ 的子问题最多只有 $\sqrt{n}$ 个
  - 规模不大于 $\sqrt{n}$ 的子问题大小的平方和也必定不会超过 $n\sqrt{n}$
- 如果输入规模之和不大于 n（例如给定多个小字符串与大字符串进行询问），那么规模超过 $\sqrt{n}$ 的问题最多只有 $\sqrt{n}$ 个

2. **序列**

- 某些维护序列的问题可以用分块/块状链表维护
- 对于静态区间询问问题，如果可以快速将左/右端点移动一位，可以考虑莫队
  - 如果强制在线可以分块预处理，但是一般空间需要 $n\sqrt{n}$
    - 例题：询问区间中有几种数出现次数恰好为 k，强制在线
  - 如果带修改可以试着想一想带修莫队，但是复杂度高达 $n^{\frac{5}{3}}$
- 线段树可以解决的问题也可以用分块来做到 $O(1)$ 询问或是 $O(1)$ 修改，具体要看哪种操作更多

3. **树**

- 与序列类似，树上也有树分块和树上莫队
  - 树上带修莫队很麻烦，常数也大，最好不要先考虑
  - 树分块不要想当然
- 树分治也可以套根号分治，道理是一样的

4. **字符串**

- 循环节长度大于 $\sqrt{n}$ 的子串最多只有 $O(n)$ 个，如果是极长子串则只有 $O(\sqrt{n})$ 个

5 字符串

5.1 KMP

```
int fail[maxn];

void kmp(const char *s, int n) {
    fail[0] = fail[1] = 0;

    for (int i = 1; i < n; i++) {
        int j = fail[i];

        while (j && s[i + 1] != s[j + 1])
            j = fail[j];

        if (s[i + 1] == s[j + 1])
            fail[i + 1] = j + 1;
        else
            fail[i + 1] = 0;
    }
}
```

5.1.1 ex-KMP

```
void exkmp(const char *s, int *a, int n) {
    int l = 0, r = 0;
    a[0] = n;

    for (int i = 1; i <= n; i++) {
        a[i] = i > r ? 0 : min(r - i + 1, a[i - l]);

        while (i + a[i] < n && s[a[i]] == s[i + a[i]])
            a[i]++;

        if (i + a[i] - 1 > r) {
            l = i;
            r = i + a[i] - 1;
        }
    }
}
```

5.2 AC 自动机

```
int ch[maxm][26], f[maxm][26], q[maxm], sum[maxm], cnt = 0;

// 在字典树中插入一个字符串 O(n)
int insert(const char *c) {
    int x = 0;
    while (*c) {
        if (!ch[x][*c - 'a'])
            ch[x][*c - 'a'] = ++cnt;
        x = ch[x][*c++ - 'a'];
    }
    return x;
}

// 建AC自动机 O(n * sigma)
void getfail() {
    int x, head = 0, tail = 0;

    for (int c = 0; c < 26; c++)
        if (ch[0][c])
            q[tail++] = ch[0][c]; // 把根节点的儿子加入队列

    while (head != tail) {
        x = q[head++];

        G[f[x][0]].push_back(x);
        fill(f[x] + 1, f[x] + 26, cnt + 1);

        for (int c = 0; c < 26; c++) {
            if (ch[x][c]) {
                int y = f[x][0];

                f[ch[x][c]][0] = ch[y][c];
                q[tail++] = ch[x][c];
            }
            else
                ch[x][c] = ch[f[x][0]][c];
        }
    }
    fill(f[0], f[0] + 26, cnt + 1);
}
```

5.3 后缀数组

5.3.1 倍增

```
constexpr int MAXN = 1000005;

void get_sa(char *s, int n, int *sa, int *rnk, int *height) { // 1-based
    static int buc[MAXN], id[MAXN], p[MAXN], t[MAXN];

    int m = 300;

    for (int i = 1; i <= n; i++)
        buc[rnk[i] = s[i]]++;
    for (int i = 1; i <= m; i++)
        buc[i] += buc[i - 1];
    for (int i = n; i; i--)
        sa[buc[rnk[i]]--] = i;

    memset(buc, 0, sizeof(int) * (m + 1));

    for (int k = 1, cnt = 0; cnt != n; k *= 2, m = cnt) {
        cnt = 0;

        for (int i = n; i > n - k; i--)
            id[++cnt] = i;
        for (int i = 1; i <= n; i++)
            if (sa[i] > k)
                id[++cnt] = sa[i] - k;

        for (int i = 1; i <= n; i++)
            buc[p[i] = rnk[id[i]]]++;
        for (int i = 1; i <= m; i++)
            buc[i] += buc[i - 1];
        for (int i = n; i; i--)
            sa[buc[p[i]]--] = id[i];

        memset(buc, 0, sizeof(int) * (m + 1));

        memcpy(t, rnk, sizeof(int) * (n + 1));
        t[n + 1] = 0; // 记得清空 n + 1

        cnt = 0;
        for (int i = 1; i <= n; i++) {
            if (t[sa[i]] != t[sa[i - 1]] || t[sa[i] + k] != t[sa[i - 1] + k])
                cnt++;

            rnk[sa[i]] = cnt;
        }
    }

    for (int i = 1; i <= n; i++)
```

```
        sa[rnk[i]] = i;

    for (int i = 1, k = 0; i <= n; i++) {
        if (k)
            k--;

        if (rnk[i] > 1) // 两个都要判，否则会左/右越界
            while (sa[rnk[i] - 1] + k <= n && s[i + k] == s[sa[rnk[i] - 1] + k])
                k++;

        height[rnk[i]] = k;
    }
}
```

5.3.2 SA-IS

```
constexpr int l_type = 0, s_type = 1;

// 判断一个字符是否为LMS字符
bool is_lms(vector<int>& tp, int x) {
    return x > 0 && tp[x] == s_type && tp[x - 1] == l_type;
}

// 判断两个LMS子串是否相同
bool equal_substr(int* s, int x, int y, vector<int>& tp) {
    do {
        if (s[x] != s[y])
            return false;
        x++;
        y++;
    } while (!is_lms(tp, x) && !is_lms(tp, y));

    return s[x] == s[y];
}

// s 是输入字符串，len 是字符串的长度，m 是字符集的大小
vector<int> sais(int *s, int len, int m) {
    int n = len - 1;

    vector<int> tp(n + 1), pos(n + 1), name(n + 1, -1), sa(n + 1, -1);
    vector<int> buc(m + 1), lbuc(m + 1), sbuc(m + 1);

    // 诱导排序（从 * 型诱导到 L 型，从 L 型诱导到 S 型）
    // 调用之前应将 * 型按要求放入 SA 中
    auto induced_sort = [&]() {
        for (int i = 0; i <= n; i++)
            if (sa[i] > 0 && tp[sa[i] - 1] == l_type)
                sa[lbuc[s[sa[i] - 1]]++] = sa[i] - 1;

        for (int i = 1; i <= m; i++)
            sbuc[i] = buc[i] - 1;

        for (int i = n; ~i; i--)
            if (sa[i] > 0 && tp[sa[i] - 1] == s_type)
                sa[sbuc[s[sa[i] - 1]]--] = sa[i] - 1;
    };

    for (int i = 0; i <= n; i++)
        buc[s[i]]++;

    for (int i = 1; i <= m; i++) {
        buc[i] += buc[i - 1];

        lbuc[i] = buc[i - 1];
        sbuc[i] = buc[i] - 1;
    }

    tp[n] = s_type;
    for (int i = n - 1; ~i; i--) {
        if (s[i] < s[i + 1])
            tp[i] = s_type;
        else if (s[i] > s[i + 1])
            tp[i] = l_type;
        else
            tp[i] = tp[i + 1];
    }

    int cnt = 0;
    for (int i = 1; i <= n; i++)
        if (tp[i] == s_type && tp[i - 1] == l_type)
            pos[cnt++] = i;

    for (int i = 0; i < cnt; i++)
        sa[sbuc[s[pos[i]]]--] = pos[i];
    induced_sort();

    int lastx = -1, namecnt = 1;
    bool flag = false;

    for (int i = 1; i <= n; i++) {
        int x = sa[i];

        if (is_lms(tp, x)) {
            if (lastx >= 0 && !equal_substr(s, x, lastx, tp))
                namecnt++;

            if (lastx >= 0 && namecnt == name[lastx])
                flag = true;

            name[x] = namecnt;
            lastx = x;
        }
    }
    name[n] = 0;

    int* t = new int[cnt];
    int p = 0;
    for (int i = 0; i <= n; i++)
        if (name[i] >= 0)
            t[p++] = name[i];

    vector<int> tsa;
    if (!flag) {
        tsa.resize(cnt);

        for (int i = 0; i < cnt; i++)
            tsa[t[i]] = i;
    }
    else
        tsa = move(sais(t, cnt, namecnt));

    lbuc[0] = sbuc[0] = 0;
    for (int i = 1; i <= m; i++) {
        lbuc[i] = buc[i - 1];
        sbuc[i] = buc[i] - 1;
    }

    sa.assign(n + 1, -1);
    for (int i = cnt - 1; ~i; i--)
        sa[sbuc[s[pos[tsa[i]]]]--] = pos[tsa[i]];
    induced_sort();

    return sa;
}

// 封装好的函数，1-based
void get_sa(char *s, int n, int *sa, int *rnk, int *height) {
```

```
    static int a[MAXN];

    a[n] = '$';
    for (int i = 1; i <= n; i++)
        a[i - 1] = s[i];

    vector<int> t = sais(a, n + 1, 256);
    copy(t.begin(), t.end(), sa);

    sa[0] = 0;
    for (int i = 1; i <= n; i++)
        rnk[++sa[i]] = i;

    for (int i = 1, k = 0; i <= n; i++) {
        if (k)
            k--;

        while (s[i + k] == s[sa[rnk[i] - 1] + k])
            k++;

        height[rnk[i]] = k; // height[i] = lcp(sa[i], sa[i - 1])
    }
}
```

5.3.3 SAMSA

```
bool vis[maxn * 2];
char s[maxn];
int n, id[maxn * 2], ch[maxn * 2][26], height[maxn], tim = 0;

void dfs(int x) {
    if (id[x]) {
        height[tim++] = val[last];
        sa[tim] = id[x];

        last = x;
    }

    for (int c = 0; c < 26; c++)
        if (ch[x][c])
            dfs(ch[x][c]);

    last = par[x];
}

int main() {
    last = ++cnt;

    scanf("%s", s + 1);
    n = strlen(s + 1);

    for (int i = n; i; i--) {
        expand(s[i] - 'a');
        id[last] = i;
    }

    vis[1] = true;
    for (int i = 1; i <= cnt; i++)
        if (id[i])
            for (int x = i, pos = n; x && !vis[x]; x = par[x]) {
                vis[x] = true;
                pos -= val[x] - val[par[x]];
                ch[par[x]][s[pos + 1] - 'a'] = x;
            }

    dfs(1);

    for (int i = 1; i <= n; i++) {
        if (i > 1)
            printf(" ");
        printf("%d", sa[i]); // 1-based
    }
    printf("\n");

    for (int i = 1; i < n; i++) {
        if (i > 1)
            printf(" ");
        printf("%d", height[i]);
    }
    printf("\n");

    return 0;
}
```

5.4 后缀平衡树

如果不需要查询排名，只需要维护前驱后继关系的题目，可以直接用二分哈希 + set 去做。

一般的题目需要查询排名，这时候就需要写替罪羊树或者 Treap 维护 tag。插入后缀时，如果首字母相同，只需比较各自删除首字母后的 tag 大小即可。

(Treap 也具有重量平衡树的性质，每次插入后影响到的子树大小期望是 $O(\log n)$ 的，所以每次做完插入操作之后直接暴力重构子树内tag就行了。)

5.5 后缀自动机

```
// 在字符集比较小的时候可以直接开go数组，否则需要用map或者哈希表替换
// 注意!!! 结点数要开成串长的两倍

// 全局变量与数组定义
int last, val[maxn], par[maxn], go[maxn][26], sam_cnt;
int c[maxn], q[maxn]; // 用来桶排序

// 在主函数开头加上这句初始化
last = sam_cnt = 1;

// 以下是按val进行桶排序的代码
for (int i = 1; i <= sam_cnt; i++)
    c[val[i] + 1]++;
for (int i = 1; i <= n; i++)
    c[i] += c[i - 1]; // 这里n是串长
for (int i = 1; i <= sam_cnt; i++)
    q[++c[val[i]]] = i;

//加入一个字符 均摊O(1)
void extend(int c) {
    int p = last, np = ++sam_cnt;
    val[np] = val[p] + 1;

    while (p && !go[p][c]) {
        go[p][c] = np;
        p = par[p];
    }

    if (!p)
        par[np] = 1;
    else {
        int q = go[p][c];

        if (val[q] == val[p] + 1)
            par[np] = q;
        else {
            int nq = ++sam_cnt;
            val[nq] = val[p] + 1;
            memcpy(go[nq], go[q], sizeof(go[q]));

```

```
            par[nq] = par[q];
            par[np] = par[q] = nq;

            while (p && go[p][c] == q){
                go[p][c] = nq;
                p = par[p];
            }
        }
    }

    last = np;
}
```

5.5.1 广义后缀自动机

下面的写法复杂度是 Σ 串长的，但是胜在简单。
如果建字典树然后 BFS 建自动机可以做到 $O(n|\Sigma|)$（n 是字典树结点数），但是写起来比较麻烦。

```
int extend(int p, int c) {
    int np = 0;

    if (!go[p][c]) {
        np = ++sam_cnt;
        val[np] = val[p] + 1;
        while (p && !go[p][c]) {
            go[p][c] = np;
            p = par[p];
        }
    }

    if (!p)
        par[np] = 1;
    else {
        int q = go[p][c];

        if (val[q] == val[p] + 1) {
            if (np)
                par[np] = q;
            else
                return q;
        }
        else {
            int nq = ++sam_cnt;
            val[nq] = val[p] + 1;
            memcpy(go[nq], go[q], sizeof(go[q]));

            par[nq] = par[q];
            par[q] = nq;
            if (np)
                par[np] = nq;

            while (p && go[p][c] == q){
                go[p][c] = nq;
                p = par[p];
            }

            if (!np)
                return nq;
        }
    }

    return np;
}
// 调用的时候直接last = 1然后一路调用last = extend(last, c) 就行了
```

5.5.2 区间本质不同子串计数（后缀自动机 + LCT + 线段树）

问题 给定一个字符串 s，多次询问 $[l,r]$ 区间的本质不同的子串个数，可能强制在线。

做法 考虑建出后缀自动机，然后枚举右端点，用线段树维护每个左端点的答案。
显然只有 right 集合在 $[l,r]$ 中的串才有可能有贡献，所以我们可以只考虑每个串最大的 right。
每次右端点 $+1$ 时找到它对应的结点 u，则 u 到根节点路径上的每个点，它的 right 集合都会被 r 更新。
对于某个特定的左端点 l，我们需要保证本质不同的子串左端点不能越过它；因此对于一个结点 p，我们知道它对应的子串长度 $(val_{par_p}, val_p]$ 之后，在 p 的 right 集合最大值减去对应长度，这样对应的 l 内全部 $+1$ 即可。这样询问时就只需要查询 r 对应的线段树中 $[l,r]$ 的区间和了。（当然旧的 right 对应的区间也要减掉）
实际上可以发现更新时都是把路径分成若干个整段更新 right 集合，因此可以用 LCT 维护这个过程。
时间复杂度 $O(n\log^2 n)$，空间 $O(n)$。当然如果强制在线的话，就把线段树改成主席树，空间复杂度就和时间复杂度同阶了。

```
int tim; // tim实际上就是当前的右端点

node *access(node *x) {
    node *y = null;

    while (x != null) {
        splay(x);

        x -> ch[1] = null;
        x -> refresh();

        if (x -> val) // val记录的是上次访问时间，也就是right集合最大值
            update(x -> val - val[x -> r] + 1, x -> val - val[par[x -> l]], -1);

        x -> val = tim;
        x -> lazy = true;

        update(x -> val - val[x -> r] + 1, x -> val - val[par[x -> l]], 1);

        x -> ch[1] = y;

        (y = x) -> refresh();

        x = x -> p;
    }

    return y;
}

// 以下是main函数中的用法
for (int i = 1; i <= n; i++) {
    tim++;
    access(null + id[i]);

    if (i >= m) // 例题询问长度是固定的，如果不固定的话就按照右端点离线即可
        ans[i - m + 1] = query(i - m + 1, i);
}
```

还有一份完整的代码，因为写起来确实细节挺多的。这份代码支持在尾部加一个字符或者询问区间有多少子串至少出现了 **两次**，并且强制在线。

```
#include <bits/stdc++.h>

using namespace std;

constexpr int maxn = 200005, maxm = maxn * 17 * 15;

int mx[maxm][2], lc[maxm], rc[maxm], seg_cnt;
```

```cpp
int root[maxn];

int s, t, d;

void modify_seg(int l, int r, int &o) {
    int u = o;
    o = ++seg_cnt;

    mx[o][0] = max(mx[u][0], t);
    mx[o][1] = max(mx[u][1], d);

    if (l == r)
        return;

    lc[o] = lc[u];
    rc[o] = rc[u];

    int mid = (l + r) / 2;
    if (s <= mid)
        modify_seg(l, mid, lc[o]);
    else
        modify_seg(mid + 1, r, rc[o]);
}

int query_seg(int l, int r, int o, int k) {
    if (s <= l && t >= r)
        return mx[o][k];

    int mid = (l + r) / 2, ans = 0;

    if (s <= mid)
        ans = max(ans, query_seg(l, mid, lc[o], k));
    if (t > mid)
        ans = max(ans, query_seg(mid + 1, r, rc[o], k));

    return ans;
}

int N;

void modify(int pos, int u, int v, int &rt) {
    s = pos;
    t = u;
    d = v;

    modify_seg(1, N, rt);
}

int query(int l, int r, int rt) {
    s = l;
    t = r;
    int ans = query_seg(1, N, rt, 0);

    s = 1;
    t = l;
    return max(ans, query_seg(1, N, rt, 1) - l);
}

struct node {
    int size, l, r, id, tim;
    node *ch[2], *p;
    bool tag;

    node() = default;

    void apply(int v) {
        tim = v;
        tag = true;
    }

    void pushdown() {
        if (tag) {
            ch[0] -> tim = ch[1] -> tim = tim;
            ch[0] -> tag = ch[1] -> tag = true;

            tag = false;
        }
    }

    void update() {
        size = ch[0] -> size + ch[1] -> size + 1;
        l = (ch[0] -> l ? ch[0] -> l : id);
        r = (ch[1] -> r ? ch[1] -> r : id);
    }
} null[maxn];

inline bool isroot(node *x) {
    return x != x -> p -> ch[0] && x != x -> p -> ch[1];
}

inline bool dir(node *x) {
    return x == x -> p -> ch[1];
}

void init(node *x, int i) {
    *x = node();
    x -> ch[0] = x -> ch[1] = x -> p = null;
    x -> size = 1;
    x -> id = x -> l = x -> r = i;
}

void rot(node *x, int d) {
    node *y = x -> ch[d ^ 1];

    y -> p = x -> p;
    if (!isroot(x))
        x -> p -> ch[dir(x)] = y;

    if ((x -> ch[d ^ 1] = y -> ch[d]) != null)
        y -> ch[d] -> p = x;
    (y -> ch[d] = x) -> p = y;

    x -> update();
    y -> update();
}

void splay(node *x) {
    x -> pushdown();

    while (!isroot(x)) {
        if (!isroot(x -> p))
            x -> p -> p -> pushdown();
        x -> p -> pushdown();
        x -> pushdown();

        if (isroot(x -> p)) {
            rot(x -> p, dir(x) ^ 1);
            break;
        }

        if (dir(x) == dir(x -> p))
            rot(x -> p -> p, dir(x -> p) ^ 1);
        else
            rot(x -> p, dir(x) ^ 1);

        rot(x -> p, dir(x) ^ 1);
    }
}

void splay(node *x, node *rt) {
    x -> pushdown();

```

```
    while (x -> p != rt) {
        if (x -> p -> p != rt)
            x -> p -> p -> pushdown();
        x -> p -> pushdown();
        x -> pushdown();

        if (x -> p -> p == rt) {
            rot(x -> p, dir(x) ^ 1);
            break;
        }

        if (dir(x) == dir(x -> p))
            rot(x -> p -> p, dir(x -> p) ^ 1);
        else
            rot(x -> p, dir(x) ^ 1);

        rot(x -> p, dir(x) ^ 1);
    }
}

int val[maxn], par[maxn], go[maxn][26], sam_cnt, sam_last;

node *access(node *x, int r) {
    root[r] = root[r - 1];

    node *y = null;

    while (x != null) {
        splay(x);

        x -> pushdown();

        x -> ch[1] = null;
        x -> update();

        if (x -> tim && val[x -> r]) { // last time visited
            int right = x -> tim, left = right - val[x -> r] + 1;
            modify(left, val[x -> r], right + 1, root[r]);
        }

        x -> apply(r);
        x -> pushdown();

        x -> ch[1] = y;
        (y = x) -> update();

        x = x -> p;
    }

    return y;
}

void new_leaf(node *x, node *par) {
    x -> p = par;
}

void new_node(node *x, node *y, node *par) {
    splay(y);

    if (isroot(y) && y -> p == par) {
        assert(y -> ch[0] == null);

        y -> ch[0] = x;
        x -> p = y;
        y -> update();
    }
    else {
        splay(par, y);

        assert(y -> ch[0] == par);
        assert(par -> ch[1] == null);
        par -> ch[1] = x;
        x -> p = par;

        par -> update();
        y -> update();
    }

    x -> tim = y -> tim;
}

void extend(int c) {
    int p = sam_last, np = ++sam_cnt;
    val[np] = val[p] + 1;

    init(null + np, np);

    while (p && !go[p][c]) {
        go[p][c] = np;
        p = par[p];
    }

    if (!p) {
        par[np] = 1;
        new_leaf(null + np, null + par[np]);
    }
    else {
        int q = go[p][c];

        if (val[q] == val[p] + 1) {
            par[np] = q;
            new_leaf(null + np, null + par[np]);
        }
        else {
            int nq = ++sam_cnt;
            val[nq] = val[p] + 1;
            memcpy(go[nq], go[q], sizeof(go[q]));

            init(null + nq, nq);

            new_node(null + nq, null + q, null + par[q]);
            new_leaf(null + np, null + nq);

            par[nq] = par[q];
            par[np] = par[q] = nq;

            while (p && go[p][c] == q) {
                go[p][c] = nq;
                p = par[p];
            }
        }
    }

    sam_last = np;
}

char str[maxn];

int main() {

    init(null, 0);

    sam_last = sam_cnt = 1;
    init(null + 1, 1);

    int n, m;
    scanf("%s%d", str + 1, &m);
    n = strlen(str + 1);
    N = n + m;
```

```cpp

    for (int i = 1; i <= n; i++) {
        extend(str[i] - 'a');
        access(null + sam_last, i);
    }

    int tmp = 0;

    while (m--) {
        int op;
        scanf("%d", &op);

        if (op == 1) {
            scanf(" %c", &str[++n]);

            str[n] = (str[n] - 'a' + tmp) % 26 + 'a';

            extend(str[n] - 'a');
            access(null + sam_last, n);
        }
        else {
            int l, r;
            scanf("%d%d", &l, &r);

            l = (l - 1 + tmp) % n + 1;
            r = (r - 1 + tmp) % n + 1;

            printf("%d\n", tmp = query(l, r, root[r]));
        }
    }

    return 0;
}
```

5.6 回文树

```cpp
// 定理：一个字符串本质不同的回文子串个数是O(n) 的
// 注意回文树只需要开一倍结点，另外结点编号也是一个可用的bfs序

// 全局数组定义
int val[maxn], par[maxn], go[maxn][26], last, cnt;
char s[maxn];

// 重要！在主函数最前面一定要加上以下初始化
par[0] = cnt = 1;
val[1] = -1;
// 这个初始化和广义回文树不一样，写普通题可以用，广义回文树就不要乱搞了

// extend函数 均摊O(1)
// 向后扩展一个字符
// 传入对应下标
void extend(int n) {
    int p = last, c = s[n] - 'a';
    while (s[n - val[p] - 1] != s[n])
        p = par[p];

    if (!go[p][c]) {
        int q = ++cnt, now = p;
        val[q] = val[p] + 2;

        do
            p = par[p];
        while (s[n - val[p] - 1] != s[n]);

        par[q] = go[p][c];
        last = go[now][c] = q;
    }
    else
        last = go[p][c];

    // a[last]++;
}
```

5.6.1 广义回文树

代码是梯子剖分的版本，压力不大的题目换成直接倍增就好了，常数只差不到一倍。

```cpp
#include <bits/stdc++.h>

using namespace std;

constexpr int maxn = 1000005, mod = 1000000007;

int val[maxn], par[maxn], go[maxn][26], fail[maxn][26], pam_last[maxn], pam_cnt;
int weight[maxn], pow_26[maxn];

int trie[maxn][26], trie_cnt, d[maxn], mxd[maxn], son[maxn], top[maxn], len[maxn], sum[maxn];
char chr[maxn];
int f[25][maxn], log_tbl[maxn];
vector<int> v[maxn];

vector<int> queries[maxn];

char str[maxn];
int n, m, ans[maxn];

int add(int x, int c) {
    if (!trie[x][c]) {
        trie[x][c] = ++trie_cnt;
        f[0][trie[x][c]] = x;
        chr[trie[x][c]] = c + 'a';
    }

    return trie[x][c];
}

int del(int x) {
    return f[0][x];
}

void dfs1(int x) {
    mxd[x] = d[x] = d[f[0][x]] + 1;

    for (int i = 0; i < 26; i++)
        if (trie[x][i]) {
            int y = trie[x][i];

            dfs1(y);

            mxd[x] = max(mxd[x], mxd[y]);
            if (mxd[y] > mxd[son[x]])
                son[x] = y;
        }
}

void dfs2(int x) {
    if (x == son[f[0][x]])
        top[x] = top[f[0][x]];
    else
        top[x] = x;

    for (int i = 0; i < 26; i++)
        if (trie[x][i]) {
            int y = trie[x][i];
            dfs2(y);
        }

    if (top[x] == x) {
```

```
        int u = x;
        while (top[son[u]] == x)
            u = son[u];

        len[x] = d[u] - d[x];

        for (int i = 0; i < len[x]; i++) {
            v[x].push_back(u);
            u = f[0][u];
        }

        u = x;
        for (int i = 0; i < len[x]; i++) { // 梯子剖分,要延长一倍
            v[x].push_back(u);
            u = f[0][u];
        }
    }
}

int get_anc(int x, int k) {
    if (!k)
        return x;
    if (k > d[x])
        return 0;

    x = f[log_tbl[k]][x];
    k ^= 1 << log_tbl[k];

    return v[top[x]][d[top[x]] + len[top[x]] - d[x] + k];
}

char get_char(int x, int k) { // 查询x前面k个的字符是哪个
    return chr[get_anc(x, k)];
}

int getfail(int x, int p) {
    if (get_char(x, val[p] + 1) == chr[x])
        return p;
    return fail[p][chr[x] - 'a'];
}

int extend(int x) {

    int p = pam_last[f[0][x]], c = chr[x] - 'a';

    p = getfail(x, p);

    int new_last;

    if (!go[p][c]) {
        int q = ++pam_cnt, now = p;
        val[q] = val[p] + 2;

        p = getfail(x, par[p]);

        par[q] = go[p][c];
        new_last = go[now][c] = q;

        for (int i = 0; i < 26; i++)
            fail[q][i] = fail[par[q]][i];

        if (get_char(x, val[par[q]]) >= 'a')
            fail[q][get_char(x, val[par[q]]) - 'a'] = par[q];

        if (val[q] <= n)
            weight[q] = (weight[par[q]] + (long long)(n - val[q] + 1) * pow_26[n - val[q]]) % mod;
        else
            weight[q] = weight[par[q]];
    }
    else
        new_last = go[p][c];

    pam_last[x] = new_last;

    return weight[pam_last[x]];
}

void bfs() {

    queue<int> q;

    q.push(1);

    while (!q.empty()) {
        int x = q.front();
        q.pop();

        sum[x] = sum[f[0][x]];
        if (x > 1)
            sum[x] = (sum[x] + extend(x)) % mod;

        for (int i : queries[x])
            ans[i] = sum[x];

        for (int i = 0; i < 26; i++)
            if (trie[x][i])
                q.push(trie[x][i]);
    }

}

int main() {

    pow_26[0] = 1;
    log_tbl[0] = -1;

    for (int i = 1; i <= 1000000; i++) {
        pow_26[i] = 26ll * pow_26[i - 1] % mod;
        log_tbl[i] = log_tbl[i / 2] + 1;
    }

    int T;
    scanf("%d", &T);

    while (T--) {
        scanf("%d%d%s", &n, &m, str);

        trie_cnt = 1;
        chr[1] = '#';

        int last = 1;
        for (char *c = str; *c; c++)
            last = add(last, *c - 'a');

        queries[last].push_back(0);

        for (int i = 1; i <= m; i++) {
            int op;
            scanf("%d", &op);

            if (op == 1) {
                char c;
                scanf(" %c", &c);

                last = add(last, c - 'a');
            }
            else
                last = del(last);
```

```
            queries[last].push_back(i);
        }

        dfs1(1);
        dfs2(1);

        for (int j = 1; j <= log_tbl[trie_cnt]; j++)
            for (int i = 1; i <= trie_cnt; i++)
                f[j][i] = f[j - 1][f[j - 1][i]];

        par[0] = pam_cnt = 1;


        for (int i = 0; i < 26; i++)
            fail[0][i] = fail[1][i] = 1;

        val[1] = -1;
        pam_last[1] = 1;

        bfs();

        for (int i = 0; i <= m; i++)
            printf("%d\n", ans[i]);

        for (int j = 0; j <= log_tbl[trie_cnt]; j++)
            memset(f[j], 0, sizeof(f[j]));

        for (int i = 1; i <= trie_cnt; i++) {
            chr[i] = 0;
            d[i] = mxd[i] = son[i] = top[i] = len[i] = pam_last[i] = sum[i] = 0;
            v[i].clear();
            queries[i].clear();

            memset(trie[i], 0, sizeof(trie[i]));
        }
        trie_cnt = 0;

        for (int i = 0; i <= pam_cnt; i++) {
            val[i] = par[i] = weight[i];

            memset(go[i], 0, sizeof(go[i]));
            memset(fail[i], 0, sizeof(fail[i]));
        }
        pam_cnt = 0;

    }

    return 0;
}
```

5.7 Manacher

```
// n 为串长，回文半径输出到 p 数组中
// 数组要开串长的两倍
void manacher(const char* t, int n) {
    static char s[maxn * 2];

    for (int i = n; i; i--)
        s[i * 2] = t[i];
    for (int i = 0; i <= n; i++)
        s[i * 2 + 1] = '#';

    s[0] = '$';
    s[(n + 1) * 2] = '\0';
    n = n * 2 + 1;

    int mx = 0, j = 0;

    for (int i = 1; i <= n; i++) {
        p[i] = (mx > i ? min(p[j * 2 - i], mx - i) : 1);
        while (s[i - p[i]] == s[i + p[i]])
            p[i]++;

        if (i + p[i] > mx) {
            mx = i + p[i];
            j = i;
        }
    }
}
```

5.8 字符串原理

KMP 和 AC 自动机的 `fail` 指针存储的都是它在串或者字典树上的最长后缀，因此要判断两个前缀是否互为后缀时可以直接用 `fail` 指针判断。当然它不能做最长公共后缀，不过可以用一个树链的并来做子串问题。

后缀数组利用的主要是 LCP 长度可以按照字典序做 RMQ 的性质，与某个串的 LCP 长度 $\geq$ 某个值的后缀形成一个区间。另外一个比较好用的性质是本质不同的子串个数 = 所有子串数 - 字典序相邻的串的 `height`。

后缀自动机实际上可以接受的是所有后缀，如果把中间状态也算上的话就是所有子串. 它的 fail 指针代表的也是当前串的后缀，不过注意每个状态可以代表很多状态，只要右端点在 `right` 集合中且长度处在 $(val_{par_p}, val_p]$ 中的串都被它代表。

后缀自动机的 `fail` 树也就是 **反串**的后缀树。每个结点代表的串和后缀自动机同理，两个串的 LCP 也就是他们在后缀树上的 LCA。

6 动态规划

6.1 决策单调性 $O(n \log n)$

```
int a[MAXN], q[MAXN], p[MAXN], g[MAXN]; // 存左端点，右端点就是下一个左端点 - 1

long long f[MAXN], s[MAXN];

int n, m;

long long calc(int l, int r) {
    if (r < l)
        return 0;

    int mid = (l + r) / 2;
    if ((r - l + 1) % 2 == 0)
        return (s[r] - s[mid]) - (s[mid] - s[l - 1]);
    else
        return (s[r] - s[mid]) - (s[mid - 1] - s[l - 1]);
}

int solve(long long tmp) {
    memset(f, 63, sizeof(f));
    f[0] = 0;

    int head = 1, tail = 0;

    for (int i = 1; i <= n; i++) {
        f[i] = calc(1, i);
        g[i] = 1;

        while (head < tail && p[head + 1] <= i)
            head++;
        if (head <= tail) {
            if (f[q[head]] + calc(q[head] + 1, i) < f[i]) {
                f[i] = f[q[head]] + calc(q[head] + 1, i);
                g[i] = g[q[head]] + 1;
            }
            while (head < tail && p[head + 1] <= i + 1)
                head++;
            if (head <= tail)
                p[head] = i + 1;
        }
        f[i] += tmp;

        int r = n;

        while(head <= tail) {
            if (f[q[tail]] + calc(q[tail] + 1, p[tail]) > f[i] + calc(i + 1, p[tail])) {
                r = p[tail] - 1;
                tail--;
            }
            else if (f[q[tail]] + calc(q[tail] + 1, r) <= f[i] + calc(i + 1, r)) {
                if (r < n) {
                    q[++tail] = i;
                    p[tail] = r + 1;
                }
                break;
            }
            else {
                int L = p[tail], R = r;
                while (L < R) {
                    int M = (L + R) / 2;

                    if (f[q[tail]] + calc(q[tail] + 1, M) <= f[i] + calc(i + 1, M))
                        L = M + 1;
                    else
                        R = M;
                }

                q[++tail] = i;
                p[tail] = L;

                break;
            }
        }
        if (head > tail) {
            q[++tail] = i;
            p[tail] = i + 1;
        }
    }

    return g[n];
}
```

6.2 例题

6.2.1 103388A Assigning Prizes 容斥

题意 给定一个长为 n 的序列 a_i，要求构造非严格递减序列 b_i，满足 $a_i \le b_i \le R$，求方案数。$n \le 5 \times 10^3, R, a_i \le 10^9$。

做法 a_i 的范围太大了，不能简单地记录上一位的值。

考虑使用容斥。方便起见把 a_i 直接变成 $R - a_i + 1$，条件就变成了 $b_i \le a_i$ 且 $b_i \ge b_{i-1}$。

这里有两个限制条件，可以固定 $b_i \le a_i$ 是必须满足的条件，只对 $b_i \ge b_{i-1}$ 使用容斥，枚举哪些位置是比上一位小的（违反限制），其他位置随意。

枚举后的形态一定是有若干个区间是严格递减的，其他位置随意。考虑如果一个区间 $[l, r]$ 是严格递减的，显然所有的数都 $< a_l$，所以这段区间的方案数就是 $\binom{a_l}{r-l+1}$。另外实际上 b_l 是没有违反限制的，所以这里对系数的贡献是 $(-1)^{r-l}$。

考虑令 dp_i 表示只考虑前 i 个位置的答案，转移时自然就是枚举一个 j，然后计算 dp_{j-1} 乘上区间 $[j, i]$ 严格递减的方案数。另外还有一种情况是 b_i 没有违反限制，这时显然直接在 dp_{i-1} 的基础上乘上一个 a_i 就好了。(转移时还要注意，由于枚举的是严格递减区间，自然就不能枚举只有一个数的区间。

```
constexpr int maxn = 5005, p = (int)1e9 + 7;

int inv[maxn];
int a[maxn], f[maxn][maxn], dp[maxn];

int main() {

    int n, m;
    scanf("%d%d", &n, &m);

    inv[1] = 1;
    for (int i = 2; i <= n; i++)
        inv[i] = (long long)(p - p / i) * inv[p % i] % p;

    for (int i = 1; i <= n; i++) {
        scanf("%d", &a[i]);
        a[i] = m - a[i] + 1;
    }

    if (any_of(a + 1, a + n + 1, [] (int x) {return x <= 0;})) {
        printf("0\n");
        return 0;
    }

```

```
    for (int i = n - 1; i; i--)
        a[i] = min(a[i], a[i + 1]);

    // b_i >= b_{i - 1} && b_i <= a_i
    // 我们可以假设 b_i <= a_i 是必定被满足的，然后对 bi 非严格递增的条件进行容斥，枚举某一段是严格递减的
    // 如果 [j, i] 严格递减，显然它们都 <= a_j，所以这个区间的方案数是 {a_j \choose i - j + 1}
    // 如果 i 是合法的，直接一个个转移即可，因为这一部分的转移和区间长度没有关系

    for (int i = 1; i <= n; i++) {
        f[i][0] = 1;

        for (int j = 1; j <= n - i + 1 && j <= a[i]; j++)
            f[i][j] = (long long)f[i][j - 1] * (a[i] - j + 1) % p * inv[j] % p;
    }

    dp[0] = 1;

    for (int i = 1; i <= n; i++) {
        dp[i] = (long long)dp[i - 1] * a[i] % p;

        for (int j = 1; j < i; j++) {
            int tmp = (long long)dp[j - 1] * f[j][i - j + 1] % p;

            if ((i - j) % 2)
                tmp = p - tmp;

            dp[i] = (dp[i] + tmp) % p;
        }
    }

    printf("%d\n", dp[n]);

    return 0;
}
```

7 计算几何

7.1 Delaunay 三角剖分

只要两个点同在某个三角形上，它们就互为一对最近点。注意返回的三角形似乎不保证顺序，所以要加边的话还是要加双向边。

如果要建 V 图的话，求出每个三角形的外心就行了，每个点控制的区域就是所在三角形的外心连起来。

```cpp
#include <bits/stdc++.h>

using namespace std;

constexpr int maxn = 500005;

using ll = long long;

constexpr int INF = 0x3f3f3f3f;
constexpr ll LINF = 0x3f3f3f3f3f3f3f3fll;
constexpr double eps = 1e-8;

template <class T>
int sgn(T x) {
    return x > 0 ? 1 : x < 0 ? -1 : 0;
}

struct point {
    ll x, y;

    point() = default;

    point(ll x, ll y) : x(x), y(y) {}

    point operator - (const point &p) const {
        return point(x - p.x, y - p.y);
    }

    ll cross(const point &p) const {
        return x * p.y - y * p.x;
    }

    ll cross(const point &a, const point &b) const {
        return (a - *this).cross(b - *this);
    }

    ll dot(const point &p) const {
        return x * p.x + y * p.y;
    }

    ll dot(const point &a, const point &b) const {
        return (a - *this).dot(b - *this);
    }

    ll abs2() const {
        return this -> dot(*this);
    }

    bool operator == (const point &p) const {
        return x == p.x && y == p.y;
    }

    bool operator < (const point &p) const {
        if (x != p.x) return x < p.x;
        return y < p.y;
    }
};



const point inf_point = point(1e18, 1e18);

struct quad_edge {
    point origin;
    quad_edge *rot = nullptr;
    quad_edge *onext = nullptr;
    bool used = false;

    quad_edge *rev() const {
        return rot -> rot;
    }
    quad_edge *lnext() const {
        return rot -> rev() -> onext -> rot;
    }
    quad_edge *oprev() const {
        return rot -> onext -> rot;
    }
    point dest() const {
        return rev() -> origin;
    }
};

quad_edge *make_edge(point from, point to) {
    quad_edge *e1 = new quad_edge;
    quad_edge *e2 = new quad_edge;
    quad_edge *e3 = new quad_edge;
    quad_edge *e4 = new quad_edge;

    e1 -> origin = from;
    e2 -> origin = to;
    e3 -> origin = e4 -> origin = inf_point;

    e1 -> rot = e3;
    e2 -> rot = e4;
    e3 -> rot = e2;
    e4 -> rot = e1;

    e1 -> onext = e1;
    e2 -> onext = e2;
    e3 -> onext = e4;
    e4 -> onext = e3;

    return e1;
}

void splice(quad_edge *a, quad_edge *b) { // 拼接
    swap(a -> onext -> rot -> onext, b -> onext -> rot -> onext);
    swap(a -> onext, b -> onext);
}

void delete_edge(quad_edge *e) {
    splice(e, e -> oprev());
    splice(e -> rev(), e -> rev() -> oprev());

    delete e -> rev() -> rot;
    delete e -> rev();
    delete e -> rot;
    delete e;
}

quad_edge *connect(quad_edge *a, quad_edge *b) {
    quad_edge *e = make_edge(a -> dest(), b -> origin);

    splice(e, a -> lnext());
    splice(e -> rev(), b);

    return e;
}

bool left_of(point p, quad_edge *e) {
    return p.cross(e -> origin, e -> dest()) > 0;
}

```

```cpp
bool right_of(point p, quad_edge *e) {
    return p.cross(e -> origin, e -> dest()) < 0;
}

template <class T>
T det3(T a1, T a2, T a3, T b1, T b2, T b3, T c1, T c2, T c3) {
    return a1 * (b2 * c3 - c2 * b3) - a2 * (b1 * c3 - c1 * b3) +
           a3 * (b1 * c2 - c1 * b2);
}

bool in_circle(point a, point b, point c, point d) { // 如果有__int128就直接计算行列式，否则算角度
#if defined(__LP64__) || defined(_WIN64)
    __int128 det = -det3<__int128>(b.x, b.y, b.abs2(), c.x, c.y, c.abs2(), d.x, d.y, d.abs2());
    det += det3<__int128>(a.x, a.y, a.abs2(), c.x, c.y, c.abs2(), d.x, d.y, d.abs2());
    det -= det3<__int128>(a.x, a.y, a.abs2(), b.x, b.y, b.abs2(), d.x, d.y, d.abs2());
    det += det3<__int128>(a.x, a.y, a.abs2(), b.x, b.y, b.abs2(), c.x, c.y, c.abs2());

    return det > 0;
#else
    auto ang = [] (point l, point mid, point r) {
        ll x = mid.dot(l, r);
        ll y = mid.cross(l, r);
        long double res = atan2((long double)x, (long double)y);
        return res;
    };

    long double kek = ang(a, b, c) + ang(c, d, a) - ang(b, c, d) - ang(d, a, b);

    return kek > 1e-10;
#endif
}

pair<quad_edge*, quad_edge*> divide_and_conquer(int l, int r, vector<point> &p) {
    if (r - l + 1 == 2) {
        quad_edge *res = make_edge(p[l], p[r]);
        return make_pair(res, res -> rev());
    }

    if (r - l + 1 == 3) {
        quad_edge *a = make_edge(p[l], p[l + 1]), *b = make_edge(p[l + 1], p[r]);
        splice(a -> rev(), b);

        int sg = sgn(p[l].cross(p[l + 1], p[r]));

        if (sg == 0)
            return make_pair(a, b -> rev());

        quad_edge *c = connect(b, a);

        if (sg == 1)
            return make_pair(a, b -> rev());
        else
            return make_pair(c -> rev(), c);
    }

    int mid = (l + r) / 2;

    quad_edge *ldo, *ldi, *rdo, *rdi;
    tie(ldo, ldi) = divide_and_conquer(l, mid, p);
    tie(rdi, rdo) = divide_and_conquer(mid + 1, r, p);

    while (true) {
        if (left_of(rdi -> origin, ldi))
            ldi = ldi -> lnext();

        else if (right_of(ldi -> origin, rdi))
            rdi = rdi -> rev() -> onext;

        else
            break;
    }

    quad_edge *basel = connect(rdi -> rev(), ldi);
    auto is_valid = [&basel] (quad_edge *e) {
        return right_of(e -> dest(), basel);
    };

    if (ldi -> origin == ldo -> origin)
        ldo = basel -> rev();
    if (rdi -> origin == rdo -> origin)
        rdo = basel;

    while (true) {
        quad_edge *lcand = basel -> rev() -> onext;
        if (is_valid(lcand)) {
            while (in_circle(basel -> dest(), basel -> origin, lcand -> dest(), lcand -> onext -> dest())) {
                quad_edge *t = lcand -> onext;
                delete_edge(lcand);
                lcand = t;
            }
        }

        quad_edge *rcand = basel -> oprev();
        if (is_valid(rcand)) {
            while (in_circle(basel -> dest(), basel -> origin, rcand -> dest(), rcand -> oprev() -> dest())) {
                quad_edge *t = rcand -> oprev();
                delete_edge(rcand);
                rcand = t;
            }
        }

        if (!is_valid(lcand) && !is_valid(rcand))
            break;

        if (!is_valid(lcand) || (is_valid(rcand) && in_circle(lcand -> dest(), lcand -> origin, rcand -> origin, rcand -> dest())))
            basel = connect(rcand, basel -> rev());
        else
            basel = connect(basel -> rev(), lcand -> rev());
    }

    return make_pair(ldo, rdo);
}

vector<tuple<point, point, point> > delaunay(vector<point> p) { // Delaunay 三角剖分
    sort(p.begin(), p.end(), [] (const point &a, const point &b) {
        return a.x < b.x || (a.x == b.x && a.y < b.y); // 实际上已经重载小于了，只是为了清晰
    });

    auto res = divide_and_conquer(0, (int)p.size() - 1, p);

    quad_edge *e = res.first;
    vector<quad_edge*> edges = {e};
```

```cpp

    while (e -> onext -> dest().cross(e -> dest(), e -> origin) < 0)
        e = e -> onext;

    auto add = [&p, &e, &edges] () { // 修改 p, e, edges
        quad_edge *cur = e;
        do {
            cur -> used = true;
            p.push_back(cur -> origin);
            edges.push_back(cur -> rev());

            cur = cur -> lnext();
        } while (cur != e);
    };

    add();
    p.clear();

    int kek = 0;
    while (kek < (int)edges.size())
        if (!(e = edges[kek++]) -> used)
            add();

    vector<tuple<point, point, point> > ans;
    for (int i = 0; i < (int)p.size(); i += 3)
        ans.push_back(make_tuple(p[i], p[i + 1], p[i + 2]));

    return ans; // 返回每个三角形
}

#define sq(x) ((x) * (ll)(x)) // 平方

ll dist(point p, point q) { // 两点间距离的平方
    return (p - q).abs2();
}

ll sarea2(point p, point q, point r) { // 三角形面积的两倍（叉积）
    return (q - p).cross(r - q);
}

point v[maxn];

int main() {
    int n;
    cin >> n;

    // read the points, v[1 ~ n]

    bool col_linear = true; // 如果给出的所有点都共线则需要特判
    for (int i = 3; i <= n; i++)
        if (sarea2(v[1], v[2], v[i]))
            col_linear = false;

    if (col_linear) {
        // do something

        return 0;
    }

    auto triangles = delaunay(vector<point>(v + 1, v + n + 1));

    // do something

    return 0;
}
```

7.2 最近点对

首先分治的做法是众所周知的。
有期望 $O(n)$ 的随机增量法：首先将所有点随机打乱，然后每次增加一个点，更新答案。
假设当前最近点对距离为 s，则把平面划分成 $s \times s$ 的方格，用哈希表存储每个方格有哪些点。
加入一个新点时，只需要枚举自身和周围共计 9 个方格中的点，显然枚举到的点最多 16 个。如果加入之后答案变小了，就 $O(n)$ 暴力重构。
前 i 个点中 i 是最近点对中的点的概率至多为 $\frac{2}{i}$，所以每个点的期望贡献都是 $O(1)$，总的复杂度就是期望 $O(n)$。
如果对每个点都要求出距离最近的点的话，也有随机化的 $O(n)$ 做法：

一个真的随机算法：

A simple randomized sieve algorithm for the closest-pair problem (https://www.cs.umd.edu/~samir/grant/cp.pdf)

1. 循环直到删完所有点：
   - 随机选一个点，计算它到所有点的最短距离 d。
   - 将所有点划分到 $l = d/3$ 的网格里，比如 $\left(\lfloor \frac{x}{l} \rfloor, \lfloor \frac{y}{l} \rfloor\right)$。
   - 将九宫格内孤立的点删除，这意味着这些点的最近点对距离不小于 $\frac{2\sqrt{2}}{3}d$，其中 $\frac{2\sqrt{2}}{3} < 1$。
2. 取最后一个 d，将所有点划分到 $\left(\lfloor \frac{x}{d} \rfloor, \lfloor \frac{y}{d} \rfloor\right)$ 的网格里，暴力计算九宫格内的答案。

第一部分每次期望会删掉至少一半的点，因为有 $\geq 1/2$ 概率随到一个最近点距离在中位数以下的点，因此第一部分的复杂度是 $O(n)$ 的。

第二部分分析类似分治做法，周围只有常数个点。

所以总复杂度是 $O(n)$ 的。

42 6 条评论 收起

8 杂项

8.1 $O(1)$ 快速乘

```cpp
// long double 快速乘
// 在两数直接相乘会爆long long时才有必要使用
// 常数比直接long long乘法 + 取模大很多，非必要时不建议使用
long long mul(long long a, long long b, long long p) {
    a %= p;
    b %= p;
    return ((a * b - p * (long long)((long double)a / p * b + 0.5)) % p + p) % p;
}

// 指令集快速乘
// 试机记得测试能不能过编译
inline long long mul(const long long a, const long long b, const long long p) {
    long long ans;
    __asm__ __volatile__ ("\tmulq %%rbx\n\tdivq %%rcx\n" : "=d"(ans) : "a"(a), "b"(b), "c"(p));
    return ans;
}

// int乘法取模，大概比直接做快一倍
inline int mul_mod(int a, int b, int p) {
    int ans;
    __asm__ __volatile__ ("\tmull %%ebx\n\tdivl %%ecx\n" : "=d"(ans) : "a"(a), "b"(b), "c"(p));
    return ans;
}
```

8.2 Kahan 求和算法

当然一般来说是用不到的，累加被卡精度了才有必要考虑。

```cpp
double kahanSum(vector<double> vec) {
    double sum = 0, c = 0;
    for (auto x : vec) {
        double y = x - c;
        double t = sum + y;
        c = (t - sum) - y;
        sum = t;
    }
    return sum;
}
```

8.3 Python Decimal

```python
import decimal

decimal.getcontext().prec = 1234 # 有效数字位数

x = decimal.Decimal(2)
x = decimal.Decimal('50.5679') # 不要用float，因为float本身就不准确

x = decimal.Decimal('50.5679'). \
    quantize(decimal.Decimal('0.00')) # 保留两位小数，50.57
x = decimal.Decimal('50.5679'). \
    quantize(decimal.Decimal('0.00'), decimal.ROUND_HALF_UP) # 四舍五入
# 第二个参数可选如下:
# ROUND_HALF_UP 四舍五入
# ROUND_HALF_DOWN 五舍六入
# ROUND_HALF_EVEN 银行家舍入法，舍入到最近的偶数
# ROUND_UP 向绝对值大的取整
# ROUND_DOWN 向绝对值小的取整
# ROUND_CEILING 向正无穷取整
# ROUND_FLOOR 向负无穷取整
# ROUND_05UP (away from zero if last digit after rounding towards zero would have been 0 or 5; otherwise towards zero)

print('%f' % x) # 这样做只有float的精度
s = str(x)

decimal.is_finate(x) # x是否有穷 (NaN也算)
decimal.is_infinate(x)
decimal.is_nan(x)
decimal.is_normal(x) # x是否正常
decimal.is_signed(x) # 是否为负数

decimal.fma(a, b, c) # a * b + c，精度更高

x.exp(), x.ln(), x.sqrt(), x.log10()

# 可以转复数，前提是要import complex
```

8.4 $O(n^2)$ 高精度

```cpp
// 注意如果只需要正数运算的话
// 可以只抄英文名的运算函数
// 按需自取
// 乘法O(n ^ 2)，除法O(10 * n ^ 2)

constexpr int maxn = 1005;

struct big_decimal {
    int a[maxn];
    bool negative;

    big_decimal() {
        memset(a, 0, sizeof(a));
        negative = false;
    }

    big_decimal(long long x) {
        memset(a, 0, sizeof(a));
        negative = false;

        if (x < 0) {
            negative = true;
            x = -x;
        }

        while (x) {
            a[++a[0]] = x % 10;
            x /= 10;
        }
    }

    big_decimal(string s) {
        memset(a, 0, sizeof(a));
        negative = false;

        if (s == "")
            return;

        if (s[0] == '-') {
            negative = true;
            s = s.substr(1);
        }
        a[0] = s.size();
        for (int i = 1; i <= a[0]; i++)
            a[i] = s[a[0] - i] - '0';

        while (a[0] && !a[a[0]])
```

```
        a[0]--;
    }

    void input() {
        string s;
        cin >> s;
        *this = s;
    }

    string str() const {
        if (!a[0])
            return "0";

        string s;
        if (negative)
            s = "-";

        for (int i = a[0]; i; i--)
            s.push_back('0' + a[i]);

        return s;
    }

    operator string () const {
        return str();
    }

    big_decimal operator - () const {
        big_decimal o = *this;
        if (a[0])
            o.negative ^= true;

        return o;
    }

    friend big_decimal abs(const big_decimal &u) {
        big_decimal o = u;
        o.negative = false;
        return o;
    }

    big_decimal &operator <<= (int k) {
        a[0] += k;

        for (int i = a[0]; i > k; i--)
            a[i] = a[i - k];

        for(int i = k; i; i--)
            a[i] = 0;

        return *this;
    }

    friend big_decimal operator << (const big_decimal &u, int k) {
        big_decimal o = u;
        return o <<= k;
    }

    big_decimal &operator >>= (int k) {
        if (a[0] < k)
            return *this = big_decimal(0);

        a[0] -= k;
        for (int i = 1; i <= a[0]; i++)
            a[i] = a[i + k];

        for (int i = a[0] + 1; i <= a[0] + k; i++)
            a[i] = 0;

        return *this;
    }

    friend big_decimal operator >> (const big_decimal &u, int k) {
        big_decimal o = u;
        return o >>= k;
    }

    friend int cmp(const big_decimal &u, const big_decimal &v) {
        if (u.negative || v.negative) {
            if (u.negative && v.negative)
                return -cmp(-u, -v);

            if (u.negative)
                return -1;

            if (v.negative)
                return 1;
        }

        if (u.a[0] != v.a[0])
            return u.a[0] < v.a[0] ? -1 : 1;

        for (int i = u.a[0]; i; i--)
            if (u.a[i] != v.a[i])
                return u.a[i] < v.a[i] ? -1 : 1;

        return 0;
    }

    friend bool operator < (const big_decimal &u, const big_decimal &v) {
        return cmp(u, v) == -1;
    }

    friend bool operator > (const big_decimal &u, const big_decimal &v) {
        return cmp(u, v) == 1;
    }

    friend bool operator == (const big_decimal &u, const big_decimal &v) {
        return cmp(u, v) == 0;
    }

    friend bool operator <= (const big_decimal &u, const big_decimal &v) {
        return cmp(u, v) <= 0;
    }

    friend bool operator >= (const big_decimal &u, const big_decimal &v) {
        return cmp(u, v) >= 0;
    }

    friend big_decimal decimal_plus(const big_decimal &u, const big_decimal &v) { // 保证u, v均为正数的话可以直接调用
        big_decimal o;

        o.a[0] = max(u.a[0], v.a[0]);

        for (int i = 1; i <= u.a[0] || i <= v.a[0]; i++) {
            o.a[i] += u.a[i] + v.a[i];

            if (o.a[i] >= 10) {
                o.a[i + 1]++;
                o.a[i] -= 10;
            }
        }

```

```
        if (o.a[o.a[0] + 1])
            o.a[0]++;

        return o;
    }

    friend big_decimal decimal_minus(const big_decimal &u, const big_decimal &v) { // 保证u, v均为正数的话可以直接调用
        int k = cmp(u, v);

        if (k == -1)
            return -decimal_minus(v, u);
        else if (k == 0)
            return big_decimal(0);

        big_decimal o;

        o.a[0] = u.a[0];

        for (int i = 1; i <= u.a[0]; i++) {
            o.a[i] += u.a[i] - v.a[i];

            if (o.a[i] < 0) {
                o.a[i] += 10;
                o.a[i + 1]--;
            }
        }

        while (o.a[0] && !o.a[o.a[0]])
            o.a[0]--;

        return o;
    }

    friend big_decimal decimal_multi(const big_decimal &u, const big_decimal &v) {
        big_decimal o;

        o.a[0] = u.a[0] + v.a[0] - 1;

        for (int i = 1; i <= u.a[0]; i++)
            for (int j = 1; j <= v.a[0]; j++)
                o.a[i + j - 1] += u.a[i] * v.a[j];

        for (int i = 1; i <= o.a[0]; i++)
            if (o.a[i] >= 10) {
                o.a[i + 1] += o.a[i] / 10;
                o.a[i] %= 10;
            }

        if (o.a[o.a[0] + 1])
            o.a[0]++;

        return o;
    }

    friend pair<big_decimal, big_decimal> decimal_divide(big_decimal u, big_decimal v) { // 整除
        if (v > u)
            return make_pair(big_decimal(0), u);

        big_decimal o;
        o.a[0] = u.a[0] - v.a[0] + 1;

        int m = v.a[0];
        v <<= u.a[0] - m;

        for (int i = u.a[0]; i >= m; i--) {
            while (u >= v) {
                u = u - v;
                o.a[i - m + 1]++;
            }

            v >>= 1;
        }

        while (o.a[0] && !o.a[o.a[0]])
            o.a[0]--;

        return make_pair(o, u);
    }

    friend big_decimal operator + (const big_decimal &u, const big_decimal &v) {
        if (u.negative || v.negative) {
            if (u.negative && v.negative)
                return -decimal_plus(-u, -v);

            if (u.negative)
                return v - (-u);

            if (v.negative)
                return u - (-v);
        }

        return decimal_plus(u, v);
    }

    friend big_decimal operator - (const big_decimal &u, const big_decimal &v) {
        if (u.negative || v.negative) {
            if (u.negative && v.negative)
                return -decimal_minus(-u, -v);

            if (u.negative)
                return -decimal_plus(-u, v);

            if (v.negative)
                return decimal_plus(u, -v);
        }

        return decimal_minus(u, v);
    }

    friend big_decimal operator * (const big_decimal &u, const big_decimal &v) {
        if (u.negative || v.negative) {
            big_decimal o = decimal_multi(abs(u), abs(v));

            if (u.negative ^ v.negative)
                return -o;
            return o;
        }

        return decimal_multi(u, v);
    }

    big_decimal operator * (long long x) const {
        if (x >= 10)
            return *this * big_decimal(x);

        if (negative)
            return -(*this * x);

        big_decimal o;

        o.a[0] = a[0];

        for (int i = 1; i <= a[0]; i++) {
            o.a[i] += a[i] * x;

```

```
        if (o.a[i] >= 10) {
            o.a[i + 1] += o.a[i] / 10;
            o.a[i] %= 10;
        }
    }

    if (o.a[a[0] + 1])
        o.a[0]++;

    return o;
}

friend pair<big_decimal, big_decimal> decimal_div(const big_decimal &u, const big_decimal &v) {
    if (u.negative || v.negative) {
        pair<big_decimal, big_decimal> o = decimal_div(abs(u), abs(v));

        if (u.negative ^ v.negative)
            return make_pair(-o.first, -o.second);
        return o;
    }

    return decimal_divide(u, v);
}

friend big_decimal operator / (const big_decimal &u, const big_decimal &v) { // v不能是0
    if (u.negative || v.negative) {
        big_decimal o = abs(u) / abs(v);

        if (u.negative ^ v.negative)
            return -o;
        return o;
    }

    return decimal_divide(u, v).first;
}

friend big_decimal operator % (const big_decimal &u, const big_decimal &v) {
    if (u.negative || v.negative) {
        big_decimal o = abs(u) % abs(v);

        if (u.negative ^ v.negative)
            return -o;
        return o;
    }

    return decimal_divide(u, v).second;
}
};
```

8.5 笛卡尔树

```
int s[maxn], root, lc[maxn], rc[maxn];

int top = 0;
s[++top] = root = 1;
for (int i = 2; i <= n; i++) {
    s[top + 1] = 0;
    while (top && a[i] < a[s[top]]) // 小根笛卡尔树
        top--;

    if (top)
        rc[s[top]] = i;
    else
        root = i;

    lc[i] = s[top + 1];
    s[++top] = i;
}
```

8.6 GarsiaWachs 算法（$O(n\log n)$ 合并石子）

设序列是 $\{a_i\}$，从左往右，找到一个最小的且满足 $a_{k-1} \le a_{k+1}$ 的 k，找到后合并 a_k 和 a_{k-1}，再从当前位置开始向左找最大的 j 满足 $a_j \ge a_k + a_{k-1}$（当然是指合并前的），然后把 $a_k + a_{k-1}$ 插到 j 的后面就行。一直重复，直到只剩下一堆石子就可以了。
另外在这个过程中，可以假设 a_{-1} 和 a_n 是正无穷的，可省略边界的判别。把 a_0 设为 INF，a_{n+1} 设为 INF-1，可实现剩余一堆石子时自动结束。

8.7 常用 NTT 素数及原根

$p = r \times 2^k + 1$	r	k	最小原根
104857601	25	22	3
167772161	5	25	3
469762049	7	26	3
985661441	235	22	3
998244353	119	23	3
1004535809	479	21	3
1005060097*	1917	19	5
2013265921	15	27	*31*
2281701377	17	27	3
31525197391593473	7	52	3
180143985094819841	5	55	*6*
1945555039024054273	27	56	5
4179340454199820289	29	57	3

*注：1005060097 有点危险，在变化长度大于 $524288 = 2^{19}$ 时不可用。

8.8 xorshift

```
ull k1, k2;
const int mod = 10000000;
ull xorShift128Plus() {
    ull k3 = k1, k4 = k2;
    k1 = k4;
    k3 ^= (k3 << 23);
    k2 = k3 ^ k4 ^ (k3 >> 17) ^ (k4 >> 26);
    return k2 + k4;
}
void gen(ull _k1, ull _k2) {
    k1 = _k1, k2 = _k2;
    int x = xorShift128Plus() % threshold + 1;
    // do sth
}


uint32_t xor128(void) {
    static uint32_t x = 123456789;
    static uint32_t y = 362436069;
    static uint32_t z = 521288629;
    static uint32_t w = 88675123;
    uint32_t t;

    t = x ^ (x << 11);
    x = y; y = z; z = w;
    return w = w ^ (w >> 19) ^ (t ^ (t >> 8));
}
```

8.9 枚举子集

（注意这是 $t \ne 0$ 的写法，如果可以等于 0 需要在循环里手动 break。）

```
for (int t = s; t; (--t) &= s) {
    // do something
}
```

8.10 STL

8.10.1 vector

- `vector(int n, const T &value)`：创建一个 `vector`，元素个数为 `n`，且值均为 `value`。
- `void emplace_back(Args&& ... args)`：自动构造并 `push_back` 一个元素，例如对一个存储 `pair` 的 `vector` 可以 `v.emplace_back(x, y)`。

8.10.2 list

- `assign()` 给list赋值
- `back()` 返回最后一个元素
- `begin()` 返回指向第一个元素的迭代器
- `clear()` 删除所有元素
- `empty()` 如果list是空的则返回true
- `end()` 返回末尾的迭代器
- `erase()` 删除一个元素
- `front()` 返回第一个元素
- `insert()` 插入一个元素到list中
- `max_size()` 返回list能容纳的最大元素数量
- `merge()` 合并两个list
- `pop_back()` 删除最后一个元素
- `pop_front()` 删除第一个元素
- `push_back()` 在list的末尾添加一个元素
- `push_front()` 在list的头部添加一个元素
- `rbegin()` 返回指向第一个元素的逆向迭代器
- `remove()` 从list删除元素
- `remove_if()` 按指定条件删除元素
- `rend()` 指向list末尾的逆向迭代器
- `resize()` 改变list的大小
- `reverse()` 把list的元素倒转
- `size()` 返回list中的元素个数
- `sort()` 给list排序
- `splice()` 合并两个list
- `swap()` 交换两个list
- `unique()` 删除list中重复的元

8.10.3 unordered_set/map

- `unordered_map<int, int, hash>`：自定义哈希函数，其中 `hash` 是一个带重载括号的类。

8.10.4 自定义 Hash

```
struct fuck_hash {
    fuck_hash() = default;

    size_t operator() (const fuck &f) const {
        return (size_t)f[0] ^ ((size_t)f[1] << 7) ^
            ((size_t)f[2] << 15) ^ ((size_t)f[3] <<
                ↪ 23);
    }
};

unordered_map<fuck, int, fuck_hash> cnt, sum;
```

8.11 Public Based DataStructure (PB_DS)

8.11.1 哈希表

```
#include<ext/pb_ds/assoc_container.hpp>
#include<ext/pb_ds/hash_policy.hpp>
using namespace __gnu_pbds;

cc_hash_table<string, int> mp1; // 拉链法
gp_hash_table<string, int> mp2; // 查探法（快一些）
```

8.11.2 堆

默认也是大根堆，和 `std::priority_queue` 保持一致。

```
#include<ext/pb_ds/priority_queue.hpp>
using namespace __gnu_pbds;

__gnu_pbds::priority_queue<int> q;
__gnu_pbds::priority_queue<int, greater<int>,
  ↪ pairing_heap_tag> pq;
```

效率参考：

* 共有五种操作：push、pop、modify、erase、join
* pairing_heap_tag：push和join为$O(1)$，其余为均摊$\Theta(\log n)$
* binary_heap_tag：只支持push和pop，均为均摊$\Theta(\log n)$
* binomial_heap_tag：push为均摊$O(1)$，其余为$\Theta(\log n)$
* rc_binomial_heap_tag：push为$O(1)$，其余为$\Theta(\log n)$
* thin_heap_tag：push为$O(1)$，不支持join，其余为$\Theta(\log n)$；果只有increase_key，那么modify为均摊$O(1)$
* “不支持”不是不能用，而是用起来很慢 csdn.net/TRiddle

常用操作：

- `push()`：向堆中压入一个元素，**返回迭代器**。
- `modify(point_iterator, const key)`：把迭代器位置的 `key` 修改为传入的 `key`。
- `erase(point_iterator)`：把迭代器位置的键值从堆中删除。
- `join(__gnu_pbds::priority_queue &other)`：把 `other` 合并到 `*this`，并把 `other` 清空

8.11.3 平衡树

```
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;

tree<int, null_type, less<int>, rb_tree_tag,
  ↪ tree_order_statistics_node_update> t;

// rb_tree_tag 红黑树（还有splay_tree_tag和ov_tree_tag,
  ↪ 后者不知道是什么）
```

注意第五个参数要填 `tree_order_statistics_node_update` 才能使用排名操作。

- `insert(x)`：向树中插入一个元素 `x`，返回`pair<point_iterator, bool>`。
- `erase(x)`：从树中删除一个元素/迭代器 `x`，返回一个 `bool` 表明是否删除成功。
- `order_of_key(x)`：返回 `x` 的排名，**0-based**。
- `find_by_order(x)`：返回排名（**0-based**）所对应元素的迭代器。
- `join(other)`：将 `other` 并入当前树，前提是两棵树的类型一样，并且二者值域不能重叠。`other` 树会被删除。

- split(x, other)：分裂成两部分，小于等于 x 的属于当前树，其余的属于 other。

（注意 **平衡树不支持多重值**，如果需要多重值，可以再开一个 unordered_map 来记录值出现的次数，将x << 32 后加上出现的次数后插入。注意此时应该为 long long 类型。）

8.12 rope

```cpp
#include <ext/rope>
using namespace __gnu_cxx;

push_back(x); // 在末尾添加x
insert(pos, x); // 在pos插入x，自然支持整个char数组的一次插入
erase(pos, x); // 从pos开始删除x个，不要只传一个参数，有毒
copy(pos, len, x); // 从pos开始到pos + len为止的部分，赋值给x
replace(pos, x); // 从pos开始换成x
substr(pos, x); // 提取pos开始x个
at(x) / [x]; // 访问第x个元素
```

8.13 其他 C++ 相关

8.13.1 cmath

- std::log1p(x)：（**注意是数字 1**）返回 $\ln(1+x)$ 的值，x 非常接近 0 时比直接 exp 精确得多。
- std::hypot(x, y[, z])：返回平方和的平方根，或者说到原点的欧几里德距离。

8.13.2 algorithm

- std::all_of(begin, end, f)：检查范围内元素调用函数 f 后是否全返回真。类似地还有 std::any_of 和 std::none_of。
- std::for_each(begin, end, f)：对范围内所有元素调用一次 f。如果传入的是引用，也可以用 f 修改。（例如 for_each(a, a + n, [](int &x){ cout << ++x << "\n"; }）)
- std::for_each_n(begin, n, f)：同上，只不过范围改成了从 begin 开始的 n 个元素。
- std::copy(), std::copy_n()：用法谁都会，但标准里说如果元素是可平凡复制的（比如 int），那么它会避免批量赋值，并且调用 std::memmove() 之类的快速复制函数。（一句话总结：它跑得快）
- std::rotate(begin, mid, end)：**向前**循环移动，移动后 mid 位置的元素会跑到 begin 位置。C++11 起会返回 begin 位置的元素移动后的位置。
- std::unique(begin, end)：去重，返回去重后的 end。
- std::partition(begin, end, f)：把 f 为 true 的放在前面，false 的放在后面，返回值是第二部分的开头，**不保持相对顺序**。如果要保留相对顺序可以用 std::stable_partition()，比如写整体二分。
- std::partition_copy(begin, end, begin_t, begin_f, f)：不修改原数组，把 true 的扔到 begin_t，false 的扔到 begin_f。返回值是两部分结尾的迭代器的 pair。
- std::equal_range(begin, end, x)：在已经排好序的数组里找到等于 x 的范围。
- std::minmax(a, b)：返回 pair(min(a, b), max(a, b))。但是要注意 **返回的是引用**，所以不能直接用来交换 l, r。

8.13.3 std::tuple

- std::get<i>(tup)：返回 tuple 的第 i 项。
- std::tuple_cat(...)：传入几个 tuple，返回按顺序连起来的 tuple。
- std::tie(x, y, z, ...)：把传入的变量的 **左值引用**绑起来作为 tuple 返回，例如可以 std::tie(x, y, z) = std::tuple(a, b, c)。

8.13.4 complex

- complex<double> imaginary = 1i, x = 2 + 3i：语法糖，可以这样直接构造复数。
- real/imag(x)：返回实部/虚部。
- conj(x)：返回共轭复数。
- arg(x)：返回辐角。
- norm(x)：返回模的平方。（直接求模用 abs(x) 就行。）
- polar(len, theta)：用模长和辐角构造复数。

8.14 一些游戏

8.14.1 德州扑克

一般来说德扑里 Ace 都是最大的，所以把 Ace 的点数规定为 14 会好写许多。

附一个高低奥马哈的参考代码，除了有四张底牌和需要比低之外和德扑区别不大。

```cpp
struct Card {
    int suit, value; // Ace is treated as 14

    Card(string s) {
        char a = s[0];

        if (isdigit(a))
            value = a - '0';
        else if (a == 'T')
            value = 10;
        else if (a == 'A')
            value = 14;
        else if (a == 'J')
            value = 11;
        else if (a == 'Q')
            value = 12;
        else if (a == 'K')
            value = 13;
        else
            value = -1; // error

        char b = s[1];
        suit = b; // Club, Diamond, Heart, Spade
    }

    friend bool operator < (const Card &a, const Card &b) {
        return a.value < b.value;
    }

    friend bool operator == (const Card &a, const Card &b) {
        return a.value == b.value;
    }
};

constexpr int Highcard = 1, Pair = 2, TwoPairs = 3, ThreeofaKind = 4, Straight = 5,
Flush = 6, FullHouse = 7, FourofaKind = 8, StraightFlush = 9;

struct Hand {
    vector<Card> v;
    int type;

    Hand() : type(0) {}

    Hand(const Hand &o) : v(o.v), type(o.type) {}

    Hand(const vector<Card> &v) : v(v), type(0) {}
```

```

    void init_high() {
        sort(v.begin(), v.end()); // 升序排序

        bool straight = false;
        if (v.back().value == 14) {
            if (v[0].value == 2 && v[1].value == 3 && v[2].value == 4 && v[3].value == 5) {
                straight = true;
                rotate(v.begin(), v.begin() + 1, v.end());
            }
        }

        if (!straight) {
            bool ok = true;
            for (int i = 1; i < 5; i++)
                ok &= (v[i].value == v[i - 1].value + 1);

            if (ok)
                straight = true;
        }

        bool flush = all_of(v.begin(), v.end(), [&] (const Card &a) {return a.suit == v.front().suit;});

        if (flush && straight) { // 同花顺
            type = StraightFlush;
            reverse(v.begin(), v.end());
            return;
        }

        vector<int> c;
        c.assign(15, 0);

        for (auto &o : v)
            c[o.value]++;

        vector<int> kind[5];

        for (int i = 2; i <= 14; i++)
            if (c[i] > 1)
                kind[c[i]].push_back(i);

        if (!kind[4].empty()) { // 四条
            type = FourofaKind;

            for (int i = 0; i < 4; i++)
                if (v[i].value != kind[4].front()) {
                    swap(v[i], v.back());
                    break;
                }

            return;
        }

        if (!kind[3].empty() && !kind[2].empty()) {
            type = FullHouse;

            sort(v.begin(), v.end(), [&] (const Card &a, const Card &b) {
                bool ta = (a.value == kind[3].front()), tb = (b.value == kind[3].front());

                return ta > tb;
            });

            return;
        }

        if (flush) {
            type = Flush;
            sort(v.begin(), v.end());
            reverse(v.begin(), v.end());

            return;
        }

        if (straight) {
            type = Straight;
            reverse(v.begin(), v.end());
            return;
        }

        if (!kind[3].empty()) {
            type = ThreeofaKind;

            sort(v.begin(), v.end(), [&] (const Card &a, const Card &b) {
                bool ta = (a.value == kind[3].front()), tb = (b.value == kind[3].front());

                return ta > tb;
            });

            if (v[3] < v[4])
                swap(v[3], v[4]);

            return;
        }

        if ((int)kind[2].size() == 2) {
            type = TwoPairs;

            sort(v.begin(), v.end(), [&] (const Card &a, const Card &b) {
                bool ta = (c[a.value] == 2), tb = (c[b.value] == 2);

                if (ta != tb)
                    return ta > tb;

                return a.value > b.value;
            });

            return;
        }

        if ((int)kind[2].size() == 1) {
            type = Pair;

            sort(v.begin(), v.end(), [&] (const Card &a, const Card &b) {
                bool ta = (c[a.value] == 2), tb = (c[b.value] == 2);

                if (ta != tb)
                    return ta > tb;

                return a.value > b.value;
            });

            return;
        }

        type = Highcard;

        sort(v.begin(), v.end());
        reverse(v.begin(), v.end());
    }

    void init_low() {
```

```
        for (auto &o : v)
            if (o.value == 14)
                o.value = 1;

        sort(v.begin(), v.end());
        reverse(v.begin(), v.end());
    }

    friend int cmp_high(const Hand &a, const Hand &b) {
        if (a.type != b.type)
            return a.type < b.type ? -1 : 1;

        if (a.v != b.v)
            return a.v < b.v ? -1 : 1;

        return 0;
    }

    friend bool small_high(const Hand &a, const Hand &b) {
        return cmp_high(a, b) < 0;
    }

    friend int cmp_low(const Hand &a, const Hand &b) {
        for (int i = 0; i < 5; i++)
            if (a.v[i].value != b.v[i].value)
                return a.v[i] < b.v[i] ? 1 : -1;

        return 0;
    }

    friend bool small_low(const Hand &a, const Hand &b) {
        return cmp_low(a, b) < 0;
    }

    bool operator ! () const {
        return v.empty();
    }

    string str() const {
        stringstream ss;

        for (auto &o : v)
            ss << o.value << ' ';

        return ss.str();
    }
};

Hand get_max_high(vector<Card> u, vector<Card> v) { // private, public
    Hand ans;

    for (int i = 0; i < 4; i++)
        for (int j = i + 1; j < 4; j++)
            for (int k = 0; k < 5; k++)
                for (int p = k + 1; p < 5; p++)
                    for (int q = p + 1; q < 5; q++) {
                        Hand tmp({u[i], u[j], v[k], v[p], v[q]});

                        tmp.init_high();

                        if (!ans || cmp_high(tmp, ans) > 0)
                            ans = tmp;
                    }

    return ans;
}

Hand get_max_low(vector<Card> tu, vector<Card> tv) {
    vector<Card> u, v;

    for (auto o : tu)
        if (o.value == 14 || o.value <= 8)
            u.push_back(o);

    for (auto o : tv)
        if (o.value == 14 || o.value <= 8)
            v.push_back(o);

    Hand ans;

    for (int i = 0; i < (int)u.size(); i++)
        for (int j = i + 1; j < (int)u.size(); j++)
            for (int k = 0; k < (int)v.size(); k++)
                for (int p = k + 1; p < (int)v.size(); p++)
                    for (int q = p + 1; q < (int)v.size(); q++) {
                        vector<Card> vec = {u[i], u[j], v[k], v[p], v[q]};

                        bool bad = false;

                        for (int a = 0; a < 5; a++)
                            for (int b = a + 1; b < 5; b++)
                                if (vec[a].value == vec[b].value)
                                    bad = true;

                        if (bad)
                            continue;

                        Hand tmp(vec);

                        tmp.init_low();

                        if (!ans || cmp_low(tmp, ans) > 0)
                            ans = tmp;
                    }

    return ans;
}

int main() {

    ios::sync_with_stdio(false);

    int T;
    cin >> T;

    while (T--) {
        int p;
        cin >> p;

        vector<Card> alice, bob, pub;

        for (int i = 0; i < 4; i++) {
            string s;
            cin >> s;
            alice.push_back(Card(s));
        }

        for (int i = 0; i < 4; i++) {
            string s;
            cin >> s;
            bob.push_back(Card(s));
        }
```

```
        for (int i = 0; i < 5; i++) {
            string s;
            cin >> s;
            pub.push_back(Card(s));
        }

        Hand alice_high = get_max_high(alice, pub), bob_high = get_max_high(bob, pub);
        Hand alice_low = get_max_low(alice, pub), bob_low = get_max_low(bob, pub);

        int dh = cmp_high(alice_high, bob_high);
        int ans[2] = {0};

        if (!alice_low && !bob_low) {
            if (!dh) {
                ans[0] = p - p / 2;
                ans[1] = p / 2;
            }
            else
                ans[dh == -1] = p;
        }
        else if (!alice_low || !bob_low) {
            ans[!alice_low] += p / 2;

            if (!dh) {
                ans[0] += p - p / 2 - (p - p / 2) / 2;
                ans[1] += (p - p / 2) / 2;
            }
            else
                ans[dh == -1] += p - p / 2;
        }
        else {
            int dl = cmp_low(alice_low, bob_low);

            if (!dl) {
                ans[0] += p / 2 - p / 2 / 2;
                ans[1] += p / 2 / 2;
            }
            else
                ans[dl == -1] += p / 2;

            if (!dh) {
                ans[0] += p - p / 2 - (p - p / 2) / 2;
                ans[1] += (p - p / 2) / 2;
            }
            else
                ans[dh == -1] += p - p / 2;
        }

        cout << ans[0] << ' ' << ans[1] << '\n';
    }

    return 0;
}
```

8.14.2 炉石传说

两个随从 (a_i, h_i) 和 (a_j, h_j) 皇城 PK，最后只有 $a_i \times h_i$ 较大的一方才有可能活下来，当然也有可能一起死。

8.15 OEIS

如果没有特殊说明，那么以下数列都从第 0 项开始，除非没有定义也没有好的办法解释第 0 项的意义。

8.15.1 计数相关

1. **卡特兰数 A000108）**
   1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, 208012, 742900, 2674440, 9694845, 35357670, ...
   性质见 1.10.7.卡特兰数 施罗德数 默慈金数（第 17 页）。

2. **（大）施罗德数 A006318**
   1, 2, 6, 22, 90, 394, 1806, 8558, 41586, 206098, 1037718, 5293446, 27297738, 142078746, 745387038, ... (0-based)
   性质同样见 1.10.7.卡特兰数 施罗德数 默慈金数（第 17 页）。

3. **小施罗德数 A001003**
   1, 1, 3, 11, 45, 197, 903, 4279, 20793, 103049, 518859, 2646723, 13648869, 71039373, 372693519, ... (0-based)
   性质位置同上。
   小施罗德数除了第 0 项以外都是施罗德数的一半。

4. **默慈金数（Motzkin numbers）A001006**
   1, 1, 2, 4, 9, 21, 51, 127, 323, 835, 2188, 5798, 15511, 41835, 113634, 310572, 853467, 2356779, ... (0-based)
   性质位置同上。

5. **将点按顺序排成一圈后不自交的树的个数 A001764**
   1, 1, 3, 12, 55, 273, 1428, 7752, 43263, 246675, 1430715, 8414640, 50067108, 300830572, 1822766520, ... (0-based)
   $a_n = \frac{\binom{3n}{n}}{2n+1}$
   也就是说，在圆上按顺序排列的 n 个点之间连 $n-1$ 条不相交（除端点外）的弦，组成一棵树的方案数。
   也等于每次只能向右或向上，并且不能高于 $y = 2x$ 这条直线，从 $(0, 0)$ 走到 $(n, 2n)$ 的方案数。
   扩展 如果改成不能高于 $y = kx$ 这条直线，走到 (n, kn) 的方案数，那么答案就是 $\frac{\binom{(k+1)n}{n}}{kn+1}$。

6. **n 个点的圆上画不相交的弦的方案数 A054726**
   1, 1, 2, 8, 48, 352, 2880, 25216, 231168, 2190848, 21292032, 211044352, 2125246464, 21681954816, ... (0-based)
   $a_n = 2^n s_{n-2}$ $(n > 2)$，其中 s_n 是上面的小施罗德数。
   和上面的区别在于，这里可以不连满 $n-1$ 条边。另外默慈金数画的弦不能共享端点，但是这里可以。

7. **Wedderburn-Etherington numbers A001190**
   0, 1, 1, 1, 2, 3, 6, 11, 23, 46, 98, 207, 451, 983, 2179, 4850, 10905, 24631, 56011, 127912, 293547, ... (0-based)
   每个结点都有 0 或者 2 个儿子，且总共有 n 个叶子结点的二叉树方案数。**（无标号）**
   同时也是 $n-1$ 个结点的 **无标号** 二叉树个数。
   $A(x) = x + \frac{A(x)^2 + A(x^2)}{2} = 1 - \sqrt{1 - 2x - A(x^2)}$

8. **分拆数 A000041**
   1, 1, 2, 3, 5, 7, 11, 15, 22, 30, 42, 56, 77, 101, 135, 176, 231, 297, 385, 490, 627, 792, 1002, ... (0-based)
   性质见 1.10.3.分拆数（第 16 页）。

9. **贝尔数 A000110**
   1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, 115975, 678570, 4213597, 27644437, 190899322, 1382958545, ... (0-based)
   性质见 1.10.5.贝尔数 Bell（第 17 页）。

10. **错位排列数 A0000166**
    1, 0, 1, 2, 9, 44, 265, 1854, 14833, 133496, 1334961, 14684570, 176214841, 2290792932, 32071101049, ... (0-based)

11. **交替阶乘 A005165**
    0, 1, 1, 5, 19, 101, 619, 4421, 35899, 326981, 3301819, 36614981, 442386619, 5784634181, 81393657019, ... (0-based)
    $$n! - (n-1)! + (n-2)! - \ldots 1! = \sum_{i=0}^{n-1} (-1)^i (n-i)!$$
    $a_0 = 0,\ a_n = n! - a_{n-1}$

8.15.2 线性递推数列

1. **Lucas 数 A000032**
2, 1, 3, 4, 7, 11, 18, 29, 47, 76, 123, 199, 322, 521, 843, 1364, 2207, 3571, 5778, 9349, 15127, ...

2. **斐波那契数 A000045**
0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144, 233, 377, 610, 987, 1597, 2584, 4181, 6765, 10946, ...

3. **泰波那契数（Tribonacci）A000071**
0, 0, 1, 1, 2, 4, 7, 13, 24, 44, 81, 149, 274, 504, 927, 1705, 3136, 5768, 10609, 19513, 35890, ...
$a_0 = a_1 = 0,\ a_2 = 1,\ a_n = a_{n-1} + a_{n-2} + a_{n-3}$

4. **Pell 数 A0000129**
0, 1, 2, 5, 12, 29, 70, 169, 408, 985, 2378, 5741, 13860, 33461, 80782, 195025, 470832, 1136689, ...
$a_0 = 0,\ a_1 = 1,\ a_n = 2a_{n-1} + a_{n-2}$

5. **Padovan 数 A0000931**
1, 0, 0, 1, 0, 1, 1, 1, 2, 2, 3, 4, 5, 7, 9, 12, 16, 21, 28, 37, 49, 65, 86, 114, 151, 200, 265, 351, 465, 616, 816, 1081, 1432, 1897, 2513, 3329, 4410, 5842, 7739, 10252, 13581, 17991, 23833, 31572, ...
$a_0 = 1,\ a_1 = a_2 = 0,\ a_n = a_{n-2} + a_{n-3}$

6. **Jacobsthal numbers A001045**
0, 1, 1, 3, 5, 11, 21, 43, 85, 171, 341, 683, 1365, 2731, 5461, 10923, 21845, 43691, 87381, 174763, ...
$a_0 = 0,\ a_1 = 1.\ a_n = a_{n-1} + 2a_{n-2}$
同时也是最接近 $\frac{2^n}{3}$ 的整数。

7. **佩林数 A001608**
3, 0, 2, 3, 2, 5, 5, 7, 10, 12, 17, 22, 29, 39, 51, 68, 90, 119, 158, 209, 277, 367, 486, 644, 853, ...
$a_0 = 3,\ a_1 = 0,\ a_2 = 2,\ a_n = a_{n-2} + a_{n-3}$

8.15.3 数论相关

1. **Carmichael 数/伪质数 A002997**
561, 1105, 1729, 2465, 2821, 6601, 8911, 10585, 15841, 29341, 41041, 46657, 52633, 62745, 63973, 75361, 101101, 115921, 126217, 162401, 172081, 188461, 252601, 278545, 294409, 314821, 334153, 340561, 399001, 410041, 449065, 488881, 512461, ...
满足 $\forall$ 与 n 互质的 a，都有 $a^{n-1} \equiv 1 \pmod n$ 的所有 **合数** n 被称为 Carmichael 数。
Carmichael 数在 10^8 以内只有255个。

2. **反质数 A002182**
1, 2, 4, 6, 12, 24, 36, 48, 60, 120, 180, 240, 360, 720, 840, 1260, 1680, 2520, 5040, 7560, 10080, 15120, 20160, 25200, 27720, 45360, 50400, 55440, 83160, 110880, 166320, 221760, 277200, 332640, 498960, 554400, 665280, 720720, 1081080, 1441440, 2162160, ...
比所有更小的数的约数数量都更多的数。

3. **前 n 个质数的乘积 A002110**
1, 2, 6, 30, 210, 2310, 30030, 510510, 9699690, 223092870, 6469693230, 200560490130, 7420738134810, ...

4. **梅森质数 A000668**
3, 7, 31, 127, 8191, 131071, 524287, 2147483647, 2305843009213693951, 618970019642690137449562111, 162259276829213363391578010288127, 170141183460469231731687303715884105727
p 是质数，同时 $2^p - 1$ 也是质数。

8.15.4 其他

1. **伯努利数 A027641**
参见 1.10.2.伯努利数 Bernoulli 自然数幂次和（第 15 页）。
（伯努利数并不是整数。）

2. **四个柱子的汉诺塔 A007664**
0, 1, 3, 5, 9, 13, 17, 25, 33, 41, 49, 65, 81, 97, 113, 129, 161, 193, 225, 257, 289, 321, 385, 449, ...
差分之后可以发现其实就是 1 次 $+1$，2 次 $+2$，3 次 $+4$，4 次 $+8$ ...的规律。

3. **乌拉姆数（Ulam numbers）A002858**
1, 2, 3, 4, 6, 8, 11, 13, 16, 18, 26, 28, 36, 38, 47, 48, 53, 57, 62, 69, 72, 77, 82, 87, 97, 99, 102, 106, 114, 126, 131, 138, 145, 148, 155, 175, 177, 180, 182, 189, 197, 206, 209, 219, 221, 236, 238, 241, 243, 253, 258, 260, 273, 282, 309, 316, 319, 324, 339，...
$a_1 = 1$，$a_2 = 2$，a_n 表示在所有 $> a_{n-1}$ 的数中，最小的、能被表示成前面的两个 **不同** 的元素的和的数。

8.16 编译选项

- `-O2 -g -std=c++20`：狗都知道
- `-Wall -Wextra -Wshadow -Wconversion`：更多警告
  - `-Werror`：强制将所有 Warning 变成 Error
- `-fsanitize=(address/undefined/ftrapv)`：检查数组越界/有符号整数溢出（算 UB）
  - 调试神器，在遇到错误时会输出信息。
  - 注意无符号类型溢出不算 UB。
- `#define debug(x) cout << #x << " = " << x << endl`

9 附录

9.1 VScode 相关

9.1.1 插件

- Chinese (Simplified)（简体中文语言包）
- C/C++
- C++ Intellisense （前提是让用）
- Better C++ Syntax
- Python
- Pylance（前提是让用）

9.1.2 设置选项

- Editor: Insert Spaces （取消勾选，改为 tab 缩进）
- Editor: Line Warp （开启折行）
- 改配色，“深色+：默认深色”
- 自动保存（F1 → “auto”）
- Terminal → Integrated: Cursor Style（修改终端光标形状）
- Terminal → Integrated: Cursor Blinking（终端光标闪烁）
- 字体改为 Cascadia Code/MonoWindows 可用）

9.1.3 快捷键

- `Ctrl + ` `（键盘左上角的倒引号）：显示终端
- `Ctrl + 1/2/3`：切到对应栏
- `F1 / Ctrl + Shift + P`：万能键，打开命令面板
- `F8`：下一个 Error　Shift+F8：上一个 Error
- `Ctrl + [ or ]`：当前行向左/右缩进
- `Alt + F12`：查看定义的缩略图（显示小窗，不跳过去）
- `Ctrl + H`：查找替换
- `Ctrl + D`：下一个匹配的也被选中（用于配合 Ctrl+F）
- `Ctrl + U`：回退上一个光标操作（防止光标飞了找不回去）
- `Ctrl + \`：水平分栏，最多 3 栏

更多快捷键参见最后两页，分别是 Windows 和 Linux 下的快捷键列表。

9.2 骂人的艺术—梁实秋

古今中外没有一个不骂人的人。骂人就是有道德观念的意思，因为在骂人的时候，至少在骂人者自己总觉得那人有该骂的地方。何者该骂，何者不该骂，这个抉择的标准，是极道德的。所以根本不骂人，大可不必。骂人是一种发泄感情的方法，尤其是那一种怨怒的感情。想骂人的时候而不骂，时常在身体上弄出毛病，所以想骂人时，骂骂何妨？

但是，骂人是一种高深的学问，不是人人都可以随便试的。有因为骂人挨嘴巴的，有因为骂人吃官司的，有因为骂人反被人骂的，这都是不会骂人的原故。今以研究所得，公诸同好，或可为骂人时之一助乎？

1. 知己知彼

骂人是和动手打架一样的，你如其敢打人一拳，你先要自己忖度下，你吃得起别人的一拳否。这叫做知己知彼。骂人也是一样。譬如你骂他是“屈死”，你先要反省，自己和“屈死”有无分别。你骂别人荒唐，你自己想想曾否吃喝嫖赌。否则别人回敬你一二句，你就受不了。所以别人有着某种短处，而足下也正有同病，那么你在骂他的时候只得割爱。

2. 无骂不如己者

要骂人须要挑比你大一点的人物，比你漂亮一点的或者比你坏得万倍而比你得势的人物，总之，你要骂人，那人无论在好的一方面或坏的一方面都要能胜过你，你才不吃亏。你骂大人物，就怕他不理你，他一回骂，你就算骂着了。因为身份相同的人才肯对骂。在坏的一方面胜过你的，你骂他就如教训一般，他既便回骂，一般人仍不会理会他的。假如你骂一个无关痛痒的人，你越骂他他越得意，时常可以把一个无名小卒骂出名了，你看冤与不冤？

3. 适可而止

骂大人物骂到他回骂的时候，便不可再骂；再骂则一般人对你必无同情，以为你是无理取闹。骂小人物骂到他不能回骂的时候，便不可再骂；再骂下去则一般人对你也必无同情，以为你是欺负弱者。

4. 旁敲侧击

他偷东西，你骂他是贼；他抢东西，你骂他是盗，这是笨伯。骂人必须先明虚实掩映之法，须要烘托旁衬，旁敲侧击，于要紧处只一语便得，所谓杀人于咽喉处着刀。越要骂他你越要原谅他，即便说些恭维话亦不为过，这样的骂法才能显得你所骂的句句是真实确凿，让旁人看起来也可见得你的度量。

5. 态度镇定

骂人最忌浮躁。一语不合，面红筋跳，暴躁如雷，此灌夫骂座，泼妇骂街之术，不足以言骂人。善骂者必须态度镇静，行若无事。普通一般骂人，谁的声音高便算谁占理，谁的来势猛便算谁骂赢，惟真善骂人者，乃能避其锋而击其懈。你等他骂得疲倦的时候，你只消轻轻的回敬他一句，让他再狂吼一阵。在他暴躁不堪的时候，你不妨对他冷笑几声，包管你不费力气，把他气得死去活来，骂得他针针见血。

6. 出言典雅

骂人要骂得微妙含蓄，你骂他一句要使他不甚觉得是骂，等到想过一遍才慢慢觉悟这句话不是好话，让他笑着的面孔由白而红，由红而紫，由紫而灰，这才是骂人的上乘。欲达到此种目的，深刻之用意固不可少，而典雅之言词则尤为重要。言词典雅可使听者不致刺耳。如要骂人骂得典雅，则首先要在骂时万万别提起女人身上的某一部分，万万不要涉及生理学范围。骂人一骂到生理学范围以内，底下再有什么话都不好说了。譬如你骂某甲，千万别提起他的令堂令妹。因为那样一来，便无是非可言，并且你自己也不免有令堂令妹，他若回敬起来，岂非势均力敌，半斤八两？再者骂人的时候，最好不要加人以种种难堪的名词，称呼起来总要客气，即使他是极卑鄙的小人，你也不妨称他先生，越客气，越骂得有力量。骂得时节最好引用他自己的词句，这不但可以使他难堪，还可以减轻他对你骂的力量。俗话少用，因为俗话一览无遗，不若典雅古文曲折含蓄。

7. 以退为进

两人对骂，而自己亦有理屈之处，则处于开骂伊始，特宜注意，最好是毅然将自己理屈之处完全承认下来，即使道歉认错均不妨事。先把自己理屈之处轻轻遮掩过去，然后你再重整旗鼓，着着逼人，方可无后顾之忧。即使自己没有理屈的地方，也绝不可自行夸张，务必要谦逊不遑，把自己的位置降到一个不可再降的位置，然后骂起人来，自有一种公正光明的态度。否则你骂他一两句，他便以你个人的事反唇相讥，一场对骂，会变成两人私下口角，是非曲直，无从判断。所以骂人者自己要低声下气，此所谓以退为进。

8. 预设埋伏

你把这句话骂过去，你便要想想看，他将用什么话骂回来。有眼光的骂人者，便处处留神，或是先将他要骂你的话替他说出来，或是预先安设埋伏，令他骂回来的话失去效力。他骂你的话，你替他说出来，这便等于缴了他的械一般。预设埋伏，便是在要攻击你的地方，你先轻轻的安下话根，然后他骂过来就等于枪弹打在沙包上，不能中伤。

9. 小题大做

如对方有该骂之处，而题目身小，不值一骂，或你所知不多，不足一骂，那时节你便可用小题大做的方法，来扩大题目。先用诚恳而怀疑的态度引申对方的意思，由不紧要之点引到大题目上去，处处用严谨的逻辑逼他说出不逻辑的话来，或是逼他说出合于逻辑但不合乎理的话来，然后你再大举骂他，骂到体无完肤为止，而原来惹动你的小题目，轻轻一提便了。

10. 远交近攻

一个时候，只能骂一个人，或一种人，或一派人。决不宜多树敌。所以骂人的时候，万勿连累旁人，即使必须牵涉多人，你也要表示好意，否则回骂之声纷至沓来，使你无从应付。

骂人的艺术，一时所能想起来的有上面十条，信手拈来，并无条理。我做此文的用意，是助人骂人。同时也是想把骂人的技术揭破一点，供爱骂人者参考。挨骂的人看看，骂人的心理原来是这样的，也算是揭破一张黑幕给你瞧瞧！

9.3 Cheat Sheet

见后面几页。

Theoretical Computer Science Cheat Sheet

Definitions

$f(n) = O(g(n))$	iff $\exists$ positive c, n_0 such that $0 \le f(n) \le cg(n)\ \forall n \ge n_0$.
$f(n) = \Omega(g(n))$	iff $\exists$ positive c, n_0 such that $f(n) \ge cg(n) \ge 0\ \forall n \ge n_0$.
$f(n) = \Theta(g(n))$	iff $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$.
$f(n) = o(g(n))$	iff $\lim_{n\to\infty} f(n)/g(n) = 0$.
$\lim\limits_{n\to\infty} a_n = a$	iff $\forall \epsilon > 0$, $\exists n_0$ such that $\lvert a_n - a\rvert < \epsilon$, $\forall n \ge n_0$.
$\sup S$	least $b \in \mathbb{R}$ such that $b \ge s$, $\forall s \in S$.
$\inf S$	greatest $b \in \mathbb{R}$ such that $b \le s$, $\forall s \in S$.
$\liminf\limits_{n\to\infty} a_n$	$\lim\limits_{n\to\infty} \inf\{a_i \mid i \ge n, i \in \mathbb{N}\}$.
$\limsup\limits_{n\to\infty} a_n$	$\lim\limits_{n\to\infty} \sup\{a_i \mid i \ge n, i \in \mathbb{N}\}$.
$\binom{n}{k}$	Combinations: Size k subsets of a size n set.
$\left[{n \atop k}\right]$	Stirling numbers (1st kind): Arrangements of an n element set into k cycles.
$\left\{{n \atop k}\right\}$	Stirling numbers (2nd kind): Partitions of an n element set into k non-empty sets.
$\left\langle{n \atop k}\right\rangle$	1st order Eulerian numbers: Permutations $\pi_1\pi_2\ldots\pi_n$ on $\{1, 2, \ldots, n\}$ with k ascents.
$\left\langle\!\left\langle{n \atop k}\right\rangle\!\right\rangle$	2nd order Eulerian numbers.
C_n	Catalan Numbers: Binary trees with $n+1$ vertices.

Series

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}, \quad \sum_{i=1}^{n} i^2 = \frac{n(n+1)(2n+1)}{6}, \quad \sum_{i=1}^{n} i^3 = \frac{n^2(n+1)^2}{4}.$$

In general:

$$\sum_{i=1}^{n} i^m = \frac{1}{m+1}\left[(n+1)^{m+1} - 1 - \sum_{i=1}^{n}\left((i+1)^{m+1} - i^{m+1} - (m+1)i^m\right)\right]$$

$$\sum_{i=1}^{n-1} i^m = \frac{1}{m+1}\sum_{k=0}^{m}\binom{m+1}{k}B_k n^{m+1-k}.$$

Geometric series:

$$\sum_{i=0}^{n} c^i = \frac{c^{n+1}-1}{c-1}, \quad c \ne 1, \quad \sum_{i=0}^{\infty} c^i = \frac{1}{1-c}, \quad \sum_{i=1}^{\infty} c^i = \frac{c}{1-c}, \quad |c| < 1,$$

$$\sum_{i=0}^{n} ic^i = \frac{nc^{n+2} - (n+1)c^{n+1} + c}{(c-1)^2}, \quad c \ne 1, \quad \sum_{i=0}^{\infty} ic^i = \frac{c}{(1-c)^2}, \quad |c| < 1.$$

Harmonic series:

$$H_n = \sum_{i=1}^{n}\frac{1}{i}, \qquad \sum_{i=1}^{n} iH_i = \frac{n(n+1)}{2}H_n - \frac{n(n-1)}{4}.$$

$$\sum_{i=1}^{n} H_i = (n+1)H_n - n, \quad \sum_{i=1}^{n}\binom{i}{m}H_i = \binom{n+1}{m+1}\left(H_{n+1} - \frac{1}{m+1}\right).$$

1. $\displaystyle\binom{n}{k} = \frac{n!}{(n-k)!k!}$, **2.** $\displaystyle\sum_{k=0}^{n}\binom{n}{k} = 2^n$, **3.** $\displaystyle\binom{n}{k} = \binom{n}{n-k}$,

4. $\displaystyle\binom{n}{k} = \frac{n}{k}\binom{n-1}{k-1}$, **5.** $\displaystyle\binom{n}{k} = \binom{n-1}{k} + \binom{n-1}{k-1}$,

6. $\displaystyle\binom{n}{m}\binom{m}{k} = \binom{n}{k}\binom{n-k}{m-k}$, **7.** $\displaystyle\sum_{k=0}^{n}\binom{r+k}{k} = \binom{r+n+1}{n}$,

8. $\displaystyle\sum_{k=0}^{n}\binom{k}{m} = \binom{n+1}{m+1}$, **9.** $\displaystyle\sum_{k=0}^{n}\binom{r}{k}\binom{s}{n-k} = \binom{r+s}{n}$,

10. $\displaystyle\binom{n}{k} = (-1)^k\binom{k-n-1}{k}$, **11.** $\displaystyle\left\{{n \atop 1}\right\} = \left\{{n \atop n}\right\} = 1$,

12. $\displaystyle\left\{{n \atop 2}\right\} = 2^{n-1} - 1$, **13.** $\displaystyle\left\{{n \atop k}\right\} = k\left\{{n-1 \atop k}\right\} + \left\{{n-1 \atop k-1}\right\}$,

14. $\displaystyle\left[{n \atop 1}\right] = (n-1)!$, **15.** $\displaystyle\left[{n \atop 2}\right] = (n-1)!H_{n-1}$, **16.** $\displaystyle\left[{n \atop n}\right] = 1$, **17.** $\displaystyle\left[{n \atop k}\right] \ge \left\{{n \atop k}\right\}$,

18. $\displaystyle\left[{n \atop k}\right] = (n-1)\left[{n-1 \atop k}\right] + \left[{n-1 \atop k-1}\right]$, **19.** $\displaystyle\left\{{n \atop n-1}\right\} = \left[{n \atop n-1}\right] = \binom{n}{2}$, **20.** $\displaystyle\sum_{k=0}^{n}\left[{n \atop k}\right] = n!$, **21.** $\displaystyle C_n = \frac{1}{n+1}\binom{2n}{n}$,

22. $\displaystyle\left\langle{n \atop 0}\right\rangle = \left\langle{n \atop n-1}\right\rangle = 1$, **23.** $\displaystyle\left\langle{n \atop k}\right\rangle = \left\langle{n \atop n-1-k}\right\rangle$, **24.** $\displaystyle\left\langle{n \atop k}\right\rangle = (k+1)\left\langle{n-1 \atop k}\right\rangle + (n-k)\left\langle{n-1 \atop k-1}\right\rangle$,

25. $\displaystyle\left\langle{0 \atop k}\right\rangle = \begin{cases} 1 & \text{if } k = 0, \\ 0 & \text{otherwise} \end{cases}$ **26.** $\displaystyle\left\langle{n \atop 1}\right\rangle = 2^n - n - 1$, **27.** $\displaystyle\left\langle{n \atop 2}\right\rangle = 3^n - (n+1)2^n + \binom{n+1}{2}$,

28. $\displaystyle x^n = \sum_{k=0}^{n}\left\langle{n \atop k}\right\rangle\binom{x+k}{n}$, **29.** $\displaystyle\left\langle{n \atop m}\right\rangle = \sum_{k=0}^{m}\binom{n+1}{k}(m+1-k)^n(-1)^k$, **30.** $\displaystyle m!\left\{{n \atop m}\right\} = \sum_{k=0}^{n}\left\langle{n \atop k}\right\rangle\binom{k}{n-m}$,

31. $\displaystyle\left\langle{n \atop m}\right\rangle = \sum_{k=0}^{n}\left\{{n \atop k}\right\}\binom{n-k}{m}(-1)^{n-k-m}k!$, **32.** $\displaystyle\left\langle\!\left\langle{n \atop 0}\right\rangle\!\right\rangle = 1$, **33.** $\displaystyle\left\langle\!\left\langle{n \atop n}\right\rangle\!\right\rangle = 0$ for $n \ne 0$,

34. $\displaystyle\left\langle\!\left\langle{n \atop k}\right\rangle\!\right\rangle = (k+1)\left\langle\!\left\langle{n-1 \atop k}\right\rangle\!\right\rangle + (2n-1-k)\left\langle\!\left\langle{n-1 \atop k-1}\right\rangle\!\right\rangle$, **35.** $\displaystyle\sum_{k=0}^{n}\left\langle\!\left\langle{n \atop k}\right\rangle\!\right\rangle = \frac{(2n)^{\underline{n}}}{2^n}$,

36. $\displaystyle\left\{{x \atop x-n}\right\} = \sum_{k=0}^{n}\left\langle\!\left\langle{n \atop k}\right\rangle\!\right\rangle\binom{x+n-1-k}{2n}$, **37.** $\displaystyle\left\{{n+1 \atop m+1}\right\} = \sum_{k}\binom{n}{k}\left\{{k \atop m}\right\} = \sum_{k=0}^{n}\left\{{k \atop m}\right\}(m+1)^{n-k}$,

Theoretical Computer Science Cheat Sheet

Identities Cont.

38. $\begin{bmatrix} n+1 \\ m+1 \end{bmatrix} = \sum_k \begin{bmatrix} n \\ k \end{bmatrix} \binom{k}{m} = \sum_{k=0}^{n} \begin{bmatrix} k \\ m \end{bmatrix} n^{\underline{n-k}} = n! \sum_{k=0}^{n} \frac{1}{k!} \begin{bmatrix} k \\ m \end{bmatrix},$

39. $\begin{bmatrix} x \\ x-n \end{bmatrix} = \sum_{k=0}^{n} \left\langle\!\!\left\langle {n \atop k} \right\rangle\!\!\right\rangle \binom{x+k}{2n},$

40. $\left\{ {n \atop m} \right\} = \sum_k \binom{n}{k} \left\{ {k+1 \atop m+1} \right\} (-1)^{n-k},$

41. $\begin{bmatrix} n \\ m \end{bmatrix} = \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \binom{k}{m} (-1)^{m-k},$

42. $\left\{ {m+n+1 \atop m} \right\} = \sum_{k=0}^{m} k \left\{ {n+k \atop k} \right\},$

43. $\begin{bmatrix} m+n+1 \\ m \end{bmatrix} = \sum_{k=0}^{m} k(n+k) \begin{bmatrix} n+k \\ k \end{bmatrix},$

44. $\binom{n}{m} = \sum_k \left\{ {n+1 \atop k+1} \right\} \begin{bmatrix} k \\ m \end{bmatrix} (-1)^{m-k},$

45. $(n-m)! \binom{n}{m} = \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \left\{ {k \atop m} \right\} (-1)^{m-k}, \quad \text{for } n \geq m,$

46. $\left\{ {n \atop n-m} \right\} = \sum_k \binom{m-n}{m+k} \binom{m+n}{n+k} \begin{bmatrix} m+k \\ k \end{bmatrix},$

47. $\begin{bmatrix} n \\ n-m \end{bmatrix} = \sum_k \binom{m-n}{m+k} \binom{m+n}{n+k} \left\{ {m+k \atop k} \right\},$

48. $\left\{ {n \atop \ell+m} \right\} \binom{\ell+m}{\ell} = \sum_k \left\{ {k \atop \ell} \right\} \left\{ {n-k \atop m} \right\} \binom{n}{k},$

49. $\begin{bmatrix} n \\ \ell+m \end{bmatrix} \binom{\ell+m}{\ell} = \sum_k \begin{bmatrix} k \\ \ell \end{bmatrix} \begin{bmatrix} n-k \\ m \end{bmatrix} \binom{n}{k}.$

Trees

Every tree with n vertices has $n-1$ edges.

Kraft inequality: If the depths of the leaves of a binary tree are $d_1, \ldots, d_n$:

$$\sum_{i=1}^{n} 2^{-d_i} \leq 1,$$

and equality holds only if every internal node has 2 sons.

Recurrences

Master method:
$T(n) = aT(n/b) + f(n), \quad a \geq 1, b > 1$

If $\exists \epsilon > 0$ such that $f(n) = O(n^{\log_b a - \epsilon})$ then

$$T(n) = \Theta(n^{\log_b a}).$$

If $f(n) = \Theta(n^{\log_b a})$ then

$$T(n) = \Theta(n^{\log_b a} \log_2 n).$$

If $\exists \epsilon > 0$ such that $f(n) = \Omega(n^{\log_b a + \epsilon})$, and $\exists c < 1$ such that $af(n/b) \leq cf(n)$ for large n, then

$$T(n) = \Theta(f(n)).$$

Substitution (example): Consider the following recurrence

$$T_{i+1} = 2^{2^i} \cdot T_i^2, \quad T_1 = 2.$$

Note that T_i is always a power of two. Let $t_i = \log_2 T_i$. Then we have

$$t_{i+1} = 2^i + 2t_i, \quad t_1 = 1.$$

Let $u_i = t_i / 2^i$. Dividing both sides of the previous equation by 2^{i+1} we get

$$\frac{t_{i+1}}{2^{i+1}} = \frac{2^i}{2^{i+1}} + \frac{t_i}{2^i}.$$

Substituting we find

$$u_{i+1} = \tfrac{1}{2} + u_i, \qquad u_1 = \tfrac{1}{2},$$

which is simply $u_i = i/2$. So we find that T_i has the closed form $T_i = 2^{i2^{i-1}}$.

Summing factors (example): Consider the following recurrence

$$T(n) = 3T(n/2) + n, \quad T(1) = 1.$$

Rewrite so that all terms involving T are on the left side

$$T(n) - 3T(n/2) = n.$$

Now expand the recurrence, and choose a factor which makes the left side "telescope"

$$\begin{aligned} 1\big(T(n) - 3T(n/2) &= n\big) \\ 3\big(T(n/2) - 3T(n/4) &= n/2\big) \\ \vdots \quad \vdots \quad &\vdots \\ 3^{\log_2 n - 1}\big(T(2) - 3T(1) &= 2\big) \end{aligned}$$

Let $m = \log_2 n$. Summing the left side we get $T(n) - 3^m T(1) = T(n) - 3^m = T(n) - n^k$ where $k = \log_2 3 \approx 1.58496$. Summing the right side we get

$$\sum_{i=0}^{m-1} \frac{n}{2^i} 3^i = n \sum_{i=0}^{m-1} \left(\tfrac{3}{2}\right)^i.$$

Let $c = \frac{3}{2}$. Then we have

$$\begin{aligned} n \sum_{i=0}^{m-1} c^i &= n \left(\frac{c^m - 1}{c - 1} \right) \\ &= 2n(c^{\log_2 n} - 1) \\ &= 2n(c^{(k-1)\log_c n} - 1) \\ &= 2n^k - 2n, \end{aligned}$$

and so $T(n) = 3n^k - 2n$. Full history recurrences can often be changed to limited history ones (example): Consider

$$T_i = 1 + \sum_{j=0}^{i-1} T_j, \quad T_0 = 1.$$

Note that

$$T_{i+1} = 1 + \sum_{j=0}^{i} T_j.$$

Subtracting we find

$$\begin{aligned} T_{i+1} - T_i &= 1 + \sum_{j=0}^{i} T_j - 1 - \sum_{j=0}^{i-1} T_j \\ &= T_i. \end{aligned}$$

And so $T_{i+1} = 2T_i = 2^{i+1}$.

Generating functions:

1. Multiply both sides of the equation by x^i.
2. Sum both sides over all i for which the equation is valid.
3. Choose a generating function $G(x)$. Usually $G(x) = \sum_{i=0}^{\infty} x^i g_i$.
3. Rewrite the equation in terms of the generating function $G(x)$.
4. Solve for $G(x)$.
5. The coefficient of x^i in $G(x)$ is g_i.

Example:

$$g_{i+1} = 2g_i + 1, \quad g_0 = 0.$$

Multiply and sum:

$$\sum_{i \geq 0} g_{i+1} x^i = \sum_{i \geq 0} 2g_i x^i + \sum_{i \geq 0} x^i.$$

We choose $G(x) = \sum_{i \geq 0} x^i g_i$. Rewrite in terms of $G(x)$:

$$\frac{G(x) - g_0}{x} = 2G(x) + \sum_{i \geq 0} x^i.$$

Simplify:

$$\frac{G(x)}{x} = 2G(x) + \frac{1}{1-x}.$$

Solve for $G(x)$:

$$G(x) = \frac{x}{(1-x)(1-2x)}.$$

Expand this using partial fractions:

$$\begin{aligned} G(x) &= x \left(\frac{2}{1-2x} - \frac{1}{1-x} \right) \\ &= x \left(2 \sum_{i \geq 0} 2^i x^i - \sum_{i \geq 0} x^i \right) \\ &= \sum_{i \geq 0} (2^{i+1} - 1) x^{i+1}. \end{aligned}$$

So $g_i = 2^i - 1$.

Theoretical Computer Science Cheat Sheet

$\pi \approx 3.14159$, $e \approx 2.71828$, $\gamma \approx 0.57721$, $\phi = \frac{1+\sqrt{5}}{2} \approx 1.61803$, $\hat{\phi} = \frac{1-\sqrt{5}}{2} \approx -.61803$

i	2^i	p_i
1	2	2
2	4	3
3	8	5
4	16	7
5	32	11
6	64	13
7	128	17
8	256	19
9	512	23
10	1,024	29
11	2,048	31
12	4,096	37
13	8,192	41
14	16,384	43
15	32,768	47
16	65,536	53
17	131,072	59
18	262,144	61
19	524,288	67
20	1,048,576	71
21	2,097,152	73
22	4,194,304	79
23	8,388,608	83
24	16,777,216	89
25	33,554,432	97
26	67,108,864	101
27	134,217,728	103
28	268,435,456	107
29	536,870,912	109
30	1,073,741,824	113
31	2,147,483,648	127
32	4,294,967,296	131

Pascal's Triangle

1

1 1

1 2 1

1 3 3 1

1 4 6 4 1

1 5 10 10 5 1

1 6 15 20 15 6 1

1 7 21 35 35 21 7 1

1 8 28 56 70 56 28 8 1

1 9 36 84 126 126 84 36 9 1

1 10 45 120 210 252 210 120 45 10 1

General

Bernoulli Numbers ($B_i = 0$, odd $i \neq 1$):

$$B_0 = 1,\ B_1 = -\tfrac{1}{2},\ B_2 = \tfrac{1}{6},\ B_4 = -\tfrac{1}{30},$$
$$B_6 = \tfrac{1}{42},\ B_8 = -\tfrac{1}{30},\ B_{10} = \tfrac{5}{66}.$$

Change of base, quadratic formula:

$$\log_b x = \frac{\log_a x}{\log_a b}, \qquad \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}.$$

Euler's number e:

$$e = 1 + \tfrac{1}{2} + \tfrac{1}{6} + \tfrac{1}{24} + \tfrac{1}{120} + \cdots$$
$$\lim_{n\to\infty}\left(1 + \frac{x}{n}\right)^n = e^x.$$
$$\left(1 + \tfrac{1}{n}\right)^n < e < \left(1 + \tfrac{1}{n}\right)^{n+1}.$$
$$\left(1 + \tfrac{1}{n}\right)^n = e - \frac{e}{2n} + \frac{11e}{24n^2} - O\left(\frac{1}{n^3}\right).$$

Harmonic numbers:

$$1,\ \tfrac{3}{2},\ \tfrac{11}{6},\ \tfrac{25}{12},\ \tfrac{137}{60},\ \tfrac{49}{20},\ \tfrac{363}{140},\ \tfrac{761}{280},\ \tfrac{7129}{2520}, \ldots$$
$$\ln n < H_n < \ln n + 1,$$
$$H_n = \ln n + \gamma + O\left(\frac{1}{n}\right).$$

Factorial, Stirling's approximation:

$$1,\ 2,\ 6,\ 24,\ 120,\ 720,\ 5040,\ 40320,\ 362880,\ \ldots$$
$$n! = \sqrt{2\pi n}\left(\frac{n}{e}\right)^n\left(1 + \Theta\left(\frac{1}{n}\right)\right).$$

Ackermann's function and inverse:

$$a(i,j) = \begin{cases} 2^j & i = 1 \\ a(i-1, 2) & j = 1 \\ a(i-1, a(i, j-1)) & i, j \geq 2 \end{cases}$$
$$\alpha(i) = \min\{j \mid a(j,j) \geq i\}.$$

Binomial distribution:

$$\Pr[X = k] = \binom{n}{k} p^k q^{n-k}, \qquad q = 1 - p,$$
$$\mathrm{E}[X] = \sum_{k=1}^{n} k \binom{n}{k} p^k q^{n-k} = np.$$

Poisson distribution:

$$\Pr[X = k] = \frac{e^{-\lambda}\lambda^k}{k!}, \quad \mathrm{E}[X] = \lambda.$$

Normal (Gaussian) distribution:

$$p(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-(x-\mu)^2/2\sigma^2}, \quad \mathrm{E}[X] = \mu.$$

The "coupon collector": We are given a random coupon each day, and there are n different types of coupons. The distribution of coupons is uniform. The expected number of days to pass before we to collect all n types is

$$nH_n.$$

Probability

Continuous distributions: If

$$\Pr[a < X < b] = \int_a^b p(x)\,dx,$$

then p is the probability density function of X. If

$$\Pr[X < a] = P(a),$$

then P is the distribution function of X. If P and p both exist then

$$P(a) = \int_{-\infty}^{a} p(x)\,dx.$$

Expectation: If X is discrete

$$\mathrm{E}[g(X)] = \sum_x g(x)\Pr[X = x].$$

If X continuous then

$$\mathrm{E}[g(X)] = \int_{-\infty}^{\infty} g(x)p(x)\,dx = \int_{-\infty}^{\infty} g(x)\,dP(x).$$

Variance, standard deviation:

$$\mathrm{VAR}[X] = \mathrm{E}[X^2] - \mathrm{E}[X]^2,$$
$$\sigma = \sqrt{\mathrm{VAR}[X]}.$$

For events A and B:

$$\Pr[A \vee B] = \Pr[A] + \Pr[B] - \Pr[A \wedge B]$$
$$\Pr[A \wedge B] = \Pr[A] \cdot \Pr[B],$$

iff A and B are independent.

$$\Pr[A|B] = \frac{\Pr[A \wedge B]}{\Pr[B]}$$

For random variables X and Y:

$$\mathrm{E}[X \cdot Y] = \mathrm{E}[X] \cdot \mathrm{E}[Y],$$

if X and Y are independent.

$$\mathrm{E}[X + Y] = \mathrm{E}[X] + \mathrm{E}[Y],$$
$$\mathrm{E}[cX] = c\,\mathrm{E}[X].$$

Bayes' theorem:

$$\Pr[A_i|B] = \frac{\Pr[B|A_i]\Pr[A_i]}{\sum_{j=1}^{n}\Pr[A_j]\Pr[B|A_j]}.$$

Inclusion-exclusion:

$$\Pr\left[\bigvee_{i=1}^{n} X_i\right] = \sum_{i=1}^{n}\Pr[X_i] + \sum_{k=2}^{n}(-1)^{k+1}\sum_{i_i<\cdots<i_k}\Pr\left[\bigwedge_{j=1}^{k} X_{i_j}\right].$$

Moment inequalities:

$$\Pr\left[|X| \geq \lambda\,\mathrm{E}[X]\right] \leq \frac{1}{\lambda},$$
$$\Pr\left[\left|X - \mathrm{E}[X]\right| \geq \lambda \cdot \sigma\right] \leq \frac{1}{\lambda^2}.$$

Geometric distribution:

$$\Pr[X = k] = pq^{k-1}, \qquad q = 1 - p,$$
$$\mathrm{E}[X] = \sum_{k=1}^{\infty} kpq^{k-1} = \frac{1}{p}.$$

Theoretical Computer Science Cheat Sheet

Trigonometry

Pythagorean theorem:

$$C^2 = A^2 + B^2.$$

Definitions:

$$\sin a = A/C, \quad \cos a = B/C,$$
$$\csc a = C/A, \quad \sec a = C/B,$$
$$\tan a = \frac{\sin a}{\cos a} = \frac{A}{B}, \quad \cot a = \frac{\cos a}{\sin a} = \frac{B}{A}.$$

Area, radius of inscribed circle:

$$\tfrac{1}{2}AB, \quad \frac{AB}{A+B+C}.$$

Identities:

$$\sin x = \frac{1}{\csc x}, \qquad \cos x = \frac{1}{\sec x},$$
$$\tan x = \frac{1}{\cot x}, \qquad \sin^2 x + \cos^2 x = 1,$$
$$1 + \tan^2 x = \sec^2 x, \qquad 1 + \cot^2 x = \csc^2 x,$$
$$\sin x = \cos\left(\tfrac{\pi}{2} - x\right), \qquad \sin x = \sin(\pi - x),$$
$$\cos x = -\cos(\pi - x), \qquad \tan x = \cot\left(\tfrac{\pi}{2} - x\right),$$
$$\cot x = -\cot(\pi - x), \qquad \csc x = \cot\tfrac{x}{2} - \cot x,$$
$$\sin(x \pm y) = \sin x \cos y \pm \cos x \sin y,$$
$$\cos(x \pm y) = \cos x \cos y \mp \sin x \sin y,$$
$$\tan(x \pm y) = \frac{\tan x \pm \tan y}{1 \mp \tan x \tan y},$$
$$\cot(x \pm y) = \frac{\cot x \cot y \mp 1}{\cot x \pm \cot y},$$
$$\sin 2x = 2 \sin x \cos x, \qquad \sin 2x = \frac{2\tan x}{1 + \tan^2 x},$$
$$\cos 2x = \cos^2 x - \sin^2 x, \qquad \cos 2x = 2\cos^2 x - 1,$$
$$\cos 2x = 1 - 2\sin^2 x, \qquad \cos 2x = \frac{1 - \tan^2 x}{1 + \tan^2 x},$$
$$\tan 2x = \frac{2\tan x}{1 - \tan^2 x}, \qquad \cot 2x = \frac{\cot^2 x - 1}{2\cot x},$$
$$\sin(x + y)\sin(x - y) = \sin^2 x - \sin^2 y,$$
$$\cos(x + y)\cos(x - y) = \cos^2 x - \sin^2 y.$$

Euler's equation:

$$e^{ix} = \cos x + i \sin x, \qquad e^{i\pi} = -1.$$

v2.02 ©1994 by Steve Seiden
sseiden@acm.org
http://www.csc.lsu.edu/~seiden

Matrices

Multiplication:

$$C = A \cdot B, \quad c_{i,j} = \sum_{k=1}^{n} a_{i,k} b_{k,j}.$$

Determinants: $\det A \neq 0$ iff A is non-singular.

$$\det A \cdot B = \det A \cdot \det B,$$
$$\det A = \sum_{\pi} \prod_{i=1}^{n} \operatorname{sign}(\pi) a_{i,\pi(i)}.$$

2×2 and 3×3 determinant:

$$\begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc,$$
$$\begin{vmatrix} a & b & c \\ d & e & f \\ g & h & i \end{vmatrix} = g\begin{vmatrix} b & c \\ e & f \end{vmatrix} - h\begin{vmatrix} a & c \\ d & f \end{vmatrix} + i\begin{vmatrix} a & b \\ d & e \end{vmatrix}$$
$$= \begin{array}{l} aei + bfg + cdh \\ \quad - ceg - fha - ibd. \end{array}$$

Permanents:

$$\operatorname{perm} A = \sum_{\pi} \prod_{i=1}^{n} a_{i,\pi(i)}.$$

Hyperbolic Functions

Definitions:

$$\sinh x = \frac{e^x - e^{-x}}{2}, \qquad \cosh x = \frac{e^x + e^{-x}}{2},$$
$$\tanh x = \frac{e^x - e^{-x}}{e^x + e^{-x}}, \qquad \operatorname{csch} x = \frac{1}{\sinh x},$$
$$\operatorname{sech} x = \frac{1}{\cosh x}, \qquad \coth x = \frac{1}{\tanh x}.$$

Identities:

$$\cosh^2 x - \sinh^2 x = 1, \qquad \tanh^2 x + \operatorname{sech}^2 x = 1,$$
$$\coth^2 x - \operatorname{csch}^2 x = 1, \qquad \sinh(-x) = -\sinh x,$$
$$\cosh(-x) = \cosh x, \qquad \tanh(-x) = -\tanh x,$$
$$\sinh(x + y) = \sinh x \cosh y + \cosh x \sinh y,$$
$$\cosh(x + y) = \cosh x \cosh y + \sinh x \sinh y,$$
$$\sinh 2x = 2 \sinh x \cosh x,$$
$$\cosh 2x = \cosh^2 x + \sinh^2 x,$$
$$\cosh x + \sinh x = e^x, \qquad \cosh x - \sinh x = e^{-x},$$
$$(\cosh x + \sinh x)^n = \cosh nx + \sinh nx, \quad n \in \mathbb{Z},$$
$$2\sinh^2 \tfrac{x}{2} = \cosh x - 1, \qquad 2\cosh^2 \tfrac{x}{2} = \cosh x + 1.$$

θ	$\sin\theta$	$\cos\theta$	$\tan\theta$
0	0	1	0
$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$
$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1
$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$
$\frac{\pi}{2}$	1	0	∞

. . . in mathematics you don't understand things, you just get used to them.
– J. von Neumann

More Trig.

Law of cosines:

$$c^2 = a^2 + b^2 - 2ab\cos C.$$

Area:

$$A = \tfrac{1}{2}hc,$$
$$= \tfrac{1}{2}ab\sin C,$$
$$= \frac{c^2 \sin A \sin B}{2\sin C}.$$

Heron's formula:

$$A = \sqrt{s \cdot s_a \cdot s_b \cdot s_c},$$
$$s = \tfrac{1}{2}(a + b + c),$$
$$s_a = s - a,$$
$$s_b = s - b,$$
$$s_c = s - c.$$

More identities:

$$\sin\tfrac{x}{2} = \sqrt{\frac{1 - \cos x}{2}},$$
$$\cos\tfrac{x}{2} = \sqrt{\frac{1 + \cos x}{2}},$$
$$\tan\tfrac{x}{2} = \sqrt{\frac{1 - \cos x}{1 + \cos x}},$$
$$= \frac{1 - \cos x}{\sin x},$$
$$= \frac{\sin x}{1 + \cos x},$$
$$\cot\tfrac{x}{2} = \sqrt{\frac{1 + \cos x}{1 - \cos x}},$$
$$= \frac{1 + \cos x}{\sin x},$$
$$= \frac{\sin x}{1 - \cos x},$$
$$\sin x = \frac{e^{ix} - e^{-ix}}{2i},$$
$$\cos x = \frac{e^{ix} + e^{-ix}}{2},$$
$$\tan x = -i\frac{e^{ix} - e^{-ix}}{e^{ix} + e^{-ix}},$$
$$= -i\frac{e^{2ix} - 1}{e^{2ix} + 1},$$
$$\sin x = \frac{\sinh ix}{i},$$
$$\cos x = \cosh ix,$$
$$\tan x = \frac{\tanh ix}{i}.$$

Theoretical Computer Science Cheat Sheet

Number Theory

The Chinese remainder theorem: There exists a number C such that:

$$C \equiv r_1 \bmod m_1$$
$$\vdots \quad \vdots \quad \vdots$$
$$C \equiv r_n \bmod m_n$$

if m_i and m_j are relatively prime for $i \neq j$.

Euler's function: $\phi(x)$ is the number of positive integers less than x relatively prime to x. If $\prod_{i=1}^{n} p_i^{e_i}$ is the prime factorization of x then

$$\phi(x) = \prod_{i=1}^{n} p_i^{e_i - 1}(p_i - 1).$$

Euler's theorem: If a and b are relatively prime then

$$1 \equiv a^{\phi(b)} \bmod b.$$

Fermat's theorem:

$$1 \equiv a^{p-1} \bmod p.$$

The Euclidean algorithm: if $a > b$ are integers then

$$\gcd(a, b) = \gcd(a \bmod b, b).$$

If $\prod_{i=1}^{n} p_i^{e_i}$ is the prime factorization of x then

$$S(x) = \sum_{d|x} d = \prod_{i=1}^{n} \frac{p_i^{e_i+1} - 1}{p_i - 1}.$$

Perfect Numbers: x is an even perfect number iff $x = 2^{n-1}(2^n - 1)$ and $2^n - 1$ is prime.

Wilson's theorem: n is a prime iff

$$(n-1)! \equiv -1 \bmod n.$$

Möbius inversion:

$$\mu(i) = \begin{cases} 1 & \text{if } i = 1. \\ 0 & \text{if } i \text{ is not square-free.} \\ (-1)^r & \text{if } i \text{ is the product of} \\ & r \text{ distinct primes.} \end{cases}$$

If

$$G(a) = \sum_{d|a} F(d),$$

then

$$F(a) = \sum_{d|a} \mu(d) G\left(\frac{a}{d}\right).$$

Prime numbers:

$$p_n = n \ln n + n \ln \ln n - n + n \frac{\ln \ln n}{\ln n} + O\left(\frac{n}{\ln n}\right),$$

$$\pi(n) = \frac{n}{\ln n} + \frac{n}{(\ln n)^2} + \frac{2!n}{(\ln n)^3} + O\left(\frac{n}{(\ln n)^4}\right).$$

Graph Theory

Definitions:

Loop	An edge connecting a vertex to itself.
Directed	Each edge has a direction.
Simple	Graph with no loops or multi-edges.
Walk	A sequence $v_0 e_1 v_1 \ldots e_\ell v_\ell$.
Trail	A walk with distinct edges.
Path	A trail with distinct vertices.
Connected	A graph where there exists a path between any two vertices.
Component	A maximal connected subgraph.
Tree	A connected acyclic graph.
Free tree	A tree with no root.
DAG	Directed acyclic graph.
Eulerian	Graph with a trail visiting each edge exactly once.
Hamiltonian	Graph with a cycle visiting each vertex exactly once.
Cut	A set of edges whose removal increases the number of components.
Cut-set	A minimal cut.
Cut edge	A size 1 cut.
k-Connected	A graph connected with the removal of any $k-1$ vertices.
k-Tough	$\forall S \subseteq V, S \neq \emptyset$ we have $k \cdot c(G - S) \leq \lvert S \rvert$.
k-Regular	A graph where all vertices have degree k.
k-Factor	A k-regular spanning subgraph.
Matching	A set of edges, no two of which are adjacent.
Clique	A set of vertices, all of which are adjacent.
Ind. set	A set of vertices, none of which are adjacent.
Vertex cover	A set of vertices which cover all edges.
Planar graph	A graph which can be embeded in the plane.
Plane graph	An embedding of a planar graph.

$$\sum_{v \in V} \deg(v) = 2m.$$

If G is planar then $n - m + f = 2$, so

$$f \leq 2n - 4, \quad m \leq 3n - 6.$$

Any planar graph has a vertex with degree ≤ 5.

Notation:

$E(G)$	Edge set
$V(G)$	Vertex set
$c(G)$	Number of components
$G[S]$	Induced subgraph
$\deg(v)$	Degree of v
$\Delta(G)$	Maximum degree
$\delta(G)$	Minimum degree
$\chi(G)$	Chromatic number
$\chi_E(G)$	Edge chromatic number
G^c	Complement graph
K_n	Complete graph
K_{n_1,n_2}	Complete bipartite graph
$\mathrm{r}(k, \ell)$	Ramsey number

Geometry

Projective coordinates: triples (x, y, z), not all x, y and z zero.

$$(x, y, z) = (cx, cy, cz) \quad \forall c \neq 0.$$

Cartesian	Projective
(x, y)	$(x, y, 1)$
$y = mx + b$	$(m, -1, b)$
$x = c$	$(1, 0, -c)$

Distance formula, L_p and L_∞ metric:

$$\sqrt{(x_1 - x_0)^2 + (y_1 - y_0)^2},$$
$$\left[|x_1 - x_0|^p + |y_1 - y_0|^p\right]^{1/p},$$
$$\lim_{p \to \infty} \left[|x_1 - x_0|^p + |y_1 - y_0|^p\right]^{1/p}.$$

Area of triangle (x_0, y_0), (x_1, y_1) and (x_2, y_2):

$$\tfrac{1}{2} \operatorname{abs} \begin{vmatrix} x_1 - x_0 & y_1 - y_0 \\ x_2 - x_0 & y_2 - y_0 \end{vmatrix}.$$

Angle formed by three points:

$$\cos\theta = \frac{(x_1, y_1) \cdot (x_2, y_2)}{\ell_1 \ell_2}.$$

Line through two points (x_0, y_0) and (x_1, y_1):

$$\begin{vmatrix} x & y & 1 \\ x_0 & y_0 & 1 \\ x_1 & y_1 & 1 \end{vmatrix} = 0.$$

Area of circle, volume of sphere:

$$A = \pi r^2, \qquad V = \tfrac{4}{3}\pi r^3.$$

If I have seen farther than others, it is because I have stood on the shoulders of giants.
– Issac Newton

Theoretical Computer Science Cheat Sheet

π

Wallis' identity:

$$\pi = 2 \cdot \frac{2 \cdot 2 \cdot 4 \cdot 4 \cdot 6 \cdot 6 \cdots}{1 \cdot 3 \cdot 3 \cdot 5 \cdot 5 \cdot 7 \cdots}$$

Brouncker's continued fraction expansion:

$$\tfrac{\pi}{4} = 1 + \cfrac{1^2}{2 + \cfrac{3^2}{2 + \cfrac{5^2}{2 + \cfrac{7^2}{2 + \cdots}}}}$$

Gregrory's series:

$$\tfrac{\pi}{4} = 1 - \tfrac{1}{3} + \tfrac{1}{5} - \tfrac{1}{7} + \tfrac{1}{9} - \cdots$$

Newton's series:

$$\tfrac{\pi}{6} = \frac{1}{2} + \frac{1}{2 \cdot 3 \cdot 2^3} + \frac{1 \cdot 3}{2 \cdot 4 \cdot 5 \cdot 2^5} + \cdots$$

Sharp's series:

$$\tfrac{\pi}{6} = \frac{1}{\sqrt{3}}\left(1 - \frac{1}{3^1 \cdot 3} + \frac{1}{3^2 \cdot 5} - \frac{1}{3^3 \cdot 7} + \cdots\right)$$

Euler's series:

$$\tfrac{\pi^2}{6} = \tfrac{1}{1^2} + \tfrac{1}{2^2} + \tfrac{1}{3^2} + \tfrac{1}{4^2} + \tfrac{1}{5^2} + \cdots$$
$$\tfrac{\pi^2}{8} = \tfrac{1}{1^2} + \tfrac{1}{3^2} + \tfrac{1}{5^2} + \tfrac{1}{7^2} + \tfrac{1}{9^2} + \cdots$$
$$\tfrac{\pi^2}{12} = \tfrac{1}{1^2} - \tfrac{1}{2^2} + \tfrac{1}{3^2} - \tfrac{1}{4^2} + \tfrac{1}{5^2} - \cdots$$

Partial Fractions

Let $N(x)$ and $D(x)$ be polynomial functions of x. We can break down $N(x)/D(x)$ using partial fraction expansion. First, if the degree of N is greater than or equal to the degree of D, divide N by D, obtaining

$$\frac{N(x)}{D(x)} = Q(x) + \frac{N'(x)}{D(x)},$$

where the degree of N' is less than that of D. Second, factor $D(x)$. Use the following rules: For a non-repeated factor:

$$\frac{N(x)}{(x-a)D(x)} = \frac{A}{x-a} + \frac{N'(x)}{D(x)},$$

where

$$A = \left[\frac{N(x)}{D(x)}\right]_{x=a}.$$

For a repeated factor:

$$\frac{N(x)}{(x-a)^m D(x)} = \sum_{k=0}^{m-1} \frac{A_k}{(x-a)^{m-k}} + \frac{N'(x)}{D(x)},$$

where

$$A_k = \frac{1}{k!}\left[\frac{d^k}{dx^k}\left(\frac{N(x)}{D(x)}\right)\right]_{x=a}.$$

The reasonable man adapts himself to the world; the unreasonable persists in trying to adapt the world to himself. Therefore all progress depends on the unreasonable.
– George Bernard Shaw

Calculus

Derivatives:

1. $\dfrac{d(cu)}{dx} = c\dfrac{du}{dx}$, **2.** $\dfrac{d(u+v)}{dx} = \dfrac{du}{dx} + \dfrac{dv}{dx}$, **3.** $\dfrac{d(uv)}{dx} = u\dfrac{dv}{dx} + v\dfrac{du}{dx}$,

4. $\dfrac{d(u^n)}{dx} = nu^{n-1}\dfrac{du}{dx}$, **5.** $\dfrac{d(u/v)}{dx} = \dfrac{v\left(\frac{du}{dx}\right) - u\left(\frac{dv}{dx}\right)}{v^2}$, **6.** $\dfrac{d(e^{cu})}{dx} = ce^{cu}\dfrac{du}{dx}$,

7. $\dfrac{d(c^u)}{dx} = (\ln c)c^u\dfrac{du}{dx}$, **8.** $\dfrac{d(\ln u)}{dx} = \dfrac{1}{u}\dfrac{du}{dx}$,

9. $\dfrac{d(\sin u)}{dx} = \cos u\dfrac{du}{dx}$, **10.** $\dfrac{d(\cos u)}{dx} = -\sin u\dfrac{du}{dx}$,

11. $\dfrac{d(\tan u)}{dx} = \sec^2 u\dfrac{du}{dx}$, **12.** $\dfrac{d(\cot u)}{dx} = \csc^2 u\dfrac{du}{dx}$,

13. $\dfrac{d(\sec u)}{dx} = \tan u \sec u\dfrac{du}{dx}$, **14.** $\dfrac{d(\csc u)}{dx} = -\cot u \csc u\dfrac{du}{dx}$,

15. $\dfrac{d(\arcsin u)}{dx} = \dfrac{1}{\sqrt{1-u^2}}\dfrac{du}{dx}$, **16.** $\dfrac{d(\arccos u)}{dx} = \dfrac{-1}{\sqrt{1-u^2}}\dfrac{du}{dx}$,

17. $\dfrac{d(\arctan u)}{dx} = \dfrac{1}{1+u^2}\dfrac{du}{dx}$, **18.** $\dfrac{d(\operatorname{arccot} u)}{dx} = \dfrac{-1}{1+u^2}\dfrac{du}{dx}$,

19. $\dfrac{d(\operatorname{arcsec} u)}{dx} = \dfrac{1}{u\sqrt{1-u^2}}\dfrac{du}{dx}$, **20.** $\dfrac{d(\operatorname{arccsc} u)}{dx} = \dfrac{-1}{u\sqrt{1-u^2}}\dfrac{du}{dx}$,

21. $\dfrac{d(\sinh u)}{dx} = \cosh u\dfrac{du}{dx}$, **22.** $\dfrac{d(\cosh u)}{dx} = \sinh u\dfrac{du}{dx}$,

23. $\dfrac{d(\tanh u)}{dx} = \operatorname{sech}^2 u\dfrac{du}{dx}$, **24.** $\dfrac{d(\coth u)}{dx} = -\operatorname{csch}^2 u\dfrac{du}{dx}$,

25. $\dfrac{d(\operatorname{sech} u)}{dx} = -\operatorname{sech} u \tanh u\dfrac{du}{dx}$, **26.** $\dfrac{d(\operatorname{csch} u)}{dx} = -\operatorname{csch} u \coth u\dfrac{du}{dx}$,

27. $\dfrac{d(\operatorname{arcsinh} u)}{dx} = \dfrac{1}{\sqrt{1+u^2}}\dfrac{du}{dx}$, **28.** $\dfrac{d(\operatorname{arccosh} u)}{dx} = \dfrac{1}{\sqrt{u^2-1}}\dfrac{du}{dx}$,

29. $\dfrac{d(\operatorname{arctanh} u)}{dx} = \dfrac{1}{1-u^2}\dfrac{du}{dx}$, **30.** $\dfrac{d(\operatorname{arccoth} u)}{dx} = \dfrac{1}{u^2-1}\dfrac{du}{dx}$,

31. $\dfrac{d(\operatorname{arcsech} u)}{dx} = \dfrac{-1}{u\sqrt{1-u^2}}\dfrac{du}{dx}$, **32.** $\dfrac{d(\operatorname{arccsch} u)}{dx} = \dfrac{-1}{|u|\sqrt{1+u^2}}\dfrac{du}{dx}$.

Integrals:

1. $\displaystyle\int cu\,dx = c\int u\,dx$, **2.** $\displaystyle\int (u+v)\,dx = \int u\,dx + \int v\,dx$,

3. $\displaystyle\int x^n\,dx = \frac{1}{n+1}x^{n+1}, \quad n \neq -1$, **4.** $\displaystyle\int \frac{1}{x}dx = \ln x$, **5.** $\displaystyle\int e^x\,dx = e^x$,

6. $\displaystyle\int \frac{dx}{1+x^2} = \arctan x$, **7.** $\displaystyle\int u\frac{dv}{dx}dx = uv - \int v\frac{du}{dx}dx$,

8. $\displaystyle\int \sin x\,dx = -\cos x$, **9.** $\displaystyle\int \cos x\,dx = \sin x$,

10. $\displaystyle\int \tan x\,dx = -\ln|\cos x|$, **11.** $\displaystyle\int \cot x\,dx = \ln|\cos x|$,

12. $\displaystyle\int \sec x\,dx = \ln|\sec x + \tan x|$, **13.** $\displaystyle\int \csc x\,dx = \ln|\csc x + \cot x|$,

14. $\displaystyle\int \arcsin\tfrac{x}{a}dx = \arcsin\tfrac{x}{a} + \sqrt{a^2 - x^2}, \quad a > 0$,

Theoretical Computer Science Cheat Sheet

Calculus Cont.

15. $\int \arccos \frac{x}{a} dx = \arccos \frac{x}{a} - \sqrt{a^2 - x^2}, \quad a > 0,$

16. $\int \arctan \frac{x}{a} dx = x \arctan \frac{x}{a} - \frac{a}{2} \ln(a^2 + x^2), \quad a > 0,$

17. $\int \sin^2(ax) dx = \frac{1}{2a}\big(ax - \sin(ax)\cos(ax)\big),$

18. $\int \cos^2(ax) dx = \frac{1}{2a}\big(ax + \sin(ax)\cos(ax)\big),$

19. $\int \sec^2 x \, dx = \tan x,$

20. $\int \csc^2 x \, dx = -\cot x,$

21. $\int \sin^n x \, dx = -\frac{\sin^{n-1} x \cos x}{n} + \frac{n-1}{n} \int \sin^{n-2} x \, dx,$

22. $\int \cos^n x \, dx = \frac{\cos^{n-1} x \sin x}{n} + \frac{n-1}{n} \int \cos^{n-2} x \, dx,$

23. $\int \tan^n x \, dx = \frac{\tan^{n-1} x}{n-1} - \int \tan^{n-2} x \, dx, \quad n \neq 1,$

24. $\int \cot^n x \, dx = -\frac{\cot^{n-1} x}{n-1} - \int \cot^{n-2} x \, dx, \quad n \neq 1,$

25. $\int \sec^n x \, dx = \frac{\tan x \sec^{n-1} x}{n-1} + \frac{n-2}{n-1} \int \sec^{n-2} x \, dx, \quad n \neq 1,$

26. $\int \csc^n x \, dx = -\frac{\cot x \csc^{n-1} x}{n-1} + \frac{n-2}{n-1} \int \csc^{n-2} x \, dx, \quad n \neq 1,$

27. $\int \sinh x \, dx = \cosh x,$

28. $\int \cosh x \, dx = \sinh x,$

29. $\int \tanh x \, dx = \ln|\cosh x|,$

30. $\int \coth x \, dx = \ln|\sinh x|,$

31. $\int \operatorname{sech} x \, dx = \arctan \sinh x,$

32. $\int \operatorname{csch} x \, dx = \ln\left|\tanh \frac{x}{2}\right|,$

33. $\int \sinh^2 x \, dx = \frac{1}{4}\sinh(2x) - \frac{1}{2}x,$

34. $\int \cosh^2 x \, dx = \frac{1}{4}\sinh(2x) + \frac{1}{2}x,$

35. $\int \operatorname{sech}^2 x \, dx = \tanh x,$

36. $\int \operatorname{arcsinh} \frac{x}{a} dx = x \operatorname{arcsinh} \frac{x}{a} - \sqrt{x^2 + a^2}, \quad a > 0,$

37. $\int \operatorname{arctanh} \frac{x}{a} dx = x \operatorname{arctanh} \frac{x}{a} + \frac{a}{2} \ln|a^2 - x^2|,$

38. $\int \operatorname{arccosh} \frac{x}{a} dx = \begin{cases} x \operatorname{arccosh} \dfrac{x}{a} - \sqrt{x^2 + a^2}, & \text{if } \operatorname{arccosh} \frac{x}{a} > 0 \text{ and } a > 0, \\ x \operatorname{arccosh} \dfrac{x}{a} + \sqrt{x^2 + a^2}, & \text{if } \operatorname{arccosh} \frac{x}{a} < 0 \text{ and } a > 0, \end{cases}$

39. $\int \frac{dx}{\sqrt{a^2 + x^2}} = \ln\left(x + \sqrt{a^2 + x^2}\right), \quad a > 0,$

40. $\int \frac{dx}{a^2 + x^2} = \frac{1}{a} \arctan \frac{x}{a}, \quad a > 0,$

41. $\int \sqrt{a^2 - x^2} \, dx = \frac{x}{2}\sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a}, \quad a > 0,$

42. $\int (a^2 - x^2)^{3/2} dx = \frac{x}{8}(5a^2 - 2x^2)\sqrt{a^2 - x^2} + \frac{3a^4}{8} \arcsin \frac{x}{a}, \quad a > 0,$

43. $\int \frac{dx}{\sqrt{a^2 - x^2}} = \arcsin \frac{x}{a}, \quad a > 0,$

44. $\int \frac{dx}{a^2 - x^2} = \frac{1}{2a} \ln\left|\frac{a + x}{a - x}\right|,$

45. $\int \frac{dx}{(a^2 - x^2)^{3/2}} = \frac{x}{a^2\sqrt{a^2 - x^2}},$

46. $\int \sqrt{a^2 \pm x^2} \, dx = \frac{x}{2}\sqrt{a^2 \pm x^2} \pm \frac{a^2}{2} \ln\left|x + \sqrt{a^2 \pm x^2}\right|,$

47. $\int \frac{dx}{\sqrt{x^2 - a^2}} = \ln\left|x + \sqrt{x^2 - a^2}\right|, \quad a > 0,$

48. $\int \frac{dx}{ax^2 + bx} = \frac{1}{a} \ln\left|\frac{x}{a + bx}\right|,$

49. $\int x\sqrt{a + bx} \, dx = \frac{2(3bx - 2a)(a + bx)^{3/2}}{15b^2},$

50. $\int \frac{\sqrt{a + bx}}{x} dx = 2\sqrt{a + bx} + a \int \frac{1}{x\sqrt{a + bx}} dx,$

51. $\int \frac{x}{\sqrt{a + bx}} dx = \frac{1}{\sqrt{2}} \ln\left|\frac{\sqrt{a + bx} - \sqrt{a}}{\sqrt{a + bx} + \sqrt{a}}\right|, \quad a > 0,$

52. $\int \frac{\sqrt{a^2 - x^2}}{x} dx = \sqrt{a^2 - x^2} - a \ln\left|\frac{a + \sqrt{a^2 - x^2}}{x}\right|,$

53. $\int x\sqrt{a^2 - x^2} \, dx = -\frac{1}{3}(a^2 - x^2)^{3/2},$

54. $\int x^2\sqrt{a^2 - x^2} \, dx = \frac{x}{8}(2x^2 - a^2)\sqrt{a^2 - x^2} + \frac{a^4}{8} \arcsin \frac{x}{a}, \quad a > 0,$

55. $\int \frac{dx}{\sqrt{a^2 - x^2}} = -\frac{1}{a} \ln\left|\frac{a + \sqrt{a^2 - x^2}}{x}\right|,$

56. $\int \frac{x \, dx}{\sqrt{a^2 - x^2}} = -\sqrt{a^2 - x^2},$

57. $\int \frac{x^2 \, dx}{\sqrt{a^2 - x^2}} = -\frac{x}{2}\sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a}, \quad a > 0,$

58. $\int \frac{\sqrt{a^2 + x^2}}{x} dx = \sqrt{a^2 + x^2} - a \ln\left|\frac{a + \sqrt{a^2 + x^2}}{x}\right|,$

59. $\int \frac{\sqrt{x^2 - a^2}}{x} dx = \sqrt{x^2 - a^2} - a \arccos \frac{a}{|x|}, \quad a > 0,$

60. $\int x\sqrt{x^2 \pm a^2} \, dx = \frac{1}{3}(x^2 \pm a^2)^{3/2},$

61. $\int \frac{dx}{x\sqrt{x^2 + a^2}} = \frac{1}{a} \ln\left|\frac{x}{a + \sqrt{a^2 + x^2}}\right|,$

Theoretical Computer Science Cheat Sheet

Calculus Cont.

62. $\displaystyle\int \frac{dx}{x\sqrt{x^2-a^2}} = \frac{1}{a}\arccos\frac{a}{|x|}, \quad a>0,$

63. $\displaystyle\int \frac{dx}{x^2\sqrt{x^2\pm a^2}} = \mp\frac{\sqrt{x^2\pm a^2}}{a^2x},$

64. $\displaystyle\int \frac{x\,dx}{\sqrt{x^2\pm a^2}} = \sqrt{x^2\pm a^2},$

65. $\displaystyle\int \frac{\sqrt{x^2\pm a^2}}{x^4}\,dx = \mp\frac{(x^2+a^2)^{3/2}}{3a^2x^3},$

66. $$\int \frac{dx}{ax^2+bx+c} = \begin{cases} \dfrac{1}{\sqrt{b^2-4ac}}\ln\left|\dfrac{2ax+b-\sqrt{b^2-4ac}}{2ax+b+\sqrt{b^2-4ac}}\right|, & \text{if } b^2>4ac, \\ \dfrac{2}{\sqrt{4ac-b^2}}\arctan\dfrac{2ax+b}{\sqrt{4ac-b^2}}, & \text{if } b^2<4ac, \end{cases}$$

67. $$\int \frac{dx}{\sqrt{ax^2+bx+c}} = \begin{cases} \dfrac{1}{\sqrt{a}}\ln\left|2ax+b+2\sqrt{a}\sqrt{ax^2+bx+c}\right|, & \text{if } a>0, \\ \dfrac{1}{\sqrt{-a}}\arcsin\dfrac{-2ax-b}{\sqrt{b^2-4ac}}, & \text{if } a<0, \end{cases}$$

68. $\displaystyle\int \sqrt{ax^2+bx+c}\,dx = \frac{2ax+b}{4a}\sqrt{ax^2+bx+c} + \frac{4ax-b^2}{8a}\int\frac{dx}{\sqrt{ax^2+bx+c}},$

69. $\displaystyle\int \frac{x\,dx}{\sqrt{ax^2+bx+c}} = \frac{\sqrt{ax^2+bx+c}}{a} - \frac{b}{2a}\int\frac{dx}{\sqrt{ax^2+bx+c}},$

70. $$\int \frac{dx}{x\sqrt{ax^2+bx+c}} = \begin{cases} \dfrac{-1}{\sqrt{c}}\ln\left|\dfrac{2\sqrt{c}\sqrt{ax^2+bx+c}+bx+2c}{x}\right|, & \text{if } c>0, \\ \dfrac{1}{\sqrt{-c}}\arcsin\dfrac{bx+2c}{|x|\sqrt{b^2-4ac}}, & \text{if } c<0, \end{cases}$$

71. $\displaystyle\int x^3\sqrt{x^2+a^2}\,dx = (\tfrac{1}{3}x^2 - \tfrac{2}{15}a^2)(x^2+a^2)^{3/2},$

72. $\displaystyle\int x^n\sin(ax)\,dx = -\tfrac{1}{a}x^n\cos(ax) + \tfrac{n}{a}\int x^{n-1}\cos(ax)\,dx,$

73. $\displaystyle\int x^n\cos(ax)\,dx = \tfrac{1}{a}x^n\sin(ax) - \tfrac{n}{a}\int x^{n-1}\sin(ax)\,dx,$

74. $\displaystyle\int x^n e^{ax}\,dx = \frac{x^n e^{ax}}{a} - \tfrac{n}{a}\int x^{n-1}e^{ax}\,dx,$

75. $\displaystyle\int x^n\ln(ax)\,dx = x^{n+1}\left(\frac{\ln(ax)}{n+1} - \frac{1}{(n+1)^2}\right),$

76. $\displaystyle\int x^n(\ln ax)^m\,dx = \frac{x^{n+1}}{n+1}(\ln ax)^m - \frac{m}{n+1}\int x^n(\ln ax)^{m-1}\,dx.$

$$\begin{aligned}
x^1 &= x^{\underline{1}} &&= x^{\overline{1}} \\
x^2 &= x^{\underline{2}} + x^{\underline{1}} &&= x^{\overline{2}} - x^{\overline{1}} \\
x^3 &= x^{\underline{3}} + 3x^{\underline{2}} + x^{\underline{1}} &&= x^{\overline{3}} - 3x^{\overline{2}} + x^{\overline{1}} \\
x^4 &= x^{\underline{4}} + 6x^{\underline{3}} + 7x^{\underline{2}} + x^{\underline{1}} &&= x^{\overline{4}} - 6x^{\overline{3}} + 7x^{\overline{2}} - x^{\overline{1}} \\
x^5 &= x^{\underline{5}} + 15x^{\underline{4}} + 25x^{\underline{3}} + 10x^{\underline{2}} + x^{\underline{1}} &&= x^{\underline{5}} - 15x^{\overline{4}} + 25x^{\overline{3}} - 10x^{\overline{2}} + x^{\overline{1}}
\end{aligned}$$

$$\begin{aligned}
x^{\overline{1}} &= x^1 & x^{\underline{1}} &= x^1 \\
x^{\overline{2}} &= x^2 + x^1 & x^{\underline{2}} &= x^2 - x^1 \\
x^{\overline{3}} &= x^3 + 3x^2 + 2x^1 & x^{\underline{3}} &= x^3 - 3x^2 + 2x^1 \\
x^{\overline{4}} &= x^4 + 6x^3 + 11x^2 + 6x^1 & x^{\underline{4}} &= x^4 - 6x^3 + 11x^2 - 6x^1 \\
x^{\overline{5}} &= x^5 + 10x^4 + 35x^3 + 50x^2 + 24x^1 & x^{\underline{5}} &= x^5 - 10x^4 + 35x^3 - 50x^2 + 24x^1
\end{aligned}$$

Finite Calculus

Difference, shift operators:

$$\Delta f(x) = f(x+1) - f(x),$$
$$\mathrm{E}\, f(x) = f(x+1).$$

Fundamental Theorem:

$$f(x) = \Delta F(x) \Leftrightarrow \sum f(x)\delta x = F(x) + C.$$
$$\sum_a^b f(x)\delta x = \sum_{i=a}^{b-1} f(i).$$

Differences:

$\Delta(cu) = c\Delta u, \qquad \Delta(u+v) = \Delta u + \Delta v,$

$\Delta(uv) = u\Delta v + \mathrm{E}\, v\Delta u,$

$\Delta(x^{\underline{n}}) = nx^{\underline{n-1}},$

$\Delta(H_x) = x^{\underline{-1}}, \qquad \Delta(2^x) = 2^x,$

$\Delta(c^x) = (c-1)c^x, \qquad \Delta\binom{x}{m} = \binom{x}{m-1}.$

Sums:

$\sum cu\,\delta x = c\sum u\,\delta x,$

$\sum(u+v)\,\delta x = \sum u\,\delta x + \sum v\,\delta x,$

$\sum u\Delta v\,\delta x = uv - \sum \mathrm{E}\, v\Delta u\,\delta x,$

$\sum x^{\underline{n}}\,\delta x = \frac{x^{\underline{n+1}}}{m+1}, \qquad \sum x^{\underline{-1}}\,\delta x = H_x,$

$\sum c^x\,\delta x = \frac{c^x}{c-1}, \qquad \sum\binom{x}{m}\,\delta x = \binom{x}{m+1}.$

Falling Factorial Powers:

$$x^{\underline{n}} = x(x-1)\cdots(x-n+1), \quad n>0,$$
$$x^{\underline{0}} = 1,$$
$$x^{\underline{n}} = \frac{1}{(x+1)\cdots(x+|n|)}, \quad n<0,$$
$$x^{\underline{n+m}} = x^{\underline{m}}(x-m)^{\underline{n}}.$$

Rising Factorial Powers:

$$x^{\overline{n}} = x(x+1)\cdots(x+n-1), \quad n>0,$$
$$x^{\overline{0}} = 1,$$
$$x^{\overline{n}} = \frac{1}{(x-1)\cdots(x-|n|)}, \quad n<0,$$
$$x^{\overline{n+m}} = x^{\overline{m}}(x+m)^{\overline{n}}.$$

Conversion:

$$\begin{aligned}
x^{\underline{n}} &= (-1)^n(-x)^{\overline{n}} = (x-n+1)^{\overline{n}} \\
&= 1/(x+1)^{\overline{-n}}, \\
x^{\overline{n}} &= (-1)^n(-x)^{\underline{n}} = (x+n-1)^{\underline{n}} \\
&= 1/(x-1)^{\underline{-n}},
\end{aligned}$$

$$x^n = \sum_{k=1}^n \left\{{n \atop k}\right\} x^{\underline{k}} = \sum_{k=1}^n \left\{{n \atop k}\right\}(-1)^{n-k}x^{\overline{k}},$$

$$x^{\underline{n}} = \sum_{k=1}^n \left[{n \atop k}\right](-1)^{n-k}x^k,$$

$$x^{\overline{n}} = \sum_{k=1}^n \left[{n \atop k}\right]x^k.$$

Theoretical Computer Science Cheat Sheet

Series

Taylor's series:

$$f(x) = f(a) + (x-a)f'(a) + \frac{(x-a)^2}{2}f''(a) + \cdots = \sum_{i=0}^{\infty} \frac{(x-a)^i}{i!} f^{(i)}(a).$$

Expansions:

$$\frac{1}{1-x} = 1 + x + x^2 + x^3 + x^4 + \cdots = \sum_{i=0}^{\infty} x^i,$$

$$\frac{1}{1-cx} = 1 + cx + c^2x^2 + c^3x^3 + \cdots = \sum_{i=0}^{\infty} c^i x^i,$$

$$\frac{1}{1-x^n} = 1 + x^n + x^{2n} + x^{3n} + \cdots = \sum_{i=0}^{\infty} x^{ni},$$

$$\frac{x}{(1-x)^2} = x + 2x^2 + 3x^3 + 4x^4 + \cdots = \sum_{i=0}^{\infty} ix^i,$$

$$x^k \frac{d^n}{dx^n}\left(\frac{1}{1-x}\right) = x + 2^n x^2 + 3^n x^3 + 4^n x^4 + \cdots = \sum_{i=0}^{\infty} i^n x^i,$$

$$e^x = 1 + x + \tfrac{1}{2}x^2 + \tfrac{1}{6}x^3 + \cdots = \sum_{i=0}^{\infty} \frac{x^i}{i!},$$

$$\ln(1+x) = x - \tfrac{1}{2}x^2 + \tfrac{1}{3}x^3 - \tfrac{1}{4}x^4 - \cdots = \sum_{i=1}^{\infty} (-1)^{i+1}\frac{x^i}{i},$$

$$\ln\frac{1}{1-x} = x + \tfrac{1}{2}x^2 + \tfrac{1}{3}x^3 + \tfrac{1}{4}x^4 + \cdots = \sum_{i=1}^{\infty} \frac{x^i}{i},$$

$$\sin x = x - \tfrac{1}{3!}x^3 + \tfrac{1}{5!}x^5 - \tfrac{1}{7!}x^7 + \cdots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{(2i+1)!},$$

$$\cos x = 1 - \tfrac{1}{2!}x^2 + \tfrac{1}{4!}x^4 - \tfrac{1}{6!}x^6 + \cdots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i}}{(2i)!},$$

$$\tan^{-1} x = x - \tfrac{1}{3}x^3 + \tfrac{1}{5}x^5 - \tfrac{1}{7}x^7 + \cdots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{(2i+1)},$$

$$(1+x)^n = 1 + nx + \tfrac{n(n-1)}{2}x^2 + \cdots = \sum_{i=0}^{\infty} \binom{n}{i} x^i,$$

$$\frac{1}{(1-x)^{n+1}} = 1 + (n+1)x + \tbinom{n+2}{2}x^2 + \cdots = \sum_{i=0}^{\infty} \binom{i+n}{i} x^i,$$

$$\frac{x}{e^x - 1} = 1 - \tfrac{1}{2}x + \tfrac{1}{12}x^2 - \tfrac{1}{720}x^4 + \cdots = \sum_{i=0}^{\infty} \frac{B_i x^i}{i!},$$

$$\frac{1}{2x}(1 - \sqrt{1-4x}) = 1 + x + 2x^2 + 5x^3 + \cdots = \sum_{i=0}^{\infty} \frac{1}{i+1}\binom{2i}{i} x^i,$$

$$\frac{1}{\sqrt{1-4x}} = 1 + x + 2x^2 + 6x^3 + \cdots = \sum_{i=0}^{\infty} \binom{2i}{i} x^i,$$

$$\frac{1}{\sqrt{1-4x}}\left(\frac{1-\sqrt{1-4x}}{2x}\right)^n = 1 + (2+n)x + \tbinom{4+n}{2}x^2 + \cdots = \sum_{i=0}^{\infty} \binom{2i+n}{i} x^i,$$

$$\frac{1}{1-x}\ln\frac{1}{1-x} = x + \tfrac{3}{2}x^2 + \tfrac{11}{6}x^3 + \tfrac{25}{12}x^4 + \cdots = \sum_{i=1}^{\infty} H_i x^i,$$

$$\frac{1}{2}\left(\ln\frac{1}{1-x}\right)^2 = \tfrac{1}{2}x^2 + \tfrac{3}{4}x^3 + \tfrac{11}{24}x^4 + \cdots = \sum_{i=2}^{\infty} \frac{H_{i-1}x^i}{i},$$

$$\frac{x}{1-x-x^2} = x + x^2 + 2x^3 + 3x^4 + \cdots = \sum_{i=0}^{\infty} F_i x^i,$$

$$\frac{F_n x}{1-(F_{n-1}+F_{n+1})x-(-1)^n x^2} = F_n x + F_{2n}x^2 + F_{3n}x^3 + \cdots = \sum_{i=0}^{\infty} F_{ni} x^i.$$

Ordinary power series:

$$A(x) = \sum_{i=0}^{\infty} a_i x^i.$$

Exponential power series:

$$A(x) = \sum_{i=0}^{\infty} a_i \frac{x^i}{i!}.$$

Dirichlet power series:

$$A(x) = \sum_{i=1}^{\infty} \frac{a_i}{i^x}.$$

Binomial theorem:

$$(x+y)^n = \sum_{k=0}^{n} \binom{n}{k} x^{n-k} y^k.$$

Difference of like powers:

$$x^n - y^n = (x-y)\sum_{k=0}^{n-1} x^{n-1-k} y^k.$$

For ordinary power series:

$$\alpha A(x) + \beta B(x) = \sum_{i=0}^{\infty} (\alpha a_i + \beta b_i) x^i,$$

$$x^k A(x) = \sum_{i=k}^{\infty} a_{i-k} x^i,$$

$$\frac{A(x) - \sum_{i=0}^{k-1} a_i x^i}{x^k} = \sum_{i=0}^{\infty} a_{i+k} x^i,$$

$$A(cx) = \sum_{i=0}^{\infty} c^i a_i x^i,$$

$$A'(x) = \sum_{i=0}^{\infty} (i+1) a_{i+1} x^i,$$

$$xA'(x) = \sum_{i=1}^{\infty} i a_i x^i,$$

$$\int A(x)\,dx = \sum_{i=1}^{\infty} \frac{a_{i-1}}{i} x^i,$$

$$\frac{A(x)+A(-x)}{2} = \sum_{i=0}^{\infty} a_{2i} x^{2i},$$

$$\frac{A(x)-A(-x)}{2} = \sum_{i=0}^{\infty} a_{2i+1} x^{2i+1}.$$

Summation: If $b_i = \sum_{j=0}^{i} a_i$ then

$$B(x) = \frac{1}{1-x}A(x).$$

Convolution:

$$A(x)B(x) = \sum_{i=0}^{\infty}\left(\sum_{j=0}^{i} a_j b_{i-j}\right) x^i.$$

God made the natural numbers;
all the rest is the work of man.
– Leopold Kronecker

Theoretical Computer Science Cheat Sheet

Series

Expansions:

$$\frac{1}{(1-x)^{n+1}}\ln\frac{1}{1-x} = \sum_{i=0}^{\infty}(H_{n+i}-H_n)\binom{n+i}{i}x^i,$$

$$\left(\frac{1}{x}\right)^{\overline{-n}} = \sum_{i=0}^{\infty}\left\{{i \atop n}\right\}x^i,$$

$$x^{\overline{n}} = \sum_{i=0}^{\infty}\left[{n \atop i}\right]x^i,$$

$$(e^x-1)^n = \sum_{i=0}^{\infty}\left\{{i \atop n}\right\}\frac{n!x^i}{i!},$$

$$\left(\ln\frac{1}{1-x}\right)^n = \sum_{i=0}^{\infty}\left[{i \atop n}\right]\frac{n!x^i}{i!},$$

$$x\cot x = \sum_{i=0}^{\infty}\frac{(-4)^iB_{2i}x^{2i}}{(2i)!},$$

$$\tan x = \sum_{i=1}^{\infty}(-1)^{i-1}\frac{2^{2i}(2^{2i}-1)B_{2i}x^{2i-1}}{(2i)!},$$

$$\zeta(x) = \sum_{i=1}^{\infty}\frac{1}{i^x},$$

$$\frac{1}{\zeta(x)} = \sum_{i=1}^{\infty}\frac{\mu(i)}{i^x},$$

$$\frac{\zeta(x-1)}{\zeta(x)} = \sum_{i=1}^{\infty}\frac{\phi(i)}{i^x},$$

$$\zeta(x) = \prod_p\frac{1}{1-p^{-x}},$$

$$\zeta^2(x) = \sum_{i=1}^{\infty}\frac{d(i)}{x^i} \quad \text{where } d(n)=\textstyle\sum_{d|n}1,$$

$$\zeta(x)\zeta(x-1) = \sum_{i=1}^{\infty}\frac{S(i)}{x^i} \quad \text{where } S(n)=\textstyle\sum_{d|n}d,$$

$$\zeta(2n) = \frac{2^{2n-1}|B_{2n}|}{(2n)!}\pi^{2n}, \quad n\in\mathbb{N},$$

$$\frac{x}{\sin x} = \sum_{i=0}^{\infty}(-1)^{i-1}\frac{(4^i-2)B_{2i}x^{2i}}{(2i)!},$$

$$\left(\frac{1-\sqrt{1-4x}}{2x}\right)^n = \sum_{i=0}^{\infty}\frac{n(2i+n-1)!}{i!(n+i)!}x^i,$$

$$e^x\sin x = \sum_{i=1}^{\infty}\frac{2^{i/2}\sin\frac{i\pi}{4}}{i!}x^i,$$

$$\sqrt{\frac{1-\sqrt{1-x}}{x}} = \sum_{i=0}^{\infty}\frac{(4i)!}{16^i\sqrt{2}(2i)!(2i+1)!}x^i,$$

$$\left(\frac{\arcsin x}{x}\right)^2 = \sum_{i=0}^{\infty}\frac{4^ii!^2}{(i+1)(2i+1)!}x^{2i}.$$

Escher's Knot

Stieltjes Integration

If G is continuous in the interval $[a,b]$ and F is nondecreasing then

$$\int_a^b G(x)\,dF(x)$$

exists. If $a\le b\le c$ then

$$\int_a^c G(x)\,dF(x) = \int_a^b G(x)\,dF(x) + \int_b^c G(x)\,dF(x).$$

If the integrals involved exist

$$\int_a^b \big(G(x)+H(x)\big)\,dF(x) = \int_a^b G(x)\,dF(x) + \int_a^b H(x)\,dF(x),$$

$$\int_a^b G(x)\,d\big(F(x)+H(x)\big) = \int_a^b G(x)\,dF(x) + \int_a^b G(x)\,dH(x),$$

$$\int_a^b c\cdot G(x)\,dF(x) = \int_a^b G(x)\,d\big(c\cdot F(x)\big) = c\int_a^b G(x)\,dF(x),$$

$$\int_a^b G(x)\,dF(x) = G(b)F(b)-G(a)F(a)-\int_a^b F(x)\,dG(x).$$

If the integrals involved exist, and F possesses a derivative F' at every point in $[a,b]$ then

$$\int_a^b G(x)\,dF(x) = \int_a^b G(x)F'(x)\,dx.$$

Cramer's Rule

If we have equations:

$$\begin{aligned} a_{1,1}x_1 + a_{1,2}x_2 + \cdots + a_{1,n}x_n &= b_1\\ a_{2,1}x_1 + a_{2,2}x_2 + \cdots + a_{2,n}x_n &= b_2\\ \vdots \qquad\qquad \vdots \qquad\qquad &\vdots\\ a_{n,1}x_1 + a_{n,2}x_2 + \cdots + a_{n,n}x_n &= b_n \end{aligned}$$

Let $A=(a_{i,j})$ and B be the column matrix (b_i). Then there is a unique solution iff $\det A\neq 0$. Let A_i be A with column i replaced by B. Then

$$x_i = \frac{\det A_i}{\det A}.$$

Improvement makes strait roads, but the crooked roads without Improvement, are roads of Genius.
– William Blake (The Marriage of Heaven and Hell)

00	47	18	76	29	93	85	34	61	52
86	11	57	28	70	39	94	45	02	63
95	80	22	67	38	71	49	56	13	04
59	96	81	33	07	48	72	60	24	15
73	69	90	82	44	17	58	01	35	26
68	74	09	91	83	55	27	12	46	30
37	08	75	19	92	84	66	23	50	41
14	25	36	40	51	62	03	77	88	99
21	32	43	54	65	06	10	89	97	78
42	53	64	05	16	20	31	98	79	87

The Fibonacci number system: Every integer n has a unique representation

$$n = F_{k_1}+F_{k_2}+\cdots+F_{k_m},$$

where $k_i\ge k_{i+1}+2$ for all i, $1\le i<m$ and $k_m\ge 2$.

Fibonacci Numbers

$1,1,2,3,5,8,13,21,34,55,89,\ldots$

Definitions:

$$F_i = F_{i-1}+F_{i-2}, \quad F_0=F_1=1,$$

$$F_{-i} = (-1)^{i-1}F_i,$$

$$F_i = \frac{1}{\sqrt{5}}\left(\phi^i-\hat{\phi}^i\right),$$

Cassini's identity: for $i>0$:

$$F_{i+1}F_{i-1}-F_i^2 = (-1)^i.$$

Additive rule:

$$F_{n+k} = F_kF_{n+1}+F_{k-1}F_n,$$

$$F_{2n} = F_nF_{n+1}+F_{n-1}F_n.$$

Calculation by matrices:

$$\begin{pmatrix} F_{n-2} & F_{n-1}\\ F_{n-1} & F_n\end{pmatrix} = \begin{pmatrix} 0 & 1\\ 1 & 1\end{pmatrix}^n.$$

Visual Studio Code

Keyboard shortcuts for Windows

General

Ctrl+Shift+P, F1	Show Command Palette
Ctrl+P	Quick Open, Go to File...
Ctrl+Shift+N	New window/instance
Ctrl+Shift+W	Close window/instance
Ctrl+,	User Settings
Ctrl+K Ctrl+S	Keyboard Shortcuts

Basic editing

Ctrl+X	Cut line (empty selection)
Ctrl+C	Copy line (empty selection)
Alt+ ↑ / ↓	Move line up/down
Shift+Alt + ↓ / ↑	Copy line up/down
Ctrl+Shift+K	Delete line
Ctrl+Enter	Insert line below
Ctrl+Shift+Enter	Insert line above
Ctrl+Shift+\	Jump to matching bracket
Ctrl+] / [	Indent/outdent line
Home / End	Go to beginning/end of line
Ctrl+Home	Go to beginning of file
Ctrl+End	Go to end of file
Ctrl+↑ / ↓	Scroll line up/down
Alt+PgUp / PgDn	Scroll page up/down
Ctrl+Shift+[	Fold (collapse) region
Ctrl+Shift+]	Unfold (uncollapse) region
Ctrl+K Ctrl+[	Fold (collapse) all subregions
Ctrl+K Ctrl+]	Unfold (uncollapse) all subregions
Ctrl+K Ctrl+0	Fold (collapse) all regions
Ctrl+K Ctrl+J	Unfold (uncollapse) all regions
Ctrl+K Ctrl+C	Add line comment
Ctrl+K Ctrl+U	Remove line comment
Ctrl+/	Toggle line comment
Shift+Alt+A	Toggle block comment
Alt+Z	Toggle word wrap

Navigation

Ctrl+T	Show all Symbols
Ctrl+G	Go to Line...
Ctrl+P	Go to File...
Ctrl+Shift+O	Go to Symbol...
Ctrl+Shift+M	Show Problems panel
F8	Go to next error or warning
Shift+F8	Go to previous error or warning
Ctrl+Shift+Tab	Navigate editor group history
Alt+ ← / →	Go back / forward
Ctrl+M	Toggle Tab moves focus

Search and replace

Ctrl+F	Find
Ctrl+H	Replace
F3 / Shift+F3	Find next/previous
Alt+Enter	Select all occurences of Find match
Ctrl+D	Add selection to next Find match
Ctrl+K Ctrl+D	Move last selection to next Find match
Alt+C / R / W	Toggle case-sensitive / regex / whole word

Multi-cursor and selection

Alt+Click	Insert cursor
Ctrl+Alt+ ↑ / ↓	Insert cursor above / below
Ctrl+U	Undo last cursor operation
Shift+Alt+I	Insert cursor at end of each line selected
Ctrl+L	Select current line
Ctrl+Shift+L	Select all occurrences of current selection
Ctrl+F2	Select all occurrences of current word
Shift+Alt+→	Expand selection
Shift+Alt+←	Shrink selection
Shift+Alt + (drag mouse)	Column (box) selection
Ctrl+Shift+Alt + (arrow key)	Column (box) selection
Ctrl+Shift+Alt +PgUp/PgDn	Column (box) selection page up/down

Rich languages editing

Ctrl+Space, Ctrl+I	Trigger suggestion
Ctrl+Shift+Space	Trigger parameter hints
Shift+Alt+F	Format document
Ctrl+K Ctrl+F	Format selection
F12	Go to Definition
Alt+F12	Peek Definition
Ctrl+K F12	Open Definition to the side
Ctrl+.	Quick Fix
Shift+F12	Show References
F2	Rename Symbol
Ctrl+K Ctrl+X	Trim trailing whitespace
Ctrl+K M	Change file language

Editor management

Ctrl+F4, Ctrl+W	Close editor
Ctrl+K F	Close folder
Ctrl+\	Split editor
Ctrl+ 1 / 2 / 3	Focus into 1st, 2nd or 3rd editor group
Ctrl+K Ctrl+ ←/→	Focus into previous/next editor group
Ctrl+Shift+PgUp / PgDn	Move editor left/right
Ctrl+K ← / →	Move active editor group

File management

Ctrl+N	New File
Ctrl+O	Open File...
Ctrl+S	Save
Ctrl+Shift+S	Save As...
Ctrl+K S	Save All
Ctrl+F4	Close
Ctrl+K Ctrl+W	Close All
Ctrl+Shift+T	Reopen closed editor
Ctrl+K Enter	Keep preview mode editor open
Ctrl+Tab	Open next
Ctrl+Shift+Tab	Open previous
Ctrl+K P	Copy path of active file
Ctrl+K R	Reveal active file in Explorer
Ctrl+K O	Show active file in new window/instance

Display

F11	Toggle full screen
Shift+Alt+0	Toggle editor layout (horizontal/vertical)
Ctrl+ = / -	Zoom in/out
Ctrl+B	Toggle Sidebar visibility
Ctrl+Shift+E	Show Explorer / Toggle focus
Ctrl+Shift+F	Show Search
Ctrl+Shift+G	Show Source Control
Ctrl+Shift+D	Show Debug
Ctrl+Shift+X	Show Extensions
Ctrl+Shift+H	Replace in files
Ctrl+Shift+J	Toggle Search details
Ctrl+Shift+U	Show Output panel
Ctrl+Shift+V	Open Markdown preview
Ctrl+K V	Open Markdown preview to the side
Ctrl+K Z	Zen Mode (Esc Esc to exit)

Debug

F9	Toggle breakpoint
F5	Start/Continue
Shift+F5	Stop
F11 / Shift+F11	Step into/out
F10	Step over
Ctrl+K Ctrl+I	Show hover

Integrated terminal

Ctrl+`	Show integrated terminal
Ctrl+Shift+`	Create new terminal
Ctrl+C	Copy selection
Ctrl+V	Paste into active terminal
Ctrl+↑ / ↓	Scroll up/down
Shift+PgUp / PgDn	Scroll page up/down
Ctrl+Home / End	Scroll to top/bottom

Other operating systems' keyboard shortcuts and additional unassigned shortcuts available at aka.ms/vscodekeybindings

Visual Studio Code

Keyboard shortcuts for Linux

General

Ctrl+Shift+P, F1	Show Command Palette
Ctrl+P	Quick Open, Go to File...
Ctrl+Shift+N	New window/instance
Ctrl+W	Close window/instance
Ctrl+,	User Settings
Ctrl+K Ctrl+S	Keyboard Shortcuts

Basic editing

Ctrl+X	Cut line (empty selection)
Ctrl+C	Copy line (empty selection)
Alt+ ↓ / ↑	Move line down/up
Ctrl+Shift+K	Delete line
Ctrl+Enter / Ctrl+Shift+Enter	Insert line below/ above
Ctrl+Shift+\	Jump to matching bracket
Ctrl+] / Ctrl+[	Indent/Outdent line
Home / End	Go to beginning/end of line
Ctrl+ Home / End	Go to beginning/end of file
Ctrl+ ↑ / ↓	Scroll line up/down
Alt+ PgUp / PgDn	Scroll page up/down
Ctrl+Shift+ [/]	Fold/unfold region
Ctrl+K Ctrl+ [/]	Fold/unfold all subregions
Ctrl+K Ctrl+0 / Ctrl+K Ctrl+J	Fold/Unfold all regions
Ctrl+K Ctrl+C	Add line comment
Ctrl+K Ctrl+U	Remove line comment
Ctrl+/	Toggle line comment
Ctrl+Shift+A	Toggle block comment
Alt+Z	Toggle word wrap

Rich languages editing

Ctrl+Space, Ctrl+I	Trigger suggestion
Ctrl+Shift+Space	Trigger parameter hints
Ctrl+Shift+I	Format document
Ctrl+K Ctrl+F	Format selection
F12	Go to Definition
Ctrl+Shift+F10	Peek Definition
Ctrl+K F12	Open Definition to the side
Ctrl+.	Quick Fix
Shift+F12	Show References
F2	Rename Symbol
Ctrl+K Ctrl+X	Trim trailing whitespace
Ctrl+K M	Change file language

Multi-cursor and selection

Alt+Click	Insert cursor*
Shift+Alt+ ↑ / ↓	Insert cursor above/below
Ctrl+U	Undo last cursor operation
Shift+Alt+I	Insert cursor at end of each line selected
Ctrl+L	Select current line
Ctrl+Shift+L	Select all occurrences of current selection
Ctrl+F2	Select all occurrences of current word
Shift+Alt + →	Expand selection
Shift+Alt + ←	Shrink selection
Shift+Alt + drag mouse	Column (box) selection

Display

F11	Toggle full screen
Shift+Alt+0	Toggle editor layout (horizontal/vertical)
Ctrl+ = / -	Zoom in/out
Ctrl+B	Toggle Sidebar visibility
Ctrl+Shift+E	Show Explorer / Toggle focus
Ctrl+Shift+F	Show Search
Ctrl+Shift+G	Show Source Control
Ctrl+Shift+D	Show Debug
Ctrl+Shift+X	Show Extensions
Ctrl+Shift+H	Replace in files
Ctrl+Shift+J	Toggle Search details
Ctrl+Shift+C	Open new command prompt/terminal
Ctrl+K Ctrl+H	Show Output panel
Ctrl+Shift+V	Open Markdown preview
Ctrl+K V	Open Markdown preview to the side
Ctrl+K Z	Zen Mode (Esc Esc to exit)

Search and replace

Ctrl+F	Find
Ctrl+H	Replace
F3 / Shift+F3	Find next/previous
Alt+Enter	Select all occurrences of Find match
Ctrl+D	Add selection to next Find match
Ctrl+K Ctrl+D	Move last selection to next Find match

Navigation

Ctrl+T	Show all Symbols
Ctrl+G	Go to Line...
Ctrl+P	Go to File...
Ctrl+Shift+O	Go to Symbol...
Ctrl+Shift+M	Show Problems panel
F8	Go to next error or warning
Shift+F8	Go to previous error or warning
Ctrl+Shift+Tab	Navigate editor group history
Ctrl+Alt+-	Go back
Ctrl+Shift+-	Go forward
Ctrl+M	Toggle Tab moves focus

Editor management

Ctrl+W	Close editor
Ctrl+K F	Close folder
Ctrl+\	Split editor
Ctrl+ 1 / 2 / 3	Focus into 1st, 2nd, 3rd editor group
Ctrl+K Ctrl + ←	Focus into previous editor group
Ctrl+K Ctrl + →	Focus into next editor group
Ctrl+Shift+PgUp	Move editor left
Ctrl+Shift+PgDn	Move editor right
Ctrl+K ←	Move active editor group left/up
Ctrl+K →	Move active editor group right/down

File management

Ctrl+N	New File
Ctrl+O	Open File...
Ctrl+S	Save
Ctrl+Shift+S	Save As...
Ctrl+W	Close
Ctrl+K Ctrl+W	Close All
Ctrl+Shift+T	Reopen closed editor
Ctrl+K Enter	Keep preview mode editor open
Ctrl+Tab	Open next
Ctrl+Shift+Tab	Open previous
Ctrl+K P	Copy path of active file
Ctrl+K R	Reveal active file in Explorer
Ctrl+K O	Show active file in new window/instance

Debug

F9	Toggle breakpoint
F5	Start / Continue
F11 / Shift+F11	Step into/out
F10	Step over
Shift+F5	Stop
Ctrl+K Ctrl+I	Show hover

Integrated terminal

Ctrl+`	Show integrated terminal
Ctrl+Shift+`	Create new terminal
Ctrl+Shift+C	Copy selection
Ctrl+Shift+V	Paste into active terminal
Ctrl+Shift+ ↑ / ↓	Scroll up/down
Shift+ PgUp / PgDn	Scroll page up/down
Shift+ Home / End	Scroll to top/bottom

* The Alt+Click gesture may not work on some Linux distributions. You can change the modifier key for the Insert cursor command to Ctrl+Click with the “editor.multiCursorModifier” setting.

ta2te