

Introduction to PyPy

Antonio Cuni

BigDive 2012

October 22 2012



What is PyPy?

- PyPy
 - ▶ started in 2003
 - ▶ Open Source, partially funded by EU and others
 - ▶ framework for fast dynamic languages
 - ▶ **Python implementation**
- as a Python dev, you care about the latter

Python in Python

- Actually: Python in **RPython**
- Restricted Python
 - ▶ Statically typed subset
 - ▶ never designed to be user friendly
 - ▶ still better than C/Java/C# in lots of aspects
 - ▶ “we write RPython so you don’t have to” (cit.)
- RPython : PyPy = C : CPython ...
- ... Java : Jython = C# : IronPython

- Run RPython programs on top of CPython
 - ▶ isn't it damn slow? Yes.
- Compile RPython programs to C
 - ▶ this is where the magic happens

- Run RPython programs on top of CPython
 - ▶ isn't it damn slow? Yes.
- Compile RPython programs to C
 - ▶ this is where the magic happens

PyPy: Software archeology

- Around since 2003
- (advertised as) production ready since December 2010
 - ▶ release 1.4
- Funding
 - ▶ EU FP6 programme
 - ▶ Eurostars programme
 - ▶ donations
 - ▶ ...

PyPy 1.9: current status

- Faster
 - ▶ **1.7x** than 1.5 (a year ago)
 - ▶ **2.2x** than 1.4
 - ▶ **5.5x** than CPython
- Implements Python 2.7.2
- Many more “PyPy-friendly” programs
- Packaging
 - ▶ Debian, Ubuntu, Fedora, Homebrew, Gentoo, ArchLinux, ...
 - ▶ Windows (32bit only), OS X
- C extension compatibility
 - ▶ runs (big part of) **PyOpenSSL** and **lxml**

PyPy features

- JIT

- ▶ automatically generated
- ▶ complete/correct by construction
- ▶ multiple backends: x86-32, x86-64, ARM

- Stackless

- ▶ not yet integrated with the JIT (in-progress)

- cpyext

- ▶ CPython C-API compatibility layer
- ▶ not always working
- ▶ often working: wxPython, PIL, cx_Oracle, mysqldb, pycairo, ...

- compact instances (as using `__slots__`)

PyPy features

- JIT

- ▶ automatically generated
- ▶ complete/correct by construction
- ▶ multiple backends: x86-32, x86-64, ARM

- Stackless

- ▶ not yet integrated with the JIT (in-progress)

- cpyext

- ▶ CPython C-API compatibility layer
- ▶ not always working
- ▶ often working: wxPython, PIL, cx_Oracle, mysqldb, pycairo, ...

- compact instances (as using `__slots__`)

PyPy features

- JIT

- ▶ automatically generated
- ▶ complete/correct by construction
- ▶ multiple backends: x86-32, x86-64, ARM

- Stackless

- ▶ not yet integrated with the JIT (in-progress)

- cpyext


- ▶ CPython C-API compatibility layer
- ▶ not always working
- ▶ often working: wxPython, PIL, cx_Oracle, mysqldb, pycairo, ...

- compact instances (as using `__slots__`)

PyPy features

- JIT
 - ▶ automatically generated
 - ▶ complete/correct by construction
 - ▶ multiple backends: x86-32, x86-64, ARM
- Stackless
 - ▶ not yet integrated with the JIT (in-progress)
- cpyext
 - ▶ CPython C-API compatibility layer
 - ▶ not always working
 - ▶ often working: wxPython, PIL, cx_Oracle, mysqldb, pycairo, ...
- compact instances (as using `__slots__`)

Speed



Real world use case (1)

- LWN's gitdm

- ▶ <http://lwn.net/Articles/442268/>
- ▶ data mining tool
- ▶ reads the output of `git log`
- ▶ generate kernel development statistics

- Performance

- ▶ CPython: 63 seconds
- ▶ PyPy: **21 seconds**

lwn.net

[...] PyPy is ready for prime time; it implements the (Python 2.x) language faithfully, and it is fast.

Real world use case (1)

- LWN's gitdm

- ▶ <http://lwn.net/Articles/442268/>
- ▶ data mining tool
- ▶ reads the output of `git log`
- ▶ generate kernel development statistics

- Performance

- ▶ CPython: 63 seconds
- ▶ PyPy: **21 seconds**

lwn.net

[...] PyPy is ready for prime time; it implements the (Python 2.x) language faithfully, and it is fast.

Real world use case (1)

- LWN's gitdm

- ▶ <http://lwn.net/Articles/442268/>
- ▶ data mining tool
- ▶ reads the output of `git log`
- ▶ generate kernel development statistics

- Performance

- ▶ CPython: 63 seconds
- ▶ PyPy: **21 seconds**

`lwn.net`

[...] PyPy is ready for prime time; it implements the (Python 2.x) language faithfully, and it is fast.

Real world use case (2)

- **MyHDL:** VHDL-like language written in Python
 - ▶ <http://www.myhdl.org/doku.php/performance>
 - ▶ (now) competitive with “real world” VHDL and Verilog simulators

myhdl.org

[...] the results are spectacular. By simply using a different interpreter, our simulations run 6 to 12 times faster.


Real world use case (2)

- **MyHDL**: VHDL-like language written in Python
 - ▶ <http://www.myhdl.org/doku.php/performance>
 - ▶ (now) competitive with “real world” VHDL and Verilog simulators

`myhdl.org`

[...] the results are spectacular. By simply using a different interpreter, our simulations run 6 to 12 times faster.

Real world use case (3)

- Translating PyPy itself
- Huge, complex piece of software
- All possible (and impossible :-)) kinds of dynamic and metaprogramming tricks
- ~2.5x faster with PyPy
- (slow warm-up phase, though)
- Ouroboros! 

Real world use case (4)



- Your own application
- Try PyPy, it might be worth it

Not convinced yet?

Real time edge detection

```
def sobelidx(img):  
    res = img.clone(typecode='d')  
    for p in img.pixeliter():  
        res[p] = (-1.0 * img[p + (-1, -1)] +  
                  1.0 * img[p + ( 1, -1)] +  
                 -2.0 * img[p + (-1,  0)] +  
                  2.0 * img[p + ( 1,  0)] +  
                 -1.0 * img[p + (-1,  1)] +  
                  1.0 * img[p + ( 1,  1)]) / 4.0  
    return res  
...  
...
```

Live demo



Is Python slow?

- ~~Python is slow~~
- Python is hard to optimize
- Huge stack of layers over the bare metal
- Abstraction has a cost (... or not?)

Is Python slow?

- ~~Python is slow~~
- Python is hard to optimize
- Huge stack of layers over the bare metal
- Abstraction has a cost (... or not?)

Is Python slow?

- ~~Python is slow~~
- Python is hard to optimize
- Huge stack of layers over the bare metal
- Abstraction has a cost (... or not?)

Python is complicated

How `a + b` works (simplified!):

- look up the method `__add__` on the type of `a`
- if there is one, call it
- if it returns `NotImplemented`, or if there is none, look up the method `__radd__` on the type of `b`
- if there is one, call it
- if there is none, or we get `NotImplemented` again, raise an exception `TypeError`

Python is a mess

How `obj.attr` or `obj.method()` works:

- ...
- no way to write it down in just one slide

Python is a mess

How `obj.attr` or `obj.method()` works:

- ...
- no way to write it down in just one slide

Killing the abstraction overhead

Python

```
class Point(object):

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def __add__(self, q):
        if not isinstance(q, Point):
            raise TypeError
        x1 = self.x + q.x
        y1 = self.y + q.y
        return Point(x1, y1)

def main():
    p = Point(0.0, 0.0)
    while p.x < 2000.0:
        p = p + Point(1.0, 0.5)
    print p.x, p.y
```

C

```
#include <stdio.h>

int main() {
    float px = 0.0, py = 0.0;
    while (px < 2000.0) {
        px += 1.0;
        py += 0.5;
    }
    printf("%f %f\n", px, py);
}
```

Killing the abstraction overhead

Python

```
class Point(object):

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def __add__(self, q):
        if not isinstance(q, Point):
            raise TypeError
        x1 = self.x + q.x
        y1 = self.y + q.y
        return Point(x1, y1)

def main():
    p = Point(0.0, 0.0)
    while p.x < 2000.0:
        p = p + Point(1.0, 0.5)
    print p.x, p.y
```

C

```
#include <stdio.h>

int main() {
    float px = 0.0, py = 0.0;
    while (px < 2000.0) {
        px += 1.0;
        py += 0.5;
    }
    printf("%f %f\n", px, py);
}
```

Pointless optimization techniques

```
#  
for item in some_large_list:  
    self.meth(item)
```

```
meth = self.meth  
for item in some_large_list:  
    meth(item)
```

```
def foo():  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
def foo(abs=abs):  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
#  
[i**2 for i in range(100)]
```

```
from itertools import *  
list(imap(pow, count(0),  
          repeat(2, 100)))
```

```
for i in range(large_number):  
    ...
```

```
for i in xrange(large_number):  
    ...
```

```
class A(object):  
    pass
```

```
class A(object):  
    __slots__ = ['a', 'b', 'c']
```

Pointless optimization techniques

```
#  
for item in some_large_list:  
    self.meth(item)
```

```
def foo():  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
#  
[i**2 for i in range(100)]
```

```
for i in range(large_number):  
    ...
```

```
class A(object):  
    pass
```

```
meth = self.meth  
for item in some_large_list:  
    meth(item)
```

```
def foo(abs=abs):  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
from itertools import *  
list(imap(pow, count(0),  
         repeat(2, 100)))
```

```
for i in xrange(large_number):  
    ...
```

```
class A(object):  
    __slots__ = ['a', 'b', 'c']
```

Pointless optimization techniques

```
#  
for item in some_large_list:  
    self.meth(item)
```

```
def foo():  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
#  
[i**2 for i in range(100)]
```

```
for i in range(large_number):  
    ...
```

```
class A(object):  
    pass
```

```
meth = self.meth  
for item in some_large_list:  
    meth(item)
```

```
def foo(abs=abs):  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
from itertools import *  
list(imap(pow, count(0),  
         repeat(2, 100)))
```

```
for i in xrange(large_number):  
    ...
```

```
class A(object):  
    __slots__ = ['a', 'b', 'c']
```


Pointless optimization techniques

```
#  
for item in some_large_list:  
    self.meth(item)
```

```
def foo():  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
#  
[i**2 for i in range(100)]
```

```
for i in range(large_number):  
    ...
```

```
class A(object):  
    pass
```

```
meth = self.meth  
for item in some_large_list:  
    meth(item)
```

```
def foo(abs=abs):  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
from itertools import *  
list(imap(pow, count(0),  
         repeat(2, 100)))
```

```
for i in xrange(large_number):  
    ...
```

```
class A(object):  
    __slots__ = ['a', 'b', 'c']
```

Pointless optimization techniques

```
#  
for item in some_large_list:  
    self.meth(item)
```

```
meth = self.meth  
for item in some_large_list:  
    meth(item)
```

```
def foo():  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
def foo(abs=abs):  
    res = 0  
    for item in some_large_list:  
        res = res + abs(item)  
    return res
```

```
#  
[i**2 for i in range(100)]
```

```
from itertools import *  
list(imap(pow, count(0),  
         repeat(2, 100)))
```

```
for i in range(large_number):  
    ...
```

```
for i in xrange(large_number):  
    ...
```

```
class A(object):  
    pass
```

```
class A(object):  
    __slots__ = ['a', 'b', 'c']
```

Concrete example: ctypes

```
import ctypes
libm = ctypes.CDLL('libm.so')
pow = libm.pow
pow.argtypes = [ctypes.c_double, ctypes.c_double]
pow.restype = ctypes.c_double
pow(2, 3) # <---
```

Layers and layers

```
CFuncPtrFast.__call__ (Python)
```

check that the cache is still valid

Layers and layers

`CFuncPtrFast.__call__` (Python)

check that the cache is still valid

`CFuncPtrFast._call_funcptr` (Python)

some runtime checks (e.g. `_flags_`)

Layers and layers

`CFuncPtrFast.__call__ (Python)`

check that the cache is still valid

`CFuncPtrFast._call_funcptr (Python)`

some runtime checks (e.g. `_flags_`)

`_ffi.FuncPtr.__call__ (RPython)`

typecheck/unbox arguments, put them in raw C buffers

Layers and layers

`CFuncPtrFast.__call__` (Python)

check that the cache is still valid

`CFuncPtrFast._call_funcptr` (Python)

some runtime checks (e.g. `_flags_`)

`_ffi.FuncPtr.__call__` (RPython)

typecheck/unbox arguments, put them in raw C buffers

`c_ffi_call` (C) [libffi.so]

takes arguments from the raw C buffers

Layers and layers

`CFuncPtrFast.__call__` (Python)

check that the cache is still valid

`CFuncPtrFast._call_funcptr` (Python)

some runtime checks (e.g. `_flags_`)

`_ffi.FuncPtr.__call__` (RPython)

typecheck/unbox arguments, put them in raw C buffers

`c_ffi_call` (C) [libffi.so]

takes arguments from the raw C buffers

`pow@0xf72de000` (C) [libm.so]

return 8

ctypes demo

Conclusion

- PyPy is fast
- mature
- stable
- abstractions for free!
- (I wonder why you all are still here instead of busy trying PyPy :-))
 - ▶ not all C extensions are supported (numpy anyone?)
 - ▶ too much memory (sometimes)

Conclusion

- PyPy is fast
- mature
- stable
- abstractions for free!
- (I wonder why you all are still here instead of busy trying PyPy :-))
 - ▶ not all C extensions are supported (numpy anyone?)
 - ▶ too much memory (sometimes)

How to help PyPy?

- Try it on your application
 - ▶ if it's slow, we want to know!
 - ▶ if it does not work, too :-)
 - ▶ if it works and it's fast, that as well
- Tell people about PyPy
- Contribute to PyPy! (it's not **that** hard :-))
- Give us money, to make PyPy better
 - ▶ donations
 - ▶ per feature contracts
 - ▶ consultancy (hire us to speed up your code)
 - ▶ support contracts

How to help PyPy?

- Try it on your application
 - ▶ if it's slow, we want to know!
 - ▶ if it does not work, too :-)
 - ▶ if it works and it's fast, that as well
- Tell people about PyPy
- Contribute to PyPy! (it's not **that** hard :-))
- Give us money, to make PyPy better
 - ▶ donations
 - ▶ per feature contracts
 - ▶ consultancy (hire us to speed up your code)
 - ▶ support contracts

Contacts, Q/A

- `http://pypy.org`
- **blog:** `http://morepypy.blogspot.com`
- mailing list: `pypy-dev (at) python.org`
- IRC: `#pypy` on freenode

