

[Home](#)[Guides](#)[Reference](#)[Learn](#)[Data schema for eas.json](#)[Migrate from "expo build"](#)[Build lifecycle hooks](#)[Use private npm packages](#)[Use Git Submodules](#)[Use npm cache with Yarn Classic](#)[Set up EAS Build with a monorepo](#)[Environment variables and secrets](#)[Build APKs for Android Emulators and devices](#)[Build for iOS Simulators](#)[App version management](#)[Troubleshoot build errors and crashes](#)[Install app variants on the same device](#)[iOS Capabilities](#)[Run builds on your own infrastructure](#)[Cache dependencies](#)[Android build process](#)

# Environment variables and secrets in EAS Build

Learn how to use environment variables and secrets in an EAS Build.

The [Environment variables in Expo guide](#) describes how to use `.env` files to set environment variables that can be inlined

## On this page

Setting plaintext environment variables in eas.json

For use in application code

For use by your Expo config

For use by other build steps

Built-in environment variables

Using secrets in environment variables

Secrets on the Expo website

Adding secrets with EAS CLI

Importing secrets from a dotenv file

Accessing secrets in EAS Build

Common questions

Can EAS Build use `.env` files?

How do I share environment variables between my local development environment, EAS Update, and EAS Build?

How are naming collisions between secrets, the `env` field in eas.json, and `.env` files handled?

How do environment variables work for my Expo Development Client builds?

Can I just set my environment variables on a CI provider?

How to upload a secret file and use it in my app config?