



API reference

Screen

Version: 6.x

Screen

`Screen` components are used to configure various aspects of screens inside a navigator.

A `Screen` is returned from a `createXNavigator` function:

```
const Stack = createNativeStackNavigator(); // Stack contains Screen & Navigator properties
```

After creating the navigator, it can be used as children of the `Navigator` component:

```
<Stack.Navigator>
  <Stack.Screen name="Home" component={HomeScreen} />
  <Stack.Screen name="Profile" component={ProfileScreen} />
</Stack.Navigator>
```

You need to provide at least a name and a component to render for each screen.

Props

name

The name to use for the screen. It accepts a string:

```
<Stack.Screen name="Profile" component={ProfileScreen} />
```

This name is used to navigate to the screen:

```
navigation.navigate('Profile');
```

It is also used for the `name` property in the `route`.

While it is supported, we recommend to avoid spaces or special characters in screen names and keep them simple.

options

Options to configure how the screen gets presented in the navigator. It accepts either an object or a function returning an object:

```
<Stack.Screen
  name="Profile"
  component={ProfileScreen}
  options={{
    title: 'Awesome app',
  }}
/>
```

When you pass a function, it'll receive the `route` and `navigation`:

```
<Stack.Screen
  name="Profile"
  component={ProfileScreen}
  options={({ route, navigation }) => ({
    title: route.params.userId,
  })}
/>
```

See [Options for screens](#) for more details and examples.

initialParams

Initial params to use for the screen. If a screen is used as `initialRouteName`, it'll contain the params from `initialParams`. If you navigate to a new screen, the params passed are shallow merged with the initial params.

```
<Stack.Screen
  name="Details"
  component={DetailsScreen}
```

```
    initialParams={{ itemId: 42 }}  
  />
```

getId

Callback to return an unique ID to use for the screen. It receives an object with the route params:

```
<Stack.Screen  
  name="Profile"  
  component={ProfileScreen}  
  getId={({ params }) => params.userId}  
/>
```

By default, `navigate('ScreenName', params)` identifies the screen by its name. So if you're on `ScreenName` and navigate to `ScreenName` again, it won't add a new screen even if the params are different - it'll update the current screen with the new params instead:

```
// Let's say you're on `Home` screen  
// Then you navigate to `Profile` screen with `userId: 1`  
navigation.navigate('Profile', { userId: 1 });  
  
// Now the stack will have: `Home` -> `Profile` with `userId: 1`  
  
// Then you navigate to `Profile` screen again with `userId: 2`  
navigation.navigate('Profile', { userId: 2 });  
  
// The stack will now have: `Home` -> `Profile` with `userId: 2`
```

If you specify `getId` and it doesn't return `undefined`, the screen is identified by both the screen name and the returned ID. Which means that if you're on `ScreenName` and navigate to `ScreenName` again with different params - and return a different ID from the `getId` callback, it'll add a new screen to the stack:

```
// Let's say you're on `Home` screen  
// Then you navigate to `Profile` screen with `userId: 1`  
navigation.navigate('Profile', { userId: 1 });  
  
// Now the stack will have: `Home` -> `Profile` with `userId: 1`
```

```
// Then you navigate to `Profile` screen again with `userId: 2`  
navigation.navigate('Profile', { userId: 2 });  
  
// The stack will now have: `Home` -> `Profile` with `userId: 1` -> `Profile`  
with `userId: 2`
```

The `getId` callback can also be used to ensure that the screen with the same ID doesn't appear multiple times in the stack:

```
// Let's say you have a stack with the screens: `Home` -> `Profile` with  
`userId: 1` -> `Settings`  
// Then you navigate to `Profile` screen with `userId: 1` again  
navigation.navigate('Profile', { userId: 1 });  
  
// Now the stack will have: `Home` -> `Profile` with `userId: 1`
```

In the above examples, `params.userId` is used as an ID, subsequent navigation to the screen with the same `userId` will navigate to the existing screen instead of adding a new one to the stack. If the navigation was with a different `userId`, then it'll add a new screen.

If `getId` is specified in a tab or drawer navigator, the screen will remount if the ID changes.

component

The React Component to render for the screen:

```
<Stack.Screen name="Profile" component={ProfileScreen} />
```

getComponent

Callback to return the React Component to render for the screen:

```
<Stack.Screen  
  name="Profile"  
  getComponent={() => require('./ProfileScreen').default}  
/>
```

You can use this approach instead of the `component` prop if you want the `ProfileScreen` module to be lazily evaluated when needed. This is especially useful when using `ram bundles` to improve initial load.

children

Render callback to return React Element to use for the screen:

```
<Stack.Screen name="Profile">
  {(props) => <ProfileScreen {...props} />}
</Stack.Screen>
```

You can use this approach instead of the `component` prop if you need to pass additional props. Though we recommend using `React context` for passing data instead.

Note: By default, React Navigation applies optimizations to screen components to prevent unnecessary renders. Using a render callback removes those optimizations. So if you use a render callback, you'll need to ensure that you use `React.memo` or `React.PureComponent` for your screen components to avoid performance issues.

navigationKey


Optional key for this screen. This doesn't need to be unique. If the key changes, existing screens with this name will be removed (if used in a stack navigator) or reset (if used in a tab or drawer navigator).

This can be useful when we have some screens which we want to be removed or reset when the condition changes:

```
<Stack.Screen
  navigationKey={isSignedIn ? 'user' : 'guest'}
  name="Profile"
  component={ProfileScreen}
/>
```

listeners

Event listeners to subscribe to. See `listeners` prop on `Screen` for more details.

 Edit this page