∧Expo 📖 Docs

Blog   ⭐ Star Us on GitHub   ◐ ⌄

🔍 Search

🏠 Home

📖 **Guides**

📚 Reference

🎓 Learn

Drawer

Nesting navigators

Modals

Platform-specific Modules

Shared routes

Settings

Apple Handoff

⌄ Reference

Hooks API

Search Parameters

Redirects

Static Rendering

Async routes

Sitemap

Typed routes

Authentication

Screen tracking for analytics

Top-level src directory

Testing

Troubleshooting

Sitemap

Learn how to use the sitemap to debug your app with Expo Router.

On native, you can use the `uri-scheme` CLI to test opening native links on a device.

For example, if you want to launch the Expo Go app on iOS to the `/form-sheet` route, run:

┌─────────────────────────────────────┐
│ ▣ Terminal   📋 Copy   │
├─────────────────────────────────────┤
│   │
│ – npx uri-scheme open exp://192.168.87.39: │
└─────────────────────────────────────┘

┌─────────────────────────────────────┐
│ ⓘ Replace `192.168.87.39:19000` with │
│   the IP address shown when running │
│   `npx expo start`.   │
└─────────────────────────────────────┘

You can also search for links directly in a browser like Safari or Chrome to test deep linking on physical devices. Learn more about [testing deep links](#).

Sitemap