



Fitting the directed S^1 model to real networks

Inputs from a real network :

1. joint degree distribution $P(k^{\text{in}}, k^{\text{out}})$
2. reciprocity r
3. density of triangles



Assuming uniform angular positions for nodes,


1. infer $(\kappa^{\text{in}}, \kappa^{\text{out}})$ to replicate $P(k^{\text{in}}, k^{\text{out}})$ on average (analytical)
2. set ν to reproduce r (analytical)
3. adjust β to recreate the density of triangles (semi-analytical)

Generate a sample of random directed networks :

1. assign angular positions randomly
2. draw directed links using the probabilities defined by the framework for deliberate reciprocity

Inference algorithm adapted from New J. Phys. 21, 123033 (2019).





Fitting the directed \mathbb{S}^1 model to real networks

Inputs from a real network :



1. joint degree distribution $P(k^{\text{in}}, k^{\text{out}})$
2. reciprocity r
3. density of triangles

Assuming uniform angular positions for nodes,

1. infer $(\kappa^{\text{in}}, \kappa^{\text{out}})$ to replicate $P(k^{\text{in}}, k^{\text{out}})$ on average (analytical)
2. set ν to reproduce r (analytical)
3. adjust β to recreate the density of triangles (semi-analytical)

Generate a sample of random directed networks :

1. assign angular positions randomly
2. draw directed links using the probabilities defined by the framework for deliberate reciprocity



Realistic clustering patterns in directed geometric networks

