

3. Draw a link between node i and node j with probability p_{ij} . \bigstar fixes the expected degree of nodes $(\kappa) \to \text{soft configuration model (CM)}$

2. Assign an expected degree κ to each node according to some pdf $\rho(\kappa)$.

 \star triangle inequality of the underlying metric space \to triangles from pairwise interactions

1. Sprinkle N nodes uniformly on a circle of radius R.

 \star level of clustering tuned with parameter β

The S¹ model

Other properties and generalizations

- ➤ Amenable to many analytical calculations
- \triangleright Geometric interpretation in terms of hyperbolic geometry (the \mathbb{H}^2 model) [1,2]
 - ▶ Parsimonious explanation of self-similarity [3,4]
 - ▶ Generalizable to weighted [5], bipartite [6,7,8], multiplex [9,10] and growing [11] networks □ Generalizable to networks with community structure [12,13,14]
 - ▶ Mapping of real complex networks unto hyperbolic space [15,16]
 - ▶ Identification of biochemical pathways in E. Coli [8]
- ▷ Efficient Internet routing protocols [17] ▶ Multiscale organization of the human connectome [18]
- ▶ Geometrical interpretation of preferential attachment [11]

[1] Phys. Rev. E 80, 035101 (2009)

[2] Phys. Rev. E 82, 036106 (2010)

[3] Phys. Rev. Lett. 100, 078701 (2008)

[4] Nat. Rev. Phys. 3, 114 (2021)

[6] Phys. Rev. E 84, 026114 (2011)

[7] Phys. Rev. E 95, 032309 (2017)

[8] Mol. Biosyst. 8, 843 (2012)

[9] Nat. Phys. 12, 1076 (2016)

[10] Phys. Rev. Lett. 118, 218301 (2017)

[11] Nature 489, 537 (2012)

[12] Sci. Rep. 5, 9421 (2015)

[13] J. Stat. Phys. 173, 775 (2018)

[14] New J. Phys. 20, 052002 (2018)

[15] New J. Phys. 21, 123033 (2019)


[16] Nat. Commun. 8, 1615 (2017)


[17] Nat. Commun. 1, 62 (2010)

[18] PNAS 117, 20244 (2020)

A geometric approach to clustering: the $\mathbb{S}^1/\mathbb{H}^2$ model

A geometric approach to clustering: the $\mathbb{S}^1/\mathbb{H}^2$ model





The S¹ model

- 1. Sprinkle N nodes uniformly on a circle of radius R.
- 2. Assign an expected degree κ to each node according to some pdf $\rho(\kappa)$.
- 3. Draw a link between node i and node j with probability p_{ij} .
- \star fixes the expected degree of nodes $(\kappa) \to \text{soft configuration model (CM)}$
- \star triangle inequality of the underlying metric space \to triangles from pairwise interactions
- \star level of clustering tuned with parameter β

Other properties and generalizations

- > Amenable to many analytical calculations
- \triangleright Geometric interpretation in terms of hyperbolic geometry (the \mathbb{H}^2 model) [1,2]
- ▶ Parsimonious explanation of self-similarity [3,4]
- ▶ Generalizable to weighted [5], bipartite [6,7,8], multiplex [9,10] and growing [11] networks
- □ Generalizable to networks with community structure [12,13,14]
- ▶ Mapping of real complex networks unto hyperbolic space [15,16]
- ▶ Identification of biochemical pathways in E. Coli [8]
- ▷ Efficient Internet routing protocols [17]
- ▶ Multiscale organization of the human connectome [18]
- ▶ Geometrical interpretation of preferential attachment [11]
- > ...

- [1] Phys. Rev. E 80, 035101 (2009) [2] Phys. Rev. E 82, 036106 (2010)
- [3] Phys. Rev. Lett. 100, 078701 (2008)
- [4] Nat. Rev. Phys. 3, 114 (2021)
- [5] Nat. Commun. 8, 14103 (2017) [6] Phys. Rev. E 84, 026114 (2011)
- [7] Phys. Rev. E 95, 032309 (2017)
- [8] Mol. Biosyst. 8, 843 (2012) [9] Nat. Phys. 12, 1076 (2016)
- [10] Phys. Rev. Lett. 118, 218301 (2017)
- [11] Nature 489, 537 (2012)

[12] Sci. Rep. 5, 9421 (2015)

- [17] Nat. Commun. 1, 62 (2010)
- [14] New J. Phys. 20, 052002 (2018) [15] New J. Phys. 21, 123033 (2019)

[13] J. Stat. Phys. 173, 775 (2018)

- [16] Nat. Commun. 8, 1615 (2017)
- [18] PNAS 117, 20244 (2020)

Three challenges in modeling directed networks

Properties of any metric space

```
Identity of indiscernibles d(x,y)=0 \Leftrightarrow x=y
Non-negativity d(x,y)\geq 0
Symmetry d(x,y)=d(y,x)
Triangle inequality d(x,y)\leq d(x,z)+d(z,y)
```