

Manual SimTK optcntrlmuscle (v2.1)

Antoine Falisse, Maarten Afschrift, Tom Van Wouwe, Friedl De Groote

05/11/2018

Contents

1	Release notes	1
1.1	Release 2.1	1
2	Overview	2
3	Installation Instruction	2
4	Main Function	3
4.1	Using GPOPS	3
4.1.1	With explicit activation dynamics formulation (De Groote et al. (2016)) .	3
4.1.2	With implicit activation dynamics formulation (De Groote et al. (2009)) .	3
4.2	Using CasADi	3
4.2.1	With explicit activation dynamics formulation (De Groote et al. (2016)) .	3
4.2.2	With implicit activation dynamics formulation (De Groote et al. (2009)) .	4
4.3	Input Arguments	4
4.4	Output arguments	5
5	GPOPS-II	6
5.1	Setup	6
5.2	Output	6
6	CasADi	6
6.1	Setup	6
6.2	Output	6
7	Muscle model	6
8	Examples	7
8.1	Walking example De Groote et al. 2016	7
8.2	Running example De Groote et al. 2016	7
8.3	OpenSim installation example Gait10dof18m	8
8.4	OpenSim installation example Gait23dof54m	9

1 Release notes

1.1 Release 2.1

- CasADi was added as an alternative to GPOPS-II and ADiGator (see section 2 for details).

- The reserve actuators (RActivation) were unscaled in the output of the main functions.
- The time derivatives of the muscle contraction dynamics states, i.e. normalized muscle fiber velocities or derivatives of normalized tendon forces, were added to the cost function with a small weighting factor to prevent spiky outputs.
- The tendon stiffness was added as an optional user parameter (see section 8.3 for example).

2 Overview

The provided MATLAB code solves the muscle redundancy problem using direct collocation as described in *De Groote F, Kinney AL, Rao AV, Fregly BJ. Evaluation of direct collocation optimal control problem formulations for solving the muscle redundancy problem. Annals of Biomedical Engineering (2016).* <http://link.springer.com/article/10.1007%2Fs10439-016-1591-9>.

From v2.1, CasADi can be used as an alternative to GPOPS-II and ADiGator. CasADi is an open-source tool for nonlinear optimization and algorithmic differentiation (<https://web.casadi.org/>). Results using CasADi and GPOPS-II are very similar (differences can be attributed to the different direct collocation formulations and scaling). We distributed two different versions of the code: one is using the standard CasADi syntax whereas the other one is using Opti stack, which is a collection of CasADi helper classes that provides a close correspondence between mathematical NLP notation and computer code (<https://web.casadi.org/docs/#document-opti>). CasADi is actively maintained and developed, and has an active forum (<https://groups.google.com/forum/#!forum/casadi-users>).

From v1.1, an implicit formulation of activation dynamics can be used to solve the muscle redundancy problem. Additionally, by using the activation dynamics model proposed by Raasch et al. (1997), we could introduce a nonlinear change of variables to exactly impose activation dynamics in a continuously differentiable form, omitting the need for a smooth approximation such as described in De Groote et al. (2016). A result of this change of variables is that muscle excitations are not directly accessible during the optimization. Therefore, we replaced muscle excitations by muscle activations in the objective function. This implicit formulation is described in *De Groote F, Pipeleers G, Jonkers I, Demeulenaere B, Patten C, Swevers J, De Schutter J. A physiology based inverse dynamic analysis of human gait: potential and perspectives F. Computer Methods in Biomechanics and Biomedical Engineering (2009).* <http://www.tandfonline.com/doi/full/10.1080/10255840902788587>. Results from both formulations are very similar (differences can be attributed to the slightly different activation dynamics models and cost functions). However, the formulation with implicit activation dynamics (De Groote et al., (2009)) is computationally faster. This can mainly be explained by the omission of a tanh function in the constraint definition, whose evaluation is computationally expensive when solving the NLP.

3 Installation Instruction

Add the main folder and subfolder to your MATLAB path

```
1 addpath(genpath('C/...../SimTK_optcntrlmuscle'))
```

Several software packages are needed to run the program

- The OpenSim MATLAB interface is used to generate the inputs to the optimal control problem based on a scaled OpenSim model and the solution of inverse kinematics (providing the solution of inverse dynamics is optional). To this aim, install OpenSim and set up the OpenSim MATLAB interface (OpenSim: https://simtk.org/frs/?group_id=91, OpenSim API: <http://simtk-confluence.stanford.edu:8080/display/OpenSim/Scripting+with+Matlab>).
- Using GPOPS
 - GPOPS-II is used to solve the optimal control problem using direct collocation (<http://www.gpops2.com/>). A one-time 30-day trial license is available for all users who register.
 - ADiGator is used for automatic differentiation (<https://sourceforge.net/projects/adigator/>).
- Using CasADi (from v2.1)
 - CasADi is used for nonlinear optimization and algorithmic differentiation (<https://web.casadi.org/>).

4 Main Function

SolveMuscleRedundancy is the main function of this program and is used to solve the muscle redundancy problem. There are multiple variants of this function that depend on the chosen optimization package (GPOPS or CasADI) and formulation of the activation dynamics (explicit or implicit).

4.1 Using GPOPS

4.1.1 With explicit activation dynamics formulation (De Groote et al. (2016))

- SolveMuscleRedundancy_FtildeState uses the normalized tendon force as a state
- SolveMuscleRedundancy_lMtildeState uses the normalized muscle fiber length as a state

4.1.2 With implicit activation dynamics formulation (De Groote et al. (2009))

- SolveMuscleRedundancy_FtildeState_actdyn uses the normalized tendon force as a state
- SolveMuscleRedundancy_lMtildeState_actdyn uses the normalized muscle fiber length as a state

4.2 Using CasADi

4.2.1 With explicit activation dynamics formulation (De Groote et al. (2016))

- SolveMuscleRedundancy_FtildeState_CasADi uses the normalized tendon force as a state
- SolveMuscleRedundancy_lMtildeState_CasADi uses the normalized muscle fiber length as a state

4.2.2 With implicit activation dynamics formulation (De Groote et al. (2009))

- `SolveMuscleRedundancy_FtildeState_actdyn_CasADi` uses the normalized tendon force as a state
- `SolveMuscleRedundancy_lMtildeState_actdyn_CasADi` uses the normalized muscle fiber length as a state

4.3 Input Arguments

Required Input arguments for `SolveMuscleRedundancy`

1. **model_path:** directory and filename of the scaled OpenSim model (.osim). The code should work with any OpenSim model with valid muscle-tendon parameters for which OpenSim's Inverse Dynamics and Muscle Analysis Tools generate reliable results. Note that only the muscle-tendon parameters and not the muscle model specified in the osim-file are used (for details see Muscle model).
2. **IK_path:** directory and filename of the inverse kinematics solution (.mot file).
3. **ID_path:** directory and filename of the inverse dynamics solution (.sto file). If left empty, the inverse dynamics solution will be computed from the external loads (see Optional input arguments).
4. **time:** 1 x 2 MATLAB array with the initial and final time of the analysis in seconds. Initial and final states influence the optimal controls over a period of about 50 ms at the beginning and end of the time interval over which the optimal control problem is solved. Since in practice the initial and final states are generally unknown, problems should be solved for a time interval containing five additional data points (considering a 100Hz sampling frequency) at the beginning and end of the motion cycle. Those additional data points should not be considered in further analyses. The user should thus not be surprised to observe unrealistically high muscle activation at the beginning of the motion (more details in companion paper).
5. **OutPath:** directory where you want to store the results from the muscle analysis.
6. **Misc:** miscellaneous input arguments
 - *DofNames_Input* is a cell array specifying for which degrees of freedom you want to solve the muscle redundancy problem. Typically the muscle redundancy problem is solved for one leg at a time (there are no muscles spanning both legs).
 - *MuscleNames_Input* is a cell array that specifies the muscles to be included in when solving the muscle redundancy problem. All muscles that actuate (i.e. have a moment arm with respect to) the degrees of freedom specified in *DofNames_Input* will be selected by default if this array is empty.

Optional input arguments

1. **Misc.Loads_path:** path to the external loads file (.xml). The program will use the OpenSim libraries to solve the inverse dynamics problem when the required input argument *ID_path* is empty and *Misc.Loads_path* points to an external loads file.
2. **Misc.ID_ResultsPath:** Path where the inverse dynamics results will be saved when the required input argument *ID_path* is empty.

3. **Misc.f_cutoff_ID**: Cutoff frequency for the butterworth recursive low pass filter applied to the inverse dynamics data (default is 6 Hz).
4. **Misc.f_order_ID**: order of the butterworth recursive low pass filter applied to the inverse dynamics data (default is 6).
5. **Misc.f_cutoff_LMT**: cutoff frequency for butterworth recursive low pass filter applied to the muscle tendon lengths from the muscle analysis (default 6 Hz).
6. **Misc.f_order_LMT**: order of the butterworth recursive low pass filter applied to the muscle tendon lengths from the muscle analysis (default 6).
7. **Misc.f_cutoff_dM**: cutoff frequency for butterworth recursive low pass filter applied to the muscle moment arms from the muscle analysis (default 6 Hz).
8. **Misc.f_order_dM**: order of the butterworth recursive low pass filter applied to the muscle moment arms from the muscle analysis (default 6).
9. **Misc.f_cutoff_IK**: cutoff frequency for the butterworth recursive low pass filter applied to the inverse kinematics data (default is 6 Hz) when performing the muscle analysis to compute muscle-tendon lengths and moment arms.
10. **Misc.f_order_IK**: order of the butterworth recursive low pass filter applied to the inverse kinematics data (default is 6).
11. **Misc.Mesh_Frequency**: Number of mesh interval per second (default is 100, but a denser mesh might be required to obtain the desired accuracy especially for faster motions).
12. **Misc.Atendon**: vector with tendon stiffness for the selected muscles. The order should correspond to *MuscleNames_Input*. The default value is 35 and a lower value corresponds to a more compliant tendon. The default value 35 will be used when left empty. An example is provided in section 8.3 to set a different stiffness to the Achilles tendon.

4.4 Output arguments

1. Time: time vector.
2. MExcitation: optimal muscle excitation (matrix dimension: number of collocation points x number of muscles).
3. MActivation: optimal muscle activation (matrix dimension: number of collocation points x number of muscles).
4. RActivation: activation of the reserve actuators (matrix dimension: number of collocation points x number of degrees of freedom).
5. TForcetilde: normalized tendon force (matrix dimension: number of collocation points x number of muscles).
6. TForce: tendon force (matrix dimension: number of collocation points x number of muscles).
7. lMtilde: normalized muscle fiber length (matrix dimension: number of collocation points x number of muscles).

8. IM: muscle fiber length (matrix dimension: number of collocation points x number of muscles) .
9. MuscleNames: cell array that contains the names of the selected muscles (matrix dimension: number of muscles).
10. OptInfo: output structure created by GPOPS-II.
11. DatStore: data structure with input information for the optimal control problem.

5 GPOPS-II

5.1 Setup

The GPOPS-II setup is accessible through the function `SolveMuscleRedundancy_< state >.m` under GPOPS setup. The user is referred to the GPOPS-II user guide for setup options. A higher accuracy can be reached by adjusting, for instance, the number of mesh intervals. This however comes at the expense of the computational time. 100 mesh intervals per second are used by default.

5.2 Output

The output variable `OptInfo` contains all information related to the optimal control problem solution. Convergence to an optimal solution is reached when `output.result.nlpinfo` is flagged 0 ("EXIT: Optimal solution found" in the command window of MATLAB). The mesh accuracy can be assessed with `output.result.maxerrors`. Cost functional, control, state (and costate) can be accessed in `output.result.solution.phase`.

To recall, the user should consider extending the time interval by 50-100 ms at the beginning and end of the motion to limit the influence of the unknown initial and final state on the solution. Results from those additional periods should not be considered realistic and will typically result in high muscle activation.

6 CasADi

6.1 Setup

The CasADi setup is accessible through the function `SolveMuscleRedundancy_< state >_-CasADi.m` under CasADi setup. The user is referred to the CasADi user guide for setup options.

6.2 Output

The output variable `OptInfo` contains information related to the optimal control problem solution.

As for GPOPS, the user should consider extending the time interval by 50-100 ms at the beginning and end of the motion to limit the influence of the unknown initial and final state on the solution. Results from those additional periods should not be considered realistic and will typically result in high muscle activation.

7 Muscle model

The musculotendon properties are fully described in the supplementary materials of the aforementioned publication. Importantly, only the tendon slack length, optimal muscle fiber length, maximal isometric muscle force, optimal pennation angle and maximal muscle fiber contraction velocity are extracted from the referred OpenSim model. Other properties are defined in the code and can be changed if desired. By default, the activation and deactivation time constants are 15 and 60 ms respectively (see `tau_act` and `tau_deact` in `SolveMuscleRedundancy_< state >.m`).

8 Examples

Four examples are provided in the folder `examples`.

8.1 Walking example De Groote et al. 2016

```
1 clear all; close all; clc
2 %% Choose formulation
3 % formulation = 'lMtildeState';
4 formulation = 'FtildeState';
5 %% Choose activation dynamics
6 % actdyn = 'DeGroote2016';
7 actdyn = 'DeGroote2009';
8 %% Example
9 % add main folder and subfolder to matlab path (installation)
10 filepath=which('Walking_DeGrooteetal2016.m');
11 [DirExample,Walking,~,~]=fileparts(filepath); ...
    [DirExample,~]=fileparts(DirExample-Walking); [MainDir,~]=fileparts(DirExample);
12 addpath(genpath(MainDir));
13
14 % Needed Input Arguments
15 IK_path=fullfile(MainDir,'Examples','Walking_DeGrooteetal2016','WalkingData','inverse_kinematics.mot');
16 ID_path=fullfile(MainDir,'Examples','Walking_DeGrooteetal2016','WalkingData','inverse_dynamics.sto');
17 model_path=fullfile(MainDir,'Examples','Walking_DeGrooteetal2016','WalkingData','subject01.osim');
18 time=[0.516 1.95]; % Right stance phase (+50ms beginning and end of time interval, more ...
    details see manual and publication)
19 OutPath=fullfile(MainDir,'Examples','Walking_DeGrooteetal2016','Results');
20
21 Misc.MuscleNames_Input={}; % Selects all muscles for the Input DOFS when this is left empty.
22 Misc.DofNames_Input={'ankle-angle-r','knee-angle-r','hip-flexion-r','hip-rotation-r','hip-adduction-r'};
23
24 % Optional Input Arguments
25 Misc.f.cutoff_ID = 6; % cutoff frequency filtering ID
26 Misc.f.order_ID = 4; % order frequency filtering ID
27 Misc.f.cutoff_lMT = 6; % cutoff frequency filtering lMT
28 Misc.f.order_lMT = 4; % order frequency filtering lMT
29 Misc.f.cutoff_dM = 6; % cutoff frequency filtering MA
30 Misc.f.order_dM = 4; % order frequency filtering MA
31 Misc.f.cutoff_IK = 6; % cutoff frequency filtering IK
32 Misc.f.order_IK = 4; % order frequency filtering IK
33 Misc.Atendon = []; % Tendon Stiffness for the selected muscles
34 %% Solve the problem
35 switch actdyn
36     case 'DeGroote2016' % Activation dynamics from De Groote et al. (2016)
37         switch formulation
38             case 'lMtildeState'
39                 [Time,MExcitation,MActivation,RActivation,TForcetilde,TForce,lMtilde,lM,MuscleNames,OptInfo,DatS
40             case 'FtildeState'
41                 [Time,MExcitation,MActivation,RActivation,TForcetilde,TForce,lMtilde,lM,MuscleNames,OptInfo,DatS
42         end
43     case 'DeGroote2009' % Activation dynamics from De Groote et al. (2009)
44         switch formulation
45             case 'lMtildeState'
46                 [Time_actdyn,MExcitation_actdyn,MActivation_actdyn,RActivation_actdyn,TForcetilde_actdyn,TForce_a
47             case 'FtildeState'
48                 [Time_actdyn,MExcitation_actdyn,MActivation_actdyn,RActivation_actdyn,TForcetilde_actdyn,TForce_a
49         end
50     end
51 end
```

8.2 Running example De Groote et al. 2016

```
1 clear all; close all; clc
```

```

2 %% Choose formulation
3 % formulation = 'lMtildeState';
4 formulation = 'FtildeState';
5 %% Choose activation dynamics formulation
6 % actdyn = 'DeGroote2016';
7 actdyn = 'DeGroote2009';
8 %% Example
9 % add main folder and subfolder to matlab path (installation)
10 filepath=which('Running_DeGrooteetal2016.m');
11 [DirExample_Running,~,~]=fileparts(filepath); ...
    [DirExample,~]=fileparts(DirExample_Running); [MainDir,~]=fileparts(DirExample);
12 addpath(genpath(MainDir));
13
14 % Needed Input Arguments
15 IK_path=fullfile(MainDir, 'Examples', 'Running_DeGrooteetal2016', 'RunningData', 'IK_Joggen_1.mot');
16 ID_path=fullfile(MainDir, 'Examples', 'Running_DeGrooteetal2016', 'RunningData', 'ID_Joggen_1.sto');
17 model_path=fullfile(MainDir, 'Examples', 'Running_DeGrooteetal2016', 'RunningData', 'AddDB_Scaled_FB_FA.osim');
18 time=[0.05 0.98]; % Right stance phase (+50ms beginning and end of time interval, more details ...
    see manual and publication)
19 OutPath=fullfile(MainDir, 'Examples', 'Running_DeGrooteetal2016', 'Results');
20
21 Misc.MuscleNames_Input={}; % Selects all muscles for the Input DOFS when this is left empty.
22 Misc.DofNames_Input={'ankle-angle-r', 'knee-angle-r', 'hip-flexion-r', 'hip-adduction-r', 'hip-rotation-r'};
23
24 % Optional Input Arguments
25 Misc.Atendon = []; % Tendon Stiffness for the selected muscles
26 Misc.f_cutoff_ID = 10; % cutoff frequency filtering ID
27 Misc.f_order_ID = 5; % order frequency filtering ID
28 Misc.f_cutoff_lMT = 10; % cutoff frequency filtering lMT
29 Misc.f_order_lMT = 5; % order frequency filtering lMT
30 Misc.f_cutoff_dM = 10; % cutoff frequency filtering MA
31 Misc.f_order_dM = 5; % order frequency filtering MA
32 Misc.f_cutoff_IK = 10; % cutoff frequency filtering IK
33 Misc.f_order_IK = 5; % order frequency filtering IK
34 %% Solve the problem
35 switch actdyn
36 case 'DeGroote2016' % Activation dynamics from De Groote et al. (2016)
37     switch formulation
38     case 'lMtildeState'
39         [Time, MExcitation, MActivation, RActivation, TForcetilde, TForce, lMtilde, lM, MuscleNames, OptInfo, DatS
40     case 'FtildeState'
41         [Time, MExcitation, MActivation, RActivation, TForcetilde, TForce, lMtilde, lM, MuscleNames, OptInfo, DatS
42     end
43
44 case 'DeGroote2009' % Activation dynamics from De Groote et al. (2009)
45     switch formulation
46     case 'lMtildeState'
47         [Time, actdyn, MExcitation_actdyn, MActivation_actdyn, RActivation_actdyn, TForcetilde_actdyn, TForce_a
48     case 'FtildeState'
49         [Time, actdyn, MExcitation_actdyn, MActivation_actdyn, RActivation_actdyn, TForcetilde_actdyn, TForce_a
50     end
51 end

```

8.3 OpenSim installation example Gait10dof18m

```

1 clear all; close all; clc
2 %% Choose formulation
3 % formulation = 'lMtildeState';
4 formulation = 'FtildeState';
5 %% Choose activation dynamics formulation
6 % actdyn = 'DeGroote2016';
7 actdyn = 'DeGroote2009';
8 %% Example
9 % add main folder and subfolder to matlab path (installation)
10 filepath=which('Example_Gait10dof18m.m'); [DirExample,~,~]=fileparts(filepath); ...
    [DirExample2,~,~]=fileparts(DirExample); [MainDir,~]=fileparts(DirExample2);
11 addpath(genpath(MainDir));
12
13 % Needed Input Arguments
14 Datapath='C:\OpenSim 3.3\Models\Gait10dof18musc\OutputReference';
15 IK_path=fullfile(Datapath, 'IK', 'subject01_walk_IK.mot');
16 ID_path=[]; % compute ID from the external loads
17 model_path=fullfile(Datapath, 'subject01.osim');
18 time=[0.7 1.4]; % Part of the right stance phase
19 OutPath=fullfile(MainDir, 'Examples', 'OpenSimInstallation-Gait10dof18m', 'Results');
20
21 Misc.DofNames_Input={'ankle-angle-r', 'knee-angle-r', 'hip-flexion-r'};
22 Misc.Loads_path=fullfile(Datapath, 'ExperimentalData', 'subject01_walk-grf.xml');
23 Misc.ID_ResultsPath=fullfile(Datapath, 'ID', 'inversedynamics.sto');
24
25 %% Solve the problem
26 switch actdyn
27 case 'DeGroote2016' % Activation dynamics from De Groote et al. (2016)
28     switch formulation
29     case 'lMtildeState'
30         [Time, MExcitation, MActivation, RActivation, TForcetilde, TForce, lMtilde, lM, MuscleNames, OptInfo, DatS
31     case 'FtildeState'
32         [Time, MExcitation, MActivation, RActivation, TForcetilde, TForce, lMtilde, lM, MuscleNames, OptInfo, DatS

```



```

33         end
34
35     case 'DeGroote2009' % Activation dynamics from De Groote et al. (2009)
36     switch formulation
37     case 'lMtildeState'
38         [Time_actdyn, MExcitation_actdyn, MActivation_actdyn, RActivation_actdyn, TForcetilde_actdyn, TForce_a
39     case 'FtildeState'
40         [Time_actdyn, MExcitation_actdyn, MActivation_actdyn, RActivation_actdyn, TForcetilde_actdyn, TForce_a
41     end
42 end

```

8.4 OpenSim installation example Gait23dof54m

```

1  clear all; close all; clc
2  %% Choose formulation
3  % formulation = 'lMtildeState';
4  formulation = 'FtildeState';
5  %% Choose activation dynamics formulation
6  % actdyn = 'DeGroote2016';
7  actdyn = 'DeGroote2009';
8  %% Example
9  % add main folder and subfolder to matlab path (installation)
10 filepath=which('Example_Gait23dof54m.m'); [DirExample,~,~]=fileparts(filepath); ...
    [DirExample2,~,~]=fileparts(DirExample); [MainDir,~]=fileparts(DirExample2);
11 addpath(genpath(MainDir));
12
13 % Needed Input Arguments
14 Datapath='C:\OpenSim 3.3\Models\Gait2354_Simbody\OutputReference';
15 IK_path=fullfile(Datapath, 'subject01_walk1_ik.mot');
16 ID_path=fullfile(Datapath, 'ResultsInverseDynamics', 'inverse_dynamics.sto');
17 model_path=fullfile(Datapath, 'subject01_scaledOnly.osim');
18 time=[0.7 1.4]; % Part of the right stance phase
19 OutPath=fullfile(MainDir, 'Examples', 'OpenSimInstallation-Gait23dof54m', 'Results');
20
21 Misc.MuscleNames_Input={}; % Selects all muscles for the Input DOFS when this is left empty.
22 Misc.DofNames_Input={'ankle_angle_r', 'knee_angle_r', 'hip_flexion_r'};
23
24 %% Solve the problem
25 switch actdyn
26 case 'DeGroote2016' % Activation dynamics from De Groote et al. (2016)
27     switch formulation
28     case 'lMtildeState'
29         [Time, MExcitation, MActivation, RActivation, TForcetilde, TForce, lMtilde, lM, MuscleNames, OptInfo, DatS
30     case 'FtildeState'
31         [Time, MExcitation, MActivation, RActivation, TForcetilde, TForce, lMtilde, lM, MuscleNames, OptInfo, DatS
32     end
33
34 case 'DeGroote2009' % Activation dynamics from De Groote et al. (2009)
35     switch formulation
36     case 'lMtildeState'
37         [Time_actdyn, MExcitation_actdyn, MActivation_actdyn, RActivation_actdyn, TForcetilde_actdyn, TForce_a
38     case 'FtildeState'
39         [Time_actdyn, MExcitation_actdyn, MActivation_actdyn, RActivation_actdyn, TForcetilde_actdyn, TForce_a
40     end
41 end

```