

Contents

1	data structure	3
1.1	binary indexed tree.cpp	3
1.2	COT.cpp	4
1.3	divide tree.cpp	7
1.4	GSS7.cxx	9
1.5	OTOCL.cpp	15
1.6	segment tree - discretization.cpp	18
1.7	size-blanced binary search tree.cpp	20
1.8	sparse table - rectangle.cpp	25
1.9	sparse table - square.cpp	27
1.10	sparse table.cpp	28
1.11	treap.cpp	28
2	geometry	33
2.1	3D.cpp	33
2.2	3DCH.cpp	37
2.3	circle & ploy's area.cpp	42
2.4	circle's area.cpp	44
2.5	circle.cpp	48
2.6	closest point pair.cpp	53
2.7	half-plane intersection.cpp	59
2.8	kdtree.cpp	63
2.9	others	65
2.10	Pick's theorem	66
2.11	PointInPoly.cpp	67
2.12	rotating caliper.cpp	68
2.13	sort - polar angle.cpp	72
2.14	triangle's fermat point	73
3	graph	75
3.1	2-sat.cpp	75
3.2	Articulation.cpp	76
3.3	Augmenting Path Algorithm for Maximum Cardinality Bipartite Matching.cpp	77

3.4	best spanning tree.cpp	78
3.5	Biconnected Component.cpp	80
3.6	Bridge.cpp	82
3.7	chu-liu algorithm.cpp	82
3.8	k-th shortest path.cpp	85
3.9	Kuhn-Munkres algorithm.cpp	88
3.10	LCA - DA.cpp	91
3.11	LCA - tarjan - minmax.cpp	92
3.12	Minimum Cost Maximum Flow.cpp	94
3.13	minimum cut.cpp	96
3.14	others	97
3.15	Shortest Augmenting Path algorithm.cpp	98
3.16	Stable Marriage.cpp	102
3.17	Strongly Connected Component.cpp	103
4	math	105
4.1	cantor.cpp	105
4.2	combinations.cpp	106
4.3	euler's totient function.cpp	107
4.4	extended euclidean algorithm.cpp	108
4.5	inverse element.cpp	109
4.6	lucas.cpp	109
4.7	matrix.cpp	111
4.8	miller rabin.cpp	112
4.9	mod	113
4.10	pollard rho.cpp	113
4.11	prime.cpp	116
5	others	119
5.1	.vimrc	119
5.2	bigint.cpp	119
5.3	java.java	124
5.4	others	126
6	search	127
6.1	dlx	127
6.2	dlx - precise cover.cpp	127
6.3	dlx - repeat cover.cpp	129
6.4	fibonacci knapsack.cpp	132
7	string	135
7.1	aho corasick.cpp	135
7.2	manacher.cpp	136
7.3	morris-pratt.cpp	137
7.4	smallest representation.cpp	138
7.5	suffix array - da.cpp	139

<i>CONTENTS</i>	3
7.6 suffix array.cpp	140
7.7 z algorithm.cpp	143

Chapter 1

data structure

1.1 binary indexed tree.cpp

```
1  int tree[MAXX];
2
3  inline int lowbit(const int &a)
4  {
5      return a&-a;
6  }
7
8  inline void update(int pos,const int &val)
9  {
10     while(pos<MAXX)
11     {
12         tree[pos]+=val;
13         pos+=lowbit(pos);
14     }
15 }
16
17 inline int read(int pos)
18 {
19     int re(0);
20     while(pos>0)
21     {
22         re+=tree[pos];
23         pos-=lowbit(pos);
24     }
25     return re;
26 }
27
28 int find_Kth(int k)
```

```

29 {
30     int now=0;
31     for (char i=20;i>=0;--i)
32     {
33         now|=(1<<i);
34         if (now>MAXX || tree[now]>=k)
35             now^=(1<<i);
36         else k-=tree[now];
37     }
38     return now+1;
39 }

```

1.2 COT.cpp

```

1  #include<cstdio>
2  #include<algorithm>
3
4  #define MAXX 100111
5  #define MAX (MAXX*23)
6  #define N 18
7
8  int sz[MAX],lson[MAX],rson[MAX],cnt;
9  int head[MAXX];
10 int pre[MAXX][N];
11 int map[MAXX],m;
12
13 int edge[MAXX],nxt[MAXX<<1],to[MAXX<<1];
14 int n,i,j,k,q,l,r,mid;
15 int num[MAXX],dg[MAXX];
16
17 int make(int l,int r)
18 {
19     if (l==r)
20         return ++cnt;
21     int id(++cnt),mid((l+r)>>1);
22     lson[id]=make(l,mid);
23     rson[id]=make(mid+1,r);
24     return id;
25 }
26
27 inline int update(int id,int pos)
28 {
29     int re(++cnt);
30     l=1;
31     r=m;
32     int nid(re);

```

```

33     sz [ nid ] = sz [ id ] + 1;
34     while ( l < r )
35     {
36         mid = ( l + r ) >> 1;
37         if ( pos <= mid )
38         {
39             lson [ nid ] = ++cnt;
40             rson [ nid ] = rson [ id ];
41             nid = lson [ nid ];
42             id = lson [ id ];
43             r = mid;
44         }
45         else
46         {
47             lson [ nid ] = lson [ id ];
48             rson [ nid ] = ++cnt;
49             nid = rson [ nid ];
50             id = rson [ id ];
51             l = mid + 1;
52         }
53         sz [ nid ] = sz [ id ] + 1;
54     }
55     return re;
56 }
57
58 void rr ( int now , int fa )
59 {
60     dg [ now ] = dg [ fa ] + 1;
61     head [ now ] = update ( head [ fa ] , num [ now ] );
62     for ( int i ( edge [ now ] ) ; i ; i = nxt [ i ] )
63         if ( to [ i ] != fa )
64         {
65             j = 1;
66             for ( pre [ to [ i ] ] [ 0 ] = now ; j < N ; ++j )
67                 pre [ to [ i ] ] [ j ] = pre [ pre [ to [ i ] ] [ j - 1 ] ] [ j - 1 ];
68             rr ( to [ i ] , now );
69         }
70 }
71
72 inline int query ( int a , int b , int n , int k )
73 {
74     static int tmp , t;
75     l = 1;
76     r = n;
77     a = head [ a ];
78     b = head [ b ];

```

```

79     t=num[n];
80     n=head[n];
81     while(l<r)
82     {
83         mid=(l+r)>>1;
84         tmp=sz[lson[a]]+sz[lson[b]]-2*sz[lson[n]]+(l<=t
            && t<=mid);
85         if(tmp>=k)
86         {
87             a=lson[a];
88             b=lson[b];
89             n=lson[n];
90             r=mid;
91         }
92         else
93         {
94             k-=tmp;
95             a=rson[a];
96             b=rson[b];
97             n=rson[n];
98             l=mid+1;
99         }
100     }
101     return l;
102 }
103
104 inline int lca(int a,int b)
105 {
106     static int i,j;
107     j=0;
108     if(dg[a]<dg[b])
109         std::swap(a,b);
110     for(i=dg[a]-dg[b];i;i>>=1,++j)
111         if(i&1)
112             a=pre[a][j];
113     if(a==b)
114         return a;
115     for(i=N-1;i>=0;--i)
116         if(pre[a][i]!=pre[b][i])
117         {
118             a=pre[a][i];
119             b=pre[b][i];
120         }
121     return pre[a][0];
122 }
123

```



```

124 int main()
125 {
126     scanf("%d_%d",&n,&q);
127     for (i=1;i<=n;++i)
128     {
129         scanf("%d",num+i);
130         map[i]=num[i];
131     }
132     std::sort(map+1,map+n+1);
133     m=std::unique(map+1,map+n+1)-map-1;
134     for (i=1;i<=n;++i)
135         num[i]=std::lower_bound(map+1,map+m+1,num[i])-map
136         ;
137     for (i=1;i<n;++i)
138     {
139         scanf("%d_%d",&j,&k);
140         nxt[++cnt]=edge[j];
141         edge[j]=cnt;
142         to[cnt]=k;
143
144         nxt[++cnt]=edge[k];
145         edge[k]=cnt;
146         to[cnt]=j;
147     }
148     cnt=0;
149     head[0]=make(1,m);
150     rr(1,0);
151     while(q--)
152     {
153         scanf("%d_%d_%d",&i,&j,&k);
154         printf("%d\n",map[query(i,j,lca(i,j),k)]);
155     }
156     return 0;
157 }

```

1.3 divide tree.cpp

```

1 //          v a l [0][1], val[0][n]
2
3 template<class Tp>class DT
4 {
5     public:
6         int n;
7         Tp val[20][MAXX], sorted[MAXX];
8         inline void make()
9         {

```

```

10         std::sort(sorted+1,sorted+1+n);
11         make(1,1,n,0);
12     }
13     inline int query(const int &l,const int &r,const
14                     int &k)
15     {
16         return query(1,1,n,l,r,k,0);
17     }
18 private:
19     int toleft[20][MAXX],mid[MAXX<2];
20     // toleft:
21     void make(const int &id,const int &l,const int &r
22              ,const int &d)
23     {
24         if(l!=r)
25         {
26             mid[id]=(l+r)>>1;
27             int lsame(mid[id]-1+1),i;
28             for(i=l;i<=r;++i)
29                 if(val[d][i]<sorted[mid[id]])
30                     --lsame;
31             int lpos(1),rpos(mid[id]+1),same(0);
32             for(i=l;i<=r;++i)
33             {
34                 if(i==1)
35                     toleft[d][i]=0;
36                 else
37                     toleft[d][i]=topleft[d][i-1];
38                 if(val[d][i]<sorted[mid[id]])
39                 {
40                     ++topleft[d][i];
41                     val[d+1][lpos++]=val[d][i];
42                 }
43                 else
44                 {
45                     if(val[d][i]>sorted[mid[id]])
46                         val[d+1][rpos++]=val[d][i];
47                     else
48                     {
49                         if(same<lsame)
50                         {
51                             ++same;
52                             ++topleft[d][i];
53                             val[d+1][lpos++]=val[d][i];
54                         }
55                     }
56                     else
57                         val[d+1][rpos++]=val[d][i];
58                 }
59             }
60         }
61     }

```

```

53         ];
54     }
55     make(id<<1,l,mid[id],d+1);
56     make(id<<1|1,mid[id]+1,r,d+1);
57 }
58 int query(const int &id,const int &ll,const int &
59          rr,const int &l,const int &r,const int &k,
60          const int &d)
61 {
62     if(l==r)
63         return val[d][l];
64     int s,ss;
65     if(l==ll)
66     {
67         s=toleft[d][r];
68         ss=0;
69     }
70     else
71     {
72         s=toleft[d][r]-toleft[d][l-1];
73         ss=toleft[d][l-1];
74     }
75     if(s>=k)
76     {
77         int newl(ll+ss),newr(ll+ss+s-1);
78         return query(id<<1,ll,mid[id],newl,newr,k,
79                     ,d+1);
80     }
81     int bb(l-ll-ss),b(r-l+1-s),newl(mid[id]+bb+1),
82     newr(mid[id]+bb+b);
83     return query(id<<1|1,mid[id]+1,rr,newl,newr,k,
84                 -s,d+1);
85 }
86 };

```

1.4 GSS7.cxx

```

1 #include<cstdio>
2 #include<algorithm>
3 #include<queue>
4
5 #define MAXX 100111
6 #define MAX (MAXX<<1)
7
8 struct node

```

```

9  {
10     bool set, rev;
11     node *pre, *nxt[2], *fa;
12     int lmax, max, rmax, sum, val, sz;
13     node();
14     node(int a);
15 } *tree[MAXX], *nil, *a, *b;
16
17 node::node()
18 {
19     rev=set=false;
20     fa=pre=nil;
21     nxt[0]=nxt[1]=nil;
22     sz=lmax=max=rmax=sum=val=0;
23 }
24
25 node::node(int a)
26 {
27     set=rev=false;
28     sum=val=a;
29     sz=1;
30     lmax=max=rmax=std::max(0, a);
31     fa=pre=nxt[0]=nxt[1]=nil;
32 }
33
34 inline void add(node &x, const node &l, const node &r)
35 {
36     x.max=std::max(l.rmax+r.lmax, std::max(l.max, r.max));
37     x.lmax=std::max(l.lmax, l.sum+r.lmax);
38     x.rmax=std::max(r.rmax, r.sum+l.rmax);
39     x.sum=l.sum+r.sum;
40 }
41
42 inline void up(node *id)
43 {
44     id->sz=id->nxt[0]->sz+id->nxt[1]->sz+1;
45     id->sum=id->val+id->nxt[0]->sum+id->nxt[1]->sum;
46     id->lmax=std::max(id->nxt[0]->lmax, id->nxt[0]->sum+id
47         ->val+id->nxt[1]->lmax);
47     id->rmax=std::max(id->nxt[1]->rmax, id->nxt[1]->sum+id
48         ->val+id->nxt[0]->rmax);
48     id->max=std::max(id->nxt[0]->rmax+id->val+id->nxt
49         [1]->lmax, std::max(id->nxt[0]->max, id->nxt[1]->max
50         ));
49 }

```

```

51 inline void set(node *id, int val)
52 {
53     if(id==nil)
54         return;
55     id->set=true;
56     id->val=val;
57     id->sum=val*id->sz;
58     id->max=id->lmax=id->rmax=std::max(0, id->sum);
59 }
60
61 inline void down(node *id)
62 {
63     if(id==nil)
64         return;
65     if(id->rev)
66     {
67         id->rev=false;
68         for(int i(0); i<2; ++i)
69             if(id->nxt[i] != nil)
70             {
71                 id->nxt[i]->rev^=true;
72                 std::swap(id->nxt[i]->nxt[0], id->nxt[i]->
73                     nxt[1]);
74                 std::swap(id->nxt[i]->lmax, id->nxt[i]->
75                     rmax);
76             }
77     }
78     if(id->set)
79     {
80         for(int i(0); i<2; ++i)
81             if(id->nxt[i] != nil)
82                 set(id->nxt[i], id->val);
83         id->set=false;
84     }
85 }
86
87 inline void rot(node *id, int tp)
88 {
89     node *k(id->pre);
90     k->nxt[tp^1]=id->nxt[tp];
91     if(id->nxt[tp] != nil)
92         id->nxt[tp]->pre=k;
93     if(k->pre != nil)
94         k->pre->nxt[k=k->pre->nxt[1]]=id;
95     id->pre=k->pre;
96     id->nxt[tp]=k;

```

```

95     k->pre=id;
96     up(k);
97     up(id);
98 }
99
100 node *fresh(node* id)
101 {
102     node *re(id);
103     if(id->pre!=nil)
104         re=fresh(id->pre);
105     down(id);
106     return re;
107 }
108
109 inline void splay(node *id)
110 {
111     node *rt(fresh(id));
112     if(id!=rt)
113         for(std::swap(rt->fa, id->fa); id->pre!=nil; rot(id,
114             id==id->pre->nxt[0]));
115 }
116
117 inline void access(node *id)
118 {
119     for(node *to(nil); id!=nil; id=id->fa)
120     {
121         splay(id);
122         id->nxt[1]->pre=nil;
123         if(id->nxt[1]!=nil)
124             id->nxt[1]->fa=id;
125         id->nxt[1]=to;
126         if(to!=nil)
127             to->pre=id;
128         to->fa=nil;
129         up(to=id);
130     }
131 }
132
133 inline void lca(node *&to, node *&id)
134 {
135     access(to);
136     splay(id);
137     for(to=nil; id->fa!=nil; splay(id=id->fa))
138     {
139         id->nxt[1]->pre=nil;
140         if(id->nxt[1]!=nil)

```

```

140         id->nxt[1]->fa=id;
141         id->nxt[1]=to;
142         if(to!=nil)
143             to->pre=id;
144         to->fa=nil;
145         up(to=id);
146     }
147 }
148
149 int n,i,j,k;
150 int nxt[MAX],to[MAX],edge[MAXX],cnt;
151 std::queue<int>q;
152
153 inline void add(int a,int b)
154 {
155     nxt[++cnt]=edge[a];
156     edge[a]=cnt;
157     to[cnt]=b;
158 }
159
160 void rr(int now,int fa)
161 {
162     for(int i=edge[now];i;i=nxt[i])
163         if(to[i]!=fa)
164         {
165             tree[to[i]]->fa=tree[now];
166             rr(to[i],now);
167         }
168 }
169
170 /*
171 void print(node *id)
172 {
173     if(id!=nil)
174     {
175         print(id->nxt[0]);
176         printf("%2d %2d %2d %2d %2d %2d %c %2d\n",id->val
177             ,id->sum,id->sz,id->lmax,id->max,id->rmax,id->
178             rev?'r':'n',id->pre->val);
179         print(id->nxt[1]);
180     }
181 }
182 */
183
184 int main()
185 {

```

```

184     nil=new node();
185     scanf("%d",&n);
186     for ( i=1;i<=n;++i )
187     {
188         scanf("%d",&j);
189         tree[i]=new node(j);
190     }
191     for ( i=1;i<n;++i )
192     {
193         scanf("%d_%d",&j,&k);
194         add(j,k);
195         add(k,j);
196     }
197     tree[0]=nil;
198     rr(1,0);
199     scanf("%d",&n);
200     while(n--)
201     {
202         scanf("%d_%d_%d",&k,&i,&j);
203         a=tree[i];
204         b=tree[j];
205         access(a);
206         splay(a);
207         a->rev^=true;
208         std::swap(a->nxt[0],a->nxt[1]);
209         std::swap(a->lmax,a->rmax);
210         access(b);
211         splay(b);
212         /*
213         print(b);
214         puts("");
215         printf("%d %d %d %d\n",b->sum,b->nxt[0]->sum,b->
                val,b->nxt[1]->sum);
216         */
217         if(k==1)
218             printf("%d\n",b->max);
219         else
220         {
221             scanf("%d",&k);
222             set(b,k);
223         }
224     }
225     return 0;
226 }

```


1.5 OTOCI.cpp

```

1  #include<cstdio>
2  #include<algorithm>
3
4  #define MAXX 30111
5
6  int  nxt[MAXX][2] , fa[MAXX] , pre[MAXX] , val[MAXX] , sum[MAXX];
7  bool rev[MAXX];
8
9  inline void up(int id)
10 {
11     static int i;
12     sum[id]=val[id];
13     for (i=0;i<2;++i)
14         if(nxt[id][i])
15             sum[id]+=sum[nxt[id][i]];
16 }
17
18 inline void rot(int id,int tp)
19 {
20     static int k;
21     k=pre[id];
22     nxt[k][tp^1]=nxt[id][tp];
23     if(nxt[id][tp])
24         pre[nxt[id][tp]]=k;
25     if(pre[k])
26         nxt[pre[k]][k==nxt[pre[k]][1]] = id;
27     pre[id]=pre[k];
28     nxt[id][tp]=k;
29     pre[k]=id;
30     up(k);
31     up(id);
32 }
33
34 inline void down(int id)
35 {
36     static int i;
37     if(rev[id])
38     {
39         rev[id]=false;
40         std::swap(nxt[id][0] , nxt[id][1]);
41         for (i=0;i<2;++i)
42             if(nxt[id][i])
43                 rev[nxt[id][i]]^=true;

```

```

44     }
45 }
46
47 int freshen(int id)
48 {
49     int re(id);
50     if(pre[id])
51         re=freshen(pre[id]);
52     down(id);
53     return re;
54 }
55
56 inline void splay(int id)
57 {
58     static int rt;
59     if(id!=(rt=freshen(id)))
60         for(std::swap(fa[id],fa[rt]);pre[id];rot(id,id==
61             nxt[pre[id]][0]));
62 }
63
64 inline void access(int id)
65 {
66     static int to;
67     for(to=0;id;id=fa[id])
68     {
69         splay(id);
70         if(nxt[id][1])
71         {
72             pre[nxt[id][1]]=0;
73             fa[nxt[id][1]]=id;
74         }
75         nxt[id][1]=to;
76         if(to)
77         {
78             pre[to]=id;
79             fa[to]=0;
80         }
81         up(to=id);
82     }
83
84 inline int getrt(int id)
85 {
86     access(id);
87     splay(id);
88     while(nxt[id][0])

```

```

89     {
90         id=nxt[id][0];
91         down(id);
92     }
93     return id;
94 }
95
96 inline void makert(int id)
97 {
98     access(id);
99     splay(id);
100     if(nxt[id][0])
101         rev[id]^=true;
102 }
103
104 int n,i,j,k,q;
105 char buf[11];
106
107 int main()
108 {
109     scanf("%d",&n);
110     for(i=1;i<=n;++i)
111         scanf("%d",val+i);
112     scanf("%d",&q);
113     while(q--)
114     {
115         scanf("%s_%d_%d",buf,&i,&j);
116         switch(buf[0])
117         {
118             case 'b':
119                 if(getrt(i)==getrt(j))
120                     puts("no");
121             else
122             {
123                 puts("yes");
124                 makert(i);
125                 fa[i]=j;
126             }
127             break;
128             case 'p':
129                 access(i);
130                 splay(i);
131                 val[i]=j;
132                 up(i);
133             break;
134             case 'e':

```

```

135         if (getrt(i) != getrt(j))
136             puts("impossible");
137         else
138         {
139             makert(i);
140             access(j);
141             splay(j);
142             printf("%d\n", sum[j]);
143         }
144         break;
145     }
146 }
147 return 0;
148 }

```

1.6 segment tree - discretization.cpp

```

1  std::map<double, short>map;    //    h a s h
2  std::map<double, short>::iterator it;
3  double rmap[inf];    //    h a s h
4
5  short mid[MAX], cnt[MAX];
6  double len[MAX];
7
8  void make(const short &id, const short &l, const short &r)
9  {
10     mid[id] = (l+r) >> 1;
11     if (l != r)
12     {
13         make(id << 1, l, mid[id]);
14         make(id << 1 | 1, mid[id] + 1, r);
15     }
16 }
17
18 void update(const short &id, const short &ll, const short &
19            rr, const short &l, const short &r, const char &val)
20 {
21     if (ll == l && rr == r)
22     {
23         cnt[id] += val;
24         if (cnt[id])
25             len[id] = rmap[r] - rmap[l - 1];
26     }
27     else
28     {
29         if (l != r)
30             len[id] = len[id << 1] + len[id << 1 | 1];
31         else

```

```

29         len[id]=0;
30     return;
31 }
32 if(mid[id]>=r)
33     update(id<<1,ll ,mid[id] ,l ,r , val );
34 else
35     if(mid[id]<l)
36         update(id<<1|1,mid[id]+1,rr ,l ,r , val );
37     else
38     {
39         update(id<<1,ll ,mid[id] ,l ,mid[id] , val );
40         update(id<<1|1,mid[id]+1,rr ,mid[id]+1,r , val );
41     }
42 if(!cnt[id])
43     len[id]=len[id<<1]+len[id<<1|1];
44 }
45
46 int main()
47 {
48     n<=<1;
49     map.clear();
50     for(i=0;i<n;++i)
51     {
52         scanf("%lf%lf%lf%lf%lf",&x1,&y1,&x2,&y2,&d);
53         if(x1>x2)
54             std::swap(x1,x2);
55         if(y1>y2)
56             std::swap(y1,y2);
57         sum+=(x2-x1)*(y2-y1)*d;
58         ln[i].l=x1;
59         ln[i].r=x2;
60         ln[i].h=y1;
61         ln[i].up=1;
62         ln[++i].l=x1;
63         ln[i].r=x2;
64         ln[i].h=y2;
65         ln[i].up=-1;
66         map[x1]=1;
67         map[x2]=1;
68     }
69     k=1;
70     for(it=map.begin();it!=map.end();++it,++k) //
71     {
72         it->second=k;
73         rmap[k]=it->first;

```

```

74     }
75     std::sort(ln,ln+n);
76     update(1,1,inf,map[ln[0].l]+1,map[ln[0].r],ln[0].up);
77     for(i=1;i<n;++i)
78     {
79         //                l e n [1]
80         //ln[i].h-ln[i-1].h

81         update(1,1,inf,map[ln[i].l]+1,map[ln[i].r],ln[i].
82             up);
83     }

```

1.7 size-blanced binary search tree.cpp

```

1  template<class Tp>class sbt
2  {
3      public:
4          inline void init()
5          {
6              rt=cnt=l[0]=r[0]=sz[0]=0;
7          }
8          inline void ins(const Tp &a)
9          {
10             ins(rt,a);
11         }
12         inline void del(const Tp &a)
13         {
14             del(rt,a);
15         }
16         inline bool find(const Tp &a)
17         {
18             return find(rt,a);
19         }
20         inline Tp pred(const Tp &a)
21         {
22             return pred(rt,a);
23         }
24         inline Tp succ(const Tp &a)
25         {
26             return succ(rt,a);
27         }
28         inline bool empty()
29         {
30             return !sz[rt];
31         }

```

```

32     inline Tp min()
33     {
34         return min(rt);
35     }
36     inline Tp max()
37     {
38         return max(rt);
39     }
40     inline void delsmall(const Tp &a)
41     {
42         dels(rt, a);
43     }
44     inline int rank(const Tp &a)
45     {
46         return rank(rt, a);
47     }
48     inline Tp sel(const int &a)
49     {
50         return sel(rt, a);
51     }
52     inline Tp delsele(int a)
53     {
54         return delsele(rt, a);
55     }
56 private:
57     int cnt, rt, l[MAXX], r[MAXX], sz[MAXX];
58     Tp val[MAXX];
59     inline void rro(int &pos)
60     {
61         int k(l[pos]);
62         l[pos]=r[k];
63         r[k]=pos;
64         sz[k]=sz[pos];
65         sz[pos]=sz[l[pos]]+sz[r[pos]]+1;
66         pos=k;
67     }
68     inline void lro(int &pos)
69     {
70         int k(r[pos]);
71         r[pos]=l[k];
72         l[k]=pos;
73         sz[k]=sz[pos];
74         sz[pos]=sz[l[pos]]+sz[r[pos]]+1;
75         pos=k;
76     }
77     inline void mt(int &pos, bool flag)

```

```

78     {
79         if (!pos)
80             return;
81         if (flag)
82             if (sz[r[r[pos]]] > sz[l[pos]])
83                 lro(pos);
84             else
85                 if (sz[l[r[pos]]] > sz[l[pos]])
86                 {
87                     rro(r[pos]);
88                     lro(pos);
89                 }
90             else
91                 return;
92         else
93             if (sz[l[l[pos]]] > sz[r[pos]])
94                 rro(pos);
95             else
96                 if (sz[r[l[pos]]] > sz[r[pos]])
97                 {
98                     lro(l[pos]);
99                     rro(pos);
100                 }
101             else
102                 return;
103         mt(l[pos], false);
104         mt(r[pos], true);
105         mt(pos, false);
106         mt(pos, true);
107     }
108 void ins(int &pos, const Tp &a)
109 {
110     if (pos)
111     {
112         ++sz[pos];
113         if (a < val[pos])
114             ins(l[pos], a);
115         else
116             ins(r[pos], a);
117         mt(pos, a >= val[pos]);
118         return;
119     }
120     pos = ++cnt;
121     l[pos] = r[pos] = 0;
122     val[pos] = a;
123     sz[pos] = 1;

```



```

124     }
125     Tp del(int &pos, const Tp &a)
126     {
127         --sz[pos];
128         if(val[pos]==a || (a<val[pos] && !l[pos]) ||
            (a>val[pos] && !r[pos]))
129         {
130             Tp ret(val[pos]);
131             if(!l[pos] || !r[pos])
132                 pos=l[pos]+r[pos];
133             else
134                 val[pos]=del(l[pos], val[pos]+1);
135             return ret;
136         }
137         else
138             if(a<val[pos])
139                 return del(l[pos], a);
140             else
141                 return del(r[pos], a);
142     }
143     bool find(int &pos, const Tp &a)
144     {
145         if(!pos)
146             return false;
147         if(a<val[pos])
148             return find(l[pos], a);
149         else
150             return (val[pos]==a || find(r[pos], a));
151     }
152     Tp pred(int &pos, const Tp &a)
153     {
154         if(!pos)
155             return a;
156         if(a>val[pos])
157         {
158             Tp ret(pred(r[pos], a));
159             if(ret==a)
160                 return val[pos];
161             else
162                 return ret;
163         }
164         return pred(l[pos], a);
165     }
166     Tp succ(int &pos, const Tp &a)
167     {
168         if(!pos)

```

```

169         return a;
170     if (a < val[pos])
171     {
172         Tp ret(succ(l[pos], a));
173         if (ret == a)
174             return val[pos];
175         else
176             return ret;
177     }
178     return succ(r[pos], a);
179 }
180 Tp min(int &pos)
181 {
182     if (l[pos])
183         return min(l[pos]);
184     else
185         return val[pos];
186 }
187 Tp max(int &pos)
188 {
189     if (r[pos])
190         return max(r[pos]);
191     else
192         return val[pos];
193 }
194 void dels(int &pos, const Tp &v)
195 {
196     if (!pos)
197         return;
198     if (val[pos] < v)
199     {
200         pos = r[pos];
201         dels(pos, v);
202         return;
203     }
204     dels(l[pos], v);
205     sz[pos] = 1 + sz[l[pos]] + sz[r[pos]];
206 }
207 int rank(const int &pos, const Tp &v)
208 {
209     if (val[pos] == v)
210         return sz[l[pos]] + 1;
211     if (v < val[pos])
212         return rank(l[pos], v);
213     return rank(r[pos], v) + sz[l[pos]] + 1;
214 }

```

```

215     Tp sel(const int &pos, const int &v)
216     {
217         if (sz[l[pos]]+1==v)
218             return val[pos];
219         if (v>sz[l[pos]])
220             return sel(r[pos], v-sz[l[pos]]-1);
221         return sel(l[pos], v);
222     }
223     Tp dsel(int &pos, int k)
224     {
225         --sz[pos];
226         if (sz[l[pos]]+1==k)
227         {
228             Tp re(val[pos]);
229             if (!l[pos] || !r[pos])
230                 pos=l[pos]+r[pos];
231             else
232                 val[pos]=del(l[pos], val[pos]+1);
233             return re;
234         }
235         if (k>sz[l[pos]])
236             return dsel(r[pos], k-1-sz[l[pos]]);
237         return dsel(l[pos], k);
238     }
239 };

```

1.8 sparse table - rectangle.cpp

```

1  #include<iostream>
2  #include<cstdio>
3  #include<algorithm>
4
5  #define MAXX 310
6
7  int mat[MAXX][MAXX];
8  int table[9][9][MAXX][MAXX];
9  int n;
10 short lg[MAXX];
11
12 int main()
13 {
14     for(int i(2); i<MAXX; ++i)
15         lg[i]=lg[i>>1]+1;
16     int T;
17     std::cin >> T;
18     while (T--)

```

```

19     {
20         std::cin >> n;
21         for (int i = 0; i < n; ++i)
22             for (int j = 0; j < n; ++j)
23                 {
24                     std::cin >> mat[i][j];
25                     table[0][0][i][j] = mat[i][j];
26                 }
27
28         //

```



```

29         for(int i=0;i<=lg[n];++i) // width
30         {
31             for(int j=0;j<=lg[n];++j) //height
32             {
33                 if(i==0 && j==0)
34                     continue;
35                 for(int ii=0;ii+(1<<j)<=n;++ii)
36                     for(int jj=0;jj+(1<<i)<=n;++jj)
37                         if(i==0)
38                             table[i][j][ii][jj]=std::min(
39                                 table[i][j-1][ii][jj],
40                                 table[i][j-1][ii+(1<<(j-1))][jj]);
41                         else
42                             table[i][j][ii][jj]=std::min(
43                                 table[i-1][j][ii][jj],
44                                 table[i-1][j][ii][jj+(1<<(i-1))]);
45             }
46         }
47         long long N;
48         std::cin >> N;
49         int r1, c1, r2, c2;
50         for (int i = 0; i < N; ++i)
51         {
52             scanf("%d%d%d%d",&r1,&c1,&r2,&c2);
53             --r1;
54             --c1;
55             --r2;
56             --c2;
57             int w=lg[c2-c1+1];
58             int h=lg[r2-r1+1];
59             printf("%d\n",std::min(table[w][h][r1][c1],
60                                     std::min(table[w][h][r1][c2-(1<<w)+1],std

```

```

56         }
57     }
58     return 0;
59 }

```

1.9 sparse table - square.cpp

```

1  int num[MAXX][MAXX], max[MAXX][MAXX][10];
2  short lg[MAXX];
3
4  int main()
5  {
6      for (i=2; i<MAXX; ++i)
7          lg[i]=lg[i>>1]+1;
8      scanf("%hd_%d", &n, &q);
9      for (i=0; i<n; ++i)
10         for (j=0; j<n; ++j)
11             {
12                 scanf("%d", num[i][j]);
13                 max[i][j][0]=num[i][j];
14             }
15     for (k=1; k<=lg[n]; ++k)
16     {
17         l=n+1-(1<<k);
18         for (i=0; i<l; ++i)
19             for (j=0; j<l; ++j)
20                 max[i][j][k]=std::max(std::max(max[i][j][k-1], max[i+(1<<(k-1))][j][k-1]), std::max(max[i][j+(1<<(k-1))][k-1], max[i+(1<<(k-1))][j+(1<<(k-1))][k-1]));
21     }
22     printf("Case_%hd:\n", t);
23     while(q--)
24     {
25         scanf("%hd_%hd_%hd", &i, &j, &l);
26         --i;
27         --j;
28         k=lg[l];
29         printf("%d\n", std::max(std::max(max[i][j][k], max[i][j+(1<<k)][k]), std::max(max[i+(1<<k)][j][k], max[i+(1<<k)][j+(1<<k)][k])));
30     }
31 }

```

1.10 sparse table.cpp

```

1  int num[MAXX] , min [MAXX] [ 20 ] ;
2  int lg [MAXX] ;
3
4
5  int main ( )
6  {
7      for ( i=2; i<MAXX; ++i )
8          lg [ i ] = lg [ i >> 1 ] + 1 ;
9      scanf ( "%d_%d" , &n , &q ) ;
10     for ( i=1; i<=n; ++i )
11     {
12         scanf ( "%d" , num+i ) ;
13         min [ i ] [ 0 ] = num [ i ] ;
14     }
15     for ( j=1; j<=lg [ n ]; ++j )
16     {
17         l=n+1-(1<<j) ;
18         j-=j-1 ;
19         j--=(1<<j-) ;
20         for ( i=1; i<=l; ++i )
21             min [ i ] [ j ] = std :: min ( min [ i ] [ j- ] , min [ i+j- ] [ j- ] )
22             ;
23     }
24     printf ( " Case_%hd: \n" , t ) ;
25     while ( q-- )
26     {
27         scanf ( "%d_%d" , &i , &j ) ;
28         k=lg [ j-i+1 ] ;
29         printf ( "%d\n" , std :: min ( min [ i ] [ k ] , min [ j-(1<<k)+1 ] [
30             k ] ) ) ;

```

1.11 treap.cpp

```

1  #include<cstdlib>
2  #include<ctime>
3  #include<cstring>
4
5  struct node
6  {
7      node *ch [ 2 ] ;
8      int sz , val , key ;

```

```

9      node() {memset(this, 0, sizeof(node));}
10      node(int a);
11  }*null;
12
13  node::node(int a):sz(1),val(a),key(rand()-1){ch[0]=ch[1]=
      null;}
14
15  class Treap
16  {
17      inline void up(node *pos)
18      {
19          pos->sz=pos->ch[0]->sz+pos->ch[1]->sz+1;
20      }
21      inline void rot(node *&pos,int tp)
22      {
23          node *k(pos->ch[tp]);
24          pos->ch[tp]=k->ch[tp^1];
25          k->ch[tp^1]=pos;
26          up(pos);
27          up(k);
28          pos=k;
29      }
30
31      void insert(node *&pos,int val)
32      {
33          if(pos!=null)
34          {
35              int t(val>=pos->val);
36              insert(pos->ch[t],val);
37              if(pos->ch[t]->key<pos->key)
38                  rot(pos,t);
39              else
40                  up(pos);
41              return;
42          }
43          pos=new node(val);
44      }
45      void rec(node *pos)
46      {
47          if(pos!=null)
48          {
49              rec(pos->ch[0]);
50              rec(pos->ch[1]);
51              delete pos;
52          }
53      }

```

```

54  inline int sel(node *pos, int k)
55  {
56      while (pos->ch[0]->sz+1!=k)
57          if (pos->ch[0]->sz>=k)
58              pos=pos->ch[0];
59          else
60              {
61                  k-=pos->ch[0]->sz+1;
62                  pos=pos->ch[1];
63              }
64      return pos->val;
65  }
66  void del(node *&pos, int val)
67  {
68      if (pos!=null)
69      {
70          if (pos->val==val)
71          {
72              int t (pos->ch[1]->key<pos->ch[0]->key);
73              if (pos->ch[t]==null)
74              {
75                  delete pos;
76                  pos=null;
77                  return;
78              }
79              rot(pos, t);
80              del(pos->ch[t^1], val);
81          }
82          else
83              del(pos->ch[val>pos->val], val);
84          up(pos);
85      }
86  }
87  public:
88  node *rt;
89
90  Treap():rt(null){}
91  inline void insert(int val)
92  {
93      insert(rt, val);
94  }
95  inline void reset()
96  {
97      rec(rt);
98      rt=null;
99  }

```



```

100     inline int sel(int k)
101     {
102         if(k<1 || k>rt->sz)
103             return 0;
104         return sel(rt,rt->sz+1-k);
105     }
106     inline void del(int val)
107     {
108         del(rt,val);
109     }
110     inline int size()
111     {
112         return rt->sz;
113     }
114 }treap[MAXX];
115
116 init:
117 {
118     srand(time(0));
119     null=new node();
120     null->val=0xc0c0c0c0;
121     null->sz=0;
122     null->key=RAND_MAX;
123     null->ch[0]=null->ch[1]=null;
124     for(i=0;i<MAXX;++i)
125         treap[i].rt=null;
126 }

```


Chapter 2

geometry

2.1 3D.cpp

```

1  struct pv
2  {
3      double x,y,z;
4      pv() {}
5      pv(double xx,double yy,double zz):x(xx),y(yy),z(
        zz) {}
6      pv operator -(const pv& b) const
7      {
8          return pv(x-b.x,y-b.y,z-b.z);
9      }
10     pv operator *(const pv& b) const
11     {
12         return pv(y*b.z-z*b.y,z*b.x-x*b.z,x*b.y-y
            *b.x);
13     }
14     double operator &(const pv& b) const
15     {
16         return x*b.x+y*b.y+z*b.z;
17     }
18 };
19
20 //
21 double Norm(pv p)
22 {
23     return sqrt(p&p);
24 }
25
26 // ‘ V t h e t a ‘

```

```

27 pv Trans(pv pa,pv V,double theta)
28 {
29     double s = sin(theta);
30     double c = cos(theta);
31     double x,y,z;
32     x = V.x;
33     y = V.y;
34     z = V.z;
35     pv pp =
36         pv(
37             (x*x*(1-c)+c)*pa.x+(x*y*(1-c)-z*s)*pa.y+(
38                 x*z*(1-c)+y*s)*pa.z,
39             (y*x*(1-c)+z*s)*pa.x+(y*y*(1-c)+c)*pa.y+(
40                 y*z*(1-c)-x*s)*pa.z,
41             (x*z*(1-c)-y*s)*pa.x+(y*z*(1-c)+x*s)*pa.y
42                 +(z*z*(1-c)+c)*pa.z
43         );
44     return pp;
45 }
46 //
47 x=r*sin( )*cos( );
48 y=r*sin( )*sin( );
49 z=r*cos( );
50 r=sqrt(x*2+y*2+z*2);//??
51 r=sqrt(x^2+y^2+z^2);//??
52
53     =atan(y/x);
54     =acos(z/r);
55
56     r    [0,    ]
57         [0,2    ]
58         [0,    ]
59
60     lat1 [-    /2,    /2]
61     lng1 [-    ,    ]
62
63 pv getpv(double lat,double lng,double r)
64 {
65     lat += pi/2;
66     lng += pi;
67     return
68     pv(r*sin(lat)*cos(lng),r*sin(lat)*sin(lng),r*cos(lat)
69         );

```

```

69  }
70
71  //
72
73  #include<stdio>
74  #include<cmath>
75
76  #define MAXX 1111
77
78  char buf[MAXX];
79  const double r=6875.0/2, pi=acos(-1.0);
80  double a,b,c,x1,x2,y2,ans;
81
82  int main()
83  {
84      double y1;
85      while( gets(buf)!=NULL)
86      {
87          gets(buf);
88          gets(buf);
89
90          scanf("%lf^%lf'%lf\" _%s\n",&a,&b,&c,buf);
91          x1=a+b/60+c/3600;
92          x1=x1*pi/180;
93          if(buf[0]=='S')
94              x1=-x1;
95
96          scanf("%s",buf);
97          scanf("%lf^%lf'%lf\" _%s\n",&a,&b,&c,buf);
98          y1=a+b/60+c/3600;
99          y1=y1*pi/180;
100         if(buf[0]=='W')
101             y1=-y1;
102
103         gets(buf);
104
105         scanf("%lf^%lf'%lf\" _%s\n",&a,&b,&c,buf);
106         x2=a+b/60+c/3600;
107         x2=x2*pi/180;
108         if(buf[0]=='S')
109             x2=-x2;
110
111         scanf("%s",buf);
112         scanf("%lf^%lf'%lf\" _%s\n",&a,&b,&c,buf);
113         y2=a+b/60+c/3600;
114         y2=y2*pi/180;

```

```

115         if (buf[0] == 'W')
116             y2 = -y2;
117
118         ans = acos(cos(x1) * cos(x2) * cos(y1 - y2) + sin(x1) * sin(
119             x2)) * r;
120         printf("The distance to the iceberg: %.2lf miles
121             .\n", ans);
122         if (ans + 0.005 < 100)
123             puts("DANGER!");
124     }
125     return 0;
126 }
127
128 inline bool ZERO(const double &a)
129 {
130     return fabs(a) < eps;
131 }
132
133 //
134 inline bool ZERO(pv p)
135 {
136     return (ZERO(p.x) && ZERO(p.y) && ZERO(p.z));
137 }
138
139 //
140 bool LineIntersect(Line3D L1, Line3D L2)
141 {
142     pv s = L1.s - L1.e;
143     pv e = L2.s - L2.e;
144     pv p = s * e;
145     if (ZERO(p))
146         return false; //
147     p = (L2.s - L1.e) * (L1.s - L1.e);
148     return ZERO(p & L2.e); //
149 }
150
151 //
152 bool inter(pv a, pv b, pv c, pv d)
153 {
154     pv ret = (a - b) * (c - d);
155     pv t1 = (b - a) * (c - a);
156     pv t2 = (b - a) * (d - a);
157     pv t3 = (d - c) * (a - c);
158     pv t4 = (d - c) * (b - c);

```

```

159     return sgn(t1&ret)*sgn(t2&ret) < 0 && sgn(t3&ret)*sgn
        (t4&ret) < 0;
160 }
161
162 //
163 bool OnLine(pv p, Line3D L)
164 {
165     return ZERO((p-L.s)*(L.e-L.s));
166 }
167
168 //
169 bool OnSeg(pv p, Line3D L)
170 {
171     return (ZERO((L.s-p)*(L.e-p)) && EQ(Norm(p-L.s)+Norm(
        p-L.e), Norm(L.e-L.s)));
172 }
173
174 //
175 double Distance(pv p, Line3D L)
176 {
177     return (Norm((p-L.s)*(L.e-L.s))/Norm(L.e-L.s));
178 }
179
180 //
181 // [0, ]
182 double Inclination(Line3D L1, Line3D L2)
183 {
184     pv u = L1.e - L1.s;
185     pv v = L2.e - L2.s;
186     return acos( (u & v) / (Norm(u)*Norm(v)) );
187 }

```

2.2 3DCH.cpp

```

1  #include<cstdio>
2  #include<cmath>
3  #include<vector>
4  #include<algorithm>
5
6  #define MAXX 1111
7  #define eps 1e-8
8  #define inf 1e20
9
10 struct pv
11 {
12     double x,y,z;

```

```

13     pv() {}
14     pv(const double &xx, const double &yy, const double &zz
15         ): x(xx), y(yy), z(zz) {}
15     inline pv operator-(const pv &i) const
16     {
17         return pv(x-i.x, y-i.y, z-i.z);
18     }
19     inline pv operator*(const pv &i) const //
20     {
21         return pv(y*i.z-z*i.y, z*i.x-x*i.z, x*i.y-y*i.x);
22     }
23     inline double operator^(const pv &i) const //
24     {
25         return x*i.x+y*i.y+z*i.z;
26     }
27     inline double len()
28     {
29         return sqrt(x*x+y*y+z*z);
30     }
31 };
32
33 struct pla
34 {
35     short a, b, c;
36     bool ok;
37     pla() {}
38     pla(const short &aa, const short &bb, const short &cc):
39         a(aa), b(bb), c(cc), ok(true) {}
39     inline void set();
40     inline void print()
41     {
42         printf("%hd_%hd_%hd\n", a, b, c);
43     }
44 };
45
46 pv pnt[MAXX];
47 std::vector<pla> fac;
48 short to[MAXX][MAXX];
49
50 inline void pla::set()
51 {
52     to[a][b]=to[b][c]=to[c][a]=fac.size();
53 }
54
55 inline double ptof(const pv &p, const pla &f) //
56     ?

```



```

56 {
57     return (pnt[f.b]-pnt[f.a])*(pnt[f.c]-pnt[f.a])^(p-pnt
        [f.a]);
58 }
59
60 inline double vol(const pv &a,const pv &b,const pv &c,
        const pv &d)//          *6
61 {
62     return (b-a)*(c-a)^(d-a);
63 }
64
65 inline double ptof(const pv &p,const short &f) //
        p          f
66 {
67     return fabs(vol(pnt[fac[f].a],pnt[fac[f].b],pnt[fac[f]
        ].c],p)/((pnt[fac[f].b]-pnt[fac[f].a])*(pnt[fac[f]
        ].c]-pnt[fac[f].a])).len());
68 }
69
70 void dfs(const short&,const short&);
71
72 void deal(const short &p,const short &a,const short &b)
73 {
74     if(fac[to[a][b]].ok)
75         if(ptof(pnt[p],fac[to[a][b]])>eps)
76             dfs(p,to[a][b]);
77     else
78     {
79         pla_add(b,a,p);
80         add.set();
81         fac.push_back(add);
82     }
83 }
84
85 void dfs(const short &p,const short &now)
86 {
87     fac[now].ok=false;
88     deal(p, fac[now].b, fac[now].a);
89     deal(p, fac[now].c, fac[now].b);
90     deal(p, fac[now].a, fac[now].c);
91 }
92
93 inline void make()
94 {
95     fac.resize(0);
96     if(n<4)

```

```

97         return;
98
99     for ( i=1; i<n; ++i )
100         if ( (pnt[0] - pnt[i]).len() > eps )
101         {
102             std::swap(pnt[i], pnt[1]);
103             break;
104         }
105     if ( i==n )
106         return;
107
108     for ( i=2; i<n; ++i )
109         if ( ((pnt[0] - pnt[1]) * (pnt[1] - pnt[i])).len() > eps )
110         {
111             std::swap(pnt[i], pnt[2]);
112             break;
113         }
114     if ( i==n )
115         return;
116
117     for ( i=3; i<n; ++i )
118         if ( fabs((pnt[0] - pnt[1]) * (pnt[1] - pnt[2]) ^ (pnt[2] -
119             pnt[i])) > eps )
120         {
121             std::swap(pnt[3], pnt[i]);
122             break;
123         }
124     if ( i==n )
125         return;
126
127     for ( i=0; i<4; ++i )
128     {
129         pla add((i+1)%4, (i+2)%4, (i+3)%4);
130         if ( ptof(pnt[i], add) > 0 )
131             std::swap(add.c, add.b);
132         add.set();
133         fac.push_back(add);
134     }
135     for ( ; i<n; ++i )
136         for ( j=0; j<fac.size(); ++j )
137             if ( fac[j].ok && ptof(pnt[i], fac[j]) > eps )
138             {
139                 dfs(i, j);
140                 break;
141             }

```

```

142     short tmp(fac.size());
143     fac.resize(0);
144     for (i=0; i<tmp; ++i)
145         if (fac[i].ok)
146             fac.push_back(fac[i]);
147 }
148
149 inline pv gc() //
150 {
151     pv re(0,0,0), o(0,0,0);
152     double all(0), v;
153     for (i=0; i<fac.size(); ++i)
154     {
155         v=vol(o, pnt[fac[i].a], pnt[fac[i].b], pnt[fac[i].c
156             ]);
157         re+=(pnt[fac[i].a]+pnt[fac[i].b]+pnt[fac[i].c])
158             *0.25*v;
159         all+=v;
160     }
161     return re*(1/all);
162 }
163
164 inline bool same(const short &s, const short &t) //
165 {
166     pv &a=pnt[fac[s].a], &b=pnt[fac[s].b], &c=pnt[fac[s].c
167         ];
168     return fabs(vol(a,b,c, pnt[fac[t].a]))<eps && fabs(vol
169         (a,b,c, pnt[fac[t].b]))<eps && fabs(vol(a,b,c, pnt[
170             fac[t].c]))<eps;
171 }
172
173 //
174 inline short facetcnt()
175 {
176     short ans=0;
177     for (short i=0; i<fac.size(); ++i)
178     {
179         for (j=0; j<i; ++j)
180             if (same(i, j))
181                 break;
182         if (j==i)
183             ++ans;
184     }
185     return ans;
186 }

```

```

182
183 //
184 inline short trianglecnt()
185 {
186     return fac.size();
187 }
188
189 //
190 inline double area(const pv &a, const pv &b, const pv &c)
191 {
192     return (b-a)*(c-a).len();
193 }
194
195 //
196 inline double area()
197 {
198     double ret(0);
199     for(i=0; i<fac.size(); ++i)
200         ret+=area(pnt[fac[i].a], pnt[fac[i].b], pnt[fac[i].
201                 c]);
202     return ret/2;
203 }
204 //
205 inline double volume()
206 {
207     pv o(0,0,0);
208     double ret(0);
209     for(short i(0); i<fac.size(); ++i)
210         ret+=vol(o, pnt[fac[i].a], pnt[fac[i].b], pnt[fac[i]
211                 ].c]);
212     return fabs(ret/6);
213 }

```

2.3 circle & ploy's area.cpp

```

1 bool InCircle(Point a, double r)
2 {
3     return cmp(a.x*a.x+a.y*a.y, r*r) <= 0;
4     // '
5 }
6
7 double CalcArea(Point a, Point b, double r)
8 {

```

```

9      Point p[4];
10     int tot = 0;
11     p[tot++] = a;
12
13     Point tv = Point(a,b);
14     Line tmp = Line(Point(0,0),Point(tv.y,-tv.x));
15     Point near = LineToLine(Line(a,b),tmp);
16     if (cmp(near.x*near.x+near.y*near.y,r*r) <= 0)
17     {
18         double A,B,C;
19         A = near.x*near.x+near.y*near.y;
20         C = r;
21         B = C*C-A;
22         double tvl = tv.x*tv.x+tv.y*tv.y;
23         double tmp = sqrt(B/tvl); //
24
25         p[tot] = Point(near.x+tmp*tv.x,near.y+tmp
26                        *tv.y);
27         if (OnSeg(Line(a,b),p[tot]) == true)
28             tot++;
29         p[tot] = Point(near.x-tmp*tv.x,near.y-tmp
30                        *tv.y);
31         if (OnSeg(Line(a,b),p[tot]) == true)
32             tot++;
33     }
34     if (tot == 3)
35     {
36         if (cmp(Point(p[0],p[1]).Length(),Point(p
37                [0],p[2]).Length()) > 0)
38             swap(p[1],p[2]);
39     }
40     p[tot++] = b;
41
42     double res = 0.0,theta,a0,a1,sgn;
43     for (int i = 0;i < tot-1;i++)
44     {
45         if (InCircle(p[i],r) == true && InCircle(
46                p[i+1],r) == true)
47         {
48             res += 0.5*xmult(p[i],p[i+1]);
49         }
50         else
51         {
52             a0 = atan2(p[i+1].y,p[i+1].x);
53             a1 = atan2(p[i].y,p[i].x);
54             if (a0 < a1) a0 += 2*pi;

```

```

48             theta = a0-a1;
49             if (cmp(theta,pi) >= 0) theta =
                2*pi-theta;
50             sgn = xmult(p[i],p[i+1])/2.0;
51             if (cmp(sgn,0) < 0) theta = -
                theta;
52             res += 0.5*r*r*theta;
53         }
54     }
55     return res;
56 }
57
58 //
59
60 area2 = 0.0;
61 for (int i = 0; i < resn; i++) //
62     area2 += CalcArea(p[i],p[(i+1)%resn],r);

```

2.4 circle's area.cpp

```

1 //
2 {
3     for (int i = 0; i < n; i++)
4     {
5         scanf("%lf%lf%lf",&c[i].c.x,&c[i].c.y,&c[i].r);
6         del[i] = false;
7     }
8     for (int i = 0; i < n; i++)
9         if (del[i] == false)
10        {
11            if (c[i].r == 0.0)
12                del[i] = true;
13            for (int j = 0; j < n; j++)
14                if (i != j)
15                    if (del[j] == false)
16                        if (cmp(Point(c[i].c,c[j].c).Len
                            ()+c[i].r,c[j].r) <= 0)
17                            del[i] = true;
18        }
19     tn = n;
20     n = 0;
21     for (int i = 0; i < tn; i++)
22         if (del[i] == false)
23             c[n++] = c[i];
24 }

```

```

25
26 //ans[i]
27 const double pi = acos(-1.0);
28 const double eps = 1e-8;
29 struct Point
30 {
31     double x,y;
32     Point() {}
33     Point(double _x, double _y)
34     {
35         x = _x;
36         y = _y;
37     }
38     double Length()
39     {
40         return sqrt(x*x+y*y);
41     }
42 };
43 struct Circle
44 {
45     Point c;
46     double r;
47 };
48 struct Event
49 {
50     double tim;
51     int typ;
52     Event() {}
53     Event(double _tim, int _typ)
54     {
55         tim = _tim;
56         typ = _typ;
57     }
58 };
59
60 int cmp(const double& a, const double& b)
61 {
62     if (fabs(a-b) < eps) return 0;
63     if (a < b) return -1;
64     return 1;
65 }
66
67 bool Eventcmp(const Event& a, const Event& b)
68 {
69     return cmp(a.tim, b.tim) < 0;
70 }

```

```

71
72 double Area(double theta,double r)
73 {
74     return 0.5*r*r*(theta-sin(theta));
75 }
76
77 double xmult(Point a,Point b)
78 {
79     return a.x*b.y-a.y*b.x;
80 }
81
82 int n,cur,tote;
83 Circle c[1000];
84 double ans[1001],pre[1001],AB,AC,BC,theta,fai,a0,a1;
85 Event e[4000];
86 Point lab;
87
88 int main()
89 {
90     while (scanf("%d",&n) != EOF)
91     {
92         for (int i = 0;i < n;i++)
93             scanf("%lf%lf%lf",&c[i].c.x,&c[i].c.y,&c[i].r
94                 );
95         for (int i = 1;i <= n;i++)
96             ans[i] = 0.0;
97         for (int i = 0;i < n;i++)
98         {
99             tote = 0;
100             e[tote++] = Event(-pi,1);
101             e[tote++] = Event(pi,-1);
102             for (int j = 0;j < n;j++)
103                 if (j != i)
104                 {
105                     lab = Point(c[j].c.x-c[i].c.x,c[j].c.
106                         y-c[i].c.y);
107                     AB = lab.Length();
108                     AC = c[i].r;
109                     BC = c[j].r;
110                     if (cmp(AB+AC,BC) <= 0)
111                     {
112                         e[tote++] = Event(-pi,1);
113                         e[tote++] = Event(pi,-1);
114                         continue;
115                     }
116                 }
117             if (cmp(AB+BC,AC) <= 0) continue;

```



```

115         if (cmp(AB,AC+BC) > 0) continue;
116         theta = atan2(lab.y,lab.x);
117         fai = acos((AC*AC+AB*AB-BC*BC)/(2.0*
            AC*AB));
118         a0 = theta-fai;
119         if (cmp(a0,-pi) < 0) a0 += 2*pi;
120         a1 = theta+fai;
121         if (cmp(a1,pi) > 0) a1 -= 2*pi;
122         if (cmp(a0,a1) > 0)
123         {
124             e[tote++] = Event(a0,1);
125             e[tote++] = Event(pi,-1);
126             e[tote++] = Event(-pi,1);
127             e[tote++] = Event(a1,-1);
128         }
129         else
130         {
131             e[tote++] = Event(a0,1);
132             e[tote++] = Event(a1,-1);
133         }
134     }
135     sort(e,e+tote,Eventcmp);
136     cur = 0;
137     for (int j = 0;j < tote;j++)
138     {
139         if (cur != 0 && cmp(e[j].tim,pre[cur]) !=
            0)
140         {
141             ans[cur] += Area(e[j].tim-pre[cur],c[
                i].r);
142             ans[cur] += xmult(Point(c[i].c.x+c[i]
                ].r*cos(pre[cur]),c[i].c.y+c[i].r*
                sin(pre[cur])),
143                 Point(c[i].c.x+c[i].r*cos(e[j]
                ].tim),c[i].c.y+c[i].r*sin
                (e[j].tim)))/2.0;
144         }
145         cur += e[j].typ;
146         pre[cur] = e[j].tim;
147     }
148 }
149 for (int i = 1;i < n;i++)
150     ans[i] -= ans[i+1];
151 for (int i = 1;i <= n;i++)
152     printf("%d] _=%.3f\n",i,ans[i]);
153 }
```

```

154     return 0;
155 }

```

2.5 circle.cpp

```

1  //
2  #include<cstdio>
3  #include<cmath>
4  #include<vector>
5  #include<algorithm>
6
7  #define MAXX 333
8  #define eps 1e-8
9
10 struct pv
11 {
12     double x,y;
13     pv() {}
14     pv(const double &xx,const double &yy):x(xx),y(yy) {}
15     inline pv operator-(const pv &i) const
16     {
17         return pv(x-i.x,y-i.y);
18     }
19     inline double cross(const pv &i) const
20     {
21         return x*i.y-y*i.x;
22     }
23     inline void print()
24     {
25         printf("%lf_%lf\n",x,y);
26     }
27     inline double len()
28     {
29         return sqrt(x*x+y*y);
30     }
31 }pnt[MAXX];
32
33 struct node
34 {
35     double k;
36     bool flag;
37     node() {}
38     node(const double &kk,const bool &ff):k(kk),flag(ff)
39     {}
40     inline bool operator<(const node &i) const
41     {

```

```

41         return k<i.k;
42     }
43 };
44
45 std::vector<node>alpha;
46
47 short n,i,j,k,l;
48 short ans,sum;
49 double R=2;
50 double theta,phi,d;
51 const double pi(acos(-1.0));
52
53 int main()
54 {
55     alpha.reserve(MAXX<<1);
56     while(scanf("%hd",&n),n)
57     {
58         for(i=0;i<n;++i)
59             scanf("%lf_%lf",&pnt[i].x,&pnt[i].y);
60         ans=0;
61         for(i=0;i<n;++i)
62         {
63             alpha.resize(0);
64             for(j=0;j<n;++j)
65                 if(i!=j)
66                 {
67                     if((d=(pnt[i]-pnt[j]).len())>R)
68                         continue;
69                     if((theta=atan2(pnt[j].y-pnt[i].y,pnt
70                                     [j].x-pnt[i].x))<0)
71                         theta+=2*pi;
72                     phi=acos(d/R);
73                     alpha.push_back(node(theta-phi,true));
74                     ;
75                     alpha.push_back(node(theta+phi,false));
76                 }
77             std::sort(alpha.begin(),alpha.end());
78             for(j=0;j<alpha.size();++j)
79             {
80                 if(alpha[j].flag)
81                     ++sum;
82                 else
83                     --sum;
84             }
85             ans=std::max(ans,sum);
86         }
87     }

```

```

84         }
85         printf("%hd\n",ans+1);
86     }
87     return 0;
88 }
89
90 //
91
92 #include<stdio>
93 #include<cmath>
94
95 #define MAXX 511
96 #define eps 1e-8
97
98 struct pv
99 {
100     double x,y;
101     pv() {}
102     pv(const double &xx,const double &yy):x(xx),y(yy) {}
103     inline pv operator-(const pv &i) const
104     {
105         return pv(x-i.x,y-i.y);
106     }
107     inline pv operator+(const pv &i) const
108     {
109         return pv(x+i.x,y+i.y);
110     }
111     inline double cross(const pv &i) const
112     {
113         return x*i.y-y*i.x;
114     }
115     inline double len()
116     {
117         return sqrt(x*x+y*y);
118     }
119     inline pv operator/(const double &a) const
120     {
121         return pv(x/a,y/a);
122     }
123     inline pv operator*(const double &a) const
124     {
125         return pv(x*a,y*a);
126     }
127 }pnt[MAXX],o,tl,lt,aa,bb,cc,dd;
128
129 short n,i,j,k,l;

```

```

130 double r,u;
131
132 inline pv ins(const pv &a1,const pv &a2,const pv &b1,
    const pv &b2)
133 {
134     tl=a2-a1;
135     lt=b2-b1;
136     u=(b1-a1).cross(lt)/(tl).cross(lt);
137     return a1+tl*u;
138 }
139
140 inline pv get(const pv &a,const pv &b,const pv &c)
141 {
142     aa=(a+b)/2;
143     bb.x=aa.x-a.y+b.y;
144     bb.y=aa.y+a.x-b.x;
145     cc=(a+c)/2;
146     dd.x=cc.x-a.y+c.y;
147     dd.y=cc.y+a.x-c.x;
148     return ins(aa,bb,cc,dd);
149 }
150
151 int main()
152 {
153     while( scanf("%hd",&n),n)
154     {
155         for(i=0;i<n;++i)
156             scanf("%lf %lf",&pnt[i].x,&pnt[i].y);
157         o=pnt[0];
158         r=0;
159         for(i=1;i<n;++i)
160             if((pnt[i]-o).len()>r+eps)
161             {
162                 o=pnt[i];
163                 r=0;
164                 for(j=0;j<i;++j)
165                     if((pnt[j]-o).len()>r+eps)
166                     {
167                         o=(pnt[i]+pnt[j])/2;
168                         r=(o-pnt[j]).len();
169                         for(k=0;k<j;++k)
170                             if((o-pnt[k]).len()>r+eps)
171                             {
172                                 o=get(pnt[i],pnt[j],pnt[k]);
173                                 r=(o-pnt[i]).len();

```

```

174         }
175     }
176 }
177     printf("%.2lf_%.2lf_%.2lf\n", o.x, o.y, r);
178 }
179 return 0;
180 }
181
182 //
183 double dis(int x, int y)
184 {
185     return sqrt((double)(x*x+y*y));
186 }
187
188 double area(int x1, int y1, int x2, int y2, double r1, double
189             r2)
189 {
190     double s = dis(x2-x1, y2-y1);
191     if(r1+r2 < s) return 0;
192     else if(r2-r1 > s) return PI*r1*r1;
193     else if(r1-r2 > s) return PI*r2*r2;
194     double q1 = acos((r1*r1+s*s-r2*r2)/(2*r1*s));
195     double q2 = acos((r2*r2+s*s-r1*r1)/(2*r2*s));
196     return (r1*r1*q1+r2*r2*q2-r1*s*sin(q1));
197 }
198
199 //
200 {
201     for (int i = 0; i < 3; i++)
202         scanf("%lf%lf", &p[i].x, &p[i].y);
203     tp = pv((p[0].x+p[1].x)/2, (p[0].y+p[1].y)/2);
204     l[0] = Line(tp, pv(tp.x-(p[1].y-p[0].y), tp.y+(p[1].x-p
205                    [0].x)));
206     tp = pv((p[0].x+p[2].x)/2, (p[0].y+p[2].y)/2);
207     l[1] = Line(tp, pv(tp.x-(p[2].y-p[0].y), tp.y+(p[2].x-p
208                    [0].x)));
209     tp = LineToLine(l[0], l[1]);
210     r = pv(tp, p[0]).Length();
211     printf("%.6f, %.6f, %.6f\n", tp.x, tp.y, r);
212 }
213
214 //
215 {
216     for (int i = 0; i < 3; i++)
217         scanf("%lf%lf", &p[i].x, &p[i].y);
218     if (xmult(pv(p[0], p[1]), pv(p[0], p[2])) < 0)

```

```

217         swap(p[1], p[2]);
218     for (int i = 0; i < 3; i++)
219         len[i] = pv(p[i], p[(i+1)%3]).Length();
220     tr = (len[0]+len[1]+len[2])/2;
221     r = sqrt((tr-len[0])*(tr-len[1])*(tr-len[2])/tr);
222     for (int i = 0; i < 2; i++)
223     {
224         v = pv(p[i], p[i+1]);
225         tv = pv(-v.y, v.x);
226         tr = tv.Length();
227         tv = pv(tv.x*r/tr, tv.y*r/tr);
228         tp = pv(p[i].x+tv.x, p[i].y+tv.y);
229         l[i].s = tp;
230         tp = pv(p[i+1].x+tv.x, p[i+1].y+tv.y);
231         l[i].e = tp;
232     }
233     tp = LineToLine(l[0], l[1]);
234     printf("(%.6f,%.6f,%.6f)\n", tp.x, tp.y, r);
235 }

```

2.6 closest point pair.cpp

```

1 // 1
2
3 struct Point {double x, y;} p[10], t[10];
4 bool cmpx(const Point& i, const Point& j) {return i.x < j
    .x;}
5 bool cmpy(const Point& i, const Point& j) {return i.y < j
    .y;}
6
7 double DnC(int L, int R)
8 {
9     if (L >= R) return 1e9; //
10
11     /*
12         D i v i d e
13         */
14
15     int M = (L + R) / 2;
16
17     /* C o n q u e r */
18
19     double d = min(DnC(L, M), DnC(M+1, R));
20     // if (d == 0.0) return d; //

```

```

20      /*
           M e r g e
           (NlogN)
        */
21
22      int N = 0; //
23      for (int i=M; i>=L && p[M].x - p[i].x < d; --i) t[N
           ++] = p[i];
24      for (int i=M+1; i<=R && p[i].x - p[M].x < d; ++i) t[N
           ++] = p[i];
25      sort(t, t+N, cmpy); // Quicksort O(NlogN)
26
27      /* M e r g e
           */
28
29      for (int i=0; i<N-1; ++i)
30          for (int j=1; j<=2 && i+j<N; ++j)
31              d = min(d, distance(t[i], t[i+j]));
32
33      return d;
34  }
35
36  double closest_pair()
37  {
38      sort(p, p+10, cmpx);
39      return DnC(0, N-1);
40  }
41
42
43  // 2
44
45  struct Point {double x, y;} p[10], t[10];
46  bool cmpx(const Point& i, const Point& j) {return i.x < j
           .x;}
47  bool cmpy(const Point& i, const Point& j) {return i.y < j
           .y;}
48
49  double DnC(int L, int R)
50  {
51      if (L >= R) return 1e9; //
52
53      /*
           D i v i d e
           */
54
55      int M = (L + R) / 2;

```



```

56
57      //
                                     X
58      double x = p[M].x;
59
60      /*  C o n q u e r                                     */
61
62      //
                                     Y
63      double d = min(DnC(L,M) , DnC(M+1,R) );
64      //  if (d == 0.0) return d; //
65
66      /*
          M e r g e
          (N)      */
                                     Y
                                     O
67
68      //
                                     Y
69
70      int N = 0; //
71      for (int i=0; i<=M; ++i)
72          if (x - p[i].x < d)
73              t[N++] = p[i];
74      //
                                     Y
75
76      int P = N; // P
77      for (int i=M+1; i<=R; ++i)
78          if (p[i].x - x < d)
79              t[N++] = p[i];
80      //      Y      M e r g e
          S o r t
81      inplace_merge(t, t+P, t+N, cmp);
82
83      /*  M e r g e                                     O (N)
          */
84
85      for (int i=0; i<N; ++i)
86          for (int j=1; j<=2 && i+j<N; ++j)
87              d = min(d, distance(t[i], t[i+j]));
88
89      /*  M e r g e      Y      O (N)
          */
90

```

```

91      //
                                           M e r g e
                                           S o r t
92      inplace_merge(p+L, p+M+1, p+R+1, cmpy);
93
94      return d;
95  }
96
97  double closest_pair()
98  {
99      sort(p, p+10, cmpx);
100     return DnC(0, N-1);
101 }
102
103 //mzry
104 //
105 double calc_dis(Point &a ,Point &b) {
106     return sqrt((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-
        b.y));
107 }
108 //
109 bool operator<(const Point &a ,const Point &b) {
110     if(a.y != b.y) return a.x < b.x;
111     return a.x < b.x;
112 }
113 double Gao(int l ,int r ,Point pnts[]) {
114     double ret = inf;
115     if(l == r) return ret;
116     if(l+1 == r) {
117         ret = min(calc_dis(pnts[l], pnts[l+1]) ,
            ret);
118         return ret;
119     }
120     if(l+2 == r) {
121         ret = min(calc_dis(pnts[l], pnts[l+1]) ,
            ret);
122         ret = min(calc_dis(pnts[l], pnts[l+2]) ,
            ret);
123         ret = min(calc_dis(pnts[l+1], pnts[l+2]) ,
            ret);
124         return ret;
125     }
126
127     int mid = l+r>>1;
128     ret = min (ret ,Gao(l ,mid ,pnts));
129     ret = min (ret , Gao(mid+1, r ,pnts));

```

```

130
131     for(int c = 1 ; c<=r; c++)
132         for(int d = c+1; d <=c+7 && d<=r; d++) {
133             ret = min(ret , calc_dis(pnts[c],
134                                     pnts[d]));
135         }
136     return ret;
137 }
138 //
139 #include <iostream>
140 #include <cstdio>
141 #include <cstring>
142 #include <map>
143 #include <vector>
144 #include <cmath>
145 #include <algorithm>
146 #define Point pair<double,double>
147 using namespace std;
148
149 const int step[9][2] =
150     {{-1,-1},{-1,0},{-1,1},{0,-1},{0,0},{0,1},{1,-1},{1,0},{1,1}};
151
152 int n,x,y,nx,ny;
153 map<pair<int,int>,vector<Point > > g;
154 vector<Point > tmp;
155 Point p[20000];
156 double tx,ty,ans,nowans;
157 vector<Point >::iterator it,op,ed;
158 pair<int,int> gird;
159 bool flag;
160
161 double Dis(Point p0,Point p1)
162 {
163     return sqrt((p0.first-p1.first)*(p0.first-p1.
164                                     first)+
165                 (p0.second-p1.second)*(p0
166                                     .second-p1.second));
167 }
168
169 double CalcDis(Point p0,Point p1,Point p2)
170 {
171     return Dis(p0,p1)+Dis(p0,p2)+Dis(p1,p2);
172 }
173
174 void build(int n,double w)

```

```

171 {
172     g.clear();
173     for (int i = 0; i < n; i++)
174         g[make_pair((int) floor(p[i].first/w), (int)
                    floor(p[i].second/w))].push_back(p[i]
                    )];
175 }
176
177 int main()
178 {
179     int t;
180     scanf("%d",&t);
181     for (int ft = 1; ft <= t; ft++)
182     {
183         scanf("%d",&n);
184         for (int i = 0; i < n; i++)
185         {
186             scanf("%lf%lf",&tx,&ty);
187             p[i] = make_pair(tx,ty);
188         }
189         random_shuffle(p,p+n);
190         ans = CalcDis(p[0],p[1],p[2]);
191         build(3,ans/2.0);
192         for (int i = 3; i < n; i++)
193         {
194             x = (int) floor(2.0*p[i].first/ans
                            );
195             y = (int) floor(2.0*p[i].second/
                            ans);
196             tmp.clear();
197             for (int k = 0; k < 9; k++)
198             {
199                 nx = x+step[k][0];
200                 ny = y+step[k][1];
201                 gird = make_pair(nx,ny);
202                 if (g.find(gird) != g.end
                    ())
203                 {
204                     op = g[gird].
                        begin();
205                     ed = g[gird].end
                        ();
206                     for (it = op; it
                        != ed; it++)
207                         tmp.
                            push_back

```

```

208                                     (*it);
209                                 }
210                             }
211                             flag = false;
212                             for (int j = 0; j < tmp.size(); j
                                ++))
213                                 for (int k = j+1; k < tmp.
                                size(); k++)
214                                 {
215                                     nowans = CalcDis(
216                                         p[i], tmp[j],
217                                         tmp[k]);
218                                     if (nowans < ans)
219                                     {
220                                         ans =
221                                             nowans
222                                             ;
223                                         flag =
224                                             true;
225                                     }
226                                 }
227                             if (flag == true)
228                                 build(i+1, ans/2.0);
229                             else
230                                 g[make_pair((int) floor
231                                     (2.0*p[i].first/ans), (
232                                         int) floor (2.0*p[i].
233                                             second/ans))]
234                                     .
235                                     push_back(p[i]);
236                         }
237                     printf("%.3f\n", ans);
238 }

```

2.7 half-plane intersection.cpp

```

1 // a b c
2 inline pv ins(const pv &p1, const pv &p2)
3 {
4     u=fabs(a*p1.x+b*p1.y+c);
5     v=fabs(a*p2.x+b*p2.y+c);
6     return pv((p1.x*v+p2.x*u)/(u+v), (p1.y*v+p2.y*u)/(u+v)
7 );
8 }

```

```

9  inline void get(const pv& p1,const pv& p2,double & a,
    double & b,double & c)
10 {
11     a=p2.y-p1.y;
12     b=p1.x-p2.x;
13     c=p2.x*p1.y-p2.y*p1.x;
14 }
15
16 inline pv ins(const pv &x,const pv &y)
17 {
18     get(x,y,d,e,f);
19     return pv((b*f-c*e)/(a*e-b*d),(a*f-c*d)/(b*d-a*e));
20 }
21
22 std::vector<pv>p[2];
23 int main()
24 {
25     k=0;
26     p[k].resize(0);
27     p[k].push_back(pv(-inf,inf));
28     p[k].push_back(pv(-inf,-inf));
29     p[k].push_back(pv(inf,-inf));
30     p[k].push_back(pv(inf,inf));
31     for(i=0;i<n;++i)
32     {
33         get(pnt[i],pnt[(i+1)%n],a,b,c);
34         c+=the*sqrt(a*a+b*b);
35         p[!k].resize(0);
36         for(l=0;l<p[k].size();++l)
37             if(a*p[k][l].x+b*p[k][l].y+c<eps)
38                 p[!k].push_back(p[k][l]);
39         else
40         {
41             m=(l+p[k].size()-1)%p[k].size();
42             if(a*p[k][m].x+b*p[k][m].y+c<-eps)
43                 p[!k].push_back(ins(p[k][m],p[k][l]));
44             ;
45             m=(l+1)%p[k].size();
46             if(a*p[k][m].x+b*p[k][m].y+c<-eps)
47                 p[!k].push_back(ins(p[k][m],p[k][l]));
48             ;
49         }
50         k=!k;
51         if(p[k].empty())
52             break;
53     }
54 }

```

```

52      //      p [k]
53      return p[k].empty();
54  }
55
56  //
57  //
58
59  inline pv ins(const pv &a, const pv &b)
60  {
61      u=fabs(ln.cross(a-pnt[i]));
62      v=fabs(ln.cross(b-pnt[i])+u);
63      tl=b-a;
64      return pv(u*tl.x/v+a.x,u*tl.y/v+a.y);
65  }
66
67  int main()
68  {
69      j=0;
70      for(i=0;i<n;++i)
71      {
72          ln=pnt[(i+1)%n]-pnt[i];
73          p[!j].resize(0);
74          for(k=0;k<p[j].size();++k)
75              if(ln.cross(p[j][k]-pnt[i])<=0)
76                  p[!j].push_back(p[j][k]);
77          else
78          {
79              l=(k-1+p[j].size())%p[j].size();
80              if(ln.cross(p[j][l]-pnt[i])<0)
81                  p[!j].push_back(ins(p[j][k],p[j][l]));
82              ;
83              l=(k+1)%p[j].size();
84              if(ln.cross(p[j][l]-pnt[i])<0)
85                  p[!j].push_back(ins(p[j][k],p[j][l]));
86              ;
87          }
88          j=!j;
89      }
90      //      p [j]
91  }
92
93  //mrzy
94
95  bool HPIcmp(Line a, Line b)
96  {
97      if (fabs(a.k - b.k) > eps)

```

```

96         return a.k < b.k;
97     return ((a.s - b.s) * (b.e-b.s)) < 0;
98 }
99
100 Line Q[100];
101
102 void HPI(Line line[], int n, Point res[], int &resn)
103 {
104     int tot = n;
105     std::sort(line, line + n, HPIcmp);
106     tot = 1;
107     for (int i = 1; i < n; i++)
108         if (fabs(line[i].k - line[i - 1].k) > eps)
109             line[tot++] = line[i];
110     int head = 0, tail = 1;
111     Q[0] = line[0];
112     Q[1] = line[1];
113     resn = 0;
114     for (int i = 2; i < tot; i++)
115     {
116         if (fabs((Q[tail].e-Q[tail].s)*(Q[tail - 1].e-Q[
117             tail - 1].s)) < eps || fabs((Q[head].e-Q[head
118             ].s)*(Q[head + 1].e-Q[head + 1].s)) < eps)
119             return;
120         while (head < tail && (((Q[tail]&Q[tail - 1]) -
121             line[i].s) * (line[i].e-line[i].s)) > eps)
122             --tail;
123         while (head < tail && (((Q[head]&Q[head + 1]) -
124             line[i].s) * (line[i].e-line[i].s)) > eps)
125             ++head;
126         Q[++tail] = line[i];
127     }
128     while (head < tail && (((Q[tail]&Q[tail - 1]) - Q[
129         head].s) * (Q[head].e-Q[head].s)) > eps)
130         tail--;
131     while (head < tail && (((Q[head]&Q[head + 1]) - Q[
132         tail].s) * (Q[tail].e-Q[tail].s)) > eps)
133         head++;
134     if (tail <= head + 1)
135         return;
136     for (int i = head; i < tail; i++)
137         res[resn++] = Q[i] & Q[i + 1];
138     if (head < tail + 1)
139         res[resn++] = Q[head] & Q[tail];
140 }

```


2.8 kdtree.cpp

```

1  #include <iostream>
2  #include <cstdio>
3  #include <cstdlib>
4  #include <algorithm>
5  #include <stack>
6  #include <algorithm>
7  using namespace std;
8  #define MAXN 100010
9  typedef long long ll;
10 struct Point{
11     ll x,y;
12     void operator =(const Point &p){
13         x=p.x; y=p.y;
14     }
15     ll dis(const Point &a){
16         return (x-a.x)*(x-a.x)+(y-a.y)*(y-a.y);
17     }
18 }point[MAXN],pp[MAXN];
19
20 struct Node{
21     int split; //{0,1}
22                                     x                                1                                y
23
24     Point p; //
25 }tree[MAXN*4];
26
27 bool cmpx(const Point &a,const Point &b)
28 {
29     return a.x<b.x;
30 }
31
32 bool cmpy(const Point &a,const Point &b)
33 {
34     return a.y<b.y;
35 }
36
37 void initTree(int x,int y,int split,int pos)
38 {
39     if(y<x) return ;
40     int mid=(x+y)>>1;
41     random_shuffle(point+x,point+y);
42     if(split==0) nth_element(point+x,point+mid,point+y+1,
43                             cmpx);

```

```

41     else nth_element ( point+x, point+mid, point+y+1, cmpy );
42     tree [ pos ]. split=split ;
43     tree [ pos ]. p=point [ mid ];
44     initTree ( x, mid-1, ( split ^1 ), 2*pos );
45     initTree ( mid+1, y, ( split ^1 ), 2*pos+1 );
46 }
47
48 ll ans;
49 void insert ( int x, int y, Point &p, int pos )
50 {
51     if ( y < x ) return ;
52     int mid = ( x+y ) >> 1;
53     ll temp = p. dis ( tree [ pos ]. p );
54     if ( temp != 0 ) ans = min ( ans, temp );
55     if ( tree [ pos ]. split == 0 ) {
56         if ( p.x <= tree [ pos ]. p.x ) {
57             insert ( x, mid-1, p, 2*pos );
58             if ( ans >= ( p.x - tree [ pos ]. p.x ) * ( p.x - tree [ pos ]. p.
59                 x ) )
60                 insert ( mid+1, y, p, 2*pos+1 );
61         }
62         else {
63             insert ( mid+1, y, p, 2*pos+1 );
64             if ( ans >= ( p.x - tree [ pos ]. p.x ) * ( p.x - tree [ pos ]. p.
65                 x ) )
66                 insert ( x, mid-1, p, 2*pos );
67         }
68     }
69     else {
70         if ( p.y <= tree [ pos ]. p.y ) {
71             insert ( x, mid-1, p, 2*pos );
72             if ( ans >= ( p.y - tree [ pos ]. p.y ) * ( p.y - tree [ pos ]. p.
73                 y ) )
74                 insert ( mid+1, y, p, 2*pos+1 );
75         }
76         else {
77             insert ( mid+1, y, p, 2*pos+1 );
78             if ( ans >= ( p.y - tree [ pos ]. p.y ) * ( p.y - tree [ pos ]. p.
79                 y ) )
80                 insert ( x, mid-1, p, 2*pos );
81         }
82     }
83 }
84 int main ( )

```

```

83 {
84     int cases , n;
85     scanf ("%d" , &cases );
86     while ( cases -- )
87     {
88         scanf ("%d" , &n );
89         for ( int i = 1 ; i <= n ; i ++ ) {
90             scanf ("%I64d%I64d" , &pp [ i ] . x , &pp [ i ] . y );
91             point [ i ] = pp [ i ];
92         }
93         initTree ( 1 , n , 0 , 1 );
94         for ( int i = 1 ; i <= n ; i ++ ) {
95             ans = 1LL < 62;
96             insert ( 1 , n , pp [ i ] , 1 );
97             printf ("%I64d\n" , ans );
98         }
99     }
100     return 0;
101 }

```

2.9 others

```

1  eps
2
3      s q r t ( a ) ,  a s i n ( a ) ,  a c o s ( a )
          a
-1e-12      s q r t ( a )
          0      a
,  a s i n ( a )  a c o s ( a )
          a

4
5
:005 ,      0 :01
          0 :005000000001(
          0 :004999999999(
p r i n t f ( "% . 2 1 f " ,  a )

6      a      a + eps ,      a - eps
7
8      -0.000
9
10     d o u b l e
11
12  a==b  fabs ( a - b ) < eps
13  a!=b  fabs ( a - b ) > eps

```

```

14  a<b      a+eps<b
15  a<=b     a<b+eps
16  a>b      a>b+eps
17  a>=b     a+eps>b
18
19
20
21  cos/sin/tan
22  acos      [-1,+1]          [0, ]
23  asin      [-1,+1]          [- /2,+ /2]
24  atan      [- /2,+ /2]
25  atan2     (y,x) (          ),      t a n (y/x),[- ,+ ]
           x y
26
27  other
28
29  log                (ln)
30  log10
31  ceil
32  floor
33
34  round
35
36  cpp:
37  java: add 0.5,then floor
38  cpp:
39
           4
40
           6
41
           5
           0
42
           5
           5
           0

```

2.10 Pick's theorem

```

1  A:
2  i:
3  b:
4  A = i + b/2 - 1
5
6
7

```

8 $A = 2i + b - 2$

2.11 PointInPoly.cpp

```

1  /*
2
3  p o l y , 3
4
5  0 — p o l y
6  1 — p o l y
7  2 — p o l y
8  */
9
10 int inPoly(pv p,pv poly[], int n)
11 {
12     int i, count;
13     Line ray, side;
14
15     count = 0;
16     ray.s = p;
17     ray.e.y = p.y;
18     ray.e.x = -1; //—
19                     I N F
20
21     for (i = 0; i < n; i++)
22     {
23         side.s = poly[i];
24         side.e = poly[(i+1)%n];
25
26         if(OnSeg(p, side))
27             return 1;
28
29         // s i d e x
30         if (side.s.y == side.e.y)
31             continue;
32
33         if (OnSeg(side.s, ray))
34         {
35             if (side.s.y > side.e.y)
36                 count++;
37         }
38         else
39         {
40             if (OnSeg(side.e, ray))
41             {
42                 if (side.e.y > side.s.y)
43                     count++;

```

```

42         }
43         else
44             if (inter(ray, side))
45                 count++;
46     }
47     return ((count % 2 == 1) ? 0 : 2);
48 }

```

2.12 rotating caliper.cpp

```

1  //
2
3  l=ans=0;
4  for ( i=0; i<n; ++i )
5  {
6      tl=pnt [ ( i+1)%n ]-pnt [ i ];
7      while ( abs ( tl . cross ( pnt [ ( l+1)%n ]-pnt [ i ] ) ) > abs ( tl . cross
8              ( pnt [ l ]-pnt [ i ] ) ) )
9          l=(l+1)%n;
10     ans=std::max ( ans, std::max ( dist ( pnt [ l ], pnt [ i ] ), dist (
11         pnt [ l ], pnt [ ( i+1)%n ] ) ) );
12 }
13 return ans;
14
15 //
16 int main ()
17 {
18     sq=sp=0;
19     for ( i=1; i<ch [ 1 ]. size (); ++i )
20         if ( ch [ 1 ] [ sq ] < ch [ 1 ] [ i ] )
21             sq=i;
22     tp=sp;
23     tq=sq;
24     ans=(ch [ 0 ] [ sp ]-ch [ 1 ] [ sq ] ). len ();
25     do
26     {
27         a1=ch [ 0 ] [ sp ];
28         a2=ch [ 0 ] [ ( sp+1)%ch [ 0 ]. size () ];
29         b1=ch [ 1 ] [ sq ];
30         b2=ch [ 1 ] [ ( sq+1)%ch [ 1 ]. size () ];
31         tpv=b1-(b2-a1);
32         tpv.x = b1.x - (b2.x - a1.x);
33         tpv.y = b1.y - (b2.y - a1.y);
34         len=(tpv-a1).cross(a2-a1);
35         if ( fabs ( len ) < eps )
36             {

```

```

35         ans=std::min(ans,p2l(a1,b1,b2));
36         ans=std::min(ans,p2l(a2,b1,b2));
37         ans=std::min(ans,p2l(b1,a1,a2));
38         ans=std::min(ans,p2l(b2,a1,a2));
39         sp=(sp+1)%ch[0].size();
40         sq=(sq+1)%ch[1].size();
41     }
42     else
43         if(len<=eps)
44         {
45             ans=std::min(ans,p2l(b1,a1,a2));
46             sp=(sp+1)%ch[0].size();
47         }
48         else
49         {
50             ans=std::min(ans,p2l(a1,b1,b2));
51             sq=(sq+1)%ch[1].size();
52         }
53     }while(tp!=sp || tq!=sq);
54     return ans;
55 }
56
57 //                                     by mzry
58 inline void solve()
59 {
60     resa = resb = 1e100;
61     double dis1,dis2;
62     Point xp[4];
63     Line l[4];
64     int a,b,c,d;
65     int sa,sb,sc,sd;
66     a = b = c = d = 0;
67     sa = sb = sc = sd = 0;
68     Point va,vb,vc,vd;
69     for (a = 0; a < n; a++)
70     {
71         va = Point(p[a],p[(a+1)%n]);
72         vc = Point(-va.x,-va.y);
73         vb = Point(-va.y,va.x);
74         vd = Point(-vb.x,-vb.y);
75         if (sb < sa)
76         {
77             b = a;
78             sb = sa;
79         }
80         while (xmult(vb,Point(p[b],p[(b+1)%n])) < 0)

```

```

81      {
82          b = (b+1)%n;
83          sb++;
84      }
85      if (sc < sb)
86      {
87          c = b;
88          sc = sb;
89      }
90      while (xmult(vc, Point(p[c], p[(c+1)%n])) < 0)
91      {
92          c = (c+1)%n;
93          sc++;
94      }
95      if (sd < sc)
96      {
97          d = c;
98          sd = sc;
99      }
100     while (xmult(vd, Point(p[d], p[(d+1)%n])) < 0)
101     {
102         d = (d+1)%n;
103         sd++;
104     }
105
106     // '      p[a], p[b], p[c], p[d]      '
107     sa++;
108 }
109 }
110
111 //
112
113
114
115
116
117
118
119 1      P      Q      y

```

$$\begin{array}{l}
 P = \{ p(1), \dots, p(m) \} \quad Q = \{ q \\
 (1), \dots, q(n) \} \quad (p(i), q(j)) \\
 P \quad Q
 \end{array}$$

$$\begin{array}{l}
 (p(i), q(j)) \\
 p(i-1), p(i+1), q(j-1), q(j+1) \quad (p(i), q(j))
 \end{array}$$


```

120  2
121  3      x
                                     (p(i), q(j))
122  4      (p(i), q(j))
      p(i-1), p(i+1), q(j-1), q(j+1)
      (p(i), q(j))
123  5
      3      4
124  6
125
126
      1      5      6      O
      (N)      N
127
128
129
130  //
131  1      P      y      y
      yminP      Q      y
      y m a x Q
132  2      LP      LQ      yminP      ymaxQ
      LP      LQ
      yminP      ymaxQ
133  3      p(i)= yminP      q(j)= ymaxQ      (p(i), q(j))
      p(i-1),p(i+1)      (p(i), q(j))
      q(j-1),q(j+1)
      (p(i), q(j))      C S
134  4

```

```

135 5

136 6                                4      5
                                (yminP ,ymaxQ)
137 7      C S
138
139 //      /      /
140 1      xminP  xmaxP  yminP  ymaxP
141 2                                P
142 3

143 4

144 5      /

145 6      4      5
                                9 0
146 7

```

2.13 sort - polar angle.cpp

```

1  inline bool cmp(const Point& a,const Point& b)
2  {
3      if (a.y*b.y <= 0)
4      {
5          if (a.y > 0 || b.y > 0)
6              return a.y < b.y;
7          if (a.y == 0 && b.y == 0)
8              return a.x < b.x;
9      }
10     return a.cross(b) > 0;
11 }

```

2.14 triangle's fermat point

1		1 2 0	
2			
3		1 2 0	
4			
5			
6			A B C
	' B C A ' C A B '		
7	C C ' B B ' A A '		

Chapter 3

graph

3.1 2-sat.cpp

```
1 #define maxn 2008
2 struct Twosat
3 {
4     int n;
5     std::vector<int>G[maxn*2];
6     bool mark[maxn*2];
7     int s[maxn*2],c;
8
9     bool dfs(int x)
10    {
11        if(mark[x^1])return false;
12        if(mark[x])return true;
13        mark[x]=true;
14        s[c++]=x;
15        for(int i=0;i<G[x].size();++i)
16            if(!dfs(G[x][i]))return false;
17        return true;
18    }
19
20    void init(int n)
21    {
22        this->n=n;
23        for(int i=0;i<n*2;++i)
24            G[i].clear();
25        memset(mark,0,sizeof(mark));
26    }
27    void add_clause(int x,int xval,int y,int yval) //
```

```

28     {
29         x=x*2+xval;
30         y=y*2+yval;
31         G[x^1].push_back(y);
32         G[y^1].push_back(x);
33     }
34
35     bool solve()
36     {
37         for(int i=0;i<n*2;i+=2)
38             if(!mark[i]&&!mark[i+1])
39                 {
40                     c=0;
41                     if(!dfs(i))
42                         {
43                             while(c>0)
44                                 mark[s[--c]]=false;
45                             if(!dfs(i+1))
46                                 return false;
47                         }
48                 }
49         return true;
50     }
51 };

```

3.2 Articulation.cpp

```

1 void dfs(int now,int fa)    // now 1
2 {
3     int p(0);
4     dfn[now]=low[now]=cnt++;
5     for(std::list<int>::const_iterator it(edge[now].begin
6         ());it!=edge[now].end();++it)
7         if(dfn[*it]==-1)
8             {
9                 dfs(*it,now);
10                ++p;
11                low[now]=std::min(low[now],low[*it]);
12                if((now==1 && p>1) || (now!=1 && low[*it]>=
13                    dfn[now])) //

```

```

14         else
15             if(*it!=fa)
16                 low[now]=std::min(low[now],dfn[*it]);
17     }

```

3.3 Augmenting Path Algorithm for Maximum Cardinality Bipartite Matching.cpp

```

1  #include<cstdio>
2  #include<cstring>
3
4  #define MAXX 111
5
6  bool Map[MAXX][MAXX], visit[MAXX];
7  int link[MAXX], n, m;
8  bool dfs(int t)
9  {
10     for (int i=0; i<m; i++)
11         if (!visit[i] && Map[t][i]) {
12             visit[i] = true;
13             if (link[i]==-1 || dfs(link[i])) {
14                 link[i] = t;
15                 return true;
16             }
17         }
18     return false;
19 }
20 int main()
21 {
22     int k, a, b, c;
23     while (scanf("%d", &n), n) {
24         memset(Map, false, sizeof(Map));
25         scanf("%d%d", &m, &k);
26         while (k--) {
27             scanf("%d%d%d", &a, &b, &c);
28             if (b && c)
29                 Map[b][c] = true;
30         }
31         memset(link, -1, sizeof(link));
32         int ans = 0;
33         for (int i=0; i<n; i++) {
34             memset(visit, false, sizeof(visit));
35             if (dfs(i))
36                 ans++;
37         }

```

```

38         printf("%d\n",ans);
39     }
40 }

```

3.4 best spanning tree.cpp

```

1  #include<stdio>
2  #include<cstring>
3  #include<cmath>
4
5  #define MAXX 1111
6
7  struct
8  {
9      int x,y;
10     double z;
11 } node[MAXX];
12
13 struct
14 {
15     double l,c;
16 } map[MAXX][MAXX];
17
18 int n,l,f[MAXX],pre[MAXX];
19 double dis[MAXX];
20
21 double mst(double x)
22 {
23     int i,j,tmp;
24     double min,s=0,t=0;
25     memset(f,0,sizeof(f));
26     f[1]=1;
27     for (i=2; i<=n; i++)
28     {
29         dis[i]=map[1][i].c-map[1][i].l*x;
30         pre[i]=1;
31     }
32     for (i=1; i<n; i++)
33     {
34         min=1e10;
35         for (j=1; j<=n; j++)
36             if (!f[j] && min>dis[j])
37             {
38                 min=dis[j];
39                 tmp=j;
40             }

```



```

41         f[tmp]=1;
42         t+=map[pre[tmp]][tmp].l;
43         s+=map[pre[tmp]][tmp].c;
44         for (j=1; j<=n; j++)
45             if (!f[j] && map[tmp][j].c-map[tmp][j].l*x<
46                 dis[j])
47             {
48                 dis[j]=map[tmp][j].c-map[tmp][j].l*x;
49                 pre[j]=tmp;
50             }
51     return s/t;
52 }
53
54 int main()
55 {
56     int i,j;
57     double a,b;
58     while (scanf("%d",&n),n);
59     {
60         for (i=1; i<=n; i++)
61             scanf("%d%d%lf",&node[i].x,&node[i].y,&node[i]
62                 ].z);
63         for (i=1; i<=n; i++)
64             for (j=i+1; j<=n; j++)
65             {
66                 map[j][i].l=map[i][j].l=sqrt(1.0*(node[i]
67                     ].x-node[j].x)*(node[i].x-node[j].x)+(
68                     node[i].y-node[j].y)*(node[i].y-node[j]
69                     ].y));
70                 map[j][i].c=map[i][j].c=fabs(node[i].z-
71                     node[j].z);
72             }
73         a=0,b=mst(a);
74         while (fabs(b-a)>1e-8)
75         {
76             a=b;
77             b=mst(a);
78         }
79         printf("%.3lf\n",b);
80     }
81     return 0;
82 }

```

3.5 Biconnected Component.cpp

```

1  #include<cstdio>
2  #include<cstring>
3  #include<stack>
4  #include<queue>
5  #include<algorithm>
6
7  const int MAXN=100000*2;
8  const int MAXM=200000;
9
10 //0-based
11
12 struct edges
13 {
14     int to,next;
15     bool cut,visit;
16 } edge[MAXN<1];
17
18 int head[MAXN],low[MAXN],dpt[MAXN],L;
19 bool visit[MAXN],cut[MAXN];
20 int idx;
21 std::stack<int> st;
22 int bcc[MAXM];
23
24 void init(int n)
25 {
26     L=0;
27     memset(head,-1,4*n);
28     memset(visit,0,n);
29 }
30
31 void add_edge(int u,int v)
32 {
33     edge[L].cut=edge[L].visit=false;
34     edge[L].to=v;
35     edge[L].next=head[u];
36     head[u]=L++;
37 }
38
39 void dfs(int u,int fu,int deg)
40 {
41     cut[u]=false;
42     visit[u]=true;
43     low[u]=dpt[u]=deg;

```

```

44     int tot=0;
45     for (int i=head[u]; i!=-1; i=edge[i].next)
46     {
47         int v=edge[i].to;
48         if (edge[i].visit)
49             continue;
50         st.push(i/2);
51         edge[i].visit=edge[i^1].visit=true;
52         if (visit[v])
53         {
54             low[u]=dpt[v]>low[u]?low[u]:dpt[v];
55             continue;
56         }
57         dfs(v,u,deg+1);
58         edge[i].cut=edge[i^1].cut=(low[v]>dpt[u] || edge[
59             i].cut);
60         if (u!=fu) cut[u]=low[v]>=dpt[u]?1:cut[u];
61         if (low[v]>=dpt[u] || u==fu)
62         {
63             while (st.top()!=i/2)
64             {
65                 int x=st.top()*2,y=st.top()*2+1;
66                 bcc[st.top()]=idx;
67                 st.pop();
68             }
69             bcc[i/2]=idx++;
70             st.pop();
71             low[u]=low[v]>low[u]?low[u]:low[v];
72             tot++;
73         }
74         if (u==fu && tot>1)
75             cut[u]=true;
76     }
77
78 int main()
79 {
80     int n,m;
81     while (scanf("%d%d",&n,&m)!=EOF)
82     {
83         init(n);
84         for (int i=0; i<m; i++)
85         {
86             int u,v;
87             scanf("%d%d",&u,&v);
88             add_edge(u,v);

```

```

89         add_edge(v,u);
90     }
91     idx=0;
92     for (int i=0; i<n; i++)
93         if (!visit[i])
94             dfs(i,i,0);
95     }
96     return 0;
97 }

```

3.6 Bridge.cpp

```

1 void dfs(const short &now,const short &fa)
2 {
3     dfn[now]=low[now]=cnt++;
4     for(int i(0); i<edge[now].size(); ++i)
5         if(dfn[edge[now][i]]==-1)
6         {
7             dfs(edge[now][i],now);
8             low[now]=std::min(low[now],low[edge[now][i]]);
9             if(low[edge[now][i]]>dfn[now]) //
10
11         {
12             if(edge[now][i]<now)
13             {
14                 j=edge[now][i];
15                 k=now;
16             }
17             else
18             {
19                 j=now;
20                 k=edge[now][i];
21             }
22             ans.push_back(node(j,k));
23         }
24     else
25         if(edge[now][i]!=fa)
26             low[now]=std::min(low[now],low[edge[now][i]]);
27 }

```

3.7 chu-liu algorithm.cpp

```

1  #include<cstdio>
2  #include<cstring>
3  #include<algorithm>
4
5  const int inf = 0x5fffffff;
6
7  int n,m,u,v,cost,dis[1001][1001],L;
8  int pre[1001],id[1001],visit[1001],in[1001];
9
10 void init(int n)
11 {
12     L = 0;
13     for (int i = 0; i < n; i++)
14         for (int j = 0; j < n; j++)
15             dis[i][j] = inf;
16 }
17
18 struct Edge
19 {
20     int u,v,cost;
21 };
22
23 Edge e[1001*1001];
24
25
26 int zhuliu(int root,int n,int m,Edge e[])
27 {
28     int res = 0,u,v;
29     while (true)
30     {
31         for (int i = 0; i < n; i++)
32             in[i] = inf;
33         for (int i = 0; i < m; i++)
34             if (e[i].u != e[i].v && e[i].cost < in[e[i].v]
35                 ])
36             {
37                 pre[e[i].v] = e[i].u;
38                 in[e[i].v] = e[i].cost;
39             }
40         for (int i = 0; i < n; i++)
41             if (i != root)
42                 if (in[i] == inf)
43                     return -1;
44         int tn = 0;
45         memset(id,-1,sizeof(id));
46         memset(visit,-1,sizeof(visit));

```

```

46     in[root] = 0;
47     for (int i = 0; i < n; i++)
48     {
49         res += in[i];
50         v = i;
51         while (visit[v] != i && id[v] == -1 && v !=
               root)
52         {
53             visit[v] = i;
54             v = pre[v];
55         }
56         if (v != root && id[v] == -1)
57         {
58             for (int u = pre[v] ; u != v ; u = pre[u])
59                 id[u] = tn;
60             id[v] = tn++;
61         }
62     }
63     if (tn == 0) break;
64     for (int i = 0; i < n; i++)
65         if (id[i] == -1)
66             id[i] = tn++;
67     for (int i = 0; i < m;)
68     {
69         int v = e[i].v;
70         e[i].u = id[e[i].u];
71         e[i].v = id[e[i].v];
72         if (e[i].u != e[i].v)
73             e[i++].cost -= in[v];
74         else
75             std::swap(e[i], e[--m]);
76     }
77     n = tn;
78     root = id[root];
79 }
80 return res;
81 }
82
83 int main()
84 {
85     freopen("asdf", "r", stdin);
86     while (scanf("%d%d", &n, &m) != EOF)
87     {
88         init(n);
89         for (int i = 0; i < m; i++)
90         {

```

```

91         scanf("%d%d%d",&u,&v,&cost);
92         if (u == v) continue;
93         dis[u][v] = std::min(dis[u][v],cost);
94     }
95     L = 0;
96     for (int i = 0; i < n; i++)
97         for (int j = 0; j < n; j++)
98             if (dis[i][j] != inf)
99                 {
100                     e[L].u = i;
101                     e[L].v = j;
102                     e[L++].cost = dis[i][j];
103                 }
104     printf("%d\n",zhuliu(0,n,L,e));
105 }
106 return 0;
107 }

```

3.8 k-th shortest path.cpp

```

1  #include<cstdio>
2  #include<cstring>
3  #include<queue>
4  #include<vector>
5
6  int K;
7
8  class states
9  {
10     public:
11         int cost,id;
12 };
13
14 int dist[1000];
15
16 class cmp
17 {
18     public:
19         bool operator()(const states &i,const states &j)
20         {
21             return i.cost>j.cost;
22         }
23 };
24
25 class cmp2
26 {

```

```

27     public:
28         bool operator () (const states &i, const states &j)
29         {
30             return i.cost+dist[i.id]>j.cost+dist[j.id];
31         }
32     };
33
34     struct edges
35     {
36         int to, next, cost;
37     } edger[100000], edge[100000];
38
39     int headr[1000], head[1000], Lr, L;
40
41     void dijkstra(int s)
42     {
43         states u;
44         u.id=s;
45         u.cost=0;
46         dist[s]=0;
47         std::priority_queue<states, std::vector<states>, cmp> q
48         ;
49         q.push(u);
50         while (!q.empty())
51         {
52             u=q.top();
53             q.pop();
54             if (u.cost!=dist[u.id])
55                 continue;
56             for (int i=headr[u.id]; i!=-1; i=edger[i].next)
57             {
58                 states v=u;
59                 v.id=edger[i].to;
60                 if (dist[v.id]>dist[u.id]+edger[i].cost)
61                 {
62                     v.cost=dist[v.id]=dist[u.id]+edger[i].
63                     cost;
64                     q.push(v);
65                 }
66             }
67         }
68     int num[1000];
69
70     inline void init(int n)

```



```

71 {
72     Lr=L=0;
73     memset(head,-1,4*n);
74     memset(headr,-1,4*n);
75     memset(dist,63,4*n);
76     memset(num,0,4*n);
77 }
78
79 void add_edge(int u,int v,int x)
80 {
81     edge[L].to=v;
82     edge[L].cost=x;
83     edge[L].next=head[u];
84     head[u]=L++;
85     edger[Lr].to=u;
86     edger[Lr].cost=x;
87     edger[Lr].next=headr[v];
88     headr[v]=Lr++;
89 }
90
91 inline int a_star(int s,int t)
92 {
93     if (dist[s]==0x3f3f3f3f)
94         return -1;
95     std::priority_queue<states,std::vector<states>,cmp2>
96         q;
97     states tmp;
98     tmp.id=s;
99     tmp.cost=0;
100    q.push(tmp);
101    while (!q.empty())
102    {
103        states u=q.top();
104        q.pop();
105        num[u.id]++;
106        if (num[t]==K)
107            return u.cost;
108        for (int i=head[u.id]; i!=-1; i=edge[i].next)
109        {
110            int v=edge[i].to;
111            tmp.id=v;
112            tmp.cost=u.cost+edge[i].cost;
113            q.push(tmp);
114        }
115    }
116    return -1;

```

```

116 }
117
118 int main()
119 {
120     int n,m;
121     scanf("%d%d",&n,&m);
122     init(n);
123     for (int i=0; i<m; i++)
124     {
125         int u,v,x;
126         scanf("%d%d%d",&u,&v,&x);
127         add_edge(u-1,v-1,x);
128     }
129     int s,t;
130     scanf("%d%d%d",&s,&t,&K);
131     if (s==t)
132         ++K;
133     dijkstra(t-1);
134     printf("%d\n", a_star(s-1,t-1));
135 }

```

3.9 Kuhn-Munkres algorithm.cpp

```

1 bool match(int u)//
2 {
3     vx[u]=true;
4     for(int i=1;i<=n;++i)
5         if(lx[u]+ly[i]==g[u][i]&&!vy[i])
6         {
7             vy[i]=true;
8             if(!d[i]||match(d[i]))
9             {
10                 d[i]=u;
11                 return true;
12             }
13         }
14     return false;
15 }
16 inline void update()//
17 {
18     int i,j;
19     int a=1<<30;
20     for(i=1;i<=n;++i) if(vx[i])
21         for(j=1;j<=n;++j) if(!vy[j])
22             a=min(a, lx[i]+ly[j]-g[i][j]);
23     for(i=1;i<=n;++i)

```

```

24     {
25         if (vx[i]) lx[i]-=a;
26         if (vy[i]) ly[i]+=a;
27     }
28 }
29 void km()
30 {
31     int i, j;
32     for (i=1; i<=n; ++i)
33     {
34         lx[i]=ly[i]=d[i]=0;
35         for (j=1; j<=n; ++j)
36             lx[i]=max(lx[i], g[i][j]);
37     }
38     for (i=1; i<=n; ++i)
39     {
40         while(true)
41         {
42             memset(vx, 0, sizeof(vx));
43             memset(vy, 0, sizeof(vy));
44             if (match(i))
45                 break;
46             update();
47         }
48     }
49     int ans=0;
50     for (i=1; i<=n; ++i)
51         if (d[i]!=0)
52             ans+=g[d[i]][i];
53     printf("%d\n", ans);
54 }
55 int main()
56 {
57     while (scanf("%d\n", &n)!=EOF)
58     {
59         for (int i=1; i<=n; ++i) gets(s[i]);
60         memset(g, 0, sizeof(g));
61         for (int i=1; i<=n; ++i)
62             for (int j=1; j<=n; ++j)
63                 if (i!=j) g[i][j]=cal(s[i], s[j]);
64         km();
65     }
66     return 0;
67 }
68
69

```

```

70 //bupt
71
72 // k m  $n^3$ 
73 int dfs(int u)//
74 {
75     int v;
76     sx[u]=1;
77     for ( v=1; v<=n; v++)
78         if (!sy[v] && lx[u]+ly[v]==map[u][v])
79             {
80                 sy[v]=1;
81                 if (match[v]==-1 || dfs(match[v]))
82                     {
83                         match[v]=u;
84                         return 1;
85                     }
86             }
87     return 0;
88 }
89
90 int bestmatch(void)// k m
91 {
92     int i,j,u;
93     for ( i=1; i<=n; i++)//
94     {
95         lx[i]=-1;
96         ly[i]=0;
97         for ( j=1; j<=n; j++)
98             if (lx[i]<map[i][j])
99                 lx[i]=map[i][j];
100     }
101     memset(match, -1, sizeof(match));
102     for (u=1; u<=n; u++)
103     {
104         while (true)
105         {
106             memset(sx,0,sizeof(sx));
107             memset(sy,0,sizeof(sy));
108             if (dfs(u))
109                 break;
110             int dx=Inf;//
~~
111
112             for ( i=1; i<=n; i++)
113             {
114                 if (sx[i])
115                     for ( j=1; j<=n; j++)

```

```

115             if (!sy[j] && dx>lx[i]+ly[j]-map[i
116                 ][j])
117                 dx=lx[i]+ly[j]-map[i][j];
118         }
119         for (i=1; i<=n; i++)
120         {
121             if (sx[i])
122                 lx[i]-=dx;
123             if (sy[i])
124                 ly[i]+=dx;
125         }
126     }
127     int sum=0;
128     for (i=1; i<=n; i++)
129         sum+=map[match[i]][i];
130     return sum;
131 }

```

3.10 LCA - DA.cpp

```

1  int edge[MAXX],nxt[MAXX<<1],to[MAXX<<1],cnt;
2  int pre[MAXX][N],dg[MAXX];
3
4  inline void add(int j,int k)
5  {
6      nxt[++cnt]=edge[j];
7      edge[j]=cnt;
8      to[cnt]=k;
9  }
10
11 void rr(int now,int fa)
12 {
13     dg[now]=dg[fa]+1;
14     for(int i=edge[now];i;i=nxt[i])
15         if(to[i]!=fa)
16         {
17             static int j;
18             j=1;
19             for(pre[to[i]][0]=now;j<N;++j)
20                 pre[to[i]][j]=pre[pre[to[i]][j-1]][j-1];
21             rr(to[i],now);
22         }
23 }
24
25 inline int lca(int a,int b)

```

```

26 {
27     static int i, j;
28     j=0;
29     if(dg[a]<dg[b])
30         std::swap(a, b);
31     for(i=dg[a]-dg[b]; i;i>>=1,++j)
32         if(i&1)
33             a=pre[a][j];
34     if(a==b)
35         return a;
36     for(i=N-1; i>=0; --i)
37         if(pre[a][i]!=pre[b][i])
38             {
39                 a=pre[a][i];
40                 b=pre[b][i];
41             }
42     return pre[a][0];
43 }

```

3.11 LCA - tarjan - minmax.cpp

```

1  #include<cstdio>
2  #include<list>
3  #include<algorithm>
4  #include<cstring>
5
6  #define MAXX 100111
7  #define inf 0x5fffffff
8
9  short T, t;
10 int set[MAXX], min[MAXX], max[MAXX], ans[2][MAXX];
11 bool done[MAXX];
12 std::list<std::pair<int, int>> edge[MAXX];
13 std::list<std::pair<int, int>> q[MAXX];
14 int n, i, j, k, l, m;
15
16 struct node
17 {
18     int a, b, id;
19     node() {}
20     node(const int &aa, const int &bb, const int &idd): a(
        aa), b(bb), id(idd) {}
21 };
22
23 std::list<node> to[MAXX];
24

```

```

25 int find(const int &a)
26 {
27     if(set[a]==a)
28         return a;
29     int b(set[a]);
30     set[a]=find(set[a]);
31     max[a]=std::max(max[a],max[b]);
32     min[a]=std::min(min[a],min[b]);
33     return set[a];
34 }
35
36 void tarjan(const int &now)
37 {
38     done[now]=true;
39     for(std::list<std::pair<int,int> >::const_iterator it
40         (q[now].begin()); it!=q[now].end();++it)
41         if(done[it->first])
42             if(it->second>0)
43                 to[find(it->first)].push_back(node(now,it
44                     ->first ,it->second));
45             else
46                 to[find(it->first)].push_back(node(it->
47                     first ,now,-it->second));
48     for(std::list<std::pair<int,int> >::const_iterator it
49         (edge[now].begin()); it!=edge[now].end();++it)
50         if(!done[it->first])
51         {
52             tarjan(it->first);
53             set[it->first]=now;
54             min[it->first]=it->second;
55             max[it->first]=it->second;
56         }
57     for(std::list<node>::const_iterator it(to[now].begin
58         ()); it!=to[now].end();++it)
59     {
60         find(it->a);
61         find(it->b);
62         ans[0][it->id]=std::min(min[it->b],min[it->a]);
63         ans[1][it->id]=std::max(max[it->a],max[it->b]);
64     }
65 }
66
67 int main()
68 {
69     scanf("%hd",&T);
70     for(t=1;t<=T;++t)

```

```

66     {
67         scanf("%d",&n);
68         for ( i=1;i<=n;++i )
69         {
70             edge[ i ]. clear ();
71             q[ i ]. clear ();
72             to[ i ]. clear ();
73             done[ i]=false;
74             set[ i]=i;
75             min[ i]=inf;
76             max[ i]=0;
77         }
78         for ( i=1;i<n;++i )
79         {
80             scanf("%d%d%d",&j,&k,&l);
81             edge[ j ]. push_back( std::make_pair(k,l) );
82             edge[ k ]. push_back( std::make_pair(j,l) );
83         }
84         scanf("%d",&m);
85         for ( i=0;i<m;++i )
86         {
87             scanf("%d_%d",&j,&k);
88             q[ j ]. push_back( std::make_pair(k,i) );
89             q[ k ]. push_back( std::make_pair(j,-i) );
90         }
91         tarjan(1);
92         printf("Case_%dhd:\n",t);
93         for ( i=0;i<m;++i )
94             printf("%d_%d\n",ans[0][ i ],ans[1][ i ] );
95     }
96     return 0;
97 }

```

3.12 Minimum Cost Maximum Flow.cpp

```

1  struct mcmf
2  {
3      struct Edge
4      {
5          int from,to,cap,flow,cost;
6      };
7      int n,m,s,t;
8      std::vector<Edge>edges;
9      std::vector<int>G[maxn];
10     int inq[maxn],d[maxn],p[maxn],a[maxn];
11

```



```

12     void init(int n)
13     {
14         this->n=n;
15         for(int i=0;i<n;++i)
16             G[i].clear();
17         edges.clear();
18     }
19
20     void addedge(int from,int to,int cap,int cost)
21     {
22         Edge x={from,to,cap,0,cost};
23         edges.push_back(x);
24         Edge y={to,from,0,0,-cost};
25         edges.push_back(y);
26         m=edges.size();
27         G[from].push_back(m-2);
28         G[to].push_back(m-1);
29     }
30     int mincost(int s,int t)
31     {
32         int flow=0,cost=0;
33         while(BellmanFord(s,t,flow,cost));
34         if(flow!=(n-1)/2)return -1;
35         return cost;
36     }
37 private:
38     bool BellmanFord(int s,int t,int& flow,int& cost)
39     {
40         for(int i=0;i<=n;++i)
41             d[i]=INF;
42         memset(inq,0,sizeof(inq));
43         d[s]=0; inq[s]=1; p[s]=0; a[s]=INF;
44         std::queue<int>Q;
45         Q.push(s);
46         while(!Q.empty())
47         {
48             int u=Q.front();
49             Q.pop();
50             inq[u]=0;
51             for(int i=0;i<G[u].size();++i)
52             {
53                 Edge& e=edges[G[u][i]];
54                 if(e.cap>e.flow && d[e.to]>d[u]+e.cost)
55                 {
56                     d[e.to]=d[u]+e.cost;
57                     p[e.to]=G[u][i];

```

```

58             a[e.to]=min(a[u],e.cap-e.flow);
59             if(!inq[e.to])
60             {
61                 Q.push(e.to);
62                 inq[e.to]=1;
63             }
64         }
65     }
66 }
67 if(d[t]==INF)
68     return false;
69 flow+=a[t];
70 cost+=d[t]*a[t];
71 int u=t;
72 while(u!=s)
73 {
74     edges[p[u]].flow+=a[t];
75     edges[p[u]^1].flow-=a[t];
76     u=edges[p[u]].from;
77 }
78 return true;
79 }
80
81 }G;

```

3.13 minimum cut.cpp

```

1  #include <iostream>
2  using namespace std;
3  const int maxn=510;
4  int map[maxn][maxn];
5  int n;
6  void contract(int x,int y)//
7  {
8      int i,j;
9      for (i=0; i<n; i++)
10         if (i!=x) map[x][i]+=map[y][i],map[i][x]+=map[i][y];
11         for (i=y+1; i<n; i++) for (j=0; j<n; j++)
12         {
13             map[i-1][j]=map[i][j];
14             map[j][i-1]=map[j][i];
15         }
16         n--;
17     }
18     int w[maxn],c[maxn];
19     int sx,tx;

```

```

20 int mincut()
21 //

22 {
23     int i,j,k,t;
24     memset(c,0,sizeof(c));
25     c[0]=1;
26     for (i=0; i<n; i++) w[i]=map[0][i];
27     for (i=1; i+1<n; i++)
28     {
29         t=k=-1;
30         for (j=0; j<n; j++) if (c[j]==0&&w[j]>k)
31             k=w[t=j];
32         c[sx=t]=1;
33         for (j=0; j<n; j++) w[j]+=map[t][j];
34     }
35     for (i=0; i<n; i++) if (c[i]==0) return w[tx=i];
36 }
37 int main()
38 {
39     int i,j,k,m;
40     while (scanf("%d%d",&n,&m)!=EOF)
41     {
42         memset(map,0,sizeof(map));
43         while (m--)
44         {
45             scanf("%d%d%d",&i,&j,&k);
46             map[i][j]+=k;
47             map[j][i]+=k;
48         }
49         int mint=999999999;
50         while (n>1)
51         {
52             k=mincut();
53             if (k<mint) mint=k;
54             contract(sx,tx);
55         }
56         printf("%d\n",mint);
57     }
58     return 0;
59 }

```

3.14 others

```

2
3
4
5
6
7
8
9
10
11
12
13
14

```

G D D
 $, v$ u $,$
 v G $=$
 U V $G = (V; E)$
 $< u; v >$ u, v U
 E U G U G
 $; v$ U $< u; v >$ G U G
 E U G U G

$+$ $= V$
 $=$
 $=$

3.15 Shortest Augmenting Path algorithm.cpp

```

1 #include <cstring>
2 #include <cstdio>
3 #include <vector>
4 #include <queue>
5 #define maxn 1005
6 #define INF 1<<30
7 using namespace std;
8 struct Edge

```

```

9  {
10      int from,to,cap,flow;
11  };
12  vector<Edge>edges;
13  vector<int>G[maxn];
14  int num[maxn],p[maxn],n,m;
15  int st[maxn],et[maxn],nt[maxn];
16  int d[maxn],s,t,cur[maxn];
17  void addedge(int from,int to,int cap)
18  {
19      struct Edge x={from,to,cap,0};
20      edges.push_back(x);
21      struct Edge y={to,from,0,0};
22      edges.push_back(y);
23      int m=edges.size();
24      G[from].push_back(m-2);
25      G[to].push_back(m-1);
26  }
27  void bfs()//
        B F S
28  {
29      queue<int>q;
30      memset(d,0,sizeof(d));
31      d[t]=1;
32      q.push(t);
33      while(!q.empty())
34      {
35          int u=q.front(); q.pop();
36          for(int i=0;i<G[u].size();++i)
37              if(G[u][i]&1)
38              {
39                  Edge& e=edges[G[u][i]];
40                  if(!d[e.to])
41                  {
42                      d[e.to]=d[u]+1;
43                      q.push(e.to);
44                  }
45              }
46      }
47  }
48  int augment()//
49  {
50      int u=t, a=INF;
51      while(u!=s)
52      {
53          Edge& e=edges[p[u]];

```

```

54         a=min(a,e.cap-e.flow); //

55         u=e.from;
56     }
57     u=t;
58     while(u!=s)
59     {
60         edges[p[u]].flow+=a;
61         edges[p[u]^1].flow-=a;
62         u=edges[p[u]].from;
63     }
64     return a;
65 }
66 int sap()
67 {
68     int flow=0;
69     bfs();
70     memset(num,0,sizeof(num));
71     for(int i=0;i<=t;++i) num[d[i]]++;
72     int u=s;
73     memset(cur,0,sizeof(cur));
74     while(d[s]<t)
75     {
76         if(u==t)
77         {
78             flow+=augment();
79             u=s;
80         }
81         int ok=0;
82         for(int i=cur[u]; i<G[u].size();++i)
83         {
84             Edge& e=edges[G[u][i]];
85             if(e.cap>e.flow && d[u]==d[e.to]
86                 +1)
87             {
88                 ok=1;
89                 p[e.to]=G[u][i];
90                 cur[u]=i;
91                 u=e.to;
92                 break;
93             }
94         }
95         if(!ok) //

```

```

95         {
96             int m=t-1;
97             for (int i=0;i<G[u].size();++i)
98             {
99                 Edge& e=edges[G[u][i]];
100                 if (e.cap>e.flow) m=min(m,
                                d[e.to]);
101             }
102             if (--num[d[u]]==0) break; //
                                g a p
103             num[d[u]=m+1]++;
104             cur[u]=0; //

105             if (u!=s) u=edges[p[u]].from;
106         }
107     }
108     return flow;
109 }
110 void init()
111 {
112     edges.clear();
113     for (int i=0;i<maxn;++i) G[i].clear();
114 }
115 int main()
116 {
117     int T, i;
118     // freopen("1.txt","r",stdin);
119     scanf("%d", &T);
120     while (T--)
121     {
122         scanf("%d%d", &n, &m);
123         s=0; t=-1;
124         int res=0;
125         init();
126         for (i=1;i<=n;++i)
127         {
128             scanf("%d%d%d",&st[i],&et[i],&nt[i]);
129             res+=nt[i];
130             if (et[i]+n+1>t) t=et[i]+n+1;
131         }
132         for (i=1; i<=n; ++i)
133         {
134             int j;
135             addedge(s,i,nt[i]);
136             for (j=st[i]; j<=et[i];++j) addedge(i,j+n,1);

```

```

137     }
138     for (i=n+1; i<t; ++i) addedge(i, t, m);
139     int ans = sap();
140     if (ans==res) printf("Yaha, _Garfield, _You_Finish_it\n");
141     else printf("Oh~~ Garfield, _You_are_just_as_before\n");
142 }
143 return 0;
144 }

```

3.16 Stable Marriage.cpp

```

1 //
2
3 while (!g.empty()) //
4 {
5     if (dfn[edge[g.front()].front()] == -1)
6         dfn[edge[g.front()].front()] = g.front(); //
7
8     else
9     {
10         for (it=edge[edge[g.front()].front()].begin(); it!=
11             edge[edge[g.front()].front()].end(); ++it)
12             if (*it==dfn[edge[g.front()].front()] || *it==
13                 g.front()) //
14
15                 break;
16         if (*it==g.front()) //
17         {
18             g.push_back(dfn[edge[g.front()].front()]);
19             dfn[edge[g.front()].front()] = g.front();
20         }
21         else
22             g.push_back(g.front()); //
23
24     }
25     edge[g.front()].pop_front(); //
26
27     g.pop_front();
28 }

```


3.17 Strongly Connected Component.cpp

```

1  void dfs(const short &now)
2  {
3      dfn[now]=low[now]=cnt++;
4      st.push(now);
5      for(std::list<short>::const_iterator it(edge[now].
        begin()); it!=edge[now].end(); ++it)
6          if(dfn[*it]==-1)
7              {
8                  dfs(*it);
9                  low[now]=std::min(low[now], low[*it]);
10             }
11         else
12             if(sc[*it]==-1)
13                 low[now]=std::min(low[now], dfn[*it]);
14     if(dfn[now]==low[now])
15     {
16         while(sc[now]==-1)
17         {
18             sc[st.top()]=p;
19             st.pop();
20         }
21         ++p;
22     }
23 }

```


Chapter 4

math

4.1 cantor.cpp

```
1  const int PermSize = 12;
2  int fac[PermSize] = {1, 1, 2, 6, 24, 120, 720, 5040,
    40320, 362880, 3628800, 39916800};
3
4  inline int Cantor(int a[])
5  {
6      int i, j, cnt;
7      int res = 0;
8      for (i = 0; i < PermSize; ++i)
9      {
10         cnt = 0;
11         for (j = i + 1; j < PermSize; ++j)
12             if (a[i] > a[j])
13                 ++cnt;
14         res = res + cnt * fac[PermSize - i - 1];
15     }
16     return res;
17 }
18
19 bool h[13];
20
21 inline void UnCantor(int x, int res[])
22 {
23     int i, j, l, t;
24     for (i = 1; i <= 12; i++)
25         h[i] = false;
26     for (i = 1; i <= 12; i++)
27     {
```

```

28         t = x / fac[12 - i];
29         x -= t * fac[12 - i];
30         for (j = 1, l = 0; l <= t; j++)
31             if (!h[j])
32                 l++;
33         j--;
34         h[j] = true;
35         res[i - 1] = j;
36     }
37 }

```

4.2 combinations.cpp

```

1  #include<cstdio>
2  #include<cstring>
3  #include<iostream>
4
5  int mod;
6  long long num[100000];
7  int ni[100],mi[100];
8  int len;
9
10 void init(int p)
11 {
12     mod=p;
13     num[0]=1;
14     for (int i=1; i<p; i++)
15         num[i]=i*num[i-1]%p;
16 }
17
18 void get(int n,int ni[],int p)
19 {
20     for (int i = 0; i < 100; i++)
21         ni[i] = 0;
22     int tlen = 0;
23     while (n != 0)
24     {
25         ni[tlen++] = n%p;
26         n /= p;
27     }
28     len = tlen;
29 }
30
31 long long power(long long x,long long y)
32 {
33     long long ret=1;

```

```

34     for (long long a=x%mod; y; y>>=1,a=a*a%mod)
35         if (y&1)
36             ret=ret*a%mod;
37     return ret;
38 }
39
40 long long getInv(long long x)// ' m o d '
41 {
42     return power(x,mod-2);
43 }
44
45 long long calc(int n,int m,int p)//C(n,m)%p
46 {
47     init(p);
48     long long ans=1;
49     for (; n && m && ans; n/=p,m/=p)
50     {
51         if (n%p>=m%p)
52             ans = ans*num[n%p]%p *getInv(num[m%p]%p)%p *
                    getInv(num[n%p-m%p])%p;
53         else
54             ans=0;
55     }
56     return ans;
57 }
58
59 int main()
60 {
61     int t;
62     scanf("%d",&t);
63     while (t--)
64     {
65         int n,m,p;
66         scanf("%d%d%d",&n,&m,&p);
67         printf("%lld\n",calc(n+m,m,p));
68     }
69     return 0;
70 }

```

4.3 euler's totient function.cpp

```

1
    (x)=x(1-1/p1)(1-1/p2)(1-1/p3)(1-1/p4) ..(1-1/pn) ,
    p 1 ,
    p 2 p n x x 0
(1)=1 1 1 m ,

```

```

n          (mn)= (m) (n)
2
3 int Euler(int n)
4 {
5     int ans = n;
6     for (int i=2; i<=sqrt(n); i++)
7     {
8         if (n%i==0)
9         {
10            ans = ans-ans/i;
11            while (n%i==0)
12                n /= i;
13        }
14    }
15    if (n>1)
16        ans = ans-ans/n;
17    return ans;
18 }
19
20 //
21 inline void Euler2()
22 {
23     memset(euler,0,sizeof(euler));
24     euler[1] = 1;
25     for (int i = 2; i <= 3000000; i++)
26     {
27         if (!euler[i])
28         {
29             for (int j = i; j <= 3000000; j += i)
30             {
31                 if (!euler[j])
32                     euler[j] = j;
33                 euler[j] = euler[j]/i*(i-1);
34             }
35         }
36     }
37 }

```

4.4 extended euclidean algorithm.cpp

```

1 //      a x + b y = gcd(a, b)
2 long long ex_gcd(long long a, long long b, long long &x,
3               long long &y)
4 {
5     if (b)
6     {

```

```

6      long long ret = ex_gcd(b,a%b,x,y),tmp = x;
7      x = y;
8      y = tmp-(a/b)*y;
9      return ret;
10     }
11     else
12     {
13         x = 1;
14         y = 0;
15         return a;
16     }
17 }

```

4.5 inverse element.cpp

```

1 inline void getInv2(int x,int mod)
2 {
3     inv[1]=1;
4     for (int i=2; i<=x; i++)
5         inv[i]=(mod-(mod/i)*inv[mod%i]%mod)%mod;
6 }
7
8 long long power(long long x,long long y,int mod)
9 {
10     long long ret=1;
11     for (long long a=x%mod; y; y>>=1,a=a*a%mod)
12         if (y&1)
13             ret=ret*a%mod;
14     return ret;
15 }
16
17 inline int getInv(int x,int mod)// m o d
18 {
19     return power(x,mod-2);
20 }

```

4.6 lucas.cpp

```

1 #include <stdio>
2 /*
3 Lucas          C (n,m)%p
4 */
5 void gcd(int n,int k,int &x,int &y)
6 {
7     if(k==0){x=1;y=0;return ;}

```

```

8      else
9      {
10         gcd(k, n%k, x, y);
11         int t=x; x=y;
12         y=t-(n/k)*y;
13         return;
14     }
15 }
16
17 int CmodP(int n, int k, int p)
18 {
19     if(k>n) return 0;
20     int a, b, flag=0, x, y;
21     a=b=1;
22     for(int i=1; i<=k; i++)
23     {
24         x=n-i+1, y=i;
25         while(x%p==0) x/=p, flag++;
26         while(y%p==0) y/=p, flag--;
27         x%=p, y%=p, a*=x, b*=y;
28         b%=p, a%=p;
29     }
30     if(flag) return 0;
31     gcd(b, p, x, y);
32     if(x<0) x+=p;
33     a*=x, a%=p;
34     return a;
35 }
36
37 // Lucas  $C(n, m) \% p, p$ 
38 long long Lucas(long long n, long long m, long long p)
39 {
40     long long ans=1;
41     long long a, b;
42     while(n&&m&&ans)
43     {
44         ans*=(CmodP(n%p, m%p, p));
45         ans=ans%p;
46         n=n/p;
47         m=m/p;
48     }
49     return ans;
50 }
51 int main()
52 {
53     long long n, k, p, ans;

```



```

54     int cas=0;
55     //      freopen("1.txt","r",stdin);
56     //      freopen("out2.txt","w",stdout);
57     while(scanf("%I64d%I64d%I64d",&n,&k,&p)!=EOF)
58     {
59         ++cas;
60         if(k>n-k)k=n-k;
61         ans=Lucas(n+1,k,p)+n-k;
62         printf("Case-#%d: %I64d\n",cas,ans%p);
63     }
64     return 0;
65 }

```

4.7 matrix.cpp

```

1  //
2  struct Matrix
3  {
4      int a[52][52];
5      Matrix operator * (const Matrix &b)const
6      {
7          Matrix res;
8          for (int i = 0; i < 52; i++)
9              for (int j = 0; j < 52; j++)
10             {
11                 res.a[i][j] = 0;
12                 for (int k = 0; k < 52; k++)
13                     res.a[i][j] += a[i][k] * b.a[k][j];
14             }
15         return res;
16     }
17     Matrix operator ^ (int y)const
18     {
19         Matrix res, x;
20         for (int i = 0; i < 52; i++)
21         {
22             for (int j = 0; j < 52; j++)
23                 res.a[i][j] = 0, x.a[i][j] = a[i][j];
24             res.a[i][i] = 1;
25         }
26         for (; y; y >>= 1, x = x * x)
27             if (y & 1)
28                 res = res * x;
29         return res;
30     }
31 };

```

4.8 miller_rabin.cpp

```

1  inline unsigned long long multi_mod(const unsigned long
    long &a,unsigned long long b,const unsigned long long
    &n)
2  {
3      unsigned long long exp(a%n),tmp(0);
4      while(b)
5      {
6          if(b&1)
7          {
8              tmp+=exp;
9              if(tmp>n)
10                 tmp-=n;
11          }
12          exp<<=1;
13          if(exp>n)
14              exp-=n;
15          b>>=1;
16      }
17      return tmp;
18  }
19
20 inline unsigned long long exp_mod(unsigned long long a,
    unsigned long long b,const unsigned long long &c)
21 {
22     unsigned long long tmp(1);
23     while(b)
24     {
25         if(b&1)
26             tmp=multi_mod(tmp,a,c);
27         a=multi_mod(a,a,c);
28         b>>=1;
29     }
30     return tmp;
31 }
32
33 inline bool miller_rabbin(const unsigned long long &n,
    short T)
34 {
35     if(n==2)
36         return true;
37     if(n<2 || !(n&1))
38         return false;
39     unsigned long long a,u(n-1),x,y;

```

```

40     short t(0), i;
41     while (!(u & 1))
42     {
43         ++t;
44         u >>= 1;
45     }
46     while (T--)
47     {
48         a = rand() % (n - 1) + 1;
49         x = exp_mod(a, u, n);
50         for (i = 0; i < t; ++i)
51         {
52             y = multi_mod(x, x, n);
53             if (y == 1 && x != 1 && x != n - 1)
54                 return false;
55             x = y;
56         }
57         if (y != 1)
58             return false;
59     }
60     return true;
61 }

```

4.9 mod

```

1  (a+b)%m = (a%m+b%m)%m
2  (a-b)%m = ((a%m-b%m)%m+m)%m (a>b)
3  (a*b)%m = (a%m*b%m)%m
4
5  (a/b)%m = (a%(b*m))/b //

```

4.10 pollard rho.cpp

```

1  #include<cstdio>
2  #include<cstdlib>
3  #include<list>
4
5  short T;
6  unsigned long long a;
7  std::list<unsigned long long> fac;
8
9  inline unsigned long long multi_mod(const unsigned long
    long &a, unsigned long long b, const unsigned long long
    &n)
10 {

```

```

11     unsigned long long exp(a%n), tmp(0);
12     while(b)
13     {
14         if(b&1)
15         {
16             tmp+=exp;
17             if(tmp>n)
18                 tmp-=n;
19         }
20         exp<<=1;
21         if(exp>n)
22             exp-=n;
23         b>>=1;
24     }
25     return tmp;
26 }
27
28 inline unsigned long long exp_mod(unsigned long long a,
29     unsigned long long b, const unsigned long long &c)
30 {
31     unsigned long long tmp(1);
32     while(b)
33     {
34         if(b&1)
35             tmp=multi_mod(tmp, a, c);
36         a=multi_mod(a, a, c);
37         b>>=1;
38     }
39     return tmp;
40 }
41 inline bool miller_rabbin(const unsigned long long &n,
42     short T)
43 {
44     if(n==2)
45         return true;
46     if(n<2 || !(n&1))
47         return false;
48     unsigned long long a, u(n-1), x, y;
49     short t(0), i;
50     while(!(u&1))
51     {
52         ++t;
53         u>>=1;
54     }
55     while(T--)
```

```

55     {
56         a=rand()%(n-1)+1;
57         x=exp_mod(a,u,n);
58         for(i=0;i<t;++i)
59         {
60             y=multi_mod(x,x,n);
61             if(y==1 && x!=1 && x!=n-1)
62                 return false;
63             x=y;
64         }
65         if(y!=1)
66             return false;
67     }
68     return true;
69 }
70
71 unsigned long long gcd(const unsigned long long &a,const
    unsigned long long &b)
72 {
73     return b?gcd(b,a%b):a;
74 }
75
76 inline unsigned long long pollar_rho(const unsigned long
    long n,const unsigned long long &c)
77 {
78     unsigned long long x(rand()%(n-1)+1),y,d,i(1),k(2);
79     y=x;
80     while(true)
81     {
82         ++i;
83         x=(multi_mod(x,x,n)+c)%n;
84         d=gcd((x-y+n)%n,n);
85         if(d>1 && d<n)
86             return d;
87         if(x==y)
88             return n;
89         if(i==k)
90         {
91             k<<=1;
92             y=x;
93         }
94     }
95 }
96
97 void find(const unsigned long long &n,short c)
98 {

```

```

99     if (n==1)
100         return;
101     if (miller_rabbin(n,6))
102     {
103         fac.push_back(n);
104         return;
105     }
106     unsigned long long p(n);
107     short k(c);
108     while (p>=n)
109         p=pollar_rho(p,c--);
110     find(p,k);
111     find(n/p,k);
112 }
113
114 int main()
115 {
116     scanf("%hd",&T);
117     while (T--)
118     {
119         scanf("%llu",&a);
120         fac.clear();
121         find(a,120);
122         if (fac.size()==1)
123             puts("Prime");
124         else
125         {
126             fac.sort();
127             printf("%llu\n",fac.front());
128         }
129     }
130     return 0;
131 }

```

4.11 prime.cpp

```

1  #include<vector>
2
3  std::vector<int>prm;
4  bool flag[MAXX];
5
6  int main()
7  {
8      prm.reserve(MAXX); //  $pi(x)=x/\ln(x)$ ;
9      for (i=2;i<MAXX;++i)
10     {

```

```
11         if (!flag [ i ])
12             prm.push_back ( i );
13         for ( j=0; j<prm.size () && i*prm [ j]<MAXX; ++j )
14         {
15             flag [ i*prm [ j ] ] = true ;
16             if ( i%prm [ j ] == 0 )
17                 break ;
18         }
19     }
20     return 0 ;
21 }
```


Chapter 5

others

5.1 .vimrc

```
1 set number
2 set history=1000000
3 set autoindent
4 set smartindent
5 set tabstop=4
6 set shiftwidth=4
7 set expandtab
8 set showmatch
9
10 set nosp
11 filetype plugin indent on
12
13 filetype on
14 syntax on
```

5.2 bigint.cpp

```
1 // header files
2 #include <cstdio>
3 #include <string>
4 #include <algorithm>
5 #include <iostream>
6
7 struct Bigint
8 {
9     // representations and structures
10     std::string a; // to store the digits
```

```

11     int sign; // sign = -1 for negative numbers, sign = 1
        otherwise
12     // constructors
13     Bigint() {} // default constructor
14     Bigint( std::string b ) { (*this) = b; } //
        constructor for std::string
15     // some helpful methods
16     int size() // returns number of digits
17     {
18         return a.size();
19     }
20     Bigint inverseSign() // changes the sign
21     {
22         sign *= -1;
23         return (*this);
24     }
25     Bigint normalize( int newSign ) // removes leading 0,
        fixes sign
26     {
27         for( int i = a.size() - 1; i > 0 && a[i] == '0';
                i— )
28             a.erase(a.begin() + i);
29         sign = ( a.size() == 1 && a[0] == '0' ) ? 1 :
                newSign;
30         return (*this);
31     }
32     // assignment operator
33     void operator = ( std::string b ) // assigns a std::
        string to Bigint
34     {
35         a = b[0] == '-' ? b.substr(1) : b;
36         reverse( a.begin(), a.end() );
37         this—>normalize( b[0] == '-' ? -1 : 1 );
38     }
39     // conditional operators
40     bool operator < ( const Bigint &b ) const // less
        than operator
41     {
42         if( sign != b.sign )
43             return sign < b.sign;
44         if( a.size() != b.a.size() )
45             return sign == 1 ? a.size() < b.a.size() : a.
                size() > b.a.size();
46         for( int i = a.size() - 1; i >= 0; i— )
47             if( a[i] != b.a[i] )
48                 return sign == 1 ? a[i] < b.a[i] : a[i] >

```

```

49         b.a[i];
50     }
51     bool operator == ( const Bigint &b ) const //
        operator for equality
52     {
53         return a == b.a && sign == b.sign;
54     }
55
56     // mathematical operators
57     Bigint operator + ( Bigint b ) // addition operator
        overloading
58     {
59         if( sign != b.sign )
60             return (*this) - b.inverseSign();
61         Bigint c;
62         for(int i = 0, carry = 0; i < a.size() || i < b.size
            () || carry; i++)
63         {
64             carry += (i < a.size() ? a[i] - 48 : 0) + (i < b.a.size
                () ? b.a[i] - 48 : 0);
65             c.a += (carry % 10 + 48);
66             carry /= 10;
67         }
68         return c.normalize(sign);
69     }
70
71     Bigint operator - ( Bigint b ) // subtraction
        operator overloading
72     {
73         if( sign != b.sign )
74             return (*this) + b.inverseSign();
75         int s = sign; sign = b.sign = 1;
76         if( (*this) < b )
77             return ((b - (*this)).inverseSign()).
                normalize(-s);
78         Bigint c;
79         for( int i = 0, borrow = 0; i < a.size(); i++ )
80         {
81             borrow = a[i] - borrow - (i < b.size() ? b.a[
                i] : 48);
82             c.a += borrow >= 0 ? borrow + 48 : borrow +
                58;
83             borrow = borrow >= 0 ? 0 : 1;
84         }
85         return c.normalize(s);

```

```

86     }
87     Bigint operator * ( Bigint b ) // multiplication
      operator overloading
88     {
89         Bigint c("0");
90         for( int i = 0, k = a[i] - 48; i < a.size(); i++,
              k = a[i] - 48 )
91         {
92             while(k-- )
93                 c = c + b; // ith digit is k, so, we add
                          k times
94                 b.a.insert(b.a.begin(), '0'); // multiplied
                          by 10
95         }
96         return c.normalize(sign * b.sign);
97     }
98     Bigint operator / ( Bigint b ) // division operator
      overloading
99     {
100         if( b.size() == 1 && b.a[0] == '0' )
101             b.a[0] /= ( b.a[0] - 48 );
102         Bigint c("0"), d;
103         for( int j = 0; j < a.size(); j++ )
104             d.a += "0";
105         int dSign = sign * b.sign;
106         b.sign = 1;
107         for( int i = a.size() - 1; i >= 0; i-- )
108         {
109             c.a.insert( c.a.begin(), '0' );
110             c = c + a.substr( i, 1 );
111             while( !( c < b ) )
112             {
113                 c = c - b;
114                 d.a[i]++;
115             }
116         }
117         return d.normalize(dSign);
118     }
119     Bigint operator % ( Bigint b ) // modulo operator
      overloading
120     {
121         if( b.size() == 1 && b.a[0] == '0' )
122             b.a[0] /= ( b.a[0] - 48 );
123         Bigint c("0");
124         b.sign = 1;
125         for( int i = a.size() - 1; i >= 0; i-- )

```

```

126     {
127         c.a.insert( c.a.begin(), '0');
128         c = c + a.substr( i, 1 );
129         while( !( c < b ) )
130             c = c - b;
131     }
132     return c.normalize(sign);
133 }
134
135 // output method
136 void print()
137 {
138     if( sign == -1 )
139         putchar( '-' );
140     for( int i = a.size() - 1; i >= 0; i-- )
141         putchar(a[i]);
142 }
143 };
144
145
146
147 int main()
148 {
149     Bigint a, b, c; // declared some Bigint variables
150     ///////////////////////////////////
151     // taking Bigint input //
152     ///////////////////////////////////
153
154     std::string input; // std::string to take input
155     std::cin >> input; // take the Big integer as std::
156         string
157     a = input; // assign the std::string to Bigint a
158
159     std::cin >> input; // take the Big integer as std::
160         string
161     b = input; // assign the std::string to Bigint b
162
163     ///////////////////////////////////
164     // Using mathematical operators //
165     ///////////////////////////////////
166
167     c = a + b; // adding a and b
168     c.print(); // printing the Bigint
169     puts(""); // newline
170
171     c = a - b; // subtracting b from a

```

```

170     c.print(); // printing the Bigint
171     puts(""); // newline
172
173     c = a * b; // multiplying a and b
174     c.print(); // printing the Bigint
175     puts(""); // newline
176
177     c = a / b; // dividing a by b
178     c.print(); // printing the Bigint
179     puts(""); // newline
180
181     c = a % b; // a modulo b
182     c.print(); // printing the Bigint
183     puts(""); // newline
184
185     //////////////////////////////////////
186     // Using conditional operators //
187     //////////////////////////////////////
188
189     if( a == b )
190         puts("equal"); // checking equality
191     else
192         puts("not_equal");
193
194     if( a < b )
195         puts("a_is_smaller_than_b"); // checking less
196                                     than operator
197
197     return 0;
198 }

```

5.3 java.java

```

1 //Scanner
2
3 Scanner in=new Scanner(new FileReader("asdf"));
4 PrintWriter pw=new PrintWriter(new FileWriter("out"));
5 boolean    in.hasNext();
6 String     in.next();
7 BigDecimal in.nextBigDecimal();
8 BigInteger in.nextBigInteger();
9 BigInteger in.nextBigInteger(int radix);
10 double     in.nextDouble();
11 int        in.nextInt();
12 int        in.nextInt(int radix);
13 String     in.nextLine();

```

```

14 long          in.nextLong();
15 long          in.nextLong(int radix);
16 short         in.nextShort();
17 short         in.nextShort(int radix);
18 int           in.radix(); //Returns this scanner's
           default radix.
19 Scanner       in.useRadix(int radix); // Sets this scanner
           's default radix to the specified radix.
20 void          in.close(); //Closes this scanner.
21
22 //String
23
24 char          str.charAt(int index);
25 int           str.compareTo(String anotherString); // <0
           if less. ==0 if equal. >0 if greater.
26 int           str.compareToIgnoreCase(String str);
27 String        str.concat(String str);
28 boolean       str.contains(CharSequence s);
29 boolean       str.endsWith(String suffix);
30 boolean       str.startsWith(String prefix);
31 boolean       str.startsWith(String prefix,int toffset);
32 int           str.hashCode();
33 int           str.indexOf(int ch);
34 int           str.indexOf(int ch,int fromIndex);
35 int           str.indexOf(String str);
36 int           str.indexOf(String str,int fromIndex);
37 int           str.lastIndexOf(int ch);
38 int           str.lastIndexOf(int ch,int fromIndex);
39 //(ry
40 int           str.length();
41 String        str.substring(int beginIndex);
42 String        str.substring(int beginIndex,int endIndex);
43 String        str.toLowerCase();
44 String        str.toUpperCase();
45 String        str.trim(); // Returns a copy of the string,
           with leading and trailing whitespace omitted.
46
47 //StringBuilder
48 StringBuilder str.insert(int offset,...);
49 StringBuilder str.reverse();
50 void          str.setCharAt(int index,int ch);
51
52 //BigInteger
53 compareTo(); equals(); doubleValue(); longValue();
           hashCode(); toString(); toString(int radix); max();
           min(); mod(); modPow(BigInteger exp, BigInteger m);

```

```

    nextProbablePrime(); pow();
54  andNot(); and(); xor(); not(); or(); getLowestSetBit();
    bitCount(); bitLength(); setBig(int n); shiftLeft(int
    n); shiftRight(int n);
55  add(); divide(); divideAndRemainder(); remainder();
    multiply(); subtract(); gcd(); abs(); signum(); negate
    ();
56
57  //BigDecimal
58  movePointLeft(); movePointRight(); precision();
    stripTrailingZeros(); toBigInteger(); toPlainString();

```

5.4 others

```

1  chmod +x [filename]
2
3  while true; do
4  ./gen > input
5  ./sol < input > output.sol
6  ./bf < input > output.bf
7
8  diff output.sol output.bf
9  if [ $? -ne 0 ]; then break fi
10 done
11
12
13 1

14 2 calm_down(); calm_down(); calm_down();
15 3
16 4
17 5          3 0 m i n          T M          ,

```


Chapter 6

search

6.1 dlx

```
1                                     0 1
2
3
4                                     0 1
5
```

6.2 dlx - precise cover.cpp

```
1 #include<cstdio>
2
3 #define INF 0x7FFFFFFF
4 #define MAXN 1000010
5
6 int n, m, size;
7 int L[MAXN], R[MAXN], U[MAXN], D[MAXN], H[MAXN];
8 int S[MAXN], C[MAXN], X[MAXN], Q[MAXN];
9
10 void Init()
11 {
12     int i;
13     for (i = 0; i <= m; i++)
14     {
15         S[i] = 0;
16         L[i + 1] = i;
```

```

17         R[i] = i + 1;
18         U[i] = D[i] = i;
19     }
20     R[m] = 0;
21     size = m + 1;
22 }
23 void Remove(int c)
24 {
25     int i, j;
26     R[L[c]] = R[c];
27     L[R[c]] = L[c];
28     for (i = D[c]; i != c; i = D[i])
29     {
30         for (j = R[i]; j != i; j = R[j])
31         {
32             D[U[j]] = D[j];
33             U[D[j]] = U[j];
34             S[C[j]]--;
35         }
36     }
37 }
38 void Resume(int c)
39 {
40     int i, j;
41     R[L[c]] = c;
42     L[R[c]] = c;
43     for (i = D[c]; i != c; i = D[i])
44     {
45         for (j = R[i]; j != i; j = R[j])
46         {
47             U[D[j]] = j;
48             D[U[j]] = j;
49             S[C[j]]++;
50         }
51     }
52 }
53 void Link(int r, int c)
54 {
55     D[size] = D[c];
56     U[size] = c;
57     U[D[c]] = size;
58     D[c] = size;
59     if (H[r] < 0)
60         H[r] = L[size] = R[size] = size;
61     else
62     {

```

```

63         L[size] = H[r];
64         R[size] = R[H[r]];
65         L[R[H[r]]] = size;
66         R[H[r]] = size;
67     }
68     S[c]++;
69     C[size] = c;
70     X[size++] = r;
71 }
72 bool Dance(int now)
73 {
74     int i, j, c, temp;
75     if (R[0] == 0)
76         return true;
77     for (temp = INF, i = R[0]; i; i = R[i])
78     {
79         if (S[i] < temp)
80         {
81             c = i;
82             temp = S[i];
83         }
84     }
85     Remove(c);
86     for (i = D[c]; i != c; i = D[i])
87     {
88         for (j = R[i]; j != i; j = R[j])
89             Remove(C[j]);
90         if (Dance(now + 1))
91             return true;
92         for (j = L[i]; j != i; j = L[j])
93             Resume(C[j]);
94     }
95     Resume(c);
96     return false;
97 }

```

6.3 dlx - repeat cover.cpp

```

1 #include<cstdio>
2 #include<cstring>
3 #include<algorithm>
4
5 #define MAXN 110
6 #define MAXM 1000000
7 #define INF 0x7FFFFFFF
8

```

```

9  using namespace std;
10
11  int G[MAXN][MAXN];
12  int L[MAXM], R[MAXM], U[MAXM], D[MAXM];
13  int size, ans, S[MAXM], H[MAXM], C[MAXM];
14  bool vis[MAXN * 100];
15  void Link(int r, int c)
16  {
17      U[size] = c;
18      D[size] = D[c];
19      U[D[c]] = size;
20      D[c] = size;
21      if (H[r] < 0)
22          H[r] = L[size] = R[size] = size;
23      else
24      {
25          L[size] = H[r];
26          R[size] = R[H[r]];
27          L[R[H[r]]] = size;
28          R[H[r]] = size;
29      }
30      S[c]++;
31      C[size++] = c;
32  }
33  void Remove(int c)
34  {
35      int i;
36      for (i = D[c]; i != c; i = D[i])
37      {
38          L[R[i]] = L[i];
39          R[L[i]] = R[i];
40      }
41  }
42  void Resume(int c)
43  {
44      int i;
45      for (i = D[c]; i != c; i = D[i])
46          L[R[i]] = R[L[i]] = i;
47  }
48  int A()
49  {
50      int i, j, k, res;
51      memset(vis, false, sizeof(vis));
52      for (res = 0, i = R[0]; i; i = R[i])
53      {
54          if (!vis[i])

```

```

55         {
56             res++;
57             for (j = D[i]; j != i; j = D[j])
58             {
59                 for (k = R[j]; k != j; k = R[k])
60                     vis[C[k]] = true;
61             }
62         }
63     }
64     return res;
65 }
66 void Dance(int now)
67 {
68     if (R[0] == 0)
69         ans = min(ans, now);
70     else if (now + A() < ans)
71     {
72         int i, j, temp, c;
73         for (temp = INF, i = R[0]; i; i = R[i])
74         {
75             if (temp > S[i])
76             {
77                 temp = S[i];
78                 c = i;
79             }
80         }
81         for (i = D[c]; i != c; i = D[i])
82         {
83             Remove(i);
84             for (j = R[i]; j != i; j = R[j])
85                 Remove(j);
86             Dance(now + 1);
87             for (j = L[i]; j != i; j = L[j])
88                 Resume(j);
89             Resume(i);
90         }
91     }
92 }
93 void Init(int m)
94 {
95     int i;
96     for (i = 0; i <= m; i++)
97     {
98         R[i] = i + 1;
99         L[i + 1] = i;
100        U[i] = D[i] = i;

```

```

101         S[i] = 0;
102     }
103     R[m] = 0;
104     size = m + 1;
105 }

```

6.4 fibonacci knapsack.cpp

```

1  #include<stdio.h>
2  #include<stdlib.h>
3  #include<algorithm>
4
5  #define MAXX 71
6
7  struct mono
8  {
9      long long weig, cost;
10 } goods[MAXX];
11
12 short n, T, t, i;
13 long long carry, sumw, sumc;
14 long long ans, las[MAXX];
15
16 int com(const void *n, const void *m)
17 {
18     struct mono *a=(struct mono *)n, *b=(struct mono *)m;
19     if(a->weig!=b->weig)
20         return a->weig-b->weig;
21     else
22         return b->cost-a->cost;
23 }
24
25 bool comp(const struct mono a, const struct mono b)
26 {
27     if(a.weig!=b.weig)
28         return a.weig<b.weig;
29     else
30         return b.cost<a.cost;
31 }
32
33 void dfs(short i, long long cost_n, long long carry_n, short
        last)
34 {
35     if(ans<cost_n)
36         ans=cost_n;

```

```

37     if(i==n || goods[i].weig>carry_n || cost_n+las[i]<=
        ans)
38         return;
39     if(last || (goods[i].weig!=goods[i-1].weig && goods[i]
        ].cost>goods[i-1].cost))
40         dfs(i+1,cost_n+goods[i].cost,carry_n-goods[i].
            weig,1);
41     dfs(i+1,cost_n,carry_n,0);
42 }
43
44 int main()
45 {
46     // freopen("asdf","r",stdin);
47     scanf("%hd",&T);
48     for(t=1;t<=T;++t)
49     {
50         scanf("%hd%lld",&n,&carry);
51         sumw=0;
52         sumc=0;
53         ans=0;
54         for(i=0;i<n;++i)
55         {
56             scanf("%lld%lld",&goods[i].weig,&goods[i].
                cost);
57             sumw+=goods[i].weig;
58             sumc+=goods[i].cost;
59         }
60         if(sumw<=carry)
61         {
62             printf("Case_%hd:_%lld\n",t,sumc);
63             continue;
64         }
65         // qsort(goods,n,sizeof(struct mono),com);
66         std::sort(goods,goods+n,comp);
67         for(i=0;i<n;++i)
68         {
69             // printf("%lld %lld\n",goods[i].weig,goods[i]
                ].cost);
70             las[i]=sumc;
71             sumc-=goods[i].cost;
72         }
73         dfs(0,0,carry,1);
74         printf("Case_%hd:_%lld\n",t,ans);
75     }
76     return 0;
77 }

```


Chapter 7

string

7.1 aho corasick.cpp

```
1  #include<cstring>
2  #include<queue>
3
4  #define MAX 1000111
5  #define N 26
6
7  int  nxt[MAX][N], fal[MAX], cnt;
8  bool ed[MAX];
9  char buf[MAX];
10
11 inline void init(int a)
12 {
13     memset(nxt[a], 0, sizeof(nxt[0]));
14     fal[a]=0;
15     ed[a]=false;
16 }
17
18 inline void insert()
19 {
20     static int i, p;
21     for(i=p=0; buf[i]; ++i)
22     {
23         if(!nxt[p][map[buf[i]]])
24             init(nxt[p][map[buf[i]]]=++cnt);
25         p=nxt[p][map[buf[i]]];
26     }
27     ed[p]=true;
28 }
```

```

29
30 inline void make()
31 {
32     static std::queue<int>q;
33     int i,now,p;
34     q.push(0);
35     while(!q.empty())
36     {
37         now=q.front();
38         q.pop();
39         for(i=0;i<N;++i)
40             if(nxt[now][i])
41             {
42                 q.push(p=nxt[now][i]);
43                 if(now)
44                     fal[p]=nxt[fal[now]][i];
45                 ed[p]=ed[fal[p]];
46             }
47             else
48                 nxt[now][i]=nxt[fal[now]][i];
49     }
50 }

```

7.2 manacher.cpp

```

1  #include<cstdio>
2  #include<vector>
3
4  #define MAXX 1111
5
6  std::vector<char>str;
7  char buf[MAXX];
8  int z[MAXX<<1];
9  int i,j,l,r;
10 int ii,n,c;
11
12 inline int match(const int &a,const int &b)
13 {
14     int i(0);
15     while(a-i>=0 && b+i<str.size() && str[a-i]==str[b+i])
16         ++i;
17     return i;
18 }
19
20 int main()
21 {

```

```

22     gets (buf);
23     str.reserve (MAXX<<1);
24     for (i=0;buf[i];++i)
25     {
26         str.push_back ( '$' );
27         str.push_back ( buf[i] );
28     }
29     str.push_back ( '$' );
30
31     z[0]=1;
32     c=l=r=0;
33     for (i=1;i<str.size();++i)
34     {
35         ii=(l<<1)-i;
36         n=r+1-i;
37
38         if (i>r)
39         {
40             z[i]=match(i,i);
41             l=i;
42             r=i+z[i]-1;
43         }
44         else
45             if (z[ii]==n)
46             {
47                 z[i]=n+match(i-n,i+n);
48                 l=i;
49                 r=i+z[i]-1;
50             }
51             else
52                 z[i]=std::min(z[ii],n);
53         if (z[i]>z[c])
54             c=i;
55     }
56
57     for (i=c-z[c]+2,n=c+z[c];i<n;i+=2)
58         putchar (str[i]);
59     puts ("");
60     return 0;
61 }

```

7.3 morris-pratt.cpp

```

1  int i,j;
2
3  inline void make(char *buf,int *fal)

```

```

4  {
5      fal[0] = -1;
6      for (i=1, j=-1; buf[i]; ++i)
7      {
8          while (j >= 0 && buf[j+1] != buf[i])
9              j = fal[j];
10         if (buf[j+1] == buf[i])
11             ++j;
12         fal[i] = j;
13     }
14
15 }
16
17 inline int void match(char *p, char *t, int* fal)
18 {
19     for (i=0, j=-1; t[i]; ++i)
20     {
21         while (j >= 0 && p[j+1] != t[i])
22             j = fal[j];
23         if (p[j+1] == t[i])
24             ++j;
25         if (!p[j+1])
26         {
27             //
28             j = fal[j];
29         }
30     }

```

7.4 smallest representation.cpp

```

1  int min(char a[], int len)
2  {
3      int i = 0, j = 1, k = 0;
4      while (i < len && j < len && k < len)
5      {
6          int cmp = a[(j+k)%len] - a[(i+k)%len];
7          if (cmp == 0)
8              k++;
9          else
10         {
11             if (cmp > 0)
12                 j += k+1;
13             else
14                 i += k+1;
15             if (i == j) j++;
16             k = 0;

```

```

17         }
18     }
19     return std::min(i, j);
20 }

```

7.5 suffix array - da.cpp

```

1  int wx[maxn], wy[maxn], *x, *y, wss[maxn], wv[maxn];
2
3  bool cmp(int *r, int n, int a, int b, int l)
4  {
5      return a+l<n && b+l<n && r[a]==r[b]&&r[a+l]==r[b+l];
6  }
7  void da(int str[], int sa[], int rank[], int height[], int n,
8          int m)
9  {
10     int *s = str;
11     int *x=wx, *y=wy, *t, p;
12     int i, j;
13     for(i=0; i<m; i++)
14         wss[i]=0;
15     for(i=0; i<n; i++)
16         wss[x[i]=s[i]]++;
17     for(i=1; i<m; i++)
18         wss[i]+=wss[i-1];
19     for(i=n-1; i>=0; i--)
20         sa[--wss[x[i]]]=i;
21     for(j=1, p=1; p<n && j<n; j*=2, m=p)
22     {
23         for(i=n-j, p=0; i<n; i++)
24             y[p++]=i;
25         for(i=0; i<n; i++)
26             if(sa[i]-j>=0)
27                 y[p++]=sa[i]-j;
28         for(i=0; i<n; i++)
29             wv[i]=x[y[i]];
30         for(i=0; i<m; i++)
31             wss[i]=0;
32         for(i=0; i<n; i++)
33             wss[wv[i]]++;
34         for(i=1; i<m; i++)
35             wss[i]+=wss[i-1];
36         for(i=n-1; i>=0; i--)
37             sa[--wss[wv[i]]]=y[i];
38         for(t=x, x=y, y=t, p=1, i=1, x[sa[0]]=0; i<n; i++)
39             x[sa[i]]=cmp(y, n, sa[i-1], sa[i], j)?p-1:p++;

```

```

39     }
40     for (int i=0; i<n; i++)
41         rank[sa[i]]=i;
42     for (int i=0, j=0, k=0; i<n; height[rank[i++]]=k)
43         if (rank[i]>0)
44             for (k?k--:0, j=sa[rank[i]-1]; i+k < n && j+k <
45                  n && str[i+k]==str[j+k]; ++k);

```

7.6 suffix array.cpp

```

1  #include<cstdio>
2  #include<cstring>
3  #include<algorithm>
4
5  #define MAXX 1111
6  #define F(x) ((x)/3+((x)%3==1?0:tb))
7  #define G(x) ((x)<tb?(x)*3+1:((x)-tb)*3+2)
8
9  int wa[MAXX], wb[MAXX], wv[MAXX], ws[MAXX];
10
11 inline bool c0(const int *str, const int &a, const int &b)
12 {
13     return str[a]==str[b] && str[a+1]==str[b+1] && str[a
14         +2]==str[b+2];
15 }
16 inline bool c12(const int *str, const int &k, const int &a,
17     const int &b)
18 {
19     if (k==2)
20         return str[a]<str[b] || str[a]==str[b] && c12(str
21             , 1, a+1, b+1);
22     else
23         return str[a]<str[b] || str[a]==str[b] && wv[a
24             +1]<wv[b+1];
25 }
26
27 inline void sort(int *str, int *a, int *b, const int &n,
28     const int &m)
29 {
30     memset(ws, 0, sizeof(ws));
31     int i;
32     for (i=0; i<n; ++i)
33         ++ws[wv[i]=str[a[i]]];
34     for (i=1; i<m; ++i)

```

```

31         ws[i]+=ws[i-1];
32     for (i=n-1;i>=0;--i)
33         b[--ws[wv[i]]]=a[i];
34 }
35
36 inline void dc3(int *str,int *sa,const int &n,const int &
    m)
37 {
38     int *strn(str+n);
39     int *san(sa+n),tb((n+1)/3),ta(0),tbc(0),i,j,k;
40     str[n]=str[n+1]=0;
41     for (i=0;i<n;++i)
42         if (i%3)
43             wa[tbc++]=i;
44     sort(str+2,wa,wb,tbc,m);
45     sort(str+1,wb,wa,tbc,m);
46     sort(str,wa,wb,tbc,m);
47     for (i=j=1,strn[F(wb[0])]=0;i<tbc;++i)
48         strn[F(wb[i])]=c0(str,wb[i-1],wb[i])?j-1:j++;
49     if (j<tbc)
50         dc3(strn,san,tbc,j);
51     else
52         for (i=0;i<tbc;++i)
53             san[strn[i]]=i;
54     for (i=0;i<tbc;++i)
55         if (san[i]<tb)
56             wb[ta++]=san[i]*3;
57     if (n%3==1)
58         wb[ta++]=n-1;
59     sort(str,wb,wa,ta,m);
60     for (i=0;i<tbc;++i)
61         wv[wb[i]]=G(san[i])=i;
62     for (i=j=k=0;i<ta && j<tbc;)
63         sa[k++]=c12(str,wb[j]%3,wa[i],wb[j])?wa[i++]:wb[j
            ++];
64     while (i<ta)
65         sa[k++]=wa[i++];
66     while (j<tbc)
67         sa[k++]=wb[j++];
68 }
69
70 int rk[MAXX],lcpa[MAXX],sa[MAXX*3];
71 int str[MAXX*3]; //      i n t
72
73 int main()
74 {

```

```

75     scanf ("%d_%d",&n,&j);
76     for ( i=0;i<n;++i )
77     {
78         scanf ("%d",&k);
79         num[ i]=k-j+100;
80         j=k;
81     }
82     num[n]=0;
83
84     dc3(num,sa,n+1,191); //191:
                        s t r
85
86     for ( i=1;i<=n;++i ) // r a n k
87         rk[ sa[ i ] ] = i;
88     for ( i=k=0;i<n;++i ) // l c p
89         if ( !rk[ i ] )
90             lcpa[0]=0;
91     else
92     {
93         j=sa[ rk[ i ] -1 ];
94         if (k>0)
95             --k;
96         while (num[ i+k]==num[ j+k ])
97             ++k;
98         lcpa[ rk[ i ] ] = k;
99     }
100
101
102     for ( i=1;i<=n;++i )
103         sptb[0][ i ] = i;
104     for ( i=1;i<=lg[ n ];++i ) //sparse table RMQ
105     {
106         k=n+1-(1<<i);
107         for ( j=1;j<=k;++j )
108         {
109             a=sptb[ i-1 ][ j ];
110             b=sptb[ i-1 ][ j+(1<<(i-1)) ];
111             sptb[ i ][ j ] = lcpa[ a ] < lcpa[ b ] ? a : b;
112         }
113     }
114 }
115
116 inline int ask(int l,int r)
117 {
118     a=lg[ r-l+1 ];
119     r--=(1<<a)-1;

```



```

120     l=sptb[a][l];
121     r=sptb[a][r];
122     return lcpa[l]<lcpa[r]?l:r;
123 }
124
125 inline int lcp(int l,int r) //           [l,r]
           r m q
126 {
127     l=rk[l];
128     r=rk[r];
129     if(l>r)
130         std::swap(l,r);
131     return lcpa[ask(l+1,r)];
132 }

```

7.7 z algorithm.cpp

```

1  inline void make(int *z,char *buf)
2  {
3      int i,j,l,r;
4      l=0;
5      r=1;
6      z[0]=strlen(buf);
7      for(i=1;i<z[0];++i)
8          if(r<=i || z[i-1]>=r-i)
9              {
10                 j=std::max(i,r);
11                 while(j<z[0] && buf[j]==buf[j-i])
12                     ++j;
13                 z[i]=j-i;
14                 if(i<j)
15                     {
16                         l=i;
17                         r=j;
18                     }
19             }
20         else
21             z[i]=z[i-1];
22     }
23
24     for(i=1;i<len && i+z[i]<len;++i); //i=

```