

APPLICATION HANDBOOK

# MADCreate User Manual

A detailed operator guide for the AI-native website and business-system generator.

## Document scope

Prepared from the current MADCreate repository structure, frontend routes, .NET Core modules, shared TypeScript contracts, Entity Framework Core, and deployment notes. Where infrastructure notes and code disagree, the documents call out the reconciliation point instead of hiding it.

Generated for MAD Prospects. Current canonical public domains: <https://madcreate.madprospects.com> and <https://madcreateapi.madprospects.com>.

# How To Use This Manual

This manual is written for owners, super administrators, workspace operators, client-facing implementation teams, and support staff. It explains what MADCreate does, how the screens fit together, and how the backend systems support each workflow.

## Practical route map

- Public pages: landing, pricing, login, registration, email verification, password reset, magic-link sign-in, and workspace invitation acceptance.
- Authenticated platform: /app/home, onboarding, tenants, sites, AI Studio, visual builder, themes, domains, integrations, deployments, analytics, leads, media, marketplace, settings, Claude tasks, and super-admin.
- Public tenant rendering: /:slug and /:slug/:page render generated websites from stored site, page, section, theme, navigation, SEO, and media data.

## Core Concept

MADCreate is a multi-tenant SaaS platform that lets a team generate, edit, publish, host, and operate websites or lightweight business systems. It combines an Angular SPA, a .NET Core REST API, Entity Framework Core relational data, a shared TypeScript contract package, queue workers for long-running work, and deployment adapters for multiple publishing targets.

### Plain-English model

A workspace is the customer account. A tenant is a deployable client brand, site, or business instance inside that workspace. A tenant owns sites, pages, sections, themes, domains, deployments, integrations, media, analytics events, forms, and leads.

## Architecture at a glance

| Layer                            | What it does                                                                                                                | Important implementation notes                                                                                                              |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Angular web app                  | Provides marketing, auth, dashboard, builder, analytics, and public tenant rendering.                                       | Standalone components, route-level lazy loading, Tailwind styling, auth/workspace interceptors, and a dynamic renderer for section schemas. |
| .NET Core API                    | Owns auth, tenant/workspace access, AI generation, CRUD, deployments, domains, billing, forms, media, and admin operations. | Global /v1 prefix, validation pipe, response wrapper, audit interceptor, throttling, pino logging, Swagger in non-production.               |
| Entity Framework Core data model | Stores identity, workspace membership, tenant content, AI records, integrations, analytics, billing, and audit logs.        | Repository schema declares a SQL Server datasource using the MADProspects production MSSQL host.                                            |
| Queues and workers               | Handle AI generation, deployment runs, email work, and background tasks.                                                    | BullMQ queues are wired through the queue module; deployment and AI modules expose event streams for live UI updates.                       |
| Public renderer                  | Turns JSON content into themed websites at tenant slugs and custom domains.                                                 | Fetches render payloads from /v1/render/site and dispatches each section kind to a matching Angular section component.                      |

## Roles And Access

MADCreate uses role-aware access at the platform and workspace level. The codebase defines SUPER\_ADMIN, WORKSPACE\_OWNER, ADMIN, EDITOR, VIEWER, and CLIENT. The Angular app uses an auth guard for /app and a super-admin guard for /app/admin; the API uses JWT guards, role decorators, and tenant/workspace checks in services.

| Role            | Typical purpose                      | Expected capabilities                                                                                              |
|-----------------|--------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| SUPER_ADMIN     | Platform operator.                   | Access admin overview, tenant administration, feature flags, suspension, deletion, and cross-tenant support views. |
| WORKSPACE_OWNER | Account owner and billing authority. | Manage workspace settings, members, billing portal, tenants, sites, and deployments.                               |
| ADMIN           | Operational lead.                    | Manage most workspace and tenant assets, publish content, configure domains and integrations.                      |
| EDITOR          | Content and build user.              | Create and edit pages, themes, AI generations, media, leads, and deployments where permitted.                      |
| VIEWER / CLIENT | Read-only or client review user.     | Inspect assigned workspace/tenant output and analytics with limited mutation rights.                               |

## Authentication Workflows

The authentication surface supports registration, login, refresh tokens, logout, password reset, email verification, password change, magic-link request/exchange, and invitation acceptance. The frontend stores tokens through the auth service and appends bearer tokens through an interceptor.

- 1 A user registers or accepts a workspace invite.
- 2 The API creates or links the user, workspace membership, and refresh-token state.
- 3 On login, the user receives access and refresh tokens plus workspace context.
- 4 The web app stores the session and redirects into /app/home.
- 5 The workspace interceptor adds X-Workspace-Id to normal dashboard requests when a workspace is selected.

### Security note

Do not embed live passwords in operator PDFs or screenshots. Store production super-admin credentials in the approved password vault, rotate them after provisioning, and use per-user accounts for day-to-day work.

## Workspace Home

The dashboard home is the operator landing point after login. It loads the current workspace, lists tenants, and shows aggregate stats for tenants, sites, AI generations, and deployments. It is intended to answer: what am I responsible for, what exists already, and where should I go next?

## Onboarding

Onboarding guides a user through the first tenant/site setup. It captures business details, industry, goals, desired integrations, and website requirements. It can create a tenant, save onboarding answers, suggest integrations by industry, and trigger generation through the AI pipeline.

| Step                  | User goal                                                 | System behavior                                                                            |
|-----------------------|-----------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Business profile      | Describe the client, offer, industry, tone, and audience. | Saves structured onboarding answers against the selected tenant.                           |
| Integration selection | Choose useful apps and channels.                          | Loads the integration catalog and /integrations/suggest output for the industry.           |
| Generate              | Produce a first website draft.                            | Calls /onboarding/generate, creates an AI generation record, then polls generation status. |
| Review                | Inspect and refine the draft.                             | Links into the tenant, site detail, AI Studio, or builder workflows.                       |

## Tenants

Tenants are the central client/project container. The tenants list shows all tenants in the selected workspace. Tenant detail provides deeper information and links into related sites, domains, deployment history, onboarding, and editing tools. Tenant records also support soft deletion and administrative suspension/purge operations.

## Sites, Pages, And Sections

A site belongs to a tenant and contains pages. A page contains a schema with ordered sections. Sections are typed blocks such as hero, features, logos, testimonials, pricing, FAQ, CTA, gallery, team, stats, contact, rich-text, video, newsletter, footer, header, split, and steps. This schema is the contract between AI generation, storage, editing, publishing, and rendering.

| Object  | What it represents                                                                     | Where users meet it                             |
|---------|----------------------------------------------------------------------------------------|-------------------------------------------------|
| Site    | A deployable website/application shell with status, navigation, settings, and version. | Sites list, site detail, deployments, renderer. |
| Page    | A route-level document such as home, about, services, pricing, or contact.             | Site detail, builder, publish actions.          |
| Section | A reusable content and layout block inside a page.                                     | Builder and public site renderer.               |
| Theme   | Color, typography, spacing, and visual tokens.                                         | Themes page, renderer CSS variables.            |

## Visual Builder

The builder opens a page by page id, shows the page schema, allows operators to modify sections, saves updates through /pages/:id, publishes through /pages/:id/publish, and can request AI-generated section content. It is the hands-on editing surface for turning generated output into production-ready client material.

- Use builder edits for copy, section ordering, section props, and publication readiness.
- Use the site detail page for page creation, deletion, and site-level publishing.

- Use themes for global visual direction rather than one-off section styling where possible.

## AI Studio

AI Studio is the generation control room. Operators choose a tenant, submit generation requests, watch history, and receive live updates via server-sent events when available. The backend supports generation kinds including site, page, section, copy, theme, palette, typography, image prompt, SEO, schema, and workflow.

### AI generation lifecycle

- 1 The frontend posts a generation request to `/v1/ai/generate` with kind, prompt variables, and tenant context.
- 2 The API creates an `AIGeneration` record with status `QUEUED` and enqueues work.
- 3 A worker picks the job, calls the configured provider, captures output, tokens, cost, and duration.
- 4 The result is stored as JSON and exposed through `/ai/generations` and `/ai/generations/:id`.
- 5 Some results can be submitted/applied back into `site/page/theme` records.

## Themes

Themes manage design tokens. A tenant can have multiple themes, one active theme, and AI-generated palettes. The public renderer applies active theme tokens to CSS variables, which lets generated sites keep a coherent brand without manually restyling every section.

## Domains

Domains connect a tenant to public hostnames. The domains page lets users add hostnames, view DNS instructions, verify records, and delete domains. The API supports domain types `SUBDOMAIN`, `APEX`, `CNAME`, and `WILDCARD` with statuses `PENDING`, `VERIFYING`, `ACTIVE`, `FAILED`, and `DISABLED`.

| Domain task       | What the user does                     | What the platform checks                                          |
|-------------------|----------------------------------------|-------------------------------------------------------------------|
| Add domain        | Enter hostname and select type.        | Creates a domain record and verification token.                   |
| Read instructions | Copy CNAME/TXT or other DNS guidance.  | Returns values from <code>/domains/:id/instructions</code> .      |
| Verify            | Click verify after DNS has propagated. | Looks up DNS records and activates the domain when records match. |
| Render            | Visit the custom hostname.             | Tenant middleware and render service resolve the tenant by host.  |

## Deployments

Deployments publish or export tenant output. The deployments page lists recent runs, can trigger a target-specific deployment, can cancel pending/running work, and receives live updates. A deployment record tracks target, status, log, artifact URL, version, timing, and triggering user.

| Target   | Purpose                                                                 |
|----------|-------------------------------------------------------------------------|
| INTERNAL | Publish inside the MADCreate platform and bump the active site version. |

| Target           | Purpose                                                             |
|------------------|---------------------------------------------------------------------|
| STATIC_EXPORT    | Write static HTML output for handoff, archive, or external hosting. |
| FTP / SFTP       | Push built output to a traditional hosting account.                 |
| CLOUDFLARE_PAGES | Publish through Cloudflare Pages.                                   |
| VERCEL           | Deploy to a Vercel project/team.                                    |
| DIGITAL_OCEAN    | Deploy through DigitalOcean App Platform.                           |
| DOCKER           | Build and push a container image.                                   |
| CUSTOM_WEBHOOK   | Notify an external system that a deployment should happen.          |

## Integrations

The integration catalog provides installable app connectors by category. Users can browse the catalog, install an integration for a tenant with JSON config, list installed integrations, and uninstall them. The current service behavior stores per-tenant configuration and enablement; provider-specific deep sync logic can be added behind the catalog entries.

## Media Library

The media module lets a tenant upload, list, and delete assets. Media records include kind, URLs, metadata, size, uploader, and tenant ownership. Storage is abstracted so local disk can be swapped for object storage when configured.

## Forms And Leads

Generated sites can contain contact or lead forms. The forms API receives public submissions, while the leads UI lets authenticated users list leads by tenant and update lead status. This makes MADCreate more than a brochure builder: it can capture and manage client demand.

| Lead stage | Operational meaning                                   |
|------------|-------------------------------------------------------|
| NEW        | Fresh submission requiring triage.                    |
| CONTACTED  | Someone has reached out to the prospect.              |
| QUALIFIED  | The opportunity is worth active follow-up.            |
| WON / LOST | Outcome is known and can feed reporting.              |
| SPAM       | Submission should be excluded from normal sales work. |

## Analytics

Analytics ingests page views, clicks, form submissions, conversions, AI generation events, deployments, and custom events. The dashboard exposes summary metrics, timeline, time series, top pages, and referrers for a selected tenant and date window.

## Marketplace And Templates

The marketplace lists templates and can instantiate a template into a tenant. Template instantiation clones the full site schema into a new site and pages, giving operators a repeatable starting point for common industries or campaign types.

## Settings, Workspace Members, And Billing

Settings combines profile editing, password change, workspace invite management, member listing, leave-workspace, billing subscription display, Payfast subscription handoff, and account deletion. Workspace owners should use this area to keep team membership and billing data current.

## Super Admin

The super-admin page is reserved for platform operators. It loads platform overview metrics, tenant listings, feature flags, and tenant actions such as suspend, unsuspend, and delete. Use it carefully: the admin surface can affect many customers.

## Claude Tasks And Prompt Templates

MADCreate includes an internal Claude task board and prompt-template manager. The UI can list tasks, create/edit/delete tasks, upload attachments, poll worker settings, import bulk errors, and manage reusable Claude prompt templates. This is an operator automation surface for development, QA, content work, or assisted build tasks.

## Public Site Rendering

The renderer is the customer-facing delivery mechanism. A request to `/:slug` or `/:slug/:page` loads tenant/site JSON through `/render/site`, applies active theme tokens, updates page metadata, and renders each section with a matching component. The API also provides dynamic robots.txt and sitemap.xml endpoints.

### Renderer principle

Generated sites are data-driven. A published page is not hard-coded Angular markup; it is a typed page schema interpreted by the renderer. That is what makes AI generation, template cloning, builder edits, and multi-tenant hosting work together.

## Operational Checklist

- Confirm canonical domains and CORS origins: `https://madcreate.madprospects.com` and `https://madcreateapi.madprospects.com`.
- Confirm database provider and connection target before migrations; repository schema and latest infrastructure notes currently need reconciliation.
- Provision a super-admin account without publishing its password in documentation.
- Keep `API_CORS_ORIGINS`, JWT secrets, SMTP, Payfast, Cloudflare, storage, AI provider keys, and deployment credentials in environment configuration.

- Run health and readiness checks after deploy, then smoke-test login, tenant list, render payload, and a deployment target.
- Keep pnpm store centralized at C:/Code/.pnpm when maintaining the Windows workspace.

## Troubleshooting Guide

| Symptom                           | Likely area                   | First checks                                                                                               |
|-----------------------------------|-------------------------------|------------------------------------------------------------------------------------------------------------|
| Login blocked by browser CORS     | API bootstrap / hosting proxy | Check API_CORS_ORIGINS, OPTIONS handling, Apache/IIS/web.config headers, and API process restart.          |
| Dashboard loads but data is empty | Workspace context             | Check stored workspace id, X-Workspace-Id header, membership status, and /workspaces response.             |
| Generated site does not render    | Tenant/site/page status       | Confirm tenant slug, published site/page, active theme, /render/site response, and browser console.        |
| Domain stuck pending              | DNS verification              | Confirm CNAME/TXT values, DNS propagation, Cloudflare proxy mode, and verify endpoint logs.                |
| Deployment hangs                  | BullMQ/worker                 | Check Redis, queue processor, deployment log, target credentials, and worker process status.               |
| AI generation never completes     | Provider/queue                | Check queue worker, API key, prompt template, provider output JSON validity, and AIGeneration error field. |

## Glossary

| Term                | Definition                                                                                |
|---------------------|-------------------------------------------------------------------------------------------|
| Workspace           | Customer account and billing/team container.                                              |
| Tenant              | A client, brand, business unit, or deployable instance inside a workspace.                |
| Site                | A website/application shell owned by a tenant.                                            |
| Page schema         | The JSON structure describing page title, SEO, and ordered sections.                      |
| Section             | A typed content/layout block rendered by Angular components.                              |
| Theme token         | Reusable visual value such as colors, fonts, spacing, or radius.                          |
| Deployment adapter  | A target-specific publisher such as internal, SFTP, Cloudflare Pages, Vercel, or webhook. |
| Integration catalog | The list of apps/connectors a tenant can install.                                         |



## Appendix A: Frontend Screen Reference

| Screen            | Route                                         | Primary job                                                                           |
|-------------------|-----------------------------------------------|---------------------------------------------------------------------------------------|
| Landing           | / and /home                                   | Explain the product and route prospects to pricing, login, or registration.           |
| Pricing           | /pricing                                      | Show plans from /billing/plans and start checkout for a workspace when authenticated. |
| Login/Register    | /login and /register                          | Create or resume a platform session.                                                  |
| Invite acceptance | /accept-invite                                | Exchange invitation token and join a workspace.                                       |
| Dashboard home    | /app/home                                     | Show workspace stats and the current tenant portfolio.                                |
| Onboarding        | /app/onboarding and /app/onboarding/:tenantId | Capture client brief and generate an initial tenant/site.                             |
| Tenants           | /app/tenants and /app/tenants/:id             | List, inspect, and manage client/project containers.                                  |
| Sites             | /app/sites and /app/sites/:id                 | List sites, create pages, publish, and open the builder.                              |
| AI Studio         | /app/studio/:tenantId                         | Submit AI generation jobs and review generation history.                              |
| Builder           | /app/builder/:pageId                          | Edit page schema, save changes, publish pages, and request AI section updates.        |
| Themes            | /app/themes                                   | Create, edit, activate, delete, and generate visual themes.                           |
| Domains           | /app/domains                                  | Add hostnames, view DNS instructions, verify, and remove domains.                     |
| Integrations      | /app/integrations                             | Browse catalog, install tenant integrations, and remove installed integrations.       |
| Deployments       | /app/deployments                              | Trigger deployments, watch status, and cancel pending/running jobs.                   |
| Analytics         | /app/analytics                                | Read summary, timeline, timeseries, top pages, and referrer reports.                  |
| Leads             | /app/leads                                    | Review form submissions and update lead status.                                       |
| Media             | /app/media                                    | Upload, list, and delete tenant media assets.                                         |
| Marketplace       | /app/marketplace                              | Browse templates and instantiate them into tenants.                                   |
| Settings          | /app/settings                                 | Manage profile, password, workspace invites/members, billing, and account lifecycle.  |
| Claude            | /app/claude                                   | Operate internal task queue, worker settings, attachments, and prompt templates.      |
| Admin             | /app/admin                                    | Super-admin overview, tenant controls, and feature flags.                             |
| Tenant renderer   | /:slug and /:slug/:page                       | Serve public generated websites.                                                      |

## Appendix B: API Endpoint Map

| Area         | Endpoints                                                                                                                                                                                             | Notes                                                    |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|
| Auth         | POST /auth/register, /auth/login, /auth/refresh, /auth/logout, /auth/password/request-reset, /auth/password/reset, /auth/email/verify, /auth/password/change, /auth/magic/request, /auth/magic        | Session, recovery, verification, and password lifecycle. |
| Users        | GET/PATCH/DELETE /users/me                                                                                                                                                                            | Profile and account self-service.                        |
| Workspaces   | GET /workspaces, GET/PATCH /workspaces/:id, POST /workspaces/:id/invites, GET /workspaces/:id/members, GET /workspaces/:id/stats, POST /workspaces/invites/accept, POST /workspaces/:id/members/leave | Team and account container operations.                   |
| Tenants      | GET/POST /tenants, GET/PATCH/DELETE /tenants/:id, POST /tenants/purge-expired, POST /tenants/:id/purge                                                                                                | Client/project lifecycle.                                |
| Sites/Pages  | GET/POST/PATCH/DELETE /sites and /pages, POST /sites/:id/publish, POST /pages/:id/publish                                                                                                             | Website content structure and publishing.                |
| AI           | POST /ai/generate, GET /ai/generations, GET /ai/generations/:id, POST /ai/generations/:id/submit                                                                                                      | Generation job creation, polling, and apply-back.        |
| Render       | GET /render/site, /render/site/:slug/page/:pageSlug, /render/:slug/robots.txt, /render/:slug/sitemap.xml                                                                                              | Public site payloads and SEO assets.                     |
| Domains      | GET/POST /domains, GET /domains/:id/instructions, POST /domains/:id/verify, DELETE /domains/:id                                                                                                       | Hostname management and DNS verification.                |
| Deployments  | GET/POST /deployments, GET /deployments/:id, POST /deployments/:id/cancel                                                                                                                             | Publishing jobs and history.                             |
| Integrations | GET /integrations/catalog, /integrations/suggest, /integrations/installed, POST /integrations/install, DELETE /integrations/:id                                                                       | Catalog and tenant installation state.                   |
| Forms/Leads  | POST/GET /forms, GET /leads, PATCH /leads/:id                                                                                                                                                         | Public submissions and internal lead management.         |
| Analytics    | POST /analytics/ingest, GET /analytics/summary, /timeline, /timeseries, /top-pages, /referrers                                                                                                        | Event capture and reporting.                             |
| Media        | GET /media, POST /media/upload, DELETE /media/:id                                                                                                                                                     | Tenant asset management.                                 |
| Billing      | GET /billing/plans, /billing/subscription, POST /billing/checkout, /billing/portal, POST /payments/payfast/onsite, POST /payments/payfast/notify                                                      | Plans, subscription state, and Payfast onsite checkout.  |
| Admin        | GET /admin/overview, /admin/tenants, /admin/flags, POST /admin/flags, PATCH /admin/tenants/:id/suspend, PATCH /admin/tenants/:id/unsuspend, DELETE /admin/tenants/:id                                 | Platform operator controls.                              |

## Appendix C: Data Model Reference

| Cluster           | Models                                                                            | Purpose                                                                                                |
|-------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Identity          | User, RefreshToken, EmailVerification, PasswordReset, MagicLink                   | Login, recovery, verification, token rotation, and profile state.                                      |
| Workspace         | Workspace, WorkspaceMember, WorkspaceInvite, ApiKey                               | Account/team boundary, role assignment, invites, and programmatic access.                              |
| Tenant content    | Tenant, Environment, Site, Page, Layout, Section, Theme, Template                 | Client/project, generated site structure, page schema, reusable layouts, themes, and template cloning. |
| Publishing        | Domain, Deployment                                                                | Hostname ownership, DNS verification, deployment target, status, logs, artifacts, and versioning.      |
| AI                | AIPrompt, AIGeneration                                                            | Prompt registry, provider, kind, status, input/output JSON, cost, tokens, and request metadata.        |
| Assets and events | Media, AnalyticsEvent, FormSubmission, Lead                                       | Files, behavioral analytics, public form capture, and lead management.                                 |
| Commercial        | Plan, Subscription, FeatureFlag                                                   | Pricing, workspace entitlement, and feature control.                                                   |
| Operations        | TenantIntegration, IntegrationCatalog, AuditLog, ClaudeTask, ClaudePromptTemplate | Installed apps, app catalog, auditability, task automation, and reusable prompts.                      |

## Appendix D: Section Renderer Reference

| Section kind             | Typical props                                        | Usage guidance                                                             |
|--------------------------|------------------------------------------------------|----------------------------------------------------------------------------|
| hero                     | eyebrow, heading, subheading, CTAs, media, alignment | Use for first impression, offer, proof, and primary action.                |
| features                 | heading, subheading, item list, columns              | Use for benefits, service groups, platform modules, or reasons to believe. |
| pricing                  | tiers, prices, intervals, features, highlighted tier | Use where the offer is productized or package-based.                       |
| faq                      | question/answer list                                 | Use to reduce objections before a CTA or contact form.                     |
| cta                      | heading, subheading, primary/secondary CTA           | Use after proof or near page end to drive action.                          |
| gallery/video/logos      | media references and captions                        | Use visual proof sparingly and keep media optimized.                       |
| team/testimonials/stats  | people, quotes, metrics                              | Use credibility blocks with real proof where possible.                     |
| contact/newsletter/forms | contact fields, form key, copy                       | Use when capture, inquiry, or subscription is the page goal.               |
| rich-text/split/steps    | structured copy, columns, ordered steps              | Use for explanatory content, processes, and detailed service pages.        |

## Appendix E: Operator Runbooks

### Create a new client site

- 1 Create or select the workspace and tenant.
- 2 Complete onboarding with industry, offer, audience, proof, tone, pages, and integration needs.
- 3 Generate the initial site and review AI output in the AI Studio.
- 4 Open site detail, inspect pages, and use the builder for copy and section refinement.
- 5 Configure active theme, upload media, connect forms, and verify analytics.
- 6 Add and verify the production domain.
- 7 Trigger an internal deployment, then run a public render smoke test.
- 8 Share the site or client review link, collect revisions, and publish final pages.

### Recover from a broken public site

- 1 Check the frontend route and browser console.
- 2 Call `/v1/render/site` for the tenant slug and confirm the payload is not empty.
- 3 Confirm tenant, site, page, theme, and domain statuses.
- 4 Check recent deployments and logs.
- 5 If the issue followed a content edit, restore or republish the prior known-good page schema.
- 6 If the issue is domain-specific, test the canonical MADCreate slug and then diagnose DNS/SSL/host resolution.

### Deployment handoff checklist

- Public URL loads on desktop and mobile.
- Primary navigation and CTAs resolve correctly.
- Forms submit and appear in Leads.
- Analytics records at least one test page view.
- Sitemap and robots endpoints respond.
- Domain verification is active and SSL is valid.
- Workspace owner and support contacts are correct.

## Appendix F: Environment And Deployment Notes

MADCreate is intended to run as a .NET Core API and Angular SPA, currently deployed behind DreamHost CloudCompute / Apache reverse proxy according to project notes. The canonical production domains are `madcreate.madprospects.com` and `madcreateapi.madprospects.com`, with API port 3005 behind the proxy.

#### Database standard

MADCreate uses SQL Server at `WINSVRSQL03.hostserv.co.za,1433`. Keep Entity Framework Core, environment examples, docs, and deployment scripts aligned to the same MSSQL connection settings before changing migrations or production data.

| Setting                | Operational guidance                                                                                       |
|------------------------|------------------------------------------------------------------------------------------------------------|
| API_CORS_ORIGINS       | Must include the production frontend origin and local dev origin where needed.                             |
| JWT secrets            | Unique per environment; rotate if exposed.                                                                 |
| DATABASE_URL           | Must match the actual Entity Framework Core provider and target DB engine.                                 |
| REDIS_URL              | Required for queues, workers, and live job behavior.                                                       |
| SMTP                   | Required for verification, reset, magic link, and invites; graceful no-op behavior should still be tested. |
| AI provider keys       | Required for real generation; mock/manual provider paths should be explicit in non-production.             |
| Storage                | Local or object storage; production should avoid accidental ephemeral disk dependence.                     |
| Deployment credentials | Store in environment or vault-backed references, not in tenant-visible config.                             |