

 POLITECNICO DI MILANO



MMSP 2nd Module – Lab2

Nicolò Bonettini
nicolo.bonettini@polimi.it

Scalar quantizers

EXERCISE 1

1. Generate a 1000-sample realization of $x(n) \sim N(\mu, \sigma^2)$ with variance 3 and mean 0
2. Quantize $x(n)$ using:
 1. A scalar mid-tread quantizer with fixed quantization step $\Delta=2$ and plot the input output characteristic
 2. A scalar mid-rise quantizer with fixed quantization step $\Delta=2$ and plot the input output characteristic
 3. A scalar mid-tread quantizer with $M = 4$ output levels and plot the input output characteristic
 4. $cb = [-5, -3, -1, 0, 1, 3, 5]$ as reproduction levels and $th = [-4, -2, -0.5, 0.5, 2, 4]$ as thresholds and plot the input output characteristic
3. For each one of the above quantizers compute the MSE and the SNR

1. Mid-tread quantizer formula:

$$q(x) = \left\lfloor \frac{x}{\Delta} + \frac{1}{2} \right\rfloor * \Delta$$

2. Mid-rise quantizer formula:

$$q(x) = \left(\left\lfloor \frac{x}{\Delta} \right\rfloor + \frac{1}{2} \right) * \Delta$$

Scalar quantizers

EXERCISE 2

1. Generate a 10000-sample realization of $s_g(n) \sim N(0,2)$ and $s_u(n) \sim U$ with variance 2 and mean 0
2. Quantize $s_g(n)$ and $s_u(n)$ with $M=[4,8,16,32,64,128]$ levels and uniform quantizer. Plot R-D curve for each number of levels. Plot the theoretical distortion obtained with a uniform scalar quantizer considering the case of the uniform distributed signal.
3. Design an optimum uniform quantizer and a Lloyd-Max quantizer for $s_g(n)$ with the same levels defined in the previous step. Compare the R-D curves obtained with those quantizers with those obtained with uniform quantizer

1. Use **rand** and **randn** for data generation
2. Use MSE as metric for distortion
3. Use SNR for R-D curves
4. Remember distortion lower bound for Gaussian pdf:

$$\sigma_e^2 = \sigma_x^2 2^{-2R}$$

5. Use **lloyds** and **quantiz** to implement Lloyd-Max

Scalar quantization

EXERCISE 3

1. Suppose that you are sampling the output of a sensor at 10 kHz for 10 seconds. Quantize the output with a uniform quantizer at 10 bit per sample. Assume that the pdf of the signal is gaussian with mean 0 V and variance 4 V^2 . What is the bit rate of the quantized signal?
2. What would be a reasonable choice for the quantization step?
3. What is the MSE?

Vector quantization

EXERCISE 4

1. Consider a 2D vector quantizer with codebook $y_1=(1,2)$, $y_2=(1,4)$, $y_3=(-1,2)$, $y_4=(0,-2)$. Show optimal assignment regions.
2. Quantize the sequence $x=(-4:5)$ using groups of 2 samples at time

1. Use `voronoi` to show a voronoi tessellation of a 2D space
2. Use `dsp.VectorQuantizerEncoder` and `step` to implement the vector quantizer