Project Swagger — Hexagonal Loan Servicing POC

Version 1.0.0 · **Runtime** Angular 18 standalone (browser bundle) · **Source of truth** `src/app`

A Swagger page answers three questions about a service: *what components exist*, *what each one accepts and returns*, and *how they call each other*. This document answers those three questions for an application that has **no HTTP API at all**.

There is no server here. But in Ports & Adapters the **port is the API** — a typed interface the compiler enforces, which is a stricter contract than a URL. So every "endpoint" below is a port operation, every "server" is a binding key, and every "client" is an adapter.

> **Related document.** `../PORTS.md` is the *interface* reference — port signatures and payload schemas in isolation. **This** document is the *component* reference: the parts, their dependencies, and the call sequences between them. Read PORTS.md to implement against a port; read this to understand how a click becomes an answer.

Table of contents


1. How to read this document
2. Component inventory
3. Runtime configuration (the "servers" block)
4. Tag: Driving adapters — UI
5. Tag: Driving ports — deterministic (BLL)
6. Tag: Driving ports — cognitive (CLL)
7. Tag: Driven ports — what the core requires
8. Tag: Driven adapters — the outside world
9. Tag: Domain — entities and rules
10. Tag: Configuration — the composition root
11. Interactions — sequence flows
12. Schemas
13. Enumerations and policies
14. Extending the system

1. How to read this document

The rings — call flow

The application is organised in concentric rings — outer ring (adapters), port ring, core. The diagram below groups them by **side** rather than by ring, so the inbound and outbound paths never cross; each node still names the ring it belongs to.

Every arrow below is a call: who invokes whom at runtime. Dependency direction is a *different* graph — see the note under the diagram, because on the driven side the two point opposite ways.


configuration/ — composition root
the only ring that names concrete classes
constructs core services, supplies their ports, and binds each to the driving port it implements
CORE — the hexagon
CLL · AccountSummaryService
aggregates, then narrates
CLL · Inquiry · ChatInsights · Personalization
proposes, interprets, phrases
BLL · Deterministic region
application services + domain
constructs adapters and binds each to the driven port it implements
findByCredentials()
AuthenticateService only
classifyInquiry() · describeTone() composeWelcome() · getHistory() getJobsForProgram()
② narrateLoan(profile, loan) · narratePayments(payment)
calls to DRIVEN ports with the ① results, already computed
OUTBOUND SIDE — the app drives adapters
Driven ports · port ring
what the core requires — pure TS, zero @angular
fetch users.csv · jobs.csv · chat-summary.csv
HTTPS to Azure
Driven adapters · outer ring
INBOUND SIDE — adapters drive the app
execute() · getSnapshot() · submit()
getLoanInfo() · getProfile() · updateProfile()
checkRateRelief()
classify() · getInsights()
getWelcome() · getJobsForProgram()
summarize()
Driving adapters · outer ring
Angular UI
resolves the port and calls it
Driving ports · port ring
① getProfile() · getLoanInfo() · getSnapshot()
calls to DRIVING ports that are part of 2-step pipeline. CLL drives the BLL through the same doors the UI uses



Reading the labels. Arrows into the port ring carry the *port operation* being invoked; arrows out of it carry what the adapter then does. The `BLL` label is abridged to fit — 7 of its 10 driving operations; `suggestedAmount()`, `fundingSources()` and `getContact()` are omitted. Every other label is complete, and the full set is tabulated in §5 and §6.

Two arrows are worth a second look:

- **`BLL → DVN` is a single operation.** Only `AuthenticateService` reaches a driven port at all. `Payment`, `LoanInfo`, `Profile` and `Eligibility` take **no constructor dependencies** (providers.ts:93-96) — once the `User` is in hand, every authoritative figure is pure computation over it. That is why the money math is trivially testable: no I/O to stub.
- **`getJobsForProgram()` appears on both sides.** `InquiryPort` exposes it as a driving operation and `KnowledgeBasePort` requires it as a driven one; `InquiryService` is a pass-through that adds the borrower's program and location. Same name, opposite directions — a pass-through is exactly what it looks like.

The green box is an **annotation, not a component** — it marks the ① calls rather than sitting between the two boxes at runtime.

The CLL pipeline — figures in, words out

① and ② are stages of one pipeline, not two independent calls. This is the detail the ring diagram would otherwise hide, and it is where the whole CLL/BLL split is actually enforced.

`narrateLoan()` does not reach a driving port. It is a **driven**-port operation — but its *arguments are what the driving ports returned* (account-summary.service.ts:33-41):

```
// ① IN through the driving ports — authoritative values, computed by the BLL
const profile = this.profilePort.getProfile(user);    // → BorrowerProfile
const loan    = this.loanInfoPort.getLoanInfo(user);  // → LoanInfo
const payment = this.paymentPort.getSnapshot(user);   // → PaymentSnapshot

// ② OUT through the driven port — the SAME objects, handed over for phrasing
const [loanSentence, paymentsSentence] = await Promise.all([
  this.languageModel.narrateLoan(profile, loan),
  this.languageModel.narratePayments(payment),
]);
```

The ordering is the guarantee, and the signature is what enforces it. Compare the two driven-port methods:

Signature	Takes	Why
`narrateLoan(profile: BorrowerProfile, loan: LoanInfo)`	**finished domain objects**	There is nothing left to compute. The model cannot re-derive `paidPercent` or `monthsToMaturity` — it is handed the completed object and asked only for a sentence.
`narratePayments(payment: PaymentSnapshot)`	**a finished snapshot**	Same: every figure is already fixed before the call.
`describeTone(label: SentimentLabel)`	**a band already chosen**	`ChatInsightsService` picks the band from the raw score *first*; the model only phrases the label it is given.
`composeWelcome(user: User)`	**a raw `User`**	The exception that proves the rule — this produces pure copy containing no authoritative figure, so there is nothing to protect.

Every method on `LanguageModelPort` returns prose, an enum, or `null` — **never a number**. Combine that with parameters that are already-computed values, and the "model may not compute" rule stops being a convention anyone has to remember: it is checked by the compiler at every call site.

Three pipeline shapes across the cognitive region

`summarize()` is one of three shapes, and the other arrows in the diagram carry the other two. What varies is **when** the core gets the last word. What never varies is **that** it does.

Shape	Where	Order	Why that order
Compute → narrate	`AccountSummaryService.summarize()`	① driving ports produce authoritative figures → ② the model phrases them	The output contains money. The figure must exist, finished, before any model sees it.
Ground → interpret → phrase	`ChatInsightsService.getInsights()`	① a driven port returns a raw signal → the core bands it → ② the model phrases the band already chosen	Facts first, same as above — but the input is a *signal*, not an authoritative figure, so stage ① is a driven port plus local policy rather than a driving port.
Propose → dispose	`InquiryService.classify()`, `PersonalizationService.getWelcome()`	the model answers **first** → the core stamps policy onto the result	Here the model's output *is* the raw material. The core cannot precompute a category or a greeting; it can only decide what the answer is permitted to mean.

The third row is where the invariant is easiest to lose, so it is worth reading closely. `classify()` lets the model pick a category and *then* applies `DETERMINISM_POLICY` to whatever came back; `getWelcome()` takes the model's copy and adds `themeClass` itself. A wrong proposal changes which topic is shown — it cannot change whether that topic is deterministic, and it cannot choose the theme.

Two operations on those arrows are not pipelines at all. `getJobsForProgram()` is a pass-through to the knowledge base adding only program and location; `findByCredentials()` is a one-line delegation in `AuthenticateService`.

And the `DRV → BLL` arrow is a different category of thing entirely. Its seven operations are not pipelines but thin delegations from an application service to a pure domain function — `submit()` → `processPayment()`, `getLoanInfo()` → `buildLoanInfo()`. One hop, no second port. That is precisely why those four services are constructed with no dependencies at all.

About that arrow. The core makes plenty of outbound calls — every other arrow leaving the hexagon above is one. What makes this arrow singular is **where it lands**: it carries the only calls that originate inside the core and arrive at a **driving** port. Everything else the core initiates arrives at a **driven** port.

Be precise about what is singular, because it is not the call count. This arrow carries **three** calls — `getProfile()`, `getLoanInfo()` and `getSnapshot()`, one per driving port — just as the `DRV → BLL` arrow carries seven. What there is only one of is the **origin**: a single component, `AccountSummaryService`, accounts for every core→driving call in the application. The wiring row in §10.2 is the check — it is the one entry whose dependency list contains driving-port keys.

Why that is worth a callout at all: in textbook Ports & Adapters a core component *implements* driving ports and *consumes* driven ones. Consuming a driving port inverts that — this service is acting as a **driver**, a primary actor against its own application, which is why the arrow doubles back instead of continuing outward.

Concretely, `AccountSummaryService` is the only component inside the hexagon that calls driving ports. It takes `ProfilePort`, `LoanInfoPort` and `PaymentPort` in its constructor (account-summary.service.ts:21-27) and invokes them at lines 33-35. The other three cognitive services import only the single driving port they *implement*, and otherwise depend on driven ports alone.

That arrow is the architecture's load-bearing claim, so it is worth stating plainly: **the CLL has no privileged back channel into the BLL.** When the cognitive layer needs an authoritative figure it queues up at the same interface the UI uses — providers.ts:9 puts it as "*they knock on the same doors the UI does.*"

> **Call direction ≠ dependency direction.** On the driven side they are deliberately opposed: the core *calls outward* through `LanguageModelPort`, but the *dependency points inward*, because the port is an interface the core owns and the adapter implements. That inversion is the mechanism that makes the model runtime swappable.
>
> The dependency rule is checkable rather than aspirational — no file under `core/` or `ports/` imports `@angular`, `adapters/`, or `configuration/`:
>
> ```
> grep -rE "from '.*(@angular|adapters/|configuration/)" src/app/core src/app/ports
> # → no matches
> ```

Direction vocabulary

Term	Meaning	Who implements it	Who calls it
Driving port (inbound, primary)	An operation the core **offers**.	The core	A driver — UI, the CLL, a test harness
Driven port (outbound, secondary)	A capability the core **requires**.	An adapter	The core
Driving adapter (primary)	Something that *makes the app do things*.	Angular components	A human
Driven adapter (secondary)	Something the app *reaches out to*.	CSV / HTTP / memory	The core, via a driven port

The two core regions

Region	Folder	Authority	May it produce a number?
Deterministic (BLL)	`core/application/` + `core/domain/`	Authoritative. Money, eligibility, identity.	**Yes** — it is the only place that may.
Cognitive (CLL)	`core/cognitive/`	Advisory. Phrasing, classification, interpretation.	**No** — it obtains authoritative figures only by calling a BLL *driving* port. (It may pass through raw grounding counts from a driven port; those are signals, not figures anyone is accountable for.)

> **The governing invariant: "The CLL proposes, the BLL disposes."** Delete the entire cognitive region and every number in the application still computes correctly. The reverse is not true.

Reading a component entry

Each component below is documented with:

- **Path** — where it lives.
- **Description** — what it is responsible for, and what it is forbidden from doing.
- **Implements / Injects** — the contracts it satisfies and the binding keys it consumes.
- **Operations** — a signature table with parameters, return type and failure behaviour.

---

2. Component inventory

Every row below is a real file in `src/` (row 44 groups the four shared-kernel types). Rings are listed outermost-first within each group.

#	Ring	Component	Path	Kind
1	Bootstrap	`bootstrapApplication`	`src/main.ts`	Entry point
2	Driving adapter	`AppComponent`	`app.component.ts`	Root shell
3	Driving adapter	`routes`	`app.routes.ts`	Route table
4	Driving adapter	`LoginComponent`	`login.component.ts`	Screen
5	Driving adapter	`DashboardComponent`	`dashboard.component.ts`	Screen / orchestrator
6	Driving adapter	`NextPaymentComponent`	`next-payment.component.ts`	Answer card
7	Driving adapter	`LoanBalanceComponent`	`loan-balance.component.ts`	Answer card
8	Driving adapter	`MakePaymentComponent`	`make-payment.component.ts`	Answer card (write)
9	Driving adapter	`UpdateProfileComponent`	`update-profile.component.ts`	Answer card (write)
10	Driving adapter	`JobOpportunitiesComponent`	`job-opportunities.component.ts`	Answer card
11	Driving adapter	`InterestReliefComponent`	`interest-relief.component.ts`	Answer card
12	Driving adapter	`RepaymentOptionsComponent`	`repayment-options.component.ts`	Answer card
13	Driving adapter	`GeneralHelpComponent`	`general-help.component.ts`	Answer card (fallback)
14	Driving adapter	`AccountSummaryComponent`	`account-summary.component.ts`	Always-on card
15	Driving adapter	`ChatInsightsComponent`	`chat-insights.component.ts`	Always-on card
16	Driving adapter	`AiBadgeComponent`	`ai-badge.component.ts`	Presentational marker
17	Driving port	`AuthenticatePort`	`authenticate.port.ts`	BLL interface
18	Driving port	`LoanInfoPort`	`loan-info.port.ts`	BLL interface
19	Driving port	`PaymentPort`	`payment.port.ts`	BLL interface
20	Driving port	`ProfilePort`	`profile.port.ts`	BLL interface
21	Driving port	`EligibilityPort`	`eligibility.port.ts`	BLL interface
22	Driving port	`InquiryPort`	`inquiry.port.ts`	**CLL** interface
23	Driving port	`AccountSummaryPort`	`account-summary.port.ts`	**CLL** interface

#	Ring	Component	Path	Kind
24	Driving port	`ChatInsightsPort`	`chat-insights.port.ts`	**CLL** interface
25	Driving port	`PersonalizationPort`	`personalization.port.ts`	**CLL** interface
26	Driven port	`UserRepositoryPort`	`user-repository.port.ts`	Required capability
27	Driven port	`LanguageModelPort`	`language-model.port.ts`	Required capability
28	Driven port	`KnowledgeBasePort`	`knowledge-base.port.ts`	Required capability
29	Driven port	`ChatHistoryPort`	`chat-history.port.ts`	Required capability
30	Core · BLL	`AuthenticateService`	`authenticate.service.ts`	Use case
31	Core · BLL	`LoanInfoService`	`loan-info.service.ts`	Use case
32	Core · BLL	`PaymentService`	`payment.service.ts`	Use case
33	Core · BLL	`ProfileService`	`profile.service.ts`	Use case
34	Core · BLL	`EligibilityService`	`eligibility.service.ts`	Use case
35	Core · CLL	`InquiryService`	`inquiry.service.ts`	Policy + classification
36	Core · CLL	`AccountSummaryService`	`account-summary.service.ts`	Aggregation + narration
37	Core · CLL	`ChatInsightsService`	`chat-insights.service.ts`	Interpretation
38	Core · CLL	`PersonalizationService`	`personalization.service.ts`	Tone + theme
39	Core · Domain	`user.entity.ts`	`user.entity.ts`	Entity
40	Core · Domain	`loan.entity.ts`	`loan.entity.ts`	Entity + money math
41	Core · Domain	`payment.entity.ts`	`payment.entity.ts`	Entity + money math
42	Core · Domain	`borrower.entity.ts`	`borrower.entity.ts`	Entity + validation
43	Core · Domain	`eligibility.entity.ts`	`eligibility.entity.ts`	Decision rules
44	Core · Domain	`inquiry.type.ts` · `sentiment.type.ts` · `job-posting.type.ts` · `date.utility.ts`	`core/domain/`	Shared kernel
45	Driven adapter	`CsvUserRepository`	`csv-user.repository.ts`	System of record
46	Driven adapter	`MockLanguageModel`	`mock-language-model.ts`	Offline model stub

#	Ring	Component	Path	Kind
47	Driven adapter	`AzureAiLanguageModel`	`azure-ai-language-model.ts`	Live model runtime
48	Driven adapter	`CsvKnowledgeBase`	`csv-knowledge-base.ts`	Grounding source
49	Driven adapter	`CsvChatHistory`	`csv-chat-history.ts`	Grounding source
50	Configuration	`tokens.ts`	`tokens.ts`	13 binding keys
51	Configuration	`providers.ts`	`providers.ts`	Composition root
52	Configuration	`ai.config.ts`	`ai.config.ts`	Model-runtime selection
53	Configuration	`session.store.ts`	`session.store.ts`	Signal-based session
54	Configuration	`auth.guard.ts`	`auth.guard.ts`	Route guard

Data assets. Three of the four driven adapters are backed by a CSV under `src/assets/` rather than by code, so the data set can change without recompiling:

Asset	Read by	Shape
`users.csv`	`CsvUserRepository`	6 borrowers, one row each — the system of record
`jobs.csv`	`CsvKnowledgeBase`	20 postings keyed by `program`, plus a `General` fallback set
`chat-summary.csv`	`CsvChatHistory`	one row per borrower: counts, recap prose, raw `toneScore`

None of them is named anywhere inside `core/` or `ports/` — only the adapter that fetches it knows the filename.

---

3. Runtime configuration (the "servers" block)

The one genuinely swappable piece of infrastructure is the **model runtime** behind `LanguageModelPort`. Selecting it is the OpenAPI equivalent of choosing a server URL — and, exactly like a server block, no application code changes when you switch.

Declared in `ai.config.ts`; resolved once per session and cached.

Mode	Adapter bound	Endpoint	Credential location	Use when
`mock` **(default)**	`MockLanguageModel`	none — in-process	none	Demos, tests, offline. No network, no key.
`proxy`	`AzureAiLanguageModel`	`/api/azure-ai` (same-origin)	**Dev server**, injected by `proxy.conf.js`	The supported way to run against real Azure OpenAI.
`directKey`	`AzureAiLanguageModel`	`https://<resource>.openai.azure.com`	**The browser bundle** — exposed	Throwaway local spikes only. Warns loudly.

Resolution order (later wins): built-in defaults → `window.__AI_CONFIG__` → `?ai=` query parameter (`?ai=mock`, `?ai=proxy`, `?ai=directKey`).

```
// Defaults — src/app/configuration/ai.config.ts
{ mode: 'mock', baseUrl: '/api/azure-ai', deployment: 'gpt-4o-mini',
  apiVersion: '2024-10-21', apiKey: '', timeoutMs: 8000,
  temperature: 0.3, maxTokens: 400 }
```

Degradation contract. In Azure mode the mock is *still constructed* and passed to `AzureAiLanguageModel` as a fallback. Any transport error, timeout, bad status or unparseable payload silently delegates to it. **A missing key degrades the prose; it never breaks the app, and it never affects a number.**

> **Why the query string is captured at module load.** `resolveAiConfig()` runs inside an Angular `useFactory`, which Angular evaluates lazily — on first injection of `LANGUAGE_MODEL_PORT`, i.e. on the dashboard. By then the router has navigated `/?ai=proxy` → `/login` → `/dashboard` and dropped the query string. The module therefore snapshots `window.location.search` at import time.

4. Tag: Driving adapters — UI

Primary adapters. They **initiate**; they never compute. Each resolves ports by **binding key typed to an interface** — no UI file imports a concrete service.

4.1 Route table

`app.routes.ts` — the closest thing this app has to a URL surface.

Path	Component	Guard	Loading	Description
`''`	—	—	—	Redirects to `/login` (`pathMatch: 'full'`).
`/login`	`LoginComponent`	none	lazy	Credential entry. The only route reachable without a session.
`/dashboard`	`DashboardComponent`	`authGuard`	lazy	The whole application. Redirects to `/login` when unauthenticated.
`**`	—	—	—	Any unknown path redirects to `/login` .

4.2 `AppComponent`

Path `ui/app.component.ts` · **Selector** `app-root`

The root shell. Its entire template is `<router-outlet />` . It holds no state and injects no port — deliberately, so the shell carries no business meaning.

4.3 `LoginComponent`

Path `ui/login/login.component.ts` · **Selector** `app-login`

Drives the core through `AuthenticatePort` and, on success, records the borrower in `SessionStore` . It performs **no credential checking of its own** — the only validation it owns is "both boxes are non-empty", which is a form concern, not a business rule.

Injects `AUTHENTICATE_PORT` , `SessionStore` , `Router`

Operation	Signature	Description
`submit()`	`(): void`	Calls `AuthenticatePort.execute` . On a `User` , stores the session and navigates to `/dashboard` . On `null` , sets an "invalid credentials" message. On a rejected promise, sets an "unable to reach the account service" message.

State

Field	Type	Description
`username` / `password`	`string`	Two-way bound form fields.
`loading`	`Signal<boolean>`	True across the async call; disables the button.
`error`	`Signal<string | null>`	The single user-facing failure message.

4.4 `DashboardComponent`

Path `ui/dashboard/dashboard.component.ts` · **Selector** `app-dashboard`

The orchestrator, and the most interesting component in the system. It takes free text, asks the **cognitive** `InquiryPort` to propose a topic, and renders the answer component that topic maps to.

> **The architectural point:** from out here, `INQUIRY_PORT` (cognitive) and `PAYMENT_PORT` (deterministic) are indistinguishable. Both are driving-port binding keys typed to an interface. The UI cannot tell which region answers, and cannot reach either except through a port.

Injects `INQUIRY_PORT`, `PERSONALIZATION_PORT`, `SessionStore`, `Router`

Operation	Signature	Description
`ask()`	`async (): Promise<void>`	Classifies `inquiryText`, then either creates a new answer card or folds the question into the existing card for that topic. No-ops on empty input or while a classification is in flight.
`clearHistory()`	`(): void`	Empties the answer history and the input box.
`logout()`	`(): void`	Clears the session and navigates to `/login`.

State

Field	Type	Description
`user`	`Signal<User | null>`	Read straight from `SessionStore`.
`welcome`	`Signal<WelcomeContent | null>`	Fetched — an `effect` calls `PersonalizationPort.getWelcome` whenever the user changes. Null on first paint and on failure; the template guards with `@if`.
`entries`	`Signal<InquiryEntry[]>`	Answer history, newest first.
`asking`	`Signal<boolean>`	True while the cognitive port is classifying. A real model call has latency.
`highlightedId`	`Signal<number | null>`	Flashes an existing card when a repeat question scrolls to it.

`InquiryEntry` shape

```
{ id: number; queries: string[]; result: InquiryResult }
```

> **Why `queries` is a list — one card per topic.** Every answer component is rendered from `[user]` alone; none receives the question text. Two questions on the same topic would therefore produce byte-identical cards. So the card is reused and each new phrasing is appended to `queries`, then the card is flashed and scrolled to. Nothing the borrower asked disappears, and nothing is duplicated. Repeat detection normalises case, whitespace and trailing punctuation via `sameQuestion()`.

Category → answer component routing (from `dashboard.component.html`)

`InquiryResult.category`	Component rendered	Deterministic?	AI badge shown?
`NEXT_PAYMENT`	`<app-next-payment>`	✅	no
`LOAN_BALANCE`	`<app-loan-balance>`	✅	no
`EXTRA_PAYMENT`	`<app-make-payment>`	✅	no
`PROFILE_UPDATE`	`<app-update-profile>`	✅	no
`HARDSHIP`	`<app-job-opportunities>`	❌	yes
`LIFE_EVENT`	`<app-interest-relief>`	❌	yes
`REPAYMENT_OPTIONS`	`<app-repayment-options>`	❌	yes
`GENERAL` *(default case)*	`<app-general-help>`	❌	yes

The badge is driven by `@if (!entry.result.deterministic)` — the flag comes from the core's fixed policy map, so **the UI's honesty marker is business-controlled, not model-controlled.**

4.5 Answer components

All eight share one contract: `@Input({ required: true }) user!: User`, and each fetches its own figures through a driving port in `ngOnInit`. None receives data from the dashboard beyond the user, and none computes a figure.

Component	Selector	Ports injected	What it renders	Writes?
`NextPaymentComponent`	`app-next-payment`	`PAYMENT_PORT`	Due amount, due date, arrears flag, on-time streak.	no
`LoanBalanceComponent`	`app-loan-balance`	`LOAN_INFO_PORT`	Balance, original amount, rate, % repaid, months to maturity.	no
`MakePaymentComponent`	`app-make-payment`	`PAYMENT_PORT`	Payment form pre-filled from `suggestedAmount()`, funding-source list, confirmation with reference number.	**yes** — `submit()`
`UpdateProfileComponent`	`app-update-profile`	`PROFILE_PORT`	Contact form pre-filled from `getContact()`, validation messages, confirmation reference.	**yes** — `updateProfile()`
`JobOpportunitiesComponent`	`app-job-opportunities`	`INQUIRY_PORT`	Job postings matched to program of study, ordered nearest-first by location. Grounding, not advice. Resolves a `Promise` — the catalog is a CSV asset.	no
`InterestReliefComponent`	`app-interest-relief`	`ELIGIBILITY_PORT`	The rate-relief **verdict**, proposed rate, estimated monthly saving, and `reason` printed verbatim.	no
`RepaymentOptionsComponent`	`app-repayment-options`	`LOAN_INFO_PORT`, `PAYMENT_PORT`, `PROFILE_PORT`, `ELIGIBILITY_PORT`	Payoff scenarios and qualifying conditions. Cognitive framing, **four deterministic sources**.	no
`GeneralHelpComponent`	`app-general-help`	*none*	Static fallback listing supported topics.	no

> `RepaymentOptionsComponent` is the clearest demonstration of the invariant: the topic is classified as **non-deterministic** (it explains levers and scenarios, so it wears the AI badge), yet every figure on the card is pulled from four separate **deterministic** driving ports, and the eligibility verdict remains `EligibilityPort`'s to give. Cognitive framing over authoritative numbers.

4.6 Always-on cards

Rendered on every dashboard load, outside the answer history.

Component	Selector	Port injected	Lifecycle	Description
`AccountSummaryComponent`	`app-account-summary`	`ACCOUNT_SUMMARY_PORT`	`OnInit`	Renders the three authoritative objects **plus** the two narrated sentences. Figures come from `summary.profile/loan/payment` — never parsed out of the prose.
`ChatInsightsComponent`	`app-chat-insights`	`CHAT_INSIGHTS_PORT`	`OnInit`	Conversation recap, session/message counts, and the sentiment reading (emoji, label, tone, blurb).

4.7 `AiBadgeComponent`

Path `ui/shared/ai-badge.component.ts` · **Selector** `app-ai-badge`

Purely presentational; injects nothing.

Input	Type	Default
`label`	`string`	`'AI-assisted'`
`hint`	`string`	`'Wording produced by the cognitive layer (CLL). Every amount, date and eligibility outcome shown here is computed by the deterministic layer (BLL).'`

What the badge does not mean: that the numbers beside it came from a model. The tooltip states the limit rather than just the fact — that is the whole design intent of the component.

---

5. Tag: Driving ports — deterministic (BLL)

Pure TypeScript, **zero `@angular` imports**. These are the authoritative operations. A caller depends on the port interface and never on the class behind it, resolving the implementation through the composition root's key:

```
import { inject } from '@angular/core';
import { PaymentPort } from '../ports/driving/payment.port';
import { PAYMENT_PORT } from '../configuration/tokens';

class SomeComponent {
  private payments: PaymentPort = inject(PAYMENT_PORT);   // interface, not class
  ngOnInit() { const snapshot = this.payments.getSnapshot(this.user); }
}
```

Conventions that hold across every port

Async means "may leave the process." Anything that touches the model runtime or the network returns a `Promise`; pure in-core computation is synchronous. The async signature is declared on the **port**, not discovered per adapter, so a remote implementation never forces a change inside the hexagon.

No port throws for an expected outcome. Failures are values:

Pattern	Used for	Example
`null` return	"not found" / "no opinion"	`AuthenticatePort.execute` → `null`
Result object with `success`	an attempted write	`PaymentResult`, `ProfileUpdateResult`
Outcome object with `reason`	a decision that can go either way	`RateReliefOutcome`

5.1 `AuthenticatePort` → `AuthenticateService`

Binding key `AUTHENTICATE_PORT` · Identity. The only port callable before a `User` exists.

Operation	Parameters	Returns	Description
`execute`	`username: string`, `password: string`	`Promise<User | null>`	Exact username + password match. `null` = rejected. Async because the CSV repository is fetched. Delegates wholly to `UserRepositoryPort.findByCredentials`.

5.2 `LoanInfoPort` → `LoanInfoService`

Binding key `LOAN_INFO_PORT` · The authoritative loan snapshot.

Operation	Parameters	Returns	Description
`getLoanInfo`	`user: User`	`LoanInfo`	Synchronous. Delegates to `buildLoanInfo()` in the domain — balances, `paidPercent`, `monthsToMaturity`.

5.3 `PaymentPort` → `PaymentService`

Binding key `PAYMENT_PORT` · All money math lives behind this door.

Operation	Parameters	Returns	Description
`getSnapshot`	`user: User`	`PaymentSnapshot`	Payment posture: due amounts, arrears, streak, suggested extra.
`submit`	`user: User`, `request: PaymentRequest`	`PaymentResult`	**Authoritative write.** Validates, computes the projected balance, issues a reference `PMT-YYYYMMDD-XXXXXX`.
`suggestedAmount`	`user: User`	`number`	A **one-off lump-sum** suggestion — 10% of balance rounded to $25, floor $1. **Not** a monthly figure.
`fundingSources`	*none*	`string[]`	Selectable sources (reference data). Takes no user.

`submit` failure modes — all returned as `{ success: false, message }`, never thrown:

Condition	Message
Amount non-finite or `< $1`	`Please enter a payment of at least $1.`
Amount `>` current balance	`The amount exceeds your current balance of $… Enter your payoff amount or less.`
No funding source	`Please choose a funding source.`

5.4 `ProfilePort` → `ProfileService`

Binding key `PROFILE_PORT`

Operation	Parameters	Returns	Description
`getProfile`	`user: User`	`BorrowerProfile`	Includes rule-derived account standing (label, tone, summary).
`getContact`	`user: User`	`ProfileContact`	Current details, for pre-filling a form.
`updateProfile`	`user: User`, `contact: ProfileContact`	`ProfileUpdateResult`	Validates, applies, returns a reference `PRF-YYYYMMDD-XXXXXX`. Blank fields fall back to current values.

`updateProfile` validation — all returned as values:

Condition	Message
All three fields blank	`Please provide at least one detail to update.`
Email fails `^[^\s@]+@[^\s@]+\.[^\s@]+$`	`Please enter a valid email address.`
Phone digits outside 10–15	`Please enter a valid phone number (10–15 digits).`

5.5 `EligibilityPort` → `EligibilityService`

Binding key `ELIGIBILITY_PORT`

Operation	Parameters	Returns	Description
`checkRateRelief`	`user: User`	`RateReliefOutcome`	**The decision is made here, never by the CLL.** The cognitive layer may only phrase `reason` — and in practice the UI prints it verbatim.

Decision rule (`eligibility.entity.ts`): eligible when `userType !== 3` **or** `paymentsMade >= 6` . Rate reduction by type — `1` → 0.75 pts, `2` → 0.50 pts, `3` → 0.35 pts, floored at 0. Monthly saving = the interest delta on the current balance, rounded to cents.

---

6. Tag: Driving ports — cognitive (CLL)

Same edge of the hexagon, same kind of door. A driver cannot tell these apart from the BLL ports above — and that is the design.

6.1 `InquiryPort` → `InquiryService`

Binding key `INQUIRY_PORT` · **Depends on** `LanguageModelPort`, `KnowledgeBasePort`

Turns free text into a topic and stamps the fixed determinism policy onto it.

Operation	Parameters	Returns	Description
`classify`	`text: string`	`Promise< InquiryResult >`	Async — the model may be remote. The model **proposes**; an abstention (`null`) or unusable answer collapses to `GENERAL` **in the core**.
`getJobsForProgram`	`user: User`	`Promise< JobPosting[] >`	Read-only grounding pass-through to the knowledge base, keyed by `programOfStudy` and `"city, province"`. Async because the catalog is a stored CSV — **not** because a model is involved.

What this service owns (and why it is inside the hexagon). It holds *policy, not technology*:

- `DETERMINISM_POLICY` — which topics are answered identically for every borrower.
- `CATEGORY_LABEL` — business-owned display labels for headers and breadcrumbs.
- `CATEGORY_DESCRIPTION` — the business-owned **meaning** of each topic.

> **The candidate list travels with the request.** `MATCHABLE_CATEGORIES` is built from `CATEGORY_DESCRIPTION` and passed to `LanguageModelPort.classifyInquiry` on every call, so **no adapter holds a copy of the taxonomy**. A semantic adapter matches wording against the descriptions; the keyword adapter ignores them entirely. Either way the core owns what the categories mean.
>
> `GENERAL` **is deliberately excluded from the candidate list.** It is the *absence* of a match, not a match. Offering it would let the model "pick" the fallback and destroy the distinction between a proposal and an abstention — the exact signal this layer depends on.
>
> **Consequence:** a wrong proposal can pick the wrong topic; it **cannot** move a topic across the deterministic line.

6.2 `AccountSummaryPort` → `AccountSummaryService`

Binding key `ACCOUNT_SUMMARY_PORT` · **Depends on** `ProfilePort`, `LoanInfoPort`, `PaymentPort`, `LanguageModelPort`

Operation	Parameters	Returns	Description
`summarize`	`user: User`	`Promise< AccountSummary >`	Returns the three authoritative objects **and** the prose, so the UI renders figures from the BLL side and never parses them out of a sentence.

The ordering is the guarantee. All three authoritative values are resolved **before** the model is called, and are never sent back for recomputation. The two narrations are then issued concurrently with `Promise.all`. This service owns the *aggregation policy* — which three facts make a summary — and nothing else.

Note that it reaches the deterministic region through the **same driving ports the UI uses**. There is no privileged internal path.

6.3 `ChatInsightsPort` → `ChatInsightsService`

Binding key `CHAT_INSIGHTS_PORT` · **Depends on** `ChatHistoryPort`, `LanguageModelPort`

Operation	Parameters	Returns	Description
`getInsights`	`user: User`	`Promise< ChatInsights >`	Reads raw conversation facts, bands the raw `toneScore`, then asks the model for a supportive blurb about the band **already chosen**.

Sentiment bands — business-owned, evaluated highest-first:

Score ≥	Label	Emoji	Tone
80	Very positive	😄	`good`
60	Positive	🙂	`good`
45	Neutral	😐	`warn`
25	Negative	😟	`warn`
—	Very negative	😢	`bad`

> The sentiment reading is a **UI signal only**. Nothing in the deterministic region reads it, and no money or eligibility outcome may depend on it.

6.4 `PersonalizationPort` → `PersonalizationService`

Binding key `PERSONALIZATION_PORT` · **Depends on** `LanguageModelPort`

Operation	Parameters	Returns	Description
`getWelcome`	`user: User`	`Promise< WelcomeContent >`	Greeting, invitation and three suggested prompts from the model, **plus** `themeClass`.

The split inside a four-line method is the whole lesson: the copy is model output; `themeClass: \` theme-${user.userType}`` is business policy and stays in the core.

---

7. Tag: Driven ports — what the core requires

Implement these to run the core against different technology. Bind in `providers.ts`; **nothing in `core/` changes.**

7.1 `UserRepositoryPort`

Binding key `USER_REPOSITORY_PORT` · The system of record. **Read-only by design** — the application structurally cannot write borrower data.

```
export interface UserRepositoryPort {
  findByCredentials(username: string, password: string): Promise<User | null>;
}
```

Operation	Parameters	Returns	Description
`findByCredentials`	`username: string`, `password: string`	`Promise<User | null>`	Exact match, or `null`. The single capability the core requires of a borrower store.

Why there is no `getUsers()` here. The core never enumerates borrowers — it authenticates exactly one. A port states what the core *requires*, so one operation is the whole contract. Bulk loading is a property of one storage technology, not a requirement of the application, and putting it on the port would have three costs:

Cost	Consequence
Every adapter must implement it	A SQL-backed adapter would owe a `SELECT * FROM users` materialising every borrower — to satisfy a method with no callers. The port would be dictating a bad implementation.
It widens what the core may do	The interface would say the core *may* enumerate every borrower. It never does, but a reader would reasonably conclude bulk access is part of the design.
It inverts who shapes the contract	The port's shape would come from "a CSV must be read whole before it can be searched" — technology dictating the contract, which is the one thing ports exist to prevent.

Keeping the whole-file load **private to the adapter** (see §8.1) costs nothing and keeps the contract honest: the core asks for one borrower, so the port offers one borrower.

7.2 `LanguageModelPort`

Binding key `LANGUAGE_MODEL_PORT` · The model runtime as a technology behind a port — exactly like `users.csv` behind `UserRepositoryPort`.

> **Every method returns prose, an enum, or `null` — never a number.** That signature is what makes it *structurally impossible* to ask the model for an authoritative value. The contract is enforced by the compiler, not by discipline.

Async by contract. Every method returns a `Promise`, including in the mock, which awaits nothing. The port is shaped by what the *slowest plausible* adapter needs, so an in-process stub and a hosted model are interchangeable.

Operation	Parameters	Returns	Purpose
`classifyInquiry`	`text: string`, `candidates: readonly CategoryDescriptor []`	`Promise<InquiryCategory | null>`	**Propose** a topic by matching wording against each description. `null` = abstain.
`narrateLoan`	`profile: BorrowerProfile`, `loan: LoanInfo`	`Promise<string>`	Phrase an already-computed fact set.
`narratePayments`	`payment: PaymentSnapshot`	`Promise<string>`	Phrase an already-computed snapshot.
`describeTone`	`label: SentimentLabel`	`Promise<string>`	One supportive sentence for a band already chosen.
`composeWelcome`	`user: User`	`Promise< WelcomeCopy >`	Greeting, invitation, three suggested prompts.

Note the shape of every signature: **computed values in, words out.**

7.3 `KnowledgeBasePort`

Binding key `KNOWLEDGE_BASE_PORT`

Operation	Parameters	Returns	Description
`getJobsForProgram`	`program: string`, `location: string`	`Promise< JobPosting[] >`	Grounding source. Never a system of record, never a place where money is computed. `location` only **ranks** the matches nearest-first — it can never invent a posting.

7.4 `ChatHistoryPort`

Binding key `CHAT_HISTORY_PORT`

Operation	Parameters	Returns	Description
`getHistory`	`user: User`	`Promise< ChatHistoryRecord >`	Returns a **raw, uninterpreted** `toneScore`. The CLL bands it; the adapter decides nothing.

> **Both grounding ports are async for the same reason, and it is not the model.** They returned plain values while their adapters held hard-coded literals. Moving the two data sets into `assets/jobs.csv` and `assets/chat-summary.csv` — a change of *storage*, with no new logic — forced both signatures to `Promise`. That is the abstraction leaking: a port's synchronicity is part of its contract, so it has to be shaped by the most distant adapter you can plausibly imagine, not by the one that happens to exist first. `UserRepositoryPort` never had the problem, because it read a CSV from day one.

---

8. Tag: Driven adapters — the outside world

Outer ring. The core never imports these; only `providers.ts` names them.

8.1 `CsvUserRepository` → `UserRepositoryPort`

Fetches `assets/users.csv` once, caches the parsed result, and searches it in memory. Minimal CSV parser — the data set deliberately avoids embedded commas and quotes, so a straightforward `split(',')` is sufficient for a POC. Username matching is case-insensitive and trimmed; password matching is exact.

```
export class CsvUserRepository implements UserRepositoryPort {
  private cache: Promise<User[]> | null = null;

  async findByCredentials(username: string, password: string): Promise<User | null> {
    const u = username.trim().toLowerCase();
    const users = await this.load();
    return users.find((row) => row.username.toLowerCase() === u && row.password === password) ?? null;
  }

  /**
   * PRIVATE — a CSV has no index, so the only way to find one row is to parse them
   * all. Loaded once, then replayed to every caller. This is the adapter's problem
   * and stays behind its own wall: the port exposes no way to enumerate borrowers.
   */
  private load(): Promise<User[]> {
    if (!this.cache) {
      this.cache = fetch('assets/users.csv')
        .then((res) => {
          if (!res.ok) throw new Error(`Failed to load users.csv (${res.status})`);
          return res.text();
        })
        .then((csv) => this.parseCsv(csv));
    }
    return this.cache;
  }
}
```

This is the shape to copy when writing any driven adapter. The expensive, technology-specific manoeuvre — read the entire file, then scan it — is real and unavoidable for CSV. It is also *invisible* from outside. Swap in a SQL adapter and `findByCredentials` becomes one indexed query with no bulk load anywhere; swap in an HTTP adapter and it becomes one request. The port never changes, because the port never described the manoeuvre in the first place.

The system of record is a plain CSV file — a detail the core never names.

8.2 `MockLanguageModel` → `LanguageModelPort`

The offline stub, and the POC default. Classification is **regex keyword matching**; narration is **string templating**. No AI call is made.

> **Rule ordering matters:** `EXTRA_PAYMENT` is tested before `LOAN_BALANCE` so that "*...extra payment to my loan balance*" doesn't match balance first. A real model replaces this list wholesale.

Every number it prints was handed to it already computed. It formats and phrases; it never calculates.

8.3 `AzureAiLanguageModel` → `LanguageModelPort`

The live runtime — Azure OpenAI Chat Completions. Constructed with `AzureAiOptions` **and a fallback** `LanguageModelPort` (the mock).

`AzureAiOptions` — declared on the adapter, not in `configuration/`, so the dependency points the right way: the composition root knows the adapter; the adapter knows nothing of the composition root.

```
{ baseUrl: string; deployment: string; apiVersion: string;
  apiKey: string; sendKeyHeader: boolean;
  timeoutMs: number; temperature: number; maxTokens: number }
```

There is no `mode` field here. Modes are a *deployment* concept; this class only needs to know whether **it** should attach the credential — `sendKeyHeader` is derived in `toAzureOptions()` and is true **only** in `directKey` mode, so `proxy` can never accidentally ship a key.

Three prohibitions, enforced by construction:

It may not...	Because
Compute an authoritative value	Every figure in a prompt arrives pre-computed, and `NARRATION_RULES` forbids inventing, recomputing or re-rounding any number, date, rate or amount.
Decide a category's meaning	It returns one of a fixed candidate set, or `null`. `InquiryService` applies the policy. An unknown or unparseable answer degrades to `null`.
Fail the user	Any transport error, timeout, bad status or unusable payload delegates to the injected fallback.

8.4 `CsvKnowledgeBase` → `KnowledgeBasePort`

Synthetic job catalog fetched from `assets/jobs.csv` — same load-once-and-cache shape as §8.1. 20 postings across six programs of study (Computer Science, Registered Nursing, Mechanical Engineering, Marketing, Graphic Design, Culinary Arts) plus a `General` set used as the fallback when a borrower's program matches nothing.

The catalog is data, not code. Each row carries its own city, province, pay and employment type, so adding a posting is a CSV edit — no recompile, and no adapter change:

```
program,title,company,city,province,salaryAmount,salaryUnit,type
Computer Science,Junior Software Engineer,Brightloop Systems,Toronto,ON,82000,yr,Full-time
Computer Science,IT Support Specialist,Nimbus Cloud,Ottawa,ON,28,hr,Contract
```

Two jobs the adapter does that are worth naming, because both are *presentation of stored data* rather than decisions:

Step	What it does
`formatSalary`	`82000` + `yr` → `C$82,000 / yr`; `28` + `hr` → `C$28 / hr`. Pay is stored as an **amount plus a unit** so the CSV needs no embedded commas.
`nearestFirst`	Ranks matches same-city-and-province → same-province → the rest. `Array.prototype.sort` is stable, so CSV order is preserved inside each band.

> **Location ranks; it never invents.** Earlier the borrower's location was simply echoed back onto every posting, which meant a Toronto borrower saw Toronto jobs whether or not any existed. Now each posting states where it actually is, and `location` is only a sort key — the adapter cannot manufacture a nearby opening.

8.5 `CsvChatHistory` → `ChatHistoryPort`

Synthetic conversation facts fetched from `assets/chat-summary.csv`, one row per borrower, parsed into a `Map` keyed by lowercase username. **It returns raw values and interprets nothing** — the raw `toneScore` is banded by the CLL.

The rows are *authored* to match each borrower's standing rather than computed from it, which is the point of moving them out of code — the recap prose and the tone score now live together as data:

Borrower	Type	Sessions	Messages	Last contact	`toneScore`	Recap
`alice`	1 — excellent	6	44	3 days ago	91	Long, engaged
`grace`	1 — excellent	6	47	3 days ago	91	Long, engaged
`bob`	2 — delinquency g1	2	12	2 weeks ago	36	Short, tense
`henry`	2 — delinquency g1	2	11	2 weeks ago	38	Short, tense
`carol`	3 — delinquency g2	1	4	6 weeks ago	13	Very short
`irene`	3 — delinquency g2	0	2	over 6 weeks ago	11	*(empty → `null`)*

Two parsing details differ from the other two CSVs:

- **`summary` is the last column and is quoted**, because a recap is prose and genuinely contains commas. Everything from that column onward is re-joined rather than split.
- **An empty `summary` cell becomes `null`**, which the port already models as "not enough history to recap" — the shape `irene` exercises. A borrower with no row at all falls back to a `NO_HISTORY` constant (zero counts, `toneScore: 50`). Neither is a decision; both are just an empty read.

---

9. Tag: Domain — entities and rules

Pure TypeScript, zero `@angular`, innermost ring. Nothing here names a port, a UI or a driver. The application services in `core/application/` are thin: they implement a driving port and delegate straight to these functions.

File	Exports	Rules it owns
`user.entity.ts`	`User`, `UserType`, `USER_TYPE_LABEL`	The borrower record; the 1/2/3 standing taxonomy.
`loan.entity.ts`	`LoanInfo`, `buildLoanInfo`, `paidPercent`, `monthsToMaturity`	`paidPercent` clamped 0–100; `monthsToMaturity` never negative.
`payment.entity.ts`	`PaymentSnapshot`, `PaymentRequest`, `PaymentResult`, `buildPaymentSnapshot`, `processPayment`, `suggestExtraPayment`, `fundingSources`	`MIN_PAYMENT = $1`; past-due derived as `nextPaymentAmount > monthlyPayment`; suggestion = 10% of balance rounded to $25; reference `PMT-YYYYMMDD-XXXXXX`.
`borrower.entity.ts`	`BorrowerProfile`, `ProfileContact`, `ProfileUpdateResult`, `buildBorrowerProfile`, `currentContact`, `applyProfileUpdate`	Standing label/tone/summary per type; email and phone validation; reference `PRF-YYYYMMDD-XXXXXX`.
`eligibility.entity.ts`	`RateReliefOutcome`, `checkRateReliefEligibility`	The rate-relief **verdict** and its money math.
`inquiry.type.ts`	`InquiryCategory`	The topic taxonomy — the one inquiry declaration that genuinely crosses rings.
`sentiment.type.ts`	`SentimentLabel`, `SentimentTone`	The sentiment vocabulary.
`job-posting.type.ts`	`JobPosting`	Grounding shape.
`date.utility.ts`	`parseIsoDate`	Parses `yyyy-MM-dd` as a **local** calendar date.

> **`standingSummary` is prose that lives in the domain, not the CLL** — because it asserts something the business is accountable for. Contrast `describeTone()`, which is decorative and is therefore model output. That asymmetry is the test for where any new piece of copy belongs.

> **Why `parseIsoDate` exists.** `new Date('2026-08-03')` parses a date-only string as **UTC** midnight, so every local-time getter renders it shifted. West of UTC that lands on the previous day — and on the 1st of a month, in the previous *month*, making a loan maturing `2031-05-01` read "April 2031". Angular's `DatePipe` already parses date-only strings as local, so a stat tile and the sentence beside it could disagree. This helper makes the hand-formatted paths agree with the pipe.

10. Tag: Configuration — the composition root

10.1 `tokens.ts` — one binding key per port

The problem this file solves: an interface is not addressable at runtime.

The composition root's job is to bind each port to an implementation. To do that it needs a **key** — something nameable at runtime that means "whatever answers for `PaymentPort`". The interface itself cannot serve as that key, because an interface is a compile-time construct that leaves no trace in the running program.

The general solution is a **stand-in key**: a runtime value created for no purpose other than to represent the interface. Implementations are registered against the stand-in; callers ask for the stand-in and receive an implementation, still typed to the interface. The consequence is the one that matters architecturally — **a caller can depend on a contract without ever naming a class.**

This codebase realises that with one key per port:

```
export const PAYMENT_PORT = new InjectionToken<PaymentPort>('PaymentPort');
//           ^ runtime key    ^ compile-time type only        ^ diagnostic name
```

The mechanism is framework-specific; the need for it is not. Any composition root in any language faces the same problem wherever the contract is an interface rather than a class, and solves it the same way — a registry keyed by something that outlives compilation.

> **A word about the word "token."** The framework calls this an `InjectionToken`, and the file is named `tokens.ts`, so you will meet the term in the source. This document deliberately says **binding key** instead, because "token" is badly overloaded — and nowhere more so than in this application, where all three meanings are live at once:
>
> | "Token" as… | Where it appears here | Relation to binding keys |
> |---|---|---|
> | a **DI lookup key** | `PAYMENT_PORT`, `USER_REPOSITORY_PORT` | this is the one — renamed "binding key" throughout |
> | an **authentication credential** | what `AuthenticatePort` does *not* issue — this POC keeps a `User` in session, no bearer token anywhere | none |
> | an **LLM billing unit** | `maxTokens: 400` in the model configuration (§3) | none |
>
> Three unrelated concepts, one word. Since a binding key has nothing to do with identity or with model usage, the document names it after what it actually does: it is the key an implementation is bound to.

Every key is typed to a **port interface**, never a concrete class. This file is permitted framework imports because it is configuration — neither core nor ports.

Group	Binding keys
Driving · BLL	`AUTHENTICATE_PORT`, `PAYMENT_PORT`, `LOAN_INFO_PORT`, `PROFILE_PORT`, `ELIGIBILITY_PORT`
Driving · CLL	`INQUIRY_PORT`, `PERSONALIZATION_PORT`, `CHAT_INSIGHTS_PORT`, `ACCOUNT_SUMMARY_PORT`
Driven	`USER_REPOSITORY_PORT`, `KNOWLEDGE_BASE_PORT`, `CHAT_HISTORY_PORT`, `LANGUAGE_MODEL_PORT`

10.2 `providers.ts` — the wiring table

The **one** file in the application that knows every concrete class. Registered into the bootstrap in `main.ts` as `...hexagonalProviders`.

Port (binding key)	Concrete class	Constructor dependencies
`USER_REPOSITORY_PORT`	`CsvUserRepository`	—
`KNOWLEDGE_BASE_PORT`	`CsvKnowledgeBase`	—
`CHAT_HISTORY_PORT`	`CsvChatHistory`	—
`LANGUAGE_MODEL_PORT`	`MockLanguageModel` *or* `AzureAiLanguageModel`	Chosen by `resolveAiConfig()`; Azure receives `(options, mockFallback)`
`AUTHENTICATE_PORT`	`AuthenticateService`	`USER_REPOSITORY_PORT`
`PAYMENT_PORT`	`PaymentService`	—
`LOAN_INFO_PORT`	`LoanInfoService`	—
`PROFILE_PORT`	`ProfileService`	—
`ELIGIBILITY_PORT`	`EligibilityService`	—
`INQUIRY_PORT`	`InquiryService`	`LANGUAGE_MODEL_PORT`, `KNOWLEDGE_BASE_PORT`
`PERSONALIZATION_PORT`	`PersonalizationService`	`LANGUAGE_MODEL_PORT`
`CHAT_INSIGHTS_PORT`	`ChatInsightsService`	`CHAT_HISTORY_PORT`, `LANGUAGE_MODEL_PORT`
`ACCOUNT_SUMMARY_PORT`	`AccountSummaryService`	`PROFILE_PORT`, `LOAN_INFO_PORT`, `PAYMENT_PORT`, `LANGUAGE_MODEL_PORT`

Read the last row again. `ACCOUNT_SUMMARY_PORT` — a cognitive service — depends on three **driving-port keys**, not on the services behind them. The CLL knocks on the same doors the UI does.

10.3 `session.store.ts`

`@Injectable({ providedIn: 'root' })`. Holds the authenticated borrower in a signal. **The core has no notion of "sessions"** — this is delivery-side plumbing.

Member	Type	Description
`currentUser`	`Signal<User | null>`	Read-only view of the session.
`isAuthenticated`	`Signal<boolean>`	Computed — `currentUser() !== null`.
`setUser(user)` / `clear()`	`void`	Set on login; clear on logout.


10.4 `auth.guard.ts`

`CanActivateFn`. Returns `true` when authenticated, otherwise a `UrlTree` for `/login`. Route guarding is a framework concern and correctly lives outside the hexagon.


---

11. Interactions — sequence flows


11.1 Bootstrap




11.2 Login


Borrower
LoginComponent
AUTHENTICATE_PORT
AuthenticateService
UserRepositoryPort
CsvUserRepository
SessionStore
submit(username, password)
both fields non-empty? (form concern only)
execute(username, password)
(bound by composition root)
findByCredentials(...)
fetch('assets/users.csv') → parse → cache
User | null
Promise<User | null>
alt
[User]
setUser(user)
navigate /dashboard
[null]
"Invalid username or password."
[rejected]
"Unable to reach the account service."
Borrower
LoginComponent
AUTHENTICATE_PORT
AuthenticateService
UserRepositoryPort
CsvUserRepository
SessionStore

11.3 Dashboard load — the always-on cards




11.4 Asking a question — the central flow




Read what the diagram makes structural: the cognitive layer chose *which card to show*. It supplied **no number on that card**. The answer component fetched every figure itself, from a deterministic port, after the fact.


11.5 Submitting a payment — an authoritative write



11.6 Component dependency map

Which UI component reaches which port:


Driving adapters
LoginComponent
MakePayment
NextPayment
JobOpportunities
DashboardComponent
AccountSummary
Driving ports · CLL
INQUIRY
PERSONALIZATION
ACCOUNT_SUMMARY
Driving ports · BLL
AUTHENTICATE
PAYMENT



`GeneralHelpComponent` and `AiBadgeComponent` are absent from this map on purpose: they inject nothing.

---

12. Schemas

User

The input to nearly every operation. One row of `assets/users.csv`.

```
{
  username: string;  password: string;  firstName: string;  lastName: string;
  userType: UserType;                // 1 | 2 | 3
  programOfStudy: string;  city: string;  province: string;
  originalAmount: number;  currentBalance: number;  interestRate: number;  // annual %, e.g. 4.25
  monthlyPayment: number;  nextPaymentDate: string;  nextPaymentAmount: number;
  maturityDate: string;              // ISO yyyy-mm-dd
  paymentsMade: number;  paymentsMissed: number;  onTimeStreak: number;
  creditScore: number;
}
```

LoanInfo

```
{
  originalAmount: number;  currentBalance: number;  interestRate: number;
  maturityDate: string;
  paidPercent: number;       // whole percent of original principal repaid, 0..100
  monthsToMaturity: number;  // whole months, never negative
}
```

PaymentSnapshot

```
{
  monthlyPayment: number;      nextPaymentAmount: number;  nextPaymentDate: string;
  paymentsMade: number;        paymentsMissed: number;     onTimeStreak: number;
  isPastDue: boolean;          pastDueAmount: number;      suggestedExtraPayment: number;
}
```

PaymentRequest

```
{
  amount: number;
  fundingSource: string;
  effectiveDate: string;                        // ISO yyyy-mm-dd
  applyTo: 'PRINCIPAL' | 'NEXT_INSTALLMENT';
}
```

PaymentResult

```
{
  success: boolean;            message: string;
  referenceNumber?: string;    amount?: number;
  projectedBalance?: number;   effectiveDate?: string;
}
```

BorrowerProfile

```
{
  firstName: string;  lastName: string;  fullName: string;
  programOfStudy: string;  city: string;  province: string;  location: string;
  creditScore: number;  userType: UserType;
  standingLabel: string;                        // rule-derived
  standingTone: 'good' | 'warn' | 'bad';
  standingSummary: string;                      // rule-derived PROSE — owned by the BLL
}
```

ProfileContact

```
{ email: string; phone: string; mailingAddress: string }
```

ProfileUpdateResult

```
{ success: boolean; message: string;
  referenceNumber?: string; updated?: ProfileContact }
```

RateReliefOutcome

```
{
  eligible: boolean;                // the DECISION — made in the domain
  proposedRate: number;
  estimatedMonthlySavings: number;
  reason: string;                   // printed verbatim by the UI
}
```

InquiryResult

```
{
  category: InquiryCategory;
  deterministic: boolean;   // from the fixed policy map, never the model
  label: string;            // business-owned display label
}
```

AccountSummary

```
{
  profile: BorrowerProfile;   // authoritative
  loan: LoanInfo;             // authoritative
  payment: PaymentSnapshot;   // authoritative
  loanSentence: string;       // narration
  paymentsSentence: string;   // narration
}
```

ChatInsights

```
{ summary: string | null;  sentiment: ChatSentiment;
  liveChatSessions: number;  chatbotMessages: number;  lastContact: string }
```

ChatSentiment

```
{ score: number;              // 0..100 raw signal
  label: SentimentLabel;      // band chosen in the core
  emoji: string;
  tone: SentimentTone;
  blurb: string }             // model output
```

WelcomeCopy

```
{ greeting: string; question: string; suggestions: string[] }
```

WelcomeContent

```
WelcomeCopy + { themeClass: string }    // themeClass added in the core, not by the model
```

ChatHistoryRecord

```
{
  liveChatSessions: number;  chatbotMessages: number;  lastContact: string;
  summary: string | null;    toneScore: number;        // RAW — uninterpreted
}
```

JobPosting

```
{ title: string; company: string; location: string; salary: string; type: string }
```

CategoryDescriptor

```
{ category: InquiryCategory; description: string }   // description = the matching signal
```

---

13. Enumerations and policies

Type	Values
`UserType`	`1` Excellent standing · `2` Delinquency grade 1 · `3` Delinquency grade 2
`InquiryCategory`	`NEXT_PAYMENT` · `LOAN_BALANCE` · `EXTRA_PAYMENT` · `PROFILE_UPDATE` · `HARDSHIP` · `LIFE_EVENT` · `REPAYMENT_OPTIONS` · `GENERAL`
`PaymentApplyTo`	`PRINCIPAL` · `NEXT_INSTALLMENT`
`SentimentLabel`	`Very positive` · `Positive` · `Neutral` · `Negative` · `Very negative`
`SentimentTone`	`good` · `warn` · `bad`
`AiMode`	`mock` · `proxy` · `directKey`

Determinism policy

Which topics are answered identically for every borrower. Owned by the business; **the model never sees this map.**

Category	`deterministic`	Label
`NEXT_PAYMENT`	`true`	Next payment
`LOAN_BALANCE`	`true`	Loan balance & maturity
`EXTRA_PAYMENT`	`true`	Make a payment
`PROFILE_UPDATE`	`true`	Update your profile
`HARDSHIP`	`false`	Payment hardship
`LIFE_EVENT`	`false`	Life event & rate relief
`REPAYMENT_OPTIONS`	`false`	Repayment options & scenarios
`GENERAL`	`false`	General help

`GENERAL` is never offered to the classifier — it is the absence of a match, and the core substitutes it when the model abstains.

Category descriptions — the classifier's actual input

These are written as **discriminators, not definitions**: each says what makes the topic different from its nearest neighbour, because that is the decision the model is being asked to make.

Category	Discriminating signal
`NEXT_PAYMENT`	The single upcoming instalment — when and how much. *Not* the total owed.
`LOAN_BALANCE`	What is owed and when the loan ends. The borrower is **asking** about figures, not trying to pay.
`EXTRA_PAYMENT`	The borrower wants to **make** a payment now. An intention to act. Beats `LOAN_BALANCE` whenever they want to pay rather than to know.
`PROFILE_UPDATE`	Changing contact details on file.
`HARDSHIP`	Present or imminent **inability to pay** — job loss, expects to miss payments.
`LIFE_EVENT`	A life event that may change entitlement (new child, marriage, return to study), including hypothetical framing. Beats `REPAYMENT_OPTIONS` when an event is mentioned; loses to `HARDSHIP` when they cannot pay now.
`REPAYMENT_OPTIONS`	Scenarios and qualifying conditions while **not** in distress — paying off faster, what assistance requires.
`GENERAL`	Anything unmatched. Never offered as a choice.

---

14. Extending the system

Adding a port

1. Declare the interface in `ports/driving/` or `ports/driven/` — pure TypeScript, no `@angular`.
2. Add a binding key — an `InjectionToken` typed to the **interface** — in `configuration/tokens.ts`.
3. Implement it — in `core/application/` (BLL) or `core/cognitive/` (CLL) for a driving port; in `adapters/driven/` for a driven one.
4. Bind it in `configuration/providers.ts`.

Nothing else in the application needs to know. **That is the property this reference exists to document.**

Adding an inquiry topic

1. Add the value to `InquiryCategory` in `inquiry.type.ts`.
2. Add entries to all three maps in `inquiry.service.ts` — `DETERMINISM_POLICY`, `CATEGORY_LABEL`, `CATEGORY_DESCRIPTION`. TypeScript's `Record<InquiryCategory, …>` makes omitting one a compile error.
3. Build the answer component in `adapters/driving/ui/inquiry/` taking `@Input() user` and injecting whichever driving ports supply its figures.
4. Add a `@case` to the `@switch` in `dashboard.component.html`.

No adapter changes. The `MockLanguageModel` needs a keyword rule only if you want the offline stub to reach the new topic; a semantic adapter picks it up from `CATEGORY_DESCRIPTION` alone.

Replacing an adapter

Change one line in `providers.ts`. A real database behind `UserRepositoryPort`, a different model vendor behind `LanguageModelPort`, a vector store behind `KnowledgeBasePort` — none of it reaches `core/` or `ports/`.

The `LanguageModelPort` swap is already demonstrated in the codebase: `mock` ↔ `proxy` is a query-string parameter, and the two adapters satisfy an identical interface.

The grounding swap is demonstrated too, and it came with a caveat worth inheriting. `KnowledgeBasePort` and `ChatHistoryPort` were once backed by in-memory adapters holding hard-coded literals; they are now backed by `CsvKnowledgeBase` and `CsvChatHistory`. Binding the new classes really was a one-line change each — but the *port signatures* had to change from plain values to `Promise`s, because a `fetch()` cannot satisfy a synchronous contract. That is not a counter-example to the claim above; it is a reminder of its precondition:

> **A port's synchronicity is part of its contract.** Pick it from the adapter you happen to have first and the abstraction leaks — the next adapter forces a change inside the hexagon. Shape every port for the most distant adapter you can plausibly imagine, and replacing one really is a composition-root change.

The rule that keeps all of this true

Never import an implementation. Depend on the port, resolve it through the composition root, and type the reference to the interface. `providers.ts` is the only file permitted to name a concrete class — and if that stays true, every claim in this document stays true with it.