```
In [1]: import httpx

In [2]: httpx.get('http://127.0.0.1:5000/home')
Out[2]: <Response [200 OK]>

In [3]: r = httpx.get('http://127.0.0.1:5000/home')

In [4]: r.json()
Out[4]: {'message': "there's no place like home"}
```

```
(.env) at gowiththeflow $ flask run --debug
 * Debug mode: on
WARNING: This is a development server. Do not use it in a production deploymen
t. Use a production WSGI server instead.
 * Running on http://127.0.0.1:5000
Press CTRL+C to quit
 * Restarting with stat
 * Debugger is active!
 * Debugger PIN: 380-198-636
127.0.0.1 - - [12/Mar/2023 00:35:43] "GET /home HTTP/1.1" 200 -
127.0.0.1 - - [12/Mar/2023 00:36:05] "GET /home HTTP/1.1" 200 -
```

```
@app.get('/')
def home():
    response = {
        "message": "There's no place like home"
    }
    return make_response(jsonify(response), 200)
```

@jesstemporal

```python
@app.get('/')
def home():
    response = {
        "message": "There's no place like home"
    }
    return make_response(jsonify(response), 200)
```

```
In [1]: import httpx

In [2]: httpx.get('http://127.0.0.1:5000/home')
Out[2]: <Response [200 OK]>

In [3]: r = httpx.get('http://127.0.0.1:5000/home')

In [4]: r.json()
Out[4]: {'message': "there's no place like home"}
```

```
(.env) at gowiththeflow $ flask run --debug
 * Debug mode: on
WARNING: This is a development server. Do not use it in a production deploymen
t. Use a production WSGI server instead.
 * Running on http://127.0.0.1:5000
Press CTRL+C to quit
 * Restarting with stat
 * Debugger is active!
 * Debugger PIN: 380-198-636
127.0.0.1 - - [12/Mar/2023 00:35:43] "GET /home HTTP/1.1" 200 -
127.0.0.1 - - [12/Mar/2023 00:36:05] "GET /home HTTP/1.1" 200 -
```

```python
@app.get('/')
def home():
    response = {
        "message": "There's no place like home"
    }
    return make_response(jsonify(response), 200)
```