


Simplifying ω -Automata through the Alternating Cycle Decomposition

Antonio Casares · University of Warsaw & Corto Mascle · LaBRI, University of Bordeaux

Automata over infinite words (ω -automata)


Automata over infinite words (ω -automata)



Automata over infinite words (ω -automata)

Automata are deterministic
in this talk


\mathcal{A}



Automata over infinite words (ω -automata)

Automata are deterministic
in this talk

\mathcal{A}




Input $w \in \Sigma^\omega \longrightarrow$ Infinite path ρ

Automata over infinite words (ω -automata)

Automata are deterministic
in this talk

\mathcal{A}




Acceptance Condition?

Input $w \in \Sigma^\omega \longrightarrow$ Infinite path ρ

Automata over infinite words (ω -automata)

Automata are deterministic
in this talk

\mathcal{A}



Acceptance Condition?

$C = \{ \alpha, \beta, \gamma \}$


output colours

Input $w \in \Sigma^\omega \longrightarrow$ Infinite path ρ

Automata over infinite words (ω -automata)

Automata are deterministic
in this talk

\mathcal{A}



Acceptance Condition?

$$C = \{ \alpha, \beta, \gamma \}$$

output colours

Input $w \in \Sigma^\omega \longrightarrow$ Infinite path ρ


$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Automata over infinite words (ω -automata)

Different Acceptance Conditions

Automata are deterministic
in this talk

\mathcal{A}



Input $w \in \Sigma^\omega \longrightarrow$ Infinite path ρ

$C = \{\alpha, \beta, \gamma\}$

output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Different Acceptance Conditions

Muller

$C = \{\alpha, \beta, \gamma\}$

output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Muller


$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$

Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$




$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$


output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



$$\mathcal{L}(A) = \Sigma^* a^\omega + \Sigma^* b^\omega$$


Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$

output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Rabin





$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



Muller

Rabin


k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$

A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$

A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$




$$G_1 = \{\alpha\}, R_1 = \{\gamma\}$$

$$G_2 = \{\beta\}, R_2 = \{\gamma\}$$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$

A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$



$$G_1 = \{\alpha\}, R_1 = \{\gamma\}$$

$$G_2 = \{\beta\}, R_2 = \{\gamma\}$$

$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$


output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$

A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$


$$G_1 = \{\alpha\}, R_1 = \{\gamma\}$$

$$G_2 = \{\beta\}, R_2 = \{\gamma\}$$

Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$


output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$

A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$


$$G_1 = \{\alpha\}, R_1 = \{\gamma\}$$

$$G_2 = \{\beta\}, R_2 = \{\gamma\}$$

Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

Streett

Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$


output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$

A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$


$$G_1 = \{\alpha\}, R_1 = \{\gamma\}$$

$$G_2 = \{\beta\}, R_2 = \{\gamma\}$$

Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

Streett

Dual to Rabin

Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$


output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$

A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$


$$G_1 = \{\alpha\}, R_1 = \{\gamma\}$$

$$G_2 = \{\beta\}, R_2 = \{\gamma\}$$

Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

Parity

Streett

Dual to Rabin

Parity


We assume $C \subseteq \mathbb{N}$

ρ accepting $\Leftrightarrow \min \text{Inf}(\rho)$ is even

Parity

We assume $C \subseteq \mathbb{N}$

ρ accepting $\Leftrightarrow \min \text{Inf}(\rho)$ is even



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$


output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$


A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$



Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$


Streett

Dual to Rabin

Parity

We assume $C \subseteq \mathbb{N}$

ρ accepting $\Leftrightarrow \min \text{Inf}(\rho)$ is even



Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$


output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$


A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$



Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$




$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$

WHY SO MANY?

Parity

We assume $C \subseteq \mathbb{N}$

ρ accepting $\Leftrightarrow \min \text{Inf}(\rho)$ is even



Streett

Dual to Rabin

Different Acceptance Conditions

$C = \{\alpha, \beta, \gamma\}$


output colours

$\text{Inf}(\rho) = \{\text{Colours appearing infinitely often in } \rho\}$

Rabin

k Rabin pairs: $(G_1, R_1), \dots, (G_k, R_k)$, $G_i, R_i \subseteq C$


A run ρ is accepting $\Leftrightarrow \bigvee \text{Inf}(\rho) \cap G_i \neq \emptyset \wedge \text{Inf}(\rho) \cap R_i = \emptyset$



Muller

$\mathcal{F} \subseteq 2^C$ family of subsets

A run ρ is accepting $\Leftrightarrow \text{Inf}(\rho) \in \mathcal{F}$



$$\mathcal{L}(\mathcal{A}) = \Sigma^* a^\omega + \Sigma^* b^\omega$$


Streett

Dual to Rabin

Parity

We assume $C \subseteq \mathbb{N}$

ρ accepting $\Leftrightarrow \min \text{Inf}(\rho)$ is even



More general conditions → Automata are simpler to produce

More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → More efficient algorithms

More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → **More efficient algorithms**

Complexity of solving 2-player games. n = Size of input graph

More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → **More efficient algorithms**

Complexity of solving 2-player games. n = Size of input graph

Muller	PSPACE-complete	$\mathcal{O}(k^{5k}n^5)$	k = #Colours

More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → **More efficient algorithms**

Complexity of solving 2-player games. n = Size of input graph

Muller	PSPACE-complete	$\mathcal{O}(k^{5k}n^5)$	$k = \# \text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3}kk!)$	$k = \# \text{Rabin pair}$

More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → **More efficient algorithms**

Complexity of solving 2-player games.

n = Size of input graph

Muller	PSPACE-complete	$\mathcal{O}(k^{5k}n^5)$	$k = \#\text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3}kk!)$	$k = \#\text{Rabin pair}$
Parity	NP ∩ coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \#\text{Colours}$

More general conditions → **Automata are simpler to produce**

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → **More efficient algorithms**

Complexity of solving 2-player games. $n = \text{Size of input graph}$

Muller	PSPACE-complete	$\mathcal{O}(k^{5k}n^5)$	$k = \#\text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3}kk!)$	$k = \#\text{Rabin pair}$
Parity	NP ∩ coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \#\text{Colours}$

Goal: Simplify the acceptance condition of automata

More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → **More efficient algorithms**

Complexity of solving 2-player games. n = Size of input graph

Muller	PSPACE-complete	$\mathcal{O}(k^{5k}n^5)$	$k = \#\text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3}kk!)$	$k = \#\text{Rabin pair}$
Parity	NP ∩ coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \#\text{Colours}$

Goal: Simplify the acceptance condition of automata

a) Simplify the type (Muller → Rabin → Parity)

More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → **More efficient algorithms**

Complexity of solving 2-player games.

n = Size of input graph

Muller	PSPACE-complete	$\mathcal{O}(k^{5k}n^5)$	$k = \#\text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3}kk!)$	$k = \#\text{Rabin pair}$
Parity	NP ∩ coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \#\text{Colours}$

Goal: Simplify the acceptance condition of automata

- a) Simplify the type (Muller → Rabin → Parity)
- b) Minimise #Colours / #Rabin pairs

Approach 1

Add states to the automaton to
maximize simplification

Approach 1

Add states to the automaton to
maximize simplification



Well understood

Approach 1

Add states to the automaton to
maximize simplification



Well understood

- ★ Optimal transformation to parity automata
(C. Colcombet, Fijalkow '21)

Approach 1

Add states to the automaton to
maximize simplification



Well understood

- ★ Optimal transformation to parity automata
(C. Colcombet, Fijalkow '21)

- ✗ Exponential blowup in the worst case
(Löding '99)

Approach 1

Add states to the automaton to
maximize simplification



Well understood

- ★ Optimal transformation to parity automata
(C. Colcombet, Fijalkow '21)



- ✗ Exponential blowup in the worst case
(Löding '99)

In this paper

Simplify the condition **without**
adding further states

Simplifying ω -Automata through the Alternating Cycle Decomposition

Antonio Casares · University of Warsaw & Corto Mascle · LaBRI, University of Bordeaux



More general conditions \rightarrow Automata are simpler to produce

- LTL \rightarrow Det. Muller automata
- ND Büchi \rightarrow Det. Rabin automata

Simpler conditions \rightarrow More efficient algorithms

Complexity of solving 2-player games. $n =$ Size of input graph

Muller	PSPACE-complete	$\mathcal{O}(k^{5k} n^5)$	$k = \# \text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3} k k!)$	$k = \# \text{Rabin pair}$
Parity	NP \cap coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \# \text{Colours}$

Approach 1

Add states to the automaton to maximize simplification



In this paper

Simplify the condition without adding further states




Exponential blowup in the worst case
(Löding '99)

Goal: Simplify the acceptance condition of automata

- Simplify the type (Muller \rightarrow Rabin \rightarrow Parity)
- Minimise #Colours / #Rabin pairs

Simplifying ω -Automata through the Alternating Cycle Decomposition

Antonio Casares · University of Warsaw & Corto Muscle · LaBRI, University of Bordeaux



More general conditions \rightarrow Automata are simpler to produce

- LTL \rightarrow Det. Muller automata
- ND Büchi \rightarrow Det. Rabin automata

Simpler conditions \rightarrow More efficient algorithms

Complexity of solving 2-player games. $n = \text{Size of input graph}$

Muller	PSPACE-complete	$\mathcal{O}(k^{5k} n^5)$	$k = \#\text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3} k k!)$	$k = \#\text{Rabin pair}$
Parity	NP \cap coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \#\text{Colours}$

Goal: Simplify the acceptance condition of automata

- Simplify the type (Muller \rightarrow Rabin \rightarrow Parity)
- Minimise #Colours / #Rabin pairs

Approach 1

Add states to the automaton to maximize simplification



Optimal transformation to parity automata
(C. Colcombet, Fijalkow '21)

Exponential blowup in the worst case
(Löding '99)

In this paper

Simplify the condition **without** adding further states

Pure Conditions

Pure Conditions

Reduction of conditions

A reduction of a condition $\mathcal{F} \subseteq 2^C$ to $\mathcal{G} \subseteq 2^{C'}$
is a mapping

$$\varphi : C \rightarrow C' \quad \text{such that}$$

$$X \in \mathcal{F} \Leftrightarrow \varphi(X) \in \mathcal{G}, \quad \text{for all } X \subseteq C$$

Pure Conditions

Reduction of conditions

A reduction of a condition $\mathcal{F} \subseteq 2^C$ to $\mathcal{G} \subseteq 2^{C'}$ is a mapping

$\varphi : C \rightarrow C'$ such that

$X \in \mathcal{F} \Leftrightarrow \varphi(X) \in \mathcal{G}, \text{ for all } X \subseteq C$

Given a condition \mathcal{F} , can we reduce it to

- ★ a Muller condition with $\leq k$ colours?
- ★ a Rabin condition? With $\leq k$ Rabin pairs?
- ★ a parity condition? With $\leq k$ colours?

Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)

Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)

$$C = \{\alpha, \beta, \gamma, \delta, \lambda\}$$

$$\mathcal{F} = \{ \{\alpha, \beta, \gamma\}, \{\alpha, \gamma\}, \{\alpha, \beta\}, \{\beta, \gamma, \delta, \lambda\}, \{\beta, \delta, \lambda\}, \\ \{\gamma, \delta, \lambda\}, \{\beta, \gamma, \lambda\}, \{\beta, \gamma, \delta\}, \{\beta, \delta\}, \{\beta, \lambda\}, \{\gamma, \delta\}, \{\gamma, \lambda\} \}$$

Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)

$$C = \{\alpha, \beta, \gamma, \delta, \lambda\}$$

$$\mathcal{F} = \{ \{\alpha, \beta, \gamma\}, \{\alpha, \gamma\}, \{\alpha, \beta\}, \{\beta, \gamma, \delta, \lambda\}, \{\beta, \delta, \lambda\}, \{\gamma, \delta, \lambda\}, \{\beta, \gamma, \lambda\}, \{\beta, \gamma, \delta\}, \{\beta, \delta\}, \{\beta, \lambda\}, \{\gamma, \delta\}, \{\gamma, \lambda\} \}$$

Root → All colours

α	β	γ	δ	λ
----------	---------	----------	----------	-----------

Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)

$$C = \{\alpha, \beta, \gamma, \delta, \lambda\}$$

$$\mathcal{F} = \{ \{\alpha, \beta, \gamma\}, \{\alpha, \gamma\}, \{\alpha, \beta\}, \{\beta, \gamma, \delta, \lambda\}, \{\beta, \delta, \lambda\}, \{\gamma, \delta, \lambda\}, \{\beta, \gamma, \lambda\}, \{\beta, \gamma, \delta\}, \{\beta, \delta\}, \{\beta, \lambda\}, \{\gamma, \delta\}, \{\gamma, \lambda\} \}$$

Root → All colours

α	β	γ	δ	λ
----------	---------	----------	----------	-----------

Square if it is a rejecting set


Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)

$$C = \{\alpha, \beta, \gamma, \delta, \lambda\}$$

$$\mathcal{F} = \{\{\alpha, \beta, \gamma\}, \{\alpha, \gamma\}, \{\alpha, \beta\}, \{\beta, \gamma, \delta, \lambda\}, \{\beta, \delta, \lambda\}, \{\gamma, \delta, \lambda\}, \{\beta, \gamma, \lambda\}, \{\beta, \gamma, \delta\}, \{\beta, \delta\}, \{\beta, \lambda\}, \{\gamma, \delta\}, \{\gamma, \lambda\}\}$$

Root → All colours

Children: Maximal accepting subsets



Square if it is a rejecting set


Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)

$$C = \{\alpha, \beta, \gamma, \delta, \lambda\}$$

$$\mathcal{F} = \{\{\alpha, \beta, \gamma\}, \{\alpha, \gamma\}, \{\alpha, \beta\}, \{\beta, \gamma, \delta, \lambda\}, \{\beta, \delta, \lambda\}, \{\gamma, \delta, \lambda\}, \{\beta, \gamma, \lambda\}, \{\beta, \gamma, \delta\}, \{\beta, \delta\}, \{\beta, \lambda\}, \{\gamma, \delta\}, \{\gamma, \lambda\}\}$$

Root → All colours

Children: Maximal accepting subsets



Square if it is a rejecting set

Round because they are accepting sets

Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)


$$C = \{\alpha, \beta, \gamma, \delta, \lambda\}$$

$$\mathcal{F} = \{\{\alpha, \beta, \gamma\}, \{\alpha, \gamma\}, \{\alpha, \beta\}, \{\beta, \gamma, \delta, \lambda\}, \{\beta, \delta, \lambda\}, \{\gamma, \delta, \lambda\}, \{\beta, \gamma, \lambda\}, \{\beta, \gamma, \delta\}, \{\beta, \delta\}, \{\beta, \lambda\}, \{\gamma, \delta\}, \{\gamma, \lambda\}\}$$

Root → All colours

Children: Maximal accepting subsets

Children: Maximal rejecting subsets



Square if it is a **rejecting set**

Round because they are **accepting sets**

Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)


$$C = \{\alpha, \beta, \gamma, \delta, \lambda\}$$

$$\mathcal{F} = \{\{\alpha, \beta, \gamma\}, \{\alpha, \gamma\}, \{\alpha, \beta\}, \{\beta, \gamma, \delta, \lambda\}, \{\beta, \delta, \lambda\}, \{\gamma, \delta, \lambda\}, \{\beta, \gamma, \lambda\}, \{\beta, \gamma, \delta\}, \{\beta, \delta\}, \{\beta, \lambda\}, \{\gamma, \delta\}, \{\gamma, \lambda\}\}$$

Root → All colours

Children: Maximal accepting subsets

Children: Maximal rejecting subsets



Square if it is a **rejecting set**

Round because they are **accepting sets**

PROPOSITION (*Hunter-Dawar '06*)

The Zielonka DAG can be computed in polynomial time in $|\mathcal{F}|$.


Typeness: Can we reduce \mathcal{F} to a Rabin/parity condition?

Typefulness: Can we reduce \mathcal{F} to a Rabin/parity condition?

Just look to the Zielonka DAG! (*Zielonka '98*)

Typeness: Can we reduce \mathcal{F} to a Rabin/parity condition?

Just look to the Zielonka DAG! (*Zielonka '98*)




Rabin

\Leftrightarrow

Round nodes have a single child


Typeness: Can we reduce \mathcal{F} to a Rabin/parity condition?

Just look to the Zielonka DAG! (*Zielonka '98*)



Rabin
↔

Round nodes have a single child




Parity
↔

A single branch


Typeness: Can we reduce \mathcal{F} to a Rabin/parity condition?

Just look to the Zielonka DAG! (*Zielonka '98*)



Rabin
↔

Round nodes have a single child



Parity
↔
A single branch

+ Minimal #Colours
=
Height of the branch

Minimisation of colours and Rabin pairs

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.


Idea (for colours):

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Idea (for colours):




Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Idea (for colours):




Two colours are equivalent if they appear in the same nodes

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Idea (for colours):




Two colours are equivalent if they appear in the same nodes

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Idea (for colours):




Two colours are equivalent if they appear in the same nodes

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Idea (for colours):



Two colours are equivalent if they appear in the same nodes


Merge equivalent colours

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Idea (for colours):



Two colours are equivalent if they appear in the same nodes

Merge equivalent colours


We show that the obtained condition is optimal

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Idea (for colours):



Two colours are equivalent if they appear in the same nodes

Merge equivalent colours

We show that the obtained condition is optimal

- Minimisation of Rabin pairs is quite involved.

Pure Conditions

Reduction of conditions

A reduction of a condition $\mathcal{F} \subseteq 2^C$ to $\mathcal{G} \subseteq 2^{C'}$ is a mapping

$$\varphi : C \rightarrow C' \quad \text{such that}$$

$$X \in \mathcal{F} \Leftrightarrow \varphi(X) \in \mathcal{G}, \quad \text{for all } X \subseteq C$$

Given a condition \mathcal{F} , can we reduce it to


- ★ a Muller condition with $\leq k$ colours?
- ★ a Rabin condition? With $\leq k$ Rabin pairs?
- ★ a parity condition? With $\leq k$ colours?

Main tool: Zielonka DAG (*Zielonka '98, Hunter-Dawar '06*)

$$C = \{\alpha, \beta, \gamma, \delta, \lambda\}$$

$$\mathcal{F} = \{\{\alpha, \beta, \gamma\}, \{\alpha, \gamma\}, \{\alpha, \beta\}, \{\beta, \gamma, \delta, \lambda\}, \{\beta, \delta, \lambda\}, \{\gamma, \delta, \lambda\}, \{\beta, \gamma, \lambda\}, \{\beta, \gamma, \delta\}, \{\beta, \delta\}, \{\beta, \lambda\}, \{\gamma, \delta\}, \{\gamma, \lambda\}\}$$

Root \rightarrow All colours




PROPOSITION (*Hunter-Dawar '06*)


The Zielonka DAG can be computed in polynomial time in $|\mathcal{F}|$.

Typeness: Can we reduce \mathcal{F} to a Rabin/parity condition?

Just look to the Zielonka DAG! (*Zielonka '98*)



Rabin
 \Leftrightarrow
Round nodes have a single child




Parity
 \Leftrightarrow
A single branch
+ Minimal #Colours
= Height of the branch

Minimisation of colours and Rabin pairs

THEOREM

We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.

Idea (for colours):



Two colours are equivalent if they appear in the same nodes


Merge equivalent colours

We show that the obtained condition is optimal

• Minimisation of Rabin pairs is quite involved.

Simplifying ω -Automata through the Alternating Cycle Decomposition

Antonio Casares · University of Warsaw & Corto Mascle · LaBRI, University of Bordeaux



More general conditions \rightarrow Automata are simpler to produce

- LTL \rightarrow Det. Muller automata
- ND Büchi \rightarrow Det. Rabin automata

Simpler conditions \rightarrow More efficient algorithms

Complexity of solving 2-player games. $n =$ Size of input graph


Muller	PSPACE-complete	$\mathcal{O}(k^{5k} n^5)$	$k = \# \text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3} k k!)$	$k = \# \text{Rabin pair}$
Parity	NP \cap coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \# \text{Colours}$

Approach 1

In this paper

Add states to the automaton to maximize simplification

Simplify the condition without adding further states



Optimal transformation to parity automata (C. Colcombet, Fijalkow '21)

Exponential blowup in the worst case (Löding '99)

Pure Conditions

Reduction of conditions

A reduction of a condition $\mathcal{F} \subseteq 2^C$ to $\mathcal{G} \subseteq 2^C$ is a mapping


$\varphi : C \rightarrow C'$ such that

$$X \in \mathcal{F} \Leftrightarrow \varphi(X) \in \mathcal{G}, \text{ for all } X \subseteq C$$


Given a condition \mathcal{F} , can we reduce it to

- a Muller condition with $\leq k$ colours?
- a Rabin condition? With $\leq k$ Rabin pairs?
- a parity condition? With $\leq k$ colours?


Main tool: Zielonka DAG (Zielonka '98, Hunter-Dawar '06)



Typeness: Can we reduce \mathcal{F} to a Rabin/parity condition?




Minimisation of colours and Rabin pairs



Simplifying ω -Automata through the Alternating Cycle Decomposition

Antonio Casares · University of Warsaw & Corto Mascle · LaBRI, University of Bordeaux



More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → More efficient algorithms

Complexity of solving 2-player games. $n = \text{Size of input graph}$

Muller	PSPACE-complete	$\mathcal{O}(k^{5k}n^5)$	$k = \#\text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3}kk!)$	$k = \#\text{Rabin pair}$
Parity	NP ∩ coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \#\text{Colours}$

Approach 1

In this paper

Add states to the automaton to maximize simplification



Optimal transformation to parity automata
(C. Colcombet, Fijalkow '21)

Exponential blowup in the worst case
(Löding '99)

Simplify the condition without adding further states

Pure Conditions

Reduction of conditions

A reduction of a condition $\mathcal{F} \subseteq 2^C$ to $\mathcal{G} \subseteq 2^C$ is a mapping

$\varphi : C \rightarrow C'$ such that


$$X \in \mathcal{F} \Leftrightarrow \varphi(X) \in \mathcal{G}, \text{ for all } X \subseteq C$$

Given a condition \mathcal{F} , can we reduce it to

- a Muller condition with $\leq k$ colours?
- a Rabin condition? With $\leq k$ Rabin pairs?
- a parity condition? With $\leq k$ colours?



Main tool: Zielonka DAG (Zielonka '98, Hunter-Dawar '06)

Given




PROPOSITION (Hunter-Dawar '06)
The Zielonka DAG can be computed in polynomial time in $|\mathcal{F}|$.

Typeless: Can we reduce \mathcal{F} to a Rabin/parity condition?




Automata

Automata



$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$


Automata




$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

Can we relabel \mathcal{A} with

- ★ a parity/Rabin condition?
- ★ $\leq k$ colours / Rabin pairs?




$$\mathcal{F} = \{ \{\alpha\}, \{\beta\} \}$$



Not parity

Requires 3 colours

$$\mathcal{F} = \{ \{\alpha\}, \{\beta\} \}$$




Not parity

Requires 3 colours

$$\mathcal{F} = \{ \{\alpha\}, \{\beta\} \}$$


But we can relabel the automaton with
a parity condition with 2 colours!

Automata



Not parity

Requires 3 colours



But we can relabel the automaton with
a parity condition with 2 colours!

Can we relabel \mathcal{A} with

- ★ a parity/Rabin condition?
- ★ $\leq k$ colours / Rabin pairs?


Main tool: Alternating Cycle Decomposition (ACD) (*C. Colcombet Fijalkow '21*)

Main tool: Alternating Cycle Decomposition (ACD) (*C. Colcombet Fijalkow '21*)

Generalisation of the Zielonka DAG

Main tool: Alternating Cycle Decomposition (ACD) (*C. Colcombet Fijalkow '21*)

Generalisation of the Zielonka DAG





$$\mathcal{F} = \{ \{ \alpha \}, \{ \beta \} \}$$

Main tool: Alternating Cycle Decomposition (ACD) (*C. Colcombet Fijalkow '21*)

Generalisation of the Zielonka DAG

Root → All edges




$$\mathcal{F} = \{ \{ \alpha \}, \{ \beta \} \}$$


Main tool: Alternating Cycle Decomposition (ACD) (*C. Colcombet Fijalkow '21*)

Generalisation of the Zielonka DAG

Root → All edges



Square if they form a
rejecting cycle




$$\mathcal{F} = \{ \{\alpha\}, \{\beta\} \}$$


Main tool: Alternating Cycle Decomposition (ACD) (*C. Colcombet Fijalkow '21*)

Generalisation of the Zielonka DAG


Root → All edges



Children: Maximal accepting subcycles



Square if they form a rejecting cycle




$$\mathcal{F} = \{ \{\alpha\}, \{\beta\} \}$$


Main tool: Alternating Cycle Decomposition (ACD) (*C. Colcombet Fijalkow '21*)

Generalisation of the Zielonka DAG

Root → All edges




Children: Maximal accepting subcycles



Square if they form a rejecting cycle

Round because they are accepting




$$\mathcal{F} = \{ \{\alpha\}, \{\beta\} \}$$


Main tool: Alternating Cycle Decomposition (ACD) (*C. Colcombet Fijalkow '21*)

Generalisation of the Zielonka DAG

Root → All edges




Children: Maximal accepting subcycles



Square if they form a rejecting cycle

Round because they are accepting



$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

THEOREM (main technical contribution)

The Alternating Cycle Decomposition can be computed in **polynomial time** in $|\mathcal{A}| + |\mathcal{F}|$.


Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?

Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?

Just look to the Alternating Cycle Decomposition! (*C. Colcombet Fijalkow '21*)


Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?

Just look to the Alternating Cycle Decomposition! (*C. Colcombet Fijalkow '21*)



Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?


Just look to the Alternating Cycle Decomposition! (*C. Colcombet Fijalkow '21*)



Restriction to the tree of a state q

Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?

Just look to the Alternating Cycle Decomposition! (*C. Colcombet Fijalkow '21*)



Restriction to the tree of a state q


Rabin

\Leftrightarrow

In the restriction-tree of every state
round nodes have a single child

Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?

Just look to the Alternating Cycle Decomposition! (*C. Colcombet Fijalkow '21*)



Restriction to the tree of a state q

Rabin

\Leftrightarrow

In the restriction-tree of every state
round nodes have a single child


Parity

\Leftrightarrow

The restriction-tree of every state
consists of a single branch.

Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?

Just look to the Alternating Cycle Decomposition! (*C. Colcombet Fijalkow '21*)



Rabin

\Leftrightarrow

In the restriction-tree of every state
round nodes have a single child

Restriction to the tree of a state q

Parity

\Leftrightarrow

The restriction-tree of every state + Minimal #Colours
consists of a single branch.

=
Height of the ACD

Minimization of colours and Rabin pairs


Minimization of colours and Rabin pairs

First idea: Do as with the Zielonka DAG!

Minimization of colours and Rabin pairs

First idea: Do as with the Zielonka DAG!

But... It does not work!



Minimization of colours and Rabin pairs

First idea: Do as with the Zielonka DAG!

But... It does not work!




THEOREM

Given an automaton \mathcal{A} and its ACD, it is **NP-complete** to determine if we can relabel it with a condition using:


- $\leq k$ colours.
- $\leq k$ Rabin pairs.

Automata



Not parity

Requires 3 colours



$$\mathcal{F} = \{\{\alpha\}, \{\beta\}\}$$

Can we relabel \mathcal{A} with


- ★ a parity/Rabin condition?
- ★ $\leq k$ colours / Rabin pairs?

But we can relabel the automaton with
a parity condition with 2 colours!

Main tool: Alternating Cycle Decomposition (ACD) (C. Colcombet Fijalkow '21)

Generalisation of the Zielonka DAG

Root \rightarrow All edges



Square if they form a rejecting cycle


Round because they are accepting

THEOREM (main technical contribution)

The Alternating Cycle Decomposition can be computed in **polynomial time** in $|\mathcal{A}| + |\mathcal{F}|$.

Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?

Just look to the Alternating Cycle Decomposition! (C. Colcombet Fijalkow '21)



Rabin
 \Leftrightarrow
 In the restriction-tree of every state
 round nodes have a single child

Restriction to the tree of a state q

Parity
 \Leftrightarrow
 The restriction-tree of every state + Minimal #Colours
 consists of a single branch.
 $=$
 Height of the ACD

Minimization of colours and Rabin pairs

First idea: Do as with the Zielonka DAG!

But... It does not work!




THEOREM

Given an automaton \mathcal{A} and its ACD, it is **NP-complete** to determine if we can relabel it with a condition using:

- $\leq k$ colours.
- $\leq k$ Rabin pairs.

Simplifying ω -Automata through the Alternating Cycle Decomposition

Antonio Casares · University of Warsaw & Corto Mascle · LaBRI, University of Bordeaux



More general conditions \rightarrow Automata are simpler to produce

- LTL \rightarrow Det. Muller automata
- ND Büchi \rightarrow Det. Rabin automata

Simpler conditions \rightarrow More efficient algorithms

Complexity of solving 2-player games. $n = \text{Size of input graph}$

Muller	PSPACE-complete	$\mathcal{O}(k^{5k}n^5)$	$k = \#\text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3}kk!)$	$k = \#\text{Rabin pair}$
Parity	NP \cap coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \#\text{Colours}$

Approach 1

Add states to the automaton to maximize simplification



In this paper

Simplify the condition without adding further states

- Optimal transformation to parity automata (C. Colcombet, Fijalkow '21)
- Exponential blowup in the worst case (Löding '99)

Goal: Simplify the acceptance condition of automata

- Simplify the type (Muller \rightarrow Rabin \rightarrow Parity)
- Minimise #Colours / #Rabin pairs

Pure Conditions


Reduction of conditions

A reduction of a condition $\mathcal{F} \subseteq 2^C$ to $\mathcal{G} \subseteq 2^C$ is a mapping


$\varphi : C \rightarrow C'$ such that

$$X \in \mathcal{F} \Leftrightarrow \varphi(X) \in \mathcal{G}, \text{ for all } X \subseteq C$$

- Given a condition \mathcal{F} , can we reduce it to
- a Muller condition with $\leq k$ colours?
 - a Rabin condition? With $\leq k$ Rabin pairs?
 - a parity condition? With $\leq k$ colours?



Not parity
Requires 3 colours




But we can relabel the automaton with a parity condition with 2 colours!


Automata

- Can we relabel \mathcal{A} with
- a parity/Rabin condition?
 - $\leq k$ colours / Rabin pairs?


Main tool: Zielonka DAG (Zielonka '98, Hunter-Dawar '06)




Typeness: Can we reduce \mathcal{F} to a Rabin/parity condition?




Minimisation of colours and Rabin pairs




Main tool: Alternating Cycle Decomposition (ACD) (C. Colcombet Fijalkow '21)



Typeness: Can we relabel \mathcal{A} with a Rabin/parity condition?




Minimisation of colours and Rabin pairs



?

	Pure Conditions	On top of automata
Tyleness		
Min. colours/ Rabin pairs		



Not parity
Requires 3 co

Main tool: Alter

Generalisation of

Root → All ed


ion

Children: Maximal
accepting subcycles

T

?

	Pure Conditions	On top of automata
Tyleness	PTIME	
Min. colours/ Rabin pairs	PTIME	



Not parity
Requires 3 co

Main tool: Alter

Generalisation of

Root → All ed

ion


Children: Maximal
accepting subcycles

Tr

?

	Pure Conditions	On top of automata
Tyleness	PTIME	
Min. colours/ Rabin pairs	PTIME	

Zielonka tree



Not parity
Requires 3 co

Main tool: Alter

Generalisation of


Root \rightarrow All ed

Children: Maximal
accepting subcycles

?

	Pure Conditions	On top of automata
Tyleness	PTIME	PTIME
Min. colours/ Rabin pairs	PTIME	

Zielonka tree



Not parity
Requires 3 co

Main tool: Alter

Generalisation of

Root \rightarrow All ed

Children: Maximal
accepting subcycles


ion

?

	Pure Conditions	On top of automata
Tyleness	PTIME	PTIME
Min. colours/ Rabin pairs	PTIME	

Zielonka tree

*Alternating Cycle
Decomposition*



Not parity
Requires 3 co

Generalisation of

Root → All ed

Children: Maximal
accepting subcycles

ion


T

?

	Pure Conditions	On top of automata
Tyleness	PTIME	PTIME
Min. colours/ Rabin pairs	PTIME	NP-complete

Zielonka tree

*Alternating Cycle
Decomposition*



Not parity
Requires 3 co

Generalisation of

Root → All ed

Children: Maximal
accepting subcycles


ion

T

	Pure Conditions	On top of automata
Tyleness	PTIME	PTIME
Min. colours/ Rabin pairs	PTIME	NP-complete

Zielonka tree

*Alternating Cycle
Decomposition*



Not parity
Requires 3 co

Main tool: Alter

Generalisation of

Root → All ed

Children: Maximal
accepting subcycles

THANK YOU!


?

ion

Th

Simplifying ω -Automata through the Alternating Cycle Decomposition

Antonio Casares · University of Warsaw & Corto Mascle · LaBRI, University of Bordeaux



More general conditions → Automata are simpler to produce

- LTL → Det. Muller automata
- ND Büchi → Det. Rabin automata

Simpler conditions → More efficient algorithms

Complexity of solving 2-player games. $n = \text{Size of input graph}$

Muller	PSPACE-complete	$\mathcal{O}(k^{5k} n^5)$	$k = \#\text{Colours}$
Rabin	NP-complete	$\mathcal{O}(n^{k+3} k k!)$	$k = \#\text{Rabin pairs}$
Parity	NP ∩ coNP. In P?	$\mathcal{O}(n^{\log(k)})$	$k = \#\text{Colours}$

Approach 1

Add states to the automaton to maximize simplification



Optimal transformation to parity automata (C. Colcombet, Fijalkow '21)

Exponential blowup in the worst case (Löding '99)

In this paper

Simplify the condition without adding further states

Goal: Simplify the acceptance condition of automata

- Simplify the type (Muller → Rabin → Parity)
- Minimise #Colours / #Rabin pairs

Pure Conditions

Reduction of conditions

A reduction of a condition $\mathcal{F} \subseteq 2^C$ to $\mathcal{G} \subseteq 2^C$ is a mapping

$\varphi : C \rightarrow C'$ such that

$X \in \mathcal{F} \Leftrightarrow \varphi(X) \in \mathcal{G}, \text{ for all } X \subseteq C$

Given a condition \mathcal{F} , can we reduce it to

- a Muller condition with $\leq k$ colours?
- a Rabin condition? With $\leq k$ Rabin pairs?
- a parity condition? With $\leq k$ colours?

	Pure Conditions	On top of automata
Typeness	PTIME	PTIME
Min. colours/ Rabin pairs	PTIME	NP-complete

Zielonka tree Alternating Cycle Decomposition

THANK YOU!

Automata

Main tool: Zielonka DAG (Zielonka '98, Hunter-Dawar '06)

Typeness: Can we reduce \mathcal{F} to a Rabin/parity condition?

$\mathcal{C} = \{\alpha, \beta, \gamma, \delta, \lambda\}$

$\mathcal{T} = \{[\alpha, \beta, \gamma], [\alpha, \beta, \gamma, \delta], [\alpha, \beta, \gamma, \lambda], [\alpha, \beta, \delta, \lambda], [\alpha, \beta, \gamma, \delta, \lambda]\}$

Root → All colours Square if it is a rejecting set
 Children: Maximal accepting subtrees Round because they are accepting sets
 Children: Maximal rejecting subtrees

PROPOSITION (Hunter-Dawar '06): The Zielonka DAG can be computed in polynomial time in $|\mathcal{T}|$.

Just look to the Zielonka DAG! (Zielonka '98)

$\mathcal{C} = \{\alpha, \beta, \gamma, \delta, \lambda\}$

$\mathcal{T} = \{[\alpha, \beta, \gamma], [\alpha, \beta, \gamma, \delta], [\alpha, \beta, \gamma, \lambda], [\alpha, \beta, \delta, \lambda], [\alpha, \beta, \gamma, \delta, \lambda]\}$

Root → All edges Square if they form a rejecting cycle
 Children: Maximal accepting subtrees Round because they are accepting
 Children: Maximal rejecting subtrees

Round nodes have a single child



Minimisation of colours and Rabin pairs

THEOREM: We can minimise the #Colours (resp. #Rabin pairs) in polynomial time.


Idea (for colour): Two colours are equivalent if they appear in the same nodes
 Merge equivalent colours
 We show that the obtained condition is optimal

Minimisation of Rabin pairs is quite involved.

PROPOSITION (Hunter-Dawar '06): The Zielonka DAG can be computed in polynomial time in $|\mathcal{T}|$.



But we can relabel the automaton with a parity condition with 2 colours!



Can we relabel \mathcal{A} with

- a parity/Rabin condition?
- $\leq k$ colours / Rabin pairs?

First idea: Do as with the Zielonka DAG!
 But... It does not work!

Minimization of colours and Rabin pairs

THEOREM: Given an automaton \mathcal{A} and its ACD, it is NP-complete to determine if we can relabel it with a condition using:

- $\leq k$ colours.
- $\leq k$ Rabin pairs.

