国elinchrom



ELB 1200

ELB 1200

The Elinchrom ELB 1200 is a revolution in portability and weather resistance, making this Li-lon battery powered pack the ideal power tool to partner every photographer's daily lighting needs.

Its robust practical design with large OLED display makes the control of its many functions simply intuitive, offering the most creative options whilst leaving your mind free to play.

Light in weight yet rich in performance, the ELB 1200 is built to deliver more! Faster recycling with more flashes per battery, a larger power range with shorter flash durations and better control of colour.

The three new ELB 1200 heads, Pro, Hi-Sync, Action each have a robust lightweight aluminium housing and tilt head, the option to use 7 mm and 8 mm umbrellas, and a powerful 92 CRI LED for both still and video use with full-sized Elinchrom accessories.

The integrated wireless Skyport[™] system provides this and seamless synchronisation, always keeping you and your camera at the heart of your photography.

WHY ELB 1200?

- Fast recycling times (1.7s in FAST mode, 3s in DEFAULT mode)
- Head with 92 CRI daylight LED equivalent to 250w Halogen.
- Heavy duty compact head
 22.5 x 14 x 23 cm weighing 2.2 kg
 with silent video mode.
- The most compact pack
 18 x 13 x 28 cm including battery.
- Weight 4.3 kg including battery
- Li-Ion Battery Air; 215 full power flashes, weight 1.1 kg (included)

- Li-lon Battery HD; 400 full power flashes, weight 1.5 kg (optional)
- Both batteries include a 5v USB power output max. 1A
- Weather resistant design
- The Creative Suite, strobo, sequence and delayed flash
- Next generation Skyport[™] offering more range, channels and control
- USB for firmware updates



TO GO SETS

This **Pro** set is the versatile option. The flash duration is very good and delivers sharp images. The Location bag is designed with the photographer in mind, made out of durable nylon and YKK zippers, this is the ideal solution to fit portable flash such as the ELB 1200.



ELB 1200 Pro To Go — N° 10304.1

Qty	Article	
lx	ELB 1200 Supplied with Li-lon battery, charger, sync cord	
lx	ELB 1200 Pro Head Supplied with 4 m flash cable and protective cap	
lx	Reflector 16 cm / 90°	
lx	Snappy carrying option with shoulder strap	
lx	Skyport Transmitter Plus	
lx	ProTec Location bag	

The Hi-Sync set is optimised to freeze motion, overpower the sun, darken backgrounds and use wider apertures with higher shutter speeds, using the optional Skyport transmitter Plus HS for Canon®, Nikon® Sony® Olympus® and Panasonic®. The Skyport Transmitter Plus HS is not part of this set and must be ordered separately.

ELB 1200 Hi-Sync To Go — N° 10305.1

Qty	Article	
lx	ELB 1200 Supplied with Li-Ion Battery, charger, sync cord	
lx	ELB 1200 Hi-Sync Head Supplied with 4m flash cable and protective cap	
lx	Reflector 16 cm / 90°	
lx	Snappy carrying option with shoulder strap	
1x	ProTec Location bag	



TO ROLL SETS

This Pro set includes our rolling case allowing you to pack more equipment when travelling over long distances. It includes also a 2-in-1 umbrella with removable cover and a grid reflector for additional lighting control



ELB 1200 Pro To Roll — N° 10306.1

Qty	Article	
lx	ELB 1200 Supplied with Li-Ion battery, charger, sync cord	
lx	ELB 1200 Pro Head Supplied with 4 m flash cable and protective cap	
lx	Grid Reflector 18 cm / 70° with 30° Grid	
lx	Snappy carrying option with shoulder strap	
lx	Umbrella shallow white/translucent 85 cm	
lx	Skyport Transmitter Plus	
lx	ProTec Rolling case	

This Hi-Sync set includes our rolling case allowing you to pack more equipment when travelling over long distances. It includes also a 2-in-1 umbrella with removable cover and a grid reflector for additional lighting control. The Skyport Transmitter Plus HS for either Canon®, Nikon® Sony® Olympus® or Panasonic® is not part of this set and must be ordered separately.

ELB 1200 Hi-Sync To Roll — N° 10307.1

Qty	Article	
lx	ELB 1200 Supplied with Li-Ion battery, charger, sync cord	
lx	ELB 1200 Hi-Sync Head Supplied with 4 m flash cable and protective cap	
lx	Grid Reflector 18 cm / 70° with 30° Grid	
lx	Snappy carrying option with shoulder strap	
lx	Umbrella shallow white/translucent 85 cm	
1x	ProTec Rolling case	



EL-SKYPORT

This radio system enables the remote control of flash power and flash triggering from the hotshoe of your camera. The optional Skyport transmitter Plus HS is a simple and reliable wireless solution that offers visual feedback and Hi-Sync features.

Extra range Trigger and adjust flash power up to 200 m (656 feet) away.

Hi-Sync Synchronise your camera up to 1/8000 s.

USB firmware For future updates.

Recommended Hi-Sync Set No 10305.1 and 10307.1

Large informative display See your unit's flash settings on the transmitter.

Compatible For Canon®, Nikon®, Sony®, Olympus® and Panasonic® cameras. **AA batteries** Never run out of power with these batteries, available everywhere.



ACCESSORIES

The three brand-new ELB 1200 heads offer lightweight robust aluminium construction and a bright dimmable daylight 92 CRI LED modelling lamp for photo and video. The new short glass dome makes the head more compact and protects the flashtube and the LED. Optionally the cooling fan can be switched to silent mode for video use. All in one, for still and video use. It's just so easy!



ELB 1200 Pro Head N°20187

Although offering a slower flash duration than the Action head, this is a great all-rounder for general use.



ELB 1200 Hi-Sync Head N°20188

Freeze action and control ambient light at up to 1/8000s with the EL-Skyport Transmitter HS



ELB 1200 Action Head N°20189

Freeze motion with very short flash durations at normal shutter speeds.



Battery Air 90 Wh N°19273

The unit comes with a high performance 90 Wh Battery Air, designed to travel safe and light. The battery offers 215 flashes at maximum power from one full charge.

Li-Ion Battery HD 144 Wh N°19296

The 144 Wh Battery is a real power house for studio and on-location use, giving about 400 full power flashes at maximum power from one full battery charge.

SPECIFICATIONS

Flash capacity (Ws/J) 1200 Asymmetrical 2:1 or symmetrical F-Stop (Im, 100 ISO, reflector 48") ELB 1200 Pro 100%: 128 100%: 128 100%: 128 100%: 128 100%: 128 100%: 128 100%: 128 100%: 128 100%: 128 100%: 128 100%: 128 100%: 14 - 1200 50%: 7 - 600 66%: 14 - 791 33%: 7 - 396 100%: 7 - 600 66%: 14 - 791 33%: 7 - 396 100%: 159 100%: 150 100%:		
F-Stop (Im, 100 ISO, reflector 48") ELB 1200 Pro F-Stop (Im, 100 ISO, reflector 48") ELB 1200 Action F-Stop (Im, 100 ISO, reflector 48") ELB 1200 Hi-Sync Power range F-stop Power range F-stop Power range ws / J 66%: 14 - 791 33%: 7 - 306 Power increments in F-Stop Best flash duration to.5 max. power ELB 1200 Action Recycling FAST to full, power, in s Recycling ECO to full, power, in s Color temperature in K" at max. power Power stability Modelling lamp modes Power bumping Flashes out of one charged battery at min. max. power ELD run time 1 / 2 heads Li-lon Battery Air (included) Li-lon Battery Air (included) Li-lon Battery HD (optional) EL-Skyport Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Weight in kg, Battery Box Policy in Second Side Side Side Side Side Side Side Sid	Flash capacity (Ws/J)	1200
F-Stop (Lm, 100 ISO, reflector 48") ELB 1200 Action	Power distribution	Asymmetrical 2:1 or symmetrical
F-Stop (Im, 100 ISO, reflector 48") ELB 1200 Hi-Sync Power range F-stop 8.5 100%: 14 – 1200 50%: 7 - 600 66%: 14 - 791 33%: 7 - 396 Power range ws / J Power increments in F-Stop Best flash duration t0.5 max, power ELB 1200 Action Recycling FAST to full power, in s Recycling FAST to full power, in s Recycling ECO to full power, in s Recycling ECO to full power, in s Color temperature in K" at max, power Power stability Adjusts power setting 4.7 Auto Power Dumping Adjusts power settings automatically Flashes out of one charged battery at min. max, power Auto Power Dumping Adjusts power settings automatically Flashes out of one charged battery at min. max, power Best flash fincluded) Li-lon Battery Air (included) Battery Box options USB charge socket for mobile devices: 5V max, 1 Amp,, shippin mode setting, battery charge status with 4 LED's Charger: approx. recharge time in h EL-Skyport Built-in, 20 frequency channels, 4 groups Sync voltage Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box (WKDXH) Dimensions in cm Battery Box (WXDXH) Power land in the first properties of the potential	F-Stop (1m, 100 ISO, reflector 48°) ELB 1200 Pro	100%: 128
Power range F-stop Power range ws / J Solve: 7 - 600 66%: 14 - 791 33%: 7 - 396 Power increments in F-Stop Best flash duration t0.5 max, power ELB 1200 Action Recycling FAST to full power, in s Recycling DEFAULT, to full power, in s Recycling ECO to full power, in s Recycling ECO to full power, in s Color temperature in K' at max, power Power stability Modelling lamp modes On, free, prop, timer 1-60 s, VFC, dimmer Power increments in F-Stop Auto Power Dunging Flashes out of one charged battery at min. max, power LED run time 1/2 heads Li-lon Battery Air, included) Li-lon Battery Air (included) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h EL-Skyport Sync voltage Sync voltage Sync voltage Sync voltage Sync voltage Weight in kg, without Battery Box / complete unit Weight in kg, Battery Box Li-lon Battery Air, included) Li-lon Battery Box (WxDxH) Dimensions in cm Battery Box / complete unit Weight in kg, Battery Box Li-lon Battery Air, included) Li-lon Battery Box (Jange) Li-lon Battery Air, included) Li-lon Batte	F-Stop (1m, 100 ISO, reflector 48°) ELB 1200 Action	100%: 90.6
Power range ws / J Comparison	F-Stop (1m, 100 ISO, reflector 48°) ELB 1200 Hi-Sync	100%: 128
Power range ws / J 50%: 7 - 600 66%: 14 - 791 33%: 7 - 396 Power increments in F-Stop Best flash duration t0.5 max. power ELB 1200 Action Recycling FAST to full power, in s Recycling FAST to full power, in s Recycling ECO to full power, in s 6 Color temperature in K* at max. power Power stability Modelling lamp modes On, free, prop, timer 1-60 s, VFC, dimmer Power increments in F-Stop Auto Power Dumping Adjusts power settings automatically Flashes out of one charged battery at min. max. power LED run time 1 / 2 heads Up to 80 / 40 min. (Li-lon Battery Air, included) Up to 80 / 40 min. (Li-lon Battery HD, optional) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h EL-Skyport Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without Battery Box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, Wathout Battery Box Up to 120, 48 lbs) (Li-lon Battery HD, optional) 11, (24 lbs) (Li-lon Battery HD, optional) 12, (31 lbs) (Li-lon Battery HD, optional) 13, (32 lbs) (Li-lon Battery Air, included) 11, (24 lbs) (Li-lon Battery Air, included) 11, (24 lbs) (Li-lon Battery HD, optional)	Power range F-stop	8.5
Best flash duration t0.5 max. power ELB 1200 Action Recycling FAST to full power, in s Recycling DEFAULT, to full power, in s Recycling ECO to full power, in s Recycling ECO to full power, in s Recycling ECO to full power, in s Color temperature in K' at max. power Power stability Modelling lamp modes Power increments in F-Stop Auto Power Dumping Flashes out of one charged battery at min. max. power LED run time 1/2 heads Li-lon Battery Air (included) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h EL-Skyport Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without Battery Box / complete unit Weight in kg, Without Battery Box (complete unit Weight in kg, Without Battery Box (complete unit) 1.7 1.7 1.7 1.7 1.7 1.7 1.7 1.	Power range ws / J	50%: 7 - 600 66%: 14 - 791
Recycling FAST to full power, in s Recycling DEFAULT, to full power, in s Recycling ECO to full power, in s Color temperature in K° at max. power Power stability Modelling lamp modes Power increments in F-Stop Auto Power Dumping Flashes out of one charged battery at min. max. power LED run time 1/2 heads Li-lon Battery Air (included) Li-lon Battery Air (included) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h EL-Skyport Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Weight in kg, without Battery Box Weight in kg, Battery Box Li-lon Battery Box Li-lon Battery Box Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.2 (Li-lon Battery Air, included) 2.3 (Res lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.2 (Li-lon Battery Air, included) 1.3 (Recycling ECO to full power, in s Battery Box Dimensions in cm, complete unit including handle & battery Battery Box (WxDxH) Recycling ECO to full power, in s Recycling ECO to full power, in s Battery Box Adjusts power settings automatically Li-lon Battery HD, optional) 1.7 1.7 1.7 1.7 1.7 1.7 1.7 1.	Power increments in F-Stop	Dial: 1/10 – left/right buttons 1 F-Stop
Recycling DEFAULT, to full power in s Recycling ECO to full power, in s Color temperature in K* at max. power Power stability Modelling lamp modes On, free, prop, timer 1-60 s, VFC, dimmer Power increments in F-Stop Dial: 1/10 – left/right buttons 1 F-Stop Auto Power Dumping Adjusts power settings automatically Flashes out of one charged battery at min. max. power LED run time 1/2 heads Up to 80 / 40 min. (Li-lon Battery Air, included) 36000 / 400 (Li-lon Battery HD, optional) Li-lon Battery Air (included) Up to 120 / 60 min. (Li-lon Battery HD, optional) Li-lon Battery HD (optional) Battery Box options USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's Charger: approx. recharge time in h 2.5 (Li-lon Battery Air, included) 3.5 (V and Air	Best flash duration t0.5 max. power ELB 1200 Action	1/8850 s at 33%, power setting 4.7
Recycling ECO to full power, in s Color temperature in K' at max. power Power stability Modelling lamp modes On, free, prop, timer 1-60 s, VFC, dimmer Power increments in F-Stop Auto Power Dumping Adjusts power settings automatically Flashes out of one charged battery at min. max. power LED run time 1/2 heads Li-lon Battery Air (included) Li-lon Battery Air (included) Li-lon Battery HD (optional) Li-lon Battery HD (optional) Battery Box options USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery HD, optional) EL-Skyport Built-in, 20 frequency channels, 4 groups Sync voltage Sync voltage Sync voltage Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Weight in kg, without Battery Box / complete unit Meight in kg, Battery Box 1.5 (Li-lon Battery Air, included) 1.2 (4 lbs) (Li-lon Battery Air, included) 1.3 (2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery Air, included)	Recycling FAST to full power, in s	1.7
Color temperature in K* at max. power Power stability #/- 0.03 % Modelling lamp modes On, free, prop, timer 1-60 s, VFC, dimmer Power increments in F-Stop Auto Power Dumping Adjusts power settings automatically Flashes out of one charged battery at min. max. power ### 120000 / 215 (Li-lon Battery Air, included) ### 36000 / 400 (Li-lon Battery Air, included) ### 120 / 60 min. (Li-lon Battery Air, included) ### 120 / 60 min. (Li-lon Battery Air, included) ### 120 / 60 min. (Li-lon Battery Air, included) ### 130 / 4.0 Ah 144 Wh ### 14ED's ### 15 (Li-lon Battery HD (optional) ### 15 (Li-lon Battery HD (optional) ### 15 (Li-lon Battery Air, included) ### 15 (Li-lon Battery Air, included) ### 25 (Li-lon Battery Air, included) ### 25 (Li-lon Battery HD, optional) ### 15 (Li-lon Battery Air, included) ### 25 (Li-lon Battery HD, optional) ### 15 (Li-lon Battery HD, optional) ### 16 (A) An 144 Wh ### 15 (Li-lon Battery HD, optional) ### 15 (Li-lon Battery HD, optional) ### 15 (Li-lon Battery HD, optional) ### 16 (A) An 144 Wh ### 15 (Li-lon Battery HD, optional) ### 15 (Li-lon Battery HD, optional) ### 16 (A) An 144 Wh ### 16 (A) An 144 Wh ### 17 (Included) ### 15 (Li-lon Battery HD, optional) ### 16 (A) An 144 Wh ### 16 (A) An 144 Wh ### 17 (Included) ### 16 (A) An 144 Wh ###	Recycling DEFAULT, to full power in s	3
Power stability Modelling lamp modes On, free, prop, timer 1-60 s, VFC, dimmer Power increments in F-Stop Auto Power Dumping Flashes out of one charged battery at min. max. power LED run time 1 / 2 heads Li-lon Battery Air, (included) Li-lon Battery Air (included) Li-lon Battery Air (included) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h LI-Skyport Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box (WxDxH) Dimensions in cm Battery Box (PxDxH) Weight in kg, without Battery Box Modelling Lamp modes On, free, prop, timer 1-60 s, VFC, dimmer Dial: 1,10 – left/right buttons 1 F-Stop Adjusts power settings automatically Polial: 1,10 – left/right buttons 1 F-Stop Adjusts power settings automatically 1,20000 / 215 (Li-lon Battery Air, included) 2,20000 / 215 (Li-lon Battery HD, optional) Up to 80 / 40 min. (Li-lon Battery HD, optional) But to 80 / 40 min. (Li-lon Battery HD, optional) Up to 80 / 40 min. (Li-lon Battery HD, optional) 36V / 2.5 Ah / 90 Wh 36V / 2.5 Ah / 90 Wh 36V / 2.5 Ah / 90 Wh 36V / 4.0 Ah 144 Wh USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's 1.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery HD, optional) EL-Skyport Built-in, 20 frequency channels, 4 groups Sync voltage Sync socket 3.5 mm jack 18x13x28 / 18x13x22 Dimensions in cm, complete unit including handle & battery box (WxDxH) 18x13x75 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Recycling ECO to full power, in s	6
Modelling lamp modes On, free, prop, timer 1-60 s, VFC, dimmer Power increments in F-Stop Auto Power Dumping Flashes out of one charged battery at min. max. power LED run time 1/2 heads Li-lon Battery Air, included) Li-lon Battery Air (included) Li-lon Battery Air (included) Li-lon Battery HD, optional) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h Li-Skyport Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box / complete unit Weight in kg, without Battery Box National Adjusts power settings automatically Adjusts power settings automatically 120000 / 215 (Li-lon Battery Air, included) 20000 / 215 (Li-lon Battery Air, included) up to 80 / 40 min. (Li-lon Battery HD, optional) 36V / 2.5 Ah / 90 Wh 36V / 2.5 Ah / 90 Wh 36V / 4.0 Ah 144 Wh USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's 1.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery HD, optional) EL-Skyport Built-in, 20 frequency channels, 4 groups Sync socket 3.5 mm jack Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Neight in kg, without Battery Box / complete unit 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Color temperature in K° at max. power	5500
Power increments in F-Stop Auto Power Dumping Flashes out of one charged battery at min. max. power LED run time 1 / 2 heads Li-lon Battery Air (included) Li-lon Battery Air (included) Li-lon Battery HD (optional) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h EL-Skyport Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box / complete unit Weight in kg, Wattery Box Weight in kg, Battery Box Dimensions in cm, Complete unit included) Weight in kg, Battery Box Dimensions in kg, Battery Box Dimensions in kg, Battery Box Li-lon Battery Box Dimensions in cm, complete unit including handle & battery box / without Battery Box / complete unit Dimensions in cm, complete unit included and included	Power stability	+/- 0.03 %
Auto Power Dumping Adjusts power settings automatically Flashes out of one charged battery at min. max. power LED run time 1/2 heads Li-lon Battery Air, included) Li-lon Battery Air (included) Li-lon Battery HD, optional) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h Li-Skyport Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box / complete unit Weight in kg, Wattery Box Weight in kg, Battery Box Adjusts power settings automatically 20000 / 215 (Li-lon Battery Air, included) up to 80 / 40 Ah 1.40 (Li-lon Battery HD, optional) USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's 1.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery HD, optional) 18x13x28 / 18x13x22 Weight in kg, without Battery Box / complete unit 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery Air, included)	Modelling lamp modes	On, free, prop, timer 1-60 s, VFC, dimmer
Flashes out of one charged battery at min. max. power 20000 / 215 (Li-Ion Battery Air, included) 36000 / 400 (Li-Ion Battery HD, optional) LED run time 1 / 2 heads Li-Ion Battery Air (included) 360 / 2.5 Ah / 90 Wh Li-Ion Battery HD (optional) 36V / 2.5 Ah / 90 Wh Li-Ion Battery HD (optional) 36V / 4.0 Ah 144 Wh Battery Box options Charger : approx. recharge time in h EL-Skyport Built-in, 20 frequency channels, 4 groups Sync voltage 5V compatible with all cameras Sync socket 3.5 mm jack Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box / complete unit Weight in kg, without Battery Box / complete unit Weight in kg, Battery Box 1.1 (2.4 lbs) (Li-Ion Battery Air, included) 1.2 (3.3 lbs) (Li-Ion Battery Air, included) 1.3 (2.4 lbs) (Li-Ion Battery Air, included) 1.4 (2.4 lbs) (Li-Ion Battery Air, included) 1.5 (3.3 lbs) (Li-Ion Battery Air, included)	Power increments in F-Stop	Dial: 1/10 — left/right buttons 1 F-Stop
LED run time 1 / 2 heads Li-lon Battery Air (included) Li-lon Battery Air (included) Li-lon Battery HD, optional) Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h EL-Skyport Sync voltage Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (Complete unit My, without Battery Box / complete unit My, included) Weight in kg, Wattery Box Up to 80 / 40 Min. (Li-lon Battery Air, Included) 36V / 2.5 Ah / 90 Wh 36V / 2.5 Ah / 90 Wh 36V / 4.0 Ah 144 Wh USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's 1.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery HD, optional) Built-in, 20 frequency channels, 4 groups 5V compatible with all cameras 3.5 mm jack 18x13x28 / 18x13x22 Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) 18x13x7.5 Weight in kg, without Battery Box / complete unit 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Auto Power Dumping	Adjusts power settings automatically
Li-lon Battery Air (included) Li-lon Battery Air (included) Battery Box options Charger: approx. recharge time in h EL-Skyport Sync voltage Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, without Battery Box Li-lon Battery HD, optional) USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's 1.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery HD, optional) Built-in, 20 frequency channels, 4 groups 5V compatible with all cameras 3.5 mm jack 18x13x28 / 18x13x22 18x13x25 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Flashes out of one charged battery at min. max. power	
Li-lon Battery HD (optional) Battery Box options Charger: approx. recharge time in h EL-Skyport Sync voltage Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, without Battery Box Weight in kg, Battery Box USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's 1.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery HD, optional) Built-in, 20 frequency channels, 4 groups 5V compatible with all cameras 3.5 mm jack 18x13x28 / 18x13x22 18x13x25 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	LED run time 1/2 heads	
Battery Box options USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's 1.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery HD, optional) EL-Skyport Built-in, 20 frequency channels, 4 groups Sync voltage 5V compatible with all cameras Sync socket 3.5 mm jack Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) 18x13x28 / 18x13x22 Weight in kg, without Battery Box / complete unit 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Li-Ion Battery Air (included)	36V / 2.5 Ah / 90 Wh
Charger: approx. recharge time in h EL-Skyport Built-in, 20 frequency channels, 4 groups Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, without Battery Box Weight in kg, Battery Box I.5 (Li-lon Battery Air, included) 2.5 (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Li-Ion Battery HD (optional)	36V / 4.0 Ah 144 Wh
EL-Skyport Built-in, 20 frequency channels, 4 groups Sync voltage Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, without Battery Box / complete unit 12.5 (Li-lon Battery HD, optional) 8 built-in, 20 frequency channels, 4 groups 5 V compatible with all cameras 18x13x28 / 18x13x22 18x13x25 18x13x75 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Battery Box options	USB charge socket for mobile devices: 5V max. 1 Amp., shippin mode setting, battery charge status with 4 LED's
Sync voltage Sync socket 3.5 mm jack Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, without Battery Box / complete unit Weight in kg, Battery Box 18x13x28 / 18x13x22 18x13x25 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Charger : approx. recharge time in h	
Sync socket Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, without Battery Box / complete unit Weight in kg, Battery Box 18x13x28 / 18x13x22 18x13x22 18x13x25 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	EL-Skyport	Built-in, 20 frequency channels, 4 groups
Dimensions in cm, complete unit including handle & battery box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, without Battery Box / complete unit Weight in kg, Battery Box 18x13x28 / 18x13x22 18x13x25 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Sync voltage	5V compatible with all cameras
box / without battery box (WxDxH) Dimensions in cm Battery Box (WxDxH) Weight in kg, without Battery Box / complete unit Weight in kg, Battery Box 18x13x28 / 18x13x22 18x13x25 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Sync socket	3.5 mm jack
Weight in kg, without Battery Box / complete unit 3.2 kg (6.8 lbs) 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)		18x13x28 / 18x13x22
Weight in kg, Without Battery Box / complete unit 4.3 (9.48 lbs) (Li-lon Battery Air, included) 1.1 (2.4 lbs) (Li-lon Battery Air, included) 1.5 (3.3 lbs) (Li-lon Battery HD, optional)	Dimensions in cm Battery Box (WxDxH)	18x13x7.5
Weight in kg, Battery Box 1.5 (3.3 lbs) (Li-Ion Battery HD, optional)	Weight in kg, without Battery Box / complete unit	
Supplied with ELB 1200, battery box, quick charger, sync cable	Weight in kg, Battery Box	
	Supplied with	ELB 1200, battery box, quick charger, sync cable









This brochure may show images of products with accessories which are not part of sets or single units. Elinchrom sets and single unit configurations may change without advice and they might be different in other countries.

Tolerances of specifications and components conform to IEC and CE standards. The listed values can differ due to tolerances in components, or measuring instruments. Technical data, subject to change. No guarantee for misprints.

Canon®, Nikon® and Sony® are protected trademarks which do not belong to Elinchrom LTD.

Photo: Tristan Shu

72127 — EN — ELB 1200 — 02.2017 — ELINCHROM — SWITZERLAND — WWW.ELINCHROM.CH