

Deployment

To deploy the project in the course's pre-production environment, please follow the steps below:

1. First, open your browser, go to <http://localhost/manager> , and undeploy the context path “/”.
2. Open the file explorer, go to C:\Program Files\Apache Software Foundation\Tomcat 7.0 and delete any folders that start with “domain.”, if any exist. This will prevent any previous Lucene indexes from interfering with our application.
3. Open a command line and navigate to the folder where the SQL script for the database is. Type the following:

```
mysql --user=root --password=[YOUR PASSWORD HERE] < Create-Acme-[PROJECT].sql
```
4. If no error appears, proceed to step 5. Otherwise, if you see some error about mysql not existing, your PATH environment is misconfigured. An easy way to sidestep this is to copy the SQL file to the MySQL bin directory, which should be C:\Program Files\MySQL\MySQL Server 5.5\bin if you are using the course's VM.
5. Copy the war file to your desktop and rename it to ROOT.war.
6. Stop and restart the Tomcat service (right click the icon next to the clock in the taskbar).
7. Open your browser, go to <http://localhost/manager>, and upload and deploy ROOT.war.
8. Open c:\windows\system32\drivers\etc\hosts and ensure the following line is in the file:
127.0.0.1 www.acme.com
9. Open your browser and go to <http://www.acme.com>. You are done.