

RENDER

3 SERVICIOS

- 1. API (Backend)
- 1 PHP (stranger)
- 1 PHP (dragón)

SERVICE NAME	3	STATUS
🌐 stranger		✓ Deployed
🌐 dragon		✓ Deployed
🌐 API REST		✓ Deployed

API (BACKEND)

ROOT DIRECTORY: backend

ENVIRONMENT VARIABLES

Apuntan a las credenciales que nos proporcionó MariaDB (las que pusimos en el properties pre) es copiar y pegar.

KEY	VALUE
PORT	8080
SPRING_DATASOURCE_PASSWORD	.UK~n31m4(sCn8Uub51o
SPRING_DATASOURCE_URL	jdbc:mysql://serverless-us-east1.sysp0000.db2.skysql.com:4042/series?useSSL=true&requireSSL=true
SPRING_DATASOURCE_USERNAME	dbpgf32546023

STRANGER (PHP)

ROOT DIRECTORY: frontend_stranger

DRAGON (PHP)

ROOT DIRECTORY: frontend_dragon

ENVIRONMENT VARIABLES

Apuntan a la dirección del Backend RENDER desplegado más el **/api**

El nombre de la KEY viene en los **index.php**

// BACKEND_URL debe terminar en /api

```
$backendUrl = rtrim(getenv("API_BACKEND_URL") ?: "http://localhost:8080/api", "/");
```

KEY	VALUE
API_BACKEND_URL	https://api-rest-kvj4.onrender.com/api