

## **Data windowing in digital signal processing**

In modern digital signal processing, after sampling and quantization, the only object we work with is the discrete-time sequence  $x[n]$ . The information that has been lost in the previous stages (due to the anti-aliasing filter, limited sampling frequency, and quantization) has already been controlled by design so as to concern a non-useful or imperceptible part of the signal. From this point on, the processing concerns exclusively  $x[n]$ .

One of the first and most important steps in many forms of digital processing is windowing. Windowing is applied to the discrete signal and consists of multiplying  $x[n]$  by a sequence  $w[n]$ , called a window:  $xw[n] = x[n]w[n]$

The windowed signal  $xw[n]$  is the new signal to be processed. This procedure is carried out entirely in the digital domain and is not related to the sampling stage or to analog processing.

### **Why windows are needed**

In practice, processing is often performed on finite segments of the signal (frames). Arbitrarily truncating a segment is equivalent to multiplying by a rectangular window, which creates abrupt discontinuities at the edges. These discontinuities cause spectral leakage, meaning energy “spills” into neighboring frequencies in the spectrum.

The use of an appropriate window reduces this leakage by smoothing the beginning and end of the segment. Thus, the signal gradually fades out at the edges instead of being cut off abruptly, which greatly improves the spectral representation.

### **Where windowing is applied**

Windowing belongs strictly to the digital processing stage and is used:

- before computing the DFT/FFT for spectral analysis
- in short-time signal analysis (STFT, spectrogram)
- in block processing (overlap–add, overlap–save)
- in frame-based speech and audio processing

In this context, it can be considered the first digital processing applied to  $x[n]$ . Conversely, when filters of the FIR or IIR type are applied directly in the time domain to the signal, windowing may not be required.

### **Types of windows**

There are many types of windows, each with a different trade-off between main lobe and side lobes in the spectrum:

- rectangular
- Hann
- Hamming

- Blackman
- Kaiser

The Hamming window is particularly popular in audio and speech applications. It offers a relatively narrow main lobe and low side lobes, limiting spectral leakage while maintaining satisfactory frequency resolution.

### **What processing after windowing means**

After the window is applied, the signal  $x_w[n]$  is the one subsequently subjected to spectral analysis, FFT, or block processing. The result of these procedures leads to the output spectrum  $Y(ej\omega)$ , which expresses the desired processing result and, if reconstruction is performed, determines the final analog signal.

### **Conclusion**

Windowing is a fundamental tool in spectral analysis and segment-based signal processing. It is applied exclusively in the digital processing stage to the discrete signal  $x[n]$  and produces the windowed signal  $x_w[n]$ , which is then processed further. With the proper choice of window, unwanted spectral distortions are reduced and the accuracy of the analysis is improved, without requiring changes to the sampling or quantization process.