

Write the Pseudocode and Flowchart for the problem statements mentioned below:

1. Smart Home Temperature Control

Problem Statement:

Design a temperature control system for a smart home. The system should read the current temperature from a sensor every minute and compare it to a user-defined setpoint.

Requirements:

- If the current temperature is above the setpoint, activate the cooling system.
 - If the current temperature is below the setpoint, activate the heating system.
 - Display the current temperature and setpoint on an LCD screen.
 - Include error handling for sensor failures.
-

Pseudocode


```
//get inputs
get_time();
get_temprature();
temperature_threshold;
delay();
//set outputs
heating_system();
cooling_system();
lcd_display();
main{
while(1){
current_time=get_time();
current_temprature=get_temprature();
if(current_temprature<=0;){
lcd_display(error);
}
else{
if(current_temprature<temperature_threshold){
heating_system();
lcd_display(current_temprature);
lcd_display(temprature_threshold);
}
else if(current_temprature>temprature_threshold){
cooling_system();
lcd_display(current_temprature);
lcd_display(temprature_threshold);
}
}
delay(60);
}
delay(){
return seconds;
}
get_time(){
return time;
}
get_temprature(){
```

```

return temprature;
}
heating_system(){
activate heating system;
}
cooling_system(){
activate cooling system;
}

```

Flowchart



2. Automated Plant Watering System

Problem Statement:

Create an automated watering system for plants that checks soil moisture levels and waters the plants accordingly.

Requirements:


- Read soil moisture level from a sensor every hour.
- If moisture level is below a defined threshold, activate the water pump for a specified duration.
- Log the watering events with timestamps to an SD card.
- Provide feedback through an LED indicator (e.g., LED ON when watering).

```

//get inputs
get_moisture();
get_time();
moisture_threshold;
delay();
//set outputs
pump_system();
ledPin;
store_data();
main{
while(1){
current_time=get_time();
current_moisture=get_moisture();
if(current_moisture<moisture_threshold){
    pump_system();
    ledPin=HIGH;
    delay(20);
store_data("pump activated", current_time);
    ledPin=LOW;
}
else{
    ledPin=LOW;
}
}
delay(3600);
}
delay(){
return seconds;
}
get_time(){
return time;
}
get_moisture(){
return moisture;
}
pump_system(){
activate pump system;
}
store_data(pump_status,timestamp){
pump_status;
timestamp;
}

```

Flowchart



3. Motion Detection Alarm System

Problem Statement:

Develop a security alarm system that detects motion using a PIR sensor.

Requirements:

- Continuously monitor motion detection status.
- If motion is detected for more than 5 seconds, trigger an alarm (buzzer).
- Send a notification to a mobile device via UART communication.
- Include a reset mechanism to deactivate the alarm.


```

//get inputs
get_motion();
get_time();
reset();
delay();
//set outputs
trigger_system();
notification();
();
main{
while(1){
motion_detected=get_motion();

if(motion_detected){
    current_time=get_time();
    while(motion_detected){
        if(get_time-current_time>=5){
            trigger_system(activate);
            notification("movement detected");
            break;
        }
    }
}
if(reset()){
    trigger_system(deactivate);
    notification("reset done");
}
}
delay(){
return seconds;
}
get_time(){
    return time;
}
get_motion(){
    return motion;
}
trigger_system(){
    activate trigger system;
}
notification(){
    return motification;
}
reset(){
    stop trigger;
    stop notification;
}

```

Flowchart



4. Heart Rate Monitor

Problem Statement:

Implement a heart rate monitoring application that reads data from a heart rate sensor.

Requirements:

- Sample heart rate data every second and calculate the average heart rate over one minute.
- If the heart rate exceeds 100 beats per minute, trigger an alert (buzzer).
- Display current heart rate and average heart rate on an LCD screen.
- Log heart rate data to an SD card for later analysis.

5. LED Control Based on Light Sensor

Problem Statement:

Create an embedded application that controls an LED based on ambient light levels detected by a light sensor.

Requirements:

- Read light intensity from the sensor every minute.
- If light intensity is below a certain threshold, turn ON the LED; otherwise, turn it OFF.
- Include a manual override switch that allows users to control the LED regardless of sensor input.
- Provide status feedback through another LED (e.g., blinking when in manual mode).


```

read_light();
light_threshold;
ledPin1;
ledPin2;
delay()
manual_mode=false;
main(){
while(1){
if(manual_mode==true){
    ledPin2=blink;

}
else if(manual_mode==false){
if(read_light<threshold){
ledPin1=high;
}
else{
ledPin1=low;
}
delay(60);
}

}
read_light(){
return light_value;
}
delay(){
return seconds;
}

```



6. Digital Stopwatch

Problem Statement:

Design a digital stopwatch application that can start, stop, and reset using button inputs.

Requirements:

- Use buttons for Start, Stop, and Reset functionalities.
- Display elapsed time on an LCD screen in hours, minutes, and seconds format.
- Include functionality to pause and resume timing without resetting.
- Log start and stop times to an SD card when stopped.

7. Temperature Logging System

Problem Statement:

Implement a temperature logging system that records temperature data at regular intervals.

Requirements:

- Read temperature from a sensor every 10 minutes.
- Store each reading along with its timestamp in an array or log file.
- Provide functionality to retrieve and display historical data upon request.
- Include error handling for sensor read failures.

8. Bluetooth Controlled Robot

Problem Statement:

Create an embedded application for controlling a robot via Bluetooth commands.

Requirements:

- Establish Bluetooth communication with a mobile device.
- Implement commands for moving forward, backward, left, and right.

- Include speed control functionality based on received commands.
- Provide feedback through LEDs indicating the current state (e.g., moving or stopped).

9. Battery Monitoring System

Problem Statement:

Develop a battery monitoring system that checks battery voltage levels periodically and alerts if voltage drops below a safe threshold.

Requirements:

- Measure battery voltage every minute using an ADC (Analog-to-Digital Converter).
- If voltage falls below 11V, trigger an alert (buzzer) and log the event to memory.
- Display current voltage on an LCD screen continuously.
- Implement power-saving features to reduce energy consumption during idle periods.

10. RFID-Based Access Control System

Problem Statement:

Design an access control system using RFID technology to grant or deny access based on scanned RFID tags.

Requirements:

- Continuously monitor for RFID tag scans using an RFID reader.
- Compare scanned tags against an authorized list stored in memory.
- Grant access by activating a relay if the tag is authorized; otherwise, deny access with an alert (buzzer).
- Log access attempts (successful and unsuccessful) with timestamps to an SD card.