

# Bioresearch Monitoring (BIMO) Data Reviewer's Guide (BDRG)

Study Name: TROPIC Re-Analysis (Study EFC6193 / XRP6258, NCT00417079)  
Compound: Mitoxantrone (MP) control arm -- real, de-identified cohort (N=371)  
Standard: FDA Bioresearch Monitoring Technical Conformance Guide (clinsite, Appendix 3)  
Created: 2026-06-16

## 1. Purpose

The summary-level clinical-site dataset (clinsite) supports the FDA Office of Scientific Investigations (OSI) / BIMO program. It aggregates subject-level enrollment, disposition, and safety experience to the study-site level so that reviewers can prioritise clinical sites for on-site inspection. It is not an analysis dataset and is not part of the ADaM define.xml; per the BIMO Technical Conformance Guide it is delivered with its own data-definition documentation (this BDRG) under 08\_submission\_package/m5/datasets/tropic/bimo/.

This guide follows the structure recommended by the PHUSE BIMO Data Reviewer's Guide Completion Guidelines.

## 2. Honest Scope vs. the Full BIMO TCG `clinsite` Specification

*The full BIMO TCG Appendix-3 `clinsite` structure specifies \*\*~39 site-level variables\*\* (investigator identity/address/contact, country, screen/randomized/treated/completed/discontinued counts, protocol-deviation counts, primary-endpoint contribution, financial-disclosure flags, etc.). This portfolio implements the **subset that is HONESTLY DERIVABLE** from the public, de-identified TROPIC release (Project Data Sphere). It deliberately does **not** fabricate variables the source cannot support. This is an *illustrative BIMO subset*, not a submission-complete clinsite.*

Variables intentionally NOT populated, and why:

| Omitted BIMO TCG content                    | Reason it is not derivable from this source                                                                                                                                                    |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Investigator name / address / phone / email | The de-identified PDS release carries <b>no</b> principal-investigator identity. `INVNAM` below is a clearly-labelled <b>synthetic placeholder</b> (`PI_<siteid>`), never a real investigator. |
| `COUNTRY` / site geography                  | Not present in the de-identified release.                                                                                                                                                      |
| Important / significant protocol deviations | No SDTM `DV` (protocol deviations) domain is available in the public release.                                                                                                                  |

| Omitted BIMO TCG content                   | Reason it is not derivable from this source                                                                                |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Screened / completed / discontinued counts | DS disposition reasons are not separable into screen-fail vs. completion vs. discontinuation in the de-identified release. |
| Financial disclosure                       | Not applicable to a public secondary-use dataset.                                                                          |

A production BIMO package would populate the full Appendix-3 structure from the sponsor's operational/CTMS data; the derivation pattern demonstrated here (subject-level ? site-level roll-up, joined across populations and safety) is the transferable skill.

### 3. Variables Delivered (`clinsite`, one row per study site; 69 sites)

| Variable  | Label                                              | Derivation                                                           |  |                   |
|-----------|----------------------------------------------------|----------------------------------------------------------------------|--|-------------------|
| `STUDYID` | Study Identifier                                   | ADSL `STUDYID`                                                       |  |                   |
| `SITEID`  | Study Site Identifier                              | ADSL `SITEID` (group key)                                            |  |                   |
| `INVNAM`  | Principal Investigator (**SYNTHETIC** placeholder) | `"PI_"`                                                              |  | SITEID` -- see §2 |
| `N_RAND`  | Number of Subjects Randomized                      | `COUNT(DISTINCT USUBJID)` per site                                   |  |                   |
| `N_SAF`   | Number of Subjects Treated (Safety Population)     | `SAFFL='Y'` per site                                                 |  |                   |
| `N_ITT`   | Number of Subjects in ITT Population               | `ITTFL='Y'` per site                                                 |  |                   |
| `N_PPROT` | Number of Subjects in Per-Protocol Population      | `PPROTFL='Y'` per site                                               |  |                   |
| `N_DEATH` | Number of Subjects Who Died                        | `DTHFL='Y'` per site                                                 |  |                   |
| `N_SAE`   | Number of Subjects with a Serious AE               | distinct `USUBJID` with ADAE<br>`AESER='Y'`, routed to site via ADSL |  |                   |

| Variable | Label                             | Derivation                                                                      |
|----------|-----------------------------------|---------------------------------------------------------------------------------|
| `N_TEAE` | Number of Subjects<br>with a TEAE | distinct `USUBJID`<br>with ADAE<br>`TRTEMFL='Y'`,<br>routed to site via<br>ADSL |

*\*\*Population note (ICH E9):\*\* Randomized, Safety (treated), ITT, and Per-Protocol are **\*\*distinct analysis sets\*\***. ITT is reported as `N\_ITT` and is **\*\*never\*\*** relabelled "Efficacy Population" (a prior version mislabelled the ITT count as efficacy -- corrected). In this de-identified single-arm release all subjects are randomized, treated, ITT, and per-protocol, so those four counts coincide per site; the safety counts (`N\_DEATH`, `N\_SAE`, `N\_TEAE`) vary by site and carry the inspection-prioritisation signal.*

#### 4. Dual-Programming / Reconciliation

clinsite is double-programmed like the ADaM domains: produced by SAS (04\_analysis\_datasets/programs/sas/B\_bimo\_generation.sas ? clinsite\_prod.xpt) and independently by R (04\_analysis\_datasets/programs/r/v\_bimo\_validation.R ? clinsite\_v.xpt), then reconciled cell-by-cell on the (STUDYID, SITEID) key by 06\_qc\_evidence/reconciliation/cross\_lang\_audit.R. As with all domains, a genuine SAS?R reconciliation requires a run executed against a real SAS engine (sas\_execution\_mode = oda/local in platform/pipeline\_health.json); a sim-mode byte-copy reconciliation is tautological.

#### 5. References

- \* FDA, \*Bioresearch Monitoring Technical Conformance Guide\* (clinsite, Appendix 3).
- \* PHUSE, \*BIMO Data Reviewer's Guide (BDRG) Completion Guidelines\*.
- \* PHUSE SA01, \*Development of a standard BIMO process to create the clinsite dataset\*.
- \* ICH E9, \*Statistical Principles for Clinical Trials\* (analysis-set definitions).