

Study Data Reviewer's Guide (SDRG)

Study Name: TROPIC Re-Analysis

Compound: Cabazitaxel (CbzP) vs. Mitoxantrone (MP)

Standard: CDISC SDTMIG v3.1.1

Created: 2026-05-23

1. Source Data Normalization & Integrity Controls

Source data are the official Sanofi de-identified SDTM datasets for NCT00417079, released in 2013 and accessed via the Project Data Sphere (PDS) repository. The files are SAS transport datasets (.sas7bdat); no other source format is used (this matches README.md Data provenance and REPRODUCIBILITY.md §5).

The custom SAS staging compiler (L_staging_ingest.sas) ingests these SDTM .sas7bdat files (set realsdtm.<domain>) and performs automated supplemental-qualifier (SUPP--) transposition and merge, coercing character-encoded continuous indicators (e.g. age, laboratory values, vital measurements) into standardized double-precision numeric values.

****Single-Arm Source Limitation:**** The source Project Data Sphere (PDS) public dataset contains only the Mitoxantrone (MP) arm (N=371). The comparator Cabazitaxel (CbzP) arm (N=378) was not included in the public release. Consequently, the SDTM datasets only represent the MP cohort. In our pipeline, the core production (SAS) and validation (R) ADaM tracks process strictly the MP cohort (N=371) to establish a clean double-programming validation setup. The comparator Cabazitaxel cohort is reconstructed from published trial literature and merged dynamically at the final reporting/TFL compilation step in [tfl_generation.R](file:///Users/apple/Desktop/TROPIC/09_tfl/tfl_generation.R).

Database Write-Protection Architecture

To guarantee database integrity and prevent raw data corruption during pipeline executions:

- * The `realsdtm` SAS libref (pointing to `01\_raw\_source/real\_sdtm/`) is mounted with `access=readonly` in [00_config.sas](file:///Users/apple/Desktop/TROPIC/02_production_sas/00_config.sas), preventing direct writes via that libref.

- * The `staging` SAS libref (same physical directory) is writable, allowing `L\_staging\_ingest.sas` to write transposed SUPP-merged domain outputs alongside source files during ODA cloud execution.

- * Intermediate mapped SDTM outputs generated during mapping runs are redirected to [sdm_mapped](file:///Users/apple/Desktop/TROPIC/04_adam/sdm_mapped/) inside the [04_adam](file:///Users/apple/Desktop/TROPIC/04_adam/) output folder.

2. SDTM Domain Mapping Summary

Standard SDTM mapping structures were built in S_sdtm_mapping.sas under the trial-era SDTM-IG 3.1.1 standard (per SAP v3.0 §1; the source data predates later IG versions):

- * ****DM (Demographics):**** Unique subject identifier `USUBJID` constructed via `STUDYID || '-' || SITEID || '-' || SUBJID`. Randomization date `RANDDT` and treatment start date `TRTSDT` mapped to standard ISO 8601 date fields.

- * ****EX (Exposure):**** Normalised cycle-level actual administered doses (`EXDOSE` in mg).

* **AE (Adverse Events):** Coded utilizing MedDRA dictionaries into `AEDECOD`, `AEBODSYS`, and standard CTCAE toxicity grades. **Date Precision Note:** The source PDS dataset contains AE timing as week-offset integers (`AESTWK`, `AEENWK`). AE start/end dates are reconstructed as `RFSTDTC + (AESTWK - 1) \* 7` and `RFSTDTC + (AEENWK - 1) \* 7`. This reconstruction yields calendar-week accuracy (± 3.5 days) rather than exact calendar dates. This precision level was present in the source data and is not a programming artefact. All safety analyses using AE dates (ADAE, ADTTE TTSAE) inherit this limitation.

* **LB (Laboratory):** Mapped continuous Absolute Neutrophil Count (ANC) and Prostate Specific Antigen (PSA) measurements.

* **DS (Disposition):** Captured study completion reasons, trial exits, and survival follow-up records.

* **RS (Response / Efficacy Fallback):** Derived from `DS` domain where `DSDECOD` indicates progression or death. Death records are mapped to standard RS structures with `RSSTRESC = 'DEATH'` to capture survival outcomes cleanly as efficacy checkpoints.

3. Reference Ranges & Baseline Criteria

* Baseline lab and vitals measurements are defined as the last non-missing assessment completed prior to first exposure (`ADY <= 0`).

* Normal reference ranges (`LBNRLO` and `LBNRHI`) were preserved from raw PDS metadata. Lab values outside these ranges are flagged accordingly in `LBNRIND`.

4. Known Data Limitations & Derivation Decisions

4.1 Baseline Laboratory Imputation

For subjects with missing baseline laboratory values (PSABL, ALPBL, HGBBL), population-median proxy values have been imputed in ADSL:

* `PSABL` default: 110.0 ng/mL

* `ALPBL` default: 140.0 U/L

* `HGBBL` default: 11.5 g/dL

* `ALBBL` fixed: 38.0 g/L (no subject-level source available)

* `LDHBL` fixed: 220.0 U/L (no subject-level source available)

This imputation strategy has no formal SAP section (the SAP v3.0 specifies no missing-data imputation method); it is a documented design choice per ADRG §5.1. These imputed baseline laboratory constants are schema placeholders and are NOT used as covariates or stratification factors in any efficacy model, consistent with ADRG §5.1. The primary and secondary Cox / log-rank analyses stratify only on ECOGBL and MEASDISF (see 09_tfl/tfl_generation.R, `compute_tte_stats() ? strata(ECOGBL, MEASDISF)`). ALBBL and LDHBL in particular are single constants for all subjects (no subject-level source available) and therefore carry no subject-level information; they are retained purely to satisfy the ADaM schema and should be read as "not available," not as analysis inputs.

4.2 Supplemental Domain Ingestion

Domains LS (Lesion) and PN (Pain/Numeric) do not have supplemental (SUPPLS, SUPPPN) datasets in the PDS source data. The `%transpose_supp()` macro gracefully handles this via the `supp_exists = 0` guard path, copying the primary domain directly without SUPP merge.

4.3 Country and Region Assignment

The DM domain in the source data does not contain country-of-study-site information. COUNTRY is assigned 'IND' and REGION as 'REST OF WORLD' for all subjects. Geographic subgroup analyses were not pre-specified in SAP v3.0 and are not reported.

4.4 Hardcoded Demographic Constant (SEX = 'M')

The demographics domain (DM) contains a hardcoded variable SEX = 'M' assigned to all subjects in A_adsl_generation.sas. This is a clinical decision consistent with the trial protocol for metastatic castration-resistant prostate cancer (mCRPC), which is an exclusively male patient population. To ensure metadata conformity, the Define-XML codelist references are maintained; however, no female subjects are present in the analysis dataset.