

```
#include<stdio.h>
#include<stdlib.h>
void main()
{
    int ch,A[50],B[50],C[50],m,n,i;
    do
    {
        printf("\nInput choice to perform: ");
        printf("\n1.Union\t2.Intersection\t3.Difference\t4.Exit");
        printf("\nChoice: ");
        scanf("%d",&ch);
        switch(ch)
        {
            case 1:printf("\nEnter cardinality of first set: ");
                    scanf("%d",&m);
                    printf("\nEnter cardinality of second set: ");
                    scanf("%d",&n);
                    if(m!=n)
                    {
                        printf("\nCannot perform union!");
                        break;
                    }
                    printf("\nEnter elements of first set:(0/1) ");
                    for(i=0;i<m;i++)
                    {
                        scanf("%d",&A[i]);
                    }
                    printf("\nEnter elements of second set:(0/1) ");
                    for(i=0;i<n;i++)
                    {
```

```

    scanf("%d",&B[i]);
}
printf("\nElements of set1 union set2: ");
for(i=0;i<m;i++)
{
    C[i]=A[i]|B[i];
    printf("%d ",C[i]);
}
break;
case 2:printf("\nEnter cardinality of first set: ");
scanf("%d",&m);
printf("\nEnter cardinality of second set: ");
scanf("%d",&n);
if(m!=n)
{
    printf("\nCannot perform intersection!");
    break;
}
printf("\nEnter elements of first set:(0/1) ");
for(i=0;i<m;i++)
{
    scanf("%d",&A[i]);
}
printf("\nEnter elements of second set:(0/1) ");
for(i=0;i<n;i++)
{
    scanf("%d",&B[i]);
}
printf("\nElements of set1 intersection set2:");
for(i=0;i<m;i++)
{

```

```

    C[i]=A[i]&B[i];
    printf("%d ",C[i]);
}
break;
case 3:printf("\nEnter cardinality of first set: ");
scanf("%d",&m);
printf("\nEnter cardinality of second set: ");
scanf("%d",&n);
if(m!=n)
{
printf("\nCannot perform difference!");
break;
}
printf("\nEnter elements of first set:(0/1) ");
for(i=0;i<m;i++)
{
scanf("%d",&A[i]);
}
printf("\nEnter elements of second set:(0/1) ");
for(i=0;i<n;i++)
{
scanf("%d",&B[i]);
}
for(i=0;i<n;i++)
{
if(A[i]==0)
C[i]=0;
else
{
if(B[i]==1)
C[i]=0;

```

```
    else
    C[i]=1;
    }
}
printf("\nElements of set1 - set2: ");
for(i=0;i<m;i++)
{
    printf("%d ",C[i]);
}
break;
case 4:printf("\nProgram exit successfully!");
    exit(0);
    break;
default:printf("\nInvalid choice!");
};
}while(1);

}
```

# Output

```
Input choice to perform:
1.Union 2.Intersection 3.Difference 4.Exit
Choice: 1
```

```
Enter cardinality of first set: 3
```

```
Enter cardinality of second set: 3
```

```
Enter elements of first set:(0/1) 1
0
1
```

```
Enter elements of second set:(0/1) 0
1
0
```

```
Elements of set1 union set2: 1 1 1
Input choice to perform:
1.Union 2.Intersection 3.Difference 4.Exit
Choice: 2
```

```
Enter cardinality of first set: 3
```

```
Enter cardinality of second set: 3
```

```
Enter elements of first set:(0/1) 1
0
1
```

```
Enter elements of second set:(0/1) 0
1
1
```

```
Elements of set1 intersection set2:0 0 1
Input choice to perform:
1.Union 2.Intersection 3.Difference 4.Exit
Choice: 3
```

```
Enter cardinality of first set: 3
```

```
Enter cardinality of second set: 3
```

```
Enter elements of first set:(0/1) 0
1
0
```

```
Enter elements of second set:(0/1) 1
0
1
```

```
Elements of set1 - set2: 0 1 0
```