

Green Score – algorithms, sources, and an audit

FROM Engineering **DATE** 2026-07-25

SUBJECT
What the Green Score computes, where every number comes from, and what the latest review changed

Summary

This sets out the Green Score end to end: the algorithm, where every constant comes from, and what the model actually produces. Section 8 lists every source with a resolvable link.

Writing it prompted a proper review of the constants, which was overdue. That turned up **five** that were uncited, self-referential, or not scientifically supportable – all now corrected and sourced (§4). I also added a validation harness that scores model output against published measurements on every run, so the model can't drift quietly again. It currently passes **8 of 8** checks, up from 4 of 10.

One correction ran opposite to expectation and is worth reading first. The headline heat figure looked roughly eight times too high against published Kolkata values, and I initially recorded it as our most serious defect. It turned out to be **mislabelled rather than miscalibrated** – the number is defensible, the name we gave it wasn't (§4.1).

Section 6 sets out what I still don't trust, without hedging.

1. What the Green Score computes

A 0-100 number, the equal-weighted mean of three sub-scores:

$$\text{GREEN SCORE} = 100 \times [\text{GREENING RATIO} + \text{COOLING ACHIEVED} + \text{BUDGET EFFICIENCY}] \div 3$$

Each sub-score is capped at 1.0, so the total cannot be bought with spending. **All three are displayed raw in the tool** alongside the total, so the composite is auditable – you can see which component produced the number rather than taking it on trust. Berlin's BAF and the Seattle Green Factor both publish their components for the same reason.

Greening ratio

A **weighted-area ratio** – the same structure used by every established green-space planning standard: Berlin's **Biotope Area Factor** (mandatory since 1994), the **Seattle Green Factor**, and Singapore's **Green Plot Ratio**. All compute *sum of (area × ecological weight) ÷ total area*.

SURFACE	WEIGHT	BASIS
In-ground vegetation	1.0	Berlin BAF “vegetation connected to soil”
Tree canopy over street	0.6	Berlin / Seattle canopy bands
Green facade	0.6	Berlin wall greening 0.5; Seattle up to 0.7
Water / wetland	0.8	Berlin water surface
Cool roof	0.1	Our own low weight – a painted roof is not habitat
Sealed surface	0.0	All three standards

Normalised against **0.45**, the midpoint of Berlin’s 0.30–0.60 target band.

Cooling achieved

Modelled surface-temperature drop versus the no-intervention baseline, normalised against 2.5 °C.

Budget efficiency

Degrees cooled per ₹ crore, normalised against 0.15 °C/crore.

2. Where every number comes from

Measured = from data · **Cited** = traceable to a named source · **Tool-relative** = normalised against our own output · **Placeholder** = explicitly temporary.

Costs

ITEM	VALUE	GRADE	SOURCE
Cool roof	₹150/m²	Cited – high	Telangana Cool Roof Policy 2023-28; NRDC India
Street tree	₹1,500/tree	Cited – med-high	Municipal planting + 3-yr maintenance
Pocket park	₹1.5 crore/ha	Cited – medium	Gujarat AMRUT 2.0 (2 named projects)
Green facade	₹9,500/m²	Cited – medium	Indian vendor pricing; excludes irrigation opex
Wetland	<i>no figure exists</i>	Open	See §6

Physical coefficients

ITEM	VALUE	GRADE	SOURCE
Dark roof albedo	0.15	Cited – high	LBNL Heat Island Group
Aged cool-roof albedo	0.60	Cited – high	LBNL <i>aged</i> value, not fresh-white 0.85 – deliberately conservative
Pocket park radius	50 m (0.785 ha)	Cited – Kolkata-specific	Mitra et al. 2022, threshold value of efficiency
Evapotranspiration L	0.43	Derived – see §4.2	Solved against two independent constraints
Facade heat reduction	0.03	Cited – corrected from 0.30	Gunawardena & Steemers 2023
Influence kernel λ	≈ 47 m	Empirical, honestly labelled	See §4.4
Warming pathways	+1.25 / +4.1 °C	Cited – corrected	Dhara et al. 2025, PLOS Climate

Score parameters

ITEM	VALUE	GRADE
Weights	equal thirds	Corrected from 40/40/20 – see §4.5
Greening reference	0.45	Cited, but transplanted (see §6)
Cooling reference	2.5 °C	Cited-ish
Efficiency reference	0.15 °C/cr	Tool-relative – labelled, not fixed

Input geometry – genuinely measured

Microsoft ML Building Footprints (ODbL) · Google Open Buildings 2.5D heights (CC BY 4.0) · OpenStreetMap road centrelines (ODbL) · Norwegian Meteorological Institute live air temperature · NASA ECOSTRESS night surface temperature (public domain, added this week)

3. What the model produces

SCENARIO	COOLING	COST	SCORE
Nothing	0.00 °C	₹0	2
Cool roofs 100%	2.25 °C	₹7.5 cr	69
Tree corridors max	2.01 °C	₹66 lakh	84
Green facades max	0.14 °C	₹190 cr	4
Everything	4.45 °C	₹203 cr	66

Trees score highest, and facades now score almost nothing. Both are consequences of the corrections, not of design. Cool roofs cost **₹3.3 crore per °C**; facades cost **₹1,382 crore per °C**. That ordering matches Indian Heat Action Plan practice, where cool roofs lead – and it emerges from cited costs rather than being put there.

Doing everything scores lower than trees alone (66 vs 84). Deliberate: the cooling term caps at 2.5 °C, so extra cooling earns nothing while cost destroys the efficiency term. It rewards cost-effectiveness. It is counterintuitive enough that the interface should explain it, and currently doesn't.

4. The audit – five corrections

4.1 The heat figure was mislabelled, not miscalibrated

The tool displayed “**UHI Δ vs rural: +11 °C**”. Published surface UHI for Kolkata is **0.85–1.5 °C** (Nayak 2023, Jain 2023, Siddiqui 2021). That looks like an eight-fold overstatement, and I initially wrote it up as our most serious defect.

It isn't. Voogt & Oke (2003), the canonical reference, put clear-sky **daytime surface** UHI at **10–15 °C**, while canopy-layer **air** UHI is 2–5 °C. The published Kolkata figures are 1 km MODIS, season-averaged, measured against a real rural population. Ours is clear-sky midday at 7 m against a synthetic all-vegetation cell. **Three different quantities.**

The number is defensible. The label was not: “UHI” and “rural” are both load-bearing terms we had no claim to.

Fixed: renamed to “**Δ vs all-green ref**”, with the reference stated in the tooltip and an explicit note that measured Kolkata SUHII is a different quantity.

I'm flagging this prominently because it is the error I would most want caught in my own work: I compared two numbers that shared a name and not a definition.

4.2 Evapotranspiration was over-strong – now derived, not tuned

The ET coefficient was 0.50, which put a fully-vegetated surface **5.8 K below air temperature** – more cooling than evapotranspiration can physically deliver.

Rather than pick a nicer number, I solved for the value satisfying **two independent published constraints at once**:

- park cool-island intensity of **4.83–8.07 °C** (Mitra et al. 2022, measured in Kolkata)
- vegetated surface no more than **4 K below air** (physical ceiling on ET)

They intersect at **0.40–0.46**. The value is now **0.43**, the midpoint. Both constraints now pass.

4.3 Green facades were overstated roughly tenfold

The facade heat-reduction coefficient was **0.30** with no source. The only neighbourhood-scale measurement I could find – Gunawardena & Steemers 2023, *Buildings & Cities* – reports green facades moving heat-island intensity **1.86 K → 1.81 K, about 3%**, and cutting space-conditioning energy 2.1%. The dramatic –13 to –20 °C figures in circulation are **local wall-surface** effects; the same authors found the vapour flux “advects away to background levels”.

Fixed: coefficient **0.30 → 0.03**, cited. I also **deleted** the facade ground-vegetation term entirely – its factor of 0.15 had no measurement support, and crediting a wall treatment with ground vegetation was double-counting.

Consequence: facades went from an apparently competitive lever (1.90 °C) to a marginal one (0.14 °C). That is what the literature says they are.

4.4 A physical constant was tuned for appearance – now honestly named

The diffusion constant controlling how far cooling spreads was selected because it produced a **legible map**, not because a measurement supported it. Our own documentation recorded this openly, which I credit, but a visual criterion had chosen a physical parameter.

It turns out the deeper problem is that it was never diffusivity at all: **lateral heat conduction between 7.3 m cells is roughly eight orders of magnitude too small to matter** (soil diurnal damping depth ≈ 0.12 m). Real horizontal coupling comes from wind-driven advection, which this model does not represent.

Fixed: relabelled throughout as an **empirical spatial-influence kernel**, with the physics stated plainly. The value is unchanged – deliberately short, because our field is surface temperature, which real thermal imagery shows as sharp. The 120–300 m park-cooling distances in the literature are an air-temperature phenomenon.

4.5 Two pathway figures were scientifically indefensible

The projection slider offered **–1.2 °C (“target 2030”)** and **+2.4 °C (“BAU 2040”)**, both uncited.

No emissions scenario produces regional cooling over India. Even the most aggressive mitigation pathway has India warming through mid-century because of committed warming. A “target” showing Kolkata 1.2 °C *cooler* than today is a mitigation aspiration drawn on a physical-temperature axis, and it reads as a forecast.

Fixed: the negative pathway is **deleted**. The remaining two are cited to Dhara et al. 2025, *PLOS Climate* (post-AR6 India update): **SSP2-4.5 +1.25 °C** (2041–2060) and **SSP5-8.5 +4.1 °C**.

Also corrected: the score weights

The 40/40/20 split had **no published precedent** and implied greening and cooling were each exactly twice as important as cost. Equal weighting is the most commonly applied approach in composite-indicator practice (OECD/JRC 2008) and the convention in urban-resilience indices. **Now equal thirds**, cited. An arbitrary split dressed as a derived one is worse than a plain one.

5. The validation harness

SCRIPTS/VALIDATE-MODEL.MJS scores model output against cited benchmarks on every run.

CHECK	VALUE	EXPECTED	
Land-cover thermal contrast	10.35 °C	8–18 °C	ok
Max ward cooling ≤ local park cooling	4.45 °C	≤ 5.42 °C	ok
Local park cooling	5.42 °C	4.83–8.07 °C	ok
Vegetated surface below air	3.52 K	≤ 4 K	ok
Built surface above air	12.17 K	5–25 K	ok
Facade vs cool-roof cost per m²	63×	40–80×	ok
Score at zero intervention	2	0–10	ok
Score at full intervention	66	0–100	ok

8 of 8, from 4 of 10 before the audit.

One methodological note you should interrogate. Three checks were demoted from pass/fail to informational. Before doing that I tested whether they were real defects, and all three borrowed **air-temperature** benchmarks for a model computing **surface** temperature. The clearest evidence: WRI India’s figures for the *same* street trees are **–0.3 °C air** and **–27.5 °C road surface** – a 90× gap. No published ward-mean *surface* benchmark exists, so max cooling is now bounded by a physically necessary rule instead (a field’s mean cannot shift further than its largest local change). “My benchmark was wrong” is what motivated reasoning sounds like, so the reasoning is written into the code for you to check.

6. What I still don't trust

- **Nothing has been validated against measurement for our own wards.** Every check is against published literature. We now have NASA ECOSTRESS night surface temperature over all three wards, and comparing model to measurement is the obvious next step. It has not been done.
- **The greening benchmark is transplanted.** Berlin's 0.30–0.60 band applies to *individual development sites in a temperate European city*. We apply it to *whole wards in tropical Kolkata*. Convenient, not validated.
- **Efficiency is still tool-relative.** No published cost-per-degree-cooled benchmark exists, so a ward can only score well relative to what our own model produces. Now labelled as such rather than presented as grounded.
- **No Indian wetland cost figure exists.** Government schemes fund *management*, not per-hectare creation. Also worth knowing: East Kolkata Wetlands sit under the 2006 Conservation Act, which prohibits conversion – so a “create wetland” lever may be modelling a legally impossible action. The lever is currently retired from the interface.
- **Several citations were verified from abstracts only.** Re-verification before any client deliverable has not happened.
- **A licensing question for you:** our building footprints are ODbL, which carries share-alike obligations for derived *databases*. Rendered maps are almost certainly fine; the derived data files we ship may not be. Worth a proper answer before anything paid.

7. Open decision

Whether the Green Score should retain the **cooling term** before the physics is validated against our own measurements.

A score built only on the greening ratio and cost would be narrower but fully defensible today – both rest on published standards and cited Indian unit costs. Including modelled cooling makes the score more useful and less certain, and it is currently two of the three components (cooling directly, plus efficiency, which is cooling divided by cost).

This is a judgement about what the firm is willing to stand behind rather than a technical question, so it sits with the partners rather than with engineering.

8. Sources

Verification status is marked per item: **[V]** full text or primary document consulted · **[A]** abstract or catalogue record only, not yet fully verified.

Scoring standards and index methodology

SOURCE	USED FOR	LINK
Berlin Biotopo Area Factor (Senate Dept. for Urban Development) [V]	Greening weights; 0.30–0.60 target band	berlin.de/sen/uvk/en/nature-and-green/landscape-planning/baf-biotopo-area-factor
Seattle Green Factor (SDCI) [V]	Cross-check on surface weights	seattle.gov/sdci/codes/codes-we-enforce-(a-z)/seattle-green-factor
Singapore Green Plot Ratio (URA LUSH) [A]	Third comparator on the weighted-area form	ura.gov.sg/Corporate/Guidelines/Development-Control/Non-Residential/EI/Greenery
OECD/JRC (2008), <i>Handbook on Constructing Composite Indicators</i> [V]	Equal weighting; sensitivity-analysis requirement	doi:10.1787/9789264043466-en

Physics, cooling evidence, and the surface-vs-air distinction

SOURCE	USED FOR	LINK
Voogt & Oke (2003), <i>Thermal remote sensing of urban climates</i> , RSE 86(3):370–384 [V]	\$4.1 – daytime <i>surface</i> UHI 10–15 °C vs canopy <i>air</i> UHI 2–5 °C	doi:10.1016/S0034-4257(03)00079-8
Mitra et al. (2022), Frontiers in Environmental Science – tropical megacities incl. Kolkata [V]	\$4.2 – park cool-island 4.83–8.07 °C; TVoE 0.77 ha; reach 420 m	doi:10.3389/fenvs.2022.1073914
Gunawardena & Steemers (2023), <i>Neighbourhood-scale vertical greening</i> , Buildings & Cities 4(1) [V]	\$4.3 – heat-island intensity 1.86→1.81 K (~3%); energy 2.1–5.2%	doi:10.5334/bc.282
LBNL Heat Island Group – cool roof materials [V]	Albedo 0.15 dark / 0.60 aged-cool	heatisland.lbl.gov/coolscience/cool-roofs
WRI India , <i>Urban Trees' Cooling Potential</i> [V]	Canopy dose-response; the –0.3 °C air vs –27.5 °C surface contrast in \$5	wri.org/insights/urban-trees-cooling-potential

Climate projections

SOURCE	USED FOR	LINK
Dhara, Deshpande, Roxy, Dalpadado & Shrestha (2025), PLOS Climate 4(11):e0000724 [V]	\$4.5 – SSP2-4.5 +1.25 °C (2041–60); SSP5-8.5 +4.1 °C	doi:10.1371/journal.pclm.0000724
Ministry of Earth Sciences (2020), <i>Assessment of Climate Change over the Indian Region</i> [A]	Cross-check: RCP4.5 +2.41 ± 0.40 °C by 2066–95	link.springer.com/book/10.1007/978-981-15-4327-2

Urban heat island benchmarks (used to sanity-check, not to calibrate)

SOURCE	KOLKATA / INDIA VALUE	LINK
Nayak, Vinod & Prasad (2023), Applied Sciences 13(24):13323 [A]	Kolkata night SUHII 0.85 °C annual	doi:10.3390/app132413323
Jain (2023), Frontiers in Sustainable Cities 5:1084573 [A]	Kolkata night 1.3–1.5 °C (DJF)	doi:10.3389/frsc.2023.1084573
Siddiqui et al. (2021), Sustainable Cities and Society 75:103374 [A]	Indian metros night 1.34–2.07 °C	doi:10.1016/j.scs.2021.103374
Peng et al. (2012), Environmental Science & Technology 46(2):696–703 [A]	Global 1.5 °C day / 1.1 °C night; equal-area rural reference method	doi:10.1021/es2030438
Chakraborty & Lee (2019), Int. J. Applied Earth Obs. & Geoinformation 74:269–280 [A]	Global 0.85 day / 0.55 night; water-masking rationale	doi:10.1016/j.jag.2018.09.015
Shastri et al. (2017), Scientific Reports 7:40178 [V]	Indian daytime <i>cool</i> /island in pre-monsoon – why Kolkata needs explaining	doi:10.1038/srep40178
Kumar et al. (2017), Scientific Reports 7:14054 [A]	60% of 89 Indian urban areas show a daytime cool island	doi:10.1038/s41598-017-14213-2

Cost sources (all Indian)

SOURCE	USED FOR	LINK
Telangana Cool Roof Policy 2023–2028 [V]	₹150/m ² cool roof; indoor –2.1 to –4.3 °C	telangana.gov.in (policy PDF)
NRDC , <i>Keeping It Cool: How India Can Protect Its People with Cool Roofs</i> [V]	Ahmedabad lime-wash rate; surface up to –30 °C	nrdc.org/resources/keeping-it-cool-how-india-can-protect-its-people-cool-roofs
Gujarat AMRUT 2.0 urban gardens (2026) [A]	₹1.5 crore/ha park capex, from two named projects	Press release; see HEAT-MAP-INTERVENTION-MODEL.MD §9
PreventionWeb / NRDC – Ahmedabad Heat Action Plan [A]	>1,100 deaths avoided/yr; –27% mortality on hottest days	preventionweb.net

Input data and licences

DATASET	LICENCE	LINK
Microsoft ML Building Footprints	ODbL – share-alike, see §6	github.com/microsoft/GlobalMLBuildingFootprints
Google Open Buildings 2.5D	CC BY 4.0	sites.research.google/open-buildings
OpenStreetMap road centrelines	ODbL	openstreetmap.org/copyright
Norwegian Meteorological Institute (live air temp)	Free, keyless	api.met.no
NASA ECOSTRESS L2T LSTE v002	US public domain	doi:10.5067/ECOSTRESS/ECO_L2T_LSTE.002
ESA WorldCover 10 m v200	CC BY 4.0	doi:10.5281/zenodo.7254221
JRC GHS-SMOD R2023A (Degree of Urbanisation)	CC BY 4.0	doi:10.2905/A0DF7A6F-49DE-46EA-9BDE-563437A6E2BA

Attribution strings required by licence are recorded in **DOCS/HEAT-MAP-INTERVENTION-MODEL.MD** and rendered on the tool itself.

Full formulas and every constant: **DOCS/HEAT-MAP-INTERVENTION-MODEL.MD** Validation harness: **SCRIPTS/VALIDATE-MODEL.MJS**

This document leads with limitations rather than capabilities by design. Anything that reads as understated should be queried – better to over-disclose internally than to have a municipal client discover it first.