Language Models for Analysing Social Media Discourse: Resources and Applications

Thesis submitted in accordance with the requirements of Cardiff University for the degree of Doctor in Philosophy by

Dimosthenis Antypas

August 2025

Acronyms

AI	Artificial Intelligence
API	Application Programming Interface
BERT	Bidirectional Encoder Representations from Transformers
RoBERTa	Robustly Optimized BERT Pretraining Approach
ELMo	Embeddings from Language Models
BoW	Bag of Words
ICL	in-context learning
LDA	Latent Dirichlet Allocation
LLM	Large Language Model
LM	Language Model
MLM	Masked Language Model

PLM	Pre-trained Language Model
ML	Machine Learning
NLP	Natural Language Processing
SoTA	State of The Art
SVM	Support Vector Machine
LSTM	Long Short-Term Memory
RNN	Recurrent Neural Network
GRU	Gated Recurrent Unit
URL	Uniform Resource Locator
MTLD	Measure of Textual Lexical Diversity
GloVe	Global Vectors for Word Representation
T5	Text-to-Text Transfer Transformer
BART	Bidirectional and Auto-Regressive Transformers
Flan-T5	Fine-tuned Language Net T5
C4	Colossal Clean Crawled Corpus
QLoRA	Quantized Low-Rank Adaptation
NER	Named Entity Recognition
LLaMA	Large Language Model Meta AI

1 Background

This chapter provides the theoretical and methodological foundation of the thesis, covering the evolution of Natural Language Processing (NLP) tools and their applications to social media data. It explores the challenges of processing noisy, heterogeneous text from platforms like Twitter and discusses existing work on key areas such as hate speech detection, misinformation analysis, and multilingual topic classification. By situating the thesis within the broader research landscape, this chapter demonstrates how the presented contributions advance the state of the art.

1.1 Language Models

Language Models (LMs) are fundamental to NLP, aiming to capture the statistical properties of language and predict the probability of a sequence of words. Their evolution has significantly impacted the capabilities of NLP systems, especially in handling complex human language.

1.1.1 Traditional Language Models

1.1.1.1 Early Language Models

Early LMs were often based on statistical methods, such as N-gram models, which predict the next word based on the previous N-1 words (Buck et al., 2014). These models, while foundational, suffered from limitations in capturing long-range dependencies and semantic meaning. To represent words, early systems frequently relied on static word embeddings such as Word2Vec (Mikolov et al., 2013) and Global Vectors for Word Representation (GloVe) (Pennington et al., 2014), where each word was mapped to a single, fixed vector regardless of context. While these representations improved over one-hot encodings by capturing some semantic similarity (e.g., "king" and "queen" being close in vector space), they failed to reflect how a word's meaning could shift depending on its usage in different contexts.

These limitations were overcomed, up to a degree, through the development of neural approaches capable of modeling sequential dependencies and context more effectively. Specifically, Recurrent Neural Networks (RNNs) and their variants, such as Long Short-Term Memory (LSTMs) and Gated Recurrent Units (GRUs), introduced a new class of language models capable of processing word sequences while maintaining a dynamic internal state (Yu et al., 2019; Dey and Salem, 2017). These models improved the contextual understanding of language over static embeddings by updating representations as each token in a sequence was processed. However, they still faced challenges in handling long-term dependencies and lacked efficient parallelization during training, which restricted scalability and performance

on large datasets (Sherstinsky, 2020).

1.1.1.2 Masked Language Models

Masked Language Models (MLMs) emerged with the introduction of the Transformer architecture (Subakan et al., 2021). Unlike traditional LMs that predict the next word, MLMs are trained by masking a percentage of the tokens in the input and then predicting those masked tokens based on the context provided by the unmasked tokens as seen in Figure 1.1 (Devlin et al., 2019). This bidirectional training allows them to learn richer, contextualized representations of words. These models are typically pretrained on massive corpora such as Wikipedia and the Common Crawl[1], enabling them to learn robust language representations.

For example, the embedding for the word bank in "he sat by the river bank" will differ significantly from that in "she went to the bank to deposit money," because the surrounding context informs the model about the intended sense of the word. This is in stark contrast to earlier approaches like Word2Vec or GloVe, which assign the same vector to bank regardless of its meaning in different contexts. These contextual embeddings allow MLMs to capture intricate semantic and syntactic relationships, making them highly effective across a wide range of downstream tasks.

Most contemporary MLMs are based on the BERT architecture, which is an encoder-based model leveraging bidirectional self-attention mechanisms to capture contextual information from both the left and right of each token (Devlin et al., 2019). Extensions to BERT include Robustly Optimized BERT Pretraining

[1] https://commoncrawl.org



Figure 1.1: Example of MLM objective for training in Bidirectional Encoder Representations from Transformers (BERT).

Approach (RoBERTa), which optimises the pre-training process and introduces larger datasets, longer training, and XLM-R, which extends RoBERTa to multilingual settings (Liu et al., 2019; Conneau et al., 2020).

One of the main benefits of these models is that their knowledge can be utilised in various downstream tasks with minimal modifications. Also, due to their encoder architecture which allows them to understand context from both left and right, they display significantly improved performance when fine-tuned on tasks like text classification, question answering, and named entity recognition (Yang et al., 2023).MLMs have become the backbone of many state-of-the-art NLP systems, enabling significant advancements in understanding and generating human language. They are particularly effective for tasks that require deep contextual understanding, such as sentiment analysis (Alaparthi and Mishra, 2021), hate speech detection (Mozafari et al., 2019), and misinformation detection (Kaliyar et al., 2021).

1.1.2 Encoder-Decoder Models

Encoder-decoder models represent a distinct approach in language modeling, particularly effective for sequence-to-sequence tasks. These architectures consist of two components: (i) an encoder that processes the input sequence and compresses its information into a latent representation, and (ii) a decoder that generates an output sequence based on this representation. This architecture is well-suited for tasks where the output differs in form or length from the input, such as translation, summarization, and question generation. Similar to MLMs, encoder-decoder models are also be pretrained on large corpora, while leveraging self-attention mechanisms in both the encoder and decoder stacks which allows them to learn bidirectional representations in the encoder while simultaneously training the decoder to generate sequences from noisy or incomplete inputs.

Encoder-decoder models became popular with the introduction of Text-to-Text Transfer Transformer (T5) (Raffel et al., 2020a). T5 casts NLP problems, such as summarisation, machine translation, and question asnwering, into a unified text-to-text format. It is pretrained on the Colossal Clean Crawled Corpus (C4) corpus(Raffel et al., 2020b) using a span corruption objective, where spans of text are masked and replaced with unique sentinel tokens, and the model learns to reconstruct the missing spans which enables it to develop robust representations for both understanding and generation (Figure 1.2).

An extension of T5, Fine-tuned Language Net T5 (Flan-T5) (Chung et al., 2024), further improves performance through instruction tuning (Wei et al., 2021) on a wide variety of tasks and datasets which enhances it's zero-shot and few-shot generalization capabilities. Another notable encoder-decoder model is Bidirectional



Figure 1.2: Example of T5 finetuning for a summarisation task.

and Auto-Regressive Transformers (BART) (Lewis et al., 2019), which is trained on a denoising autoencoder objectivewhere the model learns to reconstruct original text from corrupted input. BART combines the strengths of both MLMs and autoregressive models, making it effective for tasks like summarisation and translation.

Encoder-decoder models are widely used in tasks where the input and output differ significantly in structure or length, and similarly to MLMs they can be further finetuned for specific applications. Common use cases include machine translation, text summarization, question answering, and question generation. They can also be adapted for text generation tasks, producing coherent and contextually relevant text from prompts. However, these models are generally more complex and computationally intensive than MLMs, and they not always outperform encoder-only models on tasks that do not involve sequence generation (Gasparetto

et al., 2022). At the same time, they often lag behind decoder-only models, such as Large Language Models (LLMs), in open-ended text generation tasks (Saattrup Nielsen et al., 2025).

1.1.3 Large Language Models

LLMs represent the most recent advancement in language modeling, building upon the foundations laid by MLMs and encoder-decoder models. They are characterized by their massive scale, often containing hundreds of billions of parameters, and their ability to perform a wide range of tasks with remarkable performamce, often in a zero-shot or few-shot learning setting (Wang et al., 2020). Unlike traditional LMs, which are typically trained on specific tasks or datasets, LLMs are pretrained on vast and diverse datasets encompassing text, code, and other modalities like images.

Architecturally, most LLMs are based on the Transformer decoder-only design and are trained using an autoregressive objective (Brown et al., 2020a)where, given a sequence of tokens, the model learns to predict the next token in a left-to-right manner. In contrast to bidirectional models like BERT, decoder-only models do not have access to future tokens during training, which makes them suited for generative tasks such as text completion, dialogue, summarization, and code generation.

Modern LLMs are capable to perform tasks based purely on natural language instructions, making *prompt engineering* a critical aspect of their effective use (Reynolds and McDonell, 2021). Moreover, similarly to smaller LMs their performance on specific tasks can often be further improved through finetuning.

This is typically applied to smaller versions of the models using techniques like Quantized Low-Rank Adaptation (QLoRA) (Dettmers et al., 2023), which enables efficient adaptation with limited computational resources.

Several notable LLMs have significantly advanced the field of NLP. For example, OpenAI's GPT series, starting with GPT-2 (Radford et al., 2019), demonstrated the potential of large-scale unsupervised pretraining and autoregressive text generation. Its succesors, GPT-3 (Brown et al., 2020b) and GPT-4 (Achiam et al., 2023) further scaled up the model size and training data, achieving impressive performance on a wide range of tasks with few-shot and zero-shot learning capabilities.

Alongside proprietary models, several open-sourced LLMs have been introduceded. Meta's Large Language Model Meta AI (LLaMA) family (Touvron et al., 2023a,b) offers models that are computationally efficient and accessible to the research community, with versions as small as 1 billion parameters. Other prominent open-source alternatives include Mistral 7B and Mixtral (Jiang et al., 2024)—a mixture-of-experts model using sparse attention to activate only a subset of its parameters during inference—and Qwen (Bai et al., 2023), a high-performing model widely adopted in academia due to its open availability and strong benchmark results.

These models showcase that decoder-only architectures when scaled massively are able to achieve broad generalization across NLP tasks with minimal supervision.

However, despite their impressive capabilities, LLMs pose significant challenges. These include high computational costs, issues related to interpretability, and the risk of generating biased or harmful content (Ferrara, 2023; George et al., 2023).

While decoder-only LLMs excel in generative and open-ended tasks, encoder-only models, such as those based on the BERT architecture, remain highly competitive and often superior for certain structured tasks, like text classification and Named Entity Recognition (NER), where their bidirectional context is advantageous. Moreover, encoder-based models tend to be more efficient to train and deploy for such applications.

1.2 Social media platforms

Social media platforms have become central to the study of natural language in real world environments, offering vast amounts of real-time, user-generated content. These platforms differ significantly from traditional text sources such as books, news articles, or formal documents. Their informal, dynamic, and highly contextual nature presents unique opportunities and challenges for NLP research and applications (Mustofa and Saptomo, 2025). A lot of these paltforms focus on different modalities, for example, Instagram emphasises photos and videos, while others like Snapchat are inherently multimodal. In contrast, Twitter and Reddit have emerged as particularly rich sources of linguistic data and are widely used in computational social science and NLP research. This is primarily because text is the dominant medium of communication on these platforms, and they used to offer relatively easy access to data through official Application Programming Interfaces (APIs). This thesis focuses on these two platforms due to their complementary structures and modes of interaction.

Twitter is structured around short, standalone messages called "tweets," which are constrained to 280 characters. Although tweets are restricted in length, they often

convey substantial information and sentiment, enhanced by the use of hashtags, mentions, emojis, and embedded media. User interactions take the form of replies, retweets, and quote tweets, which together create loosely connected conversational threads. The character limit encourages users to be linguistically inventive, resulting in the widespread use of slang, abbreviations, and non-standard grammatical constructions.

Reddit, in contrast, is a forum-based platform organized into topic-specific communities known as *subreddits*. Posts on Reddit can be significantly longer than tweets and often initiate threaded discussions that allow for deeper, hierarchical conversations (1.3). This structure offers richer context and more coherent discourse patterns.

Although Reddit and Twitter differ in format and interaction design, they exhibit several common linguistic characteristics: both are informal, rapidly evolving, and rely on similar engagement mechanisms such as upvotes and likes. These features shape the type and tone of user-generated content, making both platforms valuable for studying opinion formation, discourse dynamics, and online social behaviour.

1.2.1 Specialised Language Models for Social Media

The direct application of LMs trained on formal or curated text corpora often fails to generalize effectively to social media data. Social media text presents a wide range of linguistic challenges for NLP due to its informal and dynamic nature. It often features slang, abbreviations (e.g., "brb", "smh"), and non-standard grammar, which deviate from conventional language norms. Posts frequently lack sufficient context, leading to ambiguity in interpretation, particularly when sarcasm or irony



Figure 1.3: An example of a Reddit thread from r/learningprogramming subreddit.

is involved. Additionally, platform-specific metadata such as emojis, hashtags, and mentions play an important role in conveying meaning and identifying topics. Multilinguality and code-switching are also common, with users often blending languages or dialects within a single post. Language on these platforms evolves rapidly, with new slang and trends emerging constantly, requiring models to adapt over time. Social media content also reflects societal biases and may include toxic or harmful language, posing ethical and technical challenges. Furthermore, the short and often noisy nature of posts—particularly on platforms like Twitter—demands robust pre-processing or tailored model architectures.

These challenges have led to the development of specialised language models that

are pre-trained or fine-tuned on large-scale social media corpora to capture the idiosyncrasies of online discourse (Nguyen et al., 2020).

These models are explicitly designed to handle the noise and variability inherent in social media. They often incorporate strategies for addressing spelling errors, abbreviations, emojis, and platform-specific syntax (e.g., hashtags, mentions, retweet markers). By learning from in-domain data, these models are better equipped to understand the linguistic norms, stylistic features, and emergent expressions characteristic of social platforms.

Popular examples of specialised language models include BERTweet (Nguyen et al., 2020), a RoBERTa-based model trained exclusively on 850M English tweets. Twitter-RoBERTa (Loureiro et al., 2022), which continues training from RoBERTa checkpoint using a large tweet corpora. Bernice (DeLucia et al., 2022) a multilingual social media model designed to handle cross-lingual and code-switched content, often observed on platforms like Twitter. And DialoGPT (Zhang et al., 2019) A conversational response generation model built by fine-tuning GPT-2 on approximately 147 million Reddit comment exchanges. In particaular for the case of Twitter we do not need large context so roberta is good too...

Training language models on domain-specific social media data significantly improves their performance on downstream tasks such as hate speech detection, stance classification, and misinformation detection ().

1.3 NLP APPLICAITONS FOR SOCIAL MEDIA

NLP tasks applied to social media data extract valuable insights from the vast amount of user-generated content.

1.3.1 Sentiment Analysis

Sentiment analysis (also known as opinion mining) aims to determine the emotional tone or overall sentiment expressed in a piece of text (e.g., positive, negative, neutral). On social media, this is crucial for understanding public opinion towards brands, products, events, or political figures.

Sentiment analysis involves classifying text according to its affective polarity—positive, negative, or neutral. Social media sentiment analysis is complicated by sarcasm, slang, and domain-specific terminology.

Approaches:

Lexicon-based: Using pre-defined dictionaries of words and their associated sentiment scores.

Machine Learning (Traditional): Training classifiers (e.g., Naive Bayes, SVM) on labeled data with features like N-grams, TF-IDF.

Deep Learning (Modern): Employing RNNs, LSTMs, and especially Transformers (e.g., BERT-based models fine-tuned for sentiment analysis) that can capture complex contextual patterns.

In this thesis we utilise heavily sentiment analysis to extract insights from social media posts mainly in Chapters **??**, **??** ,and **??**.

1.3.2 Emotion Detection

While sentiment analysis typically classifies text into broad categories (positive/negative/neutral), emotion detection aims for a more granular understanding of human emotions, identifying specific emotions like anger, joy, sadness, fear, surprise, disgust, etc. This is particularly relevant for understanding emotional responses to events or content on social media.

Beyond sentiment polarity, emotion detection aims to identify specific emotional states (e.g., anger, joy, sadness). Annotated corpora such as GoEmotions (**?**) have enabled supervised learning in this space. However, emotional nuance and subjectivity make this task challenging, especially in multilingual settings.

Challenges on Social Media:

Similar to sentiment analysis, but with the added complexity of distinguishing between finer emotional nuances.

Lack of large, diverse datasets labeled with fine-grained emotions.

Cultural and linguistic variations in emotion expression.

Approaches:

Often relies on annotated datasets (e.g., GoEmotions, EmoContext) and deep

learning models, particularly those based on Transformer architectures, which are well-suited for capturing the subtle linguistic cues associated with different emotions.

Lexicon-based methods for specific emotion words or phrases.

Chapters **??**, and **??**.

1.3.3 Topic Classification

Topic classification (or text categorization) assigns one or more predefined categories or topics to a given text. On social media, this helps in organizing vast amounts of information, identifying trending discussions, or filtering content based on specific themes.

Topic classification assigns thematic labels to texts. On social media, this task supports content moderation, trend analysis, and community profiling. Traditional approaches rely on supervised classification, while unsupervised methods like topic modeling (e.g., LDA) remain useful in low-resource contexts.

Challenges on Social Media:

Short Text: Tweets or short posts often don't provide enough information for accurate topic classification using traditional methods.

Dynamic Topics: Topics on social media can emerge and disappear quickly.

Multilingual Content: Discussing the same topic across different languages.

Approaches:

Traditional Machine Learning: Classifiers trained on features like bag-of-words or TF-IDF.

Topic Modeling: Unsupervised methods like Latent Dirichlet Allocation (LDA) or Non-negative Matrix Factorization (NMF) can discover underlying topics in a corpus. However, these often struggle with very short texts.

Deep Learning: Transformer-based models fine-tuned on labeled social media data for specific topic categories have shown superior performance.

Multilingual Topic Classification: Requires either language identification and separate models for each language, or multilingual embeddings and models capable of handling code-switched text.

Chapters ??, ??,??,

1.3.4 Hate Speech Detection

Hate speech detection is a critical application of NLP on social media, aiming to identify content that expresses hatred or encourages violence towards individuals or groups based on attributes like race, ethnicity, religion, gender, sexual orientation, etc. This is a highly sensitive and challenging task due to its subjective nature and the evolving tactics of hate speech perpetrators.

Hate speech detection involves identifying offensive, threatening, or discriminatory language. Prior work uses keyword matching, lexical features, and deep

learning-based classifiers. Recent benchmarks such as HatEval and datasets like HASOC provide resources for multilingual and cross-platform evaluation.

Challenges on Social Media:

Ambiguity and Context: Distinguishing genuine hate speech from offensive language, sarcasm, or legitimate criticism.

Evolving Language: Hate speech uses slang, coded language (dog whistles), and novel expressions to evade detection.

Imbalance in Data: Hate speech is typically a minority class, leading to skewed datasets and model bias towards the majority (non-hate speech) class.

Subjectivity of Definitions: What constitutes "hate speech" can vary across jurisdictions and cultural contexts.

Multilingualism: Hate speech manifests differently in various languages and cultures.

Approaches:

Rule-based Systems: Using keywords and pattern matching, but easily circumvented.

Machine Learning: Training classifiers on various linguistic features (n-grams, sentiment lexicons, parts-of-speech tags).

Deep Learning: Particularly effective, using CNNs, LSTMs, and Transformer models (e.g., BERT, RoBERTa fine-tuned for hate speech detection). These models

can capture complex semantic and syntactic patterns.

Multi-modal Approaches: Combining text with image or video analysis (though primarily text-focused in most research).

Weak Supervision/Semi-supervised Learning: Leveraging large amounts of unlabeled data, or noisy labels (e.g., from user reports) to augment smaller, carefully annotated datasets.

Ethical Considerations: Crucial for responsible development and deployment, including mitigating bias, ensuring transparency, and considering potential for censorship or chilling effects on free speech.

1.3.5 Misinformation & Polarisation

The spread of misinformation (unintentional falsehoods) and disinformation (intentional falsehoods) and its role in fostering polarisation on social media platforms pose significant societal challenges. NLP plays a crucial role in analyzing and combating these phenomena.

The spread of misinformation on social media contributes to public harm, especially in contexts like health communication and political discourse. Identifying false or misleading content is complicated by subtle rhetorical strategies and the rapid evolution of narratives.

Polarisation further exacerbates misinformation spread, as users form echo chambers and engage in selective exposure. Language models can help identify linguistic signals of polarisation and frame detection. However, challenges remain in

detecting emerging misinformation, handling multimodal content, and mitigating algorithmic biases.

Misinformation and Disinformation Analysis:

Detection: Identifying false or misleading content. This often involves:

Fact-checking: Verifying claims against reliable sources (challenging to automate fully).

Stance Detection: Determining if a text agrees, disagrees, discusses, or is unrelated to a given claim.

Propaganda Detection: Identifying rhetorical techniques used to manipulate public opinion.

Source Credibility: Assessing the reliability of the source of information.

Linguistic Features: Analyzing linguistic patterns (e.g., sensationalist language, emotional intensity, specific vocabulary) often associated with misinformation.

Propagation Analysis: Understanding how misinformation spreads across networks, often leveraging network science alongside NLP to analyze user interactions, sharing patterns, and community structures.

Debunking and Intervention: Developing NLP-powered systems to identify and flag misinformation, or to generate counter-narratives and provide accurate information.

Polarisation Analysis:

Echo Chambers and Filter Bubbles: NLP can identify communities with shared beliefs and analyze how information flows within and between these groups.

Opinion Dynamics: Tracking how opinions evolve over time and how they are influenced by social interactions and exposure to different narratives.

Stance and Ideology Detection: Classifying users or content based on their political or social leanings.

Linguistic Markers of Polarisation: Analyzing specific language choices (e.g., divisive rhetoric, "us vs. them" framing, emotional language) that indicate or contribute to polarization.

Disagreement and Deliberation: Studying how online discussions devolve into unproductive arguments versus constructive dialogue.

Challenges in Misinformation & Polarisation:

"Truth" Definition: The ground truth for misinformation can be ambiguous or rapidly change.

Evolving Tactics: Misinformation campaigns constantly adapt their language and dissemination strategies.

Subtlety: Misinformation can be subtle, relying on implications or omissions rather than outright falsehoods.

Emotional Resonance: Misinformation often leverages strong emotions, making it highly shareable.

Cross-platform Coordination: Campaigns often span multiple social media platforms.

Attribution: Identifying the source and intent behind misinformation is complex.

Ethical Implications: The risk of suppressing legitimate dissent or creating "thought police" when developing automated detection systems.

Approaches:

Hybrid Models: Combining NLP techniques with network analysis, computer vision (for multimodal misinformation), and knowledge graphs.

Adversarial Training: Developing models robust to subtle manipulations designed to evade detection.

Explainable AI (XAI): Making models more transparent to understand why they classify certain content as misinformation or polarizing.

Large Language Models: Their ability to reason, summarize, and understand complex contexts is being explored for tasks like fact-checking assistance and generating counter-narratives. However, LLMs can also generate convincing misinformation, highlighting the dual-use nature of the technology.

work based on misinformation is done in chapter **??** while Chapters **??** **??** focuses on polarisation in social discourse.

2 Conclusions and Future Work

2.1 Summary of Thesis

2.2 Summary of the Chapters

2.3 Future Work

Bibliography

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Shivaji Alaparthi and Manit Mishra. 2021. Bert: A sentiment analysis odyssey. *Journal of Marketing Analytics*, 9(2):118–126.

Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, Binyuan Hui, Luo Ji, Mei Li, Junyang Lin, Runji Lin, Dayiheng Liu, Gao Liu, Chengqiang Lu, Keming Lu, Jianxin Ma, Rui Men, Xingzhang Ren, Xuancheng Ren, Chuanqi Tan, Sinan Tan, Jianhong Tu, Peng Wang, Shijie Wang, Wei Wang, Shengguang Wu, Benfeng Xu, Jin Xu, An Yang, Hao Yang, Jian Yang, Shusheng Yang, Yang Yao, Bowen Yu, Hongyi Yuan, Zheng Yuan, Jianwei Zhang, Xingxuan Zhang, Yichang Zhang, Zhenru Zhang, Chang Zhou, Jingren Zhou, Xiaohuan Zhou, and Tianhang Zhu. 2023. Qwen technical report. *arXiv preprint arXiv:2309.16609*.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan,

Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020a. Language models are few-shot learners. In *Proceedings of the Annual Conference on Neural Information Processing Systems*.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020b. Language models are few-shot learners.

Christian Buck, Kenneth Heafield, and Bas Van Ooyen. 2014. N-gram counts and language models from the common crawl. In *Proceedings of the Language Resources and Evaluation Conference 2014*, pages 3579–3584.

Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, et al. 2024. Scaling instruction-finetuned language models. *Journal of Machine Learning Research*, 25(70):1–53.

Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised cross-lingual representation learning

at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8440–8451, Online. Association for Computational Linguistics.

Alexandra DeLucia, Shijie Wu, Aaron Mueller, Carlos Aguirre, Philip Resnik, and Mark Dredze. 2022. Bernice: a multilingual pre-trained encoder for twitter. In *Proceedings of the 2022 conference on empirical methods in natural language processing*, pages 6191–6205.

Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. 2023. Qlora: Efficient finetuning of quantized llms. *Advances in neural information processing systems*, 36:10088–10115.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Rahul Dey and Fathi M Salem. 2017. Gate-variants of gated recurrent unit (gru) neural networks. In *2017 IEEE 60th international midwest symposium on circuits and systems (MWSCAS)*, pages 1597–1600. IEEE.

Emilio Ferrara. 2023. Should chatgpt be biased? challenges and risks of bias in large language models. *arXiv preprint arXiv:2304.03738*.

Andrea Gasparetto, Matteo Marcuzzo, Alessandro Zangari, and Andrea Albarelli. 2022. A survey on text classification algorithms: From text to predictions. *Information*, 13(2):83.

A Shaji George, AS Hovan George, and AS Gabrio Martin. 2023. The environmental impact of ai: a case study of water consumption by chat gpt. *Partners Universal International Innovation Journal*, 1(2):97–104.

Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al. 2024. Mixtral of experts. *arXiv preprint arXiv:2401.04088*.

Rohit Kumar Kaliyar, Anurag Goswami, and Pratik Narang. 2021. Fakebert: Fake news detection in social media with a bert-based deep learning approach. *Multimedia tools and applications*, 80(8):11765–11788.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Ves Stoyanov, and Luke Zettlemoyer. 2019. Bart: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. *arXiv preprint arXiv:1910.13461*.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Daniel Loureiro, Francesco Barbieri, Leonardo Neves, Luis Espinosa Anke, and Jose Camacho-collados. 2022. TimeLMs: Diachronic language models from Twitter. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics: System Demonstrations*, pages 251–260, Dublin, Ireland. Association for Computational Linguistics.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*.

Marzieh Mozafari, Reza Farahbakhsh, and Noel Crespi. 2019. A bert-based transfer learning approach for hate speech detection in online social media. In *International conference on complex networks and their applications*, pages 928–940. Springer.

Badry Ali Mustofa and Wawan Laksito Yuly Saptomo. 2025. Use of natural language processing in social media text analysis. *Journal of Artificial Intelligence and Engineering Applications (JAIEA)*, 4(2):1235–1238.

Dat Quoc Nguyen, Thanh Vu, and Anh Tuan Nguyen. 2020. BERTweet: A pre-trained language model for English tweets. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 9–14, Online. Association for Computational Linguistics.

Jeffrey Pennington, Richard Socher, and Christopher Manning. 2014. GloVe: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1532–1543, Doha, Qatar. Association for Computational Linguistics.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2020a. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020b. Exploring the

limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67.

Laria Reynolds and Kyle McDonell. 2021. Prompt programming for large language models: Beyond the few-shot paradigm. In *Extended abstracts of the 2021 CHI conference on human factors in computing systems*, pages 1–7.

Dan Saattrup Nielsen, Kenneth Enevoldsen, and Peter Schneider-Kamp. 2025. Encoder vs decoder: Comparative analysis of encoder and decoder language models on multilingual NLU tasks. In *Proceedings of the Joint 25th Nordic Conference on Computational Linguistics and 11th Baltic Conference on Human Language Technologies (NoDaLiDa/Baltic-HLT 2025)*, pages 561–572, Tallinn, Estonia. University of Tartu Library.

Alex Sherstinsky. 2020. Fundamentals of recurrent neural network (rnn) and long short-term memory (lstm) network. *Physica D: Nonlinear Phenomena*, 404:132306.

Cem Subakan, Mirco Ravanelli, Samuele Cornell, Mirko Bronzi, and Jianyuan Zhong. 2021. Attention is all you need in speech separation. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 21–25. IEEE.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023a. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhos-

ale, et al. 2023b. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Yaqing Wang, Quanming Yao, James T Kwok, and Lionel M Ni. 2020. Generalizing from a few examples: A survey on few-shot learning. *ACM computing surveys (csur)*, 53(3):1–34.

Jason Wei, Maarten Bosma, Vincent Y Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M Dai, and Quoc V Le. 2021. Finetuned language models are zero-shot learners. *arXiv preprint arXiv:2109.01652*.

Linyi Yang, Shuibai Zhang, Libo Qin, Yafu Li, Yidong Wang, Hanmeng Liu, Jindong Wang, Xing Xie, and Yue Zhang. 2023. GLUE-X: Evaluating natural language understanding models from an out-of-distribution generalization perspective. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 12731–12750, Toronto, Canada. Association for Computational Linguistics.

Yong Yu, Xiaosheng Si, Changhua Hu, and Jianxun Zhang. 2019. A review of recurrent neural networks: Lstm cells and network architectures. *Neural computation*, 31(7):1235–1270.

Yizhe Zhang, Siqi Sun, Michel Galley, Yen-Chun Chen, Chris Brockett, Xiang Gao, Jianfeng Gao, Jingjing Liu, and Bill Dolan. 2019. Dialogpt: Large-scale generative pre-training for conversational response generation. *arXiv preprint arXiv:1911.00536*.