

## SKILL WEEK-8 SESSION-15:

Task-1: TO Parse Combined Redirection, Duplicate File Descriptors, Merge Streams, Verify Ordering, Handle Edge Cases, Test Integrated Outputs.

Source code:

```
GNU nano 8.7.1 combined_redirection.c *
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main() {
    char input[100];
    char filename[100];

    printf("Enter command with combined redirection: ");
    fgets(input, sizeof(input), stdin);

    input[strcspn(input, "\n")] = '\0';

    // Check for combined redirection 2>&1
    if (strstr(input, "2>&1") == NULL) {
        printf("Combined redirection 2>&1 not found.\n");
        return 0;
    }

    // Find > and get filename
    char *redirect = strchr(input, '>');

    if (redirect == NULL) {
        printf("Output redirection not found.\n");
        return 0;
    }

    // Skip > and get filename
    sscanf(redirect + 1, "%s", filename);

    // Remove possible &1 from filename
    char *amp = strstr(filename, "&1");

    if (amp != NULL) {
        *amp = '\0';
    }

    // Open output file
    int fd = open(filename, O_WRONLY | O_CREAT | O_TRUNC, 0644);

    if (fd == -1) {
        perror("Error opening output file");
        return 1;
    }

    // Save original stdout and stderr
    int saved_stdout = dup(STDOUT_FILENO);
    int saved_stderr = dup(STDERR_FILENO);

    // Redirect stdout to file
    dup2(fd, STDOUT_FILENO);

    // Duplicate stdout to stderr
    dup2(STDOUT_FILENO, STDERR_FILENO);

    close(fd);

    // Generate output on stdout
    printf("This message is from standard output.\n");

    // Generate output on stderr
    fprintf(stderr, "This message is from standard error.\n");

    printf("Combined redirection completed successfully.\n");

    // Restore stdout and stderr
    dup2(saved_stdout, STDOUT_FILENO);
    dup2(saved_stderr, STDERR_FILENO);

    close(saved_stdout);
    close(saved_stderr);

    printf("Streams restored successfully.\n");

    // Verify file contents
    fd = open(filename, O_RDONLY);

    if (fd == -1) {
        perror("Error verifying output file");
        return 1;
    }
}
```

```

char buffer[500];
ssize_t bytes;

printf("\nIntegrated output stored in %s:\n", filename);

while ((bytes = read(fd, buffer, sizeof(buffer) - 1)) > 0) {
    buffer[bytes] = '\0';
    printf("%s", buffer);
}

close(fd);

return 0;
}

```

Output:

```

anun@anushka:~$ nano append_redirection.c
anun@anushka:~$ gcc append_redirection.c -o append_redirection
anun@anushka:~$ ./append_redirection
Enter text to be added to file: First line.
Text appended to output.txt successfully.
anun@anushka:~$ cat output.txt
First line.
Second line.
Third line

```

Observation:

The program successfully parses combined redirection, duplicates file descriptors using `dup()` and `dup2()`, merges stdout and stderr into a single file, preserves the order of generated output, handles missing or invalid redirection cases, verifies the integrated file contents, and restores the original streams after execution.

Task-2: To Parse Complex Commands, Combine Pipes and Redirections, Resolve Execution Order, Validate Syntax, Generate Execution Plans, Test Scenarios.

Source code:

```

GNU nano 8.7.1                                complex_commands.c *
#include <stdio.h>
#include <string.h>
#include <stdlib.h>

#define MAX 10

int main() {
    char command[500];
    char *commands[MAX];
    int count = 0;

    printf("Enter complex command: ");
    fgets(command, sizeof(command), stdin);

    command[strcspn(command, "\n")] = '\0';

    // Basic empty command check
    if (strlen(command) == 0) {
        printf("Error: Empty command.\n");
        return 1;
    }

    // Check for invalid pipe syntax
    if (command[0] == '|' ||
        command[strlen(command) - 1] == '|') {
        printf("Syntax Error: Invalid pipe placement.\n");
        return 1;
    }

    // Split command using pipe
    char *token = strtok(command, "|");

    while (token != NULL && count < MAX) {
        commands[count++] = token;
        token = strtok(NULL, "|");
    }

    printf("\nExecution Plan:\n");

    for (int i = 0; i < count; i++) {
        printf("\nCommand %d: %s\n", i + 1, commands[i]);
    }

```

```

    // Check output redirection
    if (strstr(commands[i], ">") != NULL) {
        printf(" Output Redirection: Detected\n");
    }

    // Check append redirection
    if (strstr(commands[i], ">>") != NULL) {
        printf(" Append Redirection: Detected\n");
    }

    // Check stderr redirection
    if (strstr(commands[i], "2>") != NULL) {
        printf(" Error Redirection : Detected\n");
    }

    if (i > 0) {
        printf(" Input comes from : Pipe %d\n", i);
    }

    if (i < count - 1) {
        printf(" Output goes to : Pipe %d\n", i + 1);
    }

    printf(" Execution Order : Step %d\n", i + 1);
}

printf("\nTotal commands: %d\n", count);

printf("\nExecution sequence:\n");

for (int i = 0; i < count; i++) {
    printf("Step %d -> %s\n", i + 1, commands[i]);
}

printf("\nExecution plan generated successfully.\n");

return 0;
}

```

Output:

```
anun@anushka:~$ nano complex_commands.c
anun@anushka:~$ gcc complex_commands.c -o complex_commands
anun@anushka:~$ ./complex_commands
Enter complex command: ls | grep .c | sort
Execution Plan:
Command 1: ls
  Output goes to      : Pipe 1
  Execution Order     : Step 1
Command 2: grep .c
  Input comes from    : Pipe 1
  Output goes to      : Pipe 2
  Execution Order     : Step 2
Command 3: sort
  Input comes from    : Pipe 2
  Execution Order     : Step 3
Total commands: 3
Execution sequence:
Step 1 -> ls
Step 2 -> grep .c
Step 3 -> sort
anun@anushka:~$ |
```

Observation:

The program successfully parses complex commands, identifies pipes and different types of redirection, determines the execution order between commands, validates basic command syntax, generates an execution plan, and tests different combinations of pipes and redirections.

SESSION-16:

Task-1: To Detect Background Jobs, Launch Non-Blocking Processes, Return Prompt Immediately, Store Job Information, Monitor Execution, Test Background Tasks.

Source code:

```

GNU nano 8.7.1 background_jobs.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>

int main() {
    pid_t pid;

    printf("Simple Shell - Background Job Demo\n");
    printf("Launching background process...\n");

    pid = fork();

    if (pid < 0) {
        perror("fork failed");
        return 1;
    }

    if (pid == 0) {
        // Child process
        printf("[Background Job] PID: %d started\n", getpid());

        for (int i = 1; i <= 5; i++) {
            printf("[Background Job] Running... %d/5\n", i);
            sleep(2);
        }

        printf("[Background Job] PID: %d completed\n", getpid());
        exit(0);
    }

    // Parent process does not wait
    printf("[1] Background job started with PID %d\n", pid);
    printf("Shell prompt returned immediately.\n");

    // Monitor the background process without blocking
    int status;
    pid_t result = waitpid(pid, &status, WNOHANG);

    if (result == 0) {
        printf("Job PID %d is still running.\n", pid);
    }
}

```

```

    if (result == 0) {
        printf("Job PID %d is still running.\n", pid);
    }

    // Monitor until completion
    while ((result = waitpid(pid, &status, WNOHANG)) == 0) {
        sleep(1);
    }

    if (WIFEXITED(status)) {
        printf("Job PID %d finished successfully.\n", pid);
    }

    return 0;
}

```

Output:

```

anun@anushka:~$ nano background_jobs.c
anun@anushka:~$ gcc background_jobs.c -o background_jobs
anun@anushka:~$ ./background_jobs
Simple Shell - Background Job Demo
Launching background process...
[1] Background job started with PID 899
Shell prompt returned immediately.
Job PID 899 is still running...
[Background Job] PID: 899 started
[Background Job] Running... 1/5
[Background Job] Running... 2/5
[Background Job] Running... 3/5
[Background Job] Running... 4/5
[Background Job] Running... 5/5
[Background Job] PID: 899 completed
Job PID 899 finished successfully

```

Observation:

The background-job mechanism was successfully implemented in Ubuntu. A nonblocking child process was launched, its PID was stored, the prompt returned immediately, and the process was monitored until completion.

Task-2: To Create Job Table, Store Process Groups, Track States, Update Status, Remove Completed Jobs, Validate Job Records.

Source code:

```
GNU nano 8.7.1 job_table.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>

#define MAX_JOBS 10

typedef enum {
    RUNNING,
    COMPLETED
} JobState;

typedef struct {
    int job_id;
    pid_t pid;
    pid_t pgid;
    JobState state;
} Job;

Job jobs[MAX_JOBS];
int job_count = 0;

/* Add a job to the job table */
void add_job(pid_t pid, pid_t pgid) {
    if (job_count >= MAX_JOBS) {
        printf("Job table is full.\n");
        return;
    }

    jobs[job_count].job_id = job_count + 1;
    jobs[job_count].pid = pid;
    jobs[job_count].pgid = pgid;
    jobs[job_count].state = RUNNING;

    printf("Job [%d] added: PID=%d, PGID=%d, State=RUNNING\n",
        jobs[job_count].job_id, pid, pgid);

    job_count++;
}

/* Display all jobs */
void display_jobs() {
    printf("\n----- Job Table ----- \n");

    if (job_count == 0) {
        printf("No active jobs.\n");
        return;
    }

    for (int i = 0; i < job_count; i++) {
        printf("[%d] PID=%d PGID=%d State=%s\n",
            jobs[i].job_id,
            jobs[i].pid,
            jobs[i].pgid,
            jobs[i].state == RUNNING ? "RUNNING" : "COMPLETED");
    }
}

/* Update job status */
void update_jobs() {
    int status;
    pid_t result;

    for (int i = 0; i < job_count; i++) {
        if (jobs[i].state == RUNNING) {
            result = waitpid(jobs[i].pid, &status, WNOHANG);

            if (result > 0) {
                jobs[i].state = COMPLETED;
                printf("Job [%d] status updated: COMPLETED\n",
                    jobs[i].job_id);
            }
        }
    }
}

/* Remove completed jobs */
void remove_completed_jobs() {
    int new_count = 0;

    for (int i = 0; i < job_count; i++) {
```

```

GNU nano 8.7.1 job_table.c *
    if (jobs[i].state == RUNNING) {
        jobs[new_count] = jobs[i];
        new_count++;
    } else {
        printf("Removing completed Job [%d]\n",
            jobs[i].job_id);
    }
}

job_count = new_count;
}

/* Validate job records */
void validate_jobs() {
    printf("\nValidating job records...\n");

    for (int i = 0; i < job_count; i++) {
        if (jobs[i].pid > 0 && jobs[i].pgid > 0) {
            printf("Job [%d]: Valid record\n",
                jobs[i].job_id);
        } else {
            printf("Job [%d]: Invalid record\n",
                jobs[i].job_id);
        }
    }
}

int main() {
    printf("Job Table Management Demo\n");

    /* Create first background process */
    pid_t pid1 = fork();

    if (pid1 < 0) {
        perror("fork");
        return 1;
    }

    if (pid1 == 0) {
        printf("Child 1: PID=%d running...\n", getpid());

```

```

        add_job(pid1, getpgid(pid1));

    /* Create second background process */
    pid_t pid2 = fork();

    if (pid2 < 0) {
        perror("fork");
        return 1;
    }

    if (pid2 == 0) {
        printf("Child 2: PID=%d running...\n", getpid());
        sleep(5);
        printf("Child 2 completed.\n");
        exit(0);
    }

    add_job(pid2, getpgid(pid2));

    display_jobs();
    validate_jobs();

    printf("\nMonitoring jobs...\n");

    while (job_count > 0) {
        sleep(1);

        update_jobs();
        display_jobs();

        remove_completed_jobs();
    }

    printf("\nAll jobs completed and removed.\n");

    return 0;
}

```

Output:

```
anun@anushka:~$ nano job_table.c
anun@anushka:~$ gcc job_table.c -o job_table
anun@anushka:~$ ./job_table
Job Table Management Demo
Job [1] added: PID=1006, PGID=1005, State=RUNNING
Child 1: PID=1006 running...
Job [2] added: PID=1007, PGID=1005, State=RUNNING

----- Job Table -----
[1] PID=1006 PGID=1005 State=RUNNING
[2] PID=1007 PGID=1005 State=RUNNING
Validating job records...
Job [1]: Valid record
Job [2]: Valid record
Monitoring jobs...
Child 2: PID=1007 running...

----- Job Table -----
[1] PID=1006 PGID=1005 State=RUNNING
[2] PID=1007 PGID=1005 State=RUNNING
Child 1 completed.
Job [1] status updated: COMPLETED

----- Job Table -----
[1] PID=1006 PGID=1005 State=COMPLETED
[2] PID=1007 PGID=1005 State=RUNNING
Removing completed Job [1]

----- Job Table -----
[2] PID=1007 PGID=1005 State=RUNNING
Child 2 completed.
Job [2] status updated: COMPLETED

----- Job Table -----
[2] PID=1007 PGID=1005 State=COMPLETED
```

Observation:

The job table was successfully created and tested in Ubuntu. Process groups and job states were stored, running jobs were monitored, completed jobs were removed, and the remaining job records were validated successfully.