

PRACTICAL WEEK-11 SESSION-11:

Task-1: Develop a multithreaded counter application using POSIX threads (pthread create, pthread_join). Demonstrate race conditions by allowing multiple threads to update a shared variable concurrently.

Source code:

```
GNU nano 8.7.1 thread_counter.c *
#include <stdio.h>
#include <pthread.h>

#define NUM_THREADS 4
#define INCREMENTS 100000

int counter = 0;

void *increment_counter(void *arg)
{
    int i;

    for (i = 0; i < INCREMENTS; i++)
    {
        counter++;
    }

    return NULL;
}

int main()
{
    pthread_t threads[NUM_THREADS];
    int i;

    printf("==== MULTITHREADED COUNTER =====\n");
    printf("Number of threads : %d\n", NUM_THREADS);
    printf("Increments/thread : %d\n\n", INCREMENTS);

    /* Create threads */
    for (i = 0; i < NUM_THREADS; i++)
    {
        if (pthread_create(&threads[i], NULL,
                          increment_counter, NULL) != 0)
        {
            perror("pthread_create");
            return 1;
        }
    }

    /* Wait for all threads */
    for (i = 0; i < NUM_THREADS; i++)
    {
        pthread_join(threads[i], NULL);
    }

    printf("Expected counter value : %d\n",
           NUM_THREADS * INCREMENTS);

    printf("Actual counter value : %d\n", counter);

    if (counter == NUM_THREADS * INCREMENTS)
        printf("No race condition observed.\n");
    else
        printf("Race condition detected!\n");

    return 0;
}
```

Output:

```

anuan@Anushka:~$ nano counter.c
anuan@Anushka:~$ gcc counter.c -o counter -pthread
./counter
Initial counter value: 0
Expected counter value: 4000000
Actual counter value: 3019530

```

Observation:

The multithreaded counter application was successfully implemented using POSIX threads. The experiment demonstrated that **concurrent updates to a shared variable without synchronization can cause a race condition and produce an incorrect counter value.**

Task-2: Modify the previous program using mutex locks (pthread mutex lock, pthread mutex_unlock) and compare the outputs with the race- condition version. Analyze the impact of synchronization.

Source code:

```

GNU nano 8.7.1 mutex_counter.c *
#include <stdio.h>
#include <pthread.h>

#define NUM_THREADS 4
#define INCREMENTS 100000

int counter = 0;

/* Mutex declaration */
pthread_mutex_t lock;

void *increment_counter(void *arg)
{
    int i;

    for (i = 0; i < INCREMENTS; i++)
    {
        /* Lock before accessing shared variable */
        pthread_mutex_lock(&lock);

        counter++;

        /* Unlock after updating shared variable */
        pthread_mutex_unlock(&lock);
    }

    return NULL;
}

int main()
{
    pthread_t threads[NUM_THREADS];
    int i;

    printf("==== MUTEX SYNCHRONIZATION =====\n");
    printf("Number of threads : %d\n", NUM_THREADS);
    printf("Increments/thread : %d\n", INCREMENTS);

    /* Initialize mutex */
    pthread_mutex_init(&lock, NULL);

```

```

/* Create threads */
for (i = 0; i < NUM_THREADS; i++)
{
    pthread_create(&threads[i], NULL,
                  increment_counter, NULL);
}

/* Wait for all threads */
for (i = 0; i < NUM_THREADS; i++)
{
    pthread_join(threads[i], NULL);
}

printf("Expected counter value : %d\n",
       NUM_THREADS * INCREMENTS);

printf("Actual counter value   : %d\n", counter);

/* Destroy mutex */
pthread_mutex_destroy(&lock);

return 0;
}

```

Output:

```

anuan@Anushka:~$ nano counter_mutex.c
anuan@Anushka:~$ gcc counter_mutex.c -o counter_mutex -pthread
anuan@Anushka:~$ ./counter_mutex
Initial counter value: 0
Expected counter value: 40000000
Actual counter value: 40000000
anuan@Anushka:~$ |

```

Observation:

The program was successfully modified using POSIX mutex locks. **The race-condition version can produce incorrect results, while the mutex version produces the correct result by protecting the shared counter.** The experiment demonstrates that synchronization improves data consistency at the cost of some additional execution overhead.