

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: **CHEMLOK 218**
Product Use/Class: **Adhesive**

LORD Corporation
111 LORD Drive
Cary, NC 27511-7923 USA

Telephone: 814 868-3180
Non-Transportation Emergency: 814 763-2345
Chemtrec 24 Hr Transportation Emergency No.
800 424-9300 (Outside Continental U.S. 703 527-3887)

EFFECTIVE DATE: 05/05/2017

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Flammable liquids Category 2
Acute toxicity Inhalation - Dust and Mist Category 4 - 21.1% of the mixture consists of ingredient(s) of unknown toxicity.
Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Skin sensitization Category 1
Germ cell mutagenicity Category 2
Carcinogenicity Category 1A
Reproductive toxicity Category 1A
Specific target organ systemic toxicity (single exposure) Category 3
Specific target organ systemic toxicity (single exposure) Category 1 Central nervous system, Cardio-vascular system, Respiratory system, Kidney, Nervous system, Body, Systemic toxicity
Specific target organ systemic toxicity (repeated exposure) Category 1 Central nervous system, Kidney, Hematopoietic System, Cardio-vascular system, intestinal tract, Stomach, Digestive organs, Liver, spleen, thymus
Specific target organ systemic toxicity (repeated exposure) Category 2 Nervous system, Respiratory system
Hazardous to the aquatic environment - acute hazard Category 2
Hazardous to the aquatic environment - chronic hazard Category 2

GHS LABEL ELEMENTS:

Symbol(s)



Signal Word

DANGER

Hazard Statements

Highly flammable liquid and vapor.
Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing genetic defects.
May cause cancer.
May damage fertility or the unborn child.
May cause harm to breast-fed children.
May cause drowsiness or dizziness.

May cause respiratory irritation.

Causes damage to organs.(Central nervous system, Cardio-vascular system, Respiratory system, Kidney, Nervous system, Body, Systemic toxicity)

Causes damage to organs through prolonged or repeated exposure.(Central nervous system, Kidney, Hematopoietic System, Cardio-vascular system, intestinal tract, Stomach, Digestive organs, Liver, spleen, thymus)

May cause damage to organs through prolonged or repeated exposure.(Nervous system, Respiratory system)

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Response

In case of fire: refer to section 5 of SDS for extinguishing media.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Collect spillage.

Storage

Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. Harmful if absorbed through skin. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: May cause long-term lung damage. Trichloroethylene has been classified by IARC as a human carcinogen (Group 1) and by NTP as a reasonably anticipated human carcinogen. 1,2 butylene oxide has been classified by IARC as a possible human carcinogen (Group 2B) and reported by NTP to show clear evidence for carcinogenicity in

animals. ACGIH considers Ethyl alcohol to be an A3 carcinogen (confirmed animal carcinogen with unknown relevance in humans).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range
Toluene	108-88-3	25 - 30 %
Isopropanol	67-63-0	25 - 30 %
Trichloroethylene	79-01-6	20 - 25 %
Phenolic resin	9003-35-4	5 - 10 %
Ethyl alcohol	64-17-5	5 - 10 %
Phenol	108-95-2	1 - 5 %
1,2-Butylene oxide	106-88-7	0.1 - 0.9 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNSUITABLE EXTINGUISHING MEDIA: Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Avoid contact. Use self-contained breathing equipment.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Contain and remove with inert absorbent material and non-sparking tools.

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Avoid using pressurizable equipment which has aluminum or zinc parts; this product contains chlorinated solvents. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

STORAGE: Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.; Aluminum, zinc, caustics, halogens.; Alkalis.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>	<u>Skin</u>
Toluene	20 ppm	N.E.	200 ppm	300 ppm	N.A.
Isopropanol	200 ppm	400 ppm	980 mg/m3 400 ppm	N.E.	N.A.
Trichloroethylene	10 ppm	25 ppm	100 ppm	200 ppm	N.A.
Phenolic resin	N.E.	N.E.	N.E.	N.E.	N.A.
Ethyl alcohol	N.E.	1,000 ppm	1,900 mg/m3 1,000 ppm	N.E.	N.A.
Phenol	5 ppm	N.E.	19 mg/m3 5 ppm	N.E.	S
1,2-Butylene oxide	N.E.	N.E.	N.E.	N.E.	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

Engineering controls: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

RESPIRATORY PROTECTION: Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

SKIN PROTECTION: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

EYE PROTECTION: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

OTHER PROTECTIVE EQUIPMENT: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR:	Solvent	VAPOR PRESSURE:	N.D.
APPEARANCE:	Amber	VAPOR DENSITY:	Heavier than Air
PHYSICAL STATE:	Liquid	LOWER EXPLOSIVE LIMIT:	1.2 %(V)
FLASH POINT:	36 °F, 2 °C Setaflash	UPPER EXPLOSIVE LIMIT:	44.8 %(V)
	Closed Cup		
BOILING RANGE:	78 - 111 °C	EVAPORATION RATE:	Slower than n-butyl-acetate
AUTOIGNITION TEMPERATURE:	N.D.	DENSITY:	0.98 g/cm ³ - 8.13 lb/gal
DECOMPOSITION TEMPERATURE:	N.D.	VISCOSITY, DYNAMIC:	≥750 mPa.s @ 25 °C
ODOR THRESHOLD:	N.D.	VISCOSITY, KINEMATIC:	≥765 mm ² /s @ 25 °C
SOLUBILITY IN H₂O:	Insoluble	VOLATILE BY WEIGHT:	78.44 %
pH:	N.A.	VOLATILE BY VOLUME:	82.57 %
FREEZE POINT:	N.D.	VOC CALCULATED:	6.37 lb/gal, 764 g/l
COEFFICIENT OF WATER/OIL DISTRIBUTION:	N.D.		

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures. Sources of ignition.; High humidity.; Aluminum or galvanized parts in a closed system.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.; Aluminum, zinc, caustics, halogens.; Alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, Butyraldehyde, butyric acid, acrolein, crotonaldehyde., Phosgene

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

<u>Chemical Name</u>	<u>LD50/LC50</u>
Toluene	Oral LD50: Rat 2,600 mg/kg Dermal LD50: Rabbit 12,000 mg/kg Inhalation LC50: Rat 12.5 mg/l /4 h
Isopropanol	Oral LD50: Rat 1,870 mg/kg Dermal LD50: Rabbit 4,059 mg/kg Inhalation LC50: Rat 72,600 mg/m ³ /4 h
Trichloroethylene	Oral LD50: Rat 4,920 mg/kg Dermal LD50: Rabbit 29,000 mg/kg Inhalation LC50: Rat 26 mg/l /4 h
Phenolic resin	Oral LD50: Rat > 5 g/kg Dermal LD50: Rat > 2 g/kg
Ethyl alcohol	Oral LD50: Rat 7,060 mg/kg Inhalation LC50: Rat 124.7 mg/l /4 h
Phenol	Oral LD50: Rat 340 mg/kg Dermal LD50: Rabbit 630 mg/kg GHS LC50 (dust and mist): Acute toxicity point estimate 0.55 mg/l
1,2-Butylene oxide	Oral LD50: Rat 900 mg/kg Dermal LD50: Rabbit 1,255 - 2,546 mg/kg

	Inhalation LC50: Rat > 6,300 mg/m3 /4 h
--	---

Germ cell mutagenicity: Category 2 - Suspected of causing genetic defects.

Components contributing to classification: Trichloroethylene. Phenol.

Carcinogenicity: Category 1A - May cause cancer.

Components contributing to classification: Trichloroethylene. 1,2-Butylene oxide.

Reproductive toxicity: Category 1A - May damage fertility or the unborn child. May cause harm to breast-fed children.

Components contributing to classification: Toluene. Isopropanol. Trichloroethylene. Phenol. Methanol. 1,2-Butylene oxide.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	Ecotoxicity
Toluene	<p><u>Fish:</u> Pimephales promelas 15.22 - 19.05 mg/196 h flow-through Pimephales promelas 12.6 mg/196 h Static Oncorhynchus mykiss 5.89 - 7.81 mg/196 h flow-through Oncorhynchus mykiss 14.1 - 17.16 mg/196 h Static Oncorhynchus mykiss 5.8 mg/196 h semi-static Lepomis macrochirus 11.0 - 15.0 mg/196 h Static Oryzias latipes 54 mg/196 h Static Poecilia reticulata 28.2 mg/196 h semi-static Poecilia reticulata 50.87 - 70.34 mg/196 h Static <u>Invertebrates:</u> Daphnia magna 5.46 - 9.83 mg/148 h Static Daphnia magna 11.5 mg/148 h <u>Plants:</u> Pseudokirchneriella subcapitata > 433 mg/196 h Pseudokirchneriella subcapitata 12.5 mg/172 h Static</p>
Isopropanol	<p><u>Fish:</u> Pimephales promelas 9,640 mg/196 h flow-through Pimephales promelas 11,130 mg/196 h Static Lepomis macrochirus > 1,400,000 µg/196 h <u>Invertebrates:</u> Daphnia magna 13,299 mg/148 h <u>Plants:</u> Desmodesmus subspicatus > 1,000 mg/196 h Desmodesmus subspicatus > 1,000 mg/172 h</p>
Trichloroethylene	<p><u>Fish:</u> Pimephales promelas 31.4 - 71.8 mg/196 h flow-through Lepomis macrochirus 39 - 54 mg/196 h Static <u>Invertebrates:</u> Daphnia magna 2.2 mg/148 h <u>Plants:</u> Desmodesmus subspicatus 450 mg/196 h Pseudokirchneriella subcapitata 175 mg/196 h</p>
Phenolic resin	N.D.
Ethyl alcohol	<p><u>Fish:</u> Pimephales promelas > 100 mg/196 h Static Pimephales promelas 13,400 - 15,100 mg/196 h flow-through <u>Invertebrates:</u> Daphnia magna 9,268 - 14,221 mg/148 h Daphnia magna 2 mg/148 h Static</p>
Phenol	<p><u>Fish:</u> Pimephales promelas 20.5 - 25.6 mg/196 h Static Pimephales promelas 32 mg/196 h Oncorhynchus mykiss 5.449 - 6.789 mg/196 h flow-through Oncorhynchus mykiss 7.5 - 14 mg/196 h Static Oncorhynchus mykiss 4.23 - 7.49 mg/196 h semi-static Oncorhynchus mykiss 5.0 - 12.0 mg/196 h Lepomis macrochirus 13.5 mg/196 h Static Lepomis macrochirus 11.9 - 25.3 mg/196 h flow-through Lepomis macrochirus 11.5 mg/196 h semi-static Poecilia reticulata 34.09 - 47.64 mg/196 h Static Poecilia reticulata 31 mg/196 h semi-static Brachydanio rerio 27.8 mg/196 h Oryzias latipes 33.9 - 43.3 mg/196 h flow-through Oryzias latipes 23.4 - 36.6 mg/196 h Static Pimephales promelas 11.9 - 50.5 mg/196 h flow-through <u>Invertebrates:</u> Daphnia magna 4.24 - 10.7 mg/148 h Static Daphnia magna 10.2 - 15.5 mg/148 h <u>Plants:</u> Pseudokirchneriella subcapitata 46.42 mg/196 h Desmodesmus subspicatus 187 - 279 mg/172 h Static</p>

1,2-Butylene oxide	<u>Invertebrates:</u> Daphnia magna 69.8 mg/148 h <u>Plants:</u> Desmodemus subspicatus > 500 mg/172 h
--------------------	---

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

14. TRANSPORT INFORMATION

US DOT Road

DOT Proper Shipping Name: Adhesives
DOT Hazard Class: 3
SECONDARY HAZARD: None
DOT UN/NA Number: 1133
Packing Group: II
Emergency Response Guide Number: 128

IATA Cargo

PROPER SHIPPING NAME: Adhesives
DOT Hazard Class: 3
HAZARD CLASS: None
UN-NUMBER: 1133
PACKING GROUP: II
EMS: 3L

IMDG

PROPER SHIPPING NAME: Adhesives
DOT Hazard Class: 3
HAZARD CLASS: None
UN-NUMBER: 1133
PACKING GROUP: II
EMS: F-E

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS:

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Weight % Less Than</u>
Toluene	108-88-3	30.0 %
Isopropanol	67-63-0	30.0 %
Trichloroethylene	79-01-6	25.0 %

Phenol	108-95-2	5.0 %
1,2-Butylene oxide	106-88-7	0.9 %

TOXIC SUBSTANCES CONTROL ACT:

INVENTORY STATUS

The chemical substances in this product are on the TSCA Section 8 Inventory.

EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name
Trichloroethylene

CAS Number
79-01-6

16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2* FLAMMABILITY: 3 PHYSICAL HAZARD: 0

* - Indicates a chronic hazard; see Section 2

Revision: Section 3

Effective Date: 05/05/2017

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.