API Reference

E-Signature

API Version: 1.0.17

This API is a robust tool designed for developers and businesses looking to automate and integrate secure document signing processes into their applications. This API is fully compliant with eIDAS regulations, ensuring that all signatures meet strict European standards for legal validity.
The documentation outlines a comprehensive suite of features, allowing users to implement various types of digital signatures, including Simple Electronic Signatures (SES) secured via OTP, Qualified Electronic Seals, and Massive Automatic Qualified Electronic Signatures (QES) for high-volume needs. Key functionalities include the ability to timestamp documents, manage certificates, and access detailed audit logs to track the entire signing lifecycle.
The Swagger UI provided in the documentation enables developers to explore and test endpoints directly, managing signature flows, and verifying certification status facilitating a smooth integration process for dematerializing paper-based workflows.

CONTACT

NAME: Support
URL: https://openapi.it/en/support
Terms of service: https://openapi.it/en/terms-and-conditions

INDEX

1. CERTIFICATES 4

1.1 GET /certificates 4

1.2 GET /certificates/{id} 4

1.3 POST /certificates/namirial-automatic 6

1.4 POST /certificates/namirial-otp 7

2. SIGNATURES 9

2.1 GET /signatures 9

2.2 GET /signatures/{id}/{actionType} 9

2.3 POST /EU-QES_automatic 11

2.4 POST /EU-QES_otp 24

2.5 POST /EU-QES_eseal 38

2.6 POST /EU-SES 51

2.7 POST /verify 57

2.8 DELETE /signatures/{id} 59

Security and Authentication

SECURITY SCHEMES

KEY	TYPE	DESCRIPTION
bearerAuth	http, bearer	Enter the token you generated with the <a href='https://console.openapi.com/apis/oauth'>OAUTH</a> service here. Remember to specify the scopes you intend to use. Scopes are strings that indicate which endpoint you intend to enable, composed with the following schema: HTTP_METHOD:API_DOMAIN/RESOURCE_PATH example: POST:esignature.openapi.com/EU-QES_automatic

API

1. CERTIFICATES

Purchase or renew signature certificates

1.1 GET /certificates

Get a list of certificates

Get a list of certificates. The list can be filtered by certificateType and state. The available types are: EU-QES_automaticm EU-QES_otp. The available states are: NEW, EXPIRED, and SUSPENDED.

REQUEST

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
certificateType	enum **ALLOWED:** EU-QES_automatic, EU-QES_otp, EU-QES_eseal	Type of certificate
state	enum **ALLOWED:** NEW, EXPIRED, SUSPENDED	State of the certificate
skip	integer >=0	Number of items to skip
limit	integer between 1 and 100	Maximum number of items to return (min 1 max 100)

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
[{
Array of object:
  id                 string  ID of the certificate
  certificateOwner   string  Name of the certificate owner
  customReference    string  Custom reference for the certificate
  certificateType    enum    ALLOWED:EU-QES_automatic, EU-QES_otp
                             Type of certificate
  createdAt          string  Date and time of creation
  expireAt           string  Date and time of certificate expiration
  state              enum    ALLOWED:NEW, EXPIRED, SUSPENDED
                             State of the certificate
  certificateLink    string  URL to start the certificate attribution procedure
}]
```

STATUS CODE - 400: Invalid input

1.2 GET /certificates/{id}

Get a certificate

Get a certificate by ID. The certificate ID is required to access the service.

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	ID of the certificate

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
{
  id                          string    ID of the certificate
  certificateOwner            string    Name of the certificate owner
  customReference             string    Custom reference for the certificate
  certificateType             enum      ALLOWED:EU-QES_automatic, EU-QES_otp
                                        Type of certificate
  createdAt                   string    Date and time of creation
  expireAt                    string    Date and time of certificate expiration
  state                       enum      ALLOWED:NEW, EXPIRED, SUSPENDED
                                        State of the certificate
  certificateLink             string    URL to start the certificate attribution procedure
  callback {
  This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.
    method  enum    DEFAULT:JSON
                    ALLOWED:POST, JSON
                    Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.
    field   string  DEFAULT:data
                    This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.
    url*    string  A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.
    retry   integer between 0 and 5
                    DEFAULT:0
                    The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.
    headers {
    A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.
      key  string
    }
    custom {
    This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.
    }
  }
}
```

STATUS CODE - 400: Invalid input

STATUS CODE - 404: Certificate not found

1.3 POST /certificates/namirial-automatic

Purchase a Namirial Automatic Certificate

Purchase a Namirial Automatic Certificate which is valid for 3 years and can be used to sign documents in CAdES, PAdES, XAdES, and PKCS#1 formats. The procedure returns a certificateLink which is a one time procedure from the certification autority to qualify the owner of the certificate.

Once the procedure is complete the signer will receive an email containing a PDF file protected by a password and a link to receive the password by SMS. The PDF file contains the necessary credentials.

The callback object isn't required.

REQUEST

REQUEST BODY - application/json

```
{
  certificateOwner        string    Name of the certificate owner
  customReference         string    Custom reference for the certificate, usefull for internal tracking
  callback {
    This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.
    method  enum     DEFAULT:JSON
                     ALLOWED:POST, JSON
                     Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.
    field   string   DEFAULT:data
                     This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.
    url*    string   A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.
    retry   integer  between 0 and 5
                     DEFAULT:0
                     The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.
    headers {
      A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.
      key  string
    }
    custom {
      This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.
    }
  }
}
```

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
{
  data {
    id                string   ID of the certificate
    certificateType   enum     ALLOWED:EU-QES_automatic, EU-QES_otp, EU-QES_eseal
                               Type of certificate
    state             enum     ALLOWED:NEW, DONE, REGISTERING, WORKING, CANCELLED
                               State of the request
    certificateLink   string   URL to start the certificate attribution procedure
    certificateOwner {
    Information about the certificate owner
      owner             string   Owner reference for the certificate
      customReference   string   Custom reference for the certificate
    }
    createdAt         string   Date and time of creation
    expireAt          string   Date and time of expiration
  }
  success   boolean   Operation success
  message   string    Message
  error     string    Error code
}
```

STATUS CODE - 404: Certificate Unavailable

RESPONSE MODEL - application/json

```
{
  data {
  }
  success   boolean   Operation Failed
  message   string    Message
  error     integer   Error code
}
```

1.4 POST /certificates/namirial-otp

Purchase a Namirial OTP Certificate

Purchase a Namirial OTP Certificate. The certificate is valid for 3 years and can be used to sign documents in CAdES, PAdES, XAdES, and PKCS#1 formats.

REQUEST

REQUEST BODY - application/json

```
{
  certificateOwner   string   Name of the certificate owner
  customReference    string   Custom reference for the certificate, usefull for internal tracking
  callback {
  This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.
    method   enum   DEFAULT:JSON
                    ALLOWED:POST, JSON
                    Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.
    field    string DEFAULT:data
                    This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.
```

```
    url*    string   A valid URL capable of handling POST requests must be entered into this parameter. For endpoints
                     requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The
                     maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status
                     code is received.
    retry   integer  between 0 and  5
                     DEFAULT:0
                     The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts
                     is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time
                     interval is often introduced between attempts to avoid overloading the server. This interval may increase
                     exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is
                     configured to retry the request only in case of specific status codes, typically those indicating temporary
                     errors (e.g., 502, 503) or network issues.
    headers {
    A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for
    various purposes, including authentication, content negotiation, and custom metadata.
      key  string
    }
    custom {
    This object can be populated with any additional data you wish to include in the callback response. This data will be accessible
    within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need
    for your application.
    }
  }
}
```

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
{
  data {
    id               string  ID of the certificate
    certificateType  enum    ALLOWED:EU-QES_automatic, EU-QES_otp
                             Type of certificate
    state            enum    ALLOWED:NEW, DONE, REGISTERING, WORKING, CANCELLED
                             State of the request
    certificateLink  string  URL to start the certificate attribution procedure
    certificateOwner {
    Information about the certificate owner
      owner            string  Owner reference for the certificate
      customReference  string  Custom reference for the certificate
    }
    createdAt        string  Date and time of creation
    expireAt         string  Date and time of expiration
  }
  success   boolean   Operation success
  message   string    Message
  error     string    Error code
}
```

STATUS CODE - 404: Certificate Unavailable

RESPONSE MODEL - application/json

```
{
  data {
  }
  success  boolean  Operation Failed
  message  string   Message
  error    integer  Error code
}
```

2. SIGNATURES

Apply an electronic signature to a file

2.1 GET /signatures

Get a list of signatures

Get a list of signatures. The list can be filtered by state, certificate type, and signature type. The available states are: WAIT_VALIDATION, WAIT_SIGN, WAIT_SIGNER, DONE, and ERROR. The available certificate types are: EU-QES_automatic, EU-QES_otp and EU-SES. The available signature types are: cades, pades, xades and pkcs1.

REQUEST

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
state	enum **ALLOWED:** WAIT_VALIDATION, WAIT_SIGN, WAIT_SIGNER, DONE, ERROR	State of the signature
certificateType	enum **ALLOWED:** EU-QES_automatic, EU-QES_otp	Type of certificate
signatureType	enum **ALLOWED:** cades, pades, xades, pkcs1	Type of the signature
skip	integer >=0	Number of items to skip
limit	integer between 1 and 100	Maximum number of items to return (min 1 max 100)

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
[{
Array of object:
  id                string   ID of the signature
  updatedAt         string   Date and time of the last update
  createdAt         string   Date and time of creation
  documentTitle     string   Title of the document
  certificateType   enum     ALLOWED:EU-QES_automatic, EU-QES_remote_otp
                             Type of certificate
  signatureType     enum     ALLOWED:cades, pades, xades, pkcs1
                             Type of the signature
  state             enum     ALLOWED:WAIT_VALIDATION, WAIT_SIGN, DONE, ERROR
                             State of the signature
  errorNumber       integer  Error number
  errorMessage      string   Error message
}]
```

STATUS CODE - 404: No signatures found

2.2 GET /signatures/{id}/{actionType}

Download the signed Document, get the details, audit Trail or the validatedDocument of a signature

Get the detail, audit, the signedDocument or the validatedDocument of a signature.
 The signature ID is required to access the service.
 The actionType parameter can be used to specify the type of information to retrieve.
 The available options are: signedDocument, validatedDocument, audit and detail.
The signedDocument and validatedDocument returns the binary content of the file ready to be donwloaded.
The audit trail is available in multiple format based on the request header Accept value.
 The available formats are: application/json, text/plain, text/html, application/pdf.

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	ID of the signature
*actionType	enum ALLOWED: detail, audit, signedDocument, validatedDocument,	Type of action to perform, "detail" or leave empty for the signed document info, "signedDocument", "audit" for the audit trail or "validatedDocument"

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - */*

```
string
```

RESPONSE MODEL - application/json

```
{
  id                 string   ID of the signature
  updatedAt          string   Date and time of the last update
  createdAt          string   Date and time of creation
  certificateType    enum     ALLOWED:EU-QES_automatic
                              Type of certificate
  signatureType      enum     ALLOWED:cades, pades, xades, pkcs1
                              Type of the signature
  state              enum     ALLOWED:WAIT_VALIDATION, WAIT_SIGN, DONE, ERROR
                              State of the signature
  options {
  Additional options for the signature
    asyncDocumentsValidation boolean  Whether to validate documents asynchronously
    asyncSignature           boolean  Whether to sign documents asynchronously
    level                    string   Signature level
    hashAlgorithm            string   Hash algorithm
    encryptInAnyCase         boolean  Encrypt in any case
    page                     integer  Page number to sign
    withSignatureField       boolean  Include signature field
  }
  errorNumber      integer  Error number
  errorMessage     string   Error message
  document {
  Document to sign
    title          string   Title of the document
    description    string   Description of the document
    inputDocuments [{
    Array of object:
      sourceType  enum     ALLOWED:remote, base64
                           Source type of the document
      createdAt   string   Date and time of creation
      mimetype    string   MIME type of the document
```

```
        extension   string   Extension of the document
        size        integer  Size of the document
        id          string   ID of the document
        md5         string   MD5 hash of the document
        name        string   File Name of the document
      }]
      validatedDocument {
      Validated document
        mimetype   string   MIME type of the document
        extension  string   Extension of the document
        size       integer  Size of the document
        createdAt  string   Date and time of creation
        id         string   ID of the document
        md5        string   MD5 hash of the document
        name       string   File Name of the document
      }
      signedDocument {
      Signed document
        createdAt  string   Date and time of creation
        mimetype   string   MIME type of the document
        extension  string   Extension of the document
        size       integer  Size of the document
        id         string   ID of the document
        md5        string   MD5 hash of the document
        name       string   File Name of the document
      }
    }
  }
```

RESPONSE MODEL - text/plain

```
string
```

RESPONSE MODEL - text/html

```
string
```

RESPONSE MODEL - application/pdf

```
string
```

STATUS CODE - 400: Invalid input

STATUS CODE - 404: Signature not found

2.3 POST /EU-QES_automatic

Create QES Signature using Massive Automatic Certificate

Create a signature procedure from one or more files.

Obtaining the certificate:

To access the service, you need an automatic certificate that can be purchased through the appropriate endpoint "/certificates/namirial-automatic".

Available formats:

The system can sign in CAdES, PAdES, XAdES, and PKCS#1 formats.

If not specified, the system will look for the most suitable format based on the mimeType of the uploaded file.

Input files:

It is possible to upload single and multiple input files both in base64 format and by specifying the resource URL and any authentication parameters.

- In the case of uploading multiple files
- with PAdES signature, they will be merged into a single signed pdf
- document.
- In the case of signing multiple files in CAdES format, a zip
- file will be generated and signed.

Asynchronous mode, batch processing, callback and detached signature:

For massive signing of large quantities of files, it is possible to upload and sign in asynchronous mode. An authenticated callback system is available to receive updates.

It is also possible to sign the hash of the original file directly and obtain only the "detached" signature file.

Document and data retention in the system:

Signature structured data details and audit trail will be stored in the system for a maximum of 10 years.
Signed documents, uploaded documents and validated documents will remain in the system for a maximum of 3 months to allow for downloading.
After this period, the documents will be automatically deleted.

Qualified Timestamping available:

A qualified timestamping option is available. There is also an option to use qualified timestamping credentials already in your possession. In this case, the system allows you to specify the authentication URL of the relevant certification authority.

Sandbox:

For testing purposes, you can use the following credentials:

- certificateUsername: "openapiSandboxUsername"
- certificatePassword: "openapiSandboxPassword"

REQUEST

REQUEST BODY - application/json

```
{
  inputDocuments
    ONE OF
    0 {
    }
    prop0
    string
    A valid URL string
    prop1
    string
    A valid base64 string
    OPTION 1 {
      sourceType  enum      ALLOWED: remote, base64, base64Hash
                            Source type of the document
      url         string    URL of the remote document
      headers     [string]
```

method	enum	DEFAULT:get ALLOWED:get, post HTTP method for the remote document request
postData	string	Post data for the remote document request
payload	string	Base64 encoded payload of the document or the hash of the document

}

certificateUsername	string	Username for the certificate, must be used the Device name you received. It starts with: RHI (/EU-QES_otp), SHI (/EU-QES_eseal) or AHI (/EU-QES_automatic)
certificatePassword	string	Password for the certificate, must be used the PIN associated to device name (can be set by the customer or read into blind envelope)
certificateOtp	string	VALID ONLY FOR /EU-QES_otp endpoint, is REQUIRED and is obtainable using the relative otp app from the certification authority
certificateIdOtp	integer	VALID ONLY FOR /EU-QES_otp endpoint, is Optional and is used in the case more than one otp is set on the certification authority app. You can find it on the top right section of the otp app
title	string	Title of the signature
description	string	Description of the signature
signatureType	enum	ALLOWED:cades, pades, xades, pkcs1 Type of the signature. Could be cades, pades, xades, pkcs1

options {

Additional options for the signature. The available options depend on the `signatureType`:

- **Common Options**:
- `asyncDocumentsValidation` (boolean): Whether to validate documents asynchronously. Default: `false`.
- `asyncSignature` (boolean): Whether to sign documents asynchronously. Default: `false`.
- **PAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `encryptInAnyCase` (boolean): Encrypt in any case. Default: `false`.
- `page` (integer): Page number to sign. Default: `1`.
- `encryptionPassword` (string): Password for pdf encryption. Default: `null`.
- `signerImage` (string): Image of the signer. Default: `null`.
- `lockFields` (string): Fields to lock. Default: `null`.
- `withSignatureField` (boolean): Include signature field. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **CAdES Options**:
- `detached` (boolean): Detached signature. Default: `false`.
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `counterSignature` (boolean): Counter signature. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **XAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `detached` (boolean): Detached signature. Default: `false`.
- `withoutSignatureExclusion` (boolean): Without signature exclusion. Default: `false`.
- `XPathQuery` (string): XPath query. Default: `null`.
- `signElement` (string): Sign element. Default: `null`.
- `signatureId` (string): Signature ID. Default: `null`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **PKCS1 Options**:
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.

asyncDocumentsValidation	boolean	Whether to validate documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_VALIDATION state and will send a callback when the sign process is completed or if the document is not valid.
asyncSignature	boolean	Whether to sign documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_SIGN state and will send a callback when the signature process is completed.
level	enum	DEFAULT:B ALLOWED:B, T, LT, LTA, LTV Signature level: B (Basic), T (Time), LT (Long Term), LTA (Long Term Archive), LTV (Long Term Validation) - `B` In the signed file the electronic signature and the signing certificate are added. (Pades, Cades, Xades) - `T` Like B-Level, but adds a time-stamp, respectively a time-mark that proves the signature existed at a certain date and time. (Pades, Cades, Xades) - `LT` Like T-Level, but adds VRI (Verification Related Information) data to the DSS (Long Term). (Pades, Cades, Xades) - `LTA` Like LT-level, but adds a time stamp document and VRI data for the TSA (Time Stamping Authority). An LTA may help to validate the signature beyond any event that may limit its validity (Long Term with Archive Time-Stamps). (Pades, Cades, Xades) - `LTV` (Long Term Validation) contains the OCSP/CRL response after the signature. It is used for validation after the signing certificate has expired. (Pades)
hashAlgorithm	enum	DEFAULT:SHA256 ALLOWED:SHA1, SHA256, SHA384, SHA512 Algorithm which you want to use for signing.
encryptInAnyCase	boolean	Encrypt in any case
page	integer	DEFAULT:1 Indicate the page number on which you want to apply the signature appearance. If you want to add the appearance on the last page of the PDF file, you should set it to "-1".
encryptionPassword	string	Specify the password PDF, if present.
signerImage {		
Image of the signer		
image	string	Base64 encoded image data of the signer.
imageUrl	string	URL of the image of the signer.
signerName	string	Name of the signer to be displayed on the image.
location	string	Location of the signer to be displayed on the image.
reason	string	Reason for the signature.
signerEmail	string	Email of the signer to be displayed on the image.
imageVisible	boolean	DEFAULT:true Whether the image should be visible on the signature.
width	integer	DEFAULT:164 Width of the image in pixels.
height	integer	DEFAULT:45 Height of the image in pixels.
fieldsNameList	[string]	
signAllFields	boolean	Whether to sign all fields with the image.
}		
lockFields	string	Fields to lock
withSignatureField	boolean	Set true if you want to apply the signature on signature field in the PDF file.
detached	boolean	Detached signature. Set true if you want the signature and the files in two different files. The output will be the signature.
withoutSignatureExclusion	boolean	Without signature exclusion allows to sign the file with/without previous signature.
XPathQuery	string	Allows to sign a specified path of XML file.
signElement	string	Allows to specify the "Id" on XML which you want to sign.
signatureId	string	Allows to specify the "Id" of the signature.
counterSignature	boolean	Counter signature is used to sign an already signed .p7m document.
timezone	enum	ALLOWED:Africa/Abidjan, Africa/Accra, Africa/Addis_Ababa, Africa/Algiers, Africa/Asmara,

Africa/Bamako, Africa/Bangui, Africa/Banjul, Africa/Bissau, Africa/Blantyre, Africa/Brazzaville, Africa/Bujumbura, Africa/Cairo, Africa/Casablanca, Africa/Ceuta, Africa/Conakry, Africa/Dakar, Africa/Dar_es_Salaam, Africa/Djibouti, Africa/Douala, Africa/El_Aaiun, Africa/Freetown, Africa/Gaborone, Africa/Harare, Africa/Johannesburg, Africa/Juba, Africa/Kampala, Africa/Khartoum, Africa/Kigali, Africa/Kinshasa, Africa/Lagos, Africa/Libreville, Africa/Lome, Africa/Luanda, Africa/Lubumbashi, Africa/Lusaka, Africa/Malabo, Africa/Maputo, Africa/Maseru, Africa/Mbabane, Africa/Mogadishu, Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Costa_Rica, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Fort_Nelson, America/Fortaleza, America/Glace_Bay, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Inuvik, America/Iqaluit, America/Jamaica, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Lower_Princes, America/Maceio, America/Managua,

America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montserrat, America/Nassau, America/New_York, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Whitehorse, America/Winnipeg, America/Yakutat, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Chita, Asia/Choibalsan, Asia/Colombo, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kathmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Riyadh, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ulaanbaatar, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg,

		Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faroe, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/Perth, Australia/Sydney, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Ulyanovsk, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zurich, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Wake, Pacific/Wallis, UTC An identifier for a valid timezone, default setting will be UTC.
withTimestamp	boolean	Include timestamp. If true and the timestampUrl, timestampUsername and timestampPassword are set, the system will add a timestamp to the signature. If true but other timestamp parameters are not set, the system will timestamp anyway billing the timestamp on wallet. (check <a target='_blanc' href='https://console.openapi.com/apis/esignature/pricing'>prices</a> for more details)
timestampUrl	string	URL of the timestamp service
timestampUsername	string	Username for the timestamp service
timestampPassword	string	Password for the timestamp service

}

```
callback {
This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.
  method  enum     DEFAULT:JSON
                   ALLOWED:POST, JSON
                   Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.
  field   string   DEFAULT:data
                   This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.
  url*    string   A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.
  retry   integer  between 0 and  5
                   DEFAULT:0
                   The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.
  headers {
  A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.
    key  string
  }
  custom {
  This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.
  }
}
}
```

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
{
  inputDocuments
    ONE OF
    0 {
    }
    prop0
    string
    A valid URL string
    prop1
    string
    A valid base64 string
    OPTION 1 {
      sourceType  enum      ALLOWED:remote, base64, base64Hash
                            Source type of the document
      url         string    URL of the remote document
      headers     [string]
      method      enum      DEFAULT:get
                            ALLOWED:get, post
                            HTTP method for the remote document request
      postData    string    Post data for the remote document request
      payload     string    Base64 encoded payload of the document or the hash of the document
    }
```

certificateUsername	string	Username for the certificate, must be used the Device name you received. It starts with: RHI (/EU-QES_otp), SHI (/EU-QES_eseal) or AHI (/EU-QES_automatic)
certificatePassword	string	Password for the certificate, must be used the PIN associated to device name (can be set by the customer or read into blind envelope)
certificateOtp	string	VALID ONLY FOR /EU-QES_otp endpoint, is REQUIRED and is obtainable using the relative otp app from the certification authority
certificateIdOtp	integer	VALID ONLY FOR /EU-QES_otp endpoint, is Optional and is used in the case more than one otp is set on the certification authority app. You can find it on the top right section of the otp app
title	string	Title of the signature
description	string	Description of the signature
signatureType	enum	ALLOWED: cades, pades, xades, pkcs1 Type of the signature. Could be cades, pades, xades, pkcs1

options {

Additional options for the signature. The available options depend on the `signatureType`:

- **Common Options**:
- `asyncDocumentsValidation` (boolean): Whether to validate documents asynchronously. Default: `false`.
- `asyncSignature` (boolean): Whether to sign documents asynchronously. Default: `false`.
- **PAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `encryptInAnyCase` (boolean): Encrypt in any case. Default: `false`.
- `page` (integer): Page number to sign. Default: `1`.
- `encryptionPassword` (string): Password for pdf encryption. Default: `null`.
- `signerImage` (string): Image of the signer. Default: `null`.
- `lockFields` (string): Fields to lock. Default: `null`.
- `withSignatureField` (boolean): Include signature field. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **CAdES Options**:
- `detached` (boolean): Detached signature. Default: `false`.
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `counterSignature` (boolean): Counter signature. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **XAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `detached` (boolean): Detached signature. Default: `false`.
- `withoutSignatureExclusion` (boolean): Without signature exclusion. Default: `false`.
- `XPathQuery` (string): XPath query. Default: `null`.
- `signElement` (string): Sign element. Default: `null`.
- `signatureId` (string): Signature ID. Default: `null`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **PKCS1 Options**:
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.

asyncDocumentsValidation	boolean	Whether to validate documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_VALIDATION state and will send a callback when the sign process is completed or if the document is not valid.

asyncSignature	boolean	Whether to sign documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_SIGN state and will send a callback when the signature process is completed.
level	enum	DEFAULT:B ALLOWED:B, T, LT, LTA, LTV Signature level: B (Basic), T (Time), LT (Long Term), LTA (Long Term Archive), LTV (Long Term Validation) - `B` In the signed file the electronic signature and the signing certificate are added. (Pades, Cades, Xades) - `T` Like B-Level, but adds a time-stamp, respectively a time-mark that proves the signature existed at a certain date and time. (Pades, Cades, Xades) - `LT` Like T-Level, but adds VRI (Verification Related Information) data to the DSS (Long Term). (Pades, Cades, Xades) - `LTA` Like LT-level, but adds a time stamp document and VRI data for the TSA (Time Stamping Authority). An LTA may help to validate the signature beyond any event that may limit its validity (Long Term with Archive Time-Stamps). (Pades, Cades, Xades) - `LTV` (Long Term Validation) contains the OCSP/CRL response after the signature. It is used for validation after the signing certificate has expired. (Pades)
hashAlgorithm	enum	DEFAULT:SHA256 ALLOWED:SHA1, SHA256, SHA384, SHA512 Algorithm which you want to use for signing.
encryptInAnyCase	boolean	Encrypt in any case
page	integer	DEFAULT:1 Indicate the page number on which you want to apply the signature appearance. If you want to add the appearance on the last page of the PDF file, you should set it to "-1".
encryptionPassword	string	Specify the password PDF, if present.
signerImage {		
Image of the signer		
image	string	Base64 encoded image data of the signer.
imageUrl	string	URL of the image of the signer.
signerName	string	Name of the signer to be displayed on the image.
location	string	Location of the signer to be displayed on the image.
reason	string	Reason for the signature.
signerEmail	string	Email of the signer to be displayed on the image.
imageVisible	boolean	DEFAULT:true Whether the image should be visible on the signature.
width	integer	DEFAULT:164 Width of the image in pixels.
height	integer	DEFAULT:45 Height of the image in pixels.
fieldsNameList	[string]	
signAllFields	boolean	Whether to sign all fields with the image.
}		
lockFields	string	Fields to lock
withSignatureField	boolean	Set true if you want to apply the signature on signature field in the PDF file.
detached	boolean	Detached signature. Set true if you want the signature and the files in two different files. The output will be the signature.
withoutSignatureExclusion	boolean	Without signature exclusion allows to sign the file with/without previous signature.
XPathQuery	string	Allows to sign a specified path of XML file.
signElement	string	Allows to specify the "Id" on XML which you want to sign.
signatureId	string	Allows to specify the "Id" of the signature.
counterSignature	boolean	Counter signature is used to sign an already signed .p7m document.
timezone	enum	ALLOWED:Africa/Abidjan, Africa/Accra, Africa/Addis_Ababa, Africa/Algiers, Africa/Asmara, Africa/Bamako, Africa/Bangui, Africa/Banjul, Africa/Bissau, Africa/Blantyre, Africa/Brazzaville, Africa/Bujumbura, Africa/Cairo,

Africa/Casablanca, Africa/Ceuta, Africa/Conakry, Africa/Dakar, Africa/Dar_es_Salaam, Africa/Djibouti, Africa/Douala, Africa/El_Aaiun, Africa/Freetown, Africa/Gaborone, Africa/Harare, Africa/Johannesburg, Africa/Juba, Africa/Kampala, Africa/Khartoum, Africa/Kigali, Africa/Kinshasa, Africa/Lagos, Africa/Libreville, Africa/Lome, Africa/Luanda, Africa/Lubumbashi, Africa/Lusaka, Africa/Malabo, Africa/Maputo, Africa/Maseru, Africa/Mbabane, Africa/Mogadishu, Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Costa_Rica, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Fort_Nelson, America/Fortaleza, America/Glace_Bay, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Inuvik, America/Iqaluit, America/Jamaica, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Lower_Princes,

America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montserrat, America/Nassau, America/New_York, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Whitehorse, America/Winnipeg, America/Yakutat, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Chita, Asia/Choibalsan, Asia/Colombo, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kathmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Riyadh, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/

Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ulaanbaatar, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faroe, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/Perth, Australia/Sydney, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Ulyanovsk, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zurich, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Wake, Pacific/Wallis, UTC

An identifier for a valid timezone, default setting will be UTC.

withTimestamp	boolean	Include timestamp. If true and the timestampUrl, timestampUsername and timestampPassword are set, the system will add a timestamp to the signature. If true but other timestamp parameters are not set, the system will timestamp anyway billing the timestamp on wallet. (check <a target='_blanc' href='https://console.openapi.com/apis/esignature/pricing'>prices</a> for more details)
timestampUrl	string	URL of the timestamp service
timestampUsername	string	Username for the timestamp service
timestampPassword	string	Password for the timestamp service

}

callback {

This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.

method	enum	DEFAULT:JSON ALLOWED:POST, JSON Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.
field	string	DEFAULT:data This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.
url*	string	A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.
retry	integer	between 0 and 5 DEFAULT:0 The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.

headers {

A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.

key string

}

custom {

This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.

}

}

}

STATUS CODE - 422: Unprocessable Entity. This response is returned when validation fails or the request cannot be processed.

RESPONSE MODEL - application/json

{

success*	boolean	Indicates if the request was successful (always false for errors).
message*	string	A human-readable message explaining the specific error.
error*	integer	A specific application-defined error code.

data* {

Contains additional error data, or null if not applicable.

}

}

2.4 POST /EU-QES_otp

Create QES Signature using Remote OTP Certificate

Create a signature procedure from one or more files.

Obtaining the certificate:

To access the service, you need an automatic certificate that can be purchased through the appropriate endpoint /certificates/namirial-otp.

Available formats:

The system can sign in CAdES, PAdES, XAdES, and PKCS#1 formats.

If not specified, the system will look for the most suitable format based on the mimeType of the uploaded file.

Input files:

It is possible to upload single and multiple input files both in base64 format and by specifying the resource URL and any authentication parameters.

- In the case of uploading multiple files
- with PAdES signature, they will be merged into a single signed pdf
- document.
- In the case of signing multiple files in CAdES format, a zip
- file will be generated and signed.

Asynchronous mode, batch processing, callback and detached signature:

For massive signing of large quantities of files, it is possible to upload and sign in asynchronous mode. An authenticated callback system is available to receive updates.

It is also possible to sign the hash of the original file directly and obtain only the "detached" signature file.

Document and data retention in the system:

Signature structured data details and audit trail will be stored in the system for a maximum of 10 years.
Signed documents, uploaded documents and validated documents will remain in the system for a maximum of 3 months to allow for downloading.
After this period, the documents will be automatically deleted.

Qualified Timestamping available:

A qualified timestamping option is available. There is also an option to use qualified timestamping credentials already in your possession. In this case, the system allows you to specify the authentication URL of the relevant certification authority.

Sandbox:

For testing purposes, you can use the following credentials:

- certificateUsername: "openapiSandboxUsername"
- certificatePassword: "openapiSandboxPassword"

REQUEST

REQUEST BODY - application/json

```
{
  inputDocuments
```

ONE OF

0 {

}

prop0

string

A valid URL string

prop1

string

A valid base64 string

OPTION 1 {

sourceType	enum	ALLOWED:remote, base64, base64Hash Source type of the document
url	string	URL of the remote document
headers	[string]	
method	enum	DEFAULT:get ALLOWED:get, post HTTP method for the remote document request
postData	string	Post data for the remote document request
payload	string	Base64 encoded payload of the document or the hash of the document

}

certificateUsername	string	Username for the certificate, must be used the Device name you received. It starts with: RHI (/EU-QES_otp), SHI (/EU-QES_eseal) or AHI (/EU-QES_automatic)
certificatePassword	string	Password for the certificate, must be used the PIN associated to device name (can be set by the customer or read into blind envelope)
certificateOtp	string	VALID ONLY FOR /EU-QES_otp endpoint, is REQUIRED and is obtainable using the relative otp app from the certification authority
certificateIdOtp	integer	VALID ONLY FOR /EU-QES_otp endpoint, is Optional and is used in the case more than one otp is set on the certification authority app. You can find it on the top right section of the otp app
title	string	Title of the signature
description	string	Description of the signature
signatureType	enum	ALLOWED:cades, pades, xades, pkcs1 Type of the signature. Could be cades, pades, xades, pkcs1

options {

Additional options for the signature. The available options depend on the `signatureType`:

- **Common Options**:
- `asyncDocumentsValidation` (boolean): Whether to validate documents asynchronously. Default: `false`.
- `asyncSignature` (boolean): Whether to sign documents asynchronously. Default: `false`.
- **PAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `encryptInAnyCase` (boolean): Encrypt in any case. Default: `false`.
- `page` (integer): Page number to sign. Default: `1`.
- `encryptionPassword` (string): Password for pdf encryption. Default: `null`.
- `signerImage` (string): Image of the signer. Default: `null`.
- `lockFields` (string): Fields to lock. Default: `null`.
- `withSignatureField` (boolean): Include signature field. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **CAdES Options**:
- `detached` (boolean): Detached signature. Default: `false`.
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `counterSignature` (boolean): Counter signature. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.

- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **XAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `detached` (boolean): Detached signature. Default: `false`.
- `withoutSignatureExclusion` (boolean): Without signature exclusion. Default: `false`.
- `XPathQuery` (string): XPath query. Default: `null`.
- `signElement` (string): Sign element. Default: `null`.
- `signatureId` (string): Signature ID. Default: `null`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **PKCS1 Options**:
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.

`asyncDocumentsValidation`	`boolean`	Whether to validate documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_VALIDATION state and will send a callback when the sign process is completed or if the document is not valid.
`asyncSignature`	`boolean`	Whether to sign documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_SIGN state and will send a callback when the signature process is completed.
`level`	`enum`	DEFAULT:B ALLOWED:`B, T, LT, LTA, LTV` Signature level: B (Basic), T (Time), LT (Long Term), LTA (Long Term Archive), LTV (Long Term Validation) - `B` In the signed file the electronic signature and the signing certificate are added. (Pades, Cades, Xades) - `T` Like B-Level, but adds a time-stamp, respectively a time-mark that proves the signature existed at a certain date and time. (Pades, Cades, Xades) - `LT` Like T-Level, but adds VRI (Verification Related Information) data to the DSS (Long Term). (Pades, Cades, Xades) - `LTA` Like LT-level, but adds a time stamp document and VRI data for the TSA (Time Stamping Authority). An LTA may help to validate the signature beyond any event that may limit its validity (Long Term with Archive Time-Stamps). (Pades, Cades, Xades) - `LTV` (Long Term Validation) contains the OCSP/CRL response after the signature. It is used for validation after the signing certificate has expired. (Pades)
`hashAlgorithm`	`enum`	DEFAULT:SHA256 ALLOWED:`SHA1, SHA256, SHA384, SHA512` Algorithm which you want to use for signing.
`encryptInAnyCase`	`boolean`	Encrypt in any case
`page`	`integer`	DEFAULT:1 Indicate the page number on which you want to apply the signature appearance. If you want to add the appearance on the last page of the PDF file, you should set it to "-1".
`encryptionPassword`	`string`	Specify the password PDF, if present.
`signerImage {` Image of the signer		

`image`	`string`	Base64 encoded image data of the signer.
`imageUrl`	`string`	URL of the image of the signer.
`signerName`	`string`	Name of the signer to be displayed on the image.
`location`	`string`	Location of the signer to be displayed on the image.
`reason`	`string`	Reason for the signature.
`signerEmail`	`string`	Email of the signer to be displayed on the image.
`imageVisible`	`boolean`	DEFAULT:`true` Whether the image should be visible on the signature.
`width`	`integer`	DEFAULT:164 Width of the image in pixels.
`height`	`integer`	DEFAULT:45 Height of the image in pixels.
`fieldsNameList`	`[string]`	

signAllFields	boolean	Whether to sign all fields with the image.
}		
lockFields	string	Fields to lock
withSignatureField	boolean	Set true if you want to apply the signature on signature field in the PDF file.
detached	boolean	Detached signature. Set true if you want the signature and the files in two different files. The output will be the signature.
withoutSignatureExclusion	boolean	Without signature exclusion allows to sign the file with/without previous signature.
XPathQuery	string	Allows to sign a specified path of XML file.
signElement	string	Allows to specify the "Id" on XML which you want to sign.
signatureId	string	Allows to specify the "Id" of the signature.
counterSignature	boolean	Counter signature is used to sign an already signed .p7m document.
timezone	enum	ALLOWED:Africa/Abidjan, Africa/Accra, Africa/Addis_Ababa, Africa/Algiers, Africa/Asmara, Africa/Bamako, Africa/Bangui, Africa/Banjul, Africa/Bissau, Africa/Blantyre, Africa/Brazzaville, Africa/Bujumbura, Africa/Cairo, Africa/Casablanca, Africa/Ceuta, Africa/Conakry, Africa/Dakar, Africa/Dar_es_Salaam, Africa/Djibouti, Africa/Douala, Africa/El_Aaiun, Africa/Freetown, Africa/Gaborone, Africa/Harare, Africa/Johannesburg, Africa/Juba, Africa/Kampala, Africa/Khartoum, Africa/Kigali, Africa/Kinshasa, Africa/Lagos, Africa/Libreville, Africa/Lome, Africa/Luanda, Africa/Lubumbashi, Africa/Lusaka, Africa/Malabo, Africa/Maputo, Africa/Maseru, Africa/Mbabane, Africa/Mogadishu, Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Costa_Rica, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Fort_Nelson, America/Fortaleza, America/Glace_Bay, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe,

America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Inuvik, America/Iqaluit, America/Jamaica, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Lower_Princes, America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montserrat, America/Nassau, America/New_York, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Whitehorse, America/Winnipeg, America/Yakutat, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Chita, Asia/Choibalsan, Asia/Colombo, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kathmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/

Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Riyadh, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ulaanbaatar, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faroe, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/Perth, Australia/Sydney, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Ulyanovsk, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zurich, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/

Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Wake, Pacific/Wallis, UTC

An identifier for a valid timezone, default setting will be UTC.

withTimestamp boolean Include timestamp. If true and the timestampUrl, timestampUsername and timestampPassword are set, the system will add a timestamp to the signature. If true but other timestamp parameters are not set, the system will timestamp anyway billing the timestamp on wallet. (check <a target='_blanc' href='https://console.openapi.com/apis/esignature/pricing'>prices</a> for more details)

timestampUrl string URL of the timestamp service

timestampUsername string Username for the timestamp service

timestampPassword string Password for the timestamp service

}

callback {

This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.

method enum

DEFAULT:JSON

ALLOWED:POST, JSON

Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.

field string

DEFAULT:data

This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.

url* string A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.

retry integer between 0 and 5

DEFAULT:0

The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.

headers {

A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.

key string

}

custom {

This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.

}

}

}

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

{

inputDocuments

ONE OF

0 {

}

prop0

string

A valid URL string

prop1
string
A valid base64 string
OPTION 1 {

sourceType	enum	ALLOWED:remote, base64, base64Hash Source type of the document
url	string	URL of the remote document
headers	[string]	
method	enum	DEFAULT:get ALLOWED:get, post HTTP method for the remote document request
postData	string	Post data for the remote document request
payload	string	Base64 encoded payload of the document or the hash of the document

}

certificateUsername	string	Username for the certificate, must be used the Device name you received. It starts with: RHI (/EU-QES_otp), SHI (/EU-QES_eseal) or AHI (/EU-QES_automatic)
certificatePassword	string	Password for the certificate, must be used the PIN associated to device name (can be set by the customer or read into blind envelope)
certificateOtp	string	VALID ONLY FOR /EU-QES_otp endpoint, is REQUIRED and is obtainable using the relative otp app from the certification authority
certificateIdOtp	integer	VALID ONLY FOR /EU-QES_otp endpoint, is Optional and is used in the case more than one otp is set on the certification authority app. You can find it on the top right section of the otp app
title	string	Title of the signature
description	string	Description of the signature
signatureType	enum	ALLOWED:cades, pades, xades, pkcs1 Type of the signature. Could be cades, pades, xades, pkcs1

options {
Additional options for the signature. The available options depend on the `signatureType`:

- **Common Options**:
- `asyncDocumentsValidation` (boolean): Whether to validate documents asynchronously. Default: `false`.
- `asyncSignature` (boolean): Whether to sign documents asynchronously. Default: `false`.
- **PAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `encryptInAnyCase` (boolean): Encrypt in any case. Default: `false`.
- `page` (integer): Page number to sign. Default: `1`.
- `encryptionPassword` (string): Password for pdf encryption. Default: `null`.
- `signerImage` (string): Image of the signer. Default: `null`.
- `lockFields` (string): Fields to lock. Default: `null`.
- `withSignatureField` (boolean): Include signature field. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **CAdES Options**:
- `detached` (boolean): Detached signature. Default: `false`.
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `counterSignature` (boolean): Counter signature. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **XAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.

- `detached` (boolean): Detached signature. Default: `false`.
- `withoutSignatureExclusion` (boolean): Without signature exclusion. Default: `false`.
- `XPathQuery` (string): XPath query. Default: `null`.
- `signElement` (string): Sign element. Default: `null`.
- `signatureId` (string): Signature ID. Default: `null`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **PKCS1 Options**:
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.

`asyncDocumentsValidation`	boolean	Whether to validate documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_VALIDATION state and will send a callback when the sign process is completed or if the document is not valid.
`asyncSignature`	boolean	Whether to sign documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_SIGN state and will send a callback when the signature process is completed.
`level`	enum	DEFAULT:B ALLOWED:`B, T, LT, LTA, LTV` Signature level: B (Basic), T (Time), LT (Long Term), LTA (Long Term Archive), LTV (Long Term Validation) - `B` In the signed file the electronic signature and the signing certificate are added. (Pades, Cades, Xades) - `T` Like B-Level, but adds a time-stamp, respectively a time-mark that proves the signature existed at a certain date and time. (Pades, Cades, Xades) - `LT` Like T-Level, but adds VRI (Verification Related Information) data to the DSS (Long Term). (Pades, Cades, Xades) - `LTA` Like LT-level, but adds a time stamp document and VRI data for the TSA (Time Stamping Authority). An LTA may help to validate the signature beyond any event that may limit its validity (Long Term with Archive Time-Stamps). (Pades, Cades, Xades) - `LTV` (Long Term Validation) contains the OCSP/CRL response after the signature. It is used for validation after the signing certificate has expired. (Pades)
`hashAlgorithm`	enum	DEFAULT:SHA256 ALLOWED:`SHA1, SHA256, SHA384, SHA512` Algorithm which you want to use for signing.
`encryptInAnyCase`	boolean	Encrypt in any case
`page`	integer	DEFAULT:1 Indicate the page number on which you want to apply the signature appearance. If you want to add the appearance on the last page of the PDF file, you should set it to "-1".
`encryptionPassword`	string	Specify the password PDF, if present.
`signerImage {`		

Image of the signer

`image`	string	Base64 encoded image data of the signer.
`imageUrl`	string	URL of the image of the signer.
`signerName`	string	Name of the signer to be displayed on the image.
`location`	string	Location of the signer to be displayed on the image.
`reason`	string	Reason for the signature.
`signerEmail`	string	Email of the signer to be displayed on the image.
`imageVisible`	boolean	DEFAULT:`true` Whether the image should be visible on the signature.
`width`	integer	DEFAULT:164 Width of the image in pixels.
`height`	integer	DEFAULT:45 Height of the image in pixels.
`fieldsNameList`	[string]	
`signAllFields`	boolean	Whether to sign all fields with the image.
`}`		
`lockFields`	string	Fields to lock

withSignatureField	boolean	Set true if you want to apply the signature on signature field in the PDF file.
detached	boolean	Detached signature. Set true if you want the signature and the files in two different files. The output will be the signature.
withoutSignatureExclusion	boolean	Without signature exclusion allows to sign the file with/without previous signature.
XPathQuery	string	Allows to sign a specified path of XML file.
signElement	string	Allows to specify the "Id" on XML which you want to sign.
signatureId	string	Allows to specify the "Id" of the signature.
counterSignature	boolean	Counter signature is used to sign an already signed .p7m document.
timezone	enum	ALLOWED:Africa/Abidjan, Africa/Accra, Africa/Addis_Ababa, Africa/Algiers, Africa/Asmara, Africa/Bamako, Africa/Bangui, Africa/Banjul, Africa/Bissau, Africa/Blantyre, Africa/Brazzaville, Africa/Bujumbura, Africa/Cairo, Africa/Casablanca, Africa/Ceuta, Africa/Conakry, Africa/Dakar, Africa/Dar_es_Salaam, Africa/Djibouti, Africa/Douala, Africa/El_Aaiun, Africa/Freetown, Africa/Gaborone, Africa/Harare, Africa/Johannesburg, Africa/Juba, Africa/Kampala, Africa/Khartoum, Africa/Kigali, Africa/Kinshasa, Africa/Lagos, Africa/Libreville, Africa/Lome, Africa/Luanda, Africa/Lubumbashi, Africa/Lusaka, Africa/Malabo, Africa/Maputo, Africa/Maseru, Africa/Mbabane, Africa/Mogadishu, Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Costa_Rica, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Fort_Nelson, America/Fortaleza, America/Glace_Bay, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/

Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Inuvik, America/Iqaluit, America/Jamaica, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Lower_Princes, America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montserrat, America/Nassau, America/New_York, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Whitehorse, America/Winnipeg, America/Yakutat, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Chita, Asia/Choibalsan, Asia/Colombo, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Jakarta, Asia/Jayapura, Asia/

Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kathmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Riyadh, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ulaanbaatar, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faroe, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/Perth, Australia/Sydney, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Ulyanovsk, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zurich, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/

Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Wake, Pacific/Wallis, UTC

An identifier for a valid timezone, default setting will be UTC.

`withTimestamp` boolean — Include timestamp. If true and the timestampUrl, timestampUsername and timestampPassword are set, the system will add a timestamp to the signature. If true but other timestamp parameters are not set, the system will timestamp anyway billing the timestamp on wallet. (check <a target='_blanc' href='https://console.openapi.com/apis/esignature/pricing'>prices</a> for more details)

`timestampUrl` string — URL of the timestamp service

`timestampUsername` string — Username for the timestamp service

`timestampPassword` string — Password for the timestamp service

}

callback {

This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.

`method` enum — DEFAULT:JSON

ALLOWED:POST, JSON

Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.

`field` string — DEFAULT:data

This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.

`url*` string — A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.

`retry` integer — between 0 and 5

DEFAULT:0

The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.

headers {

A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.

`key` string

}

custom {

This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.

}

}

}

STATUS CODE - 422: Unprocessable Entity. This response is returned when validation fails or the request cannot be processed.

RESPONSE MODEL - application/json

```
{
   success*  boolean  Indicates if the request was successful (always false for errors).
   message*  string   A human-readable message explaining the specific error.
   error*    integer  A specific application-defined error code.
   data* {
   Contains additional error data, or null if not applicable.
   }
}
```

2.5 POST /EU-QES_eseal

Create QES Signature using Remote E-seal Certificate

Create a signature procedure from one or more files.

Obtaining the certificate:

To access the service, you need an automatic certificate that can be purchased through <a href="https://console.openapi.com/support">Our Customer Support</a>.

Available formats:

The system can sign in CAdES, PAdES, XAdES, and PKCS#1 formats.

If not specified, the system will look for the most suitable format based on the mimeType of the uploaded file.

Input files:

It is possible to upload single and multiple input files both in base64 format and by specifying the resource URL and any authentication parameters.

- In the case of uploading multiple files
- with PAdES signature, they will be merged into a single signed pdf
- document.
- In the case of signing multiple files in CAdES format, a zip
- file will be generated and signed.

Asynchronous mode, batch processing, callback and detached signature:

For massive signing of large quantities of files, it is possible to upload and sign in asynchronous mode. An authenticated callback system is available to receive updates.

It is also possible to sign the hash of the original file directly and obtain only the "detached" signature file.

Document and data retention in the system:

Signature structured data details and audit trail will be stored in the system for a maximum of 10 years.
Signed documents, uploaded documents and validated documents will remain in the system for a maximum of 3 months to allow for downloading.
After this period, the documents will be automatically deleted.

Qualified Timestamping available:

A qualified timestamping option is available. There is also an option to use qualified timestamping credentials already in

your possession. In this case, the system allows you to specify the authentication URL of the relevant certification authority.

Sandbox:

For testing purposes, you can use the following credentials:

- certificateUsername: "openapiSandboxUsername"
- certificatePassword: "openapiSandboxPassword"

REQUEST

REQUEST BODY - application/json

```
{
  inputDocuments
    ONE OF
    0 {
    }
    prop0
    string
    A valid URL string
    prop1
    string
    A valid base64 string
    OPTION 1 {
      sourceType  enum      ALLOWED:remote, base64, base64Hash
                            Source type of the document
      url         string    URL of the remote document
      headers     [string]
      method      enum      DEFAULT:get
                            ALLOWED:get, post
                            HTTP method for the remote document request
      postData    string    Post data for the remote document request
      payload     string    Base64 encoded payload of the document or the hash of the document
    }
  certificateUsername        string    Username for the certificate, must be used the Device name you received. It starts with: RHI (/EU-QES_otp), SHI (/EU-QES_eseal) or AHI (/EU-QES_automatic)
  certificatePassword        string    Password for the certificate, must be used the PIN associated to device name (can be set by the customer or read into blind envelope)
  certificateOtp             string    VALID ONLY FOR /EU-QES_otp endpoint, is REQUIRED and is obtainable using the relative otp app from the certification authority
  certificateIdOtp           integer   VALID ONLY FOR /EU-QES_otp endpoint, is Optional and is used in the case more than one otp is set on the certification authority app. You can find it on the top right section of the otp app
  title                      string    Title of the signature
  description                string    Description of the signature
  signatureType              enum      ALLOWED:cades, pades, xades, pkcs1
                                       Type of the signature. Could be cades, pades, xades, pkcs1
  options {
  Additional options for the signature. The available options depend on the `signatureType`:

  - **Common Options**:
  - `asyncDocumentsValidation` (boolean): Whether to validate documents asynchronously. Default: `false`.
  - `asyncSignature` (boolean): Whether to sign documents asynchronously. Default: `false`.
  - **PAdES Options**:
  - `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
```

- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `encryptInAnyCase` (boolean): Encrypt in any case. Default: `false`.
- `page` (integer): Page number to sign. Default: `1`.
- `encryptionPassword` (string): Password for pdf encryption. Default: `null`.
- `signerImage` (string): Image of the signer. Default: `null`.
- `lockFields` (string): Fields to lock. Default: `null`.
- `withSignatureField` (boolean): Include signature field. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **CAdES Options**:
- `detached` (boolean): Detached signature. Default: `false`.
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `counterSignature` (boolean): Counter signature. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **XAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `detached` (boolean): Detached signature. Default: `false`.
- `withoutSignatureExclusion` (boolean): Without signature exclusion. Default: `false`.
- `XPathQuery` (string): XPath query. Default: `null`.
- `signElement` (string): Sign element. Default: `null`.
- `signatureId` (string): Signature ID. Default: `null`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **PKCS1 Options**:
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.

`asyncDocumentsValidation`	boolean	Whether to validate documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_VALIDATION state and will send a callback when the sign process is completed or if the document is not valid.
`asyncSignature`	boolean	Whether to sign documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_SIGN state and will send a callback when the signature process is completed.
`level`	enum	DEFAULT:B ALLOWED:B, T, LT, LTA, LTV Signature level: B (Basic), T (Time), LT (Long Term), LTA (Long Term Archive), LTV (Long Term Validation) - `B` In the signed file the electronic signature and the signing certificate are added. (Pades, Cades, Xades) - `T` Like B-Level, but adds a time-stamp, respectively a time-mark that proves the signature existed at a certain date and time. (Pades, Cades, Xades) - `LT` Like T-Level, but adds VRI (Verification Related Information) data to the DSS (Long Term). (Pades, Cades, Xades) - `LTA` Like LT-level, but adds a time stamp document and VRI data for the TSA (Time Stamping Authority). An LTA may help to validate the signature beyond any event that may limit its validity (Long Term with Archive Time-Stamps). (Pades, Cades, Xades) - `LTV` (Long Term Validation) contains the OCSP/CRL response after the signature. It is used for validation after the signing certificate has expired. (Pades)
`hashAlgorithm`	enum	DEFAULT:SHA256 ALLOWED:SHA1, SHA256, SHA384, SHA512 Algorithm which you want to use for signing.
`encryptInAnyCase`	boolean	Encrypt in any case
`page`	integer	DEFAULT:1 Indicate the page number on which you want to apply the signature appearance. If you want to add the appearance on the last page of the PDF file, you should set it to "-1".
`encryptionPassword`	string	Specify the password PDF, if present.
`signerImage {`		

Image of the signer

image	string	Base64 encoded image data of the signer.
imageUrl	string	URL of the image of the signer.
signerName	string	Name of the signer to be displayed on the image.
location	string	Location of the signer to be displayed on the image.
reason	string	Reason for the signature.
signerEmail	string	Email of the signer to be displayed on the image.
imageVisible	boolean	DEFAULT:true Whether the image should be visible on the signature.
width	integer	DEFAULT:164 Width of the image in pixels.
height	integer	DEFAULT:45 Height of the image in pixels.
fieldsNameList	[string]	
signAllFields	boolean	Whether to sign all fields with the image.

}

lockFields	string	Fields to lock
withSignatureField	boolean	Set true if you want to apply the signature on signature field in the PDF file.
detached	boolean	Detached signature. Set true if you want the signature and the files in two different files. The output will be the signature.
withoutSignatureExclusion	boolean	Without signature exclusion allows to sign the file with/without previous signature.
XPathQuery	string	Allows to sign a specified path of XML file.
signElement	string	Allows to specify the "Id" on XML which you want to sign.
signatureId	string	Allows to specify the "Id" of the signature.
counterSignature	boolean	Counter signature is used to sign an already signed .p7m document.
timezone	enum	ALLOWED:Africa/Abidjan, Africa/Accra, Africa/Addis_Ababa, Africa/Algiers, Africa/Asmara, Africa/Bamako, Africa/Bangui, Africa/Banjul, Africa/Bissau, Africa/Blantyre, Africa/Brazzaville, Africa/Bujumbura, Africa/Cairo, Africa/Casablanca, Africa/Ceuta, Africa/Conakry, Africa/Dakar, Africa/Dar_es_Salaam, Africa/Djibouti, Africa/Douala, Africa/El_Aaiun, Africa/Freetown, Africa/Gaborone, Africa/Harare, Africa/Johannesburg, Africa/Juba, Africa/Kampala, Africa/Khartoum, Africa/Kigali, Africa/Kinshasa, Africa/Lagos, Africa/Libreville, Africa/Lome, Africa/Luanda, Africa/Lubumbashi, Africa/Lusaka, Africa/Malabo, Africa/Maputo, Africa/Maseru, Africa/Mbabane, Africa/Mogadishu, Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize,

America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Costa_Rica, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Fort_Nelson, America/Fortaleza, America/Glace_Bay, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Inuvik, America/Iqaluit, America/Jamaica, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Lower_Princes, America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montserrat, America/Nassau, America/New_York, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Whitehorse, America/Winnipeg, America/Yakutat, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/Syowa,

Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Chita, Asia/Choibalsan, Asia/Colombo, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kathmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Riyadh, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ulaanbaatar, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faroe, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/Perth, Australia/Sydney, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Ulyanovsk, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zurich,

Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Wake, Pacific/Wallis, UTC

An identifier for a valid timezone, default setting will be UTC.

`withTimestamp` boolean — Include timestamp. If true and the timestampUrl, timestampUsername and timestampPassword are set, the system will add a timestamp to the signature. If true but other timestamp parameters are not set, the system will timestamp anyway billing the timestamp on wallet. (check <a target='_blanc' href='https://console.openapi.com/apis/esignature/pricing'>prices</a> for more details)

`timestampUrl` string — URL of the timestamp service

`timestampUsername` string — Username for the timestamp service

`timestampPassword` string — Password for the timestamp service

}

callback {

This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.

`method` enum — DEFAULT:JSON

ALLOWED:POST, JSON

Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.

`field` string — DEFAULT:data

This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.

`url*` string — A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.

`retry` integer — between 0 and 5

DEFAULT:0

The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.

headers {

A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.

`key` string

}

custom {

This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.

}

}

}

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
{
  inputDocuments
    ONE OF
    0 {
    }
    prop0
    string
    A valid URL string
    prop1
    string
    A valid base64 string
    OPTION 1 {
      sourceType  enum      ALLOWED:remote, base64, base64Hash
                            Source type of the document
      url         string    URL of the remote document
      headers     [string]
      method      enum      DEFAULT:get
                            ALLOWED:get, post
                            HTTP method for the remote document request
      postData    string    Post data for the remote document request
      payload     string    Base64 encoded payload of the document or the hash of the document
    }
  certificateUsername          string    Username for the certificate, must be used the Device name you received. It starts with: RHI (/EU-QES_otp), SHI (/EU-QES_eseal) or AHI (/EU-QES_automatic)
  certificatePassword          string    Password for the certificate, must be used the PIN associated to device name (can be set by the customer or read into blind envelope)
  certificateOtp               string    VALID ONLY FOR /EU-QES_otp endpoint, is REQUIRED and is obtainable using the relative otp app from the certification authority
  certificateIdOtp             integer   VALID ONLY FOR /EU-QES_otp endpoint, is Optional and is used in the case more than one otp is set on the certification authority app. You can find it on the top right section of the otp app
  title                        string    Title of the signature
  description                  string    Description of the signature
  signatureType                enum      ALLOWED:cades, pades, xades, pkcs1
                                         Type of the signature. Could be cades, pades, xades, pkcs1
  options {
  Additional options for the signature. The available options depend on the `signatureType`:

  - **Common Options**:
  - `asyncDocumentsValidation` (boolean): Whether to validate documents asynchronously. Default: `false`.
  - `asyncSignature` (boolean): Whether to sign documents asynchronously. Default: `false`.
  - **PAdES Options**:
  - `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
  - `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
  - `encryptInAnyCase` (boolean): Encrypt in any case. Default: `false`.
  - `page` (integer): Page number to sign. Default: `1`.
  - `encryptionPassword` (string): Password for pdf encryption. Default: `null`.
  - `signerImage` (string): Image of the signer. Default: `null`.
  - `lockFields` (string): Fields to lock. Default: `null`.
  - `withSignatureField` (boolean): Include signature field. Default: `false`.
  - `withTimestamp` (boolean): Include timestamp. Default: `false`.
```

- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **CAdES Options**:
- `detached` (boolean): Detached signature. Default: `false`.
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `counterSignature` (boolean): Counter signature. Default: `false`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **XAdES Options**:
- `level` (string): Signature level. Values: `B`, `T`, `LT`, `LTA`, `LTV`. Default: `B`.
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- `detached` (boolean): Detached signature. Default: `false`.
- `withoutSignatureExclusion` (boolean): Without signature exclusion. Default: `false`.
- `XPathQuery` (string): XPath query. Default: `null`.
- `signElement` (string): Sign element. Default: `null`.
- `signatureId` (string): Signature ID. Default: `null`.
- `withTimestamp` (boolean): Include timestamp. Default: `false`.
- `timestampUrl` (string): URL of the timestamp service. Default: `null`.
- `timestampUsername` (string): Username for the timestamp service. Default: `null`.
- `timestampPassword` (string): Password for the timestamp service. Default: `null`.
- `timestampHashAlgo` (string): Hash algorithm for the timestamp service. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.
- **PKCS1 Options**:
- `hashAlgorithm` (string): Hash algorithm. Values: `SHA1`, `SHA256`, `SHA384`, `SHA512`. Default: `SHA256`.

`asyncDocumentsValidation`	boolean	Whether to validate documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_VALIDATION state and will send a callback when the sign process is completed or if the document is not valid.
`asyncSignature`	boolean	Whether to sign documents asynchronously, usefull for large files and batch processing. The system will return a WAIT_SIGN state and will send a callback when the signature process is completed.
`level`	enum	DEFAULT:B ALLOWED:`B, T, LT, LTA, LTV` Signature level: B (Basic), T (Time), LT (Long Term), LTA (Long Term Archive), LTV (Long Term Validation) - `B` In the signed file the electronic signature and the signing certificate are added. (Pades, Cades, Xades) - `T` Like B-Level, but adds a time-stamp, respectively a time-mark that proves the signature existed at a certain date and time. (Pades, Cades, Xades) - `LT` Like T-Level, but adds VRI (Verification Related Information) data to the DSS (Long Term). (Pades, Cades, Xades) - `LTA` Like LT-level, but adds a time stamp document and VRI data for the TSA (Time Stamping Authority). An LTA may help to validate the signature beyond any event that may limit its validity (Long Term with Archive Time-Stamps). (Pades, Cades, Xades) - `LTV` (Long Term Validation) contains the OCSP/CRL response after the signature. It is used for validation after the signing certificate has expired. (Pades)
`hashAlgorithm`	enum	DEFAULT:SHA256 ALLOWED:`SHA1, SHA256, SHA384, SHA512` Algorithm which you want to use for signing.
`encryptInAnyCase`	boolean	Encrypt in any case
`page`	integer	DEFAULT:1 Indicate the page number on which you want to apply the signature appearance. If you want to add the appearance on the last page of the PDF file, you should set it to "-1".
`encryptionPassword`	string	Specify the password PDF, if present.
`signerImage {` Image of the signer		

`image`	string	Base64 encoded image data of the signer.
`imageUrl`	string	URL of the image of the signer.

signerName	string	Name of the signer to be displayed on the image.
location	string	Location of the signer to be displayed on the image.
reason	string	Reason for the signature.
signerEmail	string	Email of the signer to be displayed on the image.
imageVisible	boolean	DEFAULT:true Whether the image should be visible on the signature.
width	integer	DEFAULT:164 Width of the image in pixels.
height	integer	DEFAULT:45 Height of the image in pixels.
fieldsNameList	[string]	
signAllFields	boolean	Whether to sign all fields with the image.

}

lockFields	string	Fields to lock
withSignatureField	boolean	Set true if you want to apply the signature on signature field in the PDF file.
detached	boolean	Detached signature. Set true if you want the signature and the files in two different files. The output will be the signature.
withoutSignatureExclusion	boolean	Without signature exclusion allows to sign the file with/without previous signature.
XPathQuery	string	Allows to sign a specified path of XML file.
signElement	string	Allows to specify the "Id" on XML which you want to sign.
signatureId	string	Allows to specify the "Id" of the signature.
counterSignature	boolean	Counter signature is used to sign an already signed .p7m document.
timezone	enum	ALLOWED:Africa/Abidjan, Africa/Accra, Africa/Addis_Ababa, Africa/Algiers, Africa/Asmara, Africa/Bamako, Africa/Bangui, Africa/Banjul, Africa/Bissau, Africa/Blantyre, Africa/Brazzaville, Africa/Bujumbura, Africa/Cairo, Africa/Casablanca, Africa/Ceuta, Africa/Conakry, Africa/Dakar, Africa/Dar_es_Salaam, Africa/Djibouti, Africa/Douala, Africa/El_Aaiun, Africa/Freetown, Africa/Gaborone, Africa/Harare, Africa/Johannesburg, Africa/Juba, Africa/Kampala, Africa/Khartoum, Africa/Kigali, Africa/Kinshasa, Africa/Lagos, Africa/Libreville, Africa/Lome, Africa/Luanda, Africa/Lubumbashi, Africa/Lusaka, Africa/Malabo, Africa/Maputo, Africa/Maseru, Africa/Mbabane, Africa/Mogadishu, Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak, America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/

Boa_Vista, America/Bogota, America/Boise, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Costa_Rica, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Fort_Nelson, America/Fortaleza, America/Glace_Bay, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Inuvik, America/Iqaluit, America/Jamaica, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Lower_Princes, America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montserrat, America/Nassau, America/New_York, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Whitehorse, America/Winnipeg, America/Yakutat, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson,

Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Chita, Asia/Choibalsan, Asia/Colombo, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kathmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Riyadh, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ulaanbaatar, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faroe, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/Perth, Australia/Sydney, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Oslo, Europe/Paris, Europe/Podgorica, Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/

Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Ulyanovsk, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zurich, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Wake, Pacific/Wallis, UTC

An identifier for a valid timezone, default setting will be UTC.

`withTimestamp` boolean — Include timestamp. If true and the timestampUrl, timestampUsername and timestampPassword are set, the system will add a timestamp to the signature. If true but other timestamp parameters are not set, the system will timestamp anyway billing the timestamp on wallet. (check <a target='_blanc' href='https://console.openapi.com/apis/esignature/pricing'>prices</a> for more details)

`timestampUrl` string — URL of the timestamp service

`timestampUsername` string — Username for the timestamp service

`timestampPassword` string — Password for the timestamp service

}

callback {

This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.

`method` enum

DEFAULT:JSON

ALLOWED:POST, JSON

Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.

`field` string

DEFAULT:data

This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.

`url*` string — A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.

`retry` integer between 0 and 5

DEFAULT:0

The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.

headers {
A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.

key string
}
custom {
This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.

}
}
}

STATUS CODE - 400: Invalid input

STATUS CODE - 422: Validation exception

2.6 POST /EU-SES

Create a SES request for one or more signers.

The call will return a link, one for each signer, to our esign webapp. In the webapp, each signer will be able to read the document and sign it after authenticating via OTP (which can be sent via SMS or email).
For every signer, you must specify at least their mobile number or their email address where the OTP code will be sent, additionally you must specify how they'll authenticate within the authentication option. It is also possible to specify the message that will be sent along with the OTP code and how the signers are going to sign the document, by default they'll be able to sign either by typing their name or by drawing it.
The user interface visible to the final signer is also completely customizable in the request. Document validation will be done asynchronously. If no signatures are passed for a signer, the default signature will be put in top left corner.

Document and data retention in the system:

Signature structured data details and audit trail will be stored in the system for a maximum of 10 years.
Signed documents, uploaded documents and validated documents will remain in the system for a maximum of 3 months to allow for downloading.
After this period, the documents will be automatically deleted.

REQUEST

REQUEST BODY - application/json

{
SES request definition.

signers* [{
Array of object:

name*	string	Signer's name.
surname*	string	Signer's surname.
email	string	Email address where the OTP code will be sent (if 'email' is the authentication method chosed).
mobile	string	Mobile number where the OTP code will be sent (if 'sms' is the authentication method chosed).
message	string	A custom message to be sent to the signer. If the message includes the {OTP} placeholder, it will be replaced by the actual OTP. Otherwise, the OTP code will be appended to the end of the message. **Note**: For SMS messages, the maximum allowed length is 160 characters (OTP or its placeholder included).
authentication*	[enum]	ALLOWED:email, sms

signatures* [{
Array of object:

page*	integer	Page number where this single signature field is present. Pages goes from 1 to N.
x*	string	X coordinate from the left.
y*	string	Y coordinate from the top.
name	string	The single signature field identifier already present on the pdf.

}]
}]

```
inputDocuments*
  ONE OF
  0 {
    ::props {
      sourceType*  enum    ALLOWED:remote, base64
      url          string  Document url (if sourceType is 'remote').
      payload      string  Base64 of the document (if sourceType is 'base64').
    }
  }
  prop0
  string
  Url from the pdf will be retrieved.
callback {
This is our standardized OpenAPI callback system. It enables the configuration of parameters for receiving notifications about status updates of asynchronous requests to this endpoint.
  method  enum     DEFAULT:JSON
                   ALLOWED:POST, JSON
                   Specify the callback method. When set to 'POST', a standard HTTP POST request will be initiated with the Content-Type header set to application/x-www-form-urlencoded. The JSON data will be encoded into a key-value pair named data (customizable using the field parameter) within the request body. If the method is set to 'JSON', a direct HTTP POST request will be made with the Content-Type header set to application/json. The raw JSON data will be directly inserted into the request body without any encoding.
  field   string   DEFAULT:data
                   This parameter works in conjunction with the 'method' parameter set to 'POST'. When provided as a string, it determines the name of the parameter that will be sent in the POST request.
  url*    string   A valid URL capable of handling POST requests must be entered into this parameter. For endpoints requiring authentication, the 'headers' parameter can be used to specify 'basic auth' or 'bearer auth'. The maximum timeout is 30 seconds. If 'retry' is set, the system will retry up to 'retry' times until a 200 status code is received.
  retry   integer  between 0 and 5
                   DEFAULT:0
                   The maximum number of attempts is defined by the 'retry' parameter. If the maximum number of attempts is reached without a successful status code (e.g., 200 OK), the request is considered a final failure. A time interval is often introduced between attempts to avoid overloading the server. This interval may increase exponentially with each attempt to reduce the impact on an overloaded server. The 'retry' parameter is configured to retry the request only in case of specific status codes, typically those indicating temporary errors (e.g., 502, 503) or network issues.
  headers {
  A collection of HTTP headers to be sent with the request. Each header is defined as a key-value pair. Headers can be used for various purposes, including authentication, content negotiation, and custom metadata.
    key  string
  }
  custom {
  This object can be populated with any additional data you wish to include in the callback response. This data will be accessible within the 'custom' parameter of the callback function. You can use this to store and retrieve any relevant information that you need for your application.
  }
}
options {
These are the optionals options to customize the ui visible to the final user or how they'll be signing.
  ui {
    sidebarBackgroundColor   string   PATTERN:^#[0-9a-fA-F]{6}$
                                      Change the color of the sidebar background
    sidebarTitleColor        string   PATTERN:^#[0-9a-fA-F]{6}$
                                      Change the color of the title sidebar
    sidebarTextColor         string   PATTERN:^#[0-9a-fA-F]{6}$
                                      Change the color of the sidebar text
    footerBackgroundColor    string   PATTERN:^#[0-9a-fA-F]{6}$
                                      Change the color of the footer background
    headerBackgroundColor    string   PATTERN:^#[0-9a-fA-F]{6}$
                                      Change the color of the header background
    headerTitleColor         string   PATTERN:^#[0-9a-fA-F]{6}$
                                      Change the color of the header title
    headerSubtitleColor      string   PATTERN:^#[0-9a-fA-F]{6}$
                                      Change the color of the header subtitle
```

buttonTextColor	string	PATTERN:^#[0-9a-fA-F]{6}$ Change the color of the button text
buttonTextColorHover	string	PATTERN:^#[0-9a-fA-F]{6}$ Change the color of the button text when you hover it
buttonBackgroundColor	string	PATTERN:^#[0-9a-fA-F]{6}$ Change the color of the button background
buttonBackgroundColorHover	string	PATTERN:^#[0-9a-fA-F]{6}$ Change the color of the button background when you hover it
signButtonTextColor	string	PATTERN:^#[0-9a-fA-F]{6}$ Change the color of the text of the sign button (the one that let you continue the procedure)
signButtonTextColorHover	string	PATTERN:^#[0-9a-fA-F]{6}$ Change the color of the text of the sign button when you hover it
signButtonBackgroundColor	string	PATTERN:^#[0-9a-fA-F]{6}$ Change the color of the background of the sign button (the one that let you continue the procedure)
signButtonBackgroundColorHover	string	PATTERN:^#[0-9a-fA-F]{6}$ Change the color of the background of the sign button when you hover it
sidebarLogo	string	Let you customize the logo shows on the top left corner, this will also be the logo shown on the email sent with the OTP (if email is the chosen authentication method)
hideSidebar	boolean	If true, the sidebar will be hidden
hideHeader	boolean	If true, the header will be hidden
hideDownloadValidated	boolean	If true, the button that lets you download the uploaded document will be hidden
hideDownloadSigned	boolean	If true, the button that lets you download the signed document will be hidden
iframeAncestors	[string]	
completeUrl	string	If evalueted, the complete button will be shown and let you redirect the final user to the url set
cancelUrl	string	If evalueted, the cancel button will be shown and let you redirect the final user to the url set

}

signatureMode [string]

userEditableData {

Choose if the signer(s) will be able to edit their data, change their name, the mobile phone or the email where the otp will be sent. By default these options are not required and will be set to true.

name	boolean	DEFAULT:true
mobile	boolean	DEFAULT:true
email	boolean	DEFAULT:true

}

timezone enum ALLOWED:Africa/Abidjan, Africa/Accra, Africa/Addis_Ababa, Africa/Algiers, Africa/Asmara, Africa/Bamako, Africa/Bangui, Africa/Banjul, Africa/Bissau, Africa/Blantyre, Africa/Brazzaville, Africa/Bujumbura, Africa/Cairo, Africa/Casablanca, Africa/Ceuta, Africa/Conakry, Africa/Dakar, Africa/Dar_es_Salaam, Africa/Djibouti, Africa/Douala, Africa/El_Aaiun, Africa/Freetown, Africa/Gaborone, Africa/Harare, Africa/Johannesburg, Africa/Juba, Africa/Kampala, Africa/Khartoum, Africa/Kigali, Africa/Kinshasa, Africa/Lagos, Africa/Libreville, Africa/Lome, Africa/Luanda, Africa/Lubumbashi, Africa/Lusaka, Africa/Malabo, Africa/Maputo, Africa/Maseru, Africa/Mbabane, Africa/Mogadishu, Africa/Monrovia, Africa/Nairobi, Africa/Ndjamena, Africa/Niamey, Africa/Nouakchott, Africa/Ouagadougou, Africa/Porto-Novo, Africa/Sao_Tome, Africa/Tripoli, Africa/Tunis, Africa/Windhoek, America/Adak,

America/Anchorage, America/Anguilla, America/Antigua, America/Araguaina, America/Argentina/Buenos_Aires, America/Argentina/Catamarca, America/Argentina/Cordoba, America/Argentina/Jujuy, America/Argentina/La_Rioja, America/Argentina/Mendoza, America/Argentina/Rio_Gallegos, America/Argentina/Salta, America/Argentina/San_Juan, America/Argentina/San_Luis, America/Argentina/Tucuman, America/Argentina/Ushuaia, America/Aruba, America/Asuncion, America/Atikokan, America/Bahia, America/Bahia_Banderas, America/Barbados, America/Belem, America/Belize, America/Blanc-Sablon, America/Boa_Vista, America/Bogota, America/Boise, America/Cambridge_Bay, America/Campo_Grande, America/Cancun, America/Caracas, America/Cayenne, America/Cayman, America/Chicago, America/Chihuahua, America/Ciudad_Juarez, America/Costa_Rica, America/Creston, America/Cuiaba, America/Curacao, America/Danmarkshavn, America/Dawson, America/Dawson_Creek, America/Denver, America/Detroit, America/Dominica, America/Edmonton, America/Eirunepe, America/El_Salvador, America/Fort_Nelson, America/Fortaleza, America/Glace_Bay, America/Goose_Bay, America/Grand_Turk, America/Grenada, America/Guadeloupe, America/Guatemala, America/Guayaquil, America/Guyana, America/Halifax, America/Havana, America/Hermosillo, America/Indiana/Indianapolis, America/Indiana/Knox, America/Indiana/Marengo, America/Indiana/Petersburg, America/Indiana/Tell_City, America/Indiana/Vevay, America/Indiana/Vincennes, America/Indiana/Winamac, America/Inuvik, America/Iqaluit, America/Jamaica, America/Juneau, America/Kentucky/Louisville, America/Kentucky/Monticello, America/Kralendijk, America/La_Paz, America/Lima, America/Los_Angeles, America/Lower_Princes, America/Maceio, America/Managua, America/Manaus, America/Marigot, America/Martinique, America/Matamoros, America/Mazatlan, America/Menominee, America/Merida, America/Metlakatla, America/Mexico_City, America/Miquelon, America/Moncton, America/Monterrey, America/Montevideo, America/Montserrat, America/Nassau, America/New_York, America/Nome, America/Noronha, America/North_Dakota/Beulah, America/North_Dakota/Center, America/North_Dakota/New_Salem, America/Nuuk, America/Ojinaga, America/Panama, America/Paramaribo, America/Phoenix, America/Port-au-Prince, America/Port_of_Spain, America/Porto_Velho, America/Puerto_Rico, America/Punta_Arenas, America/Rankin_Inlet, America/Recife, America/Regina, America/Resolute, America/Rio_Branco, America/Santarem, America/Santiago, America/Santo_Domingo, America/Sao_Paulo, America/Scoresbysund, America/Sitka, America/St_Barthelemy, America/St_Johns, America/St_Kitts, America/St_Lucia, America/St_Thomas, America/

St_Vincent, America/Swift_Current, America/Tegucigalpa, America/Thule, America/Tijuana, America/Toronto, America/Tortola, America/Vancouver, America/Whitehorse, America/Winnipeg, America/Yakutat, Antarctica/Casey, Antarctica/Davis, Antarctica/DumontDUrville, Antarctica/Macquarie, Antarctica/Mawson, Antarctica/McMurdo, Antarctica/Palmer, Antarctica/Rothera, Antarctica/Syowa, Antarctica/Troll, Antarctica/Vostok, Arctic/Longyearbyen, Asia/Aden, Asia/Almaty, Asia/Amman, Asia/Anadyr, Asia/Aqtau, Asia/Aqtobe, Asia/Ashgabat, Asia/Atyrau, Asia/Baghdad, Asia/Bahrain, Asia/Baku, Asia/Bangkok, Asia/Barnaul, Asia/Beirut, Asia/Bishkek, Asia/Brunei, Asia/Chita, Asia/Choibalsan, Asia/Colombo, Asia/Damascus, Asia/Dhaka, Asia/Dili, Asia/Dubai, Asia/Dushanbe, Asia/Famagusta, Asia/Gaza, Asia/Hebron, Asia/Ho_Chi_Minh, Asia/Hong_Kong, Asia/Hovd, Asia/Irkutsk, Asia/Jakarta, Asia/Jayapura, Asia/Jerusalem, Asia/Kabul, Asia/Kamchatka, Asia/Karachi, Asia/Kathmandu, Asia/Khandyga, Asia/Kolkata, Asia/Krasnoyarsk, Asia/Kuala_Lumpur, Asia/Kuching, Asia/Kuwait, Asia/Macau, Asia/Magadan, Asia/Makassar, Asia/Manila, Asia/Muscat, Asia/Nicosia, Asia/Novokuznetsk, Asia/Novosibirsk, Asia/Omsk, Asia/Oral, Asia/Phnom_Penh, Asia/Pontianak, Asia/Pyongyang, Asia/Qatar, Asia/Qostanay, Asia/Qyzylorda, Asia/Riyadh, Asia/Sakhalin, Asia/Samarkand, Asia/Seoul, Asia/Shanghai, Asia/Singapore, Asia/Srednekolymsk, Asia/Taipei, Asia/Tashkent, Asia/Tbilisi, Asia/Tehran, Asia/Thimphu, Asia/Tokyo, Asia/Tomsk, Asia/Ulaanbaatar, Asia/Urumqi, Asia/Ust-Nera, Asia/Vientiane, Asia/Vladivostok, Asia/Yakutsk, Asia/Yangon, Asia/Yekaterinburg, Asia/Yerevan, Atlantic/Azores, Atlantic/Bermuda, Atlantic/Canary, Atlantic/Cape_Verde, Atlantic/Faroe, Atlantic/Madeira, Atlantic/Reykjavik, Atlantic/South_Georgia, Atlantic/St_Helena, Atlantic/Stanley, Australia/Adelaide, Australia/Brisbane, Australia/Broken_Hill, Australia/Darwin, Australia/Eucla, Australia/Hobart, Australia/Lindeman, Australia/Lord_Howe, Australia/Melbourne, Australia/Perth, Australia/Sydney, Europe/Amsterdam, Europe/Andorra, Europe/Astrakhan, Europe/Athens, Europe/Belgrade, Europe/Berlin, Europe/Bratislava, Europe/Brussels, Europe/Bucharest, Europe/Budapest, Europe/Busingen, Europe/Chisinau, Europe/Copenhagen, Europe/Dublin, Europe/Gibraltar, Europe/Guernsey, Europe/Helsinki, Europe/Isle_of_Man, Europe/Istanbul, Europe/Jersey, Europe/Kaliningrad, Europe/Kirov, Europe/Kyiv, Europe/Lisbon, Europe/Ljubljana, Europe/London, Europe/Luxembourg, Europe/Madrid, Europe/Malta, Europe/Mariehamn, Europe/Minsk, Europe/Monaco, Europe/Moscow, Europe/Oslo, Europe/Paris, Europe/Podgorica,

		Europe/Prague, Europe/Riga, Europe/Rome, Europe/Samara, Europe/San_Marino, Europe/Sarajevo, Europe/Saratov, Europe/Simferopol, Europe/Skopje, Europe/Sofia, Europe/Stockholm, Europe/Tallinn, Europe/Tirane, Europe/Ulyanovsk, Europe/Vaduz, Europe/Vatican, Europe/Vienna, Europe/Vilnius, Europe/Volgograd, Europe/Warsaw, Europe/Zagreb, Europe/Zurich, Indian/Antananarivo, Indian/Chagos, Indian/Christmas, Indian/Cocos, Indian/Comoro, Indian/Kerguelen, Indian/Mahe, Indian/Maldives, Indian/Mauritius, Indian/Mayotte, Indian/Reunion, Pacific/Apia, Pacific/Auckland, Pacific/Bougainville, Pacific/Chatham, Pacific/Chuuk, Pacific/Easter, Pacific/Efate, Pacific/Fakaofo, Pacific/Fiji, Pacific/Funafuti, Pacific/Galapagos, Pacific/Gambier, Pacific/Guadalcanal, Pacific/Guam, Pacific/Honolulu, Pacific/Kanton, Pacific/Kiritimati, Pacific/Kosrae, Pacific/Kwajalein, Pacific/Majuro, Pacific/Marquesas, Pacific/Midway, Pacific/Nauru, Pacific/Niue, Pacific/Norfolk, Pacific/Noumea, Pacific/Pago_Pago, Pacific/Palau, Pacific/Pitcairn, Pacific/Pohnpei, Pacific/Port_Moresby, Pacific/Rarotonga, Pacific/Saipan, Pacific/Tahiti, Pacific/Tarawa, Pacific/Tongatapu, Pacific/Wake, Pacific/Wallis, UTC An identifier for a valid timezone, default setting will be UTC.
signerMustRead	boolean	If true, the signer will be forced to read the document before being able to sign it.

```
    }
  }
```

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
{
```

id	string	Signature's id.
errorNumber	undefined	Internal error number, if no error presents than it will be null.
errorMessage	undefined	Error message displayed if presents, if no error presents then it'll be null.
updatedAt	string	Update date.
createdAt	string	Creation date.
certificateType	string	Type of certificate.
state	string	Indicates the various possible states of the operation.
signatureType	string	Type of signature used for the operation. EU-SES only use pades.
signers [{ Array of object:		
authentication	[enum]	ALLOWED:email, sms
name	string	
surname	string	
state	string	
mobileEditable	boolean	
email	string	
emailEditable	boolean	
id	string	
url	string	
language	string	
message	string	

```
      signatures [{
      Array of object:
        page  integer
        x     integer
        y     integer
      }]
      emailValidation {
        domain       string
        host         string
        otpAttempts  integer
        mxRecords [{
        Array of object:
          host   string
          class  string
          ttl    integer
          type   string
          pri    integer
          target string
        }]
      }
    }]
    options {
    All the options for the operation, some are set to default if the caller didn't set them.
    }
    document {
    This object contains all details about the document passed with the call
    }
  }
```

STATUS CODE - 422: Validation exception. This error occurs if the request body fails semantic validation. Common reasons include:
- The 'signers' array is missing or empty.
- The 'inputDocuments' field is missing.
- A 'callback' object is provided but is malformed.
- An invalid value is passed within the 'options' object or the 'options' object isn't passed at all.

RESPONSE MODEL - application/json

```
{
  success  boolean
  message  string   One or more parameters are invalid
  error    integer  Internal error code
}
```

2.7 POST /verify

Verify a signature

Verify a signature by uploading the signed document. The system will return the verification result.

REQUEST

REQUEST BODY - application/json

```
{
  inputDocument*         string   Signed document
  detachedContent        string   Detached content
  pdfEncryptionPassword  string   Password for pdf encryption
  recursive              boolean  Recursive verification
  verifyOnDate           string   Date to verify the signature
```

```
}
```

RESPONSE

STATUS CODE - 200: Successful operation

RESPONSE MODEL - application/json

```
{
  data {
    Verification result
    checkDate                          string    Date of the verification
    verificationDate                   string    Date of the verification
    signatureFormat                    string    Format of the signature
    nrOfSignatures                     integer   Number of signatures
    overallVerified                    boolean   Overall verification result
    signatureReportList [{
      Array of object:
      id                               string    ID of the signature
      integrity                        boolean   Integrity verification result
      signatureAlgorithmName           string    Signature algorithm name
      subjectDN                        string    Subject DN
      issuerDN                         string    Issuer DN
      subjectCN                        string    Subject Common Name
      issuerCN                         string    Issuer Common Name
      serialNumber                     string    Serial number
      signerCertificateStatus          string    Signer certificate status
      signerCertificateNotBefore       string    Signer certificate not before
      signerCertificateNotAfter        string    Signer certificate not after
      signerCertificateRevocationDate  string    Signer certificate revocation date
      issuerCertificateStatus          string    Issuer certificate status
      issuerCertificateRevocationDate  string    Issuer certificate revocation date
      trustedSignatureDate             boolean   Trusted signature date indicates if the signatureDate is trusted
                                                 by a Trusted Authority by standard timestamp certificate
      signatureDate                    string    Signature date
      issuerTrustedList                boolean   Issuer is present on trusted list
      keySize                          integer   encryption Key size
      qcComplianceStatus               string    QC Compliance status
      qcSSCDStatus                     string    QC SSCD status
      derEncodedSignerCert             string    DER encoded signer certificate
    }]
    noteReportList [{
      Array of object:
      policy      integer  Policy Id
      about       integer  About Id
      type        integer  Type Id
      synopsis    string   Synopsis
      description string   Description
    }]
    plainDocument                      string    Plain document
  }
  message                    string    Message
  error                      string    Error code
  success                    boolean   Operation success
}
```

STATUS CODE - 400: Invalid input

STATUS CODE - 422: Validation exception

2.8 DELETE /signatures/{id}

Delete the signed Document, the details, audit Trail and the validatedDocument of a signature

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	ID of the signature

RESPONSE

STATUS CODE - 200: Deleted

STATUS CODE - 400: Invalid input

STATUS CODE - 404: Signature not found