FirstExercise

1.2 The first Repository

—> git init

```
> mkdir firstExercise
> cd firstExercise
> git init
Initialized empty Git repository in /Users/anaflorea/Desktop/FH/konfi/fi
ise/.git/

~/Desktop/FH/konfi/firstExercise  on main
```

1.3 Global config

```
> git condig --global user.name "anuchii"
git: 'condig' is not a git command. See 'git --help'.

The most similar command is
        config
> git config --global user.email "anaflorea1701@icloud.com"
> git config --global user.name "anuchii"
> git config --global --list

~/Desktop/FH/konfi/firstExercise  on main
>
```

1.4 Text file && 1.5 Status

```
> echo "first Text file in the repository" > firstTextFile.txt
> git status
On branch main

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        firstTextFile.txt

nothing added to commit but untracked files present (use "git add" to tr

~/Desktop/FH/konfi/firstExercise  on main ?1
> |
```

1.6. Put the file in the repository

```
> git add firstTextFile.txt

~/Desktop/FH/konfi/firstExercise  on main +1
>
```

1.7. SHA1 && 1.8 Search and output via SHA1

```
> git add firstTextFile.txt
> git hash-object firstTextFile.txt
20e4d267b7aaf424e6d43b2bd7298bc7bd08c077
> git ls-files  --stage
100644 20e4d267b7aaf424e6d43b2bd7298bc7bd08c077 0       firstTextFile.tx
> git cat-file -t 20e4d267b7
blob
> git cat-file -p 20e4d267b7
first Text file in the repository
> git cat-file -p 20e4d267b7aaf424e6d43b2bd7298bc7bd08c077
first Text file in the repository

~/Desktop/FH/konfi/firstExercise  on main +1
>
```

1.9 SHA1 Hello World

```
> echo "Hello World" | git hash-object --stdin
557db03de997c86a4a028e1ebd3a1ceb225be238

~/Desktop/FH/konfi/firstExercise  on main +1
> |
```

1.10 Save Hello World

```
> ls .git/objects
20   55   info pack
> ls .git/objects/20/
e4d267b7aaf424e6d43b2bd7298bc7bd08c077
> ls .git/objects/50/
ls: .git/objects/50/: No such file or directory
> ls .git/objects/55/
7db03de997c86a4a028e1ebd3a1ceb225be238
> git cat-file -p 20e4d267b7aaf42
first Text file in the repository
> git cat-file -p 557db03de997c86a
Hello World

~/Desktop/FH/konfi/firstExercise  on main +1
> |
```

1.11 Blobs

```
> git commit -m "first commit"
[main (root-commit) befab04] first commit
 1 file changed, 1 insertion(+)
 create mode 100644 firstTextFile.txt
```

```
~/Desktop/FH/konfi/firstExercise  on main
> git commit -a -m "mögliche nachricht für commit"
```

1.12 History output && 1.13 History

```
> git config --global alias.lol "log --graph --decorate --oneline --all"
> git config --global --list
> git lol
```

```
* befab04 (HEAD -> main) first commit
(END)
```

1.14 New File

```
* a87d7a5 (HEAD -> main) second commit
* d7a68a6 first commit
(END)
```

```
> echo fünfte Datei > fifthTextFile.txt
> git add fifthTextFile.txt
> git commit --amend --no-edit
[main 8ffd3d6] second commit
 Date: Tue Mar 3 10:13:55 2026 +0100
 4 files changed, 4 insertions(+)
 create mode 100644 fifthTextFile.txt
 create mode 100644 fourthTextFile
 create mode 100644 secondTextFile.txt
 create mode 100644 thridTextFile.txt
> git lol

~/Desktop/FH/konfi/firstExercise  on main
```

```
* 8ffd3d6 (HEAD -> main) second commit
* d7a68a6 first commit
(END)
```

1.16 Delete && 1.17 modify files

```
> rm fifthTextFile.txt
> git status
On branch main
Changes not staged for commit:
  (use "git add/rm <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        deleted:    fifthTextFile.txt

no changes added to commit (use "git add" and/or "git commit -a")

~/Desktop/FH/konfi/firstExercise  on main !1
>
```

```
> git restore fifthTextFile.txt
> git status
On branch main
nothing to commit, working tree clean

~/Desktop/FH/konfi/firstExercise  on main
```

1.18 Checkout

```
* 8ffd3d6 (HEAD -> main) second commit
* d7a68a6 first commit
(END)
```

```
> git checkout d7a68a6
Note: switching to 'd7a68a6'.

You are in 'detached HEAD' state. You can look around, make experimental
changes and commit them, and you can discard any commits you make in this
state without impacting any branches by switching back to a branch.

If you want to create a new branch to retain commits you create, you may
do so (now or later) by using -c with the switch command. Example:

  git switch -c <new-branch-name>

Or undo this operation with:

  git switch -

Turn off this advice by setting config variable advice.detachedHead to false

HEAD is now at d7a68a6 first commit

~/Desktop/FH/konfi/firstExercise  on @d7a68a62
```

```
> ls
firstTextFile.txt
```

```
* 8ffd3d6 (main) second commit
* d7a68a6 (HEAD) first commit
(END)
```

```
> git checkout main
Previous HEAD position was d7a68a6 first commit
Switched to branch 'main'
> ls
fifthTextFile.txt  fourthTextFile     thridTextFile.txt
firstTextFile.txt  secondTextFile.txt

~/Desktop/FH/konfi/firstExercise  on main
```