

# Music Recommender System using Apache Spark and Python

Estimated time: 8hrs

## Description

For this project, you are to create a recommender system that will recommend new musical artists to a user based on their listening history. Suggesting different songs or musical artists to a user is important to many music streaming services, such as Pandora and Spotify. In addition, this type of recommender system could also be used as a means of suggesting TV shows or movies to a user (e.g., Netflix).

To create this system you will be using Spark and the collaborative filtering technique. The instructions for completing this project will be laid out entirely in this file. You will have to implement any missing code as well as answer any questions.

### Submission Instructions:

- Add all of your updates to this IPython file and do not clear any of the output you get from running your code.
- Upload this file onto moodle.

## Datasets

You will be using some publicly available song data from audioscrobbler, which can be found [here](http://www-etud.iro.umontreal.ca/~bergstri/audioscrobbler_data.html) ([http://www-etud.iro.umontreal.ca/~bergstri/audioscrobbler\\_data.html](http://www-etud.iro.umontreal.ca/~bergstri/audioscrobbler_data.html)). However, we modified the original data files so that the code will run in a reasonable time on a single machine. The reduced data files have been suffixed with `_small.txt` and contains only the information relevant to the top 50 most prolific users (highest artist play counts).

The original data file `user_artist_data.txt` contained about 141,000 unique users, and 1.6 million unique artists. About 24.2 million users' plays of artists are recorded, along with their count.

Note that when plays are scribbled, the client application submits the name of the artist being played. This name could be misspelled or nonstandard, and this may only be detected later. For example, "The Smiths", "Smiths, The", and "the smiths" may appear as distinct artist IDs in the data set, even though they clearly refer to the same artist. So, the data set includes `artist_alias.txt`, which maps artist IDs that are known misspellings or variants to the canonical ID of that artist.

The `artist_data.txt` file then provides a map from the canonical artist ID to the name of the artist.

## Necessary Package Imports

```
In [1]: # Import libraries
        from pyspark.mllib.recommendation import *
        import random
        from operator import *
        from collections import defaultdict
```

## Loading data

Load the three datasets into RDDs and name them `artistData`, `artistAlias`, and `userArtistData`. View the README, or the files themselves, to see how this data is formatted. Some of the files have tab delimiters while some have space delimiters. Make sure that your `userArtistData` RDD contains only the canonical artist IDs.

```
In [2]: # Import test files from location into RDD variables
        artistData=sc.textFile('/Users/sachin/Google Drive/CSC 591 BI/Projects
        /Project 1-Recommender Systems/01.Apache.Spark.Project-1.RecommenderSy
        stems.FINAL/artist_data_small.txt')
        artistAlias=sc.textFile('/Users/sachin/Google Drive/CSC 591 BI/Project
        s/Project 1-Recommender Systems/01.Apache.Spark.Project-1.RecommenderS
        ystems.FINAL/artist_alias_small.txt')
        userArtistData=sc.textFile('/Users/sachin/Google Drive/CSC 591 BI/Proj
        ects/Project 1-Recommender Systems/01.Apache.Spark.Project-1.Recommend
        erSystems.FINAL/user_artist_data_small.txt')
```

## Data Exploration

In the blank below, write some code that will find the users' total play counts. Find the three users with the highest number of total play counts (sum of all counters) and print the user ID, the total play count, and the mean play count (average number of times a user played an artist). Your output should look as follows:

```
User 1059637 has a total play count of 674412 and a mean play count of 187
8.
User 2064012 has a total play count of 548427 and a mean play count of 945
5.
User 2069337 has a total play count of 393515 and a mean play count of 151
9.
```

```
In [3]: # Split a sequence into separate entities and store as int
artistData=artistData.map(lambda x: x.split("\t")).map(lambda x: (int(
x[0]), x[1]))
artistAlias=artistAlias.map(lambda x: x.split("\t")).map(lambda x: (in
t(x[0]), int(x[1])))
userArtistData = userArtistData.map(lambda x: x.split(" ")).map(lambda
x: (int(x[0]), int(x[1]), int(x[2])))

# Create a dictionary of the 'artistAlias' dataset
artistAliasDict = dict(artistAlias.collect())

# If artistid exists, replace with artistsid from artistAlias, else re
tain original
userArtistData = userArtistData.map(lambda x: (x[0], artistAliasDict[x
[1]], x[2]) if x[1] in artistAliasDict.keys() else x)

# Create an RDD consisting of 'userid' and 'playcount' objects of orig
inal tuple
userPlays=userArtistData.map(lambda x: (x[0],x[2]))

# Count instances by key and store in broadcast variable
userCount=sc.broadcast(userPlays.countByKey())

# Compute and display users with the highest playcount along with thei
r mean playcount across artists
topThreeUsers=userPlays.reduceByKey(lambda a,b: a+b).takeOrdered(3,key
=lambda x:-x[1])
for x in topThreeUsers:
    print('User %d has a total play count of %d and a mean play count
of %d.'%(x[0],x[1],x[1]/userCount.value[x[0]]))
```

User 1059637 has a total play count of 674412 and a mean play count of 1878.

User 2064012 has a total play count of 548427 and a mean play count of 9455.

User 2069337 has a total play count of 393515 and a mean play count of 1519.

## Splitting Data for Testing

Use the `randomSplit`

(<http://spark.apache.org/docs/latest/api/python/pyspark.html#pyspark.RDD.randomSplit>) function to divide the data (`userArtistData`) into:

- A training set, `trainData`, that will be used to train the model. This set should constitute 40% of the data.
- A validation set, `validationData`, used to perform parameter tuning. This set should constitute 40% of the data.
- A test set, `testData`, used for a final evaluation of the model. This set should constitute 20% of the data.

Use a random seed value of 13. Since these datasets will be repeatedly used you will probably want to persist them in memory using the `cache`

(<http://spark.apache.org/docs/latest/api/python/pyspark.html#pyspark.RDD.cache>) function.

In addition, print out the first 3 elements of each set as well as their sizes; if you created these sets correctly, your output should look as follows:

```
[(1059637, 1000049, 1), (1059637, 1000056, 1), (1059637, 1000113, 5)]
[(1059637, 1000010, 238), (1059637, 1000062, 11), (1059637, 1000112, 423)]
[(1059637, 1000094, 1), (1059637, 1000130, 19129), (1059637, 1000139, 4)]
19817
19633
10031
```

```
In [4]: # Split the 'userArtistData' dataset into training, validation and test datasets. Store in cache for frequent access
trainData, validationData, testData = userArtistData.randomSplit([4,4,2], seed=13)
trainData.cache()
validationData.cache()
testData.cache()

# Display the first 3 records of each dataset followed by the total count of records for each datasets
print trainData.take(3)
print validationData.take(3)
print testData.take(3)
print trainData.count()
print validationData.count()
print testData.count()

[(1059637, 1000049, 1), (1059637, 1000056, 1), (1059637, 1000113, 5)
]
[(1059637, 1000010, 238), (1059637, 1000062, 11), (1059637, 1000112, 423)]
[(1059637, 1000094, 1), (1059637, 1000130, 19129), (1059637, 1000139, 4)]
19817
19633
10031
```

# The Recommender Model

For this project, we will train the model with implicit feedback. You can read more information about this from the collaborative filtering page: <http://spark.apache.org/docs/latest/mllib-collaborative-filtering.html> (<http://spark.apache.org/docs/latest/api/python/pyspark/mllib.html#pyspark.mllib.recommendation.ALS.trainImplicit>). The function you will be using has a few tunable parameters that will affect how the model is built. Therefore, to get the best model, we will do a small parameter sweep and choose the model that performs the best on the validation set

Therefore, we must first devise a way to evaluate models. Once we have a method for evaluation, we can run a parameter sweep, evaluate each combination of parameters on the validation data, and choose the optimal set of parameters. The parameters then can be used to make predictions on the test data.

## Model Evaluation

Although there may be several ways to evaluate a model, we will use a simple method here. Suppose we have a model and some dataset of *true* artist plays for a set of users. This model can be used to predict the top X artist recommendations for a user and these recommendations can be compared the artists that the user actually listened to (here, X will be the number of artists in the dataset of *true* artist plays). Then, the fraction of overlap between the top X predictions of the model and the X artists that the user actually listened to can be calculated. This process can be repeated for all users and an average value returned.

For example, suppose a model predicted [1,2,4,8] as the top X=4 artists for a user. Suppose, that user actually listened to the artists [1,3,7,8]. Then, for this user, the model would have a score of  $2/4=0.5$ . To get the overall score, this would be performed for all users, with the average returned.

**NOTE: when using the model to predict the top-X artists for a user, do not include the artists listed with that user in the training data.**

Name your function `modelEval` and have it take a model (the output of `ALS.trainImplicit`) and a dataset as input. For parameter tuning, the dataset parameter should be set to the validation data (`validationData`). After parameter tuning, the model can be evaluated on the test data (`testData`).

```

In [5]: def modelEval(model, dataset):

    # All artists in the 'userArtistData' dataset
    allArtists = userArtistData.map(lambda x: x[1]).collect()

    # Set of all users in the current (Validation/Testing) dataset
    userArtists = set(dataset.map(lambda x: x[0]).collect())

    # Create a dictionary of (key, values) for current (Validation/Testing) dataset
    userArtistsDict = dict(dataset.map(lambda x: (x[0], x[1])).groupByKey().mapValues(set).collect())

    # Create a dictionary of (key, values) for training dataset
    userArtistTrain = dict(trainData.map(lambda x: (x[0], x[1])).groupByKey().mapValues(set).collect())

    # For each user, calculate the prediction score i.e. similarity between predicted and actual artists
    total = 0
    for key in userArtists:
        # Find the set of artists who are not in the training dataset
        nonTrainArtists = set(allArtists) - userArtistTrain[key]
        # Obtain artists actually listened to by the user
        origArtists = userArtistsDict[key]
        # Count of artists
        origArtistsCnt = len(origArtists)
        # Map user to each artists and create RDD
        userArtistTest = sc.parallelize(map(lambda x: (key, x), nonTrainArtists))
        # Predict top artists listen to by the user
        predArtists = model.predictAll(userArtistTest).sortBy(ascending=False, keyfunc = lambda x: x[2]).map(lambda x: x[1]).take(origArtistsCnt)
        # Add the score of the model
        total += (float(len(set(predArtists).intersection(origArtists))) / origArtistsCnt)

    # Print average score of the model for all users for the specified rank
    print "The model score for rank %d is %f"%(rank, float(total)/len(userArtists))

```

## Model Construction

Now we can build the best model possibly using the validation set of data and the `modelEval` function. Although, there are a few parameters we could optimize, for the sake of time, we will just try a few different values for the `rank` parameter (<http://spark.apache.org/docs/latest/mllib-collaborative-filtering.html#collaborative-filtering>) (leave everything else at its default value, **except make seed=345**). Loop through the values [2, 10, 20] and figure out which one produces the highest scored based on your model evaluation function.

Note: this procedure may take several minutes to run.

For each rank value, print out the output of the `modelEval` function for that model. Your output should look as follows:

```
The model score for rank 2 is 0.090431
The model score for rank 10 is 0.095294
The model score for rank 20 is 0.090248
```

```
In [6]: rankList = [2,10,20]
        for rank in rankList:
            model = ALS.trainImplicit(trainData, rank , seed=345)
            modelEval(model,validationData)
```

```
The model score for rank 2 is 0.093462
The model score for rank 10 is 0.097899
The model score for rank 20 is 0.084259
```

Now, using the `bestModel`, we will check the results over the test data. Your result should be  $\sim 0.0507$ .

```
In [7]: bestModel = ALS.trainImplicit(trainData, rank=10, seed=345)
        modelEval(bestModel, testData)
```

```
The model score for rank 20 is 0.061246
```



## Trying Some Artist Recommendations

Using the best model above, predict the top 5 artists for user 1059637 using the `recommendProducts` (<http://spark.apache.org/docs/1.5.2/api/python/pyspark.mllib.html#pyspark.mllib.recommendation.MatrixFactorizationModel.recommendProducts>) function. Map the results (integer IDs) into the real artist name using `artistAlias`. Print the results. The output should look as follows:

```
Artist 0: Brand New
Artist 1: Taking Back Sunday
Artist 2: Evanescence
Artist 3: Elliott Smith
Artist 4: blink-182
```

```
In [8]: # Find the top 5 artists for a particular user and list their names
topRating = bestModel.recommendProducts(1059637, 5)
artistRating = map(lambda x: x.product, topRating)
artistDataDict = dict(artistData.collect())
count = 0
for key in artistRating:
    print "Artist " + str(count) + ":", artistDataDict[key]
    count += 1
```

```
Artist 0: blink-182
Artist 1: Elliott Smith
Artist 2: Taking Back Sunday
Artist 3: Incubus
Artist 4: Death Cab for Cutie
```