



BSc (Hons) in **Information Technology**
Specialized in AI

IT3012 : Intelligent Agents

Year 3 · Semester 1 · 2026 Semester 2

Faculty of Computing

Practical 03

Objective & Lecture Mapping: In previous labs, we built a Simple Reflex Agent that moved randomly or reacted only to immediate adjacent cells. Today, we transition to a **Goal-Based/Planning Agent**. You will expose the environment's state space to the agent, allowing it to use **Breadth-First Search (BFS)**, **Depth-First Search (DFS)**, and **Uniform-Cost Search (UCS)** to simulate and find paths to the food before taking a physical action.

Part 1: Practical Implementation — Building the Search Agent

Step 1.1: Exposing the World Model

Classical search algorithms require an abstract model of the environment to simulate future states. Currently, your agent is "blind" to the overall map.

1. Create a new Branch called Week_03 in your Forked Github Repo and work on the below Questions.
2. Open `visual_grid_game.py` .
3. Locate the `get_percept(self)` method.
4. Add three new keys to the dictionary to pass the global state to the agent:

```
'grid_size': (self.width, self.height)
'walls': list(self.walls)
'all_food': list(self.food_positions)
```

Step 1.2: Implementing BFS, DFS, and UCS

You will implement three distinct uninformed search strategies. The core node expansion structure is identical; only the data structure for the **Frontier** changes!

1. Open `agent.py` and create a new class called `SearchAgent`.
2. Import required structures: `from collections import deque` and `import heapq`.
3. **BFS:** Create `def bfs_search(...)`. Use a FIFO queue (`deque.popleft()`). This explores the shallowest nodes first.
4. **DFS:** Create `def dfs_search(...)`. Use a LIFO stack (`list.pop()`). This explores the deepest nodes first.
5. **UCS:** Create `def ucs_search(...)`. Use a Priority Queue (`heapq.heappop()`) ordered by the total path cost $g(n)$.
6. For all three algorithms, you must maintain a `reached` set (or visited array) to track explored states. This converts your algorithm from a *Tree Search* to a *Graph Search*, preventing infinite loops.

Step 1.3: Executing and Comparing Offline Plans

The agent must now form a complete plan and execute it step-by-step.

1. In your `SearchAgent.__init__`, add an empty list: `self.plan = []` and a config string `self.active_algo = 'BFS'`.
2. In `sense_and_act(self, percept)`, check if `self.plan` is empty.
3. If empty, find the closest food pellet from `percept['all_food']`, execute the search method matching `self.active_algo`, and store the resulting sequence of actions in `self.plan`.
4. Return the first action from the plan using `return self.plan.pop(0)`.
5. **Observation Task:** Change `self.active_algo` between 'BFS', 'DFS', and 'UCS' and run the simulation. Watch how DFS takes erratic, winding paths, while BFS and UCS take direct, optimal paths!

Part 2: Theoretical Evaluation

Based on your implementation and Lecture 04, complete the following analytical questions.

1. (Remember) You built your search logic based on the environment coordinates. What is the fundamental difference between the "State Space" and the "Search Tree"?

State Space - Mathematical representation of the environment itself. It is the set of all physically distinct configurations and transitions between them. It is a static graph that exists independently in the algorithm.

Search tree - A data structure generated in memory by the search algorithm as it executes. Nodes in the search tree represent paths taken from the start state, not just physical locations. Because multiple paths can lead to the exact same physical location a single state from the state space can appear multiple times as different nodes in the search tree.

2. (Understand) In Step 1.2, you were instructed to use a `reached` set. In graph search theory, what specific problem does this set solve, and what would happen to your DFS agent without it?

Problem solved - The visited set upgrades the algorithm from a Tree Search to a Graph Search. It prevents the algorithm from processing redundant paths by ensuring that a physical state is only ever expanded once.

DFS agent without it - Without a reached set a DFS agent would follow a path back to a state it just came from getting trapped in an infinite loop. It would run forever and would never find the food.

3. (Analyze) Compare the visual paths generated by BFS and DFS in your simulation. Why is BFS guaranteed to be optimal in this specific grid, whereas DFS produces winding, suboptimal routes?

BFS Optimality - BFS expands the search tree level by level meaning it checks all paths of length d before looking at any paths of length $d+1$. Because every movement in your grid costs exactly the same (step cost = 1), the very first time BFS encounters the goal, it is mathematically guaranteed to be the shortest possible path.

DFS Suboptimality: DFS explores the deepest nodes first. It blindly plunges down a single branch of the search tree until it hits a dead end, backtracking only

when necessary. It makes no attempt to evaluate distance and simply returns the first path it finds to the food, which is almost always a winding, highly suboptimal route.

4. (Evaluate) If we scaled `visual\_grid\_game.py` up to a massive 1000x1000 grid, BFS and UCS might crash before finding food. According to the time and space complexity formulas from the lecture, contrast the memory bottlenecks of BFS versus DFS.

BFS Space Complexity - BFS has a space complexity of $O(b^d)$ where b is the branching factor and d is the depth. It must store the entire frontier of the search in memory at once. In a massive grid, the perimeter of the search grows exponentially which would quickly exhaust the computer's RAM before finding distinct food.

DFS Space Complexity - DFS is incredibly memory efficient with a space complexity of $O(b \cdot m)$. It only needs to store the current single path it is exploring and the unexpanded siblings along that path. DFS may take longer to find the goal in a massive grid, but it uses less memory and avoids BFS's memory limitations.

Once Completed Get a PDF of the completed File and Push into the Week 03 brach in the Github Project

Finalize and Lock Lab 03 Documentation

Incomplete: 0/11 questions answered. Please provide detailed responses for all questions.



FACULTY OF COMPUTING