



BLUE STAR



Refrigeration Systems Hermetic Series

It's not just preservation.
It's the ultimate in preservation.

Blue Star, India's leading refrigeration company, offers a complete range of evaporating and condensing units. These units are designed to deliver superior cooling for food preservation and are equipped to deliver temperatures for various applications.

The balanced selection of the evaporator and condensing units assures delivery of capacity. The matching controllers with refrigeration units support each installation and enable the controlling and monitoring of temperature. Each Blue Star installation comes with a weather-proof power panel that allows for easy, speedy, safe and long-lasting power connection. So when it comes to cold storage, trust in the experts for reliable, efficient and trouble-free refrigeration.





Evaporating Units

Blue Star's evaporators are compact and sleek. The evaporator is housed within the cold storage and occupies minimum space. This allows you to utilise the maximum volume of cold storage.

Features:



Stainless steel body (SS304) for enhanced durability and strength



Improved air throw for uniform air distribution



Excellent corrosion resistance



External rotor driven fans have low noise levels and conform to IP45 standards



Inner grooved copper tubes for superior heat transfer



Removable side panels for easy service and minimum downtime



4 FPI coil for low temperature units



Defrost heaters within the coil to ensure total defrost



Condensing Units

Blue Star's condensing units are characterised by high-efficiency heat transfer and low power consumption.



Features:



Energy-efficient scroll and reciprocating compressors



Pre-charged unit with service valves



Powder coated body makes these units UV and corrosion-resistant



Safety and control devices for better system protection



Inner grooved copper tubes and slit aluminium fins for superior heat transfer



Weather-proof polyester powder coated canopy



Filter drier for moisture and dirt protection



Thermally protected and permanently lubricated fan motors



Smaller footprint for ease of handling and installation



Controller



Blue Star's controller is a two compressor controller with separate set points and differentials for each compressor.

Features:

- Specifically designed for refrigeration applications
- Controls compressor cut off and temperature
- HACCP provision (available in model 52H)
- BMS compatibility (available in model 52H)

Power Panel

Blue Star's Refrigeration Units come with ready-to-use power panels that make electrical connections simple, fast and long-lasting.

Features:

- Embedded switchgear in the Positive Temperature Condensing Unit
- Power Panel with necessary accessories and defrost controls is available for Negative Temperature Units



Technical Specifications

High Temperature Air-cooled Refrigeration System with R404A Refrigerant

Blue Star Indoor Unit		Cooling Capacities @ +4°C Room Temperature & 35°C Ambient Temperature									
Description / Model	Units	RUAHI-0614	RUAHI-1014	RUAHI-1514	RUAHI-2014	RUAHI-3014-N	RUAHI-4014-N	RUAHI-6024-N	RUAHI-6014-N	RUAHI-8024-N	RUAHI-8014-N
Nominal Capacity	Btu/hr	6,000	10,000	15,000	20,000	30,000	40,000	60,000	60,000	80,000	80,000
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50	415/3/50
Airflow	CFM	800	1,600	2,400	3,200	4,500	5,200	12,000	12,000	11,700	11,700
Air Throw	Feet	12	12	12	12	25	40	45	45	45	45
No. of Circuits	Nos.	1	1	1	1	1	1	2	1	2	1
Overall Dimensions (W x D x H)	mm	864 x 480 x 450	1245 x 480 x 450	1780 x 480 x 450	2210 x 480 x 450	1710 x 645 x 720	1710 x 645 x 720	2140 x 840 x 925	2140 x 840 x 925	2140 x 840 x 925	2140 x 840 x 925
Dry Weight	kgs	18	25	35	45	72	82	140	140	150	150

Blue Star Outdoor Unit		Cooling Capacities @ +4°C Room Temperature & 35°C Ambient Temperature									
Description / Model	Units	RUAHOP-0614	RUAHOP-1014	RUAHOP-1514	RUAHOS-2014	RUAHOS-3014	RUAHOS-4014	RUAHOS-3014	RUAHOS-6014	RUAHOS-4014	RUAHOS-8014
Compressor Type	-	Hermetic Recip	Hermetic Recip	Hermetic Recip	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1	1	1	1	1	1	1
No. of such Chassis	Nos.	1	1	1	1	1	1	2	1	2	1
Each Chassis Overall Dimensions (W x D x H)	mm	940 x 350 x 560	940 x 350 x 560	940 x 350 x 560	1100 x 444 x 658	1100 x 444 x 1259	1100 x 444 x 1259	1100 x 444 x 1259	1435 x 635 x 947	1100 x 444 x 1259	1435 x 635 x 947
Each Chassis Dry Weight	kgs	50	51	80	105	126	130	126	185	130	190
Each Chassis Refrigerant Precharged Qty	kgs	1.2	1.6	2.0	2.5	3.5	4.0	3.5	8.0	4.0	9.0

Note: Specifications are subject to change without prior notice.

Refrigeration capacity is based on standard rated conditions.

Low Temperature Air-cooled Refrigeration System with R404A Refrigerant

Blue Star Indoor Unit		Cooling Capacities @ -23°C Room Temperature & 35°C Ambient Temperature				
Description / Model	Units	RUAL00614-I-N	RUAL00914-I-N	RUAL01214-I-N	RUAL01814-I-N	RUAL02414-I-N
Nominal Capacity	Btu/Hr	6,000	9,000	12,000	18,000	24,000
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Airflow	CFM	1600	2400	3200	5500	11700
Air Throw	feet	12	12	12	40	45
Overall Dimensions (WxDxH)	mm	1250 x 480 x 440	1780 x 480 x 440	2210 x 480 x 440	1710 x 645 x 720	2140 x 840 x 925
Dry Weight	kgs	37	45	58	89	135

Blue Star Outdoor Unit		Cooling Capacities @ -23°C Room Temperature & 35°C Ambient Temperature			
Description / Model	Units	RUAL00614S-O	RUAL00914S-O	RUAL01214S-O	RUAL01814S-O
Compressor Type	-	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Condenser Type	-	MCHX	MCHX	MCHX	MCHX
Power Supply	V/Ph/Hz	415/3/50	415/3/50	415/3/50	415/3/50
Overall Dimensions (WxDxH)	mm	1125 x 450 x 735	1125 x 450 x 735	1125 x 450 x 735	1125 x 450 x 965
Gross Weight	kgs	105	115	117	135
Refrigerant pre Charged Qty	kgs	2.5	3	4	5

Technical Specifications

High Temperature Air-cooled Refrigeration System with R22 Refrigerant

Blue Star Indoor Unit		Cooling Capacities @ +4°C Room Temperature & 35°C Ambient Temperature								
Description / Model	Units	RUAHI-0612	RUAHI-1012	RUAHI-1512	RUAHI-2012	RUAHI-3012-N	RUAHI-4012-N	RUAHI-6022-N	RUAHI-8022-N	RUAHI-8012-N
Nominal Capacity	Btu/hr	6,000	10,000	15,000	20,000	30,000	40,000	60,000	80,000	80,000
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50
Airflow	CFM	800	1,600	2,400	3,200	4,500	5,200	12,000	11,700	11,700
Air Throw	Feet	12	12	12	12	25	40	45	45	45
No. of Circuits	Nos.	1	1	1	1	1	1	2	2	1
Overall Dimensions (W x D x H)	mm	864 x 480 x 450	1245 x 480 x 450	1780 x 480 x 450	2210 x 480 x 450	1710 x 645 x 720	1710 x 645 x 720	2140 x 840 x 925	2140 x 840 x 925	2140 x 840 x 925
Dry Weight	kgs	18	25	35	45	72	82	140	150	150

Blue Star Outdoor Unit		Cooling Capacities @ +4°C Room Temperature & 35°C Ambient Temperature								
Description / Model	Units	RUAHOP-0612	RUAHOP-1012	RUAHOP-1512	RUAHOP-2012	RUAHOS-3012	RUAHOS-4012	RUAHOS-6022	RUAHOS-8022	RUAHOS-8012
Compressor Type	-	Hermetic Recip	Hermetic Recip	Hermetic Recip	Hermetic Recip	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll	Hermetic Scroll
Power Supply	V/Ph/Hz	230/1/50	230/1/50	230/1/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50	415/3/50
Comp. Quantity	Nos.	1	1	1	1	1	1	1	1	1
No. of such Chassis	Nos.	1	1	1	1	1	1	2 x RUAHOS-3012	2 x RUAHOS-4012	1
Each Chassis Overall Dimensions (W x D x H)	mm	940 x 350 x 560	940 x 350 x 560	940 x 350 x 560	1100 x 444 x 658	1100 x 444 x 1259	1100 x 444 x 1259	1100 x 444 x 1259	1100 x 444 x 1259	1454 x 632 x 947
Each Chassis Dry Weight	kgs	51	61	80	110	125	125	125	125	185
Each Chassis Refrigerant Precharged Qty	kgs	1.2	1.6	2.0	2.5	3.5	4.0	3.5	4.0	9.0

Note: Specifications are subject to change without prior notice.
Refrigeration capacity is based on standard rated conditions.



Scan QR Code -
Blue Star Customer
Care Mobile App



SMS "SERVICE" to 57575



Download Blue Star Customer
Care Mobile App from
App Store & Google Play



To know more about Blue Star, visit
www.bluestarindia.com, email us at
coolingsolutions@bluestarindia.com
or SMS 'COOL' to 57575



24X7 CUSTOMER CARE
(Toll Free) 1800 209 1177
1860 266 6666



Blue Star products comply with RoHS regulations as per E-Waste (Management & Handling) Rules, 2016. For disposal of E Waste, kindly visit our website www.bluestarindia.com or call our customer care 1800 209 1177 (Toll Free) or 1860 266 6666.