

MEGA SPLIT AC



BLUE STAR

AAMU



AVAILABLE IN 2.5 Tr. 3.0 Tr.

100%
COPPER

1 YEAR
WARRANTY
on Inverter Compressor

Technology/Cooling



iFeel



3 Phase Advantage



4 Cooling Modes

User Comfort



Comfort Sleep



Turbo Cool



Wide Angle,
Powerful Air Flow

User Convenience



Anti-Corrosive Gold
Fins for Protection



Smart Detect
Technology



Hidden Display

Technical Specifications

| SKU Code/Model Number | | FMA30AAMUP3 | FMA36AAMUP3 |
|---|--|----------------------|----------------------|
| Performance Parameters | Nominal Capacity (Tr) as per BEE | 2.5 Tr | 3 Tr |
| | Star Rating – As Per BEE | – | – |
| | (Rated) Voltage / Frequency / Phase | 415 V / 50 Hz / 3 Ph | 415 V / 50 Hz / 3 Ph |
| | Cooling Capacity (Watt) | 8792 | 10551 |
| | Cooling Capacity (BTU/Hr) | 29998 | 36000 |
| | Cooling Rated Power Input (Watt) | 3000 | 3300 |
| | ISEER | 2.93 | 3.20 |
| | Electricity Consumed In 1600 Hours. (Units/Year) | 2322.32 | 2554.55 |
| | Nominal Current (Cooling In Amps) | 5.7 | 6.8 |
| | Air Flow Volume (Wet CFM) (High / Medium / Low) | 770 / 690 / 550 | 770 / 690 / 550 |
| Compressor, Refrigerant & Ambient Operations | Noise Level Indoor (High/ Medium/ Low) In dB(A) | 51.6 / 48.2/ 43.5 | 51.6 / 48.2/ 43.5 |
| | Moisture Removal (Litres/Hour) | 3.38 | 4.73 |
| | Compressor Type | Reciprocating | Reciprocating |
| | Compressor Warranty | 1 Year | 1 Year |
| | Refrigerant | R 22 | R 22 |
| | Ambient Temp (Cooling) °C | 50°C | 50°C |
| User Interface – Remote | Remote | LCD Remote | LCD Remote |
| | Night Glow Function On Remote Buttons | Yes | Yes |
| Product Dimensions, Weight & Input Power Supply | IDU Dimension (W X H X D) mm | 1260 x 360 x 280 | 1260 x 360 x 280 |
| | Input Power Supply | Outdoor Unit | Outdoor Unit |
| | Net Weight IDU | 21.2 Kg | 21.2 Kg |
| | ODU Dimension (W X H X D) mm | 1075 x 655 x 470 | 1075 x 655 x 470 |
| | Net Weight ODU | 66 Kg | 69 Kg |
| | Noise Level Outdoor In dB(A) | 68 | 68 |
| Tube Size & Piping Capability | Suction Tube Size Outer Diameter Inch (mm) | 5/8" (15.88mm) | 5/8" (15.88mm) |
| | Liquid Tube Size Outer Diameter Inch (mm) | 3/8" (9.52mm) | 3/8" (9.52mm) |
| | Max Piping Capability Total (metre) | 20 | 20 |
| | Max Piping Capability Vertical (metre) | 10 | 10 |
| | Refrigerant Additional Charge Beyond 5M (g/m) | 15 | 15 |

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and actual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.



Scan QR Code -
Blue Star Customer
Care Mobile App



SMS "SERVICE" to 57575



Download Blue Star Customer
Care Mobile App from
App Store & Google Play



To know more about Blue Star, visit
www.bluestarindia.com, email us at
coolingsolutions@bluestarindia.com
or SMS 'COOL' to 57575

