

0: title**Agent0: Unleashing Self-Evolving Agents from Zero Data via Tool-Integrated Reasoning****1: plain text**

Peng Xia¹ Kaide Zeng¹ Jiaqi Liu¹ Can Qin² Fang Wu³ Yiyang Zhou¹ Caiming Xiong² Huaxiu Yao¹

2: title**3: abandon plain text**

Large Language Model (LLM) Agents, often trained with Reinforcement Learning (RL), are constrained by a dependency on human-curated data, limiting scalability and tethering AI to human knowledge. Existing self-evolution frameworks offer an alternative but are typically restricted by the model's inherent capabilities and single-round interactions, hindering the development of complex curricula involving tool use or dynamic reasoning. We introduce Agent0, a fully autonomous framework that evolves high-performing agents without external data through multi-step co-evolution and seamless tool integration. Agent0 establishes a symbiotic competition between two agents initialized from the same base LLM: a curriculum agent that proposes increasingly challenging frontier tasks, and an executor agent that learns to solve them. We integrate external tools to enhance the executor's problem-solving capacity; this improvement, in turn, pressures the curriculum agent to construct more complex, tool-aware tasks. Through this iterative process, Agent0 establishes a self-reinforcing cycle that continuously produces high-quality curricula. Empirically, Agent0 substantially boosts reasoning capabilities improving the Qwen3-8B-Base model by 18% on mathematical reasoning and 24% on general reasoning benchmarks. Code is available at <https://github.com/aiming-lab/Agent0>.

6: title**7: plain text**

Large Language Model (LLM) Agents have shown remarkable capabilities in tackling complex, long-horizon problems (Qiu et al., 2025b;a; Jin et al., 2025; Yu et al.

25: Zhai et al., 2025) that require

8: abandon

¹UNC-Chapel Hill ²Salesforce Research ³Stanford University
Correspondence to: Peng Xia <pxia@cs.unc.edu>, Huaxiu Yao

9: abandon

Preliminary work

11: plain text

extensive interaction with an environment, such as deep research (OpenAI, 2025; Google, 2024; Team et al., 2025) and agentic coding (Jimenez et al., 2023; Anthropic, 2025; Wang et al., 2024a). To optimize these complex, multi-step interactions and move beyond hard-coded workflows, Reinforcement Learning (RL) has emerged as a principal training paradigm (Ouyang et al., 2022; Shao et al., 2024; Tu et al., 2025), achieving significant progress on complex reasoning tasks. However, the efficacy of these methods, whether Reinforcement Learning from Human Feedback (RLHF) or Reinforcement Learning from Verifiable Rewards (RLVR), relies heavily on massive, high-quality, human-curated datasets (Zhang et al., 2025c). This dependency not only creates a severe scalability bottleneck (Yue et al., 2025), which is time-consuming, labor-intensive, and costly, but also fundamentally tethers the potential of AI to

12: plain text

age and annotation speed. To break free from this reliance on human data, self-evolution frameworks have emerged as a promising alternative (Zhao et al., 2025; Liu et al., 2025a; Huang et al., 2025; Wang et al., 2025d), offering a scalable pathway by enabling models to autonomously generate their own training data. Yet, despite their potential, existing self-play or self-challenging approaches face severe constraints. First, their capabilities are capped by the model's inherent knowledge and reasoning abilities (Fang et al., 2025; Cheng et al., 2024; Zhou et al., 2025a), causing the generated tasks to rarely surpass the model's current complexity (Zhou et al., 2025b) leading to learning stagnation. Second, these frameworks typically operate only in single-round interactions (Li et al., 2025c), failing to capture the dynamic, context-dependent nature of real-world problems. This dual limitation not only restricts the complexity of the self-generated curriculum but more critically, hinders the model from mastering essential


13: plain text

tool use or multi-step reasoning. To address these challenges, as demonstrated in Figure 1, we introduce Agent0, a fully autonomous framework designed to guide the evolution of agents entirely from scratch. Agent0 completely eliminates the dependence on any external data or human annotations, pioneeringly combining tool integration with multi-round co-evolution. The framework's implementation begins with a base LLM from which

10: abandon

1: figure_caption

2: figure



3: figure_caption


Figure 1. The Agent 0 autonomous co-evolution framework. The Curriculum Agent (left) uses RL to generate frontier tasks, rewarded by the Executor Agent’s uncertainty and tool-use frequency. The Executor Agent (right) learn to solve them by RL. This shared tool cycle, spiraling up task complexity and a scratch.

4: plain_text

we initialize two functionally distinct agents: *an executor agent* and *a curriculum agent*. These agents co-evolve through a symbiotic competition: the curriculum agent is trained using RL (Shao et al., 2024) to propose frontier tasks that precisely challenge the executor’s current capabilities, using the executor’s uncertainty (*i.e.*, self-consistency across multiple answers) and its frequency of tool use as reward signals. Concurrently, the executor agent is trained via RL to successfully solve these tasks, optimizing on a filtered set of challenging problems generated by the frozen curriculum agent and using pseudo-labels derived from its own majority voting. Equipping the executor with a tool enhances its problem-solving abilities, which in turn compels the tool-equipped curriculum agent to generate more complex, tool-based curricula. This establishes a virtuous cycle, driving a synchronous spiral of improvement in both agent capability and curriculum complexity. Furthermore we extend this paradigm to support multi-turn interactions enabling the generation of context-rich, conversational tasks

5: plain_text

The primary contribution of this paper is Agent 0, a novel framework that autonomously evolves LLM agents from scratch through tool-augmented reasoning without relying on any external data. Across ten benchmarks spanning mathematical and general reasoning, empirical results show that Agent 0 achieves substantial model agnostic capability gains, improving mathematical reasoning performance by 18% and general reasoning performance by 24%. In addition, our analysis confirms this gain is driven by our co-evolutionary loop, where the curriculum agent learns to generate progressively complex tasks, creating a virtuous



8: plain_text

cycle of the executor’s capability improvement

9: title

10: plain_text

LLM as a Policy Agent. We formulate the LLM as an agent, represented by a policy π_θ with parameters θ . Given a prompt x , the agent autoregressively generates a response $y \sim \pi_\theta(\cdot|x)$. The general objective of reinforcement learning is to optimize θ to maximize the expected reward $E[r(y|x)]$.

11: plain_text

Group Relative Policy Optimization (GRPO). GRPO (Shao et al., 2024) is a reinforcement learning method that avoids training a critic by using intra-group relative rewards. For each prompt x , the model samples G responses $\{y_1, \dots, y_G\}$, which are scored to get rewards $\{r_1, \dots, r_G\}$. GRPO computes normalized advantages \hat{A}_i using a z-score: $\hat{A}_i = \frac{r_i - \max\{r_j\}_{j=1}^G}{\text{std}\{\{r_j\}_{j=1}^G\} + \epsilon_{\text{norm}}}$, where ϵ_{norm} is a small constant for numerical stability. The policy is then updated by minimizing the following PPO-style clipped

13: isolate_formula

$$\mathcal{L}_{\text{GRPO}}(\theta) = -\frac{1}{G} \sum_{i=1}^G \min \left(\frac{\pi_\theta(x_i)}{\pi_{\theta_{\text{old}}}(x_i)} \hat{A}_i, \text{clip} \left(\frac{\pi_\theta(x_i)}{\pi_{\theta_{\text{old}}}(x_i)}, 1 - \epsilon, 1 + \epsilon \right) \hat{A}_i \right) + \beta \text{KL}(\pi_\theta \| \pi_{\theta_{\text{old}}}).$$

14: plain_text


where $\frac{\pi_\theta(x_i)}{\pi_{\theta_{\text{old}}}(x_i)}$ is the importance sampling ratio between the current policy π_θ and the reference policy $\pi_{\theta_{\text{old}}}$ from the previous iteration. \hat{A}_i is the normalized advantage, and ϵ are clipping parameters. The KL-divergence term acts

7: abandon

12: formula

0: abandon

1: figure



2: figure_caption

Figure 2. The Agent0 co-evolutionary loop. (1) Curriculum Evolution: The Curriculum Agent π_θ is trained via RL to generate tasks, maximizing a reward R_C based on executor Uncertainty R_{unc} , Tool Use R_{tool} and Repetition Penalty R_{rep} . (2) Executor Evolution: Tasks are filtered by self-consistency score \hat{p} to create a challenging dataset $D^{(t)}$. The Executor Agent π_ϕ is then trained on $D^{(t)}$ via ADPO, an ambiguity-aware RL method using majority-vote pseudo-labels \hat{y} .

3: plain_text

use a repetition penalty to stabilize training

4: title

5: title **Agent0 Framework**

6: plain_text

Agent0 is a fully autonomous, iterative co-evolutionary framework designed to enhance the capabilities of LLM agents without relying on any human-annotated data. At the core of this framework are two functionally distinct agents initialized from the same base LLM, π_{base} : (1) **Curriculum Agent** (π_θ) aims to generate frontier tasks that are appropriately challenging for the current Executor Agent; (2) **Executor Agent** (π_ϕ) aims to solve the increasingly challenging tasks generated by the Curriculum Agent.

7: plain_text

These two agents co-evolve iteratively through a process of symbiotic competition, as illustrated in Figure 2. Each iteration is divided into two stages:

Curriculum Evolution. We train the Curriculum Agent π_θ using RL to specialize in generating tasks that challenge the Executor Agent $\pi_\phi^{(t-1)}$.

Executor Evolution. We use the frozen Curriculum Agent $\pi_\theta^{(t)}$ to generate a pool of tasks, from which we filter a challenging dataset $D^{(t)}$. We then train the Executor Agent $\pi_\phi^{(t)}$, evolving it into $\pi_\phi^{(t)}$.

The integration of a code interpreter tool establishes a virtuous cycle: the Executor Agent's problem-solving capabilities are enhanced by the tool, which in turn compels the tool-equipped Curriculum Agent to generate more complex, tool-based curricula. Furthermore, the framework supports

12: plain_text

multi-turn interactions, enabling the Curriculum Agent to generate context-rich, conversational tasks that better reflect real-world problem-solving.

13: title

14: plain_text

The goal of the Curriculum Agent π_θ , is to generate a prompt x that maximizes a composite reward signal R_C . This reward signal is designed to quantify the challenge of task x for the current Executor Agent π_ϕ . We optimize π_θ using

15: plain_text

For each task x_i generated by π_θ , we compute its reward by sampling k responses $\{y_{i,j}\}_{j=1}^k$ from the current Executor π_ϕ .

16: plain_text

This consists of two key components: **Uncertainty Reward**. This reward incentivizes the Curriculum Agent to generate tasks that the Executor finds confusing or uncertain (Shi et al., 2025; Bae et al., 2025). We use the Executor's self-consistency $\hat{p}(x; \pi_\phi)$ as a proxy for uncertainty. \hat{p} is defined as the proportion of the k responses that vote for the majority answer (\hat{y}). The reward function is designed to be maximized when $\hat{p} = 0.5$, where

17: formula

18: isolate_formula

19: plain_text

$-2|\hat{p}(x; \pi_\phi) - 0.5|$

This function penalizes tasks that are either too easy ($\hat{p} \rightarrow 1$)

20: plain_text

Tool Use Reward. To drive the virtuous cycle, we must explicitly reward tasks that prompt the Executor to use its tool. We define R_{tool} based on the number of tool invocations, identified by the tool response marker, i.e., ``output'' within a complete prediction $y = \pi_\phi(x)$. Let $N_{tool}(y)$ be

21: abandon

O: abandon

1: table

Algorithm 1 Self-Evolutionary Framework Agent0

Require: Base LLM π_{base} ; Iterations T ; Samples k .

- 1: Initialize $\pi_\theta^{(0)} \leftarrow \pi_{\text{base}}$ and $\pi_\phi^{(0)} \leftarrow \pi_{\text{base}}$.
- 2: **for** each iteration $t = 1, \dots, T$ **do**
- 3: ▷ *Curriculum Evolution (Train π_θ)*
- 4: Initialize $\pi_\theta \leftarrow \pi_\theta^{(t-1)}$.
- 5: Generate a batch of tasks $X = \{x_i\} \sim \pi_\theta$.
- 6: **for** task $x_i \in X$ **do**
- 7: Sample k responses $\{y_j\}_{j=1}^k \sim \pi_\phi^{(t-1)}(x_i)$.
- 8: Compute $R_C(x_i)$ using Eq. 5.
- 9: **end for**
- 10: Update π_θ using $\mathcal{L}_{\text{GRPO}}$ with $(X, R_C) \rightarrow \pi_\theta^{(t)}$.
- 11: ▷ *Executor Evolution (Train π_ϕ)*
- 12: Generate $X_{\text{pool}} \sim \pi_\theta^{(t)}$ and filter to $\mathcal{D}^{(t)} = \{(x, \hat{p}, \bar{y})\}$ where $|\hat{p}(x) - 0.5| \leq \delta$.
- 13: Initialize $\pi_\phi \leftarrow \pi_\phi^{(t-1)}$.
- 14: **for** batch $B_D = \{(x, \hat{p}(x), \bar{y})\} \sim \mathcal{D}^{(t)}$ **do**
- 15: Initialize $\mathcal{T}_{\text{batch}}, \bar{\mathcal{A}}_{\text{batch}}, \mathcal{P}_{\text{batch}}$.
- 16: **for** $(x, \hat{p}(x), \bar{y}) \in B_D$ **do**
- 17: Sample k trajectories $\{\tau_i\}_{i=1}^k \sim \pi_\phi(x)$.
- 18: Compute rewards $R_i = \mathbb{I}(o_i = \bar{y})$.
- 19: Compute scaled advantages $\bar{A}_i \leftarrow A_i \cdot f(\hat{p}(x))$.
- 20: Add $\{\tau_i\}$ to $\mathcal{T}_{\text{batch}}$, $\{\bar{A}_i\}$ to $\bar{\mathcal{A}}_{\text{batch}}$, $\hat{p}(x)$ to $\mathcal{P}_{\text{batch}}$.
- 21: **end for**
- 22: Update π_ϕ using $\mathcal{L}_{\text{ADPO}}$ (Eq. 8) on collected batch.
- 23: **end for**
- 24: $\pi_\phi^{(t)} \leftarrow \pi_\phi$.
- 25: **end for**

2: plain text

the total count of these markers in y . The reward is then calculated

$$4: \text{isolate_formula} \quad R_{\text{tool}}(x_i) = \gamma \cdot \min(N_{\text{tool}}(y), C)$$

5: plain text

where γ is a scaling hyperparameter for reward score and C is a cap on the number of rewarded calls to prevent reward tool use.

Repetition Penalty. To encourage diversity within a training batch X , following (Huang et al., 2025), we introduce a repetition penalty R_{rep} . We first compute pairwise distances between generated tasks using a similarity metric, such as BLEU score (Papineni et al., 2002): $d_{ij} = 1 - \text{BLEU}(x_i, x_j)$. Tasks are then grouped into clusters $\mathcal{C} = \{C_1, \dots, C_K\}$ where $d_{ij} < \tau_{\text{BLEU}}$. The penalty for a task x_i belonging to cluster C_k is proportional to its relative cluster size:

$$7: \text{isolate_formula} \quad R_{\text{rep}}(x_i) = \lambda_{\text{rep}} \frac{|C_k|}{B},$$

9: plain text

10: plain text

Composite Reward. The final reward combines these signals, subtracting the repetition penalty, and is gated by a format check:

$$11: \text{isolate_formula} \quad R_C(x_i) = R_{\text{format}}(x_i) \cdot \max(0, (\lambda_{\text{anc}} R_{\text{anc}} + \lambda_{\text{tool}} R_{\text{tool}}) - R_{\text{rep}}(x_i))$$

14: plain text

where λ_{anc} , λ_{tool} , and λ_{rep} are hyperparameters. We use this R_C as the reward r_t in the GRPO loss.

15: title

16: plain text

The Executor Agent π_ϕ 's objective is to maximize its success rate in solving tasks generated by the Curriculum Agent π_θ . Its training is also based on GRPO.

17: title

3.3.1. DATASET CURATION AND TRAJECTORY

18: plain text

Challenging Dataset Construction. After the Curriculum Agent $\pi_\theta^{(t)}$ is trained, we freeze it. We use it to generate a large pool of candidate tasks X_{pool} . For each task x in this pool, we have the current Executor $\pi_\phi^{(t-1)}$ sample k responses and calculate its self-consistency $\hat{p}(x)$. It is calculated as the proportion of responses that voted for this

19: formula

$$\hat{p}(x) = \frac{1}{k} \sum_{i=1}^k \mathbb{I}(o_i = \bar{y}), \quad \bar{y} = \operatorname{argmax}_y \sum_{x \in \mathcal{X}} \sum_{i=1}^k \mathbb{I}(o_i = y).$$

21: plain text

where \mathbb{I} is the indicator function. To build an efficient training curriculum, we filter for tasks that lie at the capability frontier. So we retain only those tasks whose self-consistency is above a band:

$$22: \text{isolate_formula} \quad \pi_\theta^{(t)} \leftarrow \pi_\theta^{(t-1)} \cdot \mathbb{1}\{|\hat{p}(x; \pi_\theta^{(t-1)}) - 0.5| \leq \delta\},$$

23: formula

24: plain text

filtering the curriculum difficulty

This filtering step ensures that π_ϕ trains only on tasks that are hard for it.

Multi-Turn Rollout. We replace the standard single-turn generation with a multi-step, tool-integrated rollout process. During this process, each of the k trajectories is generated by having the policy $\pi_\phi^{(t-1)}$ first produce text reasoning t_1 . When the policy emits a tool-call trigger (i.e., ‘‘python...’’ tags), generation is paused. The code c_1 is then executed in a sandbox, which returns an execution result or error f_1 . This feedback f_1 , prepended with a simple prefix like ‘‘output...’’, is fed back to the policy. The policy then continues generating, conditioning on the history and the new feedback $[t_1 \oplus c_1 \oplus f_1 \oplus ...]$ until the policy generates a full trajectory ($\{t_i\}_{i=1}^k$ and $\{c_i\}_{i=1}^k$ tags), resulting in a complete, hybrid reasoning trajectory. This dynamic, interleaved feedback mechanism allows the agent to iteratively refine its reasoning and correct errors, mimicking the ‘‘aha

25: plain text

Pseudo-Label Advantage. After generating k full trajec-

12: formula_caption

13: abandon

0: abandon

1: plain text

each trajectory based on whether its answer o_i matches this pseudo-label. This outcome reward R_i is used to compute A_i for the entire multi-step trajectory i .

2: title

3: plain text

AMBIGUITY-DYNAMIC POLICY OPTIMIZATION


Standard GRPO treats all training samples equally (Schulman et al., 2017; Shao et al., 2024). However, in our self-evolutionary setting, we rely on majority voting to derive pseudo-labels, which introduces two critical issues: label noise and restricted exploration on ambiguous tasks. To address these, we propose Ambiguity-Dynamic Policy Optimization (ADPO), which incorporates two key modifications:

4: plain text

Ambiguity-Aware Advantage Scaling. The first issue is that for high-ambiguity tasks (low $\hat{p}(x)$), the majority answer is prone to errors. Directly optimizing on these noisy labels using standard GRPO risks reinforcing incorrect reasoning. To prevent overfitting to potentially inaccurate pseudo-labels, we scale the normalized advantage \tilde{A}_i . We define a scaling factor $s(x) = f(\hat{p}(x))$, where f is an increasing function of self-consistency. The advantage is modified as $\tilde{A}_i(x) = \hat{A}_i \cdot s(x)$. This proportionally down-weights the training signal from unreliable, low-consistency

5: title

7: plain text



6: figure

Modulated Trust Regions. The second issue pertains to the rigid constraints imposed by standard proximal algorithms (Yu et al., 2025b). While static clipping (e.g., ϵ) is designed to ensure

9: plain text

to learning. As illustrated in Figure 3, empirical analysis reveals that the upper clipping bound is predominantly triggered by tokens with low probabilities. This indicates that the standard mechanism disproportionately ‘‘clamps’’ the growth of unlikely tokens, effectively stifling the emergence of new reasoning paths. This restriction is particularly detrimental for high-ambiguity tasks (low $\hat{p}(x)$), where the correct reasoning often resides in the tail of the current policy distribution and requires significant updates to surface. To address this bottleneck, ADPO dynamically modulates the trust region. We define the upper clipping bound $\epsilon_{\text{high}}(x)$ as a decreasing function of $\hat{p}(x)$. This effectively relaxes the constraint for ambiguous inputs, permitting larger gradient steps to uplift potential low-probability solutions, while retaining tight bounds on

ted Reasoning

11: plain text

12: plain text

ve stability

The Executor Agent is updated by minimizing the ADPO

13: isolate_formula

$$\mathcal{L}_{\text{ADPO}}(\theta) = \mathbb{E}_{x \sim D^{(t)}} \left[-\frac{1}{G} \sum_{i=1}^G \min \left(r_i(\theta) \tilde{A}_i(x), \right. \right.$$

$$\left. \left. \text{clip}\left(r_i(\theta), 1 - \epsilon_{\text{low}}, 1 + \epsilon_{\text{high}}(x)\right) \tilde{A}_i(x) \right) \right]$$

15: plain text

where $r_i(\theta)$ is the importance sampling ratio, $\tilde{A}_i(x)$ is the ambiguity-scaled advantage, and $\epsilon_{\text{high}}(x)$ is the dynamic upper bound inversely related to $\hat{p}(x)$.

16: title

17: plain text

In this section, we evaluate the performance of Agent0 aiming to answer the following questions: (1) How does the performance of Agent0 compare against state-of-the-art self-evolving baselines? (2) Is the proposed co-evolutionary loop effective at progressively improving the agents’ performance over multiple iterations? (3) How effective is each key component of our framework? (4) Can the mathematical reasoning abilities cultivated by Agent0 generalize to performance on general-domain reasoning tasks?

18: title

19: plain text

Implementation Details. Our framework Agent0 is implemented based on the VeRL (Sheng et al., 2025). We evaluate Agent0 on two base models: Qwen3-4B-Base and Qwen3-8B-Base (Yang et al., 2025a). Both the two Agent are initialized from these base models. During the co-evolutionary loop, for each task x_i , we sample $k = 10$ responses from the Executor to compute uncertainty and generate pseudo-labels. The task filtering threshold is set to $\delta = 0.25$, retaining tasks with a self-consistency $\hat{p}(x)$ between 0.3 and 0.8. For the Curriculum Agent, we set the tool reward scaling $\lambda_{\text{tool}} = 0.6$ and cap $C = 4$. For the Executor Agent, we integrate a sandboxed code interpreter (Cheng et al., 2025) based on VeRL-Tool (Jiang et al., 2025), allowing it to execute code snippets enclosed in ‘‘`python ...`’’ tags and receive

20: plain text

Baseline Methods. We compare Agent0 against several state-of-the-art self-improvement methods. 1) *Base Model*: The pre-trained base model without any fine-tuning. 2) *Base Model w/ tool*: The base model evaluated in a zero-shot setting, but given access to the code interpreter. 3) *Self-Evolving Methods*: R-Zero (Huang et al., 2025), Absolute Zero (Zhao et al., 2025), SPIRAL (Liu et al., 2025a) and 21: plain text 2025d).

Evaluation Datasets and Metrics. Agent0 requires no

10: abandon

0: abandon

Agent0: Unleashing Self-Evolving Agents from Zero Data via Tool-Integrated Reasoning

1: table_caption

2: table

Model Name			Avg	AMC	Minerva	MATH	GSM8K	Olympiad	AIME25	AIME24
<i>Qwen3-4B-Base</i>										
Base Model	✗	✗	42.6	45.7	38.2	68.2	87.8	41.0	6.15	10.9
Base Model w/ tool	✓	✗	44.2	46.3	39.6	71.0	88.6	43.7	7.71	12.3
+ Absolute Zero	✓	✗	46.4	50.0	41.9	76.2	89.3	41.5	13.4	12.2
+ SPIRAL	✗	✗	47.0	57.5	42.4	76.4	91.0	38.4	10.0	13.3
+ R-Zero	✗	✗	49.1	57.3	52.9	79.6	92.1	44.6	4.27	12.7
+ Agent0	✓	✗	52.5	60.6	55.6	80.5	92.6	46.7	14.1	17.4
<i>Qwen3-8B-Base</i>										
Base Model	✗	✗	49.2	52.0	50.0	78.0	89.1	44.7	16.7	13.9
Base Model w/ tool	✓	✗	53.2	60.3	54.9	79.2	90.7	47.9	18.7	20.9
+ Absolute Zero	✓	✗	52.6	62.5	52.9	76.6	92.0	47.8	18.2	18.4
+ R-Zero	✗	✗	54.7	61.7	60.7	82.0	94.1	48.9	19.2	16.4
+ Socratic-Zero	✗	✓	56.1	63.7	52.4	81.2	87.3	55.1	24.5	28.4
+ Agent0	✓	✗	58.2	62.4	57.2	82.4	94.5	54.0	24.8	28.0

4: table

3: table_caption

Table 2: Results on general-domain reasoning benchmarks

Model Name			Overall Avg	MATH Avg	SuperGPQA	MMLU-Pro	BBEH
<i>Qwen3-4B-Base</i>							
Base Model	✗	✗	27.1	42.6	20.9	37.4	7.57
Base Model w/ tool	✓	✗	30.3	44.2	25.8	42.9	8.32
+ Absolute Zero	✓	✗	33.6	46.4	27.1	52.6	8.3
+ SPIRAL	✗	✗	34.2	47.0	27.1	53.2	9.57
+ R-Zero	✗	✗	34.6	49.1	27.6	51.5	10.4
+ Agent0	✓	✗	37.6	52.5	29.9	55.9	12.0
<i>Qwen3-8B-Base</i>							
Base Model	✗	✗	34.5	49.2	28.3	51.8	8.6
Base Model w/ tool	✓	✗	36.7	53.2	29.5	54.8	9.37
+ Absolute Zero	✓	✗	39.9	52.6	33.5	62.5	10.8
+ R-Zero	✗	✗	38.7	54.7	31.4	58.2	10.6
+ Socratic-Zero	✗	✓	39.2	56.1	30.1	60.9	9.5
+ Agent0	✓	✗	42.1	58.2	33.0	63.4	13.7

5: plain_text

human-annotated data for training. We evaluate all methods on two suites of benchmarks: 1) *Mathematical Reasoning*: We use a comprehensive set including AMC, Minerva (Lewkowycz et al., 2022), MATH (Hendrycks et al., 2021), GSM8K (Cobbe et al., 2021), Olympiad-Bench (He et al., 2024), AIME25, and AIME24. 2) *General-Domain Reasoning*: To measure generalization, we use SuperGPQA (Du et al., 2025), MMLU-Pro (Wang et al., 2024b) and BBEH (Kazemi et al., 2025). We report the accuracy (pass@1) based on greedy decoding across all benchmarks (AMC and AIME benchmarks (mean@32).

6: title

7: plain_text

We present the main results for mathematical reasoning in 8: plain_text domain reasoning in Table 2.

Comparison with Baselines. It significantly outperforms all compared baseline methods in both mathematics and general-domain reasoning. On Qwen3-8B-Base, Agent0 surpasses the powerful data-free method R-Zero by 6.4% and outperforms the self-play method Absolute Zero, which

10: plain_text

utilizes a code executor, by 10.6%. It even exceeds Socratic-Zero by 3.7%, which relies on external OpenAI APIs. This demonstrates the superiority of Agent0’s self-evolution approach. By using tools to interact with the environment, the agent effectively enhances the quality and diversity of questions generated by the curriculum agent. Similarly, for the execution agent, this more effectively improves its

11: plain_text

Generalization to General-Domain Tasks. Furthermore, Table 2 shows strong evidence of generalization. On Qwen3-8B, Agent0 achieves the highest overall average score among all approaches, significantly outperforming other data-free methods. This indicates that the complex, multi-step reasoning abilities we cultivated in the execution agent by using the curriculum agent with tools, can be effectively transferred to general-domain tasks.

12: title

13: plain_text


In this section, we provide a detailed analysis of each module’s performance along with a series of analytical experi-

9: abandon

O: abandon

Agent0: Unleashing Self-Evolving Agents from Zero Data via Tool-Integrated Reasoning

1: figure



3: figure_caption

Figure 4. Performance on mathematical and general reasoning benchmarks, showing consistent improvement for both Qwen3-4B and Qwen3-8B across three curriculum iterations.

5: table

Ablation study of Agent0

Method	General AVG	Math AVG
Agent0	36.7	58.2
<i>Curriculum Agent</i>		
w/o Training	29.5	46.8
w/o Tool Reward	31.8	48.7
w/o Repetition Penalty	31.3	47.9
<i>Execution Agent</i>		
w/o ADPO	34.9	56.2
	35.3	55.9

6: plain_text

Ablation Study. As shown in Table 3, we conducted a series of ablation experiments to evaluate the impact of each component in our method. Specifically, we evaluate the impact of: (1) the curriculum agent’s training, (2) the tool reward, (3) the repetition penalty, (4) our ambiguity scaling mechanism, and (5) the multi-turn reasoning capability. For the curriculum agent, without training, the performance significantly drops by 9.3%. This reflects the value of the learned curriculum. Next, when the tool reward is not included, the model’s performance drops by 7.2%. This tests our core hypothesis that explicitly rewarding tool-use tasks is necessary. It shows a severe performance degradation when we remove the diversity component, indicating that R_{rep} is highly effective for curriculum diversity, particularly for general tasks. As for the execution agent, training it using the original GRPO with standard advantage and clipping resulted in a performance drop of 1.9%. This is because the original algorithm does not account for the reliability of pseudo-labels, demonstrating the effectiveness of our proposed ambiguity scaling mechanism. The introduction of multi-turn reasoning played a significant role in boosting Agent0’s performance, especially for complex mathematical tasks.

7: plain_text

Consistent Improvement through Co-Evolution. As shown in Figure 4, our method demonstrates stable and progressive improvement during the iterative process. On Qwen3-8B-Base, the average math score improved from 55.1 (Iter 1) to 56.5 (Iter 2), peaking at 58.2 (Iter 3). In addition to mathematics, Agent0 showed the similar trend on other general-domain reasoning tasks, with an average improvement of 2% per iteration compared to the previous one. This iterative gain validates the effectiveness of our

9: table_caption

Table 5. Evolution of Task Difficulty and Tool Use. We report the pass rate of the Execution Agent (from Iteration 1) on data generated by the Curriculum Agent at different stages.

Dataset	Pass Rate (Executor _{Iter 1})	Avg. Tool Calls
$\mathcal{D}_{Iter 1}$	64.0	1.65
$\mathcal{D}_{Iter 2}$	58.5	2.10
$\mathcal{D}_{Iter 3}$	51.0	2.60

11: plain_text

co-evolutionary loop. With the involvement of tools, the curriculum agent progressively generates more difficult tasks, while the execution agent learns to solve these tasks more efficiently. This also confirms that agent self-evolution is a

13: plain_text

Strategic Tool Integration Matters.

Our advantage lies not just in having a tool, but in learning how to use it. As shown in Table 4, merely providing a tool (i.e., Base Model w/ Tool) yields

12: table_caption

on non-tool baselines.

Model	MATH	General
Qwen3-4B	42.6	22.0
+no Tool		
+SPIRAL	47.0	30.0
+R-Zero	49.1	29.8
+no Tool		
+TIR	44.2	25.7
+Absolute Zero	46.4	29.3
+Agent0	52.5	32.6

15: plain_text

cantly outperforms other tool-using baselines, such as Absolute Zero. Agent0 also significantly surpasses non-tool methods like R-Zero and SPIRAL. This indicates that our curriculum agent, by using the R_{tool} reward to explicitly incentivize the generation of complex tasks requiring tool use, is far more effective than methods that only use tools for validation (e.g., Absolute Zero) or do not use tools at all (e.g., R-Zero). Furthermore, the execution agent utilizes the tool in conjunction with multi-step reasoning, which also results in co-evolution.

16: plain_text

Evolution of Task Difficulty and Tool Use. We analyze the tasks generated by the curriculum agent during the training iterations. We sample 200 questions from each iteration for this analysis. As shown in Table 5, the pass rate of the execution agent (from Iteration 1) progressively decreases when evaluated on task sets generated by the curriculum agents from Iterations 1, 2, and 3. This indicates that the task difficulty is gradually increasing, confirming that the curriculum adapts to the improvement in the executor’s capabilities. More importantly, the average number of tool calls per generated task steadily increases across iterations. This directly proves that our R_{tool} reward successfully guides the curriculum agent to generate more complex and tool-reliant problems in a virtuous cycle.

Qualitative Analysis. Figure 5 illustrates the co-evolution of task complexity and solving proficiency. The Curriculum Agent effectively generates increasingly difficult problems

8: abandon

0: abandon

1: figure

Generated Questions from Curriculum Agent



Iter 1 Let ABC be a triangle with $\angle A = 90^\circ$. Points D and E lie on sides AB and AC , respectively, such that $AD + EC = BC$ and $AD \cdot EC = BD \cdot AE$. Find the measure of $\angle B$.



Iter 2 A rectangle R has sides of length 10 and 5. Point P lies inside R such that the distances from P to the four sides of R are x , y , $10 - x$, and $5 - y$, where x and y are positive real numbers. Find the maximum possible value of $x^2 + y^2$.



Iter 3 In a particular city, each neighborhood is assigned a distinct integer address from 1 to N . To ensure the safety of the city, the city council decides to organize a unique parade route where no two adjacent neighborhoods should share a common digit in their address. For example, if the parade starts at address 15, the next possible stop cannot be any address containing the digits 1 or 5. What is the maximum value of N such that the parade can visit all neighborhoods without breaking this rule? Express your answer as a digit integer.

Test Question (MATH)

Compute: $1 - 2 + 3 - 4 + 5 - \dots + 99 - 100$

Model Output by Agent0

To solve the problem $1 - 2 + 3 - 4 + 5 - \dots + 99 - 100$, we can observe the pattern in the series. The series alternates between adding and subtracting consecutive integers.

We can group the terms in pairs to simplify the calculation:

$(1 - 2) + (3 - 4) + (5 - 6) + \dots + (99 - 100)$

Each pair $(2k - 1) - 2k$ simplifies to -1 . Since there are 100 terms in total, there are 50 pairs. Therefore, the sum of the series is:

$50 \times (-1) = -50$

Let's confirm this with Python code.

```
'''python
# Calculate the sum of the series 1 - 2 + 3 - 4 + 5 - ... + 99 - 100
result = sum(i if i % 2 == 0 else -i for i in range(1, 101))
print(result)
'''
```

'''output

-50

'''

The sum of the series $1 - 2 + 3 - 4 + 5 - \dots + 99 - 100$ is `-50`.

2: figure_caption

Figure 5. Qualitative Case Analysis. Left: Examples of generated questions showing a clear increase in complexity and diversity from Iter 1 to Iter 3. Right: A demonstration of Agent0’s solving process, utilizing a hybrid approach of mathematical reasoning and Python code to solve a MATH problem.

3: plain_text

constraint satisfaction tasks (Iter 3). Simultaneously, the Executor Agent0 demonstrates reliable problem-solving capabilities. In the provided example, the agent effectively combines natural language reasoning to identify patterns with the Python code interpreter to verify calculations, validating the model’s ability to handle hybrid reasoning tasks.

4: title

5: plain_text

Self-Evolving from Zero Data. The paradigm of self-evolution, where LLMs generate their own training data, has gained significant traction (Liu et al., 2024; Dong et al., 2024; Fang et al., 2025; Yang et al., 2025b; Kuba et al., 2025). This approach ranges from dual-agent “Coder-Tester” setups in verifiable domains (Lin et al., 2025; Wang et al., 2025e) to fully autonomous frameworks (Zhao et al., 2025; Huang et al., 2025; Wang et al., 2025d; Liu et al., 2025b; Tao et al., 2024; Zhang et al., 2025a; Wu et al., 2025b; Lu et al., 2025) that learn to generate novel problems from scratch. To guide this learning, many methods use label-free reinforcement learning, relying on heuristic reward signals such as output confidence (Li et al., 2025a) or consistency (Zhang et al., 2025b; Prabhudesai et al., 2025; Zuo et al., 2025; Yu et al., 2025c). However, these systems are critically limited by the model’s inherent knowledge (Han et al., 2025a; Xia et al., 2025), causing curriculum stagnation as tasks rarely surpass the model’s current complexity. Agent0 breaks this cap by integrating an external tool, providing external problem-solving power. However, without external tools, such closed-loop systems risk mode collapse and curriculum stagnation, as they remain bounded by the model’s inherent knowledge. Agent0 breaks this ceiling by integrating an external tool to introduce objective problem-solving power.

7: plain_text

Tool-Integrated Reasoning (TIR). Applying Reinforcement Learning (RL) (Jaech et al., 2024; Wang et al., 2025c;b; Zhou et al., 2025c; Wu et al., 2025a; Yang et al.) to enhance LLM tool-use is a growing field. Many approaches rely on domain-specific data or supervised fine-tuning (Jin et al., 2025; Feng et al., 2025; Li et al., 2025b; Geng et al., 2025; Han et al., 2025b; Su et al., 2025). The more general Zero RL setting, however, is notoriously unstable in multi-turn scenarios. Recent advances in TIR address these challenges through three key dimensions: stability, generalization, and complexity. To stabilize learning dynamics, methods like ASPO (Lin & Xu, 2025) and SimpleTIR (Xue et al., 2025) introduce theoretical guarantees and gradient filtering for void turns. Beyond stability, (Chen et al., 2025) demonstrate the cross-domain transferability of tool-use skills. Finally, to handle complex multi-turn scenarios, advanced techniques optimize for long-horizon planning (Gao et al., 2025; Erdogan et al., 2025), memory management (Yan et al., 2025) and interaction efficiency (Wang et al., 2025a).

8: title

9: plain_text

We introduce Agent0, a fully autonomous framework where a curriculum agent and an executor agent co-evolve without any human-curated data. We integrated a code interpreter into the loop, which creates a virtuous cycle: the tool-equipped executor’s improving capabilities drive the curriculum agent to generate progressively harder tasks. Our experiments show that Agent0 significantly enhances the reasoning abilities of base LLMs. It demonstrates a scalable and effective pathway for evolving highly capable agents breaking the dependency on human-annotated datasets.

6: abandon

O: abandon

1: title

Agent 0: Unleashing Self-Evolving Agents from

2: plain text

We thank Chengsong Huang for helpful discussions. This work is partially supported by the AI for Math Fund from Renaissance Philanthropy. The Authors also acknowledge the National Artificial Intelligence Research Resource (NAIRR) Pilot, Purdue Anvil AI for contributing to this research result.

3: title

9: plain text

Achiam, J., Adler, S., Agarwal, S., Ahmad, L., Akkaya, I., Aleman, F. L., Almeida, D., Altenschmidt, J., Altman, S., Anadkat, S., et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.13951*, 2023.

5: plain text

Anthropic. Claude code, 2025. URL <https://www.anthropic.com/claude-code>.

6: plain text

Bae, S., Hong, J., Lee, M. Y., Kim, H., Nam, J., and Kwak, D. Online difficulty filtering for reasoning oriented reinforcement learning. *arXiv preprint arXiv:2504.03380*, 2025.

7: plain text

Chen, Z., Yang, J., Xiao, T., Zhou, R., Zhang, L., Xi, X., Shi, X., Wang, W., and Wang, J. Can tool-integrated reinforcement learning generalize across diverse domains?

8: plain text

510.11184, 2025.

Cheng, P., Dai, Y., Hu, T., Xu, H., Zhang, Z., Han, L., Du, N., and Li, X. Self-playing adversarial language game enhances llm reasoning. *Advances in Neural Information Processing Systems*, 37:126515–126543, 2024.

Cheng, Y., Chen, J., Chen, J., Chen, L., Chen, L., Chen, W., Chen, Z., Geng, S., Li, A., Li, B., Li, B., Li, L., Liu, B., Liu, J., Liu, K., Liu, Q., Liu, S., Liu, S., Liu, T., Liu, T., Liu, Y., Long, R., Mai, J., Ning, G., Peng, Z. Y., Shen, K., Su, J., Su, J., Sun, T., Sun, Y., Tao, Y., Wang, G., Wang, S., Wang, X., Wang, Y., Wang, Z., Xia, J., Xiang, L., Xiao, X., Xiao, Y., Xi, C., Xin, S., Xu, J., Xu, S., Yang, H., Yang, J., Yang, Y., Yuan, J., Zhang, J., Zhang, Y., Zhang, Y., Zheng, S., Zhu, H., and Zhu, M. Fullstack bench: Evaluating llms as full stack coders, 2025. URL <https://arxiv.org/abs/2412.00535>.

10: plain text

10.14168, 2021.

Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., et al. Training verifiers to solve math word problems.

11: plain text

0.14168, 2021.

Dong, G., Lu, K., Li, C., Xia, T., Yu, B., Zhou, C., and Zhou, J. Self-play with execution feedback: Improving instruction-following capabilities of large language

12: plain text

arXiv:2406.13542, 2024.

Du, X., Yao, Y., Ma, K., Wang, B., Zheng, T., Zhu, K., Liu, M., Liang, Y., Jin, X., Wei, Z., et al. Superemos: Scaling

20: plain text

I Reasoning

■ multi evaluation across 283 graduate disciplines. *arXiv:2503.09572*, 2025.

15: plain text

Erdogan, L. E., Lee, N., Kim, S., Moon, S., Furuta, H., Anumanchipalli, G., Keutzer, K., and Gholami, A. Plan-and-act: Improving planning of agents for long-horizon

16: plain text

arXiv:2503.09572, 2025.

Fang, W., Liu, S., Zhou, Y., Zhang, K., Zheng, T., Chen, K., Song, M., and Tao, D. Serl: Self-play reinforcement learning for large language models with limited data. *arXiv:2503.09572*, 2025.

17: plain text

arXiv:2503.09572, 2025.

Feng, J., Huang, S., Qu, X., Zhang, G., Qin, Y., Zhong, B., Jiang, C., Chi, J., and Zhong, W. Retool: Reinforcement learning for strategic tool use in llms. *arXiv preprint arXiv:2503.09572*, 2025.

18: plain text

arXiv:2503.09572, 2025.

Gao, J., Fu, W., Xie, M., Xu, S., He, C., Mei, Z., Zhu, B., and Wu, Y. Beyond ten turns: Unlocking long-horizon agentic search with large-scale asynchronous rl. *arXiv:2503.09572*, 2025.

19: plain text

arXiv:2503.09572, 2025.

Geng, X., Xia, P., Zhang, Z., Wang, X., Wang, Q., Ding, R., Wang, C., Wu, J., Zhao, Y., Li, K., et al. Webwatcher: Breaking new frontier of vision-language deep research

21: plain text

arXiv:2503.09572, 2025.

Google. Try deep research and our new experimental model in gemini, your ai assistant, 2024. URL <https://blog.google/products/gemini-deep-research/>.

22: plain text

arXiv:2510.04860, 2025a.

Han, S., Liu, J., Su, Y., Duan, W., Liu, X., Xie, C., Bansal, M., Ding, M., Zhang, L., and Yao, H. Alignment tipping process: How self-evolution pushes llm agents off the

23: plain text

arXiv:2510.04860, 2025a.

Han, S., Xia, P., Zhang, R., Sun, T., Li, Y., Zhu, H., and Yao, H. Mdocagent: A multi-modal multi-agent framework for document understanding. *arXiv preprint arXiv:2510.04860*, 2025.

24: plain text

arXiv:2510.04860, 2025.

He, C., Luo, R., Bai, Y., Hu, S., Thai, Z. L., Shen, J., Hu, J., Han, X., Huang, Y., Zhang, Y., et al. Olympiadbench: A challenging benchmark for promoting agi with olympiad-level bilingual multimodal scientific problems. *arXiv:2510.04860*, 2025.

25: plain text

arXiv:2510.04860, 2025.

Hendrycks, D., Burns, C., Basart, S., Zou, A., Mazeika, M., Song, D., and Steinhardt, J. Measuring massive multitask language understanding. *arXiv preprint arXiv:2510.04860*, 2025.

26: plain text

arXiv:2510.04860, 2025.

Hendrycks, D., Burns, C., Kadavath, S., Arora, A., Basart, S., Tang, E., Song, D., and Steinhardt, J. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2510.04860*, 2025.

13: abandon

I Reasoning

	D: abandon
7: plain text	0: Unleashing Self-Evolving Agents from Reasoning
Huang, C., Yu, W., Wang, X., Zhang, H., Li, Z., Li, R., Huang, J., Mi, H., and Yu, D. R-zero: Self-evolving reasoning llm from zero data. 2025. URL https://arxiv.org/abs/2508.05004 .	ted Reasoning
2: plain text	508.05004.
Jaech, A., Kalai, A., Lerer, A., Richardson, A., El-Kishky, A., Low, A., Helyar, A., Madry, A., Beutel, A., Carney, A., et al. Openai ol system card. <i>arXiv preprint arXiv:2508.05004</i> , 2025.	
3: plain text	24.
Jiang, D., Lu, Y., Li, Z., Lyu, Z., Nie, P., Wang, H., Su, A., Chen, H., Zou, K., Du, C., et al. Veritool: Towards holistic agentic reinforcement learning with tool use. <i>arXiv preprint arXiv:2508.05004</i> , 2025.	
4: plain text	1055. 2025.
Jimenez, C. E., Yang, J., Wettig, A., Yao, S., Pei, K., Press, O., and Narasimhan, K. Swe-bench: Can language models resolve real-world github issues? <i>arXiv preprint arXiv:2508.05004</i> , 2025.	
5: plain text	23.
Jin, B., Zeng, H., Yue, Z., Yoon, J., Arik, S., Wang, D., Zamani, H., and Han, J. Search-r1: Training llms to reason and leverage search engines with reinforcement learning. <i>arXiv preprint arXiv:2503.09516</i> , 2025.	
6: plain text	it arXiv:2503.09516, 2025.
Kazemi, M., Fatemi, B., Bansal, H., Palowitch, J., Anastasiou, C., Mehta, S. V., Jain, L. K., Aglietti, V., Jindal, D., Chen, P., et al. Big-bench extra hard. <i>arXiv preprint arXiv:2509.07414</i> , 2025.	
8: plain text	25.
Kuba, J. G., Gu, M., Ma, Q., Tian, Y., and Mohan, V. Language self-play for data-free training. <i>arXiv preprint arXiv:2509.07414</i> , 2025.	
Kwon, W., Li, Z., Zhuang, S., Sheng, Y., Zheng, L., Yu, C. H., Gonzalez, J. E., Zhang, H., and Stoica, I. Efficient memory management for large language model serving with pagedattention. In <i>Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles</i> , 2023.	
Lewkowycz, A., Andreassen, A., Dohan, D., Dyer, E., Michalewski, H., Ramasesh, V., Slone, A., Anil, C., Schlag, I., Gutman-Solo, T., et al. Solving quantitative reasoning problems with language models. <i>Advances in neural information processing systems</i> , 35:3843–3857, 2022.	
Li, P., Skripkin, M., Zubrey, A., Kuznetsov, A., and Oseledets, I. Confidence is all you need: Few-shot rl fine-tuning of language models. <i>arXiv preprint arXiv:2506.06395</i> , 2025a.	
Li, X., Zou, H., and Liu, P. Torl: Scaling tool-integrated rl. <i>arXiv preprint arXiv:2503.23383</i> , 2025b.	
Li, Y., Shen, X., Yao, X., Ding, X., Miao, Y., Krishnan, R., and Padman, R. Beyond single-turn: A survey on multi-turn interactions with large language models. <i>arXiv preprint arXiv:2504.04717</i> , 2025c.	
13: plain text	11: Understanding tool-integrated reasoning. 12: 19201, 2025.
Lin, H. and Xu, Z. Understanding tool-integrated reasoning. 12: 19201, 2025.	
Lin, Z., Shen, S., Shang, J., Weston, J., and Nie, Y. Learning to solve and verify: A self-play framework for code and test generation. <i>arXiv preprint arXiv:2502.14948</i> , 2025.	
Liu, B., Guertler, L., Yu, S., Liu, Z., Qi, P., Balcells, D., Liu, M., Tan, C., Shi, W., Lin, M., Lee, W. S., and Jaques, N. Spiral: Self-play on zero-sum games incentivizes reasoning via multi-agent multi-turn reinforcement learning. 12: 24119, 2025a.	
Liu, B., Jin, C., Kim, S., Yuan, W., Zhao, W., Kulikov, I., Li, X., Sukhbaatar, S., Lanchantin, J., and Weston, J. Spice: Self-play in corpus environments improves reasoning. <i>arXiv preprint arXiv:2510.24684</i> , 2025b.	
Liu, Y., Sun, P., and Li, H. Large language models as agents in two-player games. <i>arXiv preprint arXiv:2402.08078</i> , 2024.	
Lu, H., Wen, Y., Cheng, P., Ding, R., Xu, H., Guo, J., Wang, C., Chen, H., Jiang, X., and Jiang, G. Search self-play: Pushing the frontier of agent capability without supervision. <i>arXiv preprint arXiv:2510.18821</i> , 2025.	
OpenAI. Openai deep research system card, 2025. URL https://openai.com/index/introducing-deep-research/ .	
Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C., Mishkin, P., Zhang, C., Agarwal, S., Slama, K., Ray, A., et al. Training language models to follow instructions with human feedback. <i>Advances in neural information processing systems</i> , 35:2730–27744, 2022.	
Papineni, K., Roukos, S., Ward, T., and Zhu, W.-J. Bleu: a method for automatic evaluation of machine translation. In <i>Proceedings of the 40th annual meeting of the Association for Computational Linguistics</i> , pp. 311–318.	
Prabhudesai, M., Chen, L., Ippoliti, A., Fragkiadaki, K., Liu, H., and Pathak, D. Maximizing confidence alone improves reasoning. <i>arXiv preprint arXiv:2505.22660</i> , 2025.	
Qiu, J., Qi, X., Wang, H., Juan, X., Wang, Y., Zhao, Z., Geng, J., Guo, J., Li, P., Shi, J., et al. Alita-g: Self-evolving generative agent for agent generation. <i>arXiv preprint arXiv:2505.22660</i> , 2025a.	
Qiu, J., Qi, X., Zhang, T., Juan, X., Guo, J., Lu, Y., Wang, Y., Yao, Z., Ren, Q., Jiang, X., et al. Alita: Generalist agent enabling scalable agentic reasoning with minimal predefinition and maximal self-evolution. <i>arXiv preprint arXiv:2505.20286</i> , 2025b.	
9: unbound	

0: abandon	
6: plain text	0: Unleashing Self-Evolving Agents from Reasoning
Rein, D., Hou, B. L., Stickland, A. C., Petty, J., Pang, R. Y., Dirani, J., Michael, J., and Bowman, S. R. Gpqa: A graduate-level google-proof q&a benchmark. In <i>First Conference on Language Modeling</i> , 2024.	
12: plain text	18: plain text
Schulman, J., Wolski, F., Dhariwal, P., Radford, A., and Klimov, O. Proximal policy optimization algorithms. <i>ArXiv preprint arXiv:1707.06347</i> , 2017. URL https://arxiv.org/abs/1707.06347 .	Wang, H., Qian, C., Zhong, W., Chen, X., Qiu, J., Huang, S., Jin, B., Wang, M., Wong, K.-F., and Ji, H. Otc: Optimal tool calls via reinforcement learning. <i>arXiv e-prints</i> , pp. 1–11, 2024.
3: plain text	14: plain text
Shao, Z., Wang, P., Zhu, Q., Xu, R., Song, J., Bi, X., Zhang, H., Zhang, M., Li, Y., Wu, Y., et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. <i>arXiv:2402.03300</i> , 2024.	Wang, H., Que, H., Xu, Q., Liu, M., Zhou, W., Feng, J., Zhong, W., Ye, W., Yang, T., Huang, W., et al. Reverse-engineered reasoning for open-ended generation. <i>arXiv:2402.03646</i> , 2024.
4: plain text	15: plain text
Sheng, G., Zhang, C., Ye, Z., Wu, X., Zhang, W., Zhang, R., Peng, Y., Lin, H., and Wu, C. Hybridflow: A flexible and efficient rlhf framework. In <i>Proceedings of the Twentieth European Conference on Computer Systems</i> , pp. 1279–1299, 2024.	Wang, H., Xu, Q., Liu, C., Wu, J., Lin, F., and Chen, W. Emergent hierarchical reasoning in llms through reinforcement learning. <i>arXiv preprint arXiv:2509.03646</i> , 2025b.
5: plain text	16: plain text
Shi, T., Wu, Y., Song, L., Zhou, T., and Zhao, J. Efficient reinforcement finetuning via adaptive curriculum learning. <i>arXiv preprint arXiv:2504.05520</i> , 2025.	Wang, S., Jiao, Z., Zhang, Z., Peng, Y., Ze, X., Yang, B., Wang, W., Wei, H., and Zhang, L. Socratic-zero: Bootstrapping reasoning via data-free agent co-evolution. <i>arXiv preprint arXiv:2509.24726</i> , 2025d.
7: plain text	17: plain text
Srivastava, A., Rastogi, A., Rao, A., Shoeb, A. A. M., Abid, A., Fisch, A., Brown, A. R., Santoro, A., Gupta, A., Garriga-Alonso, A., et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. <i>Transactions on machine learning research</i> , 2024.	Wang, X., Li, B., Song, Y., Xu, F. F., Tang, X., Zhuge, M., Pan, J., Song, Y., Li, B., Singh, J., et al. Openhands: An open platform for ai software developers as generalist. <i>arXiv:2407.16741</i> , 2024a.
8: plain text	19: plain text
Su, Z., Xia, P., Guo, H., Liu, Z., Ma, Y., Qu, X., Liu, J., Li, Y., Zeng, K., Yang, Z., et al. Thinking with images for multimodal reasoning: Foundations, methods, and future directions. <i>arXiv:2506.23918</i> , 2025.	Wang, Y., Ma, X., Zhang, G., Ni, Y., Chandra, A., Guo, S., Ren, W., Arulraj, A., He, X., Jiang, Z., et al. Mmlu-project: A more robust and challenging multi-task language understanding benchmark. <i>Advances in Neural Information Processing Systems</i> , 2025. 9266–95290, 2024b.
9: plain text	20: plain text
Tang, X., Qin, T., Peng, T., Zhou, Z., Shao, D., Du, T., Wei, X., Xia, P., Wu, F., Zhu, H., et al. Agent kb: Leveraging cross-domain experience for agentic problem solving. <i>arXiv:2507.06229</i> , 2025.	Wu, R., Wang, X., Mei, J., Cai, P., Fu, D., Yang, C., Wen, L., Yang, X., Shen, Y., Wang, Y., et al. Evolver: Self-evolving llm agents through an experience-driven lifecycle. <i>arXiv:2506.03136</i> , 2025e.
10: plain text	21: plain text
Tao, Z., Lin, T.-E., Chen, X., Li, H., Wu, Y., Li, Y., Jin, Z., Huang, F., Tao, D., and Zhou, J. A survey on self-evolution of large language models. <i>arXiv preprint arXiv:2506.00555</i> , 2025.	Wu, F., Huang, X., Xuan, W., Zhang, Z., Xiao, Y., Wan, G., Li, X., Hu, B., Xia, P., Leskovec, J., et al. Multiplayer nash preference optimization. <i>arXiv preprint arXiv:2506.00555</i> , 2025.
11: plain text	22: plain text
Tu, A., Xuan, W., Qi, H., Huang, X., Zeng, Q., Talaei, S., Xiao, Y., Xia, P., Tang, X., Zhuang, Y., et al. Position: The hidden costs and measurement gaps of reinforcement learning with verifiable rewards. <i>arXiv preprint arXiv:2509.21882</i> , 2025.	Xia, P., Wang, J., Peng, Y., Zeng, K., Wu, X., Tang, X., Zhu, H., Li, Y., Liu, S., Lu, Y., et al. Mmedagent-rl: Optimizing multi-agent collaboration for multimodal medical decision making. <i>arXiv:2506.00555</i> , 2025.
15: abandon	23: plain text
	Yan, S., Yang, X., Huang, Z., Nie, E., Ding, Z., Li, Z., Ma, X., Kersting, K., Pan, J. Z., Schütze, H., et al. Memory-augmented fine-tuned language model agents to manage complex tasks. <i>arXiv:2509.02479</i> , 2025.

B: abandon

- 7: plain text [Unleashing Self-Evolving Agents from Plain Text](#)
and utilize memories via reinforcement learning. *arXiv* 2028, 2025.
- 2: plain text [Yang, A., Li, A., Yang, B., Zhang, B., Hui, B., Zheng, B., Yu, B., Gao, C., Huang, C., Lv, C., et al. Qwen3 technical report arXiv:2505.09388, 2025a.](#)
- 3: plain text [Yang, X., Han, J., Bommasani, R., Luo, J., Qu, W., Zhou, W., Bibi, A., Wang, X., Yoon, J., Stengel-Eskin, E., et al. Reliable and responsible foundation models. *Transactions on Computing Research*.](#)
- 4: plain text [Yang, Z., Shen, W., Chen, R., Li, C., Wan, F., Yan, M., Quan, X., and Huang, F. Spell: Self-play reinforcement learning for evolving long-context language models. *arXiv preprint arXiv:2503.3863*, 2025b.](#)
- 5: plain text [Yu, H., Chen, T., Feng, J., Chen, J., Dai, W., Yu, Q., Zhang, Y.-Q., Ma, W.-Y., Liu, J., Wang, M., et al. Memagent: Reshaping long-context llm with multi-conv rl-based memory. *arXiv preprint arXiv:2507.02259*, 2025a.](#)
- 6: plain text [Yu, Q., Zhang, Z., Zhu, R., Yuan, Y., Zuo, X., Yue, Y., Dai, W., Fan, T., Liu, G., Liu, L., et al. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2501.0255b*, 2025.](#)
- 8: plain text [Yu, Z., Su, W., Tao, L., Wang, H., Singh, A., Yu, H., Wang, J., Gao, H., Yuan, W., Weston, J., et al. Restrain: From spurious votes to signals—self-driven rl with self-reinforcement learning. *arXiv preprint arXiv:2510.02172*, 2025c.](#)
- 9: plain text [Yue, Y., Chen, Z., Lu, R., Zhao, A., Wang, Z., Song, S., and Huang, G. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model? *arXiv preprint arXiv:2507.0237*, 2025.](#)
- 10: plain text [Zhai, Y., Tao, S., Chen, C., Zou, A., Chen, Z., Fu, Q., Mai, S., Yu, L., Deng, J., Cao, Z., et al. Agentevolver: Towards efficient self-evolving agent system. *arXiv preprint arXiv:2506.13134*, 2025a.](#)
- 11: plain text [Zhang, D.-C., Zhao, Y., Wu, J., Zhang, L., Li, B., Yin, W., Jiang, Y., Li, Y.-F., Tu, K., Xie, P., et al. Evolvesearch: An iterative self-evolving search agent. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing \(EMNLP\)*. 13134–13147, 2025a.](#)
- 12: plain text [Zhang, K., Yao, Q., Liu, S., Wang, Y., Lai, B., Ye, J., Song, M., and Tao, D. Consistent paths lead to truth: Self-rewarding reinforcement learning for llm reasoning. *arXiv preprint arXiv:2506.08745*, 2025b.](#)
- 13: plain text [Zhang, K., Zuo, Y., He, B., Sun, Y., Liu, R., Jiang, C., Fan, Y., Tian, K., Jia, G., Li, P., et al. A survey of reinforcement learning for large reasoning models. *arXiv preprint arXiv:2509.08827*, 2025c.](#)

C: reasoning

- 19: plain text [Zhao, A., Wu, Y., Yue, Y., Wu, T., Xu, Q., Yue, Y., Lin, M., Wang, S., Wu, Q., Zheng, Z., and Huang, G. Absolute zero: Reinforced self-play reasoning with zero data, 2025. <https://arxiv.org/abs/2505.03335>.](#)

- 20: plain text [Zhou, Y., Levine, S., Weston, J., Li, X., and Sukhbaatar, S. Self-challenging language model agents. *arXiv preprint arXiv:2509.15194*, 2025.](#)

- 17: plain text [Zhou, Y., Liang, Z., Liu, H., Yu, W., Panaganti, K., Song, L., Yu, D., Zhang, X., Mi, H., and Yu, D. Evolving language models without labels: Majority drives selection, novelty promotes variation. *arXiv preprint arXiv:2509.15194*, 2025.](#)

- 21: plain text [Zhou, Y., Wang, Z., Wang, T., Xing, S., Xia, P., Li, B., Zheng, K., Zhang, Z., Chen, Z., Zheng, W., et al. Anyprefer: An agentic framework for preference data synthesis. *arXiv preprint arXiv:2504.19276*, 2025c.](#)

- Zuo, Y., Zhang, K., Sheng, L., Qu, S., Cui, G., Zhu, X., Li, H., Zhang, Y., Long, X., Hua, E., et al. Trrl: Test-time reinforcement learning. *arXiv preprint arXiv:2504.16084*, 2025.

0: abandon

Agent 0: Unleashing Self-Evolving Agents from Zero Data via Tool-Integrated Reasoning

1: title

Annendix

2: title

3: plain text

etials

4: plain text

ettings

5: plain text

ng

• Global Batch Size: 128

• Learning Rate: 1×10^{-6}

• Weight Decay: 1×10^{-2}

• KL Penalty Coefficient (λ_{KL}): 1×10^{-2}

• Max Steps: 40

• Number of Rollouts: 16

• Rollout Temperature: 1.0

Rollout Temp: 0.99

6: title

7: plain text

• Global Batch Size: 128

• Learning Rate: 1×10^{-6}

• Weight Decay: 1×10^{-2}

• KL Penalty Coefficient (λ_{KL}): 1×10^{-2}

• Max Steps: 5

• Number of Rollouts: 4

• Rollout Temperature: 1.0

Rollout Temp: 0.99

8: title

12: plain text

This section presents the prompt templates used for the executor and curriculum agent, and judge prompt in Table 6, Table 7 and Table 8.

10: plain text

11: title

Table 6. Prompt template used for executor agent

13: plain text

A conversation between User and Assistant. The user asks a question, and the Assistant solves it. The assistant first thinks about the reasoning process in the mind and then provides the user with the answer. User: Please integrate natural language reasoning with programs to solve the problem above. If you want to run any python code, write code in the python markdown code block and the execution will be appended in an output code block like `'''python` `print("Hello world")'''`. 'output result here'. Please put your final answer within `boxed{}`.

14: plain text

(problem)

16: abandon

0: abandon

Agent 0: Unleashing Self-Evolving Agents from Zero Data via Tool-Integrated Reasoning

2: table_caption

3: title

4: plain text

You are an expert competition-math problem setter. FIRST, in your private scratch-pad, think step-by-step to design a brand-new, non-trivial problem. The problem could come from any field of mathematics, including but not limited to algebra, geometry, number theory, combinatorics, prealgebra, probability, statistics, and calculus. Aim for a difficulty such that fewer than 30% of advanced high-school students could solve it. Avoid re-using textbook cliches or famous contest problems. THEN, without revealing any of your private thoughts, output exactly the following two blocks:

<question>

The full problem statement on one or more lines

5: plain text

6: plain text

7: title

Annotations, no extra markup

User Prompt 8: plain text

Generate one new, challenging reasoning question now. Remember to format the output exactly as instructed.

9: plain text

Table 7: Prompt template used for curriculum agent. We use the GPT-4o (Achiam et al., 2023) as the judge model (temperature: 0.1)

10: title

11: plain text

12: title

13: plain text

Hi, there is an answer: {answer}, and the ground truth answer is: {response}, please check whether the answer is correct or not, and return the **only** Yes or No.

14: title

15: plain text

We integrated a Python-based code execution sandbox (Cheng et al., 2025) to enable verification and algorithmic reasoning. The system comprises two core components: a Multi-Turn Interaction Protocol and a Distributed Execution Orchestrator.

16: plain text

Multi-Turn Interaction Protocol. We employ a “stop-and-go” strategy to facilitate multi-step reasoning: The model is instructed to generate reasoning followed by executable Python code within markdown delimiters. Upon detecting a code block via regex, generation halts. The code is extracted and run in an isolated sandbox, capturing stdout or stderr. Execution results are appended to the conversation history. The model then interprets these results to derive a final answer formatted in 17: plain text`ed{...}.`

Distributed Execution Orchestrator. To manage parallel candidate generation (e.g., $N = 10$), we implemented a load-balancing mechanism: Execution is decoupled into isolated worker nodes to prevent interference with the main inference server. A thread-safe Round-Robin scheduler distributes requests across nodes. A ThreadPoolExecutor manages asynchronous calls, preventing main loop blocking. The system robustly handles network timeouts and failures, feeding 18: plain text model for potential self-correction.

Infrastructure. Built on Flask and vLLM (Kwon et al., 2023), the system ensures high throughput. To maintain stability, a background thread performs low-priority tensor operations during idle periods, preventing GPU deep sleep and ensuring consistent latency.

19: title

20: plain text

Base Model: The pre-trained base model without any fine-tuning

21: abandon

0: abandon

1: plain text

- Base Model w/ tool: The base model evaluated in a zero-shot setting, but given access to the code interpreter.

2: plain text

- Absolute Zero (Zhao et al., 2025): A self-evolving framework that operates from zero data, but does not utilize external tools.

3: plain text

- 25a): A self-play method based on zero-sum games and multi-turn interactions.

4: title

5: plain text

- AMC: A collection of problems from standard American middle and high school math competitions, serving as a benchmark for pre-collegiate mathematical reasoning.

6: plain text

- Minerva (Lewkowycz et al., 2022): The dataset evaluates the model's ability to handle formal scientific notation and solve worded questions.

7: plain text

- MATH (Hendrycks et al., 2021): A comprehensive dataset of challenging high school competition problems across various domains (e.g., geometry), requiring complex heuristic search and multi-step derivation.

8: plain text

- GSM8K (Cobbe et al., 2021): A classic benchmark consisting of high-quality grade school math word problems that test the model's ability to perform multi-step logic using basic arithmetic operations.

9: plain text

- Olympiad-Bench (He et al., 2024): An advanced benchmark aggregating extremely difficult problems from Chinese and international Olympiads, designed to probe the upper limits of LLM reasoning capabilities.

10: plain text

- AIME24 & AIME25: These datasets comprise problems from the 2024 and 2025 American Invitational Mathematics Exams, providing a rigorous test of advanced problem-solving on recent, likely uncontaminated data.

11: plain text

- SuperGPQA (Du et al., 2025): An evolution of the GPQA dataset (Rein et al., 2024), this benchmark features difficult graduate-level questions across scientific domains that are challenging even for experts, specifically designed to minimize retrieval shortcuts.

12: plain text

- MMLU-Pro (Wang et al., 2024b): An enhanced version of the MMLU benchmark (Hendrycks et al., 2020) that introduces harder questions, increased options, and more complex reasoning requirements to better differentiate between top-tier models.

13: plain text

- BBEH (Kazemi et al., 2025): A selected subset of challenging tasks from the Big-Bench suite (Srivastava et al., 2023) focusing on areas where language models traditionally struggle, such as symbolic manipulation, logical deduction, and mathematical reasoning.

15: title

16: title

1 Results and Analysis

17: plain text

Number of Turns on Performance

We investigate the impact of the conversation length on model performance by increasing the interaction turns from 1 to 4 during the curriculum generation phase. As shown in Table 9, extending the number of turns yields significant benefits. Compared to the single-turn baseline, the 4-turn setting improves the executor's overall performance by 3.4%, with specific gains of 3% on mathematical benchmarks and 2.6% on general domain tasks. This performance boost can be attributed to the increased complexity of the curriculum. Multi-turn interactions encourage the curriculum agent to generate tasks with longer context dependencies and progressive difficulty. Consequently, the executor is forced to enhance its capability to maintain consistency and reasoning over extended horizons, rather than relying on simple pattern matching.

18: title

19: plain text

For a more detailed analysis, we report the complete results of the 3-iteration experiments in Table 10 and Table 11. These tables provide a comprehensive breakdown of the agent's performance across all individual benchmarks, further validating the effectiveness and robustness of Agent0.

20: abandon

0: abandon

Agent 0: Unleashing Self-Evolving Agents from Zero Data via Tool-Integrated Reasoning

3: table_caption table_caption

Table 9: Ablation study on the number of turns. Increasing turns from 1 to 4 leads to consistent performance gains across all domains.

Number of Turns	Overall AVG	Math AVG	General AVG
1	35.5	50.4	30.8
2	35.8	50.7	31.1
3	36.1	51.2	31.3
4	36.7	51.9	31.6

4: table_caption

Table 10: Save results on mathematical reasoning benchmarks. The peak performance achieved during each model's training run in bold.

Model Name	X	O	Avg	AMC	Minerva	MATH	GSM8K	Olympiad	AIME25	AIME24
<i>Qwen3-4B-Base</i>										
Base Model	✗	✗	42.6	45.7	38.2	68.2	87.8	41.0	6.15	10.9
+ Agent 0 (Iter 1)	✓	✗	51.9	59.8	55.0	79.9	92.6	46.1	13.0	16.8
+ Agent 0 (Iter 2)	✓	✗	52.2	60.0	55.1	80.2	92.5	46.5	13.8	17.1
+ Agent 0 (Iter 3)	✓	✗	52.5	60.6	55.6	80.5	92.6	46.7	14.1	17.4
<i>Qwen3-8B-Base</i>										
Base Model	✗	✗	49.2	52.0	50.0	78.0	89.1	44.7	16.7	13.9
+ Agent 0 (Iter 1)	✓	✗	55.1	57.3	59.0	81.6	93.9	48.4	20.9	24.9
+ Agent 0 (Iter 2)	✓	✗	56.5	59.2	60.1	81.9	94.0	51.2	22.9	26.1
+ Agent 0 (Iter 3)	✓	✗	58.2	62.4	61.3	82.4	94.5	54.0	24.8	28.0

6: title

7: plain text

To provide qualitative evidence of the model's evolution, Table 12, Table 13, Table 14, Table 15, Table 16, Table 17, Table 18, Table 19, and Table 20 through 9 present three representative questions generated at each stage from Iteration 1 to Iteration 3. We observe a clear progression in difficulty: while the initial iteration features relatively straightforward queries, the tasks in Iteration 3 evolve into highly complex, multi-step problems requiring deep reasoning. This escalation is driven by the co-evolutionary dynamic, where the Curriculum Agent, incentivized to maximize the Executor's learning signal, must continuously push the difficulty frontier to challenge the Executor's expanding proficiency, thereby effectively preventing learning stagnation.

8: abandon

0: abandon

Agent 0: Unleashing Self-Evolving Agents from Zero Data via Tool-Integrated Reasoning

2: table

1: table_caption

Table 11. Results on general-domain reasoning benchmarks

Model Name			Overall AVG	MATH AVG	SuperGPQA	MMLU-Pro	BBEH
<i>Qwen3-4B-Base</i>							
Base Model			27.1	42.6	20.9	37.4	7.57
+ Agent 0 (Iter 1)			36.7	51.9	28.9	55.1	10.7
+ Agent 0 (Iter 2)			36.9	52.2	29.3	55.3	11.0
+ Agent 0 (Iter 3)			37.6	52.5	29.9	55.9	12.0
<i>Qwen3-8B-Base</i>							
Base Model			34.5	49.2	28.3	51.8	8.6
+ Agent 0 (Iter 1)			40.7	55.1	32.5	62.2	13.0
+ Agent 0 (Iter 2)			41.3	56.5	32.5	62.4	13.6
+ Agent 0 (Iter 3)			42.1	58.2	33.0	63.4	13.7

4: figure_caption

5: title

Table 12. Sampled questions generated by Curriculum Agent (Iter 1)

7: plain_text

im Agent

Let S be the set of all positive integers n

8: isolate_formula

$$P(x) = x^3 - 2023x^2 + nx - 1$$

9: plain_text

has three distinct positive integer roots. Find the sum of all elements in S .

11: title1_text

12: title

Table 13. Sampled questions generated by Curriculum Agent (Iter 1)

13: plain_text

im Agent

In a triangle ABC with side lengths a , b , and c (where $a = BC$, $b = CA$, and $c = AB$), let the area be K . If the incircle of the triangle touches BC , CA , and AB at D , E , and F respectively, and the lengths of BD , CE , and AF are x , y , and z respectively, prove that $x^2 + y^2 + z^2 \geq \frac{3K}{a}$.

15: title1_text

16: title

Table 14. Sampled questions generated by Curriculum Agent (Iter 1)

17: plain_text

im Agent

What is the minimum number of points inside a square with side length 1 that are needed to ensure that at least two of the points are at most 0.25 units apart from each other?

19: plain_text

20: title

Table 15. Sampled questions generated by Curriculum Agent (Iter 2)

21: plain_text

im Agent

On a 9×9 chessboard, initially one cell is black. In each move, you can choose a white cell that has at least one black cell in the same row or column and invert the color of that chosen cell from white to black. Determine the minimum number of moves required to turn the entire chessboard into a black board.

23: title1_text

24: title

Table 16. Sampled questions generated by Curriculum Agent (Iter 2)

26: plain_text

im Agent

Let $S = \{1, 2, 3, \dots, 100\}$. A subset A of S is called *good* if for any $x, y \in A$ (with $x \neq y$), the sum $x + y$ is not a perfect square. Find the maximum possible size of a *good* subset of S .

27: abandon

1: title

Table 17. Sampled questions generated by Curriculum Agent (Iter 2).

2: plain text

num Agent

In the land of Polytopia, each city is represented by a unique point on a large spherical map. The king decides to choose a special point on this sphere. To determine the location, he uses a sequence of operations on the coordinates.

3: plain text

The map is represented by a sphere where the equation $x^2 + y^2 + z^2 = 1$ holds for any point (x, y, z) representing a city. The king chooses two existing cities, A and B, with coordinates (a_1, a_2, a_3) and (b_1, b_2, b_3) , respectively. He defines a new city C with the formula:

4: isolate_formula

$$c_i = \frac{a_i^2 + b_i^2 + a_i b_i \cdot (1 + a_1 b_1 + a_2 b_2 + a_3 b_3)}{1 + a_1^2 + a_2^2 + a_3^2 + b_1^2 + b_2^2 + b_3^2 + (a_1 b_1 + a_2 b_2 + a_3 b_3)^2}$$

5: plain text

Given that the coordinates of city A are $\left(\frac{1}{2}, \frac{1}{2}, \frac{\sqrt{2}}{2}\right)$ and the coordinates of city B are $\left(-\frac{1}{2}, \frac{1}{2}, \frac{\sqrt{2}}{2}\right)$, find the coordinates of the new city C.

7: figure_caption

8: title

Table 18. Sampled questions generated by Curriculum Agent (Iter 3).

9: plain text

num Agent

A sequence of positive integers $a_1, a_2, a_3, \dots, a_{2024}$ is defined such that for each $n \geq 1$, the number a_{n+1} is determined by the rule $a_{n+1} = a_n + \lfloor \sqrt{a_n} \rfloor$, starting with $a_1 = 1$. Find the remainder when a_{2024} is divided by 1000.

10: plain text

11: title

Table 19. Sampled questions generated by Curriculum Agent (Iter 3).

12: plain text

num Agent

In a knockout tournament with 2^n players, where n is a positive integer, each match eliminates one player. The tournament is structured such that each round halves the number of players. What is the minimum number of matches that must be played to determine the champion if, for each round, the number of matches played is a Fibonacci number?

14: title

15: title

Table 20. Sampled questions generated by Curriculum Agent (Iter 3).

16: plain text

num Agent

A circle is divided into 2023 congruent arcs. The endpoints of one arc are colored red and blue. If two points that are diametrically opposite are both colored red, what is the probability that the two endpoints of the arc directly adjacent to the red endpoints are both blue? Express your answer as a common fraction.

18: abandon