

CS153: Design of Operating Systems

You can use sledge server for the course labs.

```
$ ssh -X username@sledge.cs.ucr.edu
```

On MACOS:

```
$ ssh -Y username@sledge.cs.ucr.edu
```

Windows users may find “MobaXterm” to be a good SSH and FTP client (the free version):

<https://mobaxterm.mobatek.net/download.html>

MAC users will need:

<https://www.xquartz.org/>

for GUI

To download xv6:

```
$ git clone https://github.com/mit-pdos/xv6-public.git
```

```
$ cd xv6-public
```

Note: whenever you want to discard all of your changes do this in xv6-public:

```
$ git checkout .
```

Links:

[xv6 book](#)

[xv6 indexed/cross referenced code](#)

To run XV6:

```
$ make qemu
```

If the mouse pointer gets stuck in the QEMU emulator window press: Ctrl + Alt + G

Hint: Always do “make clean” first

```
$ make clean && make qemu
```

You may find the QEMU window to be slow so it is recommended you do this instead:

```
$ make clean && make qemu-nox
```

To exit XV6, use “ctrl + a” then hit “x”

Note: you may find the text editor geany to be useful:

```
$ cd xv6-public/
```

```
$ geany *.c *.h *.S Makefile &
```

You can right click a function or variable to find where it has been defined and used in the code.

For a quick vim tutorial type in terminal:

```
$ vimtutor
```

If you want to use vim instead of geany, use ctags to help you index the code:

<https://andrew.stwrt.ca/posts/vim-ctags/>

This grep command is helpful:

```
$ grep -rnw --color . -e "search string"
```

<https://www.cyberciti.biz/faq/howto-use-grep-command-in-linux-unix/>

hint: do “make clean” before running grep and be aware that grep results will conflict with the ctags generated file.

To run Qemu with GDB

You need to do this the first time only, in your **home** dir:

```
$ cd ~
```

```
$ echo "add-auto-load-safe-path /home/csmajs/NetID/xv6-public/.gdbinit" >> .gdbinit
```

I am assuming that your xv6 folder is placed in your home directory and named "xv6-public"

Otherwise here is a generic one;

```
$ cd ~
```

```
$ echo "add-auto-load-safe-path /home/csmajs/NetID/PATH_TO_XV6_FOLDER/.gdbinit" >> .gdbinit
```

After that you need to open another terminal at the same xv6-public folder:

```
$ xfce4-terminal &
```

In the original terminal type:

```
$ cd xv6-public
```

```
$ make qemu-gdb
```

Or \$ make qemu-nox-gdb

In the second terminal type:

```
$ cd xv6-public
```

```
$ gdb
```

```
+ target remote localhost:25049
```

```
The target architecture is assumed to be i8086 [f000:fff0] 0xffff0: ljmp $0xf000,$0xe05b  
0x0000fff0 in ?? ()
```

```
+ symbol-file kernel
```

```
$ (gdb) continue
```

For GDB with GUI, type:

```
$ gdb -tui
```

Here is a GBD tutorial:

<http://www.gdbtutorial.com>