

Importing the Dependencies

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.cluster import KMeans
```

Data Collection & Analysis

```
# loading the data from csv file to a Pandas DataFrame
customer_data = pd.read_csv('/content/Mall_Customers.csv')
```

```
# first 5 rows in the dataframe
customer_data.head()
```

	CustomerID	Gender	Age	Annual Income (k\$)	Spending Score (1-100)
0	1	Male	19	15	39
1	2	Male	21	15	81
2	3	Female	20	16	6
3	4	Female	23	16	77
4	5	Female	31	17	40

```
# finding the number of rows and columns
customer_data.shape
```

```
(200, 5)
```

```
# getting some informations about the dataset
customer_data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 200 entries, 0 to 199
Data columns (total 5 columns):
#   Column                Non-Null Count  Dtype
---  -
0   CustomerID            200 non-null   int64
1   Gender                200 non-null   object
2   Age                  200 non-null   int64
3   Annual Income (k$)    200 non-null   int64
4   Spending Score (1-100) 200 non-null   int64
dtypes: int64(4), object(1)
memory usage: 7.9+ KB
```

```
# checking for missing values
customer_data.isnull().sum()
```

```
CustomerID      0
Gender          0
Age             0
Annual Income (k$) 0
Spending Score (1-100) 0
dtype: int64
```

Choosing the Annual Income Column & Spending Score column

```
X = customer_data.iloc[:, [3, 4]].values
```

```
print(X)
```

```
[[ 15  39]
 [ 15  81]
 [ 16   6]
 [ 16  77]
 [ 17  40]
 [ 17  76]
 [ 18   6]
 [ 18  94]
 [ 19   3]
 [ 19  72]
 [ 19  14]
 [ 19  99]
```

```
[ 20 15]
[ 20 77]
[ 20 13]
[ 20 79]
[ 21 35]
[ 21 66]
[ 23 29]
[ 23 98]
[ 24 35]
[ 24 73]
[ 25  5]
[ 25 73]
[ 28 14]
[ 28 82]
[ 28 32]
[ 28 61]
[ 29 31]
[ 29 87]
[ 30  4]
[ 30 73]
[ 33  4]
[ 33 92]
[ 33 14]
[ 33 81]
[ 34 17]
[ 34 73]
[ 37 26]
[ 37 75]
[ 38 35]
[ 38 92]
[ 39 36]
[ 39 61]
[ 39 28]
[ 39 65]
[ 40 55]
[ 40 47]
[ 40 42]
[ 40 42]
[ 42 52]
[ 42 60]
[ 43 54]
[ 43 60]
[ 43 45]
[ 43 41]
[ 44 50]
[ 44 45]
```

Choosing the number of clusters

WCSS -> Within Clusters Sum of Squares

```
# finding wcss value for different number of clusters


wcss = []

for i in range(1,11):
    kmeans = KMeans(n_clusters=i, init='k-means++', random_state=42)
    kmeans.fit(X)

    wcss.append(kmeans.inertia_)

# plot an elbow graph

sns.set()
plt.plot(range(1,11), wcss)
plt.title('The Elbow Point Graph')
plt.xlabel('Number of Clusters')
plt.ylabel('WCSS')
plt.show()
```

[illegible]

Visualizing all the Clusters

<https://colab.research.google.com/drive/1izGP15oreJ9zFZ4qi8jz9jaK3nuhb8a2?usp=sharing#scrollTo=mDtt8uP0MoiH&printMode=true>

