

TASK1

```
jhansi_priya@Jhansi-Priya: ~/  + 
jhansi_priya@Jhansi-Priya:~$ cd skill3
jhansi_priya@Jhansi-Priya:~/skill3$ pwd
/home/jhansi_priya/skill3
jhansi_priya@Jhansi-Priya:~/skill3$ gcc --version
gcc (Ubuntu 13.3.0-6ubuntu2~24.04.1) 13.3.0
Copyright (C) 2023 Free Software Foundation, Inc.
This is free software; see the source for copying conditions. There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

jhansi_priya@Jhansi-Priya:~/skill3$ nano task1.c
jhansi_priya@Jhansi-Priya:~/skill3$ gcc task1.c -o task1
jhansi_priya@Jhansi-Priya:~/skill3$ ./task1
myshell> hello
You entered: hello
myshell> linux
You entered: linux
myshell> exit
Exiting shell...
jhansi_priya@Jhansi-Priya:~/skill3$ nano File1.txt
jhansi_priya@Jhansi-Priya:~/skill3$ cat File1.txt
Hello, this is File 1.
This content will be copied to File 2.

jhansi_priya@Jhansi-Priya:~/skill3$ nano task2.c

jhansi_priya@Jhansi-Priya:~/skill3$ gcc task2.c -o task2
task2.c: In function 'main':
task2.c:37:1: error: expected expression before '=' token
37 | =
   | ^
```

```
 jhansi_priya@Jhansi-Priya: ~/  
GNU nano 7.2
#include <stdio.h>
#include <string.h>

int main()
{
    char input[100];

    while (1)
    {
        printf("myshell> ");

        fgets(input, sizeof(input), stdin);

        input[strcspn(input, "\n")] = '\0';

        if (strcmp(input, "exit") == 0)
        {
            printf("Exiting shell...\n");
            break;
        }

        printf("You entered: %s\n", input);
    }

    return 0;
}
```

TASK2

```
jhansi_priya@Jhansi-Priya:~/skill3$ nano task2.c

jhansi_priya@Jhansi-Priya:~/skill3$ gcc task2.c -o task2
jhansi_priya@Jhansi-Priya:~/skill3$ ./task2
File copied successfully.
jhansi_priya@Jhansi-Priya:~/skill3$ cat File2.txt
Hello, this is File 1.
This content will be copied to File 2.

jhansi_priya@Jhansi-Priya:~/skill3$
```

```
GNU nano 7.2
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>

int main()
{
    int source, destination;
    char buffer[100];
    int bytesRead;

    source = open("File1.txt", O_RDONLY);

    if (source < 0)
    {
        perror("Error opening File1.txt");
        return 1;
    }

    destination = open("File2.txt",
                      O_WRONLY | O_CREAT | O_TRUNC,
                      0644);

    if (destination < 0)
    {
        perror("Error opening File2.txt");
        close(source);
        return 1;
    }

    while ((bytesRead = read(source, buffer, sizeof(buffer))) > 0)
    {
        write(destination, buffer, bytesRead);
    }

    close(source);
    close(destination);

    printf("File copied successfully.\n");

    return 0;
}
```

TASK3

```
jhansi_priya@Jhansi-Priya:~/skill3$ nano task2.c

jhansi_priya@Jhansi-Priya:~/skill3$ gcc task2.c -o task2
jhansi_priya@Jhansi-Priya:~/skill3$ ./task2
File copied successfully.
jhansi_priya@Jhansi-Priya:~/skill3$ cat File2.txt
Hello, this is File 1.
This content will be copied to File 2.

jhansi_priya@Jhansi-Priya:~/skill3$ nano task3.c
jhansi_priya@Jhansi-Priya:~/skill3$ gcc task3.c -o task3
jhansi_priya@Jhansi-Priya:~/skill3$ ./task3

Enter command:
You entered:

Enter command:
You entered:
hello
Enter command: hello
You entered: hello

Enter command:
You entered:
hellp
Enter command: hellp
You entered: hellp
exit
Enter command: exit
You entered: exit
```

```
GNU nano 7.2 task3.c *
#include <stdio.h>
#include <unistd.h>
#include <termios.h>

int main()
{
    char buffer[100];
    int position = 0;
    char ch;

    printf("Enter command: ");

    while (1)
    {
        read(STDIN_FILENO, &ch, 1);

        if (ch == '\n')
        {
            buffer[position] = '\0';

            printf("\nYou entered: %s\n", buffer);

            if (position == 4 &&
                buffer[0] == 'e' &&
                buffer[1] == 'x' &&
                buffer[2] == 'i' &&
                buffer[3] == 't')
            {
                break;
            }
        }
    }
}
```

```

        buffer[3] == 't')
    {
        break;
    }

    position = 0;
    printf("Enter command: ");
}
else if (ch == 127)
{
    if (position > 0)
    {
        position--;
        printf("\b \b");
    }
}
else
{
    if (position < 99)
    {
        buffer[position] = ch;
        position++;

        printf("%c", ch);
    }
}

return 0;
}

```

[^]G Help
[^]X Exit

[^]O Write Out
[^]R Read File

[^]W Where Is
[^]\ Replace

[^]K Cut
[^]U Paste

[^]T Execute
[^]J Justify

TASK4

```
jhansi_priya@Jhansi-Priya:~/skill3$ pwd
/home/jhansi_priya/skill3
jhansi_priya@Jhansi-Priya:~/skill3$ ls
File1.txt  file1.txt  task1.c  task2.c  task3.c
File2.txt  task1      task2    task3
jhansi_priya@Jhansi-Priya:~/skill3$ nano task4.c
jhansi_priya@Jhansi-Priya:~/skill3$ gcc task4.c -o task4
jhansi_priya@Jhansi-Priya:~/skill3$ ./task4
myshell> hello
You entered: hello
myshell> jhansi
You entered: jhansi
myshell> how are you keerthi
You entered: how are you keerthi
myshell> I am good
You entered: I am good
myshell> exit
jhansi_priya@Jhansi-Priya:~/skill3$ |
```

```
GNU nano 7.2
#include <stdio.h>
#include <unistd.h>
#include <termios.h>
#include <string.h>

#define MAX_INPUT 100
#define MAX_HISTORY 10

char history[MAX_HISTORY][MAX_INPUT];

int history_count = 0;
int history_index = 0;

void clear_line()
{
    printf("\033[2K\r");
    printf("myshell> ");
}

int main()
{
    char buffer[MAX_INPUT];
    int index;
    char ch;

    struct termios oldt, newt;

    /* Save original terminal settings */
    tcgetattr(STDIN_FILENO, &oldt);

    /* Create new terminal settings */
    newt = oldt;

    newt.c_lflag &= ~(ICANON | ECHO);

    /* Apply new settings */
    tcsetattr(STDIN_FILENO, TCSANOW, &newt);

    while (1)
    {
        printf("myshell> ");
        fflush(stdout);

        index = 0;
        buffer[0] = '\0';
```

```
jhansi_priya@Jhansi-Priya: ~/  + v
GNU nano 7.2

index = 0;
buffer[0] = '\0';

while (1)
{
    read(STDIN_FILENO, &ch, 1);

    /* ENTER */
    if (ch == '\n' || ch == '\r')
    {
        buffer[index] = '\0';
        printf("\n");
        break;
    }

    /* BACKSPACE */
    else if (ch == 127 || ch == 8)
    {
        if (index > 0)
        {
            index--;
            printf("\b \b");
            fflush(stdout);
        }
    }

    /* ESCAPE SEQUENCE */
    else if (ch == 27)
    {
        char seq1;
        char seq2;

        read(STDIN_FILENO, &seq1, 1);
        read(STDIN_FILENO, &seq2, 1);

        /* UP ARROW */
        if (seq1 == '[' && seq2 == 'A')
        {
            if (history_count > 0 && history_index > 0)
            {

```

```
jhansi_priya@Jhansi-Priya: ~/  + v
GNU nano 7.2

        /* UP ARROW */
        if (seq1 == '[' && seq2 == 'A')
        {
            if (history_count > 0 && history_index > 0)
            {
                history_index--;
                strcpy(buffer, history[history_index]);
                index = strlen(buffer);
                clear_line();
                printf("%s", buffer);
                fflush(stdout);
            }
        }

        /* DOWN ARROW */
        else if (seq1 == '[' && seq2 == 'B')
        {
            if (history_index < history_count - 1)
            {
                history_index++;
                strcpy(buffer, history[history_index]);
                index = strlen(buffer);
                clear_line();
                printf("%s", buffer);
                fflush(stdout);
            }
            else
            {
                history_index = history_count;
                buffer[0] = '\0';
                index = 0;
            }
        }
    }
}
```

GNU nano 7.2

```
        buffer[0] = '\\0';
        index = 0;
        clear_line();
        fflush(stdout);
    }
}

/* NORMAL CHARACTER */
else
{
    if (index < MAX_INPUT - 1)
    {
        buffer[index] = ch;
        index++;
        write(STDOUT_FILENO, &ch, 1);
    }
}

/* EXIT */
if (strcmp(buffer, "exit") == 0)
{
    break;
}

/* STORE COMMAND IN HISTORY */
if (strlen(buffer) > 0)
{
    if (history_count < MAX_HISTORY)
    {
        strcpy(history[history_count], buffer);
        history_count++;
    }

    history_index = history_count;
}

printf("You entered: %s\\n", buffer);
```

```
if (strcmp(buffer, "exit") == 0)
{
    break;
}

/* STORE COMMAND IN HISTORY */
if (strlen(buffer) > 0)
{
    if (history_count < MAX_HISTORY)
    {
        strcpy(history[history_count], buffer);
        history_count++;
    }

    history_index = history_count;
}

printf("You entered: %s\\n", buffer);
}

/* Restore original terminal settings */
tcsetattr(STDIN_FILENO, TCSANOW, &oldt);

return 0;
}
```

TASK5

```
jhansi_priya@Jhansi-Priya: ~/ X + v

jhansi_priya@Jhansi-Priya:~$ cd skill3
jhansi_priya@Jhansi-Priya:~/skill3$ nano task5.c
jhansi_priya@Jhansi-Priya:~/skill3$ gcc task1.c -o task1
jhansi_priya@Jhansi-Priya:~/skill3$ ./task1
myshell> exit
Exiting shell...
jhansi_priya@Jhansi-Priya:~/skill3$ gcc task5.c -o task5
jhansi_priya@Jhansi-Priya:~/skill3$ ./task5
myshell> hello
You entered: hello
myshell> good
You entered: good
myshell> nice
You entered: nice
myshell> exit
```

```
GNU nano 7.2

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

typedef struct Node
{
    char *command;
    struct Node *next;
} Node;

Node *head = NULL;

/* Add a command to the linked list */
void add_history(const char *command)
{
    Node *new_node;

    new_node = malloc(sizeof(Node));

    if (new_node == NULL)
    {
        perror("malloc failed");
        exit(1);
    }

    new_node->command = malloc(strlen(command) + 1);

    if (new_node->command == NULL)
    {
        perror("malloc failed");
        free(new_node);
        exit(1);
    }

    strcpy(new_node->command, command);

    new_node->next = NULL;

    if (head == NULL)
```



```
jhansi_priya@Jhansi-Priya: ~/  × + ▾
GNU nano 7.2

    if (head == NULL)
    {
        head = new_node;
    }
    else
    {
        Node *current = head;

        while (current->next != NULL)
        {
            current = current->next;
        }

        current->next = new_node;
    }
}

/* Display all stored commands */
void display_history()
{
    Node *current = head;
    int number = 1;

    while (current != NULL)
    {
        printf("%d %s\n", number, current->command);

        current = current->next;
        number++;
    }
}

/* Free the complete linked list */
void free_history()
{
    Node *current = head;

    while (current != NULL)
    {
        |
```

```
jhansi_priya@Jhansi-Priya: ~/  × + ▾
GNU nano 7.2

/* Free the complete linked list */
void free_history()
{
    Node *current = head;

    while (current != NULL)
    {
        Node *temp = current;

        current = current->next;

        free(temp->command);
        free(temp);
    }

    head = NULL;
}

int main()
{
    char *buffer = NULL;
    size_t buffer_size = 0;
    ssize_t length;

    while (1)
    {
        printf("mysHELL> ");
        fflush(stdout);

        length = getline(&buffer, &buffer_size, stdin);

        if (length == -1)
        {
            break;
        }

        if (length > 0 && buffer[length - 1] == '\n')
        {
            |
            buffer[length - 1] = '\0';
        }
    }
}
```

jhansi_priya@Jhansi-Priya: ~/    

GNU nano 7.2

```
    printf("myshell> ");
    fflush(stdout);

    length = getline(&buffer, &buffer_size, stdin);

    if (length == -1)
    {
        break;
    }

    if (length > 0 && buffer[length - 1] == '\n')
    {
        buffer[length - 1] = '\0';
    }

    if (strcmp(buffer, "exit") == 0)
    {
        break;
    }

    if (strcmp(buffer, "history") == 0)
    {
        display_history();
        continue;
    }

    if (strlen(buffer) > 0)
    {
        add_history(buffer);
    }

    printf("You entered: %s\n", buffer);
}

free(buffer);
free_history();

return 0;
}
```

