USDT checkout without customer WBT

A customer can hold the payment token and still be unable to check out. Native gas, network setup and merchant settlement plumbing add friction to a simple purchase.

— Customers need a clear amount to authorize

— Merchants need a receipt they can verify

— Gas funding is a separate operational job

The relayer pays gas. The customer authorizes USDT.

Two public SDKs connect checkout to a merchant API, a funded relayer and atomic onchain payouts. The price and any sponsorship fee are shown before the customer signs.

— 1 USDT merchant price

— 0.001 USDT disclosed fee

— 1.001 USDT total; payer WBT stays zero

One purchase, two different responsibilities

The customer reviews the exact terms and signs two authorizations. The merchant creates the session on its server and delivers only after verifying settlement evidence.

— Buyer: review → authorize → confirmed receipt

— Merchant: session → signed webhook → one entitlement

— A browser success callback never grants the purchase

Authorization, settlement and fulfillment

The merchant bridge protects customer session ownership. PostgreSQL persists exact quotes and attempts. The checkout enforces signed payouts; the indexer and merchant verify the resulting receipt.

— Merchant backend → API → funded relayer

— Whitechain checkout → official test USDT

— Matched event → outbox → verified fulfillment

A confirmed payment, with zero payer WBT

The real widget payment at block 12383593 settled the official token on chain 1874. Historical checks verified exact payouts, a zero-WBT payer and read-only replay rejection.

— Merchant +1 USDT; fee recipient +0.001 USDT

— Payer −1.001 USDT; WBT 0 → 0

— Funded relayer paid the native network fee

Checkout 0x4d1761abb4ed290f23fcda00890039800e2e53f0
Transaction 0x77784da3835084852e0f3904ba6845011725ffade891175b4b4a96d93948b41c

Bind the terms. Reconcile uncertain execution.

The order binds payer, merchant, token, amount, fee, domain and expiry. Atomic payouts and payer-scoped replay protection cover settlement; durable attempts and idempotent fulfillment cover retries.

— Tampering, rollback and replay tests

— Simulation, fee limits and a safety cutoff

— Verify the raw webhook; deduplicate in one transaction

The same SDKs, two independent merchants

The SaaS grants credits; the digital shop unlocks downloads. Each owns its credentials, customer records and fulfillment. The small React component needs an authenticated merchant server bridge.

— Public @whitepay/node and @whitepay/react alpha packages

— Frontend under 20 lines; server work is additional

— Two independent app tests use controlled receipts

A working proof, with explicit next gates

Whitechain supplies the official token and inspectable settlement. Operate alignment is the reusable integration. Source verification remains open; hosted worker delivery is pending. Video and final qualification are still to come.

— Published SDKs, docs and a real official-USDT receipt

— Complete hosted fulfillment, source verification and adversarial checks

— No mainnet, refunds or recurring subscriptions in this MVP