Anup Barman's

CP-Arsenal

AnupBarman | AnupBarman | anup_barman

Updated: April 13, 2026

Contents

1 Setup 1
- 1.1 Linux Build 1
- 1.2 Windows Build 1

2 Code 1
- 2.1 Aho Corasic 1
- 2.2 Articulation Point 2
- 2.3 BFS 2
- 2.4 Bellman Ford 2
- 2.5 Bridge Finding Algorithm 2
- 2.6 Centroid Decomposition 2
- 2.7 Co-Ordinate Compression 2
- 2.8 CoinChange(MinCoins) 2
- 2.9 CoinChange(NumberOfWays) 3
- 2.10 CountSubsetWithSumK 3
- 2.11 Cycle Detection in DAG 3
- 2.12 DSU on Trees 3
- 2.13 DSU 3
- 2.14 Digit DP 3
- 2.15 Dijkastra 3
- 2.16 Divisor Sieve 3
- 2.17 EditDistance 4
- 2.18 Euler Tour 4
- 2.19 Fast-Unordered-Map 4
- 2.20 Floyd Warshall 4
- 2.21 Inverse_Mod 4
- 2.22 Is Sorted 4
- 2.23 LCA using Binary Lifting 4
- 2.24 LCS for 3 Strings 4
- 2.25 LIS 4
- 2.26 Lucas 4
- 2.27 MST(Dense Graph) 4
- 2.28 MST(Sparse Graph) 5
- 2.29 Manachar 5
- 2.30 Matrix Exponentiation 5
- 2.31 Matrix Rotation 5
- 2.32 Max Bipartite Matching [Hopcroft-Karp] 5
- 2.33 Max Bipartite Matching [Kuhn's] 6
- 2.34 Max Flow 6
- 2.35 Max Subarray Size Sum equal K 6
- 2.36 Maximum Subarray Sum(Kadanes) 6
- 2.37 Merge Sort 6
- 2.38 Mex of All Subarray 7
- 2.39 Mobius Function 7
- 2.40 Number of Pairs with GCD equal g 7
- 2.41 Number of Subarray Sum is K 8
- 2.42 PBDS 8
- 2.43 Phi(1 to N) 8
- 2.44 Phi 8
- 2.45 Print Binary 8
- 2.46 Range-xor-Trick 8
- 2.47 SCC 8
- 2.48 SOD NOD 8
- 2.49 Segment Tree(BSUA) 8
- 2.50 Segment Tree(LzP) 9
- 2.51 Segment Tree 9
- 2.52 Segmented Sieve 9
- 2.53 Sparse-Table 9
- 2.54 String Hashing 2 9
- 2.55 String Hashing 9
- 2.56 Tonelli-Shanks 10
- 2.57 Topological Sorting 10
- 2.58 Unique Elements in vector 10
- 2.59 Unique Prime Factorization using Sieve 10
- 2.60 Weighted Union Find 10
- 2.61 erase-while-iteration 10
- 2.62 int128 10
- 2.63 legendre 11
- 2.64 nCr-and-nPr 11

3 Geometry 11
- 3.1 Convex Hull 11
- 3.2 Line Line Intersection 11
- 3.3 Point in Polygon 11
- 3.4 Polygon Area 11
- 3.5 Polygon Lattice Points 11
- 3.6 Template 11

4 Notes 12
- 4.1 Geometry 12
- 4.2 Binomial Coefficent 12
- 4.3 Wilson's Theorem 12
- 4.4 Fibonacci Number 12
- 4.5 Sums 12
- 4.6 Series 13
- 4.7 Pythagorean Triples 13
- 4.8 Number Theory 13
- 4.9 Permutations 13
- 4.10 Partitions and subsets 14
- 4.11 Coloring 14
- 4.12 General purpose numbers 14
- 4.13 Ballot Theorem 14
- 4.14 Classical Problem 14
- 4.15 Matching Formula 14
- 4.16 Inequalities 14
- 4.17 Games 14
- 4.18 Tree Hashing 15
- 4.19 Permutation 15
- 4.20 String 15
- 4.21 Bit 15
- 4.22 Convolution 15
- 4.23 Matrix Rotation 15
- 4.24 Common Formulas 15
- 4.25 Logarithms 15
- 4.26 Common Series Sums 15
- 4.27 Progressions 15

1 Setup

1.1 Linux Build

```
{
  "cmd" : ["ulimit -s 268435456; g++ -std=c++20
      $file_name -o $file_base_name && timeout 4s
  ⇄  ./$file_base_name < input.txt > output.txt"],
  "selector" : "source.c++",
  "shell" : true,
  "working_dir" : "$file_path"
}
```

1.2 Windows Build

```
{
  "cmd" : [ "g++.exe", "-std=c++20", "${file}", "-o",
      "${file_base_name}.exe", "&&",
  ⇄  "${file_base_name}.exe<input.txt>output.txt" ],
  "selector" : "source.cpp",
  "shell" : true,
  "working_dir" : "$file_path"
}
```

2 Code

2.1 Aho Corasic

```
//number of occourence of word in a text
const ll N = 1e6+10, A = 26;
ll trie[N][A], pos[N], slink[N], dp[N], tot = 1;
vector<int> order;
void initTrie(){
  order.clear();
  while(tot--){
    memset(trie[tot], 0, sizeof(trie[tot]));
  }
  memset(pos, 0, sizeof(pos));
  memset(slink, 0, sizeof(slink));
  memset(dp, 0, sizeof(dp)); tot = 1;
}
void addStr(string &s, int ind){
  ll u = 0;
  for(auto it: s){
    ll n = it-'a';
    if(trie[u][n]==0) trie[u][n] = tot++;
    u = trie[u][n];
  } pos[ind] = u;
}
void build(){
  queue<ll> q; q.push(0);
  while(!q.empty()){
    ll p = q.front(); q.pop();
    order.push_back(p);
    for(ll c = 0; c<A; c++){
      ll u = trie[p][c];
      if(!u) continue;
      q.push(u);
      if(!p) continue;
      ll v = slink[p];
      while(v && !trie[v][c]) v = slink[v];
      slink[u] = trie[v][c];
    }
  }
}
void trav(string &s){
  ll u = 0;
  for(char c: s){
    c-='a';
    while(u && !trie[u][c]) u = slink[u];
    u = trie[u][c]; dp[u]++;
  }
  reverse(order.begin(), order.end());
  for(auto u: order){
    dp[slink[u]]+=dp[u];
  }
}
void solve(){
  ll n; cin>>n;
  string text; cin>>text;
  string s;
  for(ll i = 0; i<n; i++){
    cin>>s; addStr(s, i);
  }
  build(); trav(text);
  for(ll i = 0; i<n; i++){
    cout<<dp[pos[i]]<<endl;
  }
}
int32_t main(){
  ios_base::sync_with_stdio(0);
  cin.tie(0);
  ll tc = 1;
  cin>>tc;
  for(ll i = 1; i<=tc;i++){
    cout<<"Case "<<i<<": \n";
    initTrie();
    solve();
  }
}
```

2.2 Articulation Point

```
int n;                      // number of nodes
vector<vector<int>> lst;    // adjacency list of graph
vector<bool> vis;
vector<int> tin, low;
int timer;
void dfs(int u, int p = -1) {
  vis[u] = true;
  tin[u] = low[u] = timer++;
  int children = 0;
  for (int v : lst[u]) {
    if (v == p) continue;
    if (vis[v]) {
      low[u] = min(low[u], tin[v]);
    } else {
      dfs(v, u);
      low[u] = min(low[u], low[v]);
      if (low[v] >= tin[u] && p != -1)
        IS_CUTPOINT(u);
      ++children;
    }
  }
  // if no vertex below v can reach u or higher
  ↪ removing u disconnects that subtree
  if (p == -1 && children > 1)
    IS_CUTPOINT(u);
}
void find_cutpoints() {
  timer = 0;
  vis.assign(n, false);
  tin.assign(n, -1);
  low.assign(n, -1);
  for (int i = 0; i < n; ++i) {
    if (!vis[i])
      dfs(i);
  }
}
```

2.3 BFS

```
vector<vector<int>> adj;  // adjacency list
↪ representation
int n;                    // number of nodes
int s;                    // source vertex
void bfs() {
  queue<int> q;
  vector<int> d(n), p(n);
  vector<bool> used(n);
  q.push(s);
  used[s] = true;
  p[s] = -1;
  while (!q.empty()) {
    int v = q.front();
    q.pop();
    for (int u : adj[v]) {
      if (!used[u]) {
        used[u] = true;
        q.push(u);
        d[u] = d[v] + 1;
        p[u] = v;
      }
    }
  }
}
// retrieving shortest path
if (!used[u]) {
  cout << "No path!";
} else {
  vector<int> path;
  for (int v = u; v != -1; v = p[v])
    path.push_back(v);
  reverse(path.begin(), path.end());
  cout << "Path: ";
  for (int v : path)
    cout << v << " ";
}
```

2.4 Bellman Ford

```
#define ll long long
#define INF 1e18
void solve() {
  int n, m, v;
  cin >> n >> m >> v;  // n = nodes, m = edges, v =
  ↪ source (0-indexed)
  vector<array<ll, 3>> edges(m);  // each edge: {a, b,
  ↪ cost}
  for (int i = 0; i < m; i++) cin >> edges[i][0] >>
  ↪ edges[i][1] >> edges[i][2];
  vector<ll> d(n, INF);
  vector<int> p(n, -1);
  d[v] = 0;
  int x = -1;
  for (int i = 0; i < n; i++) {
    x = -1;
    for (auto& e : edges) {
      int a = e[0], b = e[1];
      ll cost = e[2];
      if (d[a] < INF && d[b] > d[a] + cost) {
        d[b] = max(-INF, d[a] + cost);
        p[b] = a;
        x = b;
      }
    }
  }
  if (x == -1) {
    cout << "No negative cycle from vertex " << v <<
    ↪ '\n';
    return;
  }
  int y = x;
  for (int i = 0; i < n; i++) y = p[y];
  vector<int> path;
  for (int cur = y;; cur = p[cur]) {
    path.push_back(cur);
    if (cur == y && path.size() > 1) break;
  }
  reverse(path.begin(), path.end());
  cout << "Negative cycle: ";
  for (int u : path) cout << u << ' ';
  cout << '\n';
}
```

2.5 Bridge Finding Algorithm

```
const int MX = 1e5 + 10;
int n, m, timer = 0;
vector<int> adj[MX];
vector<int> tin(MX, -1), low(MX, -1);
vector<bool> vis(MX, false);
void is_bridge(int u, int v) {
  // do something with the edge
}
void dfs(int u, int p = -1) {
  vis[u] = true;
  tin[u] = low[u] = timer++;
  for (int v : adj[u]) {
    if (v == p) continue;
    if (vis[v]) {
      low[u] = min(low[u], tin[v]);
    } else {
      dfs(v, u);
      low[u] = min(low[u], low[v]);
      if (low[v] > tin[u]) {
        is_bridge(u, v);
      }
    }
  }
}
```

2.6 Centroid Decomposition

```
vector<int> lst[MX];
bool dead[MX];
int sz[MX];
void get_sz(int u, int p) {
  sz[u] = 1;
  for (int v : lst[u]) {
    if (v != p && !dead[v]) {
      get_sz(v, u);
      sz[u] += sz[v];
    }
  }
}
int find_cen(int u, int p, int tot) {
  for (int v : lst[u]) {
    if (v != p && !dead[v] && sz[v] > tot / 2) {
      return find_cen(v, u, tot);
    }
  }
  return u;
}
void calc(int cen) {
  // work on centroid here
}
void decomp(int u) {
  get_sz(u, -1);
  int tot = sz[u];
  int cen = find_cen(u, -1, tot);
  calc(cen);
  dead[cen] = true;
  for (int v : lst[cen]) {
    if (!dead[v]) {
      decomp(v);
    }
  }
}
```

2.7 Co-Ordinate Compression

```
vector<int> pos;
sort(pos.begin(), pos.end());
pos.erase(unique(pos.begin(), pos.end()), pos.end());
// then lower_bound on this pos array to find the
↪ compressed co-ordinate
```

2.8 CoinChange(MinCoins)

```
const int INF = 1e9;
int min_coins(int target, vector<int>& coins) {
  // DP Definition: dp[i] = minimum coins needed to
  ↪ make value i
  vector<int> dp(target + 1, INF);
  // Base Case: 0 coins are needed to make value 0
  dp[0] = 0;
  for (int i = 1; i <= target; i++) {
    for (int c : coins) {
      if (i - c >= 0) {
        // Transition: Try taking coin 'c', adding 1 to
        ↪ the count of (i-c)
        dp[i] = min(dp[i], dp[i - c] + 1);
      }
    }
  }
  return (dp[target] == INF) ? -1 : dp[target];
}
```

2.9 CoinChange(NumberOfWays)

```
ll count_ways(int target, vector<int>& coins) {
  // DP Definition: dp[i] = number of ways to make value i using given coins
  vector<ll> dp(target + 1, 0);
  // Base Case: There is 1 way to make value 0 (by choosing nothing)
  dp[0] = 1;
  for (int c : coins) {  // Loop coins *outside* to count combinations (unordered)
    for (int i = c; i <= target; i++) {
      // Transition: Add ways to make the remainder (i - c)
      dp[i] += dp[i - c];
    }
  }
  return dp[target];
}
```

2.10 CountSubsetWithSumK

```
int memo[105][10005];  // (N, Sum)
vector<int> nums;
int K;
int solve(int idx, int sum) {
  // DP: dp[idx][sum] = number of ways to complete the sum using suffix nums[idx...]
  // Base: End of array. Return 1 if sum matches K, else 0
  if (idx == nums.size()) {
    return sum == K;
  }
  if (memo[idx][sum] != -1) return memo[idx][sum];
  // Trans: Sum of ways (Include current element) + (Exclude current element)
  int take = (sum + nums[idx] <= K) ? solve(idx + 1, sum + nums[idx]) : 0;
  int skip = solve(idx + 1, sum);
  return memo[idx][sum] = take + skip;
}
```

2.11 Cycle Detection in DAG

```
const int MX = 1e5 + 10;
bool vis[MX], pathVis[MX];
vector<int> lst[MX];
bool dfs(int u) {
  vis[u] = true;
  pathVis[u] = true;
  for (auto v : lst[u]) {
    if (!vis[v]) {
      if (dfs(v))
        return true;
    } else if (pathVis[v]) {
      return true;
    }
  }
  pathVis[u] = false;
  return false;
}
void solve() {
  // take graph input
  for (int i = 0; i < n; ++i) {
    if (!vis[i])
      dfs(i);
  }
}
```

2.12 DSU on Trees

```
int n, color[MX], ans[MX];
vector<int> g[MX];
set<int> bucket[MX];
int merge(int a, int b) {
  if (bucket[a].size() < bucket[b].size()) swap(a, b);
  bucket[a].insert(bucket[b].begin(), bucket[b].end());
  bucket[b].clear();
  return a;
}
int dfs(int u, int p = -1) {
  int cur = u;
  for (int v : g[u])
    if (v != p)
      cur = merge(cur, dfs(v, u));
  ans[u] = (int)bucket[cur].size();
  return cur;
}
void solve() {
  cin >> n;
  for (int i = 0; i < n; ++i) {
    cin >> color[i];
    bucket[i].insert(color[i]);
  }
  // graph input
  dfs(0);
  // print output
}
```

2.13 DSU

```
const int MX = 1e5 + 10;
int par[MX], sz[MX];
void init() {
  for (int i = 0; i < MX; i++) {
    par[i] = i;
    sz[i] = 1;
  }
}
int findpar(int x) {
  if (par[x] == x) return x;
  return par[x] = findpar(par[x]);
}
void unite(int u, int v) {
  u = findpar(u);
  v = findpar(v);
  if (u != v) {
    if (sz[u] < sz[v]) {
      swap(u, v);
    }
    sz[u] += sz[v];
    par[v] = u;
  }
}
```

2.14 Digit DP

```
string S;
ll memo[20][2][180];
ll dp(int idx, bool tight, int current_sum) {
  // DP Definition:
  // dp(idx, tight, current_sum) returns the count of valid suffixes we can form
  // starting from index 'idx', given the 'tight' constraint and the current state (sum).
  // Base Case: We have placed digits for all positions
  if (idx == S.size()) {
    return 1;  // Found 1 valid number (or check: return current_sum == target ? 1 : 0)
  }
  ll &ans = memo[idx][tight][current_sum];
  if (ans != -1) {
    return ans;
  }
  ll ans = 0;
  // Determine the upper bound for the current digit
  int limit = tight ? (S[idx] - '0') : 9;
  for (int digit = 0; digit <= limit; digit++) {
    // Transition:
    // Move to next index (idx + 1).
    // New tight constraint: (tight && (digit == limit))
    // New state: Update current_sum (or other state variable)
    bool next_tight = tight && (digit == limit);
    // Example logic: filtering or constraints go here
    // if (digit == 4) continue; // Example: skip digit 4
    ans += dp(idx + 1, next_tight, current_sum + digit);
  }
  return memo[idx][tight][current_sum] = ans;
}
// Wrapper function to query for range [0, N]
ll query(ll N) {
  if (N < 0) return 0;
  if (N == 0) return 1;  // Handling 0 case if needed
  S = to_string(N);
  memset(memo, -1, sizeof(memo));
  // Start from index 0, tight constraint is initially TRUE, initial sum is 0
  return dp(0, true, 0);
}
// To get answer for range [L, R]: query(R) - query(L - 1)
```

2.15 Dijkastra

```
const int N = 1e5 + 5, INF = 1e18 + 7;
vector<pair<int, int>> g[N];
bool visited[N];
vector<int> dist(N, INF), parent(N);
bool dijkstra(int source) {
  priority_queue<pair<int, int>, vector<pair<int, int>>, greater<pair<int, int>>> pq;
  pq.push({0, source});
  dist[source] = 0;
  parent[source] = -1;
  while (pq.size()) {
    int x = pq.top().second;
    pq.pop();
    if (visited[x]) continue;
    visited[x] = 1;
    for (auto [child_x, child_wt] : g[x]) {
      if (dist[x] + child_wt < dist[child_x]) {
        parent[child_x] = x;
        dist[child_x] = child_wt + dist[x];
        pq.push({dist[child_x], child_x});
      }
    }
  }
  return (dist[n] == INF);
}
```

2.16 Divisor Sieve

```
const int mxN = 1e5 + 10;
vector<int> divisors[mxN];
void divisorSeive() {
  for (int i = 1; i < mxN; i++) {
    for (int j = i; j < mxN; j += i) {
      divisors[j].push_back(i);
    }
  }
}
```

2.17 EditDistance

```
int edit_distance(string s1, string s2) {
  int m = s1.size(), n = s2.size();
  // DP: dp[i][j] = min ops to convert s1[0...i-1] to
   ↪ s2[0...j-1]
  vector<vector<int>> dp(m + 1, vector<int>(n + 1));
  // Base: Converting empty string to s2 requires j
   ↪ inserts (and vice versa)
  for (int i = 0; i <= m; i++) dp[i][0] = i;
  for (int j = 0; j <= n; j++) dp[0][j] = j;
  for (int i = 1; i <= m; i++) {
    for (int j = 1; j <= n; j++) {
      if (s1[i - 1] == s2[j - 1]) {
        dp[i][j] = dp[i - 1][j - 1];
      } else {
        // Trans: 1 + min(Delete, Insert, Replace)
        dp[i][j] = 1 + min({dp[i - 1][j], dp[i][j -
         ↪ 1], dp[i - 1][j - 1]});
      }
    }
  }
  return dp[m][n];
}
```

2.18 Euler Tour

```
const int MX = 2e5 + 10;
int timer = -1;
// s = start pos, e = end pos
int val[MX], s[MX], e[MX], flat[MX];
vector<int> lst[MX];
void dfs(int u, int p) {
  s[u] = ++timer;
  flat[timer] = val[u];
  for (auto v : lst[u]) {
    if (v != p)
      dfs(v, u);
  }
  e[u] = timer;
}
```

2.19 Fast-Unordered-Map

```
mp.reserve(1 << 20);       // about 1M buckets
mp.max_load_factor(0.7);
```

2.20 Floyd Warshall

```
vector<vector<int>> d(n, vector<int> (n, INF));
// take graph input into d
for (int k = 0; k < n; ++k) {
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < n; ++j) {
            if (d[i][k] < INF && d[k][j] < INF)
                d[i][j] = min(d[i][j], d[i][k] +
                 ↪ d[k][j]);
        }
    }
}
```

2.21 Inverse_Mod

```
// to calculate a¹ mod M
modpow(a, M - 2)
```

2.22 Is Sorted

```
is_sorted(first, last, comp);
```

2.23 LCA using Binary Lifting

```
int n, l;
vector<vector<int>> adj;
int timer;
vector<int> tin, tout;
vector<vector<int>> up;
void dfs(int v, int p) {
  tin[v] = ++timer;
  up[v][0] = p;
  for (int i = 1; i <= l; ++i)
    up[v][i] = up[up[v][i - 1]][i - 1];
  for (int u : adj[v]) {
    if (u != p)
      dfs(u, v);
  }
  tout[v] = ++timer;
}
bool is_ancestor(int u, int v) {
  return tin[u] <= tin[v] && tout[u] >= tout[v];
}
int lca(int u, int v) {
  if (is_ancestor(u, v))
    return u;
  if (is_ancestor(v, u))
    return v;
  for (int i = l; i >= 0; --i) {
    if (!is_ancestor(up[u][i], v))
      u = up[u][i];
  }
  return up[u][0];
}
void preprocess(int root) {
  tin.resize(n);
  tout.resize(n);
  timer = 0;
  l = ceil(log2(n));
  up.assign(n, vector<int>(l + 1));
  dfs(root, root);
}
```

2.24 LCS for 3 Strings

```
string a, b, c;
ll dp[55][55][55];
ll lcs(ll i, ll j, ll k) {
  if (i == a.size() or j == b.size() or k == c.size())
   ↪ return 0;
  if (dp[i][j][k] != -1) return dp[i][j][k];
  if (a[i] == b[j] and a[i] == c[k]) return 1 + lcs(i
   ↪ + 1, j + 1, k + 1);
  ll ans = 0;
  ans = max(ans, lcs(i, j , k + 1));
  ans = max(ans, lcs(i, j + 1 , k));
  ans = max(ans, lcs(i + 1, j, k));
  return dp[i][j][k] = ans;
}
```

2.25 LIS

```
void LIS(const vector<int>& nums) {
  int n = nums.size();
  if (n == 0) return;
  // parent[i] stores the index of the predecessor of
   ↪ nums[i] in the LIS
  vector<int> parent(n, -1);
  // tails_id[k] stores the index (in nums) of the
      smallest tail of all increasing subsequences of
   ↪ length k+1
  vector<int> tails_id;
  // tails_val[k] stores the actual value of that tail
   ↪ (helper for binary search)
  vector<int> tails_val;
  // DP Definition (Implicit in greedy approach):
  // L[i] = Length of the longest increasing
   ↪ subsequence ending at index i.
  // We don't store L[i] explicitly, but compute it on
   ↪ the fly using the 'tails' arrays.
  // Base Case:
  // The first element starts a subsequence of length
   ↪ 1.
  for (int i = 0; i < n; i++) {
    int x = nums[i];
    // Find the first element in tails_val that is >= x
    auto it = lower_bound(tails_val.begin(),
     ↪ tails_val.end(), x);
    int idx = it - tails_val.begin();
    // Transition:
    // If x extends the longest existing subsequence,
     ↪ append it.
    // Otherwise, replace the existing tail to maintain
     ↪ the "smallest ending value" property
    // which allows future elements to extend the list
     ↪ easier.
    // We also link nums[i] to the element currently
     ↪ ending the subsequence of length (idx).
    if (it == tails_val.end()) {
      tails_val.push_back(x);
      tails_id.push_back(i);
    } else {
      *it = x;
      tails_id[idx] = i;
    }
    // If we are extending a sequence of length > 0,
     ↪ the parent is the end of the previous length
    if (idx > 0) {
      parent[i] = tails_id[idx - 1];
    }
  }
  // Reconstruction
  int curr = tails_id.back();  // Index of the last
   ↪ element of the LIS
  vector<int> lis_path;
  while (curr != -1) {
    lis_path.push_back(nums[curr]);
    curr = parent[curr];
  }
  reverse(lis_path.begin(), lis_path.end());
  // Output
  cout << "LIS Length: " << lis_path.size() << endl;
  for (int x : lis_path) cout << x << " ";
  cout << endl;
}
```

2.26 Lucas

```
int lucas(int n, int r) {
  int ans = 1;
  while (n > 0 or r > 0) {
    ans = ans * 1LL * nCr(n % M, r % M) % M;
    n /= M, r /= M;
  }
  return ans;
}
```

2.27 MST(Dense Graph)

```
int n;
const int MX = 2e3 + 5;
const int inf = 2e9;
vector<int> adj[MX];
int prim() {
  int total_weight = 0;
  vector<bool> selected(n, false);
  // min_w[i] stores the minimum weight to reach node i
```

```
  vector<int> min_w(n, inf);
  // par[i] stores the node that connects to i
  ↪ (previously min_e[i].to)
  vector<int> par(n, -1);
  min_w[0] = 0;
  for (int i = 0; i < n; ++i) {
    int u = -1;  // u is the Source node we are
    ↪ selecting
    // Find the unselected node with the smallest min_w
    for (int j = 0; j < n; ++j) {
      if (!selected[j] and (u == -1 || min_w[j] <
      ↪ min_w[u])) {
        u = j;
      }
    }
    if (min_w[u] == inf) {
      cout << "No MST!" << "\n";
      exit(0);
    }
    selected[u] = true;
    total_weight += min_w[u];
    // Print edge (u and the node that connected to it)
    if (par[u] != -1) {
      cout << u << " " << par[u] << "\n";
    }
    // Update neighbors
    // v is the Destination node (neighbor)
    for (int v = 0; v < n; ++v) {
      // Check if edge u -> v is shorter than v's
      ↪ current best weight
      if (adj[u][v] < min_w[v]) {
        min_w[v] = adj[u][v];
        par[v] = u;  // Store that we reached v from u
      }
    }
  }
  return total_weight;
}
```

2.28 MST(Sparse Graph)

```
// DSU first
void solve() {
  int n, m;
  cin >> n >> m;
  vector<array<int, 3>> edges;
  for (int i = 0; i < m; ++i) {
    int u, v, wt;
    cin >> u >> v >> wt;
    edges.push_back({wt, u, v});
  }
  sort(edges.begin(), edges.end());
  init(n);
  int cost = 0;
  for (auto &[wt, u, v] : edges) {
    if (findpar(u) == findpar(v)) continue;
    unite(u, v);
    cost += wt;
  }
  cout << cost << endl;
}
```

2.29 Manachar

```
// pal[1][i] = longest odd (half rounded down)
↪ palindrome around pos i and
// starts at i - pal[1][i] and ends at i + pal[1][i]
↪ pal[0][i] = half length of
// longest even palindrome around pos i, i + 1 and
↪ starts at i - par[0][i] + 1
// and ends at i + pal[0][i]
const int N = 5e5 + 10;
int pal[2][N];
void manacher(string& s) {
  int n = s.size(), idx = 2;
  while (idx--) {
    for (int l = -1, r = -1, i = 0; i < n - 1; ++i) {
      if (i > r)
        l = r = i;
      else {
        int k = min(r - i, pal[idx][l + r - i]);
        l = i - k, r = i + k;
      }
      while (l - idx >= 0 and r + 1 < n and s[l - idx]
      ↪ == s[r + 1]) l--, r++;
      pal[idx][i] = r - i;
      // [l - 1 + idx : r] palindrome
    }
  }
}
```

2.30 Matrix Exponentiation

```
const ll mod = 1e9;
vector<vector<ll>> matMul(vector<vector<ll>>& a,
↪ vector<vector<ll>>& b) {
  ll row1 = a.size(), col1 = a[0].size();
  ll row2 = b.size(), col2 = b[0].size();
  vector<vector<ll>> res(row1, vector<ll>(col2, 0));
  for (ll i = 0; i < row1; i++) {
    for (ll j = 0; j < col1; j++) {
      for (ll k = 0; k < row2; k++) {
        res[i][j] = (res[i][j] + (1LL * a[i][k] *
        ↪ b[k][j]) % mod) % mod;
      }
    }
  }
  return res;
}
vector<vector<ll>> matExpo(vector<vector<ll>>& Mat, ll
↪ exp) {
  ll row = Mat.size(), col = Mat[0].size();
  ll p = row;
  vector<vector<ll>> res(p, vector<ll>(p, 0));
  for (ll i = 0; i < p; i++) res[i][i] = 1;
  while (exp) {
    if (exp & 1) res = matMul(res, Mat);
    Mat = matMul(Mat, Mat);
    exp >>= 1;
  }
  return res;
}
// b = (A(i), A(i-1), A(i-2), A(i-3))
// M = Magic matrix, nth = nth term, known = known
↪ value
ll get_nth(ll nth, ll known, vector<ll>& b,
↪ vector<vector<ll>>& M) {
  if (nth <= known) return b[nth - 1] % mod;
  reverse(b.begin(), b.end());
  vector<vector<ll>> me = matExpo(M, nth - known);  //
  ↪ MAT^(nth-known)
  ll ans = 0;
  for (int i = 0; i < known; i++) {
    ans = (ans + (b[i] * me[i][0]) % mod) % mod;
  }
  return ans;
}
```

2.31 Matrix Rotation

```
//90* clock-wise
now = {{0, 1, 0}, { -1, 0, 0}, {0, 0, 1}};
//90* anti-clock
now = {{0, -1, 0}, {1, 0, 0}, {0, 0, 1}};
//mirror with x axis at point p
now = {{ -1, 0, 2 * p}, {0, 1, 0}, {0, 0, 1}};
//mirror with y axis at point p
now = {{1, 0, 0}, {0, -1, 2 * p}, {0, 0, 1}};
op[i + 1] = matMul(now, op[i]); // this
// op[i + 1] = matMul(op[i], now); //not this
```

2.32 Max Bipartite Matching [Hopcroft-Karp]

```
const int INF = 1e9;
void hopcroftCarp() {
  int n, m, e;
  cin >> n >> m >> e;
  vector<int> adj[n];
  for (int i = 0; i < e; ++i) {
    int u, v;
    cin >> u >> v;
    --u;
    --v;
    adj[u].push_back(v);
  }
  vector<int> ml(m, -1), mr(n, -1), dist(n);
  auto bfs = [&]() -> bool {
    queue<int> q;
    for (int u = 0; u < n; ++u) {
      if (mr[u] == -1) {
        dist[u] = 0;
        q.push(u);
      } else {
        dist[u] = INF;
      }
    }
    bool foundAugmenting = false;
    while (!q.empty()) {
      int u = q.front();
      q.pop();
      for (int v : adj[u]) {
        int pairedLeft = ml[v];
        if (pairedLeft == -1) {
          foundAugmenting = true;
        } else if (dist[pairedLeft] == INF) {
          dist[pairedLeft] = dist[u] + 1;
          q.push(pairedLeft);
        }
      }
    }
    return foundAugmenting;
  };
  function<bool(int)> dfs = [&](int u) -> bool {
    for (int v : adj[u]) {
      int pairedLeft = ml[v];
      if (pairedLeft == -1 or (dist[pairedLeft] ==
      ↪ dist[u] + 1 and dfs(pairedLeft))) {
        mr[u] = v;
        ml[v] = u;
        return true;
      }
    }
    dist[u] = INF;
    return false;
  };
  int matching = 0;
  while (bfs()) {
    for (int u = 0; u < n; ++u) {
      if (mr[u] == -1) {
        if (dfs(u)) matching++;
      }
    }
  }
  cout << matching << el;
  for (int u = 0; u < n; ++u) {
    if (mr[u] != -1) {
      cout << u << " " << mr[u] << el;
    }
  }
}
```

2.33 Max Bipartite Matching [Kuhn's]

```
// left set size, right set size, edge count
int n, k, m, visToken = 1;
vector<int> lst[MX];
int mr[MX], ml[MX], vis[MX];
bool try_kuhn(int u) {
  if (vis[u] == visToken)
    return false;
  vis[u] = visToken;
  for (auto v : lst[u]) {
    if (ml[v] == -1 or try_kuhn(ml[v])) {
      ml[v] = u;
      mr[u] = v;
      return true;
    }
  }
  return false;
}
void solve() {
  cin >> n >> k >> m;
  for (int i = 0; i < m; ++i) {
    int u, v;
    cin >> u >> v;
    --u, --v;
    lst[u].push_back(v);
  }
  fill(mr, mr + n, -1);
  fill(ml, ml + k, -1);
  int ans = 0;
  for (int u = 0; u < n; ++u) {
    for (auto v : lst[u]) {
      if (ml[v] == -1) {
        ml[v] = u;
        mr[u] = v;
        ans++;
        break;
      }
    }
  }
  for (int u = 0; u < n; ++u) {
    if (mr[u] != -1) continue;
    visToken++;
    if (try_kuhn(u))
      ans++;
  }
  cout << ans << el;
  for (int v = 0; v < k; ++v) {
    if (ml[v] != -1) {
      cout << ml[v] + 1 << " " << v + 1 << el;
    }
  }
}
```

2.34 Max Flow

```
struct Dinic {
  struct Edge {
    int to;
    ll capacity;
    int rev;  // index of reverse edge
  };
  vector<vector<Edge>> adj;
  vector<int> level;
  vector<int> ptr;
  int n;
  Dinic(int nodes) : n(nodes), adj(nodes),
  ↪  level(nodes), ptr(nodes) {}
  void add_edge(int from, int to, ll cap) {
    adj[from].push_back({to, cap,
    ↪  (int)adj[to].size()});
    adj[to].push_back({from, 0, (int)adj[from].size()
    ↪  - 1});
  }
  bool bfs(int s, int t) {
    fill(level.begin(), level.end(), -1);
    level[s] = 0;
    queue<int> q;
    q.push(s);
    while (!q.empty()) {
      int v = q.front();
      q.pop();
      for (auto& edge : adj[v]) {
        if (edge.capacity > 0 && level[edge.to] == -1)
        ↪  {
          level[edge.to] = level[v] + 1;
          q.push(edge.to);
        }
      }
    }
    return level[t] != -1;
  }
  ll dfs(int v, int t, ll pushed) {
    if (pushed == 0) return 0;
    if (v == t) return pushed;
    for (int& cid = ptr[v]; cid < adj[v].size();
    ↪  ++cid) {
      auto& edge = adj[v][cid];
      int tr = edge.to;
      if (level[v] + 1 != level[tr] || edge.capacity
      ↪  == 0) continue;
      ll tr_pushed = dfs(tr, t, min(pushed,
      ↪  edge.capacity));
      if (tr_pushed == 0) continue;
      edge.capacity -= tr_pushed;
      adj[tr][edge.rev].capacity += tr_pushed;
      return tr_pushed;
    }
    return 0;
  }
  ll max_flow(int s, int t) {
    ll flow = 0;
    while (bfs(s, t)) {
      fill(ptr.begin(), ptr.end(), 0);
      while (ll pushed = dfs(s, t, 1e18)) {
        flow += pushed;
      }
    }
    return flow;
  }
};
// Usage in int main():
int n, m;
cin >> n >> m;
Dinic dinic(n + 1); // Initialize with N+1 nodes (0 to
↪  N)
for (int i = 0; i < m; i++) {
    int u, v; ll cap;
    cin >> u >> v >> cap;
    // Add directed edge u -> v with capacity
    // For bidirectional, add edge v -> u as well
    dinic.add_edge(u, v, cap);
}
// Compute flow from node 1 (Source) to node n (Sink)
cout << dinic.max_flow(1, n) << endl;
```

2.35 Max Subarray Size Sum equal K

```
//write gpHashTable code before this part
void solution(){
int n, k; cin >> n >> k;
int total_sum = 0;
vector < int > pre(n + 7, 0);
for (int i = 1; i <= n; i++) {
  int temp; cin >> temp;
  total_sum += temp;
  if (i == 1) pre[i] = temp;
  else pre[i] = pre[i - 1] + temp;
}
if (total_sum < k) {
  cout << "-1" << endl; return;
}
if (total_sum == k) {
  cout << "0" << endl; return;
}
int maximum_subSize = 0;
gp_hash_table < int, int, customHash> table;
for (int i = 1; i <= n; i++) {
  if (pre[i] >= k) {
    int subSUM = pre[i] - k;
    if (subSUM == 0){
      maximum_subSize = max(maximum_subSize, i);
    }
    else if (table[subSUM]) {
      int left = table[subSUM];
      int right = i; int subSize = right - left;
      maximum_subSize = max(subSize, maximum_subSize);
    }
  } if (!table[pre[i]]) table[pre[i]] = i;
} cout << maximum_subSize << endl; }
```

2.36 Maximum Subarray Sum(Kadanes)

```
ll max_subarray_sum(const vector<int>& nums) {
  if (nums.empty()) return 0;
  ll current_max = nums[0];
  ll global_max = nums[0];
  for (size_t i = 1; i < nums.size(); i++) {
    current_max = max((ll)nums[i], current_max +
    ↪  nums[i]);
    global_max = max(global_max, current_max);
  }
  return global_max;
}
```

2.37 Merge Sort

```
// use array of elements, if multiple testcase make inv
↪  = 0 each time
// int inv = 0;
void merge(int vct[], int l, int m, int r) {
  int left = m - l + 1, right = r - m, lv[left],
  ↪  rv[right];
  for (int i = 0; i < left; i++) {
    lv[i] = vct[l + i];
  }
  for (int i = 0; i < right; i++) {
    rv[i] = vct[m + 1 + i];
  }
  int i = 0, j = 0, to = l;
  while (i < left && j < right) {
    if (lv[i] <= rv[j]) {
      vct[to] = lv[i];
      i++;
    } else {
      vct[to] = rv[j];
      j++;
      // inversion count
      // int pore = left-i; inv+=pore;
    }
    to++;
  }
  while (i < left) {
    vct[to] = lv[i];
    i++;
    to++;
  }
  while (j < right) {
    vct[to] = rv[j];
    j++;
    to++;
  }
```

```
}
void merge_sort(int vct[], int l, int r) {
  if (r <= l) return;
  int m = l + ((r - l) / 2);
  merge_sort(vct, l, m);
  merge_sort(vct, m + 1, r);
  merge(vct, l, m, r);
}
```

2.38 Mex of All Subarray

```
const int N = 1e5 + 9, inf = 1e9;
struct ST {
  int t[4 * N];
  ST() {}
  void build(int n, int b, int e) {
    t[n] = 0;
    if (b == e) {
      return;
    }
    int mid = (b + e) >> 1, l = n << 1, r = l | 1;
    build(l, b, mid);
    build(r, mid + 1, e);
    t[n] = min(t[l], t[r]);
  }
  void upd(int n, int b, int e, int i, int x) {
    if (b > i || e < i) return;
    if (b == e && b == i) {
      t[n] = x;
      return;
    }
    int mid = (b + e) >> 1, l = n << 1, r = l | 1;
    upd(l, b, mid, i, x);
    upd(r, mid + 1, e, i, x);
    t[n] = min(t[l], t[r]);
  }
  int get_min(int n, int b, int e, int i, int j) {
    if (b > j || e < i) return inf;
    if (b >= i && e <= j) return t[n];
    int mid = (b + e) >> 1, l = n << 1, r = l | 1;
    int L = get_min(l, b, mid, i, j);
    int R = get_min(r, mid + 1, e, i, j);
    return min(L, R);
  }
  int get_mex(int n, int b, int e, int i) {  // mex of
  ↪  [i... cur_id] if (b == e) return b;
    int mid = (b + e) >> 1, l = n << 1, r = l | 1;
    if (t[l] >= i) return get_mex(r, mid + 1, e, i);
    return get_mex(l, b, mid, i);
  }
} t;
int a[N], f[N];
int32_t main() {
  ios_base::sync_with_stdio(0);
  cin.tie(0);
  int n;
  cin >> n;
  for (int i = 1; i <= n; i++) {
    cin >> a[i];
    --a[i];
  }
  t.build(1, 0, n);
  set<array<int, 3>> seg;  // for cur_id = i, [x[0]...
  ↪  i], [x[0] + 1...i], ...[x[1]... i] has mex, ,
  ↪  x[2]
  for (int i = 1; i <= n; i++) {
    int x = a[i];
    int r = min(i - 1, t.get_min(1, 0, n, 0, x - 1));
    int l = t.get_min(1, 0, n, 0, x) + 1;
    if (l <= r) {
      auto it = seg.lower_bound({l, -1, -1});
      while (it != seg.end() && (*it)[1] <= r) {
        auto x = *it;
        it = seg.erase(it);
      }
      t.upd(1, 0, n, x, i);
      for (int j = r; j >= l;) {
        int m = t.get_mex(1, 0, n, j);
        int L = max(l, t.get_min(1, 0, n, 0, m) + 1);
        f[m] = 1;
        seg.insert({L, j, m});
        j = L - 1;
      }
      int m = !a[i];
      seg.insert({i, i, m});
      f[m] = 1;
    }
    int ans = 0;
    while (f[ans]) ++ans;
    cout << ans + 1 << '\n';
    return 0;
}
```

2.39 Mobius Function

```
//FULL MÖBIUS FUNCTION TEMPLATE
//Möbius Sieve (O(N log log N))
//Computes:
//mu[n] → Möbius value
//primes[] → list of primes
//isPrime[]
#include <bits/stdc++.h>
using namespace std;

const int MAXN = 1000000;
int mu[MAXN + 1];
bool isPrime[MAXN + 1];
vector<int> primes;

void mobius_sieve() {
    for (int i = 1; i <= MAXN; i++)
      mu[i] = 1, isPrime[i] = true;
    for (int i = 2; i <= MAXN; i++) {
        if (isPrime[i]) {
            primes.push_back(i);
            for (int j = i; j <= MAXN; j += i) {
                isPrime[j] = false;
                mu[j] *= -1;
            }
            long long sq = 1LL * i * i;
            if (sq <= MAXN) {
                for (int j = sq; j <= MAXN; j += sq)
                  mu[j] = 0;
            }
      }
    }
    mu[1] = 1;
}
//Count Numbers  n Coprime with x
long long count_coprime(long long n, int x) {
    long long ans = 0;
    for (int d = 1; d * d <= x; d++) {
        if (x % d == 0) {
            ans += 1LL * mu[d] * (n / d);
            if (d != x / d)
               ans += 1LL * mu[x / d] * (n / (x / d));
      }
    }
    return ans;
}
//Count Pairs (i, j) with gcd(i, j) = 1 (1  i,j  n)
long long count_coprime_pairs(int n) {
    long long ans = 0;
    for (int d = 1; d <= n; d++) {
      long long t = n / d;
      ans += 1LL * mu[d] * t * t;
    }
    return ans;
}

//Count Coprime Pairs in an Array (ICPC CLASSIC)
//Problem:
//Count (i,j) such that gcd(a[i], a[j]) = 1.
long long count_array_coprime_pairs(vector<int>& a) {
    int maxA = *max_element(a.begin(), a.end());
    vector<int> cnt(maxA + 1, 0);
    for (int x : a)
      cnt[x]++;
    vector<int> freq(maxA + 1, 0);
    for (int i = 1; i <= maxA; i++) {
      for (int j = i; j <= maxA; j += i)
      freq[i] += cnt[j];
    }
    long long ans = 0;
    for (int d = 1; d <= maxA; d++) {
      if (mu[d] != 0)
          ans += 1LL * mu[d] * freq[d] * (freq[d] - 1)
          ↪  / 2;
    }
    return ans;
}
//Mobius Inversion (Template)
vector<long long> mobius_inversion(vector<long long>&
↪  f, int n) {
    vector<long long> g(n + 1, 0);
    for (int i = 1; i <= n; i++) {
      for (int j = i; j <= n; j += i) {
        g[j] += mu[i] * f[j / i];
      }
    }
    return g;
}
//When to Use This Template
//Use Möbius when problem mentions:
//gcd = 1
//coprime pairs
//divisor sums
//inclusion-exclusion
//multiplicative functions
//Complexity Summary
//Task
//Time
//Sieve
//O(N log log N)
//Coprime count
//O(x)
//Pair counting
//O(N)
//Array coprime
//O(A log A)
//Contest Tips (IMPORTANT)
//Always precompute  once
//Combine with prefix sums
//Watch out for overflow
// values are only {-1, 0, +1}
```

2.40 Number of Pairs with GCD equal g

```
/*a[i] <= 1e6
for all 1<=g<=n, how many pairs exist such that g =
↪  gcd(a[i], a[j]);
complexity : nlogn
*/
ll n; cin >> n;
ll a[n + 1];
ll cnt[n + 1]; memset(cnt, 0, sizeof cnt);
for (ll i = 1; i <= n; i++) {cin >> a[i]; cnt[a[i]]++;}
ll gcd[n + 1]; memset(gcd, 0, sizeof gcd);
for (ll i = n; i >= 1; i--) {
  ll pair = 0, invalid_pair = 0;
  for (ll j = i; j <= n; j += i) {
    pair += cnt[j];
```

```
    invalid_pair += gcd[j];}
  pair = (pair * (pair - 1)) / 2;
  gcd[i] = pair - invalid_pair;
  // how many pairs exist whose gcd is i
}
```

2.41 Number of Subarray Sum is K

```
//write gpHashTable code before this part
void solution(){
int n, k; cin >> n >> k;
int total_sum = 0;
vector < int > pre(n + 7, 0);
for (int i = 1; i <= n; i++) {
  int temp; cin >> temp;
  total_sum += temp;
  if (i == 1) pre[i] = temp;
  else pre[i] = pre[i - 1] + temp; }
int cnt_subarry = 0;
gp_hash_table < int, int, customHash> table;
table[0] = 1;
for (int i = 1; i <= n; i++) {
  cnt_subarry += table[pre[i] - k];
  table[pre[i]]++;
} cout << cnt_subarry << endl; }
```

2.42 PBDS

```
#include "ext/pb_ds/assoc_container.hpp"
#include "ext/pb_ds/tree_policy.hpp"
using namespace __gnu_pbds;
template <class T>
using oset = tree<T, null_type, less<T>, rb_tree_tag,
tree_order_statistics_node_update>;
Note: Use less_equal for multiset like behaviour
Usage:
st.find_by_order(k) :: returns iterator of the k-th
 ↪ smallest element
st.order_of_key(x) :: returns index of x (number of
 ↪ elements less than x)
```

2.43 Phi(1 to N)

```
const int MX = 1e7 + 10;
int phi[MX];
void sieve() {
  for (int i = 0; i < MX; i++) phi[i] = i;
  for (int i = 2; i < MX; i++) {
    if (phi[i] == i) {
      for (int j = i; j < MX; j += i) {
        phi[j] -= phi[j] / i;
      }
    }
  }
}
```

2.44 Phi

```
int phi(int n) {
  int rt = sqrt(n);
  int result = n;
  for (int i = 2; i <= rt; i++) {
    if (n % i == 0) {
      while (n % i == 0) n /= i;
      result -= result / i;
    }
  }
  if (n > 1) result -= result / n;
  return result;
}
```

2.45 Print Binary

```
void printBin(ll n) {
  int msb = 63 - __builtin_clzll(n);
  for (int i = msb; i >= 0; i--) {
    cout << ((n >> i) & 1);
  }
  cout << "\n";
}
```

2.46 Range-xor-Trick

```
// XOR from 0 to x
int fx(int x) {
  if (x % 4 == 0) return x;
  if (x % 4 == 1) return 1;
  if (x % 4 == 2) return x + 1;
  return 0; // x % 4 == 3
}
int rangeXOR(int l, int r) {
  return fx(r) ^ fx(l - 1);
}
```

2.47 SCC

```
vector<bool> visited; // keeps track of which vertices
 ↪ are already visited
// runs depth first search starting at vertex v.
// each visited vertex is appended to the output vector
 ↪ when dfs leaves it.
void dfs(int v, vector<vector<int>> const& adj,
 ↪ vector<int> &output) {
    visited[v] = true;
    for (auto u : adj[v])
        if (!visited[u])
            dfs(u, adj, output);
    output.push_back(v);
}
// input: adj -- adjacency list of G
// output: components -- the strongy connected
 ↪ components in G
// output: adj_cond -- adjacency list of G^SCC (by root
 ↪ vertices)
void strongly_connected_components(vector<vector<int>>
 ↪ const& adj,
                                    vector<vector<int>>
                                     ↪ &components,
                                    vector<vector<int>>
                                     ↪ &adj_cond) {
    int n = adj.size();
    components.clear(), adj_cond.clear();
    vector<int> order; // will be a sorted list of G's
     ↪ vertices by exit time
    visited.assign(n, false);
    // first series of depth first searches
    for (int i = 0; i < n; i++)
        if (!visited[i])
            dfs(i, adj, order);
    // create adjacency list of G^T
    vector<vector<int>> adj_rev(n);
    for (int v = 0; v < n; v++)
        for (int u : adj[v])
            adj_rev[u].push_back(v);
    visited.assign(n, false);
    reverse(order.begin(), order.end());
    vector<int> roots(n, 0); // gives the root vertex
     ↪ of a vertex's SCC
    // second series of depth first searches
    for (auto v : order)
        if (!visited[v]) {
            std::vector<int> component;
            dfs(v, adj_rev, component);
            components.push_back(component);
            int root = *component.begin();
            for (auto u : component)
                roots[u] = root;
        }
    // add edges to condensation graph
    adj_cond.assign(n, {});
    for (int v = 0; v < n; v++)
        for (auto u : adj[v])
            if (roots[v] != roots[u])
                adj_cond[roots[v]].push_back(roots[u]);
}
```

2.48 SOD NOD

```
// SOD = ((P^(x+1)-1)/(P-1)) * ((Q^(y+1)-1)/(Q-1)) *
 ↪ ((R^(z+1)-1)/(R-1))
// NOD = P^x * Q^y * R^z  => here, P, Q, R are prime
 ↪ factors & x, y, z are
// powers NOD = (x + 1) (y + 1) (z + 1)
pair<int, int> SOD_NOD(int n) {
  int sod = 1, nod = 1;
  for (int i = 2; i * i <= n; ++i) {
    if (n % i == 0) {
      int pown = 1, pows = 0;
      while (n % i == 0) {
        pown *= i;  // p^e
        pows++;
        n /= i;
      }
      pown *= i;                        // p^e+1
      sod *= (pown - 1) / (i - 1);  //(p^e+1)-1 / p-1
      nod *= (pows + 1);
    }
  }
  if (n > 1) {
    sod *= (n + 1);
    nod *= 2;
  }
  return {sod, nod};
}
```

2.49 Segment Tree(BSUA)

```
// CSES - 1749
const int MX = 2e5 + 10;
int n;
int arr[MX], st[MX << 2];
void assign(int i, int x, int u = 1, int s = 0, int e
 ↪ = n - 1) {
  if (s == e) {
    st[u] = x;
    return;
  }
  int v = u << 1, w = v | 1, m = (s + e) >> 1;
  if (i <= m) assign(i, x, v, s, m);
  else assign(i, x, w, m + 1, e);
  st[u] = st[v] + st[w];
}
int kth(int k, int u = 1, int s = 0, int e = n - 1) {
  if (st[u] < k) return -1;
  if (s == e) {
    return s;
  }
  int v = u << 1, w = v | 1, m = (s + e) >> 1;
  if (st[v] >= k) return kth(k, v, s, m);
  else return kth(k - st[v], w, m + 1, e);
}
void solve() {
  cin >> n;
  for (int i = 0; i < n; ++i) {
    cin >> arr[i];
  }
  for (int i = 0; i < n; ++i) {
    assign(i, 1);
```

```
  }
  for (int i = 0; i < n; ++i) {
    int x;
    cin >> x;
    int ind = kth(x);
    assign(ind, 0);
    cout << arr[ind] << " ";
  }
}
```

2.50 Segment Tree(LzP)

```
class stree {
  vector<ll> st, lazy;
 public:
  stree(int n) {
    st.assign((n << 2) + 10, 0);
    lazy.assign((n << 2) + 10, 0);
  }
  void push(int u, int s, int e) {
    if (!lazy[u]) return;
    st[u] += (e - s + 1) * 1LL * lazy[u];
    if (s != e) {
      int v = u << 1, w = v | 1, m = (s + e) >> 1;
      lazy[v] += lazy[u];
      lazy[w] += lazy[u];
    }
    lazy[u] = 0;
  }
  void build(int u, int s, int e, int arr[]) {
    if (s == e) {
      st[u] = arr[s];
      return;
    }
    int v = u << 1, w = v | 1, m = (s + e) >> 1;
    build(v, s, m, arr);
    build(w, m + 1, e, arr);
    st[u] = st[v] + st[w];
  }
  void update(int l, int r, int x, int u, int s, int
  ↪ e) {
    push(u, s, e);
    if (e < l or r < s) return;
    int v = u << 1, w = v | 1, m = (s + e) >> 1;
    if (l <= s and e <= r) {
      st[u] += (e - s + 1) * 1LL * x;
      if (s != e) {
        lazy[v] += x;
        lazy[w] += x;
      }
      return;
    }
    update(l, r, x, v, s, m);
    update(l, r, x, w, m + 1, e);
    st[u] = st[v] + st[w];
  }
  ll query(int l, int r, int u, int s, int e) {
    push(u, s, e);
    if (e < l or r < s) return 0;
    if (l <= s and e <= r) return st[u];
    int v = u << 1, w = v | 1, m = (s + e) >> 1;
    return query(l, r, v, s, m) + query(l, r, w, m +
    ↪ 1, e);
  }
};
```

2.51 Segment Tree

```
struct stree {
  vector<ll> st;
  stree(int n) {
    st.assign((n << 2) + 10, 0);
  }
  void build(int u, int s, int e, int arr[]) {
    if (s == e) {
      st[u] = arr[s];
      return;
    }
    int v = u << 1, w = v | 1, m = (s + e) >> 1;
    build(v, s, m, arr);
    build(w, m + 1, e, arr);
    st[u] = st[v] + st[w];
  }
  ll query(int l, int r, int u, int s, int e) {
    if (e < l or r < s) return 0;
    if (l <= s and e <= r) return st[u];
    int v = u << 1, w = v | 1, m = (s + e) >> 1;
    return query(l, r, v, s, m) + query(l, r, w, m +
    ↪ 1, e);
  }
  void update(int i, int x, int u, int s, int e) {
    if (s == e) {
      st[u] = x;
      return;
    }
    int v = u << 1, w = v | 1, m = (s + e) >> 1;
    if (i <= m)
      update(i, x, v, s, m);
    else
      update(i, x, w, m + 1, e);
    st[u] = st[v] + st[w];
  }
};
```

2.52 Segmented Sieve

```
void segSeive(ll low, ll high) {
  vector < bool > area((high - low) + 1, true);
  for (ll i = 0; primes[i]*primes[i] <= high; i++) {
    ll start = ((low / primes[i]) * primes[i]);
    if (start < low) start += primes[i];
    for (ll j = start; j <= high; j += primes[i]) {
      if (j == primes[i]) continue;
      area[j - low] = false;
    }
  }
  for (ll i = 0; i < (high - low) + 1; i++) {
    if (area[i]) {
      if (i + low != 1 and i + low != 0) {
        cout << i + low << endl;
      }
    }
  }
}
```

2.53 Sparse-Table

```
const int MAXN = 2e5 + 10;
const int K = 26;
int n, arr[MX], spt[25][MX];
int log2Floor(int i) {
  return 31 - __builtin_clz(i);
}
void build() {
  int k = log2Floor(n);
  copy(arr, arr + n, spt[0]);
  for (int i = 1; i <= k; ++i) {
    for (int j = 0; j + (1 << i) <= n; j++) {
      spt[i][j] = min(spt[i - 1][j], spt[i - 1][j + (1
      ↪ << (i - 1))]);
    }
  }
}
int query(int l, int r) {
  int i = log2Floor(r - l + 1);
  return min(spt[i][l], spt[i][r - (1 << i) + 1]);
}
```

2.54 String Hashing 2

```
const int N = 1000010, MOD = 1e9 + 7;
const ll P[] = {97, 1000003};
ll bigMod(ll a, ll e) {
  if (e == -1) e = MOD - 2;
  ll ret = 1;
  while (e) {
    if (e & 1) ret = ret * a % MOD;
    a = a * a % MOD, e >>= 1;
  }
  return ret;
}
ll pwr[2][N], inv[2][N];
void initHash() {
  for (int it = 0; it < 2; ++it) {
    pwr[it][0] = inv[it][0] = 1;
    ll INV_P = bigMod(P[it], -1);
    for (int i = 1; i < N; ++i) {
      pwr[it][i] = pwr[it][i - 1] * P[it] % MOD;
      inv[it][i] = inv[it][i - 1] * INV_P % MOD;
    }
  }
}
struct RangeHash {
  vector<ll> h[2], rev[2];
  RangeHash(const string S, bool revFlag = 0) {
    for (int it = 0; it < 2; ++it) {
      h[it].resize(S.size() + 1, 0);
      for (int i = 0; i < S.size(); ++i) {
        h[it][i + 1] = (h[it][i] + pwr[it][i + 1] *
        ↪ (S[i] - 'a' + 1)) % MOD;
      }
      if (revFlag) {
        rev[it].resize(S.size() + 1, 0);
        for (int i = 0; i < S.size(); ++i) {
          rev[it][i + 1] =
              (rev[it][i] + inv[it][i + 1] * (S[i] -
              ↪ 'a' + 1)) % MOD;
        }
      }
    }
  }
  inline ll get(int l, int r) {
    ll one = (h[0][r + 1] - h[0][l]) * inv[0][l + 1] %
    ↪ MOD;
    ll two = (h[1][r + 1] - h[1][l]) * inv[1][l + 1] %
    ↪ MOD;
    if (one < 0) one += MOD;
    if (two < 0) two += MOD;
    return one << 31 | two;
  }
  inline ll getReverse(int l, int r) {
    ll one = (rev[0][r + 1] - rev[0][l]) * pwr[0][r +
    ↪ 1] % MOD;
    ll two = (rev[1][r + 1] - rev[1][l]) * pwr[1][r +
    ↪ 1] % MOD;
    if (one < 0) one += MOD;
    if (two < 0) two += MOD;
    return one << 31 | two;
  }
};
```

2.55 String Hashing

```
const int mod1 = 911382323, mod2 = 972663749, b1 =
↪ 137, b2 = 139;
const int mxN = 5000010;
int pow_b1[mxN], pow_b2[mxN], inv_b1[mxN], inv_b2[mxN];
int binExp(int base, int power, int mod) {
  int res = 1;
  while (power) {
    if (power & 1) res = (1LL * res * base) % mod;
    base = (1LL * base * base) % mod;
    power >>= 1;
  }
```

```
  return res;
}
void pre() {
  pow_b1[0] = pow_b2[0] = 1;
  for (int i = 1; i < mxN; i++) {
    pow_b1[i] = (1LL * pow_b1[i - 1] * b1) % mod1;
    pow_b2[i] = (1LL * pow_b2[i - 1] * b2) % mod2;
  }
  inv_b1[mxN - 1] = binExp(pow_b1[mxN - 1], mod1 - 2,
  ↪ mod1);
  inv_b2[mxN - 1] = binExp(pow_b2[mxN - 1], mod2 - 2,
  ↪ mod2);
  for (int i = mxN - 2; i >= 0; i--) {
    inv_b1[i] = (1LL * inv_b1[i + 1] * b1) % mod1;
    inv_b2[i] = (1LL * inv_b2[i + 1] * b2) % mod2;
  }
}
vector<pair<int, int>> getPref(string& s) {
  int qq = s.size();
  vector<pair<int, int>> hsh(qq);
  for (int i = 0; i < qq; i++) {
    if (i == 0) {
      hsh[i].first = (1LL * s[i] * pow_b1[i]) % mod1;
      hsh[i].second = (1LL * s[i] * pow_b2[i]) % mod2;
    } else {
      hsh[i].first =
          (hsh[i - 1].first + (1LL * s[i] * pow_b1[i])
          ↪ % mod1) % mod1;
      hsh[i].second =
          (hsh[i - 1].second + (1LL * s[i] *
          ↪ pow_b2[i]) % mod2) % mod2;
    }
  }
  return hsh;
}
pair<int, int> getHash(string& str) {
  int hsh1 = 0, hsh2 = 0, sz = str.size();
  for (int i = 0; i < sz; ++i) {
    hsh1 = (hsh1 + 1LL * str[i] * pow_b1[i] % mod1) %
    ↪ mod1;
  }
  for (int i = 0; i < sz; ++i) {
    hsh2 = (hsh2 + 1LL * str[i] * pow_b2[i] % mod2) %
    ↪ mod2;
  }
  return {hsh1, hsh2};
}
pair<int, int> getSub(int l, int r, vector<pair<int,
↪ int>>& v) {
  pair<int, int> q;
  if (l == 0) {
    q = {v[r].first, v[r].second};
  } else {
    int x = (1LL * ((v[r].first - v[l - 1].first +
    ↪ mod1) % mod1) * inv_b1[l]) %
            mod1;
    int y =
        (1LL * ((v[r].second - v[l - 1].second + mod2)
        ↪ % mod2) * inv_b2[l]) %
        mod2;
    q = {x, y};
  }
  return q;
}
```

2.56 Tonelli-Shanks

```
// Calculate X when we know Y and P for X^2  Y (mod P)
ll tonelli_shanks(ll Y, ll P) {
  if (Y == 0) return 0;
  if (P == 2) return Y % 2;
  // Euler's criterion: Check if Y is a quadratic
  ↪ residue
  if (modPow(Y, (P - 1) / 2, P) != 1) {
    return -1;
  }
  ll Q = P - 1;
  ll S = 0;
  while (Q % 2 == 0) {
    Q /= 2;
    S++;
  }
  ll z = 2;
  while (modPow(z, (P - 1) / 2, P) != P - 1) {
    z++;
  }
  ll M = S;
  ll c = modPow(z, Q, P);
  ll t = modPow(Y, Q, P);
  ll R = modPow(Y, (Q + 1) / 2, P);
  while (t != 0 && t != 1) {
    ll t2i = t;
    ll i = 0;
    for (i = 1; i < M; i++) {
        t2i = (t2i * t2i) % P;
        if (t2i == 1) break;
    }
    ll b = c;
    for (int j = 0; j < M - i - 1; j++) {
        b = (b * b) % P;
    }
    ll b2 = (b * b) % P;
    M = i;
    c = b2;
    t = (t * b2) % P;
    R = (R * b) % P;
  }
  return R;
}
```

2.57 Topological Sorting

```
const int MX = 1e5 + 10;
vector<int> lst[MX];
vector<int> topSort(int n) {
  int in[n]{};
  for (int u = 0; u < n; ++u) {
    for (int v : lst[u]) {
      in[v]++;
    }
  }
  queue<int> q;
  for (int u = 0; u < n; ++u) {
    if (in[u] == 0) {
      q.push(u);
    }
  }
  vector<int> order;
  while (!q.empty()) {
    int u = q.front();
    q.pop();
    order.push_back(u);
    for (int v : lst[u]) {
      in[v]--;
      if (in[v] == 0) {
        q.push(v);
      }
    }
  }
  // If the topological sort doesn't contain all nodes,
  ↪ there is a cycle.
  if (order.size() < n) {
    return {};  // Return empty to indicate cycle
  }
  return order;
}
```

2.58 Unique Elements in vector

```
sort(v.begin(), v.end());
v.erase(unique(v.begin(), v.end()), v.end());
```

2.59 Unique Prime Factorization using Sieve

```
const int MX = 2e5 + 10;
vector<int> pfac[MX];
void factorize() {
    for (int i = 2; i < MX; i++){
        if (!pfac[i].empty()) continue;
        for (int j = i; j < MX; j += i)
            pfac[j].push_back(i);
    }
}
```

2.60 Weighted Union Find

```
const int MX = 2e5 + 10;
int par[MX], sz[MX];
ll d[MX];
void init() {
  for (int i = 0; i < MX; ++i) {
    par[i] = i;
    sz[i] = 1;
    d[i] = 0;
  }
}
int findpar(int x) {
  if (par[x] == x) return x;
  int p = par[x];
  par[x] = findpar(p);
  d[x] += d[p];
  return par[x];
}
bool unite(int a, int b, ll w) {
  int ra = findpar(a);
  int rb = findpar(b);
  if (ra == rb) {
    return (d[b] - d[a] == w);
  }
  if (sz[ra] < sz[rb]) {
    swap(a, b);
    swap(ra, rb);
    w = -w;
  }
  par[rb] = ra;
  d[rb] = d[a] + w - d[b];
  sz[ra] += sz[rb];
  return true;
}
ll dist(int a, int b) {
  findpar(a), findpar(b);
  return d[b] - d[a];
}
```

2.61 erase-while-iteration

```
for (auto it = st.begin(); it != st.end(); ) {
  if (temp.find(*it) == temp.end()) {
    st.erase(it++);
  } else {
    ++it;
  }
}
```

2.62 int128

```
__int128 read() {
    __int128 x = 0, f = 1;
  char ch = getchar();
  while (ch < '0' || ch > '9') {
    if (ch == '-') f = -1;
    ch = getchar();
  }
  while (ch >= '0' && ch <= '9') {
```

```
    x = x * 10 + ch - '0';
    ch = getchar();
  }
  return x * f;
}
void print(__int128 x) {
  if (x < 0) {
    putchar('-');
    x = -x;
  }
  if (x > 9) print(x / 10);
  putchar(x % 10 + '0');
}
```

2.63 legendre

```
// returns power of prime p in n!
long long legendre(long long n, long long p) {
    long long ans = 0;
    while (n > 0) {
        n /= p;
        ans += n;
    }
    return ans;
}
```

2.64 nCr-and-nPr

```
const int MX = 1e6 + 10;
const int M = 1e9 + 7;
int fact[MX], inv_fact[MX];
// modpow here
void precalFact() {
  fact[0] = inv_fact[0] = 1;
  for (int i = 1; i < MX; i++) {
    fact[i] = (1LL * fact[i - 1] * i) % M;
  }
  inv_fact[MX - 1] = modpow(fact[MX - 1], M - 2);
  for (int i = MX - 2; i >= 1; i--) {
    inv_fact[i] = (1LL * inv_fact[i + 1] * (i + 1)) %
     ↪ M;
  }
}
int nCr(int n, int r) {
  if (r < 0 or r > n) return 0;
  return 1LL * fact[n] * inv_fact[r] % M * inv_fact[n
  ↪ - r] % M;
}
int nPr(int n, int r) {
  if (n < r) return 0;
  return 1LL * fact[n] * inv_fact[n - r] % M;
}
```

3 Geometry

3.1 Convex Hull

```
vector<pt> convexHull(vector<pt> p) {
  sort(p.begin(), p.end());
  vector<pt> hull;
  for (int rep = 0; rep < 2; ++rep) {
    const int S = hull.size();
    for (pt c : p) {
      while ((int)hull.size() - S >= 2) {
        pt a = hull.end()[-2];
        pt b = hull.end()[-1];
        if (a.cross(b, c) <= 0) {
          // b is on the left of c, it is valid
          break;
        }
        hull.pop_back();  // remove b
      }
      hull.push_back(c);
    }
    hull.pop_back();
    reverse(p.begin(), p.end());
  }
  return hull;
}
```

3.2 Line Line Intersection

```
bool lineLineIntersection(P p1, P p2, P p3, P p4) {
  if ((p2 - p1).cross((p4 - p3)) == 0) {
    // lines are parallel
    // basically the slopes of two lines are same,
    ↪ producing the cross product 0
    if (p1.cross(p2, p3) != 0) {
      // lines are not collinear
      return false;
    }
    // bounding box idea, 2 lines are collinear but not
    ↪ intersecting
    for (int rep = 0; rep < 2; ++rep) {
      if (max(p1.x, p2.x) < min(p3.x, p4.x) or
       ↪ max(p1.y, p2.y) < min(p3.y, p4.y)) {
        return false;
      }
      swap(p1, p3), swap(p2, p4);
    }
    // lines are collinear and intersecting
    return true;
  }
  // lines are not parallel
  for (int rep = 0; rep < 2; ++rep) {
    ll cp1 = p1.cross(p2, p3);
    ll cp2 = p1.cross(p2, p4);
    if ((cp1 < 0 and cp2 < 0) or (cp1 > 0 and cp2 >
     ↪ 0)) {
      // lines are not intersecting
      return false;
    }
    swap(p1, p3), swap(p2, p4);
  }
  // lines are intersecting
  return true;
}
```

3.3 Point in Polygon

```
bool segmentContains(pt a, pt b, pt c) {
  if (a.cross(b, c) != 0) {
    return false;
  }
  return (min(a.x, b.x) <= c.x and c.x <= max(a.x,
      b.x)) and (min(a.y, b.y) <= c.y and c.y <=
  ↪ max(a.y, b.y));
}
void solve() {
  int n;
  cin >> n;
  pt p[n];
  for (int i = 0; i < n; ++i) {
    cin >> p[i];
  }
  int q;
  cin >> q;
  while (q--) {
    pt temp;
    cin >> temp;
    int cnt = 0;
    bool flag = false;
    for (int i = 0; i < n; ++i) {
      int j = (i + 1) % n;
      if (segmentContains(p[i], p[j], temp)) {
        flag = true;
        break;
      }
      pt l, r;
      if (p[i].x <= p[j].x) {
        l = p[i];
        r = p[j];
      } else {
        l = p[j];
        r = p[i];
      }
      if (temp.cross(l, r) < 0) {
        if (l.x <= temp.x and temp.x < r.x) {
          cnt++;
        }
      }
    }
    if (flag) {
      cout << "BOUNDARY\n";
    } else if (cnt % 2 == 0) {
      cout << "OUTSIDE\n";
    } else {
      cout << "INSIDE\n";
    }
  }
}
```

3.4 Polygon Area

```
// the given points needs to be adjacent
void polygonArea() {
  int n;
  cin >> n;
  P p[n];
  for (int i = 0; i < n; ++i) {
    cin >> p[i];
  }
  ll area = 0;
  for (int i = 0; i < n; ++i) {
    // calculating wrt the origin
    area += p[i].cross(p[(i + 1) % n]);
  }
  cout << abs(area) << "\n";
}
```

3.5 Polygon Lattice Points

```
// using picks theorem
// interior = area - (boundary / 2) + 1
// 2 * interior = 2 * area - boundary + 2
void solve() {
  int n;
  cin >> n;
  pt p[n];
  for (int i = 0; i < n; ++i) {
    cin >> p[i];
  }
  ll boundary = 0, area = 0;
  for (int i = 0; i < n; ++i) {
    int j = (i + 1) % n;
    pt diff = p[j] - p[i];
    boundary += gcd(diff.x, diff.y);
    area += p[i].cross(p[j]);
  }
  area = abs(area);
  ll interior = (area - boundary + 2) / 2;
  cout << interior << " " << boundary << "\n";
}
```

3.6 Template

```
struct pt {
  ll x, y;
  friend istream& operator>>(istream& is, pt& p) {
    return is >> p.x >> p.y;
  }
  friend ostream& operator<<(ostream& os, const pt& p)
  ↪ {
    return os << p.x << " " << p.y;
```

```
  }
  pt operator-(const pt& other) const {
    return {x - other.x, y - other.y};
  }
  void operator-=(const pt& other) {
    x -= other.x, y -= other.y;
  }
  bool operator<(const pt& b) {
    return make_pair(x, y) < make_pair(b.x, b.y);
  }
  ll cross(const pt& other) const {
    return x * other.y - y * other.x;
  }
  ll cross(const pt& a, const pt& b) const {
    return (a - *this).cross(b - *this);
  }
};
```

4 Notes

4.1 Geometry

4.1.1 Triangles

Circumradius: $R = \dfrac{abc}{4A}$, Inradius: $r = \dfrac{A}{s}$

The area of a triangle using two sides and the included angle can be given as:

$$A = \frac{1}{2}ab\sin\angle C$$

Length of median (divides triangle into two equal-area triangles): $m_a = \frac{1}{2}\sqrt{2b^2+2c^2-a^2}$

Length of bisector (divides angles in two): $s_a = \sqrt{bc\left[1-\left(\frac{a}{b+c}\right)^2\right]}$

Law of tangents: $\dfrac{a+b}{a-b} = \dfrac{\tan\frac{\alpha+\beta}{2}}{\tan\frac{\alpha-\beta}{2}}$

Area given 3 sides of a triangle a,b,c :A=$\sqrt{s(s-a)(s-b)(s-c)}$ where $s = \dfrac{a+b+c}{2}$

4.1.2 Sphere

Volume of a sphere: $V = \frac{4}{3}\pi R^3$

Spherical Cap volume: $V(h) = \frac{\pi h^2(3R-h)}{3}$

4.1.3 Quadrilaterals

With side lengths a,b,c,d, diagonals e,f, diagonals angle θ, area A and magic flux $F = b^2+d^2-a^2-c^2$:

$$4A = 2ef\cdot\sin\theta = F\tan\theta = \sqrt{4e^2f^2-F^2}$$

For cyclic quadrilaterals the sum of opposite angles is 180°, $ef = ac+bd$, and $A = \sqrt{(p-a)(p-b)(p-c)(p-d)}$.

4.1.4 Spherical coordinates

$$x = r\sin\theta\cos\phi \qquad r = \sqrt{x^2+y^2+z^2}$$
$$y = r\sin\theta\sin\phi \qquad \theta = \operatorname{acos}(z/\sqrt{x^2+y^2+z^2})$$
$$z = r\cos\theta \qquad \phi = \operatorname{atan2}(y,x)$$

4.1.5 Pick's Theorem:

Given a lattice polygon with non-zero area, we define: S as the area of the polygon, I as the number of integer-coordinate points strictly inside the polygon, B as the number of integer-coordinate points on the boundary of the polygon. Then, Pick's Theorem states:

$$S = I + \frac{B}{2} - 1$$

The number of lattice points on segments (x1, y1) to (x2 , y2) is: gcd(abs(x2 - x1) , abs(y2 - y1)) + 1

4.1.6 Polygon

For a regular polygon with n sides and side length a, the circumradius R is given by:

$$R = \frac{a}{2\sin\left(\frac{\pi}{n}\right)}$$

4.1.7 Area of a Circular Segment

The area of a circular segment, which is the region enclosed by a chord and the corresponding arc, can be calculated using the formula:

$$A = \frac{R^2}{2}(\theta - \sin\theta)$$

where: R is the radius of the circle, θ is the central angle subtended by the chord, in radians.

4.2 Binomial Coefficent

- Factoring in: $\binom{n}{k} = \frac{n}{k}\binom{n-1}{k-1}$
- Sum over k: $\sum_{k=0}^{n}\binom{n}{k} = 2^n$
- Alternating sum: $\sum_{k=0}^{n}(-1)^k\binom{n}{k} = 0$
- Even and odd sum: $\sum_{k=0}^{n}\binom{n}{2k} = \sum_{k=0}^{n}\binom{n}{2k+1}2^{n-1}$
- The Hockey Stick Identity

  - (Left to right) Sum over n and k: $\sum_{k=0}^{m}\binom{n+k}{k} = \binom{n+m-1}{m}$

  - (Right to left) Sum over n: $\sum_{m=0}^{n}\binom{m}{k} = \binom{n+1}{k+1}$
- Sum of the squares: $\sum_{k=0}^{n}(\binom{n}{k})^2 = \binom{2n}{n}$
- Weighted sum: $\sum_{k=1}^{n}k\binom{n}{k} = n2^{n-1}$
- Connection with the fibonacci numbers: $\sum_{k=0}\binom{n-k}{k} = F_{n+1}$
- Vandermonde's Identity: $\sum_{i=0}^{k}\binom{m}{i}\binom{n}{k-i} = \binom{m+n}{k}$
- If $f(n,k) = C(n,0)+C(n,1)+\ldots+C(n,k)$, Then $f(n+1,k) = 2*f(n,k)-C(n,k)$ [For multiple $f(n,k)$ queries, use Mo's algo]

Lucas Theorem

$$\binom{m}{n} \equiv \prod_{i=0}^{k}\binom{m_i}{n_i}(\mod p)$$

- $\binom{m}{n}$ is divisible by p if and only if at least one of the base-p digits of n is greater than the corresponding base-p digit of m.
- The number of entries in the nth row of Pascal's triangle that are not divisible by $p = \prod_{i=0}^{k}(n_i+1)$
- All entries in the $(p^k-1)th$ row are not divisible by p.
- $\binom{n}{m} \equiv \lfloor\frac{n}{p}\rfloor(\mod p)$

4.3 Wilson's Theorem

Wilson's Theorem states that an integer $p > 1$ is a prime number if and only if:

$$(p-1)! \equiv -1 \pmod p$$

Equivalently, in positive modulo representation:

$$(p-1)! \equiv p-1 \pmod p$$

Competitive Programming Applications: While not practical for general primality testing due to the $O(p)$ factorial computation, Wilson's Theorem is extremely useful for calculating factorials close to p modulo p.

If you need to find $(p-k)!$ (mod p) for a small k, you can use Wilson's Theorem to compute it in $O(k\log p)$ time (using modular inverse) instead of $O(p)$ time.

Useful Corollaries: By expanding $(p-1)! = (p-1)(p-2)!$ and dividing out terms, we get:

- $(p-1)! \equiv -1 \pmod p$
- $(p-2)! \equiv 1 \pmod p$
- $(p-k)! \equiv \frac{(-1)^k}{(k-1)!} \pmod p$ (for $1 \le k \le p$)

4.4 Fibonacci Number

1. $k = A-B, F_AF_B = F_{k+1}F_A^2 + F_kF_AF_{A-1}$

2.$\sum_{i=0}^{n}F_i^2 = F_{n+1}F_n$ **3.**$\sum_{i=0}^{n}F_iF_{i+1} = F_{n+1}^2 - (-1)^n$

4.$\sum_{i=0}^{n}F_iF_{i+1} = F_{n+1}^2 - (-1)^n$ **5.**$\sum_{i=0}^{n}F_iF_{i-1} = \sum_{i=0}^{n-1}F_iF_{i+1}$

6.$\gcd(F_m,F_n) = F_{\gcd(m,n)}$ **7.**$\sum_{0\le k\le n}\left(\binom{n-k}{k}\right) = F_{n+1}$

8.$\gcd(F_n,F_{n+1}) = \gcd(F_n,F_{n+2}) = \gcd(F_{n+1},F_{n+2}) = 1$

4.5 Sums

$1^2+2^2+3^2+\cdots+n^2 = \frac{n(2n+1)(n+1)}{6}$

$1^3+2^3+3^3+\cdots+n^3 = \frac{n^2(n+1)^2}{4}$

$1^4+2^4+3^4+\cdots+n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$

$\sum_{i=1}^{n}i^m = \frac{1}{m+1}\left[(n+1)^{m+1}-1-\sum_{i=1}^{n}\left((i+1)^{m+1}-i^{m+1}-(m+1)i^m\right)\right]$

$\sum_{i=1}^{n-1}i^m = \frac{1}{m+1}\sum_{k=0}^{m}\binom{m+1}{k}B_kn^{m+1-k}$

$\sum_{k=0}^{n}kx^k = (x-(n+1)x^{n+1}+nx^{n+2})/(x-1)^2$

4.6 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \ldots, (-\infty < x < \infty)$$

$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \ldots, (-1 < x \le 1)$$

$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \ldots, (-1 \le x \le 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \ldots, (-\infty < x < \infty)$$

$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \ldots, (-\infty < x < \infty)$$

$$(x+a)^{-n} = \sum_{k=0}^{\infty} (-1)^k \binom{n+k-1}{k} x^k a^{-n-k}$$

Generating Function

$$1/(1-x) = 1 + x + x^2 + x^3 + \ldots$$

$$1/(1-ax) = 1 + ax + (ax)^2 + (ax)^3 + \ldots$$

$$1/(1-x)^2 = 1 + 2x + 3x^2 + 4x^3 + \ldots$$

$$1/(1-x)^3 = C(2,2) + C(3,2)x + C(4,2)x^2 + C(5,2)x^3 + \ldots$$

$$1/(1-ax)^(k+1) = 1 + C(1+k,k)(ax) + C(2+k,k)(ax)^2 + C(3+k,k)(ax)^3 + \ldots$$

$$x(x+1)(1-x)^-3 = 1 + x + 4x^2 + 9x^3 + 16x^4 + 25x^5 + \ldots$$

$$e^x = 1 + x + (x^2)/2! + (x^3)/3! + (x^4)/4! + \ldots$$

4.7 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2),\ b = k \cdot (2mn),\ c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

4.8 Number Theory

- HCN: 1e6(240), 1e9(1344), 1e12(6720), 1e14(17280), 1e15(26880), 1e16(41472)
- $gcd(a,b,c,d,\ldots) = gcd(a, b-a, c-b, d-c, \ldots)$
- $gcd(a+k, b+k, c+k, d+k, \ldots) = gcd(a+k, b-a, c-b, d-c, \ldots)$
- Primitive root exists iff $n = 1, 2, 4, p^k, 2 \times p^k$, where p is an odd prime.
- If primtive root exists, there are $\phi(\phi(n))$ primtive roots of n.
- The numbers from 1 to n have in total $O(n \log\log n)$ unique prime factors.
- $x \equiv r_1 \bmod m1$ and $x \equiv r_2 \bmod m2$ has a solution iff $\gcd(m_1, m_2) | (r_1 - r_2)$ Solution of $x^2 \equiv a(\mod p)$
- $ca \equiv cb \pmod m \iff a \equiv b \pmod{\frac{n}{\gcd(n,c)}}$
- $ax \equiv b \pmod m$ has a solution $\iff \gcd(a,m)|b$
- If $ax \equiv b \pmod m$ has a solution, then it has $gcd(a,m)$ solutions and they are separated by $\frac{m}{\gcd(a,m)}$
- $ax \equiv 1 \pmod m$ has a solution or a is invertible $\pmod m \iff \gcd(a,m) = 1$
- $x^2 \equiv 1 \pmod p$ then $x \equiv \pm 1 \pmod p$
- There are $\frac{p-1}{2}$ has no solution.
- There are $\frac{p-1}{2}$ has exaclty two solutions.
- When $p\%4 = 3$, $x \equiv \pm a^{\frac{p+1}{4}}$
- When $p\%8 = 5$, $x \equiv a^{\frac{p+3}{8}}$ or $x \equiv 2^{\frac{p-1}{4}} a^{\frac{p+3}{8}}$

4.8.1 Primes

$p = 962592769$ is such that $2^{21} \mid p-1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a, except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

4.8.2 Estimates

$\sum_{d|n} d = O(n \log\log n)$.

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

4.8.3 Perfect numbers

$n > 1$ is called perfect if it equals sum of its proper divisors and 1. Even n is perfect iff $n = 2^{p-1}(2^p - 1)$ and $2^p - 1$ is prime (Mersenne's). No odd perfect numbers are yet found.

4.8.4 Carmichael numbers

A positive composite n is a Carmichael number ($a^{n-1} \equiv 1 \pmod n$ for all a: $\gcd(a,n) = 1$), iff n is square-free, and for all prime divisors p of n, $p-1$ divides $n-1$.

4.8.5 Totient

- If p is a prime $(p^k) = p^k - p^{k-1}$
- If a b are relatively prime, $\phi(ab) = \phi(a)\phi(b)$
- $\phi(n) = n(1 - \frac{1}{p_1})(1 - \frac{1}{p_2})(1 - \frac{1}{p_3})\ldots(1 - \frac{1}{p_k})$
- Sum of coprime to $n = n * \frac{\phi(n)}{2}$
- If $n = 2^k, \phi(n) = 2^{k-1} = \frac{n}{2}$
- For a b, $\phi(ab) = \phi(a)\phi(b)\frac{d}{\phi(d)}$
- $\phi(ip) = p\phi(i)$ whenever p is a prime and it divides i
- The number of $a(1 <= a <= N)$ such that $gcd(a,N) = d$ is $\phi(\frac{n}{d})$
- If $n > 2$, $\phi(n)$ is always even
- Sum of gcd, $\sum_{i=1}^{n} gcd(i,n) = \sum_{d|n} d\phi(\frac{n}{d})$
- Sum of lcm, $\sum_{i=1} nlcm(i,n) = \frac{n}{2}(\sum_{d|n}(d\phi(d)) + 1)$
- $\phi(1) = 1$ and $\phi(2) = 1$ which two are only odd ϕ
- $\phi(3) = 2$ and $\phi(4) = 2$ and $\phi(6) = 2$ which three are only prime ϕ
- Find minimum n such that $\frac{\phi(n)}{n}$ is maximum- Multiple of small primes- $2*3*5*7*11*13*\ldots$

4.8.6 Mobius function

$\mu(1) = 1$. $\mu(n) = 0$, if n is not squarefree. $\mu(n) = (-1)^s$, if n is the product of s distinct primes. Let f, F be functions on positive integers. If for all $n \in N$, $F(n) = \sum_{d|n} f(d)$, then $f(n) = \sum_{d|n} \mu(d)F(\frac{n}{d})$, and vice versa. $\phi(n) = \sum_{d|n} \mu(d)\frac{n}{d}$. $\sum_{d|n} \mu(d) = 1$.

If f is multiplicative, then $\sum_{d|n} \mu(d)f(d) = \prod_{p|n}(1 - f(p))$, $\sum_{d|n} \mu(d)^2 f(d) = \prod_{p|n}(1 + f(p))$.

$$\sum_{i=1}^{n}\sum_{j=1}^{n}[gcd(i,j) = 1] = \sum_{k=1}^{n} \mu(k)\lfloor\frac{n}{k}\rfloor^2$$

$$\sum_{i=1}^{n}\sum_{j=1}^{n} gcd(i,j) = \sum_{k=1}^{n} k \sum_{l=1}^{\lfloor\frac{n}{k}\rfloor} \mu(l)\lfloor\frac{n}{kl}\rfloor^2$$

$$\sum_{i=1}^{n}\sum_{j=1}^{n} gcd(i,j) = \sum_{k=1}^{n} (\frac{\lfloor\frac{n}{k}\rfloor)(1 + \lfloor\frac{n}{k}\rfloor)}{2})^2 \sum_{d|k} \mu(d)kd$$

4.8.7 Legendre symbol

If p is an odd prime, $a \in \mathbb{Z}$, then $\left(\frac{a}{p}\right)$ equals 0, if $p|a$; 1 if a is a quadratic residue modulo p; and -1 otherwise. Euler's criterion: $\left(\frac{a}{p}\right) = a^{\left(\frac{p-1}{2}\right)} \pmod p$.

4.8.8 Jacobi symbol

If $n = p_1^{a_1} \cdots p_k^{a_k}$ is odd, then $\left(\frac{a}{n}\right) = \prod_{i=1}^{k} \left(\frac{a}{p_i}\right)^{k_i}$.

4.8.9 Primitive roots

If the order of g modulo m (min $n > 0$: $g^n \equiv 1 \pmod m$) is $\phi(m)$, then g is called a primitive root. If Z_m has a primitive root, then it has $\phi(\phi(m))$ distinct primitive roots. Z_m has a primitive root iff m is one of 2, 4, p^k, $2p^k$, where p is an odd prime. If Z_m has a primitive root g, then for all a coprime to m, there exists unique integer $i = \text{ind}_g(a)$ modulo $\phi(m)$, such that $g^i \equiv a \pmod m$. $\text{ind}_g(a)$ has logarithm-like properties: $\text{ind}(1) = 0$, $\text{ind}(ab) = \text{ind}(a) + \text{ind}(b)$.

If p is prime and a is not divisible by p, then congruence $x^n \equiv a \pmod p$ has $\gcd(n, p-1)$ solutions if $a^{(p-1)/\gcd(n,p-1)} \equiv 1 \pmod p$, and no solutions otherwise. (Proof sketch: let g be a primitive root, and $g^i \equiv a \pmod p$, $g^u \equiv x \pmod p$. $x^n \equiv a \pmod p$ iff $g^{nu} \equiv g^i \pmod p$ iff $nu \equiv i \pmod p$.)

4.8.10 Discrete logarithm problem

Find x from $a^x \equiv b \pmod m$. Can be solved in $O(\sqrt{m})$ time and space with a meet-in-the-middle trick. Let $n = \lceil\sqrt{m}\rceil$, and $x = ny - z$. Equation becomes $a^{ny} \equiv ba^z \pmod m$. Precompute all values that the RHS can take for $z = 0, 1, \ldots, n-1$, and brute force y on the LHS, each time checking whether there's a corresponding value for RHS.

4.8.11 Pythagorean triples

Integer solutions of $x^2 + y^2 = z^2$ All relatively prime triples are given by: $x = 2mn, y = m^2 - n^2, z = m^2 + n^2$ where $m > n, \gcd(m,n) = 1$ and $m \not\equiv n \pmod 2$. All other triples are multiples of these. Equation $x^2 + y^2 = 2z^2$ is equivalent to $(\frac{x+y}{2})^2 + (\frac{x-y}{2})^2 = z^2$.

4.8.12 Postage stamps/McNuggets problem

Let a, b be relatively-prime integers. There are exactly $\frac{1}{2}(a-1)(b-1)$ numbers *not* of form $ax + by$ $(x, y \ge 0)$, and the largest is $(a-1)(b-1) - 1 = ab - a - b$.

4.8.13 Fermat's two-squares theorem

Odd prime p can be represented as a sum of two squares iff $p \equiv 1 \pmod 4$. A product of two sums of two squares is a sum of two squares. Thus, n is a sum of two squares iff every prime of form $p = 4k + 3$ occurs an even number of times in n's factorization.

4.9 Permutations

4.9.1 Factorial

n	1	2	3	4	5	6	7	8	9	10
$n!$	1	2	6	24	120	720	5040	40320	362880	3628800

n	11	12	13	14	15	16	17
$n!$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14

n	20	25	30	40	50	100	150	171
$n!$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX

4.9.2 Cycles

Let $g_S(n)$ be the number of n-permutations whose cycle lengths all belong to the set S. Then

$$\sum_{n=0}^{\infty} g_S(n)\frac{x^n}{n!} = \exp\left(\sum_{n\in S}\frac{x^n}{n}\right)$$

4.9.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1)+D(n-2)) = nD(n-1)+(-1)^n = \left\lfloor \frac{n!}{e} \right\rceil$$

4.9.4 Burnside's lemma

Given a group G of symmetries and a set X, the number of elements of X *up to symmetry* equals

$$\frac{1}{|G|}\sum_{g\in G}|X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).
If $f(n)$ counts "configurations" (of some sort) of length n, we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n}\sum_{k=0}^{n-1} f(\gcd(n,k)) = \frac{1}{n}\sum_{k|n} f(k)\phi(n/k)$$

4.10 Partitions and subsets

4.10.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1,\ p(n) = \sum_{k\in\mathbb{Z}\setminus\{0\}} (-1)^{k+1} p(n-k(3k-1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

n	0	1	2	3	4	5	6	7	8	9	20	50	100
$p(n)$	1	1	2	3	5	7	11	15	22	30	627	~2e5	~2e8

4.10.2 Partition Number

- Time Complexity: $O(n\sqrt{n})$

```
for (int i = 1; i <= n; ++i) {
  pent[2 * i - 1] = i * (3 * i - 1) / 2;
  pent[2 * i] = i * (3 * i + 1) / 2;
}
p[0] = 1;
for (int i = 1; i <= n; ++i) {
  p[i] = 0;
  for (int j = 1, k = 0; pent[j] <= i; ++j) {
    if (k < 2) p[i] = add(p[i], p[i - pent[j]]);
    else p[i] = sub(p[i], p[i - pent[j]]); ++k, k &= 3;
  }
}
```

- The number of partitions of a positive integer n into exactly k parts equals the number of partitions of n whose largest part equals k

$$p_k(n) = p_k(n-k) + p_{k-1}(n-1)$$

4.10.3 2nd Kaplansky's Lemma

The number of ways of selecting k objects, no two consecutive,from n labelled objects arrayed in a circle is $\frac{n}{k}\binom{n-k-1}{k-1} = \frac{n}{n-k}\binom{n-k}{k}$

4.10.4 Distinct Objects into Distinct Bins

- n distinct objects into r distinct bins $= r^n$
- Among n distinct objects, exactly k of them into r distincts bins $= \binom{n}{k}r^k$
- n distinct objects into r distinct bins such that each bin contains at least one object $= \sum_{i=0}^{r}(-1)^i\binom{r}{i}(r-i)^n$

4.11 Coloring

The number of labeled undirected graphs with n vertices, $G_n = 2^{\binom{n}{2}}$

The number of labeled directed graphs with n vertices, $G_n = 2^{n(n}$
1)

The number of connected labeled undirected graphs with n vertices, $C_n = 2^{\binom{n}{2}} - \frac{1}{n}\sum_{k=1}^{n-1} k\binom{n}{k}2^{\binom{n-k}{2}}C_k = 2^{\binom{n}{2}} - \sum_{k=1}^{n-1}\binom{n-1}{k-1}2^{\binom{n-k}{2}}C_k$

The number of k-connected labeled undirected graphs with n vertices, $D[n][k] = \sum_{s=1}^{n}\binom{n-1}{s-1}C_s D[n-s][k-1]$

Cayley's formula: the number of trees on n labeled vertices = the number of spanning trees of a complete graph with n labeled vertices = n^{n-2}

Number of ways to color a graph using k color such that no two adjacent nodes have same color
Complete graph = $k(k-1)(k-2)...(k-n+1)$
Tree = $k(k-1)^{n-1}$
Cycle = $(k-1)^n + (-1)^n(k-1)$

Number of trees with n labeled nodes: n^{n-2}

4.12 General purpose numbers

4.12.1 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j:s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j:s s.t. $\pi(j) \geq j$, k j:s s.t. $\pi(j) > j$.

$$E(n,k) = (n-k)E(n-1,k-1) + (k+1)E(n-1,k)$$

$$E(n,0) = E(n,n-1) = 1$$

$$E(n,k) = \sum_{j=0}^{k}(-1)^j\binom{n+1}{j}(k+1-j)^n$$

4.12.2 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1,1,2,5,15,52,203,877,4140,21147,\ldots$. For p prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod p$$

4.12.3 Bernoulli numbers

$\sum_{j=0}^{m}\binom{m+1}{j}B_j = 0.$ $B_0 = 1, B_1 = -\frac{1}{2}$. $B_n = 0$, for all odd $n \neq 1$.

4.12.4 Catalan numbers

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1,\ C_{n+1} = \frac{2(2n+1)}{n+2}C_n,\ C_{n+1} = \sum C_i C_{n-i}$$

- $C_n = 1,1,2,5,14,42,132,429,1430,4862,16796,58786,\ldots$
- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n+1$ leaves (0 or 2 children).
- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.
- Find the count of balanced parentheses sequences consisting of $n+k$ pairs of parentheses where the first k symbols are open brackets.

$$C_n^{(k)} = \frac{k+1}{n+k+1}\binom{2n+k}{n}$$

- Recursive formula of Catalan Numbers:

$$C_n^{(k)} = \frac{(2n+k-1)\cdot(2n+k)}{n\cdot(n+k+1)}C_{n-1}^{(k)}$$

4.12.5 Lucas Number

Number of edge cover of a cycle graph C_n is L_n

$$L(n) = L(n-1) + L(n-2); L(0) = 2, L(1) = 1$$

4.13 Ballot Theorem

Suppose that in an election, candidate A receives a votes and candidate B receives b votes, where a kb for some positive integer k. Compute the number of ways the ballots can be ordered so that A maintains more than k times as many votes as B throughout the counting of the ballots.
The solution to the ballot problem is $\frac{a-kb}{a+b} \times C(a+b,a)$

4.14 Classical Problem

$F(n,k)$ = number of ways to color n objects using exactly k colors
Let $G(n,k)$ be the number of ways to color n objects using no more than k colors.
Then, $F(n,k) = G(n,k) - C(k,1)*G(n,k-1) + C(k,2)*G(n,k-2) - C(k,3)*G(n,k-3)...$

Determining G(n, k) :
Suppose, we are given a 1 * n grid. Any two adjacent cells can not have same color. Then, $G(n,k) = k*((k-1)^(n-1))$
If no such condition on adjacent cells. Then, $G(n,k) = k^n$

4.15 Matching Formula

4.15.1 Normal Graph

MM + MEC = n (exculding vertex), IS + VC = G, MIS + MVC = G

4.15.2 Bipartite Graph

MIS = n - MBM, MVC = MBM, MEC = n - MBM

4.16 Inequalities

4.16.1 Titu's Lemma

For positive reals $a_1, a_2, \ldots, a_n$ and $b_1, b_2, \ldots, b_n$,

$$\frac{{a_1}^2}{b_1} + \frac{{a_2}^2}{b_2} + \ldots + \frac{{a_n}^2}{b_n} \geq \frac{a_1 + a_2 + \ldots + {a_n}^2}{b_1 + b_2 + \ldots + b_n}$$

Equality holds if and only if $a_i = kb_i$ for a non-zero real constant k.

4.17 Games

4.17.1 Grundy numbers

For a two-player, normal-play (last to move wins) game on a graph (V,E): $G(x) = \text{mex}(\{G(y) : (x,y) \in E\})$, where $\text{mex}(S) = \min\{n \geq 0 : n \notin S\}$. x is losing iff $G(x) = 0$.

4.17.2 Sums of games

- *Player chooses a game and makes a move in it* Grundy number of a position is xor of grundy numbers of positions in summed games.
- *Player chooses a non-empty subset of games (possibly, all) and makes moves in all of them* A position is losing iff each game is in a losing position.
- *Player chooses a proper subset of games (not empty and not all), and makes moves in all chosen ones.* A position is losing iff grundy numbers of all games are equal.

- *Player must move in all games, and loses if can't move in some game* A position is losing if any of the games is in a losing position.

4.17.3 Misère Nim

A position with pile sizes $a_1, a_2, \ldots, a_n \geq 1$, not all equal to 1, is losing iff $a_1 \oplus a_2 \oplus \cdots \oplus a_n = 0$ (like in normal nim.) A position with n piles of size 1 is losing iff n is *odd*.

4.18 Tree Hashing

$f(u) = sz[u] * \sum_{i=0} f(v) * p^i$; $f(v)$ are sorted $f(child) = 1$

4.19 Permutation

To maximize the sum of adjacent differences of a permuation, it is necessary and sufficient to place the smallest half numbers in odd position and the greatest half numbers in even position. Or, vice versa.

4.20 String

- If the sum of length of some strings is N, there can be at most $\sqrt{N}$ distinct length.
- A Text can have at most $O(N \times \sqrt{N})$ distinct substrings that match with given patterns where the sum of the length of the given patterns is N.
- Period = n % (n - pi.back() == 0)? n - pi.back(): n
- The first $(period)$ cyclic rotations of a string are distinct. Further cyclic rotations repeat the previous strings.
- S is a palindrome if and only if it's period is a palindrome.
- If S and T are palindromes, then the periods of S T are same if and only if $S + T$ is a palindrome.

4.21 Bit

- (a xor b) and (a + b) has the same parity
- (a + b) = (a xor b) + 2 (a b)
- gcd(a, b) <= a - b <= xor(a, b)

4.22 Convolution

- Hamming Distance: Replace 0 with -1 - SQRT Decomposition: Find block size, B = $\sqrt{(8 * n)}$

4.23 Matrix Rotation

4.23.1 Anti-Clockwise Rotation

$$\begin{bmatrix} \cos\theta & \sin\theta \\ -\sin\theta & \cos\theta \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} = \begin{bmatrix} x' \\ y' \end{bmatrix}$$

4.23.2 Clockwise Rotation

$$\begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}$$

4.24 Common Formulas

4.24.1 Permutation

$$^nP_r = \frac{n!}{(n-r)!}$$

4.24.2 Combination

$$^nC_r = \frac{n!}{r!(n-r)!}$$

4.25 Logarithms

4.25.1 Change of Base Formula

$$\log_a x = \frac{\log_b x}{\log_b a}$$

4.26 Common Series Sums

4.26.1 Sum of first n positive integers

$$1 + 2 + 3 + \cdots + n = \frac{n(n+1)}{2}$$

4.26.2 Sum of first n odd positive integers

$$1 + 3 + 5 + \cdots + (2n-1) = n^2$$

4.26.3 Sum of first n even positive integers

$$2 + 4 + 6 + \cdots + 2n = n(n+1)$$

4.26.4 Sum of first n squares

$$1^2 + 2^2 + 3^2 + \cdots + n^2 = \frac{n(n+1)(2n+1)}{6}$$

4.26.5 Sum of first n cubes

$$1^3 + 2^3 + 3^3 + \cdots + n^3 = \left[\frac{n(n+1)}{2}\right]^2$$

4.27 Progressions

4.27.1 Arithmetic Progression

- **Sequence:** $a, a+d, a+2d, \ldots, a+(n-1)d$
- **Sum of first n terms:** $S_n = \frac{n}{2}[2a + (n-1)d]$

4.27.2 Geometric Progression

- **Sequence:** $a, ar, ar^2, \ldots, ar^{n-1}$
- **Sum (for $r > 1$):** $S_n = \frac{a(r^n - 1)}{r-1}$
- **Sum (for $r < 1$):** $S_n = \frac{a(1-r^n)}{1-r}$