

Assignment Lab 7
Anupam Godse 111408016
Nikhil Gawande 111408013

1. “The child “exec” call inherits the file descriptors of parent if Close_on_exec is not set”. Demonstrate with an example.


Program:-

```
l7q1.c
1 #include <unistd.h>
2 #include <sys/types.h>
3 #include <sys/stat.h>
4 #include <fcntl.h>
5 #include <stdio.h>
6 #include <stdlib.h>
7
8 int main() {
9     int fd;
10    pid_t pid;
11    fd = open("testfile", O_RDWR | O_CREAT, 0777);
12    if(fd == -1) {
13        printf("open failed\n");
14    }
15    write(fd, "This is a line added by parent.\n", 32);
16    //we will check default status of close on exec flag
17    int val = fcntl(fd, F_GETFD);
18    if(val) {
19        printf("close on exec is set :- %d\n", val);
20    }
21    else {
22        printf("close on exec is not set\n");
23    }
24    if((pid = fork()) < 0) {
25        printf("fork failed\n");
26    }
27    else if(pid == 0) {
28        char buff[20];
29        snprintf(buff, 20, "%d", fd);
30        printf("%s\n", buff);
31        if(execl("progforexec", "progforexec", buff, (char*)NULL) == -1) {
32            printf("exec failed\n");
33        }
34    }
35    return 0;
36 }
37
```

Program used for execution in child :-

```
1 #include <unistd.h>
2 #include <sys/types.h>
3 #include <sys/stat.h>
4 #include <fcntl.h>
5 #include <stdio.h>
6 #include <string.h>
7 #include <stdlib.h>
8
9 int main(int argc, char *argv[]) {
10     int fd = atoi(argv[1]);
11     if(write(fd, "This is line written by program executed in child using exec().\n",
12             strlen("This is line written by program executed in child using exec().\n")) < 0) {
13         printf("Demonstration failed\n");
14     }
15     else {
16         printf("The child \"exec\" call inherits the file descriptors of parent if Close_on_exec is not set : Demonstation successfull\n");
17         exit(0);
18     }
19     return 0;
20 }
```


Directory contents:-




Execution:-

```
anupam@anupam-Inspiron-7548:~/aup$ cc l7q1.c -o a
anupam@anupam-Inspiron-7548:~/aup$ ./a
close on exec is not set
3
The child "exec" call inherits the file descriptors of parent if Close_on_exec is not set : Demonstation successfull
anupam@anupam-Inspiron-7548:~/aup$
```

Before exec call:-



After exec call:-



```
testfile x
1 This is a line added by parent.
2 This is line written by program executed in child using exec().
```

Explanation:-

As close on exec flag is not set all the file descriptors open in parent are inherited by child exec() call. This can be demonstrated by,

- 1) Creating a new file in parent and writing some content to the file.
- 2) Passing the file descriptor as an argument to the program to be executed.
- 3) Using the same descriptor in the program that is executed using exec to see if it can be used to write/read from the same file.

As demonstrated in above program output, we can see that the file was created by parent program and the file descriptor was passed to the program to be executed. The program to be executed used the file descriptor to write some content in file which was successful. Hence we can conclude that, “The child “exec” call inherits the file descriptors of parent if Close_on_exec is not set”.

2. Write a program that takes a file name as an argument, opens the file, reads it and closes the file. The file should contain a string with the name of another application (e.g., 'ls' or 'ps' or any of your own applications) and the program forks a new process that executes the application named in the file.

Program:-

```
1 #include <unistd.h>
2 #include <sys/types.h>
3 #include <sys/stat.h>
4 #include <fcntl.h>
5 #include <stdio.h>
6 #include <stdlib.h>
7 #include <string.h>
8 #include <sys/wait.h>
9
10
11 int main(int argc, char *argv[]) {
12     int fd, count = 0;;
13     pid_t pid;
14     char *arg[128];
15     fd = open("testfile", O_RDONLY);
16     if(fd == -1) {
17         printf("Open failed\n");
18     }
19     char buff[128];
20     read(fd, buff, 128);
21     printf("%s\n", buff);
22     char *token = strtok(buff, " \n");
23     while(token) {
24         arg[count++] = token;
25         printf("%s\n", token);
26         token = strtok(NULL, " \n");
27     }
28     arg[count] = NULL;
29     if((pid = fork()) < 0) {
30         printf("fork failed\n");
31     }
32     else if(pid == 0) {
33         execvp(arg[0], arg);
34     }
35     else {
36         wait(NULL);
37     }
38     return 0;
39 }
```

Testfile :-

```
1 ls -l
```

Output :-

```
anupam@anupam-Inspiron-7548:~/aup/lab7/q2$ cc l7q2.c -o a
anupam@anupam-Inspiron-7548:~/aup/lab7/q2$ ./a
total 88
-rwxrwxr-x 1 anupam anupam 8968 Oct 7 18:00 a
-rw-rw-r-- 1 anupam anupam 695 Oct 7 18:00 l7q2.c
-rw-rw-r-- 1 anupam anupam 63928 Oct 7 17:49 l7q2.png
-rw-rw-r-- 1 anupam anupam 1234 Oct 7 17:50 l7q2_testfile.png
-rw-rw-r-- 1 anupam anupam 6 Oct 7 17:40 testfile
anupam@anupam-Inspiron-7548:~/aup/lab7/q2$
```

3. Implement `cat < hw.txt > hw-copy.txt`

Program:-

```
1 #include <stdio.h>
2 #include <unistd.h>
3 #include <sys/types.h>
4 #include <sys/wait.h>
5 #include <sys/stat.h>
6 #include <fcntl.h>
7 #include <errno.h>
8
9 int main(int argc, char *argv[]){
10     int fdr = open(argv[1], O_RDONLY);
11     int fdw = open(argv[2], O_WRONLY | O_CREAT | O_TRUNC, 0777);
12     pid_t pid;
13     if((pid = fork()) < 0) {
14         printf("fork failed\n");
15     }
16     else if(pid == 0){
17         dup2(fdr,0);
18         dup2(fdw,1);
19         execl("/bin/sh","sh", "-c", "cat", (char*)0);
20         _exit(127);
21     }
22     if(waitpid(pid, NULL, 0) != pid) {
23         return errno;
24     }
25     return 0;
26 }
```

Execution :-

```
anupam@anupam-Inspiron-7548:~/aup/lab7/q3/new$ ls
copyfrom  copyto  l7q3.c  l7q3.png
anupam@anupam-Inspiron-7548:~/aup/lab7/q3/new$ cat copyfrom
content of copyfrom.
anupam@anupam-Inspiron-7548:~/aup/lab7/q3/new$ cat copyto
anupam@anupam-Inspiron-7548:~/aup/lab7/q3/new$ cc l7q3.c -o a
anupam@anupam-Inspiron-7548:~/aup/lab7/q3/new$ ./a copyfrom copyto
anupam@anupam-Inspiron-7548:~/aup/lab7/q3/new$ cat copyfrom
content of copyfrom.
anupam@anupam-Inspiron-7548:~/aup/lab7/q3/new$ cat copyto
content of copyfrom.
anupam@anupam-Inspiron-7548:~/aup/lab7/q3/new$ █
```

4. Bob works for an auditing agency needs to be able to read all the files in the system. The system admin has to protect the integrity of the system and should not allow Bob to modify or delete any file. Write a special SETUID program for the admin so that he can give the executable permission of it to Bob. This program requires Bob to type a file name at the command line and then it will run /bin/cat to display the specified file. Can Bob compromise the integrity (by adding/modifying/deleting files) of this system? How?

Program:

```

1 #include <unistd.h>
2 #include <sys/types.h>
3 #include <sys/stat.h>
4 #include <fcntl.h>
5 #include <stdio.h>
6 #include <stdlib.h>
7 #include <string.h>
8 #include <sys/wait.h>
9 #include <errno.h>
10
11 int main(int argc, char *argv[]) {
12     if(setuid(1000) == -1) {
13         printf("setuid failed\n");
14     }
15     pid_t pid;
16
17     if((pid = fork()) < 0) {
18         printf("fork failed\n");
19     }
20     else if(pid == 0) {
21         execl("/bin/cat", "cat", argv[1], (char*)0);
22     }
23     else {
24         wait(NULL);
25     }
26     return 0;
27 }

```

testfile content:

```

anupam@anupam-Inspiron-7548:~/aup/lab7/q4$ cat tes
cat: tes: No such file or directory
anupam@anupam-Inspiron-7548:~/aup/lab7/q4$ cat testfile
success
anupam@anupam-Inspiron-7548:~/aup/lab7/q4$ █

```

Execution:

```
anupam@anupam-Inspiron-7548:~$ cd aup/lab7/q4/
anupam@anupam-Inspiron-7548:~/aup/lab7/q4$ l
a* l7q4.c* testfile*
anupam@anupam-Inspiron-7548:~/aup/lab7/q4$ ls -l
total 20
-rwsrwxr-x 1 anupam anupam 8808 Oct 12 15:56 a
-rwxrw-r-- 1 anupam anupam 458 Oct 12 15:55 l7q4.c
-rwx----- 1 anupam anupam 8 Oct 12 15:45 testfile
anupam@anupam-Inspiron-7548:~/aup/lab7/q4$ su - bob
Password:
bob@anupam-Inspiron-7548:~$ cd aup/
bob@anupam-Inspiron-7548:~/aup$ ls -l
total 12
-rwsrwxr-x 1 anupam anupam 8808 Oct 12 15:56 a
bob@anupam-Inspiron-7548:~/aup$ ./a /home/anupam/aup/lab7/q4/testfile
success
bob@anupam-Inspiron-7548:~/aup$ █
```

Explanation:

No. Bob cannot compromise the integrity of the system because he has no permissions for other files other than execute permission of executable given by admin. As he has no permissions of files given by admin (as we can see here, testfile has only rwx permissions for owner).