

Search

INTRODUCTION

Installation

Multi-goal API

ENVIRONMENTS

Fetch

Shadow Dexterous Hand

Manipulate Block

Manipulate Block Touch Sensors

Manipulate Egg

Manipulate Egg Touch Sensors

Manipulate Pen

Manipulate Pen Touch Sensors

Reach

Maze

Adroit Hand

Franka Kitchen

MaMuJoCo (Multi-Agent MuJoCo)

DEVELOPMENT

Github

Release Notes

Shadow Dexterous Hand

These environments are based on the [Shadow Dexterous Hand](#), 5 which is an anthropomorphic robotic hand with 24 degrees of freedom. Of those 24 joints, 20 can be controlled independently whereas the remaining ones are coupled joints.

- `HandReach-v1`: ShadowHand has to reach with its thumb and a selected finger until they meet at a desired goal position above the palm.
- `HandManipulateBlock-v1`: ShadowHand has to manipulate a block until it achieves a desired goal position and rotation.
- `HandManipulateEgg-v1`: ShadowHand has to manipulate an egg until it achieves a desired goal position and rotation.
- `HandManipulatePen-v1`: ShadowHand has to manipulate a pen until it achieves a desired goal position and rotation.

Shadow Dexterous Hand with Touch Sensors


Touch sensor observations are also available in all Hand environments, with exception of `HandReach`. These environments add to the palm of the hand and the phalanges of the fingers 92 touch sensors with different recorded data depending on the environment. These touch sensors are:

- Boolean Touch Sensor**: the observations of each touch sensor return a value of `0` if no contact is detected with an object, and `1` otherwise.
- Continuous Touch Sensor**: the value returned by each touch sensor is a continuous value that represents the external force made by an object over the sensor.


These environments are instantiated by adding the following strings to the Hand environment id's: `_BooleanTouchSensor` or `_ContinuousTouchSensor`. For example, to add boolean touch sensors to `HandManipulateEgg-v1`, make the environment in the following way:

```
import gymnasium as gym


env = gym.make('HandManipulateEgg_BooleanTouchSensors-v1')
```




Reach




Manipulate Block




Manipulate Block Touch Sensors




Manipulate Egg



Manipulate Egg Touch Sensors



Manipulate Pen



Manipulate Pen Touch Sensors

References

If using the `Shadow Hand` environments, please cite:

```
@misc{1802.09464,
  Author = {Matthias Plappert and Marcin Andrychowicz and Alex Ray and Bob McGrew and Bowen Berman},
  Title = {Multi-Goal Reinforcement Learning: Challenging Robotics Environments and Request for Generalization},
  Year = {2018},
  Eprint = {arXiv:1802.09464},
}
```

To cite the `Shadow Dexterous Hand with Touch Sensors` environments, please use:

```
@article{melnik2021using,
  title={Using tactile sensing to improve the sample efficiency and performance of deep deterministic policy gradient},
  author={Melnik, Andrew and Lach, Luca and Plappert, Matthias and Korthals, Timo and Haschke, Jan},
  journal={Frontiers in Robotics and AI},
  pages={57},
  year={2021},
  publisher={Frontiers}
}
```